GENERAL DESCRIPTION	250kVA
New Name after Emission Certification	**AL8NTIDG6**
No of Cylinders	6
Gross Rated Power	223 / 303.4
Overload Power (110 %)	245.3 / 333.7
RPM	1800
Typical Alternator Efficiency	93.9
Working Principle	4
BORE / STROKE	112 x 135
Displacement	7980
Compression Ratio	17.5 ± 0.5:1
Unit Dry Wt of Bare Engine Kg	800
Flywheel Housing	SAE 1
Direction of Rotation from Flywheel End	Counter Clockwise
Firing Order	1-4-2-6-3-5
Mechanical efficiency	94.0%
Thermal efficiency	40%
Reference Standard	ISO 8178
Governing system	Elecronic
Type of Governor	
Class Of Governor	A0
Engine Speed Droop (Governing)	0%
Heat Rejection to atmosphere	4-7%
Battery Volts	24V
Battery Capacity	105 AH
No. of Starter Motors provided	1
Rating Of starter motor	4.5
Battery Charging alternator Capacity amps	55
Intake Manifold Temperature (Max)	45 ± 2
Intake Manifold Pressure	195 ± 15
Intake Air Flow	12.6
Max. Allowable restriction in Air Element	14
Air Cleaner efficiency for dirt removal	99.95%
Engine Cooling System Coolant Capacity	46
Cooling Heat Rejection, kW	202
Max Cooling System Pressure	14.5
Coolant Outlet Temp (Max)	95
Coolant Inlet Temperature	80
Start to Open temp for Thermostat	82
Fully Open temp for Thermostat	95
Coolant topping-up / draining frequency	Every 2 Years or 1000 hrs.
Fan Diameter	30"
Fan Power	9
Manifold Type	Dry Type

Max. Wt of Exhaust System on Engine	30
Dia of Exhaust Outlet (inside)	100
No of Exhaust outlet	1
Max allowable System back pressure kPa	15
Heat rejection to exhaust	131.3
Heat rejection to coolant	203
Heat rejection to atmosphere	~4to7%
Stack Temp	500
SFC at 100%	151.8
SFC at 75%	150.6
SFC at 50%	153.3
No of Holes	3
Dia of Hole	13
PCD	140
Fuel Pump	Inline
Fuel Transfer pump type	Plunger
Filter Type	Spin On
No of filters	1
Refill volume with Lube Filter change	27.5
Lub Oil system capacity (with filters)	27.5
Lub Oil temperature (max)	120
Fuel Shut-Off solenoid type & Travel	Electrical
Low Lub Oil Pressure Shut-Off	7.5
High Water Tempo Shut-Off	105 ± 3
Crank termination signal	Oil Pressure
Lub Oil Pressure Guage	Digital
Water Temp Guage	Digital
Hourmeter cum r.p.m meter	Digital
Ammeter	Digital
Flywheel Housing Coupling Size	SAE 1
Flywheel Coupling Size	SAE 14
Flywheel Diameter	477
Flywheel Width	88
Flywheel No of teeth	159
Flywheel Weight	39
Noise on Full Load at 1 m	102
Engine Warm-Up time before putting load	60
Engine Cooling time before Engine Shut-Down	120
Sudden 100% decrease in Load. =<10%	NA
Sudden 100% increase in Load. =<10%	NA
Recovery for 100% decrease inload =<8 sec	NA
Recovery for 100% increase inload =<8 sec	NA

250 KVA Ashok Leyland – Generator Specification.

Bore x Stroke (mm)	112 x 135 mm
Rating	250 kVA
Genset Brand	Ashok Leyland
Model Number	SG250AL
Fuel Consumption (at 100% Load)	50.3 L/Hours
Frequency	50 / 60 Hz
Battery Capacity	105 Ah
Dimension	4730 x 1610 x 2420 mm (L x W x H)
Fuel Tank Capacity	765 Liter
Electric Power	200 kWe
DG Weight Approx.	4500 kg
System DC Voltage	24 V
Engine Model	AL8NTIDG6/AL8NTIDG3
Engine Rated HP/kW	299/223
Aspiration	TA
No. of Cylinders	6
Lube Oil Capacity Approx.	25 Liter
Coolant Capacity Approx.	49 Liter
Oil Change Period	500 Hrs./6 months
Displacement	7.98 Liter
Lube Oil Specification	SAE15W 40 CI4
IP Rating	IP33

Key Features:

- Reliable, Robust & Rugged engines designed to deliver continuously in arduous environment
- Better Block Loading Capability
- Compact engine: Engineered for Optimized Power Solutions
- Low Oil & Fuel consumption
- Continuous duty Power rating
- Minimal vibrations and lower noise levels

Specifications:

Compression ratio: 17.5 ± 0.5 : 1

- Governing Class: A0
- Governor Used: Electronic
- Engine Configuration: In line
- **Alternator:** Brushless, Single Bearing, Class H Insulated, Voltage Regulation + 0.5%, 0.8PF Lag