400KVA DIESEL GENERATOR SET

1.General Characteristics

MODEL	SWB400GES
Voltage/Frequency/Phase	127/220, 220/380, 277/480, 50/ 60HZ, 3phase
Standby Power	440KVA /352KW
Prime Power	400KVA/320KW
Silent Type Size/Weight	4200*1550*2180 / 4200kgs
Fuel tank capacity (L)	**608L（SR-PO-2024-14428）** **1000L（SR-PO-2025-16531）**
Coolant capacity radiator and pipes **(L)**	**22L**

1. 1Power

Prime power (PRP): Prime power is available for an unlimited number of annual hours in available load application , in according with GB/T2820-97(EQVLso8528); A 10% overload capability is available for a period of 1 hour within a 12-hour period of operation.

Standby power Rating (ESP) ; The standby power rating is application for supplying emergency power for the duration of a utility power interruption. No overload, utility parallel or negotiated outage operation capability is available at this rating.

Engine specification:

Manufacturer /Model:	Baudouin 6M21G390/6
Country of origin	China
Air intake System:	Turbocharged intercooled, intercooled
Cooling system:	water cooling
Cylinder Arrangement:	6L
Displacement :	12.54L
Bore and Stroke:	127 x 165 (MM)
Compression Ratio:	17:1
Rated RPM:	1800rpm
Prime power at rated RPM:	407KW
Max standby Power at Rated RPM:	448KW
Oil capacity:	30-34L
Governor Type:	electric
Frequency Regulation ,Steady State :	<±0.5%
Fuel consumption@100% load:	200g/kw.h
Including :	Diesel generator ventilation system Diesel generator lubrication system Diesel generator start system Diesel generator charging system Diesel generator cooling system

1.2 Alternator specification

Compliance with GB755, BS5000, VDE0530, NEMAMG1-22, IED34-1, CSA C22-100 and AS1359 standards.

Manufacture /Model:	Stamford S4L1D-F41
Number of Phase:	three

Connecting Type:	3 Phase and 4 wire Rotating Field
Number of Bearing:	Single
Power Factor:	0.8
Protection Grade:	IP23
Altitude:	≤1000m
Exciter Type:	Brush less, self-exciting
Insulation Class, Temperature Rise:	H/H
THF:	<2%
Voltage Regulation, Steady State:	≤1.5%
Frequency:	60HZ
Alternator Capacity:	416.3KVA

Optional: Stamford , Mecc alter ,Marathon ect.

1.3Controller specification

Controller Brand : DEEPSEA	**Model: DSE8610**
The control module gives digital readouts of: ◆Generator voltage ◆Output frequency ◆Engine speed ◆Battery voltage ◆Engine running hours ◆The control module has indicators for failure information: ◆Over speed/Low speed, ◆Emergency stop ◆Low oil pressure ◆High water temperature ◆Failure to start ◆Battery charger failure	 ◆Automatic shutdown occurs under: ◆Low engine oil pressure ◆High engine water temperature ◆Over speed/Low speed ◆Failure to start after three attempts.

1.4 Standard Configuration details

STANDARD ACCESSORIES	Open type	Silent type
Engine	√	√
Stamford alternator 311winding ,12leads ,PMG	√	√
Canopy with rock wool and mesh plate	N/A	√
Base fuel tank 1000L（SR-PO-2025-16531）	√	√
Intelligent LED display control panel	√	√
Schneider circuit breaker,3P， 1250A	√	√
Free maintenance battery and cable	√	√
Radiator 55°C max, fans are driven by belt ,with safety guard	√	√
Electronic and mechanical fuel level valve,three-way fuel value,304 door lock and hinges ,door stay	√	√
High-efficient silencer	√	√
Exhaust elbow	√	√
Steel base-frame shock absorbers	√	√
Operation& Maintenance manual,test report	√	√