LTS
Light Towers

Turns the night into day

The Light Tower LTS is suitable for a wide range of applications - from construction site lighting and the lighting of temporary parking spaces to music events. Four variants with different lamp types and drives are available. Due to the integrated generator, all models may be operated independent of power supply.

- Up to 8.5m mast height extendable with a hand winch.
- Stands steady also on uneven ground and with up to 80 km/h wind speed thanks to five individually adjustable supports.
- Up to 10 units can be transported on a truck loading area.

Technical specifications

LTS Light Towers

	LTS4K (60 Hz)
Operating data	
L x W x H mm	2,560 x 1,390 x 2,560
Lamp type	LED - 4 X 300 W
Mast height m	8.5
Power kW	4
Frequency Hz	60
Voltage V	230
Engine / Motor	
Generator model	Brushless
Generator insulation (class)	H
Voltage control (+/-) %	5
Engine / Motor manufacturer	Kubota (Z482)
Engine / Motor type	Liquid-cooled, 2-cylinder
Fuel type	Diesel
Displacement cm^3	479
Rated performance kW	4.4
at rpm rpm	1,800
Rated performance	DIN 6271
Tank capacity (oil) l	2.5
Tank capacity (fuel) l	80
Fuel consumption (100% prime load) l/h	0.9

Please note
that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions.
Subject to alterations and errors excepted. Applicable also to illustrations.
Copyright © 2018 Wacker Neuson SE.