



TEWATT

DIESEL AIR COMPRESSOR

EU STAGE III/TIER 3 SERIES

**ESSENTIAL
POWER ENTIRE
SAFEGUARD**

Technical Specifications and Compliance Certifications

Model		TWT406D-10T
Stage		Single
Free Air Delivery	CFM	406
	m³/min	11.5
Working Pressure (psig/bar)		145/10
Screw Oil	l	50
	us gal	13.2
Brand		CUMMINS
Model		4BTA3.9-C125
Power(HP/KW)		125/93
Rated/Idle Speed(rpm)		2200/1500
Emission		EU Stage II/Tier 2
Battery Voltage(V)		24
Fuel Tank (L)	l	140
	us gal	37.0
Connector×Qty		3/4"×1, 2"×1
Wheel×Qty		185R14LT×2
Weight(kg)		1800
Dimension(mm) Skid-mounted		2200×1400×1900
Dimension(mm)Tow		3250×1950×2200
Noise (dB(A))		72±5
Working Temp.(°C)		—10°C~+55°C(Special Working Conditions Can be Customized)



Air System Solutions

PTO



Electric air compressor



Electric oil-free air compressor



Diesel oil-free air compressor



Don't include the samples for the products described explicit or implicit guarantees. Any guarantees or other sales standards would follow Hubei Teweite Power Technology Co., Ltd. Product improvement is our persistent pursuit, and Teweite reserves the modified rights about the design and technical specifications.
Print version: 202209



CHINESE FACTORY
HUBEI TEWEITE POWER TECHNOLOGY CO., LTD.
No.20 Fuguang Rd., XiaoNan Economic Development
Zone, Xiaogan-432100, Hubei, China
TEL: +86-712-2517118
FAX: +86-712-2595359
Web: www.tewatt.com
Email: 036@tewatt.com.cn