Product Description

Diesel air compressor Atlas Copco V1200

Max. pressure:15-25bar

Capacity:34-36.8m³/min

The Atlas Copco V 1200 diesel compressor is designed to perform both drilling operations and pipeline pressure testing, testing and cleaning operations. This model uses a patented technology that allows you to select the operating pressure, which allows you to use one compressor for various jobs.

Industries and applications

Drilling

Geothermal drilling and construction.

Mining

Blast hole drilling and exploration.

Oil & Gas

Pipeline, well services and aerated drilling.

Specification

Technical Specifications

(Custom configurations available upon request.)

TECHNICAL DATA

		XATS 1200	XAVS 1000	V900	V1200	X1300	Y1300
Max. pressure	bar	5-10	5-14	16-25	15-25	15-30	15-35
	psi	72-150	72-203	232-363	217-363	217-435	217-508
Flow	m³/min	34,6-31,5	28,9-25,6	25,4-22,8	36,8-34	38,9-35,4	37,1-33
	l/s	578-520	482-425	423-380	613-566	648-590	618-550
	cfm	1225-1102	1021-901	896-805	1299-1200	1373-1250	1309-1165
Regulation system		PACE	PACE	PACE	DrillAirXpert	DrillAirXpert	DrillAirXpert
Extended Pressure Range XPR (optional)	bar	NA	NA	NA	NA	13-19	13-19
Flow in Dynamic Flow Boost mode	m³/min (l/s)	N/A	N/A	N/A	36.8 (613) at 15 bar	38.9 (648) at 15 bar	37.1 (618) at 15 bar
Engine model		DCEC QSL8.9-C360-30	DCEC QSL8.9-C360-30	DCEC QSL8.9-C360-30	DCEC QSZ13-C475-30	DCEC QSZ13-C550-30	DCEC QSZ13-C550-30
Engine band answer		Cummins Stage III	Cummins Stage III	Cummins Stage III	Cummins Stage III	Cummins Stage III	Cummins Stage III
Engine power	kW	264	264	264	364	410	410
Engine speed range	rpm	1200-1900 (1700 nom)	1200-1900 (1700 nom)	1200-1900 (1700 nom)	1300-1700 (1600 nom)	1300-1850 (1700 nom)	1300-1900 (1700 nom)
Dimensions wagon (lxwxh)	mm	4252x2100x2500	4252x2100x2500	4252x2100x2500	5000x2100x2405	5000x2250x2510	5000x2250x2510
Dimensions support (lxwxh)	mm	3830x2100x2250	3830x2100x2250	3830x2100x2250	4100x2100x2180	4210x2250x2270	4210x2250x2270
Dimensions skid	mm	3650x2100x2360	3650x2100x2360	3650x2100x2360	4100x2100x2180	4210x2250x2440	4210x2250x2440
Dry weight wagon	kg	4079	4079	4079	5765	6190	6190
Wet weight wagon	kg	4583	4583	4583	6500	7150	7150
Dry weight support	kg	3850	3850	3850	5118	5540	5540
Wet weight support	kg	4355	4355	4355	5850	6500	6500
Fuel tank capacity	Lit	420	420	420	614	876	876