62.5 KVA Ashok Leyland – Generator Specifications.

Power	62.5 kVA
Bore x Stroke (mm)	104 x 113 mm
Engine Model	AL4CTIDG5
Frequency	50/60 Hz
Battery Capacity	90 Ah
Dimension	3000 x 1200 x 1800 mm (L x W x H)
Fuel Tank Capacity	650 Liter
Electric Power	50 kWe
Rated Current @380V	95 A
Genset Model	LP62.5D
DG Weight Approx.	1750 Kg
System DC Voltage	12 V
Engine Rated	59 kW
Aspiration	TA
No. of Cylinders	4
Displacement	3.84 Liter
Fuel Consumption @ 100% load	13.3 L/Hours
Lube Oil Capacity Approx.	8.5 Liter
Coolant Capacity Approx.	13.5 Liter
Oil Change Period	300 Hours
Lube Oil Specification	SAE15W 40 CI4
IP Rating	IP33
Brand	Ashok Leyland

Key Features:

- Reliable, Robust & Rugged engines designed to deliver continuously in arduous environment
- Better Block Loading Capability
- Compact engine: Engineered for Optimized Power Solutions
- Governor: Mechanical
- Low Oil & Fuel consumption
- Continuous duty Power rating
- Minimal vibrations and lower noise levels
- Easy Serviceability & Repairability
- Alternator: STAMFORD Brushless, Single Bearing, Class H Insulated, Voltage Regulation: ± 0.5%, 0.8PF Lag

GENERAL DESCRIPTION	UoM	63kVA - E	63kVA-M
New Name after Emission Certification	Engine Model	**AL4CTIDG2**	**AL4CTIDG5**
No of Cylinders	Qty	4	4
Gross Rated Power	kW/hp	59 / 80.2	59 / 80.2
Overload Power (110 %)	kW/hp	64.9 / 88.3	64.9 / 88.3
RPM		1800	1800
Typical Alternator Efficiency	% age	90.5	90.5
Working Principle	2/4 Stroke	4	4
BORE / STROKE	mm / mm	104 x 113	104 x 113
Displacement	cc	3840	3840
Compression Ratio	mm	16.5 ± 0.5:1	16.5 ± 0.5:1
Unit Dry Wt of Bare Engine Kg	kg	350	350
Flywheel Housing	SAE	SAE 3	SAE 3
Direction of Rotation from Flywheel End		Counter Clockwise	Counter Clockwise
Firing Order	Seq	1-3-4-2	1-3-4-2
Mechanical efficiency	% age	91.8%	91.8%
Thermal efficiency	% age	40.40%	40.40%
Reference Standard	REF	ISO 8178	ISO 8178
Governing system Type of Governor		Elecronic	Mechanical
Class Of Governor		A0	A1
Engine Speed Droop (Governing)	% age	0%	0%
Heat Rejection to atmosphere	% age	4-7%	4-7%
Battery Volts	Volts	12V	12V
Battery Capacity	A.H.	90 AH	90 AH
No. of Starter Motors provided	Qty.	1	1
Rating Of starter motor	kW	2.2	2.2
Battery Charging alternator Capacity amps	amp	35	35
Intake Manifold Temperature (Max)	deg.C	48 ± 2	48 ± 2
Intake Manifold Pressure	kPa	90 - 110	90 - 110
Intake Air Flow	m3/min	3.29	3.3
Max. Allowable restriction in Air Element	inch	14	14
Air Cleaner efficiency for dirt removal	% age	99.95%	99.95%
Engine Cooling System Coolant Capacity	Lit.	13.5	13.5
Cooling Heat Rejection, kW	kW	50.2	50.2
Max Cooling System Pressure	PSI	12.8	12.8
Coolant Outlet Temp (Max)	deg. C	95	95
Coolant Inlet Temperature	deg. C	75	75
Start to Open temp for Thermostat	deg. C	82	82
Fully Open temp for Thermostat	deg. C	95	95
Coolant topping-up / draining frequency		Every 2 Years or 1000 hrs.	Every 2 Years or 1000 hrs.
Fan Diameter	inch	22"	22"

Fan Power	kW	2	2
Manifold Type		Dry Type	Dry Type
Max. Wt of Exhaust System on Engine	kg	15	15
Dia of Exhaust Outlet (inside)	mm	72	72
No of Exhaust outlet	Nos.	1	1
Max allowable System back pressure kPa	kPa	5	5
Heat rejection to exhaust	kW	41.8	41.8
Heat rejection to coolant	kW	50.2	50.2
Heat rejection to atmosphere	%	~4to7%	~4to7%
Stack Temp	deg. C	530	530
SFC at 100%	gms/bhp/Hr	156.60	157.20
SFC at 75%	gms/bhp/Hr	169.80	170.40
SFC at 50%	gms/bhp/Hr	181.50	182.40
No of Holes	no	4	4
Dia of Hole	mm	10	10
PCD	mm	125	125
Fuel Pump		Rotary	Inline
Fuel Transfer pump type		Plunger	Plunger
Filter Type		Spin On	Spin On
No of filters		1	1
Refill volume with Lube Filter change	lit	9	9
Lub Oil system capacity (with filters)	lit	9	9
Lub Oil temperature (max)	deg. C	120	120
Fuel Shut-Off solenoid type & Travel		Electrical	Electrical /24mm
Low Lub Oil Pressure Shut-Off	psi	7.5	7.5
High Water Tempo Shut-Off	deg.C	105 ± 3	105 ± 3
Crank termination signal	r.p.m / Oil. Press	Oil Pressure	Oil Pressure
Lub Oil Pressure Guage		Digital	Digital
Water Temp Guage		Digital	Digital
Hourmeter cum r.p.m meter		Digital	Digital
Ammeter		Digital	Digital
Flywheel Housing Coupling Size	SAE	SAE 3	SAE 3
Flywheel Coupling Size	SAE	SAE 10	SAE 10
Flywheel Diameter	mm	390	390
Flywheel Width	mm	88	88
Flywheel No of teeth	no.	126	126
Flywheel Weight	kg	30	30
Noise on Full Load at 1 m	dba	98	98
Engine Warm-Up time before putting load	Sec	60	60

Engine Cooling time before Engine Shut-Down	Sec	120	120
Sudden 100% decrease in Load. =<10%	%	NA	5
Sudden 100% increase in Load. =<10%	%	NA	5
Recovery for 100% decrease inload =<8 sec	Sec	NA	3
Recovery for 100% increase inload =<8 sec	Sec	NA	3