

DUMP TRUCK

HOWO-NX 8x4 | 24 CBM

Suitable for sand and aggregate

STRONG POWER

- MC11.44-50 engine, 440 HP, Euro V emissions.
- ZF 16S2230TO + PTO transmission for the tipping hydraulics.
- 8x4 drive with 9,500 kg x 2 front axles and 16,000 kg x 2 rear axles, suited to heavy sand and aggregate loads.

DURABILITY

- Q355 steel cargo body: 10 mm floor and 8 mm walls.
- Leaf-spring suspension front and rear; (8+8)/300 mm frame.
- 12.00R24 tyres.

CHARACTERISTIC CONFIGURATIONS

- H77L cab, one sleeper, with A/C.
- BOSCH steering.
- HYVA lifting system.
- 400 L fuel tank.

TECHNICAL SPECIFICATION

	Item	Specification
Overall Parameters	Model	HOWO-NX 8x4 Dump Truck
	Driving Type	8x4
	GVW (kg)	51000
	Dimension, approx. (L×W×H)(mm)	10100×2500×3400
	Wheel Base (mm)	1800+2800+1400
	Frame (mm)	(8+8)/300
	Suspension (F/R)	Leaf spring / Leaf spring
Chassis	Engine	MC11.44-50, 440 HP
	Emission Standard	Euro V
	Transmission	ZF16S2230TO + PTO
	Steering	BOSCH
	Front Axles (kg)	9500 × 2
	Rear Axles (kg)	16000 × 2
	Cab	H77L, one sleeper, with A/C
	Tyre	12.00R24
	Fuel Tank (L)	400
Truck	Cargo Capacity (m³)	24
	Body Size (mm)	7000×2300×1500
	Body Material	Q355
	Floor / Wall Thickness	10 mm / 8 mm
	Lifting System	HYVA brand