Supplement to TrajCert: Sharp risk identification and anytime-valid certification with informative outcome-resolution paths

Salaheddine Naslouby*[1] Mohamed Lachgar [2] Hamid Hrimech [1]

[1]Hassan First University, National School of Applied Sciences (ENSA),
LAMSAD Laboratory, Berrechid, Morocco
[2]Cadi Ayyad University, Higher Normal School (ENS),
L2IS Laboratory, Marrakech, Morocco

This supplement supplies analytical details, conditional numerical arguments, the complete final-cell power results and reproducibility information. Notation agrees with the article: A, G, c are resolved harmful, resolved beneficial and terminal unresolved masses, u is terminal harmful mass, and $r = A + G$.

1 Information decomposition and all boundary cases

For fixed observable masses, every completion has the joint table

$$\begin{array}{c|cccc} & 1 & \cdots & K & \infty \\ \hline L=1 & a_1 & \cdots & a_K & u \\ L=0 & b_1 & \cdots & b_K & c-u \end{array}. \tag{S1}$$

Its entries are nonnegative and sum to one exactly when $0 \le u \le c$. The row harmful marginal is $A + u$. Conditioning on columns gives

$$H(L \mid J_\Pi) = \sum_{k:a_k+b_k>0} (a_k + b_k) h\left(\frac{a_k}{a_k + b_k}\right) + q(u, c-u). \tag{S2}$$

This proves the information profile in the article without a selection-model assumption. When $r, c > 0$, put $p_R = A/r$, $p_U = u/c$ and $\theta = rp_R + cp_U$. Then

$$\mathcal{S}_\Pi(u) - \tau_\Pi = h(\theta) - rh(p_R) - ch(p_U) \tag{S3}$$

$$= rD_{\mathrm{KL}}\{\mathrm{Bern}(p_R) \| \mathrm{Bern}(\theta)\} + cD_{\mathrm{KL}}\{\mathrm{Bern}(p_U) \| \mathrm{Bern}(\theta)\} \ge 0. \tag{S4}$$

The equality is interpreted by continuity if a marginal is zero. For $0 < r, c < 1$, equality in the divergence inequality holds precisely at $p_R = p_U$, proving $u = Ac/r$. Thus τ_Π is the minimal possible full information and is determined by the resolved timing distribution. Equation (S4) also displays the model as an information budget for terminal selection after accounting for observed timing.

For interior hidden masses, $h'(x) = \log\{(1-x)/x\}$ and $h''(x) = -1/\{x(1-x)\}$. Hence

$$\mathcal{S}''(u) = \frac{1}{u} + \frac{1}{c-u} - \frac{1}{A+u} - \frac{1}{G+c-u} = \frac{A}{u(A+u)} + \frac{G}{(c-u)(G+c-u)}. \tag{S5}$$

If $r > 0$, at least one numerator is positive, so the profile is strictly convex whenever $c > 0$. If $A = 0 < G$, the derivative is $\log\{(G+c-u)/(c-u)\} > 0$ and the minimum is $u = 0$. If $G = 0 < A$, the derivative is $\log\{u/(A+u)\} < 0$ and the minimum is $u = c$. If $c = 0$, the only completion is $u = 0$, with information $h(A) - T_\Pi = \tau_\Pi$. If $r = 0$, $c = 1$, the profile is $h(u) - h(u) = 0$ throughout $[0, 1]$. These cases also show why no minimum-information risk is defined from resolved cases when $r = 0$.

*Corresponding author: naslouby.salahe@gmail.com; ORCID: 0009-0002-7295-7816.

For $r > 0, c > 0$, strict convexity and continuity imply that the sublevel set is empty below its minimum, is the unique minimizer at equality, and is a nonempty compact interval above it. It can touch either boundary; an interior root need not exist on both branches. Since every feasible completion is a valid table and no other completion is possible, its risk interval is sharp. If only coarse observations are supplied, any completion can be lifted to a hypothetical finer representation with no additional within-coarse-band outcome dependence, preserving mutual information. Known fine margins restrict such a lift, which is why the article states sharpness with respect to the supplied partition.

2 Refinement, strictness and decision frontiers

Let each finite coarse band B collect fine bands with masses $m_k = a_k + b_k$ and harmful proportions $r_k = a_k/m_k$. For $m_B = \sum_{k\in B} m_k > 0$, its harmful proportion is $\bar{r}_B = \sum_{k\in B} m_k r_k / m_B$. Its entropy gain is

$$m_B h(\bar{r}_B) - \sum_{k\in B} m_k h(r_k) \geq 0. \tag{S6}$$

Strict concavity makes the inequality strict exactly when positive-mass proportions within B differ. Sum over coarse bands. The unresolved column is unchanged, so this sum is $T_c - T_f$, independent of its hidden label split. The chain rule for the deterministic map $J_c = g(J_f)$ gives

$$I(L; J_f) = I(L; J_c) + I(L; J_f \mid J_c), \tag{S7}$$

and identifies the sum with the conditional information. Comparing profiles gives nesting at every common budget, including empty-set cases.

For the sufficient strictness condition in the article, fine compatibility gives $\rho \geq \tau_f > \tau_c$. Therefore the coarse right endpoint is strictly to the right of its minimizer. If it is below c, its coarse profile value is ρ and its fine profile value is $\rho + \Delta$. Fine feasibility excludes that point. Compactness prevents the fine upper endpoint from approaching it without attaining it, proving strict inequality. If both right endpoints are c, the upper risks coincide despite $\Delta > 0$. Thus informative timing is insufficient for strict improvement when both bounds are saturated. If $c = 0$, there is no hidden risk to tighten.

For the frontier, first note that every compatible set contains $\theta^\dagger = A/r$. Hence $\beta < \theta^\dagger$ is intrinsically uncertifiable even if $A \leq \beta$; $\beta < A$ is the stronger direct obstruction. If $\beta \geq A + c$, every completion is safe. Otherwise, $\theta^\dagger \leq \beta < A + c$ puts $u_\beta = \beta - A$ on the right branch, where the profile is strictly increasing beyond its minimum. If $\rho \leq \mathcal{S}(u_\beta)$, its sublevel-set right endpoint is at most u_β. If $\rho > \mathcal{S}(u_\beta)$, continuity gives a feasible point to the right of u_β (as $u_\beta < c$), so certification fails. Equality therefore belongs to the certifying side. Subtracting the two profiles at u_β gives the exact frontier shift. In the case $\beta = \theta^\dagger < A + c$, the only certifying budget is $\rho = \tau$.

3 Proof of the simultaneous and projected guarantee

For a true category probability $p_j \in (0, 1)$, write $X_{j,i} = \mathbf{1}\{Y_i = j\}$. For any fixed $z \in [0, 1]$, the process

$$Z_n(z; p_j) = \prod_{i=1}^{n} \left(\frac{z}{p_j}\right)^{X_{j,i}} \left(\frac{1-z}{1-p_j}\right)^{1-X_{j,i}} \tag{S8}$$

is a nonnegative martingale, since its next multiplicative factor has conditional expectation $p_j(z/p_j) + (1 - p_j)\{(1-z)/(1-p_j)\} = 1$. Integrating against a Beta$(1/2, 1/2)$ law preserves this property by conditional Tonelli, with initial value one, and gives the article's $M_{j,n}(p_j)$. At $p_j = 0$, all $X_{j,i} = 0$ almost surely and the limiting mixture is nonincreasing with initial value one; $p_j = 1$ is analogous. The maximal inequality therefore gives

$$\mathbb{P}\{\exists n : M_{j,n}(p_j) \geq d/\delta\} \leq \delta/d. \tag{S9}$$

A union bound over the d categories proves simultaneous containment in every raw interval with probability at least $1 - \delta$. Taking running intersections and intersecting with the simplex preserve this same event. Categories within an event need not be independent. No union bound over monitoring times is used.

On simultaneous containment, the true summary belongs to the exact observable-law region at every n. The actual terminal harmful mass supplies a feasible completion because its finest-path information is at most ρ, and coarse information cannot be larger. Therefore θ is contained in the union of partition-specific risk sets at every n. Its supremum is bounded by the aggregate relaxation and by any conservative numerical enclosure. This proves the article's time-uniform risk guarantee. Restricting reports to checkpoints or adding evidence gates can only remove opportunities to certify, so neither requires extra error spending. If the sensitivity assumption fails, this feasibility step fails; compatibility of some other completion does not repair it.

The event also implies simultaneous coverage of every member of the partition-specific identified set: on it, the entire true observable-law set is part of each projection. Thus the guarantee is stronger than pointwise containment of a selected terminal completion, while the implemented relaxation may be wider than necessary. Across multiple partitions or multiple streams the same reasoning needs a simultaneous observable region or an explicit union allocation; the single-partition theorem does not supply such an allocation automatically.

4 Envelope, numerical contracts and branch-and-bound

For any selected set of categories B, simplex membership implies

$$\max\{\sum_{j\in B}\ell_j, 1-\sum_{j\notin B}v_j, 0\} \le \sum_{j\in B}p_j \le \min\{\sum_{j\in B}v_j, 1-\sum_{j\notin B}\ell_j, 1\}. \tag{S10}$$

These inequalities give the aggregate mass bounds. For $a, b > 0$, $\partial q/\partial a = \log\{(a+b)/a\} \ge 0$ and $\partial q/\partial b = \log\{(a+b)/b\} \ge 0$. Continuity extends monotonicity to boundaries. Thus evaluating q at simultaneous lower or upper coordinates gives valid lower or upper entropy bounds. The raw upper sum is valid but can be loose; intersecting it with the resolved-mass entropy ceiling and $\log 2$ tightens it. A ceiling is not needed to turn the raw sum into an upper bound. This monotonicity argument, rather than attainability of simultaneous upper coordinates, justifies the envelope.

Every categorical summary maps into $\mathcal{E}_n$. Since $\mathcal{S} = h(A+u) - T - q(u, c-u)$ decreases in T, replacing the actual T by T_U can only enlarge its feasible set. For a search box $B = [A_-, A_+] \times [G_-, G_+] \times [u_-, u_+]$, define

$$c_- = \max(c_L, 1-A_+-G_+, 0), \qquad c_+ = \min(c_U, 1-A_--G_-, 1), \tag{S11}$$

$$\tilde{u}_+ = \min(u_+, c_+), \qquad z_- = \max(0, c_- - \tilde{u}_+), \quad z_+ = \max(0, c_+ - u_-). \tag{S12}$$

Impossible mass constraints discard the box. Otherwise every feasible point has $u \in [u_-, \tilde{u}_+]$, terminal beneficial mass in $[z_-, z_+]$, and $\theta \in [A_- + u_-, \min(1, A_+ + \tilde{u}_+)]$. A lower enclosure is

$$\underline{S}_B = \max\left\{0, \inf_{x\in[A_-+u_-, \min(1,A_++\tilde{u}_+)]} h(x) - T_U - \sup_{u\in[u_-,\tilde{u}_+],\, z\in[z_-,z_+]} q(u,z) - \eta_B\right\}, \tag{S13}$$

Here $\eta_B = 0$ in the current source: the intended enclosure comes from directed helper operations rather than an empirical additive allowance. The binary-entropy infimum is at an interval endpoint. The upper mass-entropy bound is the smaller of an Arb interval upper bound, when both arguments are positive, and $(u_+ + z_+)\log 2$. Clamping the information lower bound at zero need not lower-bound a negative relaxed expression, but preserves every feasible relaxed point for $\rho \ge 0$. Thus enclosing arithmetic makes $\underline{S}_B > \rho$ a valid exclusion rule.

The numerical argument has three distinct requirements: enclosing elementary mass and entropy operations; correct likelihood signs in confidence inversion; and retention of all feasible boxes at every search exit. The last requirement follows from the search invariant below. Arb provides enclosing transcendental evaluations under its library contract (Johansson, 2017, in the article reference list). The current accelerated confidence code also accepts some signs from ordinary floating-point logarithms. Its available validation does not supply a uniform error derivation for that filter. The complete implemented guarantee is therefore conditional on the component contracts specified here, rather than established by the tests alone.

Inputs denote exact binary64 dyadics. Assume exact Python integer/rational operations, correctly rounded binary64 conversions and division, correct adjacent-float stepping, and the Arb enclosure contract. Each

process must execute numerical calls serially without external mutation of its Arb context; parallel streams use separate processes. Confidence inversion and projection read the configured precision, 128 bits in this campaign. Summary entropy uses the active Arb context and outward endpoints, so it can be a wider enclosure at another precision without changing the mathematical target.

Mass sums and endpoint conversion. For an exact rational v, a nearest binary64 conversion f is compared with v exactly and moved one adjacent float when necessary to obtain the requested direction. Exact-rational normalization and membership checks are retained for singleton tables and feasible witnesses. General mass, complement, objective and gap sums instead compute $f = \texttt{fsum}(x_i)$ and a residual $e = \texttt{fsum}(x_i, -f)$; a lower result steps down if $e < 0$, and an upper result steps up if $e > 0$. This encloses the exact sum if both sums are correctly rounded, with no overflow or loss of subnormal residuals. Indeed, a nonzero exact sum of binary64 dyadics has magnitude at least the smallest subnormal, so correct residual rounding preserves its sign. This explicit summation contract is stronger than merely assuming each ordinary addition is rounded correctly. Arb endpoints are extracted as integer–power-of-two pairs; their nearest conversions are compared against those exact pairs and stepped outward, with a rational fallback for exceptional exponent ranges. Nonfinite values yield uninformative bounds or failure, rather than a favorable sign.

Accelerated confidence inversion. Let $b = \log B(s + 1/2, n - s + 1/2) - \log B(1/2, 1/2)$ and $t = \log(d/\delta)$. Arb supplies outer binary64 endpoints o_L, o_U for $b - t$. The fast filter evaluates

$$\widehat{\ell}(x) = s\,\texttt{log}(x) + (n - s)\,\texttt{log1p}(-x), \tag{S14}$$

$$e(x) = 2^{10}\epsilon_{\text{mach}}\{|o_L| + |o_U| - \widehat{\ell}(x)\} + o_U - o_L. \tag{S15}$$

It declares a positive root sign when $o_L - \widehat{\ell}(x) > e(x)$ and a negative sign when $o_U - \widehat{\ell}(x) < -e(x)$. Otherwise it evaluates the complete root expression with Arb; an unresolved Arb sign leaves the outer bracket unchanged. Newton-like root estimates are proposals. The auxiliary verified-bracket routine also uses the fast filter, so its name does not imply an Arb check of both endpoints.

The required filter contract is that every accepted sign agrees with the exact mixture-log expression. A complete derivation would need bounds for the platform logarithms, count conversion, products, cancellation and the computed allowance itself. The factor $2^{10}\epsilon_{\text{mach}}$ and finite regression checks do not by themselves establish this contract. No incorrect filter sign in a reported experimental stream has been demonstrated here; a uniform implementation guarantee remains unverified.

Conditional on correct signs, convexity gives the usual bracket invariant: a positive sign moves the outer endpoint and a nonpositive sign moves the inner endpoint. If no inner sign is obtained, the entire corresponding side is retained. Zero-count and all-count boundaries use continuous likelihood values. Running intersections use endpoint maxima and minima. These operations then contain the exact confidence sequence, which is the numerical input hypothesis stated explicitly in the article's time-uniform theorem.

Summary representation. A category-subset sum is enclosed both directly and by its simplex complement. The larger lower endpoint and smaller upper endpoint still enclose every law in the confidence rectangle intersected with the simplex. Monotonicity of q supplies the resolved-entropy bounds, additionally capped above by the resolved-mass upper bound times $\log 2$. Point category tables also use directed aggregate sums and an Arb entropy interval. Their "singleton" flag describes the categories, not exact real entropy. Approximate input normalization accepted by the population data layer is never taken as an exact simplex identity by the certifier.

Upper-search invariant and exits. Initially, every feasible point of the relaxed projection is in the aggregate box. Directed geometry tests reject only impossible mass constraints, and the preceding information lower bound rejects only points outside the information budget. A split uses a representable midpoint inside its parent interval; its two closed children cover the parent, even when rounding makes one child identical to it. A retained box contributes the upward-rounded bound $\min(1, A_+ + u_+)$. Consequently the largest active or queued objective upper bound encloses the remaining supremum. Incumbents can raise this reported maximum but cannot lower it. Objective-gap, decision, box-width, stall and node-cap exits retain the relevant active and queued bounds. If arithmetic fails during a step, the active parent is retained even if only some children have been inserted. Failure before a conservative result is available propagates as a technical failure. When no boxes or incumbent remain, the reported upper bound is one. Thus convergence is unnecessary for domination of V_n.

Singleton shortcut. The scalar right-branch search is used only for point category inputs with point

aggregate mass intervals. It additionally checks exact equality of those aggregates with the category sums and exact normalization with c. A failed identity check gives an assumption-free upper bound, without an incumbent. Exactly normalized tables with non-point aggregate sums use the box search; non-normalized point tables go directly to the conservative fallback. For fixed valid A, G, c, the largest relaxed endpoint uses exactly the supplied entropy upper endpoint T_U, not an independently recomputed nominal entropy. The initial right-branch lower bracket is at or above the exact minimizer $Ac/(A+G)$, and the upper bracket is c. Only a certified profile value above ρ can reduce the upper bracket. Convexity on this branch proves that every feasible hidden mass remains below it; an ambiguous sign cannot reduce that upper bracket. Upward conversion of $A + u_{\mathrm{hi}}$ gives the risk enclosure. Zero resolved or unresolved mass is covered by the continuous boundary formulas. The label `EXACT_SINGLETON` is used only when a verified lower incumbent equals the upper bound; otherwise the result is enclosed or a conservative fallback.

Feasible witnesses and gaps. Candidate allocation and the population root solver are proposal mechanisms only. For a proposed table, the certifier sums its supplied category entries exactly and defines terminal mass as the rational complement $c = 1 - A - G$. It checks exact category, aggregate, terminal and hidden-mass membership, including $0 \le u \le c$. The actual resolved entropy must lie inside its envelope, and an Arb upper bound on the actual table's information must be at most ρ. These checks construct a normalized original joint table regardless of the proposal's rounded aggregate metadata. Its risk is converted downward before becoming an incumbent. The singleton path applies the same entropy-membership and actual-information conditions after its exact mass identities. Failed or unresolved checks give no witness. Thus an incumbent cannot exceed the original supremum and also belongs below the relaxed supremum. The reported gap is rounded upward from the enclosure minus this lower incumbent; no witness means no claimed gap. A lower incumbent above β refutes certification by this projection, without establishing that the true risk exceeds β.

Rejection searches and final assessment. The compatibility search assigns each box the downward bound $\max\{0, \inf q(A, G) - T_U\}$, which is below every original compatibility floor in that box. The intrinsic search uses a downward enclosure of $A_-/(A_- + G_+)$, taking zero if its denominator vanishes, and discards boxes only by the same safe geometry and information tests. This ratio bounds $A/(A+G)$ for every compatible original law retained in the box. In both searches, the minimum active or queued lower bound is therefore a global lower bound. Approximate point values can trigger stopping but never prune boxes or become the reported lower bound. At any early return the active box is included; after splitting its covering children are included. An empty retained queue returns zero rather than a point estimate. Exceptions propagate without a scientific result. If zero resolved mass remains plausible, the intrinsic bound is withheld. Finally, assessment checks that the projection and requested sensitivity budget agree. Rejections use strict comparisons with upward-rounded budget-plus-guard thresholds, while certification uses only $\widehat{U}_n \le \beta$ after the evidence gates. Subject to the confidence-sign and summation contracts above, these facts compose the confidence input, summary enclosure, searches and assessment into the numerical condition of the article's time-uniform theorem.

The current singleton shortcut no longer substitutes an approximate population-root midpoint for an upper enclosure. Existing directional regressions support the repaired normalization, entropy and exit paths. They are finite checks, not a proof of the fast sign filter or a source attestation for every saved run.

Strict comparison guards are 10^{-12}. Population root tolerance is 10^{-12}; identity residual tolerance is 10^{-10}; categorical inversion tolerance is 10^{-12}; the nominal outer objective gap is 10^{-6} with a 2,000,000-node cap. A normalized box-width exit or stall is reported separately from objective convergence.

5 Complete confirmatory outcomes and design

All rows in Table S1 have 100 independent streams, $\delta = 0.05$, and confirmatory indices 1,000,000–1,000,099. Within a law, the same finest-resolution streams feed each partition. The ordinary grid is 2,000, 5,000, 10,000, 20,000; the power and matched-control grids and low-prevalence grid are given in the article. Dense monitoring uses 250, 500, 750, 1,000, 1,250, 1,500, 1,750, 2,000, 2,500, 3,000, 3,500, 4,000, 4,500, 5,000, 5,500, 6,000, 6,500, 7,000, 7,500, 8,000, 8,500, 9,000, 9,500, 10,000. Endpoint-uncertifiable uses 10,000, 20,000, 50,000. Zero counts include all streams and do not imply zero certification probability.

Table S1: All 32 final-cell certification outcomes. Intervals are conditionwise two-sided exact 95% intervals for ever certifying by the horizon, using 100 trials per row.

Scenario	K	ρ	β	Horizon	Certified	95% interval
Endpoint-uncertifiable	1	0.0800	0.070	50,000	0/100	[0.000, 0.036]
Endpoint-uncertifiable	2	0.0800	0.070	50,000	100/100	[0.964, 1.000]
Endpoint-uncertifiable	4	0.0800	0.070	50,000	100/100	[0.964, 1.000]
Endpoint-uncertifiable	8	0.0800	0.070	50,000	99/100	[0.946, 1.000]
Population decision boundary	1	0.0500	0.060	20,000	0/100	[0.000, 0.036]
Population decision boundary	8	0.0500	0.060	20,000	0/100	[0.000, 0.036]
Ignorable delay	1	0.0200	0.090	20,000	98/100	[0.930, 0.998]
Ignorable delay	8	0.0200	0.090	20,000	0/100	[0.000, 0.036]
Intrinsic impossibility	1	0.0500	0.050	20,000	0/100	[0.000, 0.036]
Low prevalence	1	0.0200	0.050	20,000	100/100	[0.964, 1.000]
Low prevalence	2	0.0200	0.050	20,000	99/100	[0.946, 1.000]
Low prevalence	4	0.0200	0.050	20,000	99/100	[0.946, 1.000]
Low prevalence	8	0.0200	0.050	20,000	99/100	[0.946, 1.000]
No timing control	1	0.0800	0.090	50,000	94/100	[0.874, 0.978]
No timing control	2	0.0800	0.090	50,000	28/100	[0.195, 0.379]
No timing control	4	0.0800	0.090	50,000	0/100	[0.000, 0.036]
No timing control	8	0.0800	0.090	50,000	0/100	[0.000, 0.036]
Misspecified sensitivity	1	0.0200	0.045	20,000	0/100	[0.000, 0.036]
Misspecified sensitivity	2	0.0200	0.045	20,000	0/100	[0.000, 0.036]
Incompatible budget	4	0.0200	0.060	20,000	16/100	[0.094, 0.247]
Incompatible budget	8	0.0200	0.060	20,000	0/100	[0.000, 0.036]
Near degeneracy	1	0.0493	0.050	20,000	99/100	[0.946, 1.000]
Near degeneracy	8	0.0493	0.050	20,000	99/100	[0.946, 1.000]
Dense monitoring	1	0.0200	0.065	10,000	0/100	[0.000, 0.036]
Strong timing	1	0.0800	0.090	50,000	96/100	[0.901, 0.989]
Strong timing	2	0.0800	0.090	50,000	100/100	[0.964, 1.000]
Strong timing	4	0.0800	0.090	50,000	100/100	[0.964, 1.000]
Strong timing	8	0.0800	0.090	50,000	99/100	[0.946, 1.000]
Risk near budget	1	0.0500	0.052	20,000	0/100	[0.000, 0.036]
Risk near budget	8	0.0500	0.052	20,000	0/100	[0.000, 0.036]
Unsafe law	1	0.0500	0.040	20,000	0/100	[0.000, 0.036]
Unsafe law	8	0.0500	0.040	20,000	0/100	[0.000, 0.036]

Table S2: Current search states among 96 decision-targeted streams at selected checkpoints. C: certified; R: refuted; U: unresolved; S: stopped. Four full-search representatives per cell are excluded. Runtime is the median projection-related checkpoint time over available targeted updates, in seconds.

Scenario	K	Events	C	R	U	S	Median (s)
Strong timing, $\beta = .09$	1	5,000	0	89	7	0	0.0080
Strong timing, $\beta = .09$	2	5,000	96	0	0	0	0.6113
Strong timing, $\beta = .09$	1	50,000	92	0	4	0	4.1088
Matched control	2	50,000	27	1	67	1	13.8887
Matched control	8	50,000	0	94	0	2	0.0981

Each row sums to 96. These are states at the specified checkpoint, whereas the headline proportions count all streams that have ever certified among 100, including the four full-search representatives. Decision-targeted execution can stop when a bound settles the risk-budget comparison; full search continues toward its objective-gap target. A full search can report a stall after already obtaining a certifying upper bound. Here, refutation denotes the recorded decision-refuted termination, conditional on a numerically verified feasible lower incumbent above β; it withholds certification and does not show that the true risk exceeds β. The

interpretation requires the numerical contracts above; saved termination labels alone do not prove them. Unresolved denotes a stalled search that neither certified nor supplied a refutation; further search need not certify. Stopped paths have no current update after their running confidence region became empty, but remain in all denominators. No model-incompatible state was recorded at any of the 160 power checkpoints.

Additional laws use the parameter order $(\theta, q_1, q_0, \lambda_1, \lambda_0)$. High unresolvedness has $(.05, .70, .40, .35, -.10)$. The timing-only law has $(.05, .10, .10, .45, -.15)$ and the terminal-only law has $(.05, .30, .05, 0, 0)$. Near degeneracy has $(.01, .90, .01, .80, -.80)$; intrinsic impossibility has $(.15, .10, .10, 0, 0)$. The unsafe, risk-near-budget, incompatible-budget, misspecified-sensitivity and population-decision-boundary scenarios use the ordinary timing-and-terminal harmful-late law from the article. The ignorable-delay and dense-monitoring scenarios use the independent-resolution law. The 32-band validity law is regenerated at 32 bands with the ordinary timing-and-terminal parameters, rather than being a coarsening of the eight-band law.

In the seven validity scenarios, $\rho = I_{\text{true}} + 0.01$, except the minimum-information completion, which sets terminal harmful mass to Ac/r and uses $\rho = \tau + 0.002$. The near-certification risk budget is its own sharp upper bound at the designated ρ plus 0.002; other validity budgets are 0.05. Each scenario uses 500 independent streams, seed indices 0–499, through 500 matured events. The nominal error budget is unchanged. Construction exclusions are monitored at every event and risk-bound diagnostics at the five 100-event checkpoints.

A separate descriptive assessment of the longer-horizon power records retains the longest observed horizon for each of 21 distinct law–partition stream sets. Across 2,100 indexed stream outcomes, 58 exclusions of the true categorical law were recorded (2.8%), with at most six exclusions among 100 streams in any set. These observations are not 2,100 independent Bernoulli trials: some partitions share event streams, and empty confidence regions terminate further updates. Accordingly, this aggregate is descriptive and is not assigned a pooled binomial confidence interval or a campaign-wide coverage interpretation.

For a count x of m streams, the two-sided 95% binomial interval has lower endpoint zero if $x = 0$ and otherwise $B^{-1}_{x,m-x+1}(0.025)$, and upper endpoint one if $x = m$ and otherwise $B^{-1}_{x+1,m-x}(0.975)$. One-sided violation limits equal one if $x = m$ and otherwise use $B^{-1}_{x+1,m-x}(0.95)$. This distinguishes the Monte Carlo intervals from the stream's own time-uniform confidence region. The prespecified final-horizon power target uses the two-sided interval's lower endpoint, exactly as stored in the publication artifacts.

Repeated-static monitoring uses per-category Wilson intervals with $z = \Phi^{-1}\{1 - \delta/(2d)\}$ and no correction across looks. It can therefore have greater power without sharing TrajCert's exact time-uniform guarantee. At the final horizon of the valid ignorable-delay regime, its counts are 98/100 at $K = 1$ and 0/100 at $K = 8$, while the ignorable-delay reference certifies 98/100 at either partition. In the unsafe law, the latter reference certifies falsely in 7/100 at each displayed partition, but its independence assumption fails there. These are assumption-violation diagnostics. In the dense-monitoring scenario it certifies 97/100, whereas neither sensitivity projection certifies; the stronger identifying assumption changes the population target bound.

All TrajCert power cells record zero false risk certification. The stored premature-certification counter is also zero: it counts certificates in cells classified as compatible but not population-certifiable, and does not include model-incompatible cells. The sensitivity-misspecified two-band cell is population-certifiable under its assumed model but has true risk $0.05 > 0.045$ and true partition information above $\rho = 0.02$; its observed zero certifications do not validate that assumption. The incompatible four-band cell certifies 16/100 although $\rho < \tau$ in the population, with true risk below its budget. These outcomes illustrate the distinction between risk error and a certificate issued under a false structural assumption.

6 Secondary numerical and transport diagnostics

A node-budget sweep at the same finite-sample envelope returns the upper bound 0.356365 for all seven caps from 1,000 to 2,000,000 nodes. Every search stops at 104 nodes by box resolution, with gap 0.157533. Increasing the cap cannot improve a search already terminated by another rule. This is a documented limitation of the relaxation and stopping configuration, not evidence of optimizer convergence or numerical stability.

The foreign-information diagnostic applies local risk decisions to altered population tables. The path replacement preserves local endpoint masses but substitutes conditional timing shapes from a second law; naive pooling averages local and second-law masses equally. Heterogeneity interpolates the five law parameters

from local to foreign values. Table S3 retains every effect category over 280 design cells per row. At full heterogeneity, pooling introduces an error relative to the local analysis in 63 cells, and path replacement in two. These are deterministic design-grid counts, not Monte Carlo error probabilities.

Table S3: Foreign-information effects relative to the local analysis. Each row sums to 280. NC: no change; BT: tightening without a newly introduced error; CW: widening; EB: newly introduced erroneous bound; MI: model incompatible. Labels classify relative effects, not validity under the local true law.

Heterogeneity	Replacement	NC	BT	CW	EB	MI
0.00	Path	271	0	1	0	8
0.00	Pooled	280	0	0	0	0
0.25	Path	102	61	87	1	29
0.25	Pooled	31	80	110	28	31
0.50	Path	102	53	87	3	35
0.50	Pooled	31	68	98	48	35
0.75	Path	102	43	87	3	45
0.75	Pooled	31	62	91	60	36
1.00	Path	114	42	72	2	50
1.00	Pooled	30	57	94	63	36

An introduced error means loss of true-risk containment, an upper bound below the true risk, or a false population certificate when that error was absent locally. The grid includes budgets that already fail for the local law. For example, at full heterogeneity the path and pooled tables have 62 and 106 containment failures, respectively, but only two and 63 newly introduced errors. A "tightening" or "widening" label therefore does not establish validity. At zero heterogeneity, naive pooling leaves all 280 cells unchanged; path replacement regenerates shapes at the analysis resolution and can differ from coarsening the finest local law. It is consequently not a pure zero-change control. These diagnostics motivate using trajectories from the target population; they do not provide a transportability theorem. The full outcome counts, including underestimation and false-certification indicators, are retained in the evidence archive.

7 Reproducibility record

The current canonical configuration, `configs/trajcert.yaml`, has SHA-256

`932d1995d99ed3b91963220aedae29a64b7c0091768b220001a6da4eb762b866.`

The retained 19 October design copy has SHA-256

`865eeb27e1bdbead6198ecfc1f45349a483fe44e4ea6a06e71012ca0e35058b7.`

The two files differ only in execution batch sizes: coverage 50 versus one, and power ten versus one. The scientific law parameters, budgets, grids, seed indices and thresholds are identical. The completed current records contain 3,200 power batches and 3,500 coverage batches, each holding one stream. Their scientific-specification digest is

`bfd5e15eac0bfe08b1c0f095b5c99d28d25ad10efe9c9dcecb8c1f33ba4549e7.`

The current report records commit `1cdf6d737c4b4a1f81214348945de4338ad62471`; this manuscript revision inspected `e4f5cef47d3af18f5badcb0a644dbc3636d52cd5`. The report's configuration and source hashes agree with the available files. Its commit identifies a reporting checkout, whereas the per-cell dependency fingerprint omits the source tree. These records establish which numerical artifacts support the manuscript, but do not independently attest the implementation bytes used by every historical stream. Earlier selected-case equivalence and feasible-oracle diagnostics are retained as historical validation, not proof of full campaign equivalence.

The report's environment-lock digest is

`2f94341d20401569cbbd305333d78becd88a046ca1b272c30b49997836fcf9db.`

The manifest declares Python 3.12 or later, NumPy 2.5.2, SciPy 1.17.1, mpmath 1.3.0 and python-flint 0.9.0; `uv.lock` supplies the resolved graph and `requirements.lock` its hash-locked export. The declared environment does not independently identify the physical CPU or machine load for the timing measurements. The retained quality log records 1,005 passing tests and 91.98% branch-aware coverage; these are previously completed checks, not tests executed during this manuscript revision.

Seeds derive from SHA-256 of a semantic event-stream namespace and stream index, using NumPy's PCG64 generator. The namespace includes the law and finest band count but excludes analysis partition, sensitivity budget, risk budget and experiment name. Coarse analyses reuse the same stream and shorter horizons use prefixes. Disjoint exploratory pilots informed law and horizon selection: ten streams ordinarily and twenty for the optional-stopping grid. A separate ten-stream pilot of the ordinary population-decision example recorded no certification through 200,000 matured events. It is not part of the 100-stream confirmatory estimates and does not establish that certification is impossible at later horizons. The retained pilot records are private; their local design account is not an external preregistration.

The publication archive `evidence_current.zip` contains unchanged copies of the current scientific records and their completion markers, individual power and validity batches, all cited numerical tables, figure source data, the current configuration and dependency locks, with a SHA-256 manifest. No raw external diagnostic data or private pilot records are distributed. The previous `evidence.zip` is a historical preparation artifact and is not the evidence archive for this revision. Reproduction of the publication assets reads these records; it does not require a new simulation.

The manuscript checks reconstruct all 160 power-checkpoint counts and exact intervals, the 32 final-cell summaries, the seven validity-study denominators and limits, the population-decision grid, solver discrepancies and scaling-unit conversions. They also verify all 116 rendered source/destination pairs in the current report. Compared with the previous publication archive, the complete final power-summary table is unchanged, while all 160 runtime medians and 119 bound-gap medians differ. Accordingly, all runtime and gap descriptions use the current records. The no-false-risk-certification counts, stopped paths, incompatible-model certificates and noncertifying controls remain visible. No scientific experiment was executed and no scientific input or result was modified during this revision.