ZENTRONIC BIOSYSTEMS

3-Part Auto Hematology Analyzer

- 2 Reagents.
- 21 Parameters.
- 60 Samples/hour.
- Low consumption of reagent and sample.



Smart Auto Hematology Analyzer Designed for Clinic

Low Consumption

- Only need two reagents.
- Sample volume⩽20uL.

Efficient

- 60 samples per hour.

Compatibility

- Two modes of sampling: Whole blood, pre-diluted blood.
- Build-in thermal printer, external laser printer or inkjet printer.
- 4 USB, 1 LAN support protocol HL7 and compatible with LIS system.
- Accompanying quality control material.

Lightweight

- 390mm(L)×285mm(W)×390mm(H)
- Weight⩽16Kg.

Less Maintenance

- Auto-cleaning of sample probe and tubes.
- Automatic fault processing function.

User-friendly

- 10.4" colorful touchscreen.
- Liquid Crystal Display.
- Resolution: 800×600.
- 10° incline adapt to visual observation.

Specifications

Parameter	Precision	Linear Range	Contamination Rate
WBC	⩽2.0% (3.5-15.0×10⁹)/L	(0-100.0×10⁹)/L	⩽0.5%
RBC	⩽1.5% (3.0-6.0×10¹²)/L	(0.10-8.00×10¹²)/L	⩽0.5%
HGB	⩽1.5% (100-180) g/L	(0-250) g/L	⩽0.6%
MCV	⩽1.0% (70-120)fL	—	—
PLT	⩽4.0% (150-500×10⁹)/L	(0-1000×10⁹)/L	⩽1.0%

Power	Voltage: AC 100V~240V, 50/60Hz Rated Power: 120VA
Principle	Electric impedance method and Colorimetry method.
Parameters	21 reportable parameters: WBC, LYM#, MID#, GRAN#, LYM%, MID%, GRAN%, RBC, HGB, HCT, MCV, MCH, MCHC, RDW-CV, RDW-SD, PLT, MPV, PDW, PCT, P-LCR, P-LCC 3 histograms
Quality Control	3 Level QC, L-J graph, X-B
Calibration	Manual and Auto-calibration
Reagents	Build-in LH Lyse, External Diluent, Probe Cleaner for maintenance.
Flag System	RBC, WBC, PLT abnormal sample and support customized test groups
Storage	Up to 50,000 results including histograms, scattergrams and patient information.
Accessories	Standard: waste liquid barrel, ground wire(3m) Option: mouse, external barcode scanner
Operational Environment	Working Temperature: 10℃~35℃ Relative Humidity: 20%~85%

Marketed By :
Bindushree Biomedicals
177/B 4th Main 10th Cross Bapujinagar
Banglore -560 026
Mob: 9964390305