COUNT with CONFIDENCE



Analyze the Vanguard way

VANGUARD DIAGNOSTICS

VANALYZE™ - V30s

3- Part Differential Automated Hematology Analyzer

Correct, Consistent, Creditable COUNTS

NEW Efficient Technology

- Minimum size with footprint of a 17 inch laptop.
- Space saving design allows internal storage of VANALYZE™ LYSE reagent.
- Powerful software to enhance user experience.

- Only two reagents required, VANALYZE™ DILUENT and LYSE.
- New technology that eliminates the need for Cleanser & Rinse.
- Lower reagent consumption.



ADVANTAGE : Intelligent Flagging

- Different 'flag information' provided with histograms - a First for a 3 - Part Analyzer.


Flag	Description
'Leucopenia'	Low levels of White Blood Cells
'Lymph decreased'	Low levels of Lymphocytes
'Pancytopenia'	Low levels of all three blood cells – RBCs, WBCs & Platelets
'R3'	Displayed simultaneously

VANALYZE™ - V30s

Correct, Consistent, Creditable COUNTS

Enhanced Performance

- Up to 70 tests /hour.
- 21 parameters; 3 histograms; 2 research parameters.
- Smart counting mode for reliable low & high end linearity.
- Only two reagents – cyanide free.
- Data storage – 5,00,000 samples with histograms.
- Intuitive operation system with 10.4 inch TFT touch screen.
- Open vial sampling.
- Micro sample volume at 9.0µL for whole blood mode with capillary whole blood samples supported, perfect for pediatric samples.



Broad Connectivity

- WIFI capability provides an added option for data communication with bi-directional LIS, USB port and LAN port, barcode reader, printer and keyboard.



Complete Solution from Vanguard Diagnostics

Instrument, Reagents, Controls, Calibrators

VANALYZE™ - V30s

Technical Specifications

Principle

Impedance method for WBC, RBC and PLT counting, Cyanide free reagent for hemoglobin test.

Performace

Parameter	Linearity Range	Precision (CV %)	Carryover
WBC(10°/L)	0-200	≤3.5% (4.0-6.9) ≤2.0% (7.0-15.0)	≤0.5%
RBC(10'/L)	0-8.00	≤1.5% (3.5-6.5)	≤0.5%
HGB(g/L)	0-280	≤1.5% (100 -180)	≤0.5%
MCV(fL)		≤1.0% (70-110)	
PLT(109/L)	0-4000	≤5.0% (100-149) ≤4.0% (150 -500)	≤1.0%

Parameters

21 parameters: WBC, Lymph#, Mid#, Gran#, Lymph%, Mid%, Gran%, RBC, HGB, HCT, MCV, MCH, MCHC, RDW-CV, RDW-SD, PLT, MPV, PDW, PCT, P-LCR,P-LCC
3 histograms for WBC, RBC and PLT
2 research parameters: NLR, PLR

Data Storage Capacity

Up to 5,00,000 results including numeric and graphical information

Printout

Thermal recorder, 50 mm wide paper, various printout formats
External printer optional

Interface

4 USB port (for external printer, software upgrade, barcode reader, WIFI adapter,keyboard and mouse), LAN port (1)

Communication

LAN Port supports HL7 protocol
Supports bi-directional LIS

Dimension and Weight

Dimension: Depth(410 mm) x width(300 mm) x height(400 mm)
Weight: ≤20Kg

Reagents

VANALYZE™ DILUENT
VANALYZE™ LYSE

Sample Volume

Prediluted mode - 20µl
Whole blood mode - 9µl

Throughput

70 samples per hour

Display

10.4 inch TFT Touch Screen

Power Requirement

100V-240V
<300VA
50Hz/60Hz

Operating Environment

Temperature: 10°C - 40°C
Humidity: 10% - 90%
Air pressure: 70kPa - 106kPa

C-123, Phase-I, Okhla Industrial Area, New Delhi-110020, INDIA
+91-9899529499
info@vanguarddiagnostics.com
www.vanguarddiagnostics.com

VANGUARD DIAGNOSTICS