

\$40	(read_n / write)	ID ID	\$08 \$D4	MSX2+ FS-A1 SERIES* 1CHIPMSX	w/ Z80B 5.37MHz w/ OCM-PLD Pack v2.4
\$41	(read_n / write)	BIT 0 BIT 1 BIT 2 BIT 3 BIT 4 BIT 5 BIT 6 BIT 7		Smart Commands	Get \$FF if Not Found
\$42	(read / write_n)	BIT 0 BIT 1 BIT 2 BIT 3 BIT 4 BIT 5 BIT 6 BIT 7		Green Turbo Display (MSB) Display (LSB) Slot-1 Slot-2 (MSB) Slot-2 (LSB) Current Mapper Current MegaSD	Virtual DIP-SW1 Virtual DIP-SW2 Virtual DIP-SW3 Virtual DIP-SW4 Virtual DIP-SW5 Virtual DIP-SW6 Virtual DIP-SW7 Virtual DIP-SW8
\$43	(read / write_n)	BIT 0 BIT 1 BIT 2 BIT 3 BIT 4 BIT 5 BIT 6 BIT 7		Lock Mask of Toggles**	Turbo Display Audio Mixer & CMT Slot-1 Slot-2 Hard Reset Mapper MegaSD
\$44	(read / write_n)	BIT 0 BIT 1 BIT 2 BIT 3 BIT 4 BIT 5 BIT 6 BIT 7		Lights Mode I/O	Green Led 1 Green Led 2 Green Led 3 Green Led 4 Green Led 5 Green Led 6 Green Led 7 Green Led 8
\$45	(read / write_n) (read only) (read / write_n) (read only)	BIT 0 BIT 1 BIT 2 BIT 3 BIT 4 BIT 5 BIT 6 BIT 7		PSG Volume PSG Mute Master Volume Master Mute	BIT 0 (LSB) BIT 1 BIT 2 (MSB) Status BIT 0 (LSB) BIT 1 BIT 2 (MSB) Status
\$46	(read / write_n) (read only) (read / write_n) (read only)	BIT 0 BIT 1 BIT 2 BIT 3 BIT 4 BIT 5 BIT 6 BIT 7		OPLL Volume OPLL Mute SCC-I Volume SCC-I Mute	BIT 0 (LSB) BIT 1 BIT 2 (MSB) Status BIT 0 (LSB) BIT 1 BIT 2 (MSB) Status
\$47	(read only)	BIT 0 BIT 1 BIT 2 BIT 3 BIT 4 BIT 5 BIT 6 BIT 7		Custom Speed Turbo MegaSD (tMSD) Turbo Pana Redirection (tPR) VGA 60Hz Forced Next Mapper Next MegaSD	BIT 0 (LSB) BIT 1 BIT 2 (MSB) Status Status Status Status Status
\$48	(read only)	BIT 0 BIT 1 BIT 2 BIT 3 BIT 4 BIT 5 BIT 6 BIT 7		Red Turbo (tPANA)* Keyboard Layout CMT Lights Mode Red Mode Last Reset Flag Reset Required Flag MegaSD Blink	Status Status Status 0=Auto, 1=ON Red LED Status 0=Cold, 1=Warm Status Status
\$49 - \$4D	(read only)	BIT 0 BIT 1 BIT 2 BIT 3 BIT 4 BIT 5 BIT 6 BIT 7		Null	Free
\$4E	(read only)	BIT 0 BIT 1 BIT 2 BIT 3 BIT 4 BIT 5 BIT 6 BIT 7		Green Turbo Display (MSB) Display (LSB) Slot-1 Slot-2 (MSB) Slot-2 (LSB) Mapper MegaSD	Hard DIP-SW1 Hard DIP-SW2 Hard DIP-SW3 Hard DIP-SW4 Hard DIP-SW5 Hard DIP-SW6 Hard DIP-SW7 Hard DIP-SW8
\$4F	(read only)	BIT 0 BIT 1 BIT 2 BIT 3 BIT 4 BIT 5 BIT 6 BIT 7		Revision Number Keyboard Layout	BIT 0 (LSB) BIT 1 BIT 2 BIT 3 BIT 4 BIT 5 BIT 6 (MSB) Default Status

(*)

Adv. to FS-A1WX, FS-A1WSX and FS-A1FX specs:
http://map.grauw.nl/resources/msx_io_ports.php#switch_io

SMART COMMANDS TABLE		
\$00	(000)	Null Command (reserved)
\$01	(001)	Set Turbo Pana Redirection OFF (default)
\$02	(002)	Set Turbo Pana Redirection ON
\$03	(003)	Set Standard Speed 3.58MHz
\$04	(004)	Set Custom Speed 4.10MHz
\$05	(005)	Set Custom Speed 4.48MHz
\$06	(006)	Set Custom Speed 4.90MHz
\$07	(007)	Set Custom Speed 5.39MHz
\$08	(008)	Set Custom Speed 6.10MHz
\$09	(009)	Set Custom Speed 6.96MHz
\$0A	(010)	Set Custom Speed 8.06MHz (default) (originally called 10MHz)
\$0B	(011)	Set Turbo MegaSD OFF
\$0C	(012)	Set Turbo MegaSD ON (default)
\$0D	(013)	Set External Slot-1 + External Slot-2
\$0E	(014)	Set Internal SCC-I Slot-1 + External Slot-2
\$0F	(015)	Set External Slot-1 + Internal SCC-I Slot-2
\$10	(016)	Set Internal SCC-I Slot-1 + Internal SCC-I Slot-2
\$11	(017)	Set External Slot-1 + Internal ASCII-8K Slot-2
\$12	(018)	Set Internal SCC-I Slot-1 + Internal ASCII-8K Slot-2
\$13	(019)	Set External Slot-1 + Internal ASCII-16K Slot-2
\$14	(020)	Set Internal SCC-I Slot-1 + Internal ASCII-16K Slot-2
\$15	(021)	Set Japanese Keyboard Layout
\$16	(022)	Set Non-Japanese Keyboard Layout
\$17	(023)	Set Display Mode to 15KHz Composite / S-Video
\$18	(024)	Set Display Mode to 15KHz RGB w/ Audio (Mono)
\$19	(025)	Set Display Mode to 31KHz VGA
\$1A	(026)	Set Display Mode to 31KHz VGA w/ High Luminance
\$1B	(027)	Set VGA to Original Mode (50Hz + 60Hz)
\$1C	(028)	Set VGA to 60Hz Forced (default)
\$1D	(029)	Preset MegaSD OFF for next Warm Reset
\$1E	(030)	Preset MegaSD ON for next Warm Reset
\$1F	(031)	Set MegaSD Blink OFF
\$20	(032)	Set MegaSD Blink ON (default)
\$21	(033)	Set Lights Mode OFF w/ Auto LEDs Control (default)
\$22	(034)	Set Lights Mode ON + Red Led OFF
\$23	(035)	Set Lights Mode ON + Red Led ON
\$24	(036)	Set Audio Mute on PSG, SCC-I and OPLL
\$25	(037)	Set Original Audio Settings on PSG, SCC-I and OPLL
\$26	(038)	Set Audio at Max Volume on PSG, SCC-I and OPLL (default)
\$27	(039)	Set CMT OFF (default)
\$28	(040)	Set CMT ON
\$29	(041)	Lock Turbo Toggles
\$2A	(042)	Unlock Turbo Toggles
\$2B	(043)	Lock Display Toggles
\$2C	(044)	Unlock Display Toggles
\$2D	(045)	Lock Audio Mixer & CMT Toggles
\$2E	(046)	Unlock Audio Mixer & CMT Toggles
\$2F	(047)	Lock Slot-1 Toggles
\$30	(048)	Unlock Slot-1 Toggles
\$31	(049)	Lock Slot-2 Toggles
\$32	(050)	Unlock Slot-2 Toggles
\$33	(051)	Lock Slot-1 & Slot-2 Toggles
\$34	(052)	Unlock Slot-1 & Slot-2 Toggles
\$35	(053)	Lock Hard Reset Key
\$36	(054)	Unlock Hard Reset Key
\$37	(055)	Lock Mapper Toggle
\$38	(056)	Unlock Mapper Toggle
\$39	(057)	Lock MegaSD Toggle
\$3A	(058)	Unlock MegaSD Toggle
\$3B	(059)	Lock All Toggles
\$3C	(060)	Unlock All Toggles (default)
...
...
...
\$80	(128)	Null Command (useful for programming)
...
...
\$D3	(211)	Restore Keyboard to Default Layout
\$D4	(212)	Null Command (reserved)
\$D5	(213)	Restore Turbo to Default Setting
...
...
...
\$FA	(250)	Restore Last Reset Flag to Cold Reset Status
\$FB	(251)	Cold Reset (= Hard Reset)
\$FC	(252)	Warm Reset w/ Mapper 2048KB
\$FD	(253)	Warm Reset
\$FE	(254)	Warm Reset w/ Mapper 4096KB
\$FF	(255)	Restore all Default Settings + Preset Mapper & MegaSD to Default
R / W	(read / write)	0 = OFF 1 = ON Positive Logic
	(read_n / write_n)	0 = ON 1 = OFF Negative Logic
(**)	Turbo	[F12] [SHIFT+PGUP/PGDOWN] [DIP-SW1]
	Display	[PRNSCR] [SHIFT+PRNSCR] [DIP-SW2] [DIP-SW3]
	Audio Mixer & CMT	[F9/F10/F11] [SHIFT+F9/F10/F11] [PGUP/PGDOWN] [SCRLCK]
	Slot-1	[SHIFT+F12] [DIP-SW4]
	Slot-2	[SHIFT+SCRLCK] [DIP-SW5] [DIP-SW6]
	Hard Reset	[HARD RESET KEY]
	Mapper	[DIP-SW7]
	MegaSD	[DIP-SW8]