

Data Tracking Plan (Cocktail Recipes MVP) — V2

1. General information

Product: Cocktail Recipes Website

Version: V2

Changes in V2:

- **Added user authentication**
- **Added rating system**
- **Added reviews**
- **Added user_id tracking**
- **Added new events**
- **Added source parameter for UI context**

Goal:

- Analysis of searches
- Analysis of filters usage
- Analysis of cocktail popularity
- Analysis of authorized users behavior
- Analysis of ratings and reviews
- Product metrics calculation

2. Event Tracking (UPDATED)

The system should record the following events.

No	Event	Meaning
1	age_confirmation	user confirmed / rejected 18+
2	page_view	open page
3	search_query	text search
4	filter_applied	apply filter

5	filters_reset	reset filters
6	cocktail_card_view	cocktail shown
7	cocktail_page_open	cocktail page open
8	servings_changed	change servings
9	signup	user registration
10	login	user login
11	logout	user logout
12	rating_added	user rated cocktail
13	review_added	user left review

All events must contain:

Common fields	Type
timestamp	datetime
session_id	string
anonymous_user_id	string
user_id	string nullable

user_id is NULL for anonymous users.

2.1 Age Confirmation

Event name: age_confirmation

Trigger: click Yes / No

Parameters

Parameter	Type	Description
age_confirmed	boolean	true / false
timestamp	datetime	event time
session_id	string	session identifier

2.2 Page View

Event name: page_view

Trigger: any page opening

Parameters

Parameter	Type
page_name	string
page_url	string
session_id	string

page_name values:

home
search
cocktail_page
login
signup

2.3 Search Query

Event name: search_query

Trigger: click the search button

Parameters

Parameter	Type
search_text	string
results_count	integer
filters_applied	boolean

2.4 Filter Applied

Event name: filter_applied

Parameters

Parameter	Type
filter_type	string
filter_value	string
results_count	integer

2.5 Reset Filters

Event name: filters_reset

Parameters

Parameter	Type
previous_filters	string

2.6 Cocktail Card View (UPDATED)

Event name: cocktail_card_view

Parameters

Parameter	Type
cocktail_id	int
position	integer
source	string

source values:

search_results

similar_cocktails

2.7 Cocktail Page Open (UPDATED)

Event name: cocktail_page_open

Parameters

Parameter	Type
cocktail_id	int
position	integer
source	string

source values:

search_results

similar_cocktails

2.8 Servings Calculator

Event name: servings_changed

Parameters

Parameter	Type
cocktail_id	int
servings_number	integer

2.9 Signup (ADDED)

Event name: signup

Trigger: user registration success

Parameters

Parameter	Type
method	string
success	boolean

method values:

email

Google

2.10 Login (ADDED)

Event name: login

Parameters

Parameter	Type
auth_method	string
success	boolean

2.11 Logout (ADDED)

Event name: logout

Parameters

Parameter	Type
user_id	string

2.12 Rating Added (ADDED)

Event name: rating_added

Trigger: user clicks stars

Parameters

Parameter	Type
cocktail_id	int
rating_value	integer

rating_value:

1–5

2.13 Review Added (ADDED)

Event name: review_added

Trigger: user submits review

Parameters

Parameter	Type
cocktail_id	int
review_length	integer

Review text is stored in Reviews table, not in events.

3. Filter reference values

Alcohol Type

vodka
rum
gin
tequila
whiskey
liqueur
non-alcoholic

Alcohol Level

low
medium
strong

Sweetness Level

dry
medium
sweet

Price Range

Filter by price range: from 0 to max price

Vibe

party
romantic
summer
tropical
classic

4. Key Product Metrics

Search metrics

- total searches
- searches with results
- zero-result searches
- top queries

Filter metrics

- most used filters
- filter combinations

Cocktail metrics

- most viewed cocktails
- $\text{CTR} = \text{cocktail_page_open} / \text{cocktail_card_view}$

Calculator

- $\text{servings_changed} / \text{cocktail_page_open}$

Conversion

- $\text{search_query} \rightarrow \text{cocktail_page_open}$

5. Analytics Questions

- What cocktails are searched for most often?
- What filters are used most often?
- What search queries do not return results?
- What cocktails are opened most often after a search?
- Do users use a portion calculator?

6. Database Schema Changes (V2)

Users (ADDED)

column	type
user_id	int PK
email	varchar
created_at	timestamp
auth_provider	varchar

Notice:

User Identification

anonymous_user_id is used to track users before authentication.

After signup/login, user_id is assigned.

anonymous_user_id and user_id are linked within the same session to connect pre-login and post-login behavior.

For MVP, historical events are not backfilled with user_id.

Ratings (ADDED)

column	type
id	int PK
user_id	int

cocktail_id	int
rating	int
created_at	timestamp

Reviews (ADDED)

column	type
id	int PK
user_id	int
cocktail_id	int
review_text	text
created_at	timestamp
rating	int nullable

Events table (UPDATED)

Add columns:

column
user_id
rating_value
auth_method
success
review_length
source

7. Intire list of the relations

ERD V2

Cardinality

Від → До	Type	Optional / Mandatory	Explanation
Cocktails → Cocktail_ingredients	1 → many	mandatory 1..*	A cocktail always has ≥1 ingredients
Cocktail_ingredients → Cocktails	many → 1	mandatory 1..1	1 and only 1
Ingredients → Cocktail_ingredients	1 → many	optional 0..*	A single ingredient may not be used in any cocktail
Cocktail_ingredients → Ingredients	many → 1	mandatory 1..1	Each recipe line must have exactly one ingredient
Cocktails → Cocktail_tags	1 → many	optional 0..*	A cocktail can have from 0 to many tags, 0..many, because a cocktail can be untagged 1 and only 1
Cocktail_tags → Cocktails	many → 1	mandatory 1..1	1 and only 1
Tags → Cocktail_tags	1 → many	optional 0..*	0 to many, i.e. a tag may not belong to any cocktail_tags
Cocktail_tags → Tags	many → 1	mandatory 1..1	1 and only 1
Cocktails → Cocktail_similar	1 → many	optional 0..*	0 to many, i.e. a cocktail can have 0 or many similar ones
Cocktail_similar → Cocktails	many → 1	mandatory 1..1	1 and only 1 – each connection line always refers to a specific cocktail
Sessions → Events	1 → many	optional 0..*	a session can have 0 to many events
Events → Sessions	many → 1	mandatory 1..1	1 and only 1
Sessions → Page_views	1 → many	optional 0..*	a session can have 0 or many page views
Page_views → Sessions	many → 1	mandatory 1..1	1 and only 1

Cocktails → Events	1 → many	optional 0..*	a cocktail can have 0 or many events
Events → Cocktails	many → 1	optional 0..1	1 and only 1 – each event is related to a specific cocktail or null if the event is not about a cocktail
Cocktails → Page_views	1 → many	optional 0..*	a cocktail can have 0 or many page views
Page_views → Cocktails	many → 1	optional 0..1	1 and only 1
Users → Sessions	1 → many	optional 0..*	A user can have 0 to many sessions. Session may belong to anonymous user (user_id nullable).
Sessions → Users	many → 1	optional 0..1	Session may belong to one user or be anonymous.
Cocktails → Ratings	1 → many	optional 0..*	A cocktail can have 0 to many ratings.
Ratings → Cocktails	many → 1	mandatory 1..1	Each rating belongs to one cocktail.
Users → Ratings	1 → many	optional 0..*	User can create 0 to many ratings.
Ratings → Users	many → 1	mandatory 1..1	Each rating belongs to one user. Constraint: (user_id, cocktail_id) must be unique. User can rate cocktail only once.
Cocktails → Reviews	1 → many	optional 0..*	A cocktail can have 0 to many reviews.
Reviews → Cocktails	many → 1	mandatory 1..1	Each review belongs to one cocktail.

Users → Reviews	1 → many	optional 0..*	User can create 0 to many reviews.
Reviews → Users	many → 1	mandatory 1..1	Each review belongs to one user. Constraint: (user_id, cocktail_id) unique (optional rule)