

Neural Coreference Resolution Models

Natalie Parde

UIC CS 421


Neural Classification Models

- Generally end-to-end systems
- May not have a separate mention detection step
 - Instead, consider every possible text span of length $< k$ as a possible mention
- Same overall goal as usual:
 - Assign to each span i an antecedent y_i ranging over the values $Y(i) = \{1, \dots, i - 1, \varepsilon\}$


What goes on behind the scenes?

- For each pair of spans i and j , the system assigns a score $s(i, j)$ for the coreference link between the two
 - $s(i, j) = m(i) + m(j) + c(i, j)$
 - $m(i)$: Whether span i is a mention
 - $m(j)$: Whether span j is a mention
 - $c(i, j)$: Whether j is the antecedent of i
- The functions $m(\cdot)$ and $c(\cdot, \cdot)$ are computed using neural models:
 - $m(i) = w_m \cdot \text{FFNN}_m(g_i)$
 - $c(i, j) = w_c \cdot \text{FFNN}_c([g_i, g_j, g_i \circ g_j, \phi(i, j)])$
 - Where g_i is a vector representation of span i , and $\phi(i, j)$ encodes manually-defined characteristics of the relationship between i and j
 - Note that the exact definition of $c(i, j)$ may differ across models!


Altogether, a neural coreference resolution model might look like the following....




Altogether, a neural coreference resolution model might look like the following....




Altogether, a neural coreference resolution model might look like the following....




Altogether, a neural coreference resolution model might look like the following....



Altogether, a neural coreference resolution model might look like the following....



Altogether, a neural coreference resolution model might look like the following....



Altogether, a neural coreference resolution model might look like the following....

