1. Start MariaDB

2. Create Tables and Insert Data

a. Schema: Create the necessary tables

```
SQL Statements
                                                                                                      Output
                                                                                iaDB [hw3_database]> CREATE TABLE Booking (
-> agent VARCHAR(50),
-> traveler_ssn INTEGER,
-> trip_id INTEGER,
CREATE TABLE Booking (
             agent VARCHAR(50),
             traveler_ssn INTEGER,
                                                                                -> PRIMARY KEY (agent, traveler_ssn, trip_id)
             trip id INTEGER,
                                                                              ery OK, 0 rows affected (0.008 sec)
                                                                             ariaDB [hw3_database]> show tables;
             PRIMARY KEY (agent, traveler ssn, trip id)
                                                                              Tables_in_hw3_database |
);
                                                                             row in set (0.001 sec)
                                                                             ariaDB [hw3_database]> DESCRIBE booking;
                                                                                                          | Null | Key | Default | Extra |
                                                                                           | Type
                                                                              agent varchar(50)
traveler_ssn int(11)
trip_id int(11)
                                                                              rows in set (0.026 sec)
                                                                               CREATE TABLE TravelAgent (
             name VARCHAR(50),
             years experience INTEGER,
                                                                                   > PRIMARY KEY (name)
             phone VARCHAR(50),
                                                                               MariaDB [hw3_database]> show tables;
                                                                               Tables_in_hw3_database |
             PRIMARY KEY (name)
                                                                               booking
travelagent
);
                                                                               rows in set (0.001 sec)
                                                                               ariaDB [hw3_database]> DESCRIBE travelagent;
                                                                                               | Type | | Null | Key | Default | Extra |
                                                                               name | varchar(50) | NO
years_experience | int(11) | YES
phone | varchar(50) | YES
                                                                               rows in set (0.023 sec)
                                                                               MariaDB [hw3_database]>|
```

```
CREATE TABLE Traveler (
              name VARCHAR(50),
              ssn INT,
                                                                                          -> PRIMARY KEY(name)
              dob DATE,
                                                                                       -> );
uery OK, 0 rows affected (0.009 sec)
                                                                                      MariaDB [hw3_database]> show tables;
              PRIMARY KEY(name)
                                                                                        Tables_in_hw3_database
);
                                                                                       booking
travelagent
traveler
                                                                                       rows in set (0.001 sec)
                                                                                      MariaDB [hw3_database]> DESCRIBE traveler;
                                                                                                                | Null | Key | Default | Extra
                                                                                               | varchar(50) |
| int(11) |
| date |
                                                                                                                  NO
YES
YES
                                                                                                                           PRI |
                                                                                                                                  NULL
NULL
NULL
                                                                                       rows in set (0.016 sec)
                                                                                      Arriads [hwd. database] - CREATE TABLE Trip(

-> id INTEGER,
-> start_location VARCHAR(50),
-> end_location VARCHAR(50),
-> end_tate DATE,
-> end_date DATE,
-> -> CRIMARY KEY (id)
-> );
Query OK, 0 rows affected (0.008 sec)
CREATE TABLE Trip(
              id INTEGER,
              start_location VARCHAR(50),
              end_location VARCHAR(50),
              start_date DATE,
              end_date DATE,
                                                                                        booking
travelagent
traveler
trip
              PRIMARY KEY (id)
);
                                                                                        rows in set (0.001 sec)
                                                                                                                      | Null | Key | Default | Extra
                                                                                                       | Type
                                                                                        NULL
NULL
NULL
NULL
NULL
                                                                                        rows in set (0.021 sec)
```

b. Insert Sample Data

SQL Statements	Output				
NSERT INTO TravelAgent (name, years_experience, phone) VALUES ('Alice Brown', 12, '123-456-7890'), ('John Smith', 8, '234-567-8901'), ('Michael Johnson', 5, '345-678-9012'), ('Sarah Williams', 15, '456-789-0123'),	-> VALUES -> ('Alice Bro -> ('John Smit -> ('Michael J -> ('Sarah Wil -> ('Sarah Wil -> ('Rachel Gr Query OK, 6 rows a Records: 6 Duplic MariaDB [hw3_datab	MariaDB [hw3_database]> INSERI INTO TravelAgent (name, years_experience, phone) -> VAULES -> ('Altice Brown', 12, '123-456-7890'), -> ('John Smith', 8, '234-567-8901'), -> ('Michael Johnson', 5, '345-678-9012'), -> ('Sarah Williams', 15, '436-7678-9012'), -> ('Sarah Williams', 15, '436-789-9012'), -> ('Baniel Lee', 20, '567-890-1234'), -> ('Rachel Green', 3, '678-901-2345'); Query Olk, 6 rows affected (0.020 sec) Records: 6 Duplicates: 0 Warnings: 0 MariaDB [hw3_database]> SELECT * -> FROM TravelAgent;			
('Daniel Lee', 20, '567-890-1234'),	name	years_experience	phone		
('Rachel Green', 3, '678-901-2345');	Alice Brown Daniel Lee John Smith Michael Johnson Rachel Green Sarah Williams	12 20 8 5 3	123-456-7890 567-890-1234 234-567-8901 345-678-9012 678-901-2345 456-789-0123		

```
INSERT INTO Traveler (name, ssn, dob
INSERT INTO Traveler (name, ssn, dob)
VALUES
('David Harris', 101, '1985-06-12'),
('Sarah Connor', 102, '1992-03-05'),
('Mike Johnson', 103, '1998-09-17'),
('Laura White', 104, '1995-04-23'),
('James Miller', 105, '2000-08-14'),
                                                                                       iaDB [hw3_database]> SELECT *
-> FROM Traveler;
('Emma Watson', 106, '1997-11-30'),
('Chris Evans', 107, '1993-06-21'),
('Sophia Brown', 108, '1999-02-25');
                                                                                                         107
101
106
105
104
103
102
108
                                                                                   8 rows in set (0.001 sec)
                                                                         8 rows in set (0.001 sec)

MariaDB [hw3_database]> INSERT INTO Trip (id, start_location, end_location start_date, end_date)
-> VALUES
-> (201, 'New York', 'Paris', '2025-08-01', '2025-08-15'),
-> (202, 'Tokyo', 'Sydney', '2025-09-05', '2025-09-15'),
-> (203, 'Loudon', 'Rome', '2025-06-15', '2025-09-15'),
-> (204, 'Hiami', 'New York', '2025-06-15', '2025-06-20'),
-> (206, 'Sian Francisco', 'Berlin', '2025-10-01', '2025-10-10'),
-> (206, 'Chicago', 'Los Angeles', '2025-09-10', '2025-09-12'),
-> (206, 'Chicago', 'Los Angeles', '2025-09-10', '2025-09-12'),
-> (208, 'New York', 'Dubai', '2025-07-05', '2025-09-15');
Query OK, 8 rows affected (0.001 sec)

Records: 8 Duplicates: 0 Warnings: 0
INSERT INTO Trip (id, start location,
end location, start date, end date)
VALUES
(201, 'New York', 'Paris', '2025-07-10',
'2025-07-20'),
(202, 'Tokyo', 'Sydney', '2025-08-01',
'2025-08-15'),
(203, 'London', 'Rome', '2025-09-05',
                                                                          MariaDB [hw3_database]> SELECT *
-> FROM Trip;
'2025-09-15'),
                                                                            id | start_location | end_location | start_date | end_date
(204, 'Miami', 'New York', '2025-06-15',
                                                                                  New York
Tokyo
London
Miami
San Francisco
Chicago
Boston
                                                                                                         Paris
Sydney
Rome
New York
Berlin
'2025-06-20'),
(205, 'San Francisco', 'Berlin', '2025-10-
01', '2025-10-10'),
                                                                                                         Los Angeles
Dubai
Dubai
(206, 'Chicago', 'Los Angeles', '2025-09-
10', '2025-09-12'),
                                                                           rows in set (0.000 sec)
(207, 'Boston', 'Dubai', '2025-07-05',
'2025-07-18'),
(208, 'New York', 'Dubai', '2025-09-10',
'2025-09-15');
INSERT INTO Booking (agent,
traveler ssn, trip id)
VALUES
('Alice Brown', 101, 201),
('John Smith', 102, 202),
('Michael Johnson', 103, 203),
('Sarah Williams', 104, 204),
                                                                               ariaDB [hw3_database]> SELECT *
-> FROM booking;
('Daniel Lee', 105, 205),
                                                                                                    traveler_ssn | trip_id
('Alice Brown', 106, 206),
('Rachel Green', 107, 207),
('John Smith', 108, 201),
('Alice Brown', 101, 208);
                                                                                  ws in set (0.001 sec)
```

3. SQL Query Exercises

#	SQL Query	Screenshot of SQL Query and Query Output
1	SELECT name, phone, 'Experienced Agent' AS Experience FROM TravelAgent WHERE years_experience > 10;	MariaDB [hw3_database]> SELECT name, phone, 'Experienced Agent' AS Experience -> FROM TravelAgent -> WHERE years_experience > 10;
2	SELECT start_date, end_date FROM Trip WHERE start_location = 'New York';	MariaDB [hw3_database]> SELECT start_date, end_date -> FROM Trip -> WHERE start_location = 'New York';
3	SELECT * FROM Trip WHERE start_location = 'New York' AND end_location = 'Paris';	MariaDB [hw3_database]> SELECT * -> FROM Trip -> WHERE start_location = 'New York' AND end_location = 'Paris'; id start_location end_location start_date end_date 201 New York
4	SELECT * FROM Trip WHERE start_location = 'New York' OR start_location = 'Miami';	MariaDB [hw3_database]> SELECT * -> FROM Trip -> WHERE start_location = 'New York' OR start_location = 'Miami'; id start_location end_location start_date end_date 201 New York Paris 2025-07-10 2025-07-20 204 Miami New York 2025-06-15 2025-06-20 208 New York Dubai 2025-09-10 2025-09-15 3 rows in set (0.008 sec)
5	SELECT * FROM Trip WHERE start_date > '2025-08- 01';	MariaDB [hw3_database]> SELECT * -> FROM Trip -> WHERE start_date > '2025-08-01';
6	SELECT traveler_ssn, trip_id FROM Booking WHERE agent = 'Alice Brown';	<pre>MariaDB [hw3_database]> SELECT traveler_ssn, trip_id -> FROM Booking -> WHERE agent = 'Alice Brown'; traveler_ssn trip_id </pre>
7	SELECT * FROM Traveler WHERE name LIKE '_a%';	MariaDB [hw3_database]> SELECT *

8	SELECT * FROM Traveler	MariaDB [hw3_database]> SELECT * -> FROM Traveler -> WHERE name NOT LIKE 'David Harris';	
	WHERE name NOT LIKE 'David	name ssn dob	
	Harris';	Chris Evans 107 1993-06-21 Emma Watson 106 1997-11-30 James Miller 105 2000-08-14 Laura White 104 1995-04-23 Mike Johnson 103 1998-09-17 Sarah Connor 102 1992-03-05 Sophia Brown 108 1999-02-25 Tows in set (0.003 sec)	
9	SELECT * FROM TravelAgent	<pre>MariaDB [hw3_database]> SELECT * -> FROM TravelAgent -> WHERE phone LIKE '456'; ++</pre>	
	WHERE phone LIKE '456	name years_experience phone	
	 ;	Sarah Williams 15 456-789-0123	
		<pre>++ 1 row in set (0.002 sec)</pre>	
10	SELECT * FROM Trip	MariaDB [hw3_database]> SELECT * -> FROM Trip -> WHERE start_date BETWEEN '2025-07-01' AND '2025-09-30';	
	WHERE start_date BETWEEN	id start_location end_location start_date end_date	
'2025-07-01' AND '2025-09- 30';	201 New York		