

Flight advisor

Create Flight advisor API for finding the cheapest flights.

There are two types of the users: administrator and regular user.

Every user has: first name, last name, user name, password and salt.

The regular user has to register in order to be able to use a Flight advisor.

The administrator is able to :

- Add cities.
For each city, the name, country and description must be provided.
- Import the data for the airports and routes from the datasets given in an attachment.
Each airport contains a city and country name. Don't import airports and routes if the city doesn't exist.

Regular user can:

- Get all the cities (all the comments should be returned, or if specified, only the x latest comments).
- Search for cities by name (all the comments should be returned, or if specified, only the x latest comments).
- Add a comment for the city.
- Delete a comment .
- Update a comment.
- Traveling from city A to B, can include many stops, many airports, and it can cost a lot.
Find the cheapest flight from city A to B, return all the routes included, total price and length. For simplification, each returned route can contain the name of the source and destination cities and price.

Besides the comment's description, each comment should have created and modified date.

Route dataset description:

Airline	2-letter (IATA) or 3-letter (ICAO) code of the airline.
Airline ID	Identifier for airline.
Source airport	3-letter (IATA) or 4-letter (ICAO) code of the source airport.
Source airport ID	Identifier for source airport.
Destination airport	3-letter (IATA) or 4-letter (ICAO) code of the destination airport.
Destination airport ID	Unique OpenFlights identifier for destination airport .
Codeshare	"Y" if this flight is a codeshare, empty otherwise.
Stops	Number of stops on this flight ("0" for direct).
Equipment	3-letter codes for plane type(s) generally used on this flight, separated by spaces.
Price	Flight cost.

Airport dataset description:

Airport ID	Identifier for this airport.
Name	Name of airport.
City	Main city served by airport.
Country	Country or territory where airport is located.
IATA	3-letter IATA code. Null if not assigned/unknown.
ICAO	4-letter ICAO code. Null if not assigned.
Latitude	Decimal degrees, usually to six significant digits.
Longitude	Decimal degrees, usually to six significant digits.
Altitude	In feet.
Timezone	Hours offset from UTC.

DST	Daylight savings time. One of E (Europe), A (US/Canada), S (South America), O (Australia), Z (New Zealand), N (None) or U (Unknown).
Tz	Timezone in "tz" (Olson) format, eg. "America/Los_Angeles".
database	
time zone	
Type	Type of the airport.
Source	Source of this data.