Hybrid Decentralization for Multi-Robot Orienteering with Mothership-Passenger Systems



Nathan L. Butler and Geoffrey A. Hollinger

Collaborative Robotics and Intelligent Systems (CoRIS) Institute, Oregon State University


Multi-robot teams are useful for efficiently exploring isolated, hazardous environments.

If reaching the environment is itself a hazardous task, a larger **mothership** robot can be used to first **transport the team** to regions of interest.

Once the team is deployed, passengers must solve a challenging **Stochastic Multiagent Orienteering Problem** to allocate tasks, plan paths, and return to the mothership for extraction within a travel budget in a stochastic environment.


This problem is typically solved in a **fully decentralized** manner that **struggles** to produce globally-coordinated plans.

Opportunity: How can we leverage a **hybrid centralized-decentralized** network available in Mothership-Passenger systems to **solve complex orienteering problems**?




Hybrid Decentralized Mission Planning

We inject plans developed by a powerful centralized planner onboard the mothership into passengers' decentralized planning routines to improve system-level coordination.



Passengers' decentralized planning routine supports coordination with neighbors in communication range. Plans received from the mothership align passenger actions with distant robots as well.




Experiments and Results

We evaluate our framework in a simulated underwater environment.

Tasks (T) and the mothership location (M) are distributed randomly.

Ocean currents from high-fidelity underwater simulator provide stochastic travel times.





We compare four algorithmic variants:

- Offline, centralized solution only
- Decentralized planning only
- Offline + decentralized replanning
- Offline + hybrid replanning

We inject disturbances (robot failures, new tasks) at specified rates into the system.

These disturbances introduce heterogeneity in team observations and allow us to evaluate each method's performance in replanning.





Our hybrid planning framework offers an initial performance boost from the mothership's centralized solver. Global coordination provided by the mothership improves system robustness in high-disturbance scenarios.

Acknowledgements: Financial support provided by U.S. National Science Foundation, award #2322055. Special thanks to our collaborators at Arizona State University, Brigham Young University, Purdue University, Temple University, and Woods Hole Oceanographic Institution.

