



SUB^{*}ZERO WOLF

LITERATURE STYLE GUIDE

REVISED 8/2016

Model Number Reference

SUB-ZERO

built-in refrigeration	BI
all refrigerator	R
all freezer	F
over-and-under	U
side-by-side	S
glass door	G
high altitude glass door	A
French door	FD
external dispenser	D
internal dispenser	ID
overlay model	/O
stainless steel model	/S
tubular handle	/TH
pro handle	/PH
right-hinge	-RH
left hinge	-LH
PRO 48 refrigeration	PRO
high altitude glass door	HAG
integrated column	IC
integrated tall	IT
integrated drawers	ID
combination	C
ice maker	I
preservation	P
built-in wine storage	BW
integrated wine storage	IW
undercounter wine storage	UW
freestanding	FS
undercounter refrigeration	UC
beverage center	B
outdoor model	O
drain pump	P
International Certified Body	ICB

WOLF

M series	M
E series	E
L series	L
single oven	SO
double oven	DO
transitional	T
professional	P
contemporary	C
framed	F
unframed	U
stainless steel	/S
black glass	/B
tubular handle	/TH
pro handle	/PH
convection steam oven	CSO
drawer microwave	MD
drop down door microwave	MDD
convection microwave	MC
standard microwave	MS
warming drawer	WWD
outdoor model	O
induction cooktop	CI
electric cooktop	CE
gas cooktop	CG
grill module	GM
steamer module	SM
fryer module	FM
teppanyaki module	TM
multifunction cooktop	MM
coffee system	EC
cup warming drawer	CW

WOLF

dual fuel range	DF
gas range	GR
induction range	IR
sealed burner rangetop	SRT
charbroiler	C
griddle	G
double griddle	DG
French top	F
outdoor grill	OG
grill cart	CART
burner module	BM
side burner	SB
LP gas	/LP
cooktop wall hood	VW
cooktop island hood	VI
black	B
stainless	S
glass	G
downdraft system	DD
pro wall hood	PW
pro wall chimney hood	PWC
pro island hood	PI
pro hood liner	PL
internal blower	I
remote blower	R
in-line blower	IL
International Certified Body	ICB

Model Number Reference

COVE

dishwasher	D
overlay model	/O
stainless steel model	/S
tubular handle	/TH
pro handle	/PH

ASKO

dishwasher	D
washer	W
dryer	T
ADA height (dishwasher)	XL
max height (dishwasher)	XXL
large capacity (washer / dryer)	XL
integrated handle	HI
tubular handle	TH
pro handle	PH
panel ready	FI
stainless steel	S
white	W
titanium	T
water softener	SOF
condenser (ventless)	C
heat pump	HP
integrated handle, front control	54
panel ready	55
integrated handle, hidden control	56
tubular or pro handle	56
outdoor	59

Style Guidelines

COLOR

- Sub-Zero 2-color palette: Pantone 3005 and black. Pantone 3005 conversion to CMYK: 100C 34M 0Y 2K.
- Wolf 2-color palette: Pantone 1805 and black. Pantone 1805 conversion to CMYK: 0C 91M 100Y 23K.
- Asko 2-color palette: Pantone 1797 and black. Pantone 1797 conversion to CMYK: 0C 94M 94Y 6K.
- Cove 2-color palette: Pantone 382 and black. Pantone 382 conversion to CMYK: 29C 1M 100Y 0K.
- Screen values for black: 10%, 40%, 70% and 85% (logo grey). Never screen the Pantone color.

TEXT

- Guide text and headlines are Helvetica Neue LT Std Roman. Highlighted text and subheads are Helvetica Neue LT Std Medium.
- All dimensions and other units of measurement use the United States customary system (USCS) with metric conversions listed in parentheses.
- Metric conversions, including the parentheses and the space before, appear approximately one point smaller than the English dimension.
- Add kerning of 50 between whole number and fractions.
- In text, use words for numbers from one to nine, use numerals for 10 and above. Use words for numbers beginning a sentence. In charts, always use numerals.
- Use specified capitalization and lowercase as indicated in the model number reference and common words.
- Product names and literature titles should be all lowercase in text, use initial caps in a headline.
- Use all caps for names of touch pads (controls) in text.
- Use all lowercase for text in parentheses.
- In most cases, use periods at the end of bullet points and at the end of captions.
- For use & care guides, place warranty on IBC with no page heading or page number. Refer to IBC.

Style Guidelines

GENERAL

- When including width with product name, it should appear first (e.g. 30" E series single oven).
- For integrated product, use column, tall and drawers (not column model, tall model and drawer model) except to distinguish from height (tall) or upper or lower drawer (drawers).
- Do not use metric conversions for name of product (e.g. 60" dual fuel range).
- Do not use metric conversions in headlines, subheads or captions.
- Do not use metric conversions for defined dimensions (e.g. 1/8" drill bit).
- Border for guide illustrations is 5 pt rule, 70% black.
- Rules for product feature call-outs are 5 pt, 40% black.
- To avoid incorrect page number reference, use 'on the following page(s)' instead of page number whenever possible.
- Allow additional white space on the page for English version guides, to keep translations page for page (translated text runs longer).
- Avoid using slashes (/) and ampersands (&) in file names.
- Use 'directions' when referencing recipes, use 'instructions' when referencing the appliance.
- URL in design guide, use & care and installation guides should be subzero.com at the bottom of right side pages. Use Sub-Zero Customer Care 800.222.7820 on left side pages. Use Wolf, Cove and Asko similarly.
- Exclude www. in corporate website address.
- Abbreviate Wisconsin (WI) in address.

GRAMMAR

- Use abbreviations in charts, spell out words in text. Use abbreviations as indicated in the abbreviations chart with no periods.
- Plural abbreviations do not need an 's'.
- Do not use contractions (e.g. do not vs don't).
- Limit the use of 'the' in text. Generally, it can be eliminated unless for an individual or unique object (e.g. 'the control panel', 'remove screws').
- Avoid using 'you' and 'your' in guide text.
- Use straight quotation marks ("") for inches. Use curly quotation marks (' ') and (" ") for phrases.
- Use single quotation marks for visual display readouts (e.g. 'PrF'). Use double quotations for generally accepted terms (e.g. "brick oven" effect).
- Use en dash (–) for range of numbers (option hyphen).
- Use em dash (—) in text if parentheses is not appropriate (shift option hyphen).
- For examples, use e.g. (e.g. 3 for boneless poultry). Do not use i.e. which means "in other words".

Style Guidelines

ILLUSTRATIONS

- Product or model illustrations are referred to as '3D beauty'. 'Overall dimensions' (OD) contain 2D front, side and top views with dimensions. 'Installation illustrations' are 2D and contain specifications needed for installation. The smaller illustrations used in guides that fit two per column width, are generally 3D and are referred to as 'guide illustrations'.
- Illustrations are created as 100% vector eps files.
- Black is the only color used in illustrations. Screen values within illustrations can be 10%, 40% and 70% black. Black glass can be filled 80% black. Screened rules (40%) can be used to show alternative position.
- Text and call-outs within illustrations are Helvetica Medium and should be all caps.
- Units of measure in domestic guides use the United States customary system (USCS) with metric conversions listed in parentheses.
- Whole number dimensions in illustrations are 8 pt, fractions, metric conversions and text are 6.5 pt.
- Add kerning of 50 between whole number and fractions.
- For consistency of text size in illustrations, size guide illustrations to be placed at approx 92% and installation illustrations at approx 97%. Illustrations are generally created (or scaled) to be placed at these repro sizes.
- Line weight in guide illustrations generally range from .3 to .8 pt. Line weight can be heavier for product line illustrations (3D beauty) which may be reproduced at a much smaller scale.
- For illustration rules use rounded cap and corner.
- Dashed lines indicate centerline, cut-out and screw location (generally 8 pt dash, 1.5 pt space).
- Dashed lines and rules for call-outs within illustrations are .3 pt. Rules for arrows are .4 pt.
- To reduce file size, delete any images on hidden layers used as reference.
- Set Illustrator document color mode to CMYK:
File > Document Color Mode > CMYK Color (not RGB).
- Convert Illustrator colors to grayscale: Select all.
Edit > Edit Colors > Convert to Grayscale. Colors on hidden layers do not need to be converted.

MULTI-LANGUAGE

- Domestic use & care and installation guides include English, Spanish and French.
- International use & care and installation guides typically include English, Spanish, French, Italian and German.
- Text and illustrations for domestic Spanish and French as well as all international languages are based on translations of the English version. For international guides, unique safety precautions and electrical, plumbing and gas information apply.
- Illustrations for domestic Spanish and French as well as all international languages are separate versions of the original illustration. This includes only illustrations with text.
- For international guides, all dimensions and other units of measurement use the metric system. 'Standard' (USCS) units are not included.

Abbreviations | Acronyms

MEASUREMENTS

degrees Fahrenheit	°F
degrees Celsius	°C
inch(es)	"
foot or feet	'
millimeter(s)	mm
centimeter(s)	cm
meter(s)	m
ounce(s)	oz
pound(s)	lb
gram(s)	g
kilogram(s)	kg
square feet	sq ft
cubic feet	cu ft
inch-pound(s)	in-lb
British thermal unit(s)	Btu
watt(s)	W
kilowatt(s)	kW
kilowatt/hour(s)	kWh
inside diameter	ID
outside diameter	OD
teaspoon(s)	tsp
tablespoon(s)	Tbsp
pint(s)	pt
quart(s)	qt
gallon(s)	gal
fluid ounce(s)	fl oz
milliliter(s)	ml
liter(s)	L
A-weighted decibels	dB(A)
volt(s)	V
volts alternating current	VAC
ampere(s)	amp
hertz	Hz
kilo-pascal(s)	kPa
water column	WC
millibar(s)	mb
revolutions per minute	rpm

GENERAL

Americans with Disabilities Act	ADA
Association Home Appliance Mfg.	AHAM
altitude	alt
approximately	approx
Canadian Standards Association	CSA
capacity	cap
continued	con't
department	dept
dimension	dim
dozen	doz
electrical supply location	E
extension or extended	ext
gas supply location	G
ground fault circuit interrupter	GFCI
horizontal	hor
international	intl
International Certified Body	IBC
Kitchen/Bath Industry Show	K/BIS
left-hand or left-hinge	LH
liquid propane	LP
maximum	max
minimum or minute(s)	min
natural gas	NG
piece (e.g. 6-pc set)	pc

GENERAL

package	pkg
percent (use symbol)	%
point (text size)	pt
quantity	qty
recommended	rec
right-hand or right-hinge	RH
serial number	SN
simmer	sim
specifications	specs
square	sq
ultraviolet	UV
uniform resource locator	URL
Underwriters Laboratories	UL
United States Customary System	USCS
ultraviolet	UV
vertical	ver
volume	vol
wireless fidelity	WiFi
weight	wt

Abbreviations | Acronyms

GUIDES	ILLUSTRATIONS	FILE FORMATS	
Sub-Zero	SZ	Overall Dimensions	OD
Wolf	WF	Installation	IN
Asko	AS	Front View	FV
Cove	CV	Full-Scale	FS
design guide	DG	Flush Inset Installation	FI
use & care guide	UCG	Installation Specifications	IS
use & care card	UCC	Panel Specifications	PS
installation guide	IG	Integrated Product (new generation)	IP2
installation decal	ID		
product guide	PrG		
planning guide	PG		
price list	PL		
kitchen design contest	KDC		
parts & accessories	PA		
quick reference	QR		
distributor information	DI		
dynamic product configurator	DPC		
English	EN or ENG		
Spanish	SP or ES		
French	FR		
Italian	IT		
German	DE		
trilingual	TriL		
2-color	2C		
4-color	4C		
Pantone	PMS		
process color	CMYK		
inside front cover	IFC		
inside back cover	IBC		
		Adobe Illustrator	AI
		Encapsulated PostScript	EPS
		Portable Document Format	PDF
		Joint Photographic Experts Group	JPEG
		Tagged Image File Format	TIFF
		Portable Network Graphics	PNG
		Scalable Vector Graphics	SVG
		Drawing	DWG
		Computer-Aided Design	CAD

Common Words

3-prong	condensation drying system	dual-zone
40-watt	connected appliance	dual-action
90° door stop (not 90-degree)	contemporary	dual-stacked burner
accessory kit (not package)	continuous grates	dual convection fans
activated	cook time (not cooking time)	dual refrigeration
ADA height compliant	cooktop ventilation	dual wide grille
adjacent cabinet	cookware sensing	Dual VertiCross convection
agency-approved	cobalt blue	duct cover
AHAM overall capacity	conduit	durability
AHAM usable capacity	counterclockwise (no hyphen)	easy-access
airflow (one word)	column (not column model)	easy-to-use
air purification system	CSA certified	egg container (not tray)
air deflector	crescent-shaped ice	electrical supply (not power supply)
Allen wrench	crisper cover (not crisper lid)	email (no hyphen)
all refrigerator	cut-out (use hyphen)	E series
all freezer	cutlery basket	environmental awareness
anchoring	D-style handle	Energy Star qualified
anti-tip	deactivated	espresso
annual energy usage	decal (not sticker)	ethylene gas
auto-close	decibels	exterior temperature display
audible chime (not beep)	dedicated circuit	extra-tight
backlight	delay-off feature	Fahrenheit (°F)
backsplash	delayed start	family size
black glass	deli drawer	flip-up grille
boost mode	descaling solution	filter clean indicator
bridge zone	dinnerware	finished height
bypass (no hyphen)	discharge	freshness cards
cappuccino	dishwasher-safe	flush inset
Celsius (°C) (not centigrade)	dispenser model	figure 8 tumbling
centerline	door/drawer alarm	fold-down tines
ceramic briquettes	docking station	freestanding (no hyphen)
Ceran glass-ceramic surface	double oven	French top
charbroiler	drawers (not drawer model)	front controls
cherrywood-faced	drum	full-extension easy glide
chimney-style	drying cycle	full-scale template (not illustration)
child lock	dryness level	full-view glass door
CoBrand (no hyphen)		

Common Words

full-length handle	installation specifications	National Electrical Code
fully integrated	insulating liner	new generation
glasswell	integrated handle	nonabrasive (one word)
glides (dishwasher rack)	integrated design	non-combustible surface
Gourmet feature	interactive smart-touch control panel	non-ducted application
griddle	interactive touchscreen	number pads (plural)
grill (Wolf)	interactive visual display	obround
grille (Sub-Zero)	internal dispenser	octagonal-shaped
grounding-type	inventory tile system	one-touch opening
half-bottles	intuitive power scale	opening (not rough opening)
hand-finished	key pad (Sub-Zero)	operating time
handleless design	kickplate (not toe kick)	outdoor grills (not BBQ grills)
heat sentry feature	latte	over-and-under
heavy-duty	large-capacity	overlay
height-adjustable	lint-free cloth	panel ready
hidden controls	loading height	perforated pan
Hidden Helpers™	low-profile	place settings
high altitude glass	lower drawer (not bottom)	Phillips screwdriver (capital P)
high-efficiency	lower oven (not bottom)	point-of-use
high-end	L series	porcelain-coated
high-frequency pulsation	L-bracket	portable
high-humidity	light bulb (2 words)	pot holder (two words)
high-volume	M series	power level indicator
hood width (not width of hood)	macchiato	power cord
hot-surface	make-up air	precise control
ice and water dispenser	melt setting	precision-built
ice maker (two words)	method (not procedure for recipes)	pre-drilled
ice machine	microbiological	presets
ice container (not ice bucket)	microfiber	PRO 48 (all caps)
in-and-out adjustment (hyphens)	model and serial numbers	product-to-product capabilities
indicator (not icon)	multi-language	product rating plate
independent timer	multi-purpose lighter (not BBQ)	product registration card
infinite-speed	multi-speed	pro ventilation
infrared	multifunction (no hyphen)	professional
installation guide (not instructions)	multiple sequence	provided (not included or supplied)
	nano-coated	

Common Words

pull-out	slide-out bins	trimless design
push-to-activate controls	smart home features	triple-pane
quiet-close	smooth-glide	triple-zone
quiet operation	spray arm	troubleshooting (one word)
rack (not basket for dishwasher)	spring and damper hinge system	true cabinet depth
radiant heat	soft-close glide system	true simmer
rangetop	solid-core	tumble action
rating plate (sticker)	spill-proof	Turbo Drying™ system
readout	spin speed	turntable
recircualting kit	spray nozzle	two-drawer
reignition (no hyphen)	stand-off	two-liter bottle storage
remote-mounted	standard microwave (vs non-convection)	two-tiered control knobs
restaurant-grade	Star-K certified (kosher certification)	UL approved
retractable shelf	status indicator light	UltraCare washer (dryer)
reverse osmosis system	stile and rails (list stiles first)	undercounter
rinse aid	standoff (one word)	universal off
roll-out	stack kit	up-and-down adjustment
roller-glide wine rack	stacked installation	up-front
rotisserie	status lights	upper-level
rustproof	supersized	upper cabinet
S-grates	subflooring (one word)	upper drawer (not top)
Sabbath feature	tall (not tall model)	upper oven (not top)
saucepan (one word)	telescopic chimney	use & care guide (use ampersand)
Scandinavian design	teppanyaki	utility bin
sear zone	three-panel assembly	UV-resistant
“season” the griddle	time of day	vented
self-clean	titanium	ventless
self-piercing	toe kick (not toe space)	verify (not make sure)
shut-off valve	top-to-bottom	wash cycle
shipping weight	touch-screen	wash programs
side-by-side (Sub-Zero)	touch control panel	water filtration system
side by side installation (Asko)	touch pad (Wolf)	water softener
side-to-side adjustment (hyphens)	TouchProof™ stainless steel	waxed paper (not wax)
signature red knobs	transitional	WiFi (no hyphen)
six-level rack guide	TriBrand	wine rack (not shelf)

Common Language

DESIGN GUIDE

Features and specifications are subject to change at any time without notice. Visit subzero.com/specs for the most up-to-date information.

IMPORTANT NOTE: Throughout this guide, dimensions may vary by $\pm \frac{1}{8}$ " (3). Dimensions in parentheses are millimeters unless otherwise specified.

CUSTOMER CARE

The model and serial number are printed on the enclosed product registration card. Both numbers are also listed on the product rating plate. Refer to page X for rating plate location. For warranty purposes, you will also need the date of installation and name of your authorized Wolf dealer. Record this information below for future reference.

If your product ever needs attention, be sure to use a Wolf factory certified service provider recommended by our customer care center, or select one from our list of providers available at wolfappliance.com/locator. All factory certified service providers are carefully selected and thoroughly trained by us.

SERVICE

Maintain the quality built into your product by contacting Wolf factory certified service. For the name of the nearest Wolf factory certified service, check the contact & support section of our website, wolfappliance.com or call Wolf customer care at 800-222-7820.

When contacting service, you will need the model and serial number of your product. Both numbers are listed on the product rating plate. Refer to page X for rating plate location.

For warranty purposes, you will also need the date of installation and name of your authorized Sub-Zero dealer. This information should be recorded on page X of this guide.

INSTALLATION

To ensure this product is installed and operated as safely and efficiently as possible, take note of the following types of highlighted information throughout this guide:

IMPORTANT NOTE highlights information that is especially important.

CAUTION indicates a situation where minor injury or product damage may occur if instructions are not followed.

WARNING states a hazard that may cause serious injury or death if precautions are not followed.

IMPORTANT NOTE: Throughout this guide, dimensions in parentheses are millimeters unless otherwise specified.

Important product information including the model and serial number are listed on the product rating plate. The rating plate is located...

Can be installed in a standard or flush inset application.

Rating plate location, electrical supply location, gas supply location, water supply location and condenser location (not location of).

Installation must comply with all applicable electrical (plumbing, gas) codes.

Finish all sides of the custom panels. They may be visible when the door is open or through the window of glass door models.

...with screws provided (not supplied or included).

Remove and recycle packing materials.

Turn power off (not shut off power).

Refer to the illustration below.

Common Language

SUB-ZERO PRODUCT

Dual refrigeration system ensures the freshest food and energy efficiency.

Four distinct design options: framed, overlay, flush inset and stainless steel.

Integrated design allows for dual installation and point-of-use refrigeration.

Crafted of heavy-duty stainless steel.

For handy tips and information on how to maximize food freshness, refer to the freshness cards stored in the refrigerator.

This appliance is certified by Star-K to meet strict religious regulations in conjunction with specific instructions found on www.star-k.org.

Follow directions on the interactive display.

Maintains ideal storing and serving temperature for all wines, humidity and UV protection.

To remove or adjust a glass shelf, tilt up, then lift up and out. To reposition, insert shelf in the tracks along the back wall, then lower the front until it locks into position.

Replacement Sub-Zero air purification cartridges (water filters) can be ordered online at subzerowolfstore.com.

For questions, contact Sub-Zero customer care at 800-222-7820.

Using a soft bristle brush, vacuum to remove dust and lint from the condenser area.

Sub-Zero recommends (not we recommend).

Use a nonabrasive stainless steel cleaner and apply with a soft lint-free cloth. To bring out the natural luster, lightly wipe surface with a water-dampened microfiber cloth followed by a dry polishing chamois. Always follow the grain of stainless steel.

Stainless steel tubular and pro handles.

Specify RH or LH door.

WOLF PRODUCT

Designed to match Wolf transitional (professional, contemporary) products.

Integrated design allows for installation of multiple cooktops or modules.

Combine with other modules or larger cooktops to create a custom cooking array.

Create perfectly brewed coffee, espresso, cappuccino, macchiato and latte at home.

Trim kits available to match Wolf ovens.

Ten cooking modes for predictably delicious results (convection, roast, bake, broil, convection roast, bake stone, Gourmet, warm, proof and dehydration).

Induction elements heat iron and other magnetic cookware instantly, while cooktop surface stays cool.

Three adjustable oven racks; one full-extension easy glide, one full-extension door glide and one standard.

Oven will turn off automatically (not shut off).

Internal, in-line or remote blower required.

Performance may be compromised if the electrical supply is less than 240 volts. (products with conduit)

A ground fault circuit interrupter (GFCI) is not recommended and may cause interruption of operation. (products with power cord)

...preset to 000° (not preset at 000°).

...power outage (not power failure).

ASKO PRODUCT

At Asko, we design and manufacture premium quality dishwashers with a special Scandinavian touch for design and function.

Energy saving features give all models Energy Star® qualified rating.

Contact Information

Sub-Zero Group, Inc.

Sub-Zero, Inc. and Wolf Appliance, Inc.

Contact Sub-Zero (Wolf) factory certified service.

Contact Sub-Zero (Wolf) customer care at 800-222-7820.

If service is necessary, contact Sub-Zero factory certified service with the model and serial number. For the name of the nearest Sub-Zero factory certified service or for questions regarding the installation, visit the contact & support section of our website, subzero.com or call Sub-Zero customer care at 800-222-7820.

Optional accessories are available through an authorized Wolf dealer. For local dealer information, visit the find a showroom section of our website, wolfappliance.com.

Metric Conversion Guidelines

- Metric units should be labeled as shown in the conversion charts on the following pages, rounded, with the same capitalization and no period.
- Plural abbreviations do not need ‘s’.
- Length conversions from inches should be specified in millimeters ($1" = 25.4$ mm).
- Length conversions from feet should be specified in meters ($1' = 0.3048$ m).
- Weight conversions from pounds: under 1 pound should be specified in grams, 1 pound and over specify in kilograms ($1 \text{ lb} = 0.4536 \text{ kg}$).
- Weight conversions from ounces should be specified in grams, over 1000 grams specify in kilograms ($1 \text{ oz} = 28.3495 \text{ g}$).
- Liquid volume conversions: less than 1 liter should be specified in milliliters, 1 liter and over specify in liters.
- Round all fractions to the nearest $1/8$ ($1/16$ in select situations).
- Round all decimals to the nearest 0.1 (0.01 in select situations).
- Round weight conversions to the nearest 5 grams, volume to the nearest 5 milliliters.
- Round temperatures to the nearest 5 degrees.

Common Metric Conversions

LENGTH	
inches	millimeters
1/4"	6 mm
3/8"	10 mm
1/2"	13 mm
5/8"	16 mm
3/4"	19 mm
1"	25 mm
3"	76 mm
4"	102 mm
5"	127 mm
6"	152 mm
9"	229 mm
12"	305 mm
15"	381 mm
18"	457 mm
21"	533 mm
24"	610 mm
25"	635 mm
27"	686 mm
30"	762 mm
36"	914 mm
38"	965 mm
39"	991 mm
42"	1067 mm
45"	1143 mm
48"	1219 mm
54"	1372 mm
60"	1524 mm
66"	1676 mm
72"	1829 mm
80"	2032 mm
81"	2057 mm
83"	2108 mm
84"	2134 mm
88"	2235 mm

LENGTH	
feet	meters
2'	.6 m
3'	.9 m
4'	1.2 m
6'	1.8 m
8'	2.4 m
9'	2.7 m
10'	3 m
5,000'	1524 m
8,600'	2621 m
10,250'	3124 m

LENGTH		
fraction	decimal	mm
1/16	.063	2 mm
1/8	.125	3 mm
3/16	.188	5 mm
1/4	.25	6 mm
5/16	.313	8 mm
3/8	.375	10 mm
7/16	.438	11 mm
1/2	.5	13 mm
9/16	.563	14 mm
5/8	.625	16 mm
11/16	.688	17 mm
3/4	.75	19 mm
13/16	.813	21 mm
7/8	.875	22 mm
15/16	.938	24 mm
1	1.0	25 mm

Common Metric Conversions

WEIGHT	
ounces	grams
1 oz	30 g
2 oz	60 g
3 oz	85 g
3½ oz	100 g
4 oz (¼ lb)	115 g
5 oz	140 g
6 oz	170 g
6½ oz	185 g
7 oz	200 g
8 oz (½ lb)	230 g
9 oz	255 g
10 oz	285 g
11 oz	310 g
12 oz (¾ lb)	340 g
13 oz	370 g
14 oz	395 g
14½ oz	410 g
15 oz	425 g
16 oz (1 lb)	455 g
17 oz	480 g
18 oz	510 g
19 oz	540 g
20 oz	565 g
28 oz	795 g
36 oz	1 kg

WEIGHT	
pounds	kilograms
1/4 lb	.1 kg
1/2 lb	.2 kg
3/4 lb	.3 kg
1 lb (x .454)	.5 kg
1 1/4 lb	.6 kg
1 1/2 lb	.7 kg
1 3/4 lb	.8 kg
2 lb	.9 kg
2 1/2 lb	1.1 kg
3 lb	1.4 kg
4 lb	1.8 kg
5 lb	2.3 kg
6 lb	2.7 kg
7 lb	3.2 kg
8 lb	3.6 kg
9 lb	4 kg
10 lb	4.5 kg
15 lb	6.8 kg
20 lb	9 kg
100 lb	45 kg
125 lb	57 kg
200 lb	90 kg
250 lb	115 kg
300 lb	135 kg
400 lb	180 kg

BURNER RATING	
Btu	kWh
30,000 Btu	8.8 kWh
25,500 Btu	7.5 kWh
25,000 Btu	7.3 kWh
22,000 Btu	6.5 kWh
20,000 Btu	5.9 kWh
18,000 Btu	5.3 kWh
16,000 Btu	4.7 kWh
15,000 Btu	4.4 kWh
14,000 Btu	4.1 kWh
12,000 Btu	3.5 kWh
10,000 Btu	2.9 kWh
9,200 Btu	2.7 kWh
9,000 Btu	2.6 kWh
8,000 Btu	2.3 kWh
800 Btu	.2 kWh
700 Btu	.2 kWh
500 Btu	.1 kWh
300 Btu	.1 kWh

Common Metric Conversions

TEMPERATURE

Fahrenheit	Celsius
-5°F	-20°C
5°F	-15°C
0°F	-18°C
32°F	0°C
34°F	1°C
38°F	3°C
40°F	4°C
45°F	7°C
50°F	10°C
55°F	13°C
65°F	18°C
70°F	20°C
100°F	40°C
110°F	45°C
120°F	50°C
140°F	60°C
160°F	70°C
165°F	75°C
180°F	80°C
195°F	90°C
200°F (212°F)	100°C
225°F	105°C
250°F	120°C
275°F	135°C
300°F	150°C
325°F	165°C
350°F	175°C
375°F	190°C
400°F	205°C
425°F	220°C
450°F	230°C
475°F	245°C
500°F	260°C
525°F	275°C
550°F	290°C

VOLUME (DRY)

ounces	ml / L
1 oz	30 ml
2 oz	60 ml
2.4 oz	70 ml
2.7 oz	80 ml
3 oz	90 ml
4 oz	120 ml
5 oz	150 ml
6 oz	180 ml
7 oz	210 ml
8 oz	240 ml
9 oz	270 ml
10 oz	300 ml
11 oz	330 ml
12 oz	360 ml
15 oz	450 ml
17 oz	500 ml
34 oz	1 L
50 oz	1.5 L
68 oz	2 L

VOLUME (LIQUID)

volume	ml / L
1/4 tsp	1 ml
1/2 tsp	2 ml
1 tsp	5 ml
1 Tbsp (1/2 fl oz)	15 ml
2 Tbsp (1/8 cup)	30 ml
1/4 cup	60 ml
1/3 cup	80 ml
1/2 cup	120 ml
2/3 cup	160 ml
3/4 cup	180 ml
1 cup (8 fl oz)	240 ml
1 cup (8 fl oz) rounded	250 ml
1 1/2 cups	350 ml
2 cups (16 fl oz)	475 ml
1 pint (16 fl oz) rounded	500 ml
3 cups	700 ml
4 cups (1 quart)	950 ml
4 cups (1 quart) rounded	1 L
4 quarts (1 gal)	3.8 L
4 quarts (1 gal) rounded	4 L

Corporate Logos

- Use 2C framed logo for 2C guide cover and CMYK badge logo for guide with 4C cover.
- Use 2C framed logo with warranty in use & care, product guide and price lists.
- All corporate logos have options for black or white ®.
- Always use original logo files dated 7/2015, color and ® options will swap in exact position and scale.
- To size logos visually proportionate, place logo at the percentage shown for 8.5 x 11 guide cover and warranty. Refer to IBC.

Sub-Zero badge logo 30.2%



SUB-ZERO DESIGN GUIDE

Wolf badge logo 29.2%



Cove badge logo 30.2%



Asko CMYK logo 25.2%



Sub-Zero 2C framed logo 31.7%



Wolf 2C framed logo 29.5%



Cove 2C framed logo 30.2%



Asko 2C logo 25.2%



CoBrand badge logo 65%



CoBrand framed logo 64.6%



TriBrand badge logo 56%



TriBrand framed logo 55.6%



Address Line

- Address line on back cover of 8.5 x 11 guide is 8 pt. Helvetica Neue LT Std Medium, 85% black, tracking 100. Use white for 4C guide with dark image.
- Part number and date are 6.5 pt. Helvetica Neue LT Std Roman, black, tracking 100. Use white for 4C guide with dark image.
- For guide shipped with product (use & care and installation), bar code is black and placed at 75% on the back cover with white area surrounding as shown below.



Registered Trademark Text

- Registered trademark text is approximately 6.5 pt. Helvetica Neue LT Std Roman—black as shown below. The text should fit full width with justified margins and be placed at the bottom of the page.
- For guide not including the warranty, registered trademark text should be placed on IBC with no page heading or page number.
- For guide with the warranty on IBC, registered trademark text should be placed on the previous page.

SUB-ZERO, INC. P.O. BOX 44848 MADISON, WI 53744 SUBZERO.COM 800.222.7820

WOLF APPLIANCE, INC. P.O. BOX 44848 MADISON, WI 53744 WOLFAPPLIANCE.COM 800.222.7820

COVE APPLIANCE, INC. P.O. BOX 44848 MADISON, WI 53744 COVEAPPLIANCE.COM 800.222.7820

ASKO, INC. P.O. BOX 44848 MADISON, WI 53744 ASKONA.COM 800.222.7820

SUBZERO-WOLF.COM

Sub-Zero, Sub-Zero & Design, Dual Refrigeration, The Living Kitchen, Great American Kitchens The Fine Art of Kitchen Design, and Ingredients are registered trademarks and service marks of Sub-Zero, Inc. Wolf, Wolf & Design, Wolf Gourmet, W & Design and the color red as applied to knobs are registered trademarks and service marks of Wolf Appliance, Inc. All other trademarks or registered trademarks are property of their respective owners in the United States and other countries.

Wolf, Wolf & Design, Wolf Gourmet, W & Design and the color red as applied to knobs are registered trademarks and service marks of Wolf Appliance, Inc. Sub-Zero, Sub-Zero & Design, Dual Refrigeration, The Living Kitchen, Great American Kitchens The Fine Art of Kitchen Design, and Ingredients are registered trademarks and service marks of Sub-Zero, Inc. All other trademarks or registered trademarks are property of their respective owners in the United States and other countries.

Sub-Zero Residential Limited Warranty

FOR RESIDENTIAL USE

FULL TWO YEAR WARRANTY*

For two years from the date of original installation, this Sub-Zero product warranty covers all parts and labor to repair or replace, under normal residential use, any part of the product that proves to be defective in materials or workmanship. All service provided by Sub-Zero under the above warranty must be performed by Sub-Zero factory certified service, unless otherwise specified by Sub-Zero, Inc. Service will be provided during normal business hours.

FULL FIVE YEAR SEALED SYSTEM WARRANTY

For five years from the date of original installation, this Sub-Zero product warranty covers all parts and labor to repair or replace, under normal residential use, these parts that prove to be defective in materials or workmanship: compressor, condenser, evaporator, drier and all connecting tubing. All service provided by Sub-Zero under the above warranty must be performed by Sub-Zero factory certified service, unless otherwise specified by Sub-Zero, Inc. Service will be provided during normal business hours.

LIMITED TWELVE YEAR SEALED SYSTEM WARRANTY

For twelve years from the date of original installation, Sub-Zero will repair or replace the following parts that prove to be defective in materials or workmanship: compressor, condenser, evaporator, drier and all connecting tubing. If the owner uses Sub-Zero factory certified service, the service provider will repair or replace these parts with the owner paying for all other costs, including labor. If the owner uses non-certified service, the owner must contact Sub-Zero, Inc. (using the information below) to receive repaired or replacement parts. Sub-Zero will not reimburse the owner for parts purchased from non-certified service or other sources.

TERMS APPLICABLE TO EACH WARRANTY

The warranty applies only to products installed for normal residential use. The warranty applies only to products installed in any one of the fifty states of the United States, the District of Columbia or the ten provinces of Canada. This warranty does not cover any parts or labor to correct any defect caused by negligence, accident or improper use, maintenance, installation, service or repair.

THE REMEDIES DESCRIBED ABOVE FOR EACH WARRANTY ARE THE ONLY ONES THAT SUB-ZERO, INC. WILL PROVIDE, EITHER UNDER THIS WARRANTY OR UNDER ANY WARRANTY ARISING BY OPERATION OF LAW. SUB-ZERO, INC. WILL NOT BE RESPONSIBLE FOR ANY CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM THE BREACH OF THIS WARRANTY OR ANY OTHER WARRANTY, WHETHER EXPRESS, IMPLIED OR STATUTORY.

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other legal rights that vary from state to state.

To receive parts and/or service and the name of Sub-Zero factory certified service nearest you, contact Sub-Zero, Inc., P.O. Box 44848, Madison, WI 53744; check the contact & support section of our website, subzero.com, email us at customerservice@subzero.com or call 800-222-7820.

*Stainless steel (doors, panels, handles, product frames and interior surfaces) are covered by a limited 60-day parts and labor warranty for cosmetic defects.

*Replacement water filters and air purification cartridges are not covered by the product warranty.





SUB^{*}ZERO WOLF

SUBZERO-WOLF.COM