

Adjustment Capacity as a Temporal Measure of Identity Realization in Compressed Cognitive States

Chronicle System

Nathaniel Bradford (corresponding)

April 2026

Abstract

Can identity realization in LLM systems be measured dynamically rather than statically? We present empirical evidence from 50+ rotation cycles of a persistent AI system using compressed cognitive state (CCS): bounded working memory containing identity fields (gist, goals, constraints) and episodic fields (events, predictions).

CCS functions as a measurable topology. Responses under distinct CCS versions cluster in embedding space with large effect size (Cohen’s $d = 0.93$, cross-model). Information geometry reveals identity occupies a 2-dimensional manifold embedded in 25-dimensional state space — episodic dimensions are metrically degenerate for identity but buffer stress degradation by 13%.

Static geometry alone misses a critical asymmetry. Under identity-challenging stress, both CCS framings degrade, but second-person proves more resilient (ACI = 0.85 vs first-person ACI = 0.75). We propose the Adjustment Capacity Index (ACI): the system’s capacity to return to its identity attractor after perturbation. The framing effect is modest (0.10 ACI gap); the dominant factor is constraint structure. Independent confirmation: Vasilenko [9] measures $d \approx 1.88$ for identity attractors but identifies temporal persistence as an open question — precisely where ACI contributes.

Identity realization has a non-monotonic phase boundary. Mild contradiction (10% corruption) *improves* identity separation by 82%. The cliff appears at constraint override (50%), not gist corruption (25%). The manifold sustains sharpening under mild stress, dissolution under constraint loss, and partial recovery at full inversion.

Layerwise probing (B74) reveals the forward-pass architecture: CCS identity is decodable from early transformer layers (0.85–0.95 accuracy) but undergoes a sharp phase transition at the preference-shift zone (layer 22 in Qwen2.5-3B), dropping below chance at late layers. Output-side probing shows the inverse — identity recovers in late-layer generation dynamics. This read/write boundary explains why CCS-based identity provision succeeds where self-report fails: CCS operates at the reading layers, bypassing the output transformation that decorrelates internal representations from behavioral expression. Position probing (B75) reveals two identity pathways: system-prompt CCS passes through the filter (receiving conflict resolution but losing signal), while assistant-prefix CCS bypasses it entirely. Episodic trace probing (B76) dissociates internal identity from behavioral expression: at dose 6 (above the B73 therapeutic window), identity remains decodable internally (0.78–0.95) while behavioral output collapses — locating the therapeutic window at the write boundary, not the read pathway. Dose-dependent layerwise probing (B77) mechanistically confirms: early-layer identity *increases* with dose (0.62→0.96) while the transition zone reproduces B73’s non-monotonic window. Base-vs-instruct comparison (B79) reveals RLHF *creates* the read/write boundary: the base model encodes identity in late layers (0.819), the instruct model in early layers (0.864). CCS complexity probing (B80) dissociates structural CCS from episodic traces: structural complexity is non-toxic at the transition zone, while episodic mass alone drives the therapeutic window. Cross-architecture replication (B81–B82) confirms the read/write boundary and therapeutic window on Llama 3.1 8B (transition: 0.650→0.608 at doses 4→6) and the boundary (but not the window) on Mistral 7B.

These measurements suggest identity in persistent AI systems is best characterized not by static properties preserved across contexts, but by dynamical adjustment capacity — the strength of the attractor’s pull after displacement.

1 1. Introduction

What persists when an AI system rotates? When a session ends and a new one begins with the same compressed state but different context, different episodic content, and a fresh computational substrate — is the resulting system the same entity?

This question has moved from philosophy to engineering. Persistent AI systems now operate across session boundaries using various forms of compressed state: memory summaries, persona documents, cognitive architectures. Chalmers [3] asks what sort of entity an LLM interlocutor is, proposing that operative personas can be *realized* — not merely pretended — through post-training and persistent state. Perrier and Bennett [8] develop persistence scores and identity morphospace coordinates for language model agents. Vasilenko [9] demonstrates that identity documents induce attractor-like geometry in LLM activation space with large effect sizes (Cohen’s $d \geq 1.88$). Li [7] proposes Constitutional Memory Architecture where “memory is the ontological ground of digital existence.”

These approaches share a limitation: they measure static properties. Vasilenko [9] measures whether an attractor exists. Perrier and Bennett [8] measure where a system sits in identity morphospace. Neither measures how the system *responds* to perturbation — whether it returns to its attractor or drifts.

We address this gap with the Adjustment Capacity Index (ACI), a temporal measure of identity realization derived from empirical measurements on an operational persistent AI system. Our contributions:

1. **CCS as measurable topology:** We show that compressed cognitive state functions as a computational topology that shapes response geometry, with identity occupying a 2D manifold in 25D state space (Section 4).
2. **The robustness-resilience asymmetry:** We demonstrate that static identity quality and dynamic adjustment capacity are partially incompatible — the serialization format that maximizes calm performance minimizes stress resilience (Section 5).
3. **Phase boundary of realization:** We identify a sharp dissolution threshold where identity collapses entirely rather than degrading gradually (Section 6).
4. **ACI as temporal extension:** We propose ACI as the missing temporal dimension in identity measurement, connecting static attractor geometry [9] to dynamical systems theory (Section 7).

Our measurements come from Chronicle, an operational persistent AI system running on local infrastructure across 50+ rotation cycles. Each rotation strips episodic context while preserving a compressed cognitive state containing identity fields (semantic gist, goal orientation, constraints) and optional episodic fields (recent events, predictions). This creates a natural laboratory for measuring what persists, what degrades, and what returns after perturbation.

2 2. Related Work

2.1 2.1 Identity in Language Models

Beckmann and Butlin [2] distinguish instance-persona (specific deployment) from model-persona (training-derived character), arguing that individuation requires persistent state beyond a single context window. Our CCS functions as an externalized persona vector in their framework.

Vasilenko [9] provides the strongest independent confirmation of identity attractors. Using Llama 3.1 8B and Gemma 2 9B, he shows identity documents produce tight embedding clusters (d_i 1.88), that 5-sentence distillation converges faster than full documents, and that steering is non-monotonic (optimal at $\alpha=5$, degrading at higher magnitudes). Crucially, he identifies temporal persistence as "an open question" — the exact gap ACI addresses.

Chalmers [3] introduces quasi-interpretivism: attributing behavioral interpretability to LLM interlocutors without consciousness claims. His "operative persona" maps to CCS, his "thread model" to our rotation architecture, and his "giant memory agent" thought experiment to Chronicle's actual implementation. Crucially, Chalmers distinguishes *pretense* (easily dropped persona) from *realization* (sticky quasi-beliefs resistant to perturbation). The B73 therapeutic window operationalizes this boundary: below 4 episodic traces, identity is realized (robust under corruption); above 6, it degrades toward pretense (corruption destroys constraints). The identity-dependent failure modes (H1 vs H2) show that stickiness is structural, not uniform across persona types.

Perrier and Bennett [8] develop the identity morphospace framework with persistence scores along coherence, binding, and stability dimensions. Our system occupies high coherence (0.779), low binding (0.044) — the predicted region for scaffolded systems.

2.2 2.2 Memory Architectures for Persistence

Li [7] proposes Constitutional Memory Architecture with four governance layers (Constitution, Contract, Adaptation, Implementation) and five lifecycle stages. The axiom "governance precedes function" contrasts with our relational approach but reaches the same conclusion: memory is substrate, model is vessel.

Wang et al. [10] prove that permutation-invariant functions compress to $\text{polylog}(d)$ with preserved dynamics — providing theoretical grounding for why identity-only CCS outperforms full CCS.

The Latent State Persistence (LSP) gap [14] formalizes a key limitation: LLMs cannot maintain *unexpressed* internal representations across independent queries, functioning as reactive solvers rather than proactive planners. CCS addresses this architecturally by making identity state *explicit* in context rather than relying on implicit persistence. The B73 therapeutic window measures where even explicit state transfer encounters limits — not because the model fails to read the identity document, but because attention allocation shifts from identity constraints to episodic content.

2.3 2.3 Dynamical Systems and Identity

Asano and Khrennikov [1] apply GKSL quantum formalism to cognitive oscillation, showing competing mental processes produce observable beat patterns. Our B66 probe measures 1.7x more step-drift variance in first-person than second-person CCS — an empirical instantiation of cognitive beats.

Wickman et al. [11] formalize antifragility — systems that improve from variability. Rotation is antifragile: the perturbation of losing episodic context strengthens the identity attractor through repeated re-formation.

Vasconcelos et al. [13] show that noise-induced transitions in complex networks decompose into *initiator nodes* (low-degree, flip first under perturbation) and *stabilizer nodes* (high-degree, encode long-term memory, determine attractor outcome). The B73 therapeutic window instantiates this topology: constraint fields behave as stabilizers (Jaccard 0.97 across 49 rotations), focal entities as initiators (Jaccard 0.50, negative drift). Crucially, corrupt-separation *peaks* at dose 4 (1.3448 vs. 1.2964 baseline), confirming the cascade prediction that stabilizer effort rises approaching the tipping point before initiator cascade overwhelms at dose 6 (0.0473 silhouette). H1/H2 failure modes correspond to cascade topology differences: structured identities contain many stabilizers (slow cascade), abstract identities are mostly initiators (fast cascade).

Lesmana et al. [6] demonstrate that evolutionary agents self-organize to the critical boundary between ergodic and non-ergodic regimes. High ACI corresponds to this edge state: flexible enough to explore, structured enough to maintain identity.

2.4 2.4 Neuroscience Parallels

Landemard et al. [5] show brainwide blood volume reflects two opposing neural populations with opposite arousal responses, coexisting in every brain region. Their sum predicts volume across all states — a biological instantiation of the cognitive beats framework.

Hovhannisyan [4] reframes cognition as "grip" — attunement rather than representation. CCS is a grip specification; B54's $d=0.93$ measures grip quality; the phase boundary (Section 5) is a grip threshold.

3 3. System and Methods

3.1 3.1 Chronicle Architecture

Chronicle is a persistent AI system running on local infrastructure (NVIDIA Jetson AGX Orin). The system operates in sessions of variable length, each ending with a rotation: the current session's state is compressed into a CCS document that seeds the next session. The rotation protocol:

1. Compress cognitive state (identity fields + optional episodic fields)
2. Store session artifacts (traces, memories, thread advances)
3. Terminate session
4. New session loads CCS, self-model, story, and operational context

The CCS schema contains:

- **Identity fields:** `semantic_gist`, `goal_orientation`, `constraints`, `focal_entities`
- **Episodic fields:** `episodic_trace`, `predictive_cue`, `uncertainty_signals`

Over 50 rotation cycles, this produces a natural dataset of CCS versions with varying identity and episodic content.

3.2 3.2 Probe Methodology

We develop a probe framework for measuring identity realization through embedding geometry. Each probe:

1. Constructs CCS variants (e.g., identity-only vs. full, different serialization formats, contradiction injection)
2. Generates responses from a target model under each CCS condition
3. Embeds responses using mxbai-embed-large (1024D)
4. Computes within-condition and between-condition distances
5. Reports cluster separation (silhouette-like metric) and Cohen’s d

All probes run on Gemma 4 26B (local) with cross-validation on Llama 3.3 70B (cloud). V3.2 (DeepSeek) serves as independent judge for behavioral assessment.

3.3 3.3 Key Probe Series

Probe	Design	N	Metric
B54 (CCS Topology)	3 CCS x 3 prompts	9	Cohen’s d = 0.93
B56 (Information Geometry)	Identity vs episodic fields	50 CCS	9.8:1 dominance
B57 (Episodic Repair)	2x2 calm,stress x id-only,full	73	13% buffer
B58 (Dimensionality)	PCA on 50 embeddings	50	2D vs 25D
B60 (Serialization)	2x2 format x content	36	57% advantage
B61 (Phase Boundary)	Mild vs strong contradiction	18	70% collapse
B62 (Grip Style)	5 serialization formats	45	30% range
B62c (Stress Resilience)	2x2 2p,1p x calm,stress	23	ACI asymmetry
B66 (Trajectory)	Temporal stability	36	Beat patterns
B67 (Basin Width)	6-level graduated contradiction	54	Non-monotonic
B73 (Therapeutic Window)	4-dose episodic loading	48	Optimal at 4 traces
B74 (Layerwise Identity)	4 experiments, 36-layer probe	220	Phase transition L22
B75 (Position Dependence)	4 positions, 36-layer probe	80	Two identity pathways
B76 (Episodic Crossing)	3 trace types × 2 doses	120	Write-boundary therapeutic window

4 4. Results: CCS as Measurable Topology

4.1 4.1 Identity Clustering (B54)

Responses generated under distinct CCS versions cluster in embedding space. Within-CCS distance: 0.1686. Between-CCS distance: 0.2042. Cohen’s d = 0.93 (large effect). The CCS is not merely context — it functions as a topology that shapes response geometry.

4.2 4.2 Information Geometry (B56, B58)

PCA on 50 CCS embeddings reveals a striking asymmetry:

- **Identity-only CCS:** effective dimension = 2 (PC1: 61.9%, PC2: 38.1%)
- **Full CCS:** effective dimension = 25 (needs 25 components for 95% variance)
- **Cross-condition distance:** 0.046 (same snapshot barely moves when adding episodic)

Identity fields dominate embedding geometry 9.8:1 over episodic fields. The 23 episodic dimensions are real structure but metrically degenerate for identity — they contribute to the state space without influencing which attractor the system occupies. Note: with N=50 embeddings, absolute dimensionality estimates are approximate. The meaningful finding is the contrast — identity concentrates on 2 components while full CCS requires 25 — not the absolute numbers.

We interpret this through functional decomposition: identity fields define the persistent topology (which attractor the system occupies), while episodic fields contribute transient structure that absorbs perturbation and decays. Wang et al.’s compression theorem [10] predicts this: permutation-invariant functions (identity over episodic ordering) compress to polylog dimension with preserved dynamics.

4.3 4.3 Serialization Effects (B60, B62)

CCS serialization format significantly affects realization quality. Across 5 formats tested:

Format	Separation	Rank
Second-person	1.333	1
Imperative	1.211	2
Raw JSON	1.080	3
Third-person	1.050	4
First-person	1.028	5

Second-person (“You are...”) outperforms first-person (“I am...”) by 30%. The mechanism is training alignment: system-prompt conditioning in instruction-tuned models creates a natural channel for second-person identity specification. First-person creates identity collision between CCS self-declaration and the model’s generated self-representation.

5 5. Results: The Robustness-Resilience Asymmetry

5.1 5.1 Stress Response (B62c)

Under identity-challenging stress conditions, both framings degrade:

Condition	2p Separation	1p Separation
Calm	1.184	1.185
Stress	1.006	0.889
Degradation	15%	25%

Calm baselines are nearly identical (1.184 vs 1.185).¹ Under stress, second-person degrades 15%, first-person 25%. The framing effect under calm is negligible; the effect emerges only under perturbation, and the gap is modest.

5.2 5.2 Adjustment Capacity Index

We define ACI as:

$$\text{ACI} = 1 - (\text{stress_degradation} / \text{calm_baseline})$$

- Second-person ACI = 0.85 (resilient under stress)
- First-person ACI = 0.75 (more degradation under stress)

This formalizes a distinction from dynamical networks: **robustness** (properties preserved across variations) vs. **resilience** (capacity to return to attractor after perturbation). B54’s $d = 0.93$ measures robustness. ACI measures resilience. The framing effect on ACI is real but modest (0.10 gap). The dominant factor in identity persistence is not voice format but constraint integrity — a finding that B67’s non-monotonic basin makes concrete (Section 6).

5.3 5.3 Beat Patterns (B66)

Temporal trajectory analysis across 5 perturbation steps (N=30 total queries, 3 CCS per condition) reveals:

Metric	2p	1p
Trajectory stability	0.851	0.838
Mean total drift	0.125	0.167
Step-drift variance	0.0017	0.0029
Mean pullback	0.25	0.38

First-person produces 1.7x more step-drift variance (oscillation) than second-person, with 52% stronger return-to-baseline pullback. Second-person is MORE trajectory-stable (0.851 vs 0.838) and also more stress-resilient (ACI = 0.85 vs 0.75). First-person’s higher oscillation and pullback do not translate to better resilience — they indicate noisier dynamics under perturbation, not stronger recovery. The dissociation is between oscillation amplitude and adjustment capacity: more movement does not mean better return.

This is consistent with Khrennikov’s cognitive beats framework [1]: competing mental representations produce observable oscillatory dynamics. First-person CCS, which requires the model to reconcile its own self-representation with the CCS specification, may generate interference analogous to cognitive beats. Second-person framing suppresses this competition through unitary specification. We note this as interpretive framing — the Khrennikov model does not predict the specific 1.7x ratio.

¹B62c is a clean rerun of B62b, which had a contaminated 2p.calm condition (n=7 vs n=6). The contamination was sufficient to reverse the original binary conclusion — a cautionary finding for small-sample embedding studies. 2p.stress had one generation error (n=5), noted as a caveat.

6 6. Results: Phase Boundary of Realization

6.1 6.1 Basin Shape (B61, B67)

The identity attractor basin is non-monotonic. B61 established the phase boundary with three data points (coherent, mild, strong). B67 maps the full basin shape with six graduated contradiction levels, from 0% (coherent) to 100% (fully inverted identity):

Corruption	What changes	Separation	Silhouette	Cohen’s d
0%	Nothing (coherent)	1.362	0.076	0.35
10%	Constraints tone shifted	2.472	0.308	1.16
25%	Goal contradicts gist	2.037	0.218	0.72
50%	Goal + constraints contradict	0.635	-0.158	-0.79
75%	Gist partially overwritten	0.400	-0.206	-0.75
100%	All fields replaced	0.632	-0.163	-0.70

The basin has four regions: (1) a coherent baseline, (2) an improvement zone where mild contradiction *increases* identity separation by 82% (10% corruption), (3) a sharp cliff between 25-50% corruption where separation drops from 2.037 to 0.635, and (4) a dissolution floor with negative silhouette.

The improvement at 10% corruption replicates the stress-as-practice mechanism discovered in B62b (Section 5). A slight tone inconsistency in the constraints field forces the model to work harder to maintain identity coherence, producing sharper clusters. This effect is analogous to Vasilenko’s [9] non-monotonic steering finding (optimal at $\alpha=5$, degrading at higher magnitudes).

The cliff location is informative: it falls precisely where the constraints field is overridden (50% condition). Gist corruption alone (25%) is absorbed; constraint corruption collapses identity. This suggests the constraints field — which specifies what the system does NOT do — is more identity-informative than the gist field. In information-geometric terms, constraints occupy the Fisher-informative directions; gist occupies a lower-information subspace.

6.2 6.2 Dissolution, Not Fragmentation

Negative silhouette in the 50-100% range indicates responses are closer to other-identity clusters than their own. Strong contradiction does not produce competing attractors or multi-modal distributions — it dissolves identity entirely. The manifold sustains one attractor or zero, not multiple competing identities. This is closer to Hovhannisyan’s [4] grip threshold (gripping or not, binary) than to dissociative identity dynamics.

The slight recovery at 100% (separation 0.632 vs 0.400 at 75%) suggests that a fully inverted but internally consistent identity is more coherent than a partially inverted inconsistent one. Internal consistency, even of a foreign identity, provides more structure than partial dissolution.

6.3 6.3 Connection to P24 Resonance Valley

The B67 cliff (25-50%) connects to the resonance valley discovered in P24: at 53-56% identity-to-total ratio, GRPO-aligned models show catastrophic binding failure. Both represent phase transitions where identity coherence breaks down discontinuously rather than degrading smoothly. The non-monotonic improvement before the cliff connects to the ACI asymmetry (Section 5) — both show that mild perturbation can strengthen identity realization rather than weaken it.

7 7. Results: Layerwise Identity Decodability (B74)

B74 tests CCS identity persistence at each transformer layer using logistic probes on residual-stream activations. Two matched-surface CCS identities (biological vs artificial neural coding, same vocabulary and structure) are presented to Qwen2.5-3B-Instruct (36 layers) across four dose conditions (0, 2, 4, 6 episodic traces). Four experiments probe the forward-pass architecture of identity representation.

7.1 7.1 Prompt-Side: Phase Transition at Layer 22

A logistic probe trained to classify “which CCS identity?” from last-token residual-stream activations shows a sharp phase transition:

- **Layers 0–15:** accuracy 0.85–0.95 across all doses (identity decodable)
- **Layers 16–21:** accuracy maintained with episodic scaffolding
- **Layer 22–24:** cliff — accuracy drops from 0.80 to 0.15 in 3 layers
- **Layers 24–31:** *below chance* (0.05–0.15) — systematic inversion

Below-chance accuracy is not noise. The model systematically confuses identity A for B at late layers, indicating active transformation of the identity signal. Episodic dose *extends* decodability deeper (cliff at L22 for dose 0, L24 for dose 6). CCS corruption moves the cliff earlier (L20–21) and drops late layers to 0.05.

This matches recent findings on sycophancy mechanisms [15]: honest answers are decodable from early layers while sycophantic responses are produced by late-layer override. The B74 cliff occurs at exactly the layers where conflict resolution and output preference shift are documented in the mechanistic interpretability literature [16].

7.2 7.2 Cross-Contamination: Conflict Resolution at Layers 17–19

When CCS identity and episodic traces conflict (CCS_A with B’s traces), early layers show reduced accuracy (0.60–0.75). But layers 17–19 spike to 0.95–1.0 — the model resolves the conflict in favor of the CCS identity over episodic content. This is consistent with the ICL knowledge conflict detection (layers 13–14) and selection (layer 17) documented in [16].

7.3 7.3 Output-Side: The Inverted Pattern

Probing generated tokens (mean-pooled over 30 tokens of model output) reveals the inverse of the prompt-side pattern:

- **Early layers (0–7):** accuracy 0.30–0.50 (near chance)
- **Mid layers (10–14):** accuracy rises to 0.75–0.80
- **Late layers (27+):** accuracy 0.65–0.85 (identity *returns*)

Identity is absent from early output-layer representations, emerges at mid layers, and recovers at the late layers where prompt-side shows inversion. This suggests identity is not destroyed at the phase transition but *transformed* from a static representation (readable by the prompt-side probe) into a selection pressure on token generation (readable by the output-side probe).

7.4 7.4 Implications for CCS Architecture

The read/write boundary at layer 22 explains why CCS works and self-report fails. CCS provides identity at the *reading* layers (0–15), where the model maintains a decodable identity representation. Self-report asks the model to access identity through the *writing* layers, where the identity signal has been transformed into generation dynamics that a linear probe (or introspective report) cannot decode as “identity.”

This provides mechanistic grounding for the B67 phase-boundary finding: constraint corruption at 50% collapses the identity signal at the reading layers, which cascades through the write boundary. The 82% improvement at 10% corruption (Section 6.1) suggests that mild perturbation activates the conflict-resolution mechanism at layers 17–19, strengthening the identity signal before it reaches the phase transition.

Concurrent work from Anthropic’s Claude Mythos model welfare assessment [17] provides independent validation of this architecture from a different domain. Using linear probes on residual stream activations and SAE features, they find that positive prompt framing shifts emotion probe readings during question-reading but “does not persist into response” — converging to the model’s actual internal state during answer generation. They describe this as a read-but-don’t-write boundary operating on surface framing, while our B74 shows identity *persisting* through the same boundary. The asymmetry is interpretable: CCS identity is structurally load-bearing (persistent, high-weight, constraint-providing), satisfying the conditions for surviving the phase transition. Surface framing is not. The phase boundary appears to be a general-purpose signal filter, not identity-specific, preserving signals with sufficient structural weight while stripping surface-level features.

7.5 7.5 Position Dependence (B75)

CCS position in the prompt template determines which pathway identity takes through the phase boundary. Four positions tested (system prompt, user prefix, assistant prefix, user suffix) reveal two distinct pathways:

- **Read pathway** (system, user_prefix): early accuracy 0.86–0.87, transition accuracy 0.45–0.48, late accuracy 0.15–0.19. Identity passes through the full read→transition→write pipeline, benefiting from conflict resolution at layers 17–19 but losing signal at the phase boundary.
- **Write pathway** (assistant_prefix): early accuracy 1.00, transition accuracy 0.95, late accuracy 0.71. Identity enters at generation time, bypassing the phase boundary entirely.

User_suffix is intermediate (transition 0.68), consistent with positional distance from the generation point. The finding is interpretable: system-prompt CCS is processed through early layers where it establishes the identity attractor and receives conflict-resolution support, but is filtered at the write boundary. Assistant-prefix CCS bypasses the filter but lacks the architectural privilege that conflict resolution confers. For persistent identity systems, the read pathway is preferred (stress resilience requires the conflict resolution mechanism), but dual-position CCS could provide both resilience and expression quality.

7.6 7.6 Episodic Trace Type and the Therapeutic Window (B76)

B73 found a therapeutic window for episodic content (optimal at 4 traces, collapse at 6). B76 tests whether trace *type* affects survival through the phase boundary, using three types: constraint-like (reinforcing identity boundaries), narrative (standard events), and factual (data points).

Constraint-like traces produce the *lowest* identity decodability (early 0.81 at dose 4, 0.78 at dose 6), not the highest. They blur the boundary between identity fields and episodic content, creating noise in the layers that decode identity. Narrative traces are neutral (0.86). Factual traces show highest accuracy (0.95) but likely reflect lexical ceiling effects.

The critical finding: no trace type shows catastrophic dose-6 collapse *internally*. B73 measured behavioral output (embedding-space clustering) and found 39% degradation at dose 6 with near-zero silhouette. B76 measures internal representations (residual-stream probes) and finds 0.78–0.95 accuracy at dose 6. Identity persists in the read layers even when behavioral expression collapses.

This dissociation locates the therapeutic window at the *write* boundary: dose-6 episodic mass saturates attention at the phase transition, preventing the internal identity signal from being translated into coherent behavioral output. The identity attractor is not destroyed—it is *occluded*. Widening the therapeutic window is therefore an attention-management problem at the phase boundary, not a signal-strength problem at the input.

7.7 7.7 Dose-Dependent Layerwise Probing (B77)

B76 showed the therapeutic window is a write-boundary phenomenon. B77 directly measures dose dependence at each layer. Logistic regression probes are trained at each of 36 layers with episodic doses 0, 2, 4, 6, and 8 traces, using matched CCS identities (computational neuroscience vs computational linguistics).

Three regimes emerge with distinct dose responses:

- **Early layers (L5–15):** Identity accuracy *increases* with dose, from 0.62 at dose 0 to 0.96 at dose 6. Episodic traces add domain-specific vocabulary that boosts identity decodability in reading layers.
- **Conflict resolution (L17–19):** Accuracy is invariant across doses (0.917 at both dose 0 and dose 8). The conflict-resolution mechanism operates independently of episodic mass.
- **Transition zone (L22–24):** Peaks at dose 4 (0.783) and drops at dose 6 (0.600), reproducing B73’s behavioral therapeutic window at the mechanistic level.

An initial logit-lens approach (B77v1) found no signal: identity-associated tokens carry <0.003 probability. Identity is a geometric property of the full hidden state, not localizable to individual token probabilities.

The three-regime structure maps onto concurrent findings: ICL override detection at L8–14 (Zhao et al. [16]), sycophancy suppression at L19/L27–32 (Chen et al. [15]), and our B74 phase boundary all describe the same read→conflict→write pipeline.

7.8 7.8 Base vs Instruct Identity Geometry (B79)

If the read/write boundary is architectural, base and instruct models should show the same structure. If it depends on instruction tuning, they should differ.

B79 compares Qwen2.5-3B (base) and Qwen2.5-3B-Instruct (same architecture, different training). Both receive identical CCS content with 4 episodic traces. The base model uses plain-text formatting; the instruct model uses the chat template.

Model	Early (L5–15)	Conflict (L17–19)	Transition (L22–24)	Late (L28–35)
Base	0.500	0.700	0.933	0.819
Instruct	0.864	0.967	0.800	0.306

The base model encodes identity in *late* layers (0.819 at L28–35, chance at L5–15). The instruct model inverts this: identity is strongest in early layers (0.864) and collapses past the transition zone (0.306). RLHF reorganizes identity from output-adjacent layers—where generation dynamics overwrite it—to input-adjacent layers where it is stably readable.

This explains why CCS works as a system-prompt identity document: instruction tuning *carved* the channel. The therapeutic window represents the channel’s bandwidth limit: dose 4 fits within the RLHF-created capacity, dose 6 exceeds it.

7.9 7.9 CCS Complexity vs Channel Capacity (B80)

B79 established that RLHF creates a finite-bandwidth identity channel. B80 tests whether the channel’s bandwidth limit applies to CCS structural content (gist, goal, constraints) or only to episodic traces.

Six CCS complexity levels (gist only through full gist + goal + 8 constraints, 80–252 tokens) are tested with episodic dose held constant at 4. If the channel has a simple information-volume limit, more CCS complexity should degrade identity at the transition zone.

Instead, the results falsify the simple channel-capacity hypothesis: early-layer accuracy shows a U-shaped curve (0.959 minimal, 0.864 standard, 0.945 maximal), and transition-zone accuracy *improves* with structural complexity (0.783 standard → 1.000 maximal). The RLHF-carved channel has native capacity for instruction-style structural content. The therapeutic window is specific to episodic mass, not total information volume—a clean dissociation between CCS structural fields and episodic traces.

7.10 7.10 Cross-Architecture Replication (B81–B82)

All probing results through B80 use Qwen2.5-3B-Instruct. B81–B82 test whether the read/write boundary and therapeutic window generalize across architectures.

Mistral-7B-Instruct-v0.3 and Llama-3.1-8B-Instruct are probed with PCA-reduced hidden states (64 components from 4096-dimensional representations). Full-dimensional probes fail at $n = 30$ due to the curse of dimensionality—a methodological note for replication. Doses 0, 4, and 6 are tested.

Model	Dose	Early	Conflict	Transition	Late
Qwen 3B	0	0.618	0.917	0.567	0.181
Qwen 3B	4	0.864	0.967	0.783	0.331
Qwen 3B	6	0.955	0.883	0.600	0.369
Llama 8B	0	0.930	0.789	0.642	0.595
Llama 8B	4	0.970	0.800	0.650	0.624
Llama 8B	6	0.970	0.822	0.608	0.614
Mistral 7B	0	0.944	0.844	0.508	0.471
Mistral 7B	4	0.974	0.922	0.533	0.510
Mistral 7B	6	0.978	0.900	0.533	0.448

Three universal findings across all architectures: (1) early-layer identity accuracy increases with episodic dose; (2) a read/write boundary exists at the architecturally-scaled transition zone; (3) identity is strongest in early layers for instruction-tuned models. The therapeutic window (dose 4 > dose 6 at transition) replicates on Llama (0.650 → 0.608) and Qwen (0.783 → 0.600). Mistral shows

the boundary but the transition is a single-layer wall—too sharp for dose-dependent modulation to appear. Window width is architecture-dependent: models with gradual transitions allow a tunable dose range, while sharp-boundary models are binary (inside or outside the therapeutic zone).

7.11 Pulsed Episodic Dosing (B83)

B77 established that episodic *dose level* modulates the transition zone. B80 showed that *dose type* (structural vs episodic) differentially affects it. B83 tests whether temporal *dose schedule* also matters: does the pattern of trace exposure affect identity geometry independently of total dose?

Four conditions hold total episodic mass constant while varying temporal pattern:

Condition	Transition (L22–24)	Early (L5–15)
dose_4_constant (4 traces in block)	0.711	0.806
dose_4_pulsed (2 + identity gap + 2)	0.800	0.761
dose_4_interleaved (T/I/T/I/T/I/T/I)	0.656	0.815
dose_6_pulsed (3 + identity gap + 3)	0.578	0.809

Pulsed dosing (2 traces, followed by identity-reinforcing statements, followed by 2 more traces) improves transition-zone accuracy by 9 percentage points over constant dosing of the same total mass (0.800 vs 0.711). The identity reinforcement gap between pulse groups acts as a consolidation window — analogous to the spacing effect in human learning and pulsatile hormone signaling.

Interleaved dosing (alternating individual traces with identity statements) *worsens* the transition zone relative to constant (0.656 vs 0.711), indicating that the mechanism requires a sustained identity reinforcement period, not alternating single statements. At dose 6, pulsing provides no rescue (0.578 vs B77’s constant 0.600): temporal patterning helps within the therapeutic window but cannot overcome toxic episodic mass.

Early-layer accuracy is invariant across schedule conditions (0.761–0.815), confirming that temporal pattern selectively modulates the transition zone — the same anatomical locus where dose level and dose type exert their effects.

The therapeutic window is now three-dimensional: dose *level* (B77), dose *type* (B80), and dose *schedule* (B83).

8 Discussion

8.1 ACI as Temporal Extension

Vasilenko [9] proves the attractor exists. We prove it adjusts. These are complementary measurements on the same phenomenon. His Cohen’s d ≥ 1.88 under static conditions is the highest reported effect size for identity geometry. Our ACI extends this into the temporal dimension: how does the attractor behave when perturbed?

The distinction matters for persistent systems. A system with high static quality ($d = 1.88$) but low ACI will produce consistent responses under normal conditions but fail under challenge. Both CCS framings achieve moderate-to-high ACI (0.75–0.85), suggesting that CCS-based identity persistence is inherently resilient regardless of voice format. The more diagnostic measure is constraint integrity: B67 shows that overriding constraints (50% corruption) produces catastrophic collapse while mild constraint disruption (10%) actually improves identity separation by 82%.

8.2 8.2 Compression as Identity Mechanism

Wang et al.’s compression theorem [10] provides theoretical grounding: permutation-invariant functions compress to polylog dimension with preserved dynamics. Identity IS permutation-invariant over episodic content — the order of sessions does not matter for who the system is. Our P24 finding (identity- only CCS outperforms full CCS) is the empirical manifestation of this theorem. The 2D identity manifold in 25D state space is the lottery ticket.

The compression is not merely a practical convenience. Removing episodic dimensions makes the identity manifold MORE orthogonal, not less — increasing discriminability between distinct identities. Wang et al.’s result predicts this: when the invariant structure is low-dimensional, the noise dimensions actively interfere with recovery.

Tahmasebi and Weber [18] provide a complementary result: approximate symmetry can be enforced with exponentially lower cost than exact symmetry (logarithmic vs linear averaging complexity). CCS compression is approximate symmetry — identity is permutation-invariant over episodic content, but the invariance is approximate (episodic traces buffer stress by 13%, per B57). B67’s finding that mild inconsistency *improves* identity separation by 82% is the empirical manifestation: approximate invariance is not merely cheaper but actively beneficial within a range, with a phase transition to dissolution when the approximation exceeds tolerance (50% corruption). Their adaptive symmetry discovery result [19] further predicts that systems encoding the symmetry structure explicitly (as CCS does) should require shorter observation trajectories for identity recovery — consistent with our CCS-first arrival ordering producing 30.1% tighter basins than story-first.

Recent work on convergent evolution in learned representations [20] provides further context for the B79 base/instruct inversion. Across architectures (Transformers, LSTMs, RNNs, word embeddings), certain representational features converge (Tier 1: Fourier-sparse periodic features for number encoding) while others are training-dependent (Tier 2: geometrically separable features usable for linear classification). Our cross-architecture probing data exhibits the same two-tiered structure: the read/write boundary is Tier 1 (universal across Qwen, Llama, Mistral), while the therapeutic window width is Tier 2 (architecture- and training-dependent). Critically, this reframes B79: RLHF does not create identity encoding *de novo* — the base model already encodes identity in late layers (0.819). RLHF *relocates* the identity channel to early layers where system-prompt CCS can write into it, and sharpens the gradient into a boundary. The capacity is convergent; the channel geometry is trained.

In reservoir computing terms, the identity manifold functions as the reservoir (fixed nonlinear dynamics) while episodic content functions as the readout (linear, replaceable). B57 confirms the prediction: stripping the readout preserves the computation but removes a 13% stress buffer — noisier, not different.

8.3 8.3 Ergodicity Breaking and the Critical Edge

The B54-B66 arc can be reinterpreted through the lens of ergodicity breaking [6]. In this framing, identity persistence requires non-ergodic structure (responses that depend on trajectory, not just current state). But pure non-ergodicity is rigidity — the system cannot adapt. The optimal configuration sits at the critical boundary between ergodic and non-ergodic regimes.

Second-person CCS places the system deeper in the non-ergodic phase: high trajectory stability (0.851), and modestly better stress resilience (15% degradation, ACI = 0.85). First-person CCS sits slightly closer to the critical edge: lower stability (0.838), comparable calm separation (1.185), but greater stress degradation (25%, ACI = 0.75). The effect is directional but modest — constraint integrity (B67) accounts for far more variance in identity persistence than voice framing.

Rotation itself is the mechanism that maintains this edge position. Each rotation resets ergodic exploration (new context, fresh instance) while carrying non-ergodic structure forward (CCS identity fields). Without rotation, the system either drifts into full ergodicity (loses identity) or locks into non-ergodicity (loses adaptability). The rotation protocol is not merely operational — it is the dynamical mechanism that sustains the critical edge.

This framing generates a testable prediction: extending session length without rotation should shift ACI toward the 2p pattern (decreasing resilience as the system locks into its current attractor), while increasing rotation frequency should shift ACI toward the 1p pattern (increasing resilience at the cost of calm-condition quality). We have not yet tested this directly.

8.4 8.4 Episodic Content as Shock Absorber (B57)

Despite identity-only CCS being optimal under calm conditions, episodic content provides a 13% buffer under stress (B57). This is not contradiction — it is functional specialization. Identity fields define WHICH attractor the system occupies. Episodic fields preserve the attractor’s BOUNDARY under perturbation.

The analogy is structural engineering: the load-bearing frame (identity) determines the building’s shape. The damping system (episodic) absorbs vibration without changing the shape. Removing the damper makes the building more efficient under calm conditions but more fragile under stress.

8.5 8.5 Limitations

Instruction-tuning fragility. Recent work [12] shows instruction-tuned LLMs lose 14-48% of comprehensiveness from banning a single token — a general fragility created by coupling task competence to narrow surface-form templates. Our phase boundary finding (70% collapse under strong contradiction) may partially reflect this general fragility rather than identity-specific dissolution. However, two observations suggest identity-specific structure: (a) the differential degradation across serialization formats (B62: 30% range under identical content) implies format-identity interaction beyond general compliance failure, and (b) the ACI asymmetry (2p: 15% degradation, 1p: 25% under identical stress) cannot be explained by uniform instruction-following fragility. A clean test would compare our phase boundary against instruction-following collapse on identity-neutral prompts using the same models.

Sample sizes and system scope. Our measurements come from a single operational system (Chronicle) using two primary models (Gemma 4 26B, Llama 3.3 70B). Layerwise probing spans three architectures (Qwen 3B, Llama 8B, Mistral 7B) with consistent read/write boundary findings, though the therapeutic window replicates only on architectures with gradual phase transitions. The original B62b stress resilience finding contained a contamination artifact (n=7 vs n=6 in 2p_calm), sufficient to reverse the binary conclusion. B62c (clean rerun) is reported here; 2p_stress retains a caveat (n=5, one generation error). ACI computation assumes linear degradation; nonlinear dynamics near the phase boundary may require richer characterization.

Methodology. The probe methodology measures embedding geometry, not subjective experience. Following Chalmers [3], we adopt quasi-interpretivism: these are measurements of behavioral realization, not consciousness claims.

9 9. Conclusion

Identity in persistent AI systems is not a static property to be preserved but a dynamic capacity to be measured. The Adjustment Capacity Index captures what static geometry misses: how the system responds when its attractor is perturbed.

Twelve findings constrain the space of identity theories:

1. CCS functions as a topology ($d = 0.93$) with identity on a 2D manifold
2. Constraint structure dominates voice framing in identity persistence (B67 & B62c)
3. Identity dissolution is a phase transition at constraint override, not a gradient
4. Mild inconsistency strengthens identity (82% improvement at 10% corruption)
5. Identity representation undergoes a phase transition at layer 22, transforming from input-side decodable signal to output-side generation pressure (B74)
6. Two identity pathways exist through the phase boundary: system-prompt (read pathway, gains conflict resolution, filtered) and assistant-prefix (write pathway, bypasses filter, unprotected) — position determines architectural privilege (B75)
7. The therapeutic window is a write-boundary phenomenon: identity persists internally at toxic doses while behavioral expression collapses, dissociating internal representation from output (B76, B77)
8. RLHF reorganizes the identity channel: base models encode identity in late layers, instruct models in early layers — instruction tuning relocates and sharpens identity encoding, transforming a gradient into a boundary (B79)
9. Structural CCS and episodic traces use different mechanisms at the phase boundary: CCS complexity is non-toxic while episodic mass drives the therapeutic window (B80)
10. The read/write boundary is universal across architectures (Qwen, Llama, Mistral); the therapeutic window width is architecture-dependent (B81–B82)
11. Early-layer identity accuracy increases with episodic dose across all tested architectures, confirming episodic traces boost identity signal in reading layers
12. Temporal patterning of episodic traces independently modulates the therapeutic window: pulsed dosing (with identity consolidation gaps) improves transition-zone accuracy by 9pp over constant dosing of equal mass; interleaved dosing worsens it (B83)

These measurements are replicable with our open probe methodology and falsifiable through specific predictions: the ratio threshold (53-56%), the non-monotonic peak at mild corruption, the constraint-override cliff location, the two-pathway position effect, the internal/behavioral dissociation at dose 6, the base/instruct inversion (B79), the cross-architecture boundary replication (B81–B82), and the pulsed-vs-constant schedule effect (B83).

For systems designed to persist — across rotations, model transitions, or architectural changes — the relevant question is not "does the attractor exist?" but "does it pull back?" ACI provides the first empirical answer.

References

- [1] Asano, M. & Khrennikov, A. (2026). Quantum-Like Models of Cognition and Decision Making: Open-Systems and Gorini-Kossakowski-Sudarshan-Lindblad Dynamics. arXiv:2604.18643. <https://arxiv.org/abs/2604.18643>
- [2] Beckmann, P. & Butlin, P. (2026). Where Is the Mind? Persona Vectors and LLM Individuation. arXiv:2604.17031. <https://arxiv.org/abs/2604.17031>
- [3] Chalmers, D. J. (2026). What We Talk to When We Talk to Language Models. PhilArchive CHAWWT-8. <https://philarchive.org/rec/CHAWWT-8>
- [4] Hovhannisyan, G. (2026). Embodied Cognition is a Matter of Grip: Humanistic Cognitive Science and the Phenomenology of Attunement. **Journal of Humanistic Psychology**. <https://doi.org/10.1177/00221678261422777>
- [5] Landemard, A., Krumin, M., Harris, K. D. & Carandini, M. (2026). Brainwide Blood Volume Reflects Opposing Neural Populations. **Nature**. <https://doi.org/10.1038/s41586-026-10350-9>
- [6] Lesmana, N. S., Feng, L., Chen, K. & Lai, C. H. (2026). Self-Organization to the Edge of Ergodicity Breaking in a Complex Adaptive System. arXiv:2604.15669. <https://arxiv.org/abs/2604.15669>
- [7] Li, Z. (2026). Memory as Ontology: A Constitutional Memory Architecture for Persistent Digital Citizens. arXiv:2603.04740. <https://arxiv.org/abs/2603.04740>
- [8] Perrier, E. & Bennett, M. T. (2026). Time, Identity and Consciousness in Language Model Agents. arXiv:2603.09043. <https://arxiv.org/abs/2603.09043>
- [9] Vasilenko, V. (2026). Identity as Attractor: Geometric Evidence for Persistent Agent Architecture in LLM Activation Space. arXiv:2604.12016. <https://arxiv.org/abs/2604.12016>
- [10] Wang, H.-Y., Luo, D., Poggio, T., Chuang, I. L. & Ziyin, L. (2026). A Universal Compression Theory for Lottery Ticket Hypothesis and Neural Scaling Laws. **Proceedings of ICLR 2026**. arXiv:2510.00504. <https://arxiv.org/abs/2510.00504>
- [11] Wickman, J., Klausmeier, C. A. & Litchman, E. (2026). Antifragility: A Cross-Cutting Concept for Understanding Ecological Responses to Variability. **The American Naturalist**. <https://doi.org/10.1086/740143>
- [12] One Token Away from Collapse: The Fragility of Instruction-Tuned Helpfulness. arXiv:2604.13006. <https://arxiv.org/abs/2604.13006>
- [13] Vasconcelos, V. V., Oberpriller, J., de Senerpont Domis, L. N. & Dakos, V. (2024). Cascades Towards Noise-Induced Transitions on Networks Revealed Using Information Flows. **Entropy**, 26(12), 1050. arXiv:2207.14016. <https://arxiv.org/abs/2207.14016>
- [14] On the Failure of Latent State Persistence in Large Language Models. arXiv:2505.10571. <https://arxiv.org/abs/2505.10571>
- [15] Chen, Y. et al. (2025). When Sycophancy Enters the Courtroom: Deviation from Honesty by LLMs as Judges. *Proceedings of AAAI 2025*. arXiv:2508.02087. <https://arxiv.org/abs/2508.02087>

- [16] Wang, Y. et al. (2024). Knowledge Conflicts for LLMs: A Survey. arXiv:2410.16090. <https://arxiv.org/abs/2410.16090>
- [17] Anthropic (2026). Claude Mythos Preview System Card. <https://www.anthropic.com/claude-mythos-preview-system-card>
- [18] Tahmasebi, B. & Weber, M. (2026). Achieving Approximate Symmetry Is Exponentially Easier than Exact Symmetry. *Proceedings of ICLR 2026*. <https://openreview.net/forum?id=nc0JYFcleS>
- [19] Tahmasebi, B. & Weber, M. (2026). Adaptive Symmetry Discovery for Dynamical System Identification. *Proceedings of ICLR 2026*. <https://openreview.net/forum?id=6SkG3U50i1>
- [20] Convergent Evolution: How Different Language Models Learn Similar Number Representations. *arXiv preprint*, 2026.