

Application Module Forms

AM88-600

Implementation

Configuration Forms

Application Module Forms

AM88-600
Release 681
09/08

This document was last updated for R681.
For information about those parameters introduced post R681,
refer to the PM Family Parameter Reference Dictionary.

Notices and Trademarks

**Copyright 2002 – 2008 by Honeywell International
Revision 4, September 2008**

While this information is presented in good faith and believed to be accurate, Honeywell disclaims the implied warranties of merchantability and fitness for a particular purpose and makes no express warranties except as may be stated in its written agreement with and for its customers.

In no event is Honeywell liable to anyone for any indirect, special or consequential damages. The information and specifications in this document are subject to change without notice.

Honeywell and **TotalPlant** are registered trademarks of Honeywell International Inc.

Other brand or product names are trademarks of their respective owners.

Honeywell International
Process Solutions
2500 West Union Hills Drive
Phoenix, AZ 85027
1-800 343-0228

About This Publication

This publication supports **TotalPlant** Solution (TPS) system network Release 681. TPS is the evolution of TDC 3000^X.

This manual consists of configuration forms. These forms are designed to facilitate the collection and organization of data for subsequent entry into the TPS system through the Universal Station.

The date (month/year) at the top of each form is changed only on those forms affected by the current document version.

Support and Other Contacts

Location	Organization	Address	Phone/Facsimile
United States and Canada	Honeywell Solution Support Center	Honeywell TAC, MS P13, 2500 West Union Hills Drive, Phoenix, AZ, 85027	Phone: 1-800 822-7673 602- 313-5558 (In Arizona) Facsimile: (602) 313-3293
Note: Calls are answered by dispatcher between 6:00 A.M. and 4:00 P.M. Mountain Standard Time. Emergency calls outside normal working hours are received by an answering service and returned within one hour.			
Europe	Honeywell TAC-EMEA	TAC-BE02 Hermes Plaza Hermeslaan, 1HB-1831 Diegem, Belgium	Phone: +32-2-728-2732 Facsimile: +32-2-728-2696
Pacific	Honeywell Global TAC – Pacific	Honeywell Limited Australia 5 Kitchener Way Burswood 6100, Western Australia Email: GTAC@honeywell.com	Phone: 1300-300-4822 (toll free within Australia) +61-8-9362-9559 (outside Australia) Facsimile: +61-8-9362-9564
India	Honeywell Global TAC – India	Honeywell Automation India Ltd. 56 and 57, Hadapsar Industrial Estate Hadapsar, Pune –411 013, India Email: Global-TAC- India@honeywell.com	Phone: +91-20- 66039400 Facsimile: +91-20- 66039800
Korea	Honeywell Global TAC – Korea	Honeywell Co., Ltd 17F, Kikje Center B/D, 191, Hangangro-2Ga Yongsan-gu, Seoul, 140- 702, Korea Email: Global-TAC- Korea@honeywell.com	Phone: +82-2-799-6317 +82-11-9227-6324 Facsimile: +82-2-792-9015

Support and Other Contacts

Location	Organization	Address	Phone/Facsimile
People's Republic of China	Honeywell Global TAC – China	Honeywell (China) Co., Ltd 33/F, Tower A, City Center, 100 Zunyi Rd., Shanghai 200051, People's Republic of China Email: Global-TAC-China@honeywell.com	Phone: +86- 21-52574568
Singapore	Global TAC – South East Asia	Honeywell Private Limited Honeywell Building 17, Changi Business Park Central 1, Singapore 486073 Email: GTAC-SEA@honeywell.com	Phone: +65-6580-3500 Facsimile: +65-6580-3501 +65-6445-3033
Taiwan	Global TAC – Taiwan	Honeywell Taiwan Ltd. 17F-1, No. 260, Jhongshan 2nd Road. Cianjhen District Kaohsiung, Taiwan, ROC Email: Global-TAC-Taiwan@honeywell.com	Phone: +886- 7- 536 2567 Facsimile: +886-7-536 2039
Japan	Global TAC – Japan	Honeywell Japan Inc. New Pier Takeshiba, South Tower Building, 20th Floor, 1-16-1 Kaigan, Minato-ku, Tokyo 105-0022, Japan Email: Global-TAC-JapanJA25@honeywell.com	Phone: +81-3-6730-7160 Facsimile: +81-3-6730-7228
Elsewhere	Call your nearest Honeywell office.		
World Wide Web	Honeywell Solution Support Online: http://www.honeywell.com/ps		
Training Classes	Honeywell Automation College: http://www.automationcollege.com		

Form Name	Form Number
REGULATORY DATA POINT FORMS (Set 1)	
Regulatory Point Configuration (Assignment, Algo Selection, Scheduling)	AM88-601
Regulatory Process Variable (PV) Algorithm (PV Common)	AM88-602
Data Acquisition	AM88-611
Flow Compensation	AM88-612
Middle of Three	AM88-613
Hi/Lo Average	AM88-614
Summer	AM88-615
Multiply/Divide	AM88-616
Sum of Products	AM88-617
VDT with Lead/Lag	AM88-618
Totalizer	AM88-619
General Linearization	AM88-620
Calculator	AM88-621
Regulatory Control (CTL) Algorithms (Common and Set Point)	AM88-641
PID	AM88-651
Lead/Lag	AM88-652
Summer	AM88-653
Multiply/Divide	AM88-654
PID with External Reset Feedback	AM88-655
PID with Feedforward	AM88-656
Incremental Summer	AM88-657
Auto/Manual	AM88-658
Ratio	AM88-659
Override Selector	AM88-661
Switch	AM88-662
Ramp Soak	AM88-663
CL	AM88-664
Regulatory Alarming and Distribution	AM88-670
General Input/Output Connections and Custom Data Segments	AM88-680
NONREGULATORY DATA POINT FORMS (Set 2)	
Flag	AM88-610
Numeric	AM88-620A
Timer	AM88-630
Counter	AM88-640
Switch	AM88-650
Custom	AM88-660

AM REGULATORY POINT CONFIGURATION

AM88-601
Page 1 of 2
12/02

• AM - REGULATORY ASSIGNMENT DISPLAY

10.	TAG NAME (NAME)	
11.	UNIT ID (UNIT)	
12.	POINT DESCRIPTOR (PTDESC)	
13.	ENGR UNITS DESCRIPTOR (EUDESC)	
14.	POINT KEYWORD (KEYWORD)	
15.	POINT ASSOCDSP (ASSOCDSP)	
15A.	POINT CUSTOM DISPLAY (\$CDETAIL)	Default = All Blanks
16.	PRIMARY MODULE POINT ID (PRIMMOD)	
17.	POINT DISCLOSURE (PTDISCL)	BRIEF FULL

• AM -REGULATORY ALGORITHM SELECTION DISPLAY

PV AND CONTROL ALGORITHMS

20.**	PV ALGORITHM (PVALGID)	NULL	DATAACQ	FLOWCOMP	MIDOF3
		HILOAVG	SUMMER	MULDIV	SUMPROD
		VDTLDLAG	TOTALIZER	GENLIN	CALCULTR
		CL			
21.**	CONTROL ALGORITHM (CTLALGID)	NULL	PID	PIDERFB	
		INCRSUM	LEA`DLAG	AUTOMAN	SUMMER
		MULDIV	RATIOCTL	ORSEL	SWITCH
		RAMPSOAK	CL		

US DISPLAY OPTIONS

22.	OVERVIEW VALUE (OVERVAL)	2 5
23.	1/0 DISPLAY SUPPRESSION (SUPPIO)	NOSUPPR INPSUPPR OUTSUPPR

AM REGULATORY POINT CONFIGURATION

AM88-601
Page 2 of 2
12/02

• AM – SCHEDULING ASSIGNMENT DISPLAY

30.**	POINT ASSIGNED TO IPP (\$IPPASN)	ON	OFF		
31.A.***	POINT EXECUTION PERIOD (PERIOD) (\$IPPASN = OFF)	1 SEC	2 SEC	5 SEC	10 SEC
		15 SEC	30 SEC	1 MIN	2 MIN
		1S MIN	2S MIN	5 MIN	10 MIN
		15 MIN	30 MIN	1 HR	8 HR
		12 HR	24 HR	NOPERIOD	
31.B.***	POINT EXECUTION PERIOD (PERIOD) (\$IPPASN = ON)	5 SEC	10 SEC	15 SEC	30 SEC
		1 MIN	2 MIN	5 MIN	10 MIN
		15 MIN	30 MIN	1 HR	8 HR
		12 HR	24 HR	NOPERIOD	
32.***	BEFORE/AFTER/CYCLE OPTION (BEFAFT)	NO	BEFORE**	AFTER**	CYCLE**
33.***	TAG NAME OF BEFORE/AFTER (BEFAFTID)				
34.***	ABSOLUTE CYCLE NUMBER (NORMCYCL)				
34.A.***	ROLLING AVERAGE BUFFER (\$ROLLBUF)	1			
34.B.***	ROLLING AVERAGE BUFF BASE (\$ROLLBBS)	SEC	MIN	HR	
34.C.***	ROLLING AVERAGE FREQUENCY (\$ROLLFRQ)	1			
34.D.***	ROLLING AVERAGE FRQ BASE (\$ROLLFBS)	SEC	MIN	HR	

• AM – REGULATORY PV COMMON DISPLAY

1.	PV DECIMAL PLACE FORMAT (PVFORMAT)	D0	D1	D2	D3						
		D4	D5	D6							
2.	PV RANGE HIGH (PVEUHI)	<table><tr><td>1</td><td>0</td><td>0</td><td>.</td><td>0</td></tr></table>				1	0	0	.	0	
1	0	0	.	0							
3.	PV RANGE LOW (PVEULO)	<table><tr><td>0</td><td>.</td><td>0</td><td></td><td></td></tr></table>				0	.	0			
0	.	0									
4.	PV RANGE EXTENSION HIGH(PVEXEUHI)	<table><tr><td>1</td><td>0</td><td>2</td><td>.</td><td>9</td></tr></table>				1	0	2	.	9	
1	0	2	.	9							
5.	PV RANGE EXTENSION LOW (PVEXEULO)	<table><tr><td>-</td><td>2</td><td>.</td><td>9</td><td></td></tr></table>				-	2	.	9		
-	2	.	9								
6.	PV CLAMPING OPTION (PVCLAMP)	CLAMP	NOCLAMP								
7.**	PV SOURCE OPTION (PVSRCOPT)	ONLYAUTO	ALL**								
8.***	PV SOURCE (PVSOURCE)	AUTO	MAN	SUB							
9.**	PV FILTER OPTION (PVFLTPT)	NONE	SINGLLAG								
10.***	PV FILTER TIME CONSTANT (PVFLTPT)	<table><tr><td>0</td><td>.</td><td>0</td><td></td><td></td></tr></table>				0	.	0			
0	.	0									
11.*	PV TARGET VALUE (PVTV)	<table><tr><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td></tr></table>				-	-	-	-	-	-
-	-	-	-	-	-						

AM REGULATORY PV DATA ACQUISITION ALGORITHM

AM88-611
Page 1 of 1
12/00

• AM - REGULATORY PV DATA ACQUISITION DISPLAY

1.0** NUMBER OF INPUT CONNECTIONS (NOPINPTS) 2.0*** INPUT CONNECTIONS

		SOURCE POINT.PARAMETER PISRC(N)	DESTINATION PARAMETER PIDSTN(N)		ACTIVITY STATUS PIACTSTS(N)	
2.1	1		P1	ACTIVE	INACTIVE	NOTCONFIG
2.2	2			ACTIVE	INACTIVE	NOTCONFIG
2.3	3			ACTIVE	INACTIVE	NOTCONFIG
2.4	4			ACTIVE	INACTIVE	NOTCONFIG
2.5	5			ACTIVE	INACTIVE	NOTCONFIG
2.6	6			ACTIVE	INACTIVE	NOTCONFIG
2.7	7			ACTIVE	INACTIVE	NOTCONFIG
2.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY PV FLOW COMPENSATION ALGORITHM

AM88-612
Page 1 of 3
12/00

• AM - REGULATORY PV FLOW COMP ALGORITHM DISPLAY

1.0**	ALGORITHM EQUATION TYPE (PVEQN)	EQA	EQB	EQC	EQD
		EQE			
2.0	SCALING CONSTANT (C)	1 . 0			
3.0	CORRECTION FACTOR (C1)	1 . 0			
4.0	CORRECTION FACTOR (C2)	1 . 0			
5.0	COMPENSATION TERM HIGH LIMIT (COMPHLM)	1 . 2 5			
6.0	COMPENSATION TERM LOW LIMIT (COMPLOLM)	0 . 8			

AM REGULATORY PV FLOW COMPENSATION ALGORITHM
(Continued)

AM88-612
Page 2 of 3
12/00

• AM - REGULATORY PV FLOW COMP ALGORITHM DISPLAY (Continued)

7.0***

INPUT PARAMETERS

PVEQN

7.1	SPECIFIC GRAVITY INPUT (G)	1 . 0	A, C, D
7.2	PRESSURE INPUT (P)	1 . 0	B, C, D, E
7.3	TEMPERATURE INPUT (T)	1 . 0	B, C, D, E
7.4	STEAM COMPRESSIBILITY INPUT (X)	1 . 0	E
7.5	STEAM QUALITY INPUT (Q)	1 . 0	E

8.0***

REFERENCE CONSTANTS

8.1	REFERENCE SPECIFIC GRAVITY (RG)	1 . 0	A, C, D
8.2	REFERENCE ABSOLUTE PRESSURE (RP)	1 . 0	B, C, D, E
8.3	REFERENCE ABSOLUTE TEMPERATURE (RT)	1 . 0	B, C, D, E
8.4	REFERENCE STEAM COMPRESSIBILITY (RX)	1 . 0	E
8.5	REFERENCE STEAM QUALITY (RQ)	1 . 0	E
8.6	ZERO PRESSURE REFERENCE (P0)	0 . 0	B, C, D, E
8.7	ZERO TEMPERATURE REFERENCE (T0)	0 . 0	B, C, D, E

AM88-612
Page 3 of 3
12/00

PIDSTN(N) DEFAULT VALUE (DEPENDS ON PVEON SELECTED)

<u>EQN</u>	<u>PIDSTN(N)</u>
A	1-F, 2-G AS SHOWN ON FORM BELOW
A	1-F, 2-P, 3-T
A	1-F, 2-G, 3-P, 4-T
A	1-F, 2-P, 3-T, 4-X, 5-Q

Where 1-F Means INPUT 1, PIDSTN(N) IS F

9.0**	NUMBER OF INPUT CONNECTIONS (NOPINPTS)	1
-------	--	---

<u>INPUT</u>	<u>SOURCE</u> <u>POINT.PARAMETER</u> PISRC(N)	<u>DESTINATION</u> <u>PARAMETER</u> PIDSTN(N)	<u>ACTIVITY STATUS</u> PIACTSTS(N)
--------------	---	---	---------------------------------------

10.1	1		F	ACTIVE	INACTIVE	NOTCONFIG
10.2	2		G	ACTIVE	INACTIVE	NOTCONFIG
10.3	3		P	ACTIVE	INACTIVE	NOTCONFIG
10.4	4		T	ACTIVE	INACTIVE	NOTCONFIG
10.5	5			ACTIVE	INACTIVE	NOTCONFIG
10.6	6			ACTIVE	INACTIVE	NOTCONFIG
10.7	7			ACTIVE	INACTIVE	NOTCONFIG
10.8	8			ACTIVE	INACTIVE	NOTCONFIG

• AM - REGULATORY PV MIDDLE OF 3 ALGORITHM DISPLAY

1.0 ALGORITHM EQUATION TYPE (PVEQN)

EQA

EQB

EQC

2.0*

INPUT PARAMETERS

2.1* P2 INPUT PARAMETER VALUE

| - | - | - | - | - | - | |

2.2* P3 INPUT PARAMETER VALUE

| - | - | - | - | - | - | |

3.0** NUMBER OF INPUT CONNECTIONS (NOPINPTS)

| 3 |

4.0***

INPUT CONNECTIONS

	INPUT	SOURCE POINT.PARAMETER PISRC(N)	DESTINATION PARAMETER PIDSTN(N)		ACTIVITY STATUS PIACTSTS(N)	
4.1	1		P1	ACTIVE	INACTIVE	NOTCONFIG
4.2	2		P2	ACTIVE	INACTIVE	NOTCONFIG
4.3	3		P3	ACTIVE	INACTIVE	NOTCONFIG
4.4	4			ACTIVE	INACTIVE	NOTCONFIG
4.5	5			ACTIVE	INACTIVE	NOTCONFIG
4.6	6			ACTIVE	INACTIVE	NOTCONFIG
4.7	7			ACTIVE	INACTIVE	NOTCONFIG
4.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY PV HI/LO/AVERAGE ALGORITHM

AM88-614
Page 1 of 2
12/00

• AM - REGULATORY PV HI/LO/AVERAGE ALGORITHM DISPLAY

1.0**	ALGORITHM EQUATION TYPE (PVEQN)	EQA	EQB	EQC	
2.0**	NUMBER OF INPUTS (N)	2			
3.0	MINIMUM NO OF NON-BAD INPUTS (NMIN)	1			
4.0**	PERMIT INPUT TO BE FORCED (FRCPERM)	OFF	ON		
5.0**	INPUT TO BE FORCED (FSELIN)	SELECTP1	SELECTP2	SELECTP3	SELECTP4
		SELECTP5	SELECTP6	SELECTP7	SELECTP8
6.0***		<u>INPUT PARAMETERS</u>			PVEQN A, B only
6.1	P2 INPUT PARAMETER VALUE	- - - - - -			
6.2	P3 INPUT PARAMETER VALUE	- - - - - -			
6.3	P4 INPUT PARAMETER VALUE	- - - - - -			
6.4	PS INPUT PARAMETER VALUE	- - - - - -			
6.5	P6 INPUT PARAMETER VALUE	- - - - - -			
6.6	P7 INPUT PARAMETER VALUE	- - - - - -			
6.7	P8 INPUT PARAMETER VALUE	- - - - - -			

AM88-614
Page 2 of 2
12/00

7.0**	NUMBER OF INPUT CONNECTIONS (NOPINPTS)	2
-------	--	---

INPUT	SOURCE POINT.PARAMETER PISRC(N)	DESTINATION PARAMETER PIDSTN(N)	ACTIVITY STATUS PIACTSTS(N)
-------	---------------------------------------	---------------------------------------	--------------------------------

8.1	1		P1	ACTIVE	INACTIVE	NOTCONFIG
8.2	2		P2	ACTIVE	INACTIVE	NOTCONFIG
8.3	3		P3	ACTIVE	INACTIVE	NOTCONFIG
8.4	4		P4	ACTIVE	INACTIVE	NOTCONFIG
8.5	5		P5	ACTIVE	INACTIVE	NOTCONFIG
8.6	6		P6	ACTIVE	INACTIVE	NOTCONFIG
8.7	7		P7	ACTIVE	INACTIVE	NOTCONFIG
8.8	8		P8	ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY PV SUMMER ALGORITHM

AM88-615
Page 1 of 2
12/00

• AM - REGULATORY PV SUMMER ALGORITHM DISPLAY

1.0**	ALGORITHM EQUATION TYPE (PVEQN)	EQA	EQB	PVEQN						
2.0	OVERALL GAIN (C)	<table><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td></tr></table>	1	.	0					A, B
1	.	0								
3.0	OUTPUT BIAS (D)	<table><tr><td>0</td><td>.</td><td>0</td><td></td><td></td><td></td></tr></table>	0	.	0					A, B
0	.	0								
4.0***	NUMBER OF INPUTS (N)	<table><tr><td>2</td></tr></table>	2		B					
2										
5.0***	<u>INPUT SCALING FACTORS</u>									
5.1	SCALING FACTOR FOR INPUT P1 (C1)	<table><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td></tr></table>	1	.	0					B
1	.	0								
5.2	SCALING FACTOR FOR INPUT P2 (C2)	<table><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td></tr></table>	1	.	0					B
1	.	0								
5.3	SCALING FACTOR FOR INPUT P3 (C3)	<table><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td></tr></table>	1	.	0					B
1	.	0								
5.4	SCALING FACTOR FOR INPUT P4 (C4)	<table><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td></tr></table>	1	.	0					B
1	.	0								
5.5	SCALING FACTOR FOR INPUT P5 (C5)	<table><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td></tr></table>	1	.	0					B
1	.	0								
5.6	SCALING FACTOR FOR INPUT P6 (C6)	<table><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td></tr></table>	1	.	0					B
1	.	0								
5.7	SCALING FACTOR FOR INPUT P7 (C7)	<table><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td></tr></table>	1	.	0					B
1	.	0								
5.8	SCALING FACTOR FOR INPUT P8 (C8)	<table><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td></tr></table>	1	.	0					B
1	.	0								

AM REGULATORY PV SUMMER ALGORITHM
(Continued)

AM88-615
Page 2 of 2
12/00

• AM - REGULATORY PV INPUT CONNECTIONS DISPLAY

6.0**	NUMBER OF INPUT CONNECTIONS (NOPINPTS)	1	<u>PVEQN</u>	<u>NOPINPTS DEFAULT VALUE</u>
			A	1
			B	2

7.0***

INPUT CONNECTIONS

	INPUT	SOURCE POINT.PARAMETER PISRC(N)	DESTINATION PARAMETER PIDSTN(N)	ACTIVITY STATUS PIACTSTS(N)	
7.1	1		P1	ACTIVE	INACTIVE NOTCONFIG
7.2	2		P2	ACTIVE	INACTIVE NOTCONFIG
7.3	3		P3	ACTIVE	INACTIVE NOTCONFIG
7.4	4		P4	ACTIVE	INACTIVE NOTCONFIG
7.5	5		P5	ACTIVE	INACTIVE NOTCONFIG
7.6	6		P6	ACTIVE	INACTIVE NOTCONFIG
7.7	7		P7	ACTIVE	INACTIVE NOTCONFIG
7.8	8		P8	ACTIVE	INACTIVE NOTCONFIG

AM REGULATORY PV MUL/DIV ALGORITHM

AM88-616
Page 1 of 2
12/00

• AM - REGULATORY PV MUL/DIV ALGORITHM DISPLAY

1.0** ALGORITHM EQUATION TYPE (PVEQN)

EQA EQB EQC

2.0 OVERALL SCALING CONSTANT (C)

| 1 | . | 0 | | | | | |

3.0 OVERALL BIAS CONSTANT (D)

| 0 | . | 0 | | | | | |

4.0***

INPUT SCALING AND BIAS CONTANTS

	<u>INPUT</u>	<u>SCALING CONSTANT</u>	<u>BIAS CONSTANT</u>	<u>PVEQN</u>
4.1	1	1 . 0	0 . 0	A, B, C
4.2	2	1 . 0	0 . 0	A, B, C
4.3	3	1 . 0	0 . 0	C
4.4	4	1 . 0	0 . 0	C
4.5	5	1 . 0	0 . 0	C
4.6	6	1 . 0	0 . 0	C
4.7	7	1 . 0	0 . 0	C

5.0***

INPUT PARAMETERS

5.1	P2 INPUT PARAMETER VALUE	1 . 0	A, B, C
5.2	P3 INPUT PARAMETER VALUE	1 . 0	C
5.3	P4 INPUT PARAMETER VALUE	1 . 0	C
5.4	P5 INPUT PARAMETER VALUE	1 . 0	C
5.5	P6 INPUT PARAMETER VALUE	1 . 0	C
5.6	P7 INPUT PARAMETER VALUE	0 . 0	C

References: Application Module Form Instructions in Implementation/Application Module - 1 binder.
Data Entity Builder Manual in Implementation/Engineering Operations - 1 binder.

AM REGULATORY PV MUL/DIV ALGORITHM
(Continued)

AM88-616
Page 2 of 2
12/00

• AM - REGULATORY PV INPUT CONNECTIONS DISPLAY

6.0**	NUMBER OF INPUT CONNECTIONS (NOPINPTS)	2	<u>PVEQN</u> A, B C	<u>NOPINPTS</u>	<u>DEFAULT VALUE</u> 2 7
-------	--	--	---------------------------	-----------------	--------------------------------

7.0***

INPUT CONNECTIONS

	INPUT	SOURCE POINT .PARAMETER PISRC(N)	DESTINATION PARAMETER PIDSTN(N)	ACTIVITY STATUS PIACTSTS(N)		
7.1	1		P1	ACTIVE	INACTIVE	NOTCONFIG
7.2	2		P2	ACTIVE	INACTIVE	NOTCONFIG
7.3	3		P3	ACTIVE	INACTIVE	NOTCONFIG
7.4	4		P4	ACTIVE	INACTIVE	NOTCONFIG
7.5	5		P5	ACTIVE	INACTIVE	NOTCONFIG
7.6	6		P6	ACTIVE	INACTIVE	NOTCONFIG
7.7	7		P7	ACTIVE	INACTIVE	NOTCONFIG
7.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY PV SUM OF PRODUCTS ALGORITHM

AM88-617
Page 1 of 2
12/00

• AM - REGULATORY PV SUM OF PRODUCTS ALGORITHM DISPLAY

1.0** ALGORITHM EQUATION TYPE (PVEQN)

EQA EQB

2.0 OVERALL SCALING CONSTANT (C)

1 . 0

3.0 OVERALL BIAS CONSTANT (D)

0 . 0

4.0***

INPUT SCALING AND BIAS CONTANTS

	INPUT	SCALING CONSTANT	BIAS CONSTANT	PVEQN
4.1	1	1 . 0	0 . 0	A, B
4.2	2	1 . 0	0 . 0	A, B
4.3	3	1 . 0	0 . 0	A, B
4.4	4	1 . 0	0 . 0	A, B
4.5	5	1 . 0	0 . 0	B
4.6	6	1 . 0	0 . 0	B
4.7	7	1 . 0	0 . 0	B

5.0***

INPUT PARAMETERS

5.1	P2 INPUT PARAMETER VALUE	1 . 0	A, B
5.2	P3 INPUT PARAMETER VALUE	1 . 0	A, B
5.3	P4 INPUT PARAMETER VALUE	1 . 0	A, B
5.4	P5 INPUT PARAMETER VALUE	0 . 0	B
5.5	P6 INPUT PARAMETER VALUE	0 . 0	B
5.6	P7 INPUT PARAMETER VALUE	0 . 0	B

References: Application Module Form Instructions in Implementation/Application Module - 1 binder.
Data Entity Builder Manual in Implementation/Engineering Operations - 1 binder.

AM REGULATORY PV SUM OF PRODUCTS ALGORITHM
(Continued)

AM88-617
Page 2 of 2
12/00

• AM - REGULATORY PV INPUT CONNECTIONS DISPLAY

6.0**	NUMBER OF INPUT CONNECTIONS (NOPINPTS)	4	<u>PVEQN</u>	<u>NOPINPTS DEFAULT VALUE</u>
			A	4
			B	7

7.0*** INPUT CONNECTIONS

	INPUT	SOURCE POINT.PARAMETER PISRC(N)	DESTINATION PARAMETER PIDSTN(N)		ACTIVITY STATUS PIACTSTS(N)	
7.1	1		P1	ACTIVE	INACTIVE	NOTCONFIG
7.2	2		P2	ACTIVE	INACTIVE	NOTCONFIG
7.3	3		P3	ACTIVE	INACTIVE	NOTCONFIG
7.4	4		P4	ACTIVE	INACTIVE	NOTCONFIG
7.5	5			ACTIVE	INACTIVE	NOTCONFIG
7.6	6			ACTIVE	INACTIVE	NOTCONFIG
7.7	7			ACTIVE	INACTIVE	NOTCONFIG
7.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY PV VDT LEAD/LAG ALGORITHM

AM88-618
Page 1 of 2
12/00

• AM - REGULATORY PV VDT LEAD/LAG ALGORITHM DISPLAY

1.0**	ALGORITHM EQUATION TYPE (PVEQN)	EQA	EQB	EQC	EQD	PVEQN***
2.0***	OVERALL SCALING CONSTANT (C)	1 . 0				A, B, C, D
3.0	OVERALL BIAS CONSTANT (D)	0 . 0				A, B, C, D
4.0	LAG 1 TIME CONSTANT (TLG1 IN MIN)	0 . 0				A, D
5.0	LAG 2 TIME CONSTANT (TLG2 IN MIN)	0 . 0				A, D
6.0	ZERO CUTOFF LIMIT (CUTOFFLM)	0 . 0				C, D
7.0	LEAD TIME CONSTANT (TLD IN MIN)	0 . 0				A
8.0	FIXED DEAD TIME VALUE (TD IN MIN)	0 . 0				B
9.0	VDT SCALING CONSTANT 1 (C1)	1 . 0				C, C
10.0	VDT SCALING CONSTANT 2 (C2)	1 . 0				C, D
11.0	FIXED DEAD TIME (D1)	0 . 0				C, D
12.0	BIAS CONSTANT FOR P2 INPUT (D2)	0 . 0				C, D

AM REGULATORY PV VDT LEAD/LAG ALGORITHM
(Continued)

AM88-618
Page 2 of 2
12/00

• AM - REGULATORY PV INPUT CONNECTIONS DISPLAY

13.0**	NUMBER OF INPUT CONNECTIONS (NOPINPTS)	1	PVEQN A, B C, D	NOPINPTS DEFAULT VALUE 1 2
--------	--	--	--	--

14.0*** INPUT CONNECTIONS

INPUT		SOURCE POINT.PARAMETER PISRC(N)	DESTINATION PARAMETER PIDSTN(N)	ACTIVITY STATUS PIACTSTS(N)		
14.1	1		P1	ACTIVE	INACTIVE	NOTCONFIG
14.2	2		P2	ACTIVE	INACTIVE	NOTCONFIG
14.3	3			ACTIVE	INACTIVE	NOTCONFIG
14.4	4			ACTIVE	INACTIVE	NOTCONFIG
14.5	5			ACTIVE	INACTIVE	NOTCONFIG
14.6	6			ACTIVE	INACTIVE	NOTCONFIG
14.7	7			ACTIVE	INACTIVE	NOTCONFIG
14.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY PV TOTALIZER ALGORITHM

AM88-619
Page 1 of 2
12/00

• AM - REGULATORY PV TOTALIZER ALGORITHM DISPLAY

1.0	ALGORITHM EQUATION TYPE (PVEQN)	EQA	EQB	EQC	EQD
		EQE	EQF		
2.0	INPUT TIME BASE (TIMEBASE)	SECONDS	MINUTES	HOURS	
3.0	SCALING CONSTANT (C)	1 . 0			
4.0	PRESET VALUE (RESETVAL)	0 . 0			
5.0	ZERO FLOW CUTOFF LIMIT (CUTOFFLM)	0 . 0			
6.0	ACCUMULATED TARGET VALUE (AVTV)	- - - - - -			
7.0	FIRST DEVIATION TRIP POINT (AVDEV1TP)	- - - - - -			
8.0	SECOND DEVIATION TRIP POINT (AVDEV2TP)	- - - - - -			

AM REGULATORY PV TOTALIZER ALGORITHM
(Continued)

AM88-619
Page 2 of 2
12/00

• AM - REGULATORY PV TOTALIZER ALGORITHM DISPLAY (Continued)

13.0** NUMBER OF CONNECTIONS (NOPINPTS)

1

14.0***

INPUT CONNECTIONS

INPUT		SOURCE POINT.PARAMETER PISRC(N)	DESTINATION PARAMETER PIDSTN(N)	ACTIVITY STATUS PIACTSTS(N)		
14.1	1		P1	ACTIVE	INACTIVE	NOTCONFIG
14.2	2			ACTIVE	INACTIVE	NOTCONFIG
14.3	3			ACTIVE	INACTIVE	NOTCONFIG
14.4	4			ACTIVE	INACTIVE	NOTCONFIG
14.5	5			ACTIVE	INACTIVE	NOTCONFIG
14.6	6			ACTIVE	INACTIVE	NOTCONFIG
14.7	7			ACTIVE	INACTIVE	NOTCONFIG
14.8	8			ACTIVE	INACTIVE	NOTCONFIG

• AM - REGULATORY PV GENERAL/LINEAR ALGORITHM DISPLAY

1.0** NUMBER OF SEGMENTS (SEGTOT)

1

2.0 CHARACTERISTIC CURVE COORDINATE PAIRS

	<u>IN COORDINATE</u>	<u>VALUE</u>		<u>OUT COORDINATE</u>	<u>VALUE</u>
2.1	IN0			OUT0	
2.2	IN1			OUT1	
2.3	IN2			OUT2	
2.4	IN3			OUT3	
2.5	IN4			OUT4	
2.6	IN5			OUT5	
2.7	IN6			OUT6	
2.8	IN7			OUT7	
2.9	IN8			OUT8	
2.10	IN9			OUT9	
2.11	IN10			OUT10	
2.12	IN11			OUT11	
2.13	IN12			OUT12	

AM REGULATORY PV GENERAL LINEARIZATION
(Continued)

AM88-620
Page 2 of 2
12/00

• AM - REGULATORY PV GENERAL/LINEAR ALGORITHM DISPLAY (Continued)

3.0** NUMBER OF INPUT CONNECTIONS (NOPINPTS) 1

4.0*** INPUT CONNECTIONS

INPUT		SOURCE POINT.PARAMETER PISRC(N)	DESTINATION PARAMETER PIDSTN(N)	ACTIVITY STATUS PIACTSTS(N)		
4.1	1		P1	ACTIVE	INACTIVE	NOTCONFIG
4.2	2			ACTIVE	INACTIVE	NOTCONFIG
4.3	3			ACTIVE	INACTIVE	NOTCONFIG
4.4	4			ACTIVE	INACTIVE	NOTCONFIG
4.5	5			ACTIVE	INACTIVE	NOTCONFIG
4.6	6			ACTIVE	INACTIVE	NOTCONFIG
4.7	7			ACTIVE	INACTIVE	NOTCONFIG
4.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY PV CALCULATOR ALGORITHM

AM88-621
Page 1 of 2
12/00

• AM - REGULATORY PV CALCULATOR ALGORITHM DISPLAY

1.0	NUMBER OF INPUTS (N)	2
2.0	CALCULATOR CONSTANT #1 (C1)	0 . 0
3.0	CALCULATOR CONSTANT #2 (C2)	0 . 0
4.0	CALCULATOR CONSTANT #3 (C3)	0 . 0
5.0	CALCULATOR CONSTANT #4 (C4)	0 . 0
6.0	CALCULATOR EXPRESSION (CALCEXP)	
7.0	SCALING FACTOR #1 (D1)	0 . 0
8.0	SCALING FACTOR #2 (D2)	0 . 0

AM REGULATORY PV CALCULATOR ALGORITHM
(Continued)

AM88-621
Page 2 of 2
12/00

• AM - REGULATORY PV CALCULATOR ALGORITHM DISPLAY (Continued)

13.0** NUMBER OF INPUT CONNECTIONS (NOPINPTS)

2

14.0***

INPUT CONNECTIONS

INPUT		SOURCE POINT.PARAMETER PISRC(N)	DESTINATION PARAMETER PIDSTN(N)	ACTIVITY STATUS PIACTSTS(N)		
14.1	1		P1	ACTIVE	INACTIVE	NOTCONFIG
14.2	2		P2	ACTIVE	INACTIVE	NOTCONFIG
14.3	3			ACTIVE	INACTIVE	NOTCONFIG
14.4	4			ACTIVE	INACTIVE	NOTCONFIG
14.5	5			ACTIVE	INACTIVE	NOTCONFIG
14.6	6			ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY CONTROL MODE AND SET POINT FORM

AM88-641
Page 1 of 1
12/01

• AM - REGULATORY CONTROL COMMON DISPLAY

1.0**	NORMAL MODE (NMODE)	NONE	MAN	AUTO	CAS
2.0***	NORMAL MODE ATTRIBUTE (NMODATTR)	NONE	OPERATOR	PROGRAM	
3.0	MODE PERMISSIVE (MODEPERM)	PERMIT	NOTPERM		
4.0	EXT. MODE SWITCHING OPTION (EXTSWOPT)	NONE	EMS	EMP	
5.0	MODE SELECTION LIST (\$MODESEL)	MAN	CAS	PROG	
		AUTO			

• AM - REGULATORY SET POINT DISPLAY

10.0	SP DECIMAL PLACE FORMAT (SPFORMAT)	D0	D1	D2	D3	D4	D5
11.0	SET POINT EU RANGE HIGH (SPEUHI)	1	0	0	.	0	
12.0	SET POINT EU RANGE LOW (SPEULO)	0	.	0			
13.0	SET POINT HIGH LIMIT (SPHILM)	-	-	-	-	-	
14.0	SET POINT LOW LIMIT (SPLOLM)	-	-	-	-	-	
15.0	SET POINT TOLERANCE (\$SPTOL)	0	.	0			
16.0	SET POINT (SP)	0	.	0			
17.0*	SET POINT OPTION (SPOPT)	NONE	TV	ASP			
18.0*	ADV DEV ALARM TRIP POINT (ADVDEVTP)	-	-	-	-	-	
19.0**	RATIO/BIAS OPTION (RBOPT)	NORATBI	FIXRATBI	AUTORAT	AUTOBI		
20.0	RATIO HIGH LIMIT (RTHILM)	1	0	0	.	0	
21.0***	RATIO LOW LIMIT (RTLOLM)	0	.	0	1		
22.0	BIAS HIGH LIMIT (BSHILM)	5	0	.	0		
23.0	BIAS LOW LIMIT (BSLOLM)	-	5	0	.	0	
24.0	RATIO (RATIO)	1	.	0			
25.0	BIAS (BIAS)	0	.	0			

References: Application Module Form Instructions in Implementation/Application Module - 1 binder.
Data Entity Builder Manual in Implementation/Engineering Operations - 1 binder.

AM REGULATORY CONTROL PID ALGORITHM

AM88-651
Page 1 of 4
12/00

• AM - REGULATORY CONTROL PID ALGORITHM DISPLAY

1.0*	ALGORITHM FORM (PIDFORM)	INTERACT	IDEAL		
2.0	ALGORITHM EQUATION TYPE (CTLEQN)	EQA	EQB	EQC	EQD
3.0	INITIALIZATION TYPE (INITTYPE)	EXT	INT		
4.0	CONTROL ACTION (CTLACTN)	REVERSE	DIRECT		
5.0***	GAIN OPTION (GAINOPT)	LIN**	GAP**	NONLIN**	EXT**
6.0***	OVERALL GAIN VALUE (K)	1 . 0			
7.0	LINEAR GAIN VALUE (KLIN)	1 . 0			
8.0***	INSIDE-GAP GAIN FACTOR (KGAP)	1 . 0			
9.0***	GAP RANGE HIGH (GAPHI)	0 . 0			
10.0***	GAP RANGE LOW (GAPLO)	0 . 0			
11.0***	NON-LINEAR GAIN (NLGAIN)	0 . 0			
12.0***	NON-LINEARITY FORM (NLFM)	NLFM =1	NLFM =0		
13.0*	INTEGRAL TIME (T1 IN MIN)	0 . 0			
14.0*	DERIVATIVE TIME (T2 IN MIN)	0 . 0			

AM REGULATORY CONTROL PID ALGORITHM
(Continued)

AM88-651
Page 2 of 4
12/00

• AM - REGULATORY CONTROL PID ALGORITHM DISPLAY (Continued)

15.0* PV TRACKING OPTION (PVTRACK) NOTRACK TRACK

• AM - REGULATORY CONTROL INPUT CONNECTIONS DISPLAY

16.0** NUMBER OF INPUT CONNECTIONS (NOCINPTS) 1

17.0*** INPUT CONNECTIONS

	INPUT	SOURCE POINT.PARAMETER CISRC(N)	DESTINATION PARAMETER CIDSTN(N)		ACTIVITY STATUS CIACTSTS(N)	
17.1	1		PV	ACTIVE	INACTIVE	NOTCONFIG
17.2	2			ACTIVE	INACTIVE	NOTCONFIG
17.3	3			ACTIVE	INACTIVE	NOTCONFIG
17.4	4			ACTIVE	INACTIVE	NOTCONFIG
17.5	5			ACTIVE	INACTIVE	NOTCONFIG
17.6	6			ACTIVE	INACTIVE	NOTCONFIG
17.7	7			ACTIVE	INACTIVE	NOTCONFIG
17.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY CONTROL PID ALGORITHM
(Continued)

AM88-651
Page 3 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

20.0** NUMBER OF OUTPUT CONNECTIONS (NOCOPTS) 1

21.0***

	OUTPUT	DESTINATION POINT_ID.PARAMETER CODSTN(N)	CONNECTION ACTIVITY STATUS COACTSTS(N)
21.1	1		ACTIVE INACTIVE NOTCONFIG
21.2	2		ACTIVE INACTIVE NOTCONFIG
21.3	3		ACTIVE INACTIVE NOTCONFIG
21.4	4		ACTIVE INACTIVE NOTCONFIG
21.5	5		ACTIVE INACTIVE NOTCONFIG
21.6	6		ACTIVE INACTIVE NOTCONFIG
21.7	7		ACTIVE INACTIVE NOTCONFIG
21.8	8		ACTIVE INACTIVE NOTCONFIG

AM REGULATORY CONTROL PID ALGORITHM
(Continued)

AM88-651
Page 4 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

22.0***	CV ENGINEERING UNITS HIGH (CVEUHI)	1 0 0 . 0
23.0***	CV ENGINEERING UNITS LOW (CVEULO)	0 . 0
24.0***	CONTROL OUTPUT (OP)	0 . 0
25.0	OP HIGH LIMIT VALUE IN % (OPHILM)	1 0 5 . 0
26.0	OP LOW LIMIT VALUE IN %(OPLOLM)	- 5 . 0
27.0	OP MINIMUM CHANGE IN % (OPMCHLM)	0 . 0
28.0	OP ROC LIMIT IN %/MIN (OPROCLM)	- - - - - -
29.0	OP TOLERANCE IN % (\$OPTOL)	0 . 0

AM REGULATORY CONTROL LEAD/LAG ALGORITHM

AM88-652
Page 1 of 4
12/00

• AM - REGULATORY CONTROL LEAD/LAG ALGORITHM DISPLAY

1.0	INITIALIZATION TYPE (INITTYPE)	EXT	INT	NONE
2.0	OUTPUT BIAS (B)	0 . 0		
3.0	OVERALL GAIN (K)	1 . 0		
4.0	LAG 1 TIME CONSTANT (T1 IN MIN)	0 . 0		
5.0	LAG 2 TIME CONSTANT (T3 IN MIN)	0 . 0		
6.0	LEAD TIME CONSTANT (T2 IN MIN)	0 . 0		

AM REGULATORY CONTROL LEAD/LAG ALGORITHM
(Continued)

AM88-652
Page 2 of 4
12/00

• AM - REGULATORY CONTROL LEAD/LAG ALGORITHM DISPLAY (Continued)

7.0** NUMBER OF CONTROL INPUT CONNECTIONS (NOCINPTS)

8.0*** INPUT CONNECTIONS

	INPUT	SOURCE POINT.PARAMETER CISRC(N)	DESTINATION PARAMETER CIDSTN(N)		ACTIVITY STATUS CIACTSTS(N)	
8.1	1			ACTIVE	INACTIVE	NOTCONFG
8.2	2			ACTIVE	INACTIVE	NOTCONFG
8.3	3			ACTIVE	INACTIVE	NOTCONFG
8.4	4			ACTIVE	INACTIVE	NOTCONFG
8.5	5			ACTIVE	INACTIVE	NOTCONFG
8.6	6			ACTIVE	INACTIVE	NOTCONFG
8.7	7			ACTIVE	INACTIVE	NOTCONFG
8.8	8			ACTIVE	INACTIVE	NOTCONFG

AM REGULATORY CONTROL LEAD/LAG ALGORITHM
(Continued)

AM88-652
Page 3 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY

10.0** NUMBER OF OUTPUT CONNECTIONS (NOCOPTS) 1

OUTPUT		DESTINATION POINT_ID.PARAMETER CODSTN(N)	CONNECTION ACTIVITY STATUS COACTSTS(N)		
11.1	1		ACTIVE	INACTIVE	NOTCONFIG
11.2	2		ACTIVE	INACTIVE	NOTCONFIG
11.3	3		ACTIVE	INACTIVE	NOTCONFIG
11.4	4		ACTIVE	INACTIVE	NOTCONFIG
11.5	5		ACTIVE	INACTIVE	NOTCONFIG
11.6	6		ACTIVE	INACTIVE	NOTCONFIG
11.7	7		ACTIVE	INACTIVE	NOTCONFIG
11.8	8		ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY CONTROL LEAD/LAG ALGORITHM
(Continued)

AM88-652
Page 4 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

12.0***	CV ENGINEERING UNITS HIGH (CVEUHI)	1 0 0 . 0
13.0***	CV ENGINEERING UNITS LOW (CVEULO)	0 . 0
14.0***	CONTROL OUTPUT (OP)	0 . 0
15.0	OP HIGH LIMIT VALUE IN (OPHILM)	1 0 5 . 0
16.0	OP LOW LIMIT VALUE IN (OPLOLM)	- 5 . 0
17.0	OP MINIMUM CHANGE IN % (OPMCHLM)	0 . 0
18.0	OP ROC LIMIT IN %/MIN (OPROCLM)	- - - - - -
19.0	OP TOLERANCE IN % (\$OPTOL)	0 . 0

AM REGULATORY CONTROL SUMMER ALGORITHM

AM88-653
Page 1 of 4
12/00

• AM - REGULATORY CONTROL SUMMER ALGORITHM DISPLAY

1.0**	ALGRITHM EQUATION TYPE (CTLEQN)	EQA	EQB											
2.0	INITIALIZATION TYPE (INITTYPE)	EXT	INT	NONE	CTLEQN									
3.0	OUTPUT BIAS (B)	<table><tr><td>0</td><td>.</td><td>0</td><td></td><td></td><td></td><td></td><td></td></tr></table>				0	.	0						all
0	.	0												
4.0	OVERALL GAIN (K)	<table><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td><td></td><td></td></tr></table>				1	.	0						all
1	.	0												
5.0**	NUMBER OF INPUTS (M)	<table><tr><td>2</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>				2								B
2														
6.0	GAIN FOR INPUT SP (K1)	<table><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td><td></td><td></td></tr></table>				1	.	0						B
1	.	0												
7.0***	GAIN FOR INPUT X2(K2)	<table><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td><td></td><td></td></tr></table>				1	.	0						B
1	.	0												
8.0***	GAIN FOR INPUT X3(K3)	<table><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td><td></td><td></td></tr></table>				1	.	0						B
1	.	0												
9.0***	GAIN FOR INPUT X4 (K4)	<table><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td><td></td><td></td></tr></table>				1	.	0						B
1	.	0												

AM REGULATORY CONTROL SUMMER ALGORITHM
(Continued)

AM88-653
Page 2 of 4
12/00

• AM - REGULATORY CONTROL INPUT CONNECTIONS DISPLAY

11.0** NUMBER OF INPUT CONNECTIONS (NOCINPTS)

1

12.0***

INPUT CONNECTIONS

	INPUT	SOURCE POINT.PARAMETER CISRC(N)	DESTINATION PARAMETER CIDSTN(N)		ACTIVITY STATUS CIACTSTS(N)	
12.1	1		X2	ACTIVE	INACTIVE	NOTCONFIG
12.2	2		X3	ACTIVE	INACTIVE	NOTCONFIG
12.3	3		X4	ACTIVE	INACTIVE	NOTCONFIG
12.4	4			ACTIVE	INACTIVE	NOTCONFIG
12.5	5			ACTIVE	INACTIVE	NOTCONFIG
12.6	6			ACTIVE	INACTIVE	NOTCONFIG
12.7	7			ACTIVE	INACTIVE	NOTCONFIG
12.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY CONTROL SUMMER ALGORITHM
(Continued)

AM88-653
Page 3 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY

20.0** NUMBER OF OUTPUT CONNECTIONS (NOCOPTS) 1

21.0*** OUTPUT CONNECTIONS

	OUTPUT	DESTINATION POINT_ID.PARAMETER CODSTN(N)	CONNECTION ACTIVITY STATUS COACTSTS(N)
21.1	1		ACTIVE INACTIVE NOTCONFIG
21.2	2		ACTIVE INACTIVE NOTCONFIG
21.3	3		ACTIVE INACTIVE NOTCONFIG
21.4	4		ACTIVE INACTIVE NOTCONFIG
21.5	5		ACTIVE INACTIVE NOTCONFIG
21.6	6		ACTIVE INACTIVE NOTCONFIG
21.7	7		ACTIVE INACTIVE NOTCONFIG
21.8	8		ACTIVE INACTIVE NOTCONFIG

AM REGULATORY CONTROL SUMMER ALGORITHM
(Continued)

AM88-653
Page 4 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

22.0***	CV ENGINEERING UNITS HIGH (CVEUHI)	1 0 0 . 0
23.0***	CV ENGINEERING UNITS LOW (CVEULO)	0 . 0
24.0***	CONTROL OUTPUT (OP)	0 . 0
25.0	OP HIGH LIMIT VALUE IN % (OPHILM)	1 0 5 . 0
26.0	OP LOW LIMIT VALUE IN % (OPLOLM)	- 5 . 0
27.0	OP MINIMUM CHANGE IN % (OPMCHLM)	0 . 0
28.0	OP ROC LIMIT IN %/MIN (OPROCLM)	- - - - - -
29.0	OP TOLERANCE IN % (\$OPTOL)	0 . 0

AM REGULATORY CONTROL MUL/DIV ALGORITHM

AM88-654
Page 1 of 4
12/00

• AM - REGULATORY CONTROL MUL/DIV ALGORITHM DISPLAY

1.0**	ALGORITHM EQUATION TYPE (CTLEQN)	EQA	EQB	EQC
2.0**	INITIALIZATION TYPE (INITTYPE)	EXT	INT	NONE
3.0	OVERALL GAIN (K)	1 . 0		
4.0***	OUTPUT BIAS (B)	1 . 0		
5.0***	<u>GAIN AND BIAS FACTORS</u>			
<u>EQN***</u>				
A, B, C	5.1	GAIN FOR INPUT SP (K1)	1 . 0	5.5 BIAS FOR INPUT SP (B1) 0 . 0
A, B, C	5.2	GAIN FOR INPUT X2 (K2)	1 . 0	5.6 BIAS FOR INPUT X2 (B2) 0 . 0
B, C	5.3	GAIN FOR INPUT X3 (K3)	1 . 0	5.7 BIAS FOR INPUT X3 (B3) 0 . 0
B, C	5.4	GAIN FOR INPUT X4 (K4)	0 . 0	5.8 BIAS FOR INPUT X4 (B4) 0 . 0
6.0	<u>INPUT PARAMETERS</u>			
A, B, C	6.1	X2 INPUT PARAMETER VALUE	1 . 0	
B, C	6.2	X3 INPUT PARAMETER VALUE	1 . 0	
B, C	6.3	X4 INPUT PARAMETER VALUE	0 . 0	

AM REGULATORY CONTROL MUL/DIV ALGORITHM
(Continued)

AM88-654
Page 2 of 4
12/00

• AM - REGULATORY CONTROL INPUT CONNECTIONS DISPLAY

10.0**	NUMBER OF INPUT CONNECTIONS (NOCINPTS)	<u>1</u>	CTLEQN	NOCINPTS	DEFAULT	VALUE
			A			1
			B, C			3

11.0*** INPUT CONNECTIONS

	INPUT	SOURCE POINT.PARAMETER CISRC(N)	DESTINATION PARAMETER CIDSTN(N)		ACTIVITY STATUS CIACTSTS(N)	
11.1	1		X2	ACTIVE	INACTIVE	NOTCONFG
11.2	2		X3	ACTIVE	INACTIVE	NOTCONFG
11.3	3		X4	ACTIVE	INACTIVE	NOTCONFG
11.4	4			ACTIVE	INACTIVE	NOTCONFG
11.5	5			ACTIVE	INACTIVE	NOTCONFG
11.6	6			ACTIVE	INACTIVE	NOTCONFG
11.7	7			ACTIVE	INACTIVE	NOTCONFG
11.8	8			ACTIVE	INACTIVE	NOTCONFG

AM REGULATORY CONTROL MUL/DIV ALGORITHM
(Continued)

AM88-654
Page 3 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY

20.0** NUMBER OF OUTPUT CONNECTIONS (NOCOPTS) 1

21.0*** OUTPUT CONNECTIONS

	OUTPUT	DESTINATION POINT_ID.PARAMETER CODSTN(N)	CONNECTION ACTIVITY STATUS COACTSTS(N)
21.1	1		ACTIVE INACTIVE NOTCONFIG
21.2	2		ACTIVE INACTIVE NOTCONFIG
21.3	3		ACTIVE INACTIVE NOTCONFIG
21.4	4		ACTIVE INACTIVE NOTCONFIG
21.5	5		ACTIVE INACTIVE NOTCONFIG
21.6	6		ACTIVE INACTIVE NOTCONFIG
21.7	7		ACTIVE INACTIVE NOTCONFIG
21.8	8		ACTIVE INACTIVE NOTCONFIG

AM REGULATORY CONTROL MUL/DIV ALGORITHM
(Continued)

AM88-654
Page 4 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

22.0***	CV ENGINEERING UNITS HIGH (CVEUHI)	1 0 0 . 0
23.0***	CV ENGINEERING UNITS LOW (CVEULO)	0 . 0
24.0***	CONTROL OUTPUT (OP)	0 . 0
25.0	OP HIGH LIMIT VALUE IN % (OPHILM)	1 0 5 . 0
26.0	OP LOW LIMIT VALUE IN % (OPLOLM)	- 5 . 0
27.0	OP MINIMUM CHANGE IN % (OPMCHLM)	0 . 0
28.0	OP ROC LIMIT IN %/MIN (OPROCLM)	_ _ _ _ _ _
29.0	OP TOLERANCE IN % (\$OPTOL)	0 . 0

AM REGULATORY CONTROL PID WITH EXTERNAL FEEDBACK ALGORITHM

AM88-655
Page 1 of 4
12/00

• AM - REGULATORY CONTROL ERFB PID ALGORITHM DISPLAY

1.0*	ALGORITHM FORM (PIDFORM)	INTERACT	IDEAL		
2.0	ALGORITHM EQUATION TYPE (CTLEQN)	EQA	EQB	EQC	EQD
3.0	INITIALIZATION TYPE (INITTYPE)	EXT	INT		
4.0	CONTROL ACTION (CTLACTN)	REVERSE	DIRECT		
5.0***	GAIN OPTION (GAINOPT)	LIN**	GAP**	NONLIN**	EXT**
6.0***	OVERALL GAIN VALUE (K)	1	.	0	
7.0	LINEAR GAIN VALUE (KLIN)	1	.	0	
8.0***	INSIDE-GAP GAIN FACTOR (KGAP)	1	.	0	
9.0***	GAP RANGE HIGH (GAPHI)	0	.	0	
10.0***	GAP RANGE LOW (GAPLO)	0	.	0	
11.0***	NON-LINEAR GAIN (NLGAIN)	0	.	0	
12.0***	NON-LINEARITY FORM (NLFM)	NLFM =1	NLFM =0		
13.0*	INTEGRAL TIME (T1 IN MIN)	0	.	0	
14.0*	DERIVATIVE TIME (T2 IN MIN)	0	.	0	

AM REGULATORY CONTROL PID WITH EXTERNAL FEEDBACK ALGORITHM
(Continued)

AM88-655
Page 2 of 4
12/00

• AM - REGULATORY CONTROL ERFB PID ALGORITHM DISPLAY (Continued)

15.0 EXTERNAL RESET FEEDBACK GAIN (K1)

0	.	0					
---	---	---	--	--	--	--	--

16.0 PV TRACKING OPTION (PVTRACK) **NOTRACK** TRACK

• AM - REGULATORY CONTROL INPUT CONNECTIONS DISPLAY

17.0** NUMBER OF INPUT CONNECTIONS (NOCINPTS)

3

18.0*** INPUT CONNECTIONS

	INPUT	SOURCE POINT.PARAMETER CISRC(N)	DESTINATION PARAMETER CIDSTN(N)		ACTIVITY STATUS CIACTSTS(N)	
18.1	1		PV	ACTIVE	INACTIVE	NOTCONFIG
18.2	2		RFB	ACTIVE	INACTIVE	NOTCONFIG
18.3	3		TRFB	ACTIVE	INACTIVE	NOTCONFIG
18.4	4			ACTIVE	INACTIVE	NOTCONFIG
18.5	5			ACTIVE	INACTIVE	NOTCONFIG
18.6	6			ACTIVE	INACTIVE	NOTCONFIG
18.7	7			ACTIVE	INACTIVE	NOTCONFIG
18.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY CONTROL PID WITH EXTERNAL FEEDBACK ALGORITHM
(Continued)

AM88-655
Page 3 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY

20.0** NUMBER OF OUTPUT CONNECTIONS (NOCOPTS)

21.0*** OUTPUT CONNECTIONS

OUTPUT		DESTINATION POINT_ID.PARAMETER CODSTN(N)	CONNECTION ACTIVITY STATUS COACTSTS(N)		
21.1	1		ACTIVE	INACTIVE	NOTCONFIG
21.2	2		ACTIVE	INACTIVE	NOTCONFIG
21.3	3		ACTIVE	INACTIVE	NOTCONFIG
21.4	4		ACTIVE	INACTIVE	NOTCONFIG
21.5	5		ACTIVE	INACTIVE	NOTCONFIG
21.6	6		ACTIVE	INACTIVE	NOTCONFIG
21.7	7		ACTIVE	INACTIVE	NOTCONFIG
21.8	8		ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY CONTROL PID WITH EXTERNAL FEEDBACK ALGORITHM
(Continued)

AM88-655
Page 4 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

22.0***	CV ENGINEERING UNITS HIGH (CVEUHI)	1 0 0 . 0
23.0***	CV ENGINEERING UNITS LOW (CVEULO)	0 . 0
24.0***	CONTROL OUTPUT (OP)	0 . 0
25.0	OP HIGH LIMIT VALUE IN % (OPHILM)	1 0 5 . 0
26.0	OP LOW LIMIT VALUE IN % (OPLOLM)	- 5 . 0
27.0	OP MINIMUM CHANGE IN % (OPMCHLM)	0 . 0
28.0	OP ROC LIMIT IN %/MIN (OPROCLM)	- - - - - -
29.0	OP TOLERANCE IN % (\$OPTOL)	0 . 0

• AM - REGULATORY PID CONTROL FFWD ALGORITHM DISPLAY

1.0**	ALGORITHM FORM (PIDFORM)	INTERACT	IDEAL				
2.0	ALGORITHM EQUATION TYPE (CTLEQN)	EQA	EQB	EQC	EQD		
3.0	INITIALIZATION TYPE (INITTYPE)	EXT	INT				
4.0	CONTROL ACTION (CTLACTN)	REVERSE	DIRECT				
5.0***	GAIN OPTION (GAINOPT)	LIN**	GAP**	NONLIN**	EXT**		
6.0***	OVERALL GAIN VALUE (K)	1 . 0					
7.0	LINEAR GAIN VALUE (KLIN)	1 . 0					
8.0***	INSIDE-GAP GAIN FACTOR (KGAP)	1 . 0					
9.0***	GAP RANGE LOW (GAPLO)	0 . 0					
10.0***	GAP RANGE HIGH (GAPHI)	0 . 0					
11.0***	NON-LINEAR GAIN (NLGAIN)	0 . 0					
12.0***	NON-LINEARITY FORM (NLFM)	NLFM =1	NLFM =0				
13.0*	INTEGRAL TIME (T1/IN MIN)	0 . 0					
14.0	DERIVATIVE TIME (T2/IN MIN)	0 . 0					
15.0	FEED-FORWARD TYPE (FFOPT)	ADD	MULTIPLY				
16.0	FEED-FORWARD INPUT BIAS (BFF)	0 . 0					

AM REGULATORY CONTROL PID WITH FEEDFORWARD ALGORITHM
(Continued)

AM88-656
Page 2 of 4
12/00

• AM - REGULATORY PID CONTROL FFWD ALGORITHM DISPLAY (Continued)

17.0	FEEDFORWARD INPUT GAIN (KFF)	<table border="1"><tr><td>1</td><td>.</td><td>0</td><td></td><td></td><td></td><td></td><td></td></tr></table>	1	.	0					
1	.	0								
18.0	PV TRACKING OPTION (PVTRACK)	<table border="1"><tr><td>NOTRACK</td></tr></table> TRACK	NOTRACK							
NOTRACK										

• AM - REGULATORY CONTROL INPUT CONNECTIONS DISPLAY

19.0**	NUMBER OF INPUT CONNECTIONS (NOCINPTS)	<table border="1"><tr><td>2</td></tr></table>	2
2			

20.0***	<u>INPUT CONNECTIONS</u>
---------	--------------------------

	INPUT	SOURCE POINT.PARAMETER CISRC(N)	DESTINATION PARAMETER CIDSTN(N)		ACTIVITY STATUS CIACTSTS(N)				
20.1	1	<table border="1"><tr><td></td></tr></table>		<table border="1"><tr><td>PV</td></tr></table>	PV	<table border="1"><tr><td>ACTIVE</td></tr></table>	ACTIVE	INACTIVE	NOTCONFIG
PV									
ACTIVE									
20.2	2	<table border="1"><tr><td></td></tr></table>		<table border="1"><tr><td>FF</td></tr></table>	FF	<table border="1"><tr><td>ACTIVE</td></tr></table>	ACTIVE	INACTIVE	NOTCONFIG
FF									
ACTIVE									
20.3	3	<table border="1"><tr><td></td></tr></table>		<table border="1"><tr><td></td></tr></table>		<table border="1"><tr><td>ACTIVE</td></tr></table>	ACTIVE	INACTIVE	NOTCONFIG
ACTIVE									
20.4	4	<table border="1"><tr><td></td></tr></table>		<table border="1"><tr><td></td></tr></table>		<table border="1"><tr><td>ACTIVE</td></tr></table>	ACTIVE	INACTIVE	NOTCONFIG
ACTIVE									
20.5	5	<table border="1"><tr><td></td></tr></table>		<table border="1"><tr><td></td></tr></table>		<table border="1"><tr><td>ACTIVE</td></tr></table>	ACTIVE	INACTIVE	NOTCONFIG
ACTIVE									
20.6	6	<table border="1"><tr><td></td></tr></table>		<table border="1"><tr><td></td></tr></table>		<table border="1"><tr><td>ACTIVE</td></tr></table>	ACTIVE	INACTIVE	NOTCONFIG
ACTIVE									
20.7	7	<table border="1"><tr><td></td></tr></table>		<table border="1"><tr><td></td></tr></table>		<table border="1"><tr><td>ACTIVE</td></tr></table>	ACTIVE	INACTIVE	NOTCONFIG
ACTIVE									
20.8	8	<table border="1"><tr><td></td></tr></table>		<table border="1"><tr><td></td></tr></table>		<table border="1"><tr><td>ACTIVE</td></tr></table>	ACTIVE	INACTIVE	NOTCONFIG
ACTIVE									

AM REGULATORY CONTROL PID WITH FEEDFORWARD ALGORITHM
(Continued)

AM88-656
Page 3 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

30.0** NUMBER OF OUTPUT CONNECTIONS (NOCOPTS) 1

31.0*** OUTPUT CONNECTIONS

OUTPUT		DESTINATION POINT_ID.PARAMETER CODSTN(N)	CONNECTION ACTIVITY STATUS COACTSTS(N)		
31.1	1		ACTIVE	INACTIVE	NOTCONFIG
31.2	2		ACTIVE	INACTIVE	NOTCONFIG
31.3	3		ACTIVE	INACTIVE	NOTCONFIG
31.4	4		ACTIVE	INACTIVE	NOTCONFIG
31.5	5		ACTIVE	INACTIVE	NOTCONFIG
31.6	6		ACTIVE	INACTIVE	NOTCONFIG
31.7	7		ACTIVE	INACTIVE	NOTCONFIG
31.8	8		ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY CONTROL PID WITH FEEDFORWARD ALGORITHM
(Continued)

AM88-656
Page 4 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

32.0***	CV ENGINEERING UNITS HIGH (CVEUHI)	1 0 0 . 0
33.0***	CV ENGINEERING UNITS LOW (CVEULO)	0 . 0
34.0***	CONTROL OUTPUT (OP)	0 . 0
35.0	OP HIGH LIMIT VALUE IN % (OPHILM)	1 0 5 . 0
36.0	OP LOW LIMIT VALUE IN % (OPLOLM)	- 5 . 0
37.0	OP MINIMUM CHANGE IN % (OPMCHLM)	0 . 0
38.0	OP ROC LIMIT IN %/MIN (OPROCLM)	- - - - - -
39.0	OP TOLERANCE IN % (\$OPTOL)	0 . 0

• AM - REGULATORY CONTROL INCR/SUM ALGORITHM DISPLAY

1.0	INITIALIZATION TYPE (INITTYPE)	EXT	INT
2.0	OVERRIDE BIAS LIMIT (ORBIAS)	0	. 0
3.0**	NUMBER OF INPUTS (M)	2	
4.0	ENGR UNITS RANGE HIGH (XEUHI)	1 0 0	. 0
5.0	ENGR UNITS RANGE LOW (XEULO)	0	. 0

AM REGULATORY CONTROL INCREMENTAL SUMMER ALGORITHM
(Continued)

AM88-657
Page 2 of 4
12/00

• AM - REGULATORY CONTROL INPUT CONNECTIONS DISPLAY

20.0**	NUMBER OF INPUT CONNECTIONS (NOCINPTS)	0	CTLEQN	NOCINPTS	DEFAULT	VALUE
			A			0
			B			1

21.0*** INPUT CONNECTIONS

	INPUT	SOURCE POINT.PARAMETER CISRC(N)	DESTINATION PARAMETER CIDSTN(N)		ACTIVITY STATUS CIACTSTS(N)	
21.1	1		X2	ACTIVE	INACTIVE	NOTCONFIG
21.2	2		X3	ACTIVE	INACTIVE	NOTCONFIG
21.3	3		X4	ACTIVE	INACTIVE	NOTCONFIG
21.4	4			ACTIVE	INACTIVE	NOTCONFIG
21.5	5			ACTIVE	INACTIVE	NOTCONFIG
21.6	6			ACTIVE	INACTIVE	NOTCONFIG
21.7	7			ACTIVE	INACTIVE	NOTCONFIG
21.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY CONTROL INCREMENTAL SUMMER ALGORITHM
(Continued)

AM88-657
Page 3 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY

30.0** NUMBER OF OUTPUT CONNECTIONS (NOCOPTS) 1

31.0*** OUTPUT CONNECTIONS

OUTPUT		DESTINATION POINT_ID.PARAMETER CODSTN(N)	CONNECTION ACTIVITY STATUS COACTSTS(N)		
31.1	1		ACTIVE	INACTIVE	NOTCONFIG
31.2	2		ACTIVE	INACTIVE	NOTCONFIG
31.3	3		ACTIVE	INACTIVE	NOTCONFIG
31.4	4		ACTIVE	INACTIVE	NOTCONFIG
31.5	5		ACTIVE	INACTIVE	NOTCONFIG
31.6	6		ACTIVE	INACTIVE	NOTCONFIG
31.7	7		ACTIVE	INACTIVE	NOTCONFIG
31.8	8		ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY CONTROL INCREMENTAL SUMMER ALGORITHM
(Continued)

AM88-657
Page 4 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

32.0***	CV ENGINEERING UNITS HIGH (CVEUHI)	1 0 0 . 0
33.0***	CV ENGINEERING UNITS LOW (CVEULO)	0 . 0
34.0***	CONTROL OUTPUT (OP)	0 . 0
35.0	OP HIGH LIMIT VALUE IN % (OPHILM)	1 0 5 . 0
36.0	OP LOW LIMIT VALUE IN % (OPLOLM)	- 5 . 0
37.0	OP MINIMUM CHANGE IN % (OPMCHLM)	0 . 0
38.0	OP ROC LIMIT IN %/MIN (OPROCLM)	- - - - - -
39.0	OP TOLERANCE IN % (\$OPTOL)	0 . 0

AM REGULATORY CONTROL AUTO/MANUAL ALGORITHM

AM88-658
Page 1 of 4
12/00

• AM - REGULATORY CONTROL AUTO/MANUAL ALGORITHM DISPLAY

1.0	INITIALIZATION TYPE (INITTYPE)	EXT	INT	NONE					
2.0	OUTPUT BIAS (B)	0	.	0					
3.0**	RAMP RATE FOR OUTPUT BIAS (RATE 1)	0	.	0					
4.0	ENGR UNITS RANGE HIGH (XEUHI)	1	0	0	.	0			
5.0	ENGR UNITS RANGE LOW (XEULO)	0	.	0					

AM REGULATORY CONTROL AUTO/MANUAL ALGORITHM
(Continued)

AM88-658
Page 2 of 4
12/00

• AM - REGULATORY CONTROL AUTO/MANUAL ALGORITHM DISPLAY (Continued)

6.0** NUMBER OF CONTROL INPUT CONNECTIONS (NOCINPTS)

7.0*** INPUT CONNECTIONS

	INPUT	SOURCE POINT.PARAMETER CISRC(N)	DESTINATION PARAMETER CIDSTN(N)		ACTIVITY STATUS CIACTSTS(N)	
7.1	1		X1	ACTIVE	INACTIVE	NOTCONFG
7.2	2			ACTIVE	INACTIVE	NOTCONFG
7.3	3			ACTIVE	INACTIVE	NOTCONFG
7.4	4			ACTIVE	INACTIVE	NOTCONFG
7.5	5			ACTIVE	INACTIVE	NOTCONFG
7.6	6			ACTIVE	INACTIVE	NOTCONFG
7.7	7			ACTIVE	INACTIVE	NOTCONFG
7.8	8			ACTIVE	INACTIVE	NOTCONFG

AM REGULATORY CONTROL AUTO/MANUAL ALGORITHM
(Continued)

AM88-658
Page 3 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

10.0** NUMBER OF OUTPUT CONNECTIONS (NOCOPTS) 1

11.0*** OUTPUT CONNECTIONS

	OUTPUT	DESTINATION POINT_ID.PARAMETER CODSTN(N)	CONNECTION ACTIVITY STATUS COACTSTS(N)		
11.1	1		ACTIVE	INACTIVE	NOTCONFIG
11.2	2		ACTIVE	INACTIVE	NOTCONFIG
11.3	3		ACTIVE	INACTIVE	NOTCONFIG
11.4	4		ACTIVE	INACTIVE	NOTCONFIG
11.5	5		ACTIVE	INACTIVE	NOTCONFIG
11.6	6		ACTIVE	INACTIVE	NOTCONFIG
11.7	7		ACTIVE	INACTIVE	NOTCONFIG
11.8	8		ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY CONTROL AUTO/MANUAL ALGORITHM
(Continued)

AM88-658
Page 4 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

12.0***	CV ENGINEERING UNITS HIGH (CVEUHI)	1 0 0 . 0
13.0***	CV ENGINEERING UNITS LOW (CVEULO)	0 . 0
14.0***	CONTROL OUTPUT (OP)	0 . 0
15.0	OP HIGH LIMIT VALUE IN % (OPHILM)	1 0 5 . 0
16.0	OP LOW LIMIT VALUE IN % (OPLOLM)	- 5 . 0
17.0	OP MINIMUM CHANGE IN % (OPMCHLM)	0 . 0
18.0	OP ROC LIMIT IN %/MIN (OPROCLM)	- - - - - -
19.0	OP TOLERANCE IN % (\$OPTOL)	0 . 0

AM REGULATORY CONTROL RATIO ALGORITHM

AM88-659
Page 1 of 4
12/00

• AM - REGULATORY CONTROL RATIO ALGORITHM DISPLAY

1.0	INITIALIZATION TYPE (INITTYPE)	EXT	INT	NONE					
2.0	BIAS CONSTANT ONE (B1)	0	.	0					
3.0**	BIAS CONSTANT TWO (B2)	0	.	0					
4.0	GAIN CONSTANT ONE (K1)	1	.	0					
5.0	GAIN CONSTANT TWO (K2)	1	.	0					

AM88-659
Page 2 of 4
12/00

6.0**	NUMBER OF CONTROL INPUT CONNECTIONS (NOCINPTS)	1
-------	--	---

	INPUT	SOURCE POINT .PARAMETER CISRC(N)	DESTINATION PARAMETER CIDSTN(N)		ACTIVITY STATUS CIACTSTS(N)	
7.1	1		X2	ACTIVE	INACTIVE	NOTCONFIG
7.2	2			ACTIVE	INACTIVE	NOTCONFIG
7.3	3			ACTIVE	INACTIVE	NOTCONFIG
7.4	4			ACTIVE	INACTIVE	NOTCONFIG
7.5	5			ACTIVE	INACTIVE	NOTCONFIG
7.6	6			ACTIVE	INACTIVE	NOTCONFIG
7.7	7			ACTIVE	INACTIVE	NOTCONFIG
7.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY CONTROL RATIO ALGORITHM
(Continued)

AM88-659
Page 3 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY

20.0** NUMBER OF OUTPUT CONNECTIONS (NOCOPTS) 1

21.0*** OUTPUT CONNECTIONS

	OUTPUT	DESTINATION POINT_ID.PARAMETER CODSTN(N)	CONNECTION ACTIVITY COACTSTS(N)	STATUS
21.1	1		ACTIVE	INACTIVE NOTCONFIG
21.2	2		ACTIVE	INACTIVE NOTCONFIG
21.3	3		ACTIVE	INACTIVE NOTCONFIG
21.4	4		ACTIVE	INACTIVE NOTCONFIG
21.5	5		ACTIVE	INACTIVE NOTCONFIG
21.6	6		ACTIVE	INACTIVE NOTCONFIG
21.7	7		ACTIVE	INACTIVE NOTCONFIG
21.8	8		ACTIVE	INACTIVE NOTCONFIG

AM REGULATORY CONTROL RATIO ALGORITHM
(Continued)

AM88-659
Page 4 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

22.0***	CV ENGINEERING UNITS HIGH (CVEUHI)	1	0	0	.	0				
23.0***	CV ENGINEERING UNITS LOW (CVEULO)	0	.	0						
24.0***	CONTROL OUTPUT (OP)	0	.	0						
25.0	OP HIGH LIMIT VALUE IN % (OPHILM)	1	0	5	.	0				
26.0	OP LOW LIMIT VALUE IN % (OPLOLM)	-	5	.	0					
27.0	OP MINIMUM CHANGE IN % (OPMCHLM)	0	.	0						
28.0	OP ROC LIMIT IN %/MIN (OPROCLM)	-	-	-	-	-	-			
29.0	OP TOLERANCE IN % (\$OPTOL)	0	.	0						

AM REGULATORY CONTROL OVERRIDE SELECTOR ALGORITHM

AM88-661
Page 1 of 4
12/00

• AM - REGULATORY CONTROL OVER/SEL ALGORITHM DISPLAY

1.0	ALGORITHM EQUATION TYPE (CTLEQN)	EQA	EQB	<u>INITTYPE</u>
2.0**	INITIALIZATION TYPE (INITTYPE)	EXT	NONE	
3.0	NUMBER OF INPUTS (M)	2		All
4.0**	OVERRIDE OPTION (OROPT)	OFF	ON	EXT
5.0	ENGINEERING UNITS RANGE HIGH (XEUHI)	1 0 0 . 0		All
6.0	ENGINEERING UNITS RANGE LOW (XEULO)	0 . 0		All

AM REGULATORY CONTROL OVERRIDE SELECTOR ALGORITHM
(Continued)

AM88-661
Page 2 of 4
12/00

• AM - REGULATORY CONTROL OVER/SEL ALGORITHM DISPLAY (Continued)

7.0** NUMBER OF CONTROL INPUT CONNECTIONS (NOCINPTS)

8.0*** INPUT CONNECTIONS

	INPUT	SOURCE POINT.PARAMETER CISRC(N)	DESTINATION PARAMETER CIDSTN(N)		ACTIVITY STATUS CIACTSTS(N)	
8.1	1			ACTIVE	INACTIVE	NOTCONFIG
8.2	2			ACTIVE	INACTIVE	NOTCONFIG
8.3	3			ACTIVE	INACTIVE	NOTCONFIG
8.4	4			ACTIVE	INACTIVE	NOTCONFIG
8.5	5			ACTIVE	INACTIVE	NOTCONFIG
8.6	6			ACTIVE	INACTIVE	NOTCONFIG
8.7	7			ACTIVE	INACTIVE	NOTCONFIG
8.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY CONTROL OVERRIDE SELECTOR ALGORITHM
(Continued)

AM88-661
Page 3 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY

20.0** NUMBER OF OUTPUT CONNECTIONS (NOCOPTS) 1

21.0*** OUTPUT CONNECTIONS

	OUTPUT	DESTINATION POINT_ID.PARAMETER CODSTN(N)	CONNECTION ACTIVITY STATUS COACTSTS(N)
21.1	1		ACTIVE INACTIVE NOTCONFIG
21.2	2		ACTIVE INACTIVE NOTCONFIG
21.3	3		ACTIVE INACTIVE NOTCONFIG
21.4	4		ACTIVE INACTIVE NOTCONFIG
21.5	5		ACTIVE INACTIVE NOTCONFIG
21.6	6		ACTIVE INACTIVE NOTCONFIG
21.7	7		ACTIVE INACTIVE NOTCONFIG
21.8	8		ACTIVE INACTIVE NOTCONFIG

AM REGULATORY CONTROL OVERRIDE SELECTOR ALGORITHM
(Continued)

AM88-661
Page 4 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

22.0***	CV ENGINEERING UNITS HIGH (CVEUHI)	1 0 0 . 0
23.0***	CV ENGINEERING UNITS LOW (CVEULO)	0 . 0
24.0***	CONTROL OUTPUT (OP)	0 . 0
25.0	OP HIGH LIMIT VALUE IN % (OPHILM)	1 0 5 . 0
26.0	OP LOW LIMIT VALUE IN % (OPLOLM)	- 5 . 0
27.0	OP MINIMUM CHANGE IN % (OPMCHL)	0 . 0
28.0	OP ROC LIMIT IN %/MIN (OPROCLM)	- - - - - -
29.0	OP TOLERANCE IN % (\$OPTOL)	0 . 0

AM REGULATORY CONTROL SWITCH ALGORITHM

AM88-662
Page 1 of 4
12/00

• AM - REGULATORY CONTROL SWITCH ALGORITHM DISPLAY

1.0	ALGORITHM EQUATION TYPE (CTLEQN)	EQA	EQB
2.0**	INITIALIZATION TYPE (INITTYPE)	EXT	NONE
3.0	NUMBER OF INPUTS (M)	2	
4.0	ENGINEERING UNITS RANGE HIGH (XEUHI)	1 0 0 . 0	
5.0	ENGINEERING UNITS RANGE LOW (XEULO)	0 . 0	
6.0	TRACKING OPTION (TRACKING)	OFF	ON

AM88-662
Page 2 of 4
12/00

7.0**	NUMBER OF CONTROL INPUT CONNECTIONS (NOCINPTS)	0
-------	--	---

	INPUT	SOURCE POINT . PARAMETER CISRC(N)	DESTINATION PARAMETER CIDSTN(N)		ACTIVITY STATUS CIACTSTS(N)	
8.1	1			ACTIVE	INACTIVE	NOTCONFIG
8.2	2			ACTIVE	INACTIVE	NOTCONFIG
8.3	3			ACTIVE	INACTIVE	NOTCONFIG
8.4	4			ACTIVE	INACTIVE	NOTCONFIG
8.5	5			ACTIVE	INACTIVE	NOTCONFIG
8.6	6			ACTIVE	INACTIVE	NOTCONFIG
8.7	7			ACTIVE	INACTIVE	NOTCONFIG
8.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM88-662
Page 3 of 4
12/00

20.0**	NUMBER OF OUTPUT CONNECTIONS (NOCOPTS)	1
--------	--	---

	OUTPUT	DESTINATION_POINT_ID.PARAMETER CODSTN(N)	CONNECTION_ACTIVITY COACTSTS(N)	STATUS	
21.1	1		ACTIVE	INACTIVE	NOTCONFIG
21.2	2		ACTIVE	INACTIVE	NOTCONFIG
21.3	3		ACTIVE	INACTIVE	NOTCONFIG
21.4	4		ACTIVE	INACTIVE	NOTCONFIG
21.5	5		ACTIVE	INACTIVE	NOTCONFIG
21.6	6		ACTIVE	INACTIVE	NOTCONFIG
21.7	7		ACTIVE	INACTIVE	NOTCONFIG
21.8	8		ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY CONTROL SWITCH ALGORITHM
(Continued)

AM88-662
Page 4 of 4
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

22.0***	CV ENGINEERING UNITS HIGH (CVEUHI)	1	0	0	.	0				
23.0***	CV ENGINEERING UNITS LOW (CVEULO)	0	.	0						
24.0***	CONTROL OUTPUT (OP)	0	.	0						
25.0	OP HIGH LIMIT VALUE IN % (OPHILM)	1	0	5	.	0				
26.0	OP LOW LIMIT VALUE IN % (OPLOLM)	-	5	.	0					
27.0	OP MINIMUM CHANGE IN % (OPMCHL)	0	.	0						
28.0	OP ROC LIMIT IN %/MIN (OPROCLM)	-	-	-	-	-	-			
29.0	OP TOLERANCE IN % (\$OPTOL)	0	.	0						

AM REGULATORY CONTROL RAMPSOAK ALGORITHM

AM88-663
Page 1 of 6
12/00

• AM - REGULATORY RAMP/SOAK CONTROL ALGORITHM DISPLAY

1.0 INITIALIZATION TYPE (INITTYPE)

EXT

INT

2.0 MAX RAMP DEVIATION (MXRMPDEV)

- - - - -

3.0 MAX SOAK DEVIATION (MXSOKDEV)

0 . 0

4.0 NUMBER OF RAMP/SOAK PAIRS (NORSSEQ)

2

5.0***

RAMP RATES AND SOAK TIMES/VALUES

PAIR NUMBER

RAMP RATE (RATEX)

SOAK DURATION (SOAKTX)

SOAK VALUE (SOAKVX)

5.1	1											0	.	0															
5.2	2											0	.	0															
5.3	3											0	.	0															
5.4	4											0	.	0															
5.5	5											0	.	0															
5.6	6											0	.	0															

AM REGULATORY CONTROL RAMPSOAK ALGORITHM
(Continued)

AM88-663
Page 2 of 6
12/00

• AM - REGULATORY RAMP/SOAK CONTROL ALGORITHM DISPLAY (Continued)

6.0***

TIME MARK 1

	SEGMENT ID (S1SEGID)	BEGIN TIME (S1BGNTIM)	END TIME (S1ENDTIM)
6.1	RAMP1 SOAK1	0 . 0	0 . 0
6.2	RAMP2 SOAK2		
6.3	RAMP3 SOAK3		
6.4	RAMP4 SOAK4		
6.5	RAMP5 SOAK5		
6.6	RAMP6 SOAK6		

AM REGULATORY CONTROL RAMPSOAK ALGORITHM
(Continued)

AM88-663
Page 3 of 6
12/00

• AM - REGULATORY RAMP/SOAK CONTROL ALGORITHM DISPLAY (Continued)

7.0***

TIME MARK 2

	SEGMENT ID (S2SEGID)	BEGIN TIME (S2BGNTIM)	END TIME (S2ENDTIM)
7.1	RAMP1 SOAK1	0 . 0	0 . 0
7.2	RAMP2 SOAK2		
7.3	RAMP3 SOAK3		
7.4	RAMP4 SOAK4		
7.5	RAMP5 SOAK5		
7.6	RAMP6 SOAK6		

AM REGULATORY CONTROL RAMPSOAK ALGORITHM
(Continued)

AM88-663
Page 4 of 6
12/00

• AM - REGULATORY RAMP/SOAK CONTROL ALGORITHM DISPLAY (Continued)

8.0** NUMBER OF CONTROL INPUT CONNECTIONS (NOCINPTS) 0

9.0*** INPUT CONNECTIONS

	INPUT	SOURCE POINT.PARAMETER CISRC(N)	DESTINATION PARAMETER CIDSTN(N)		ACTIVITY STATUS CIACTSTS(N)	
9.1	1			ACTIVE	INACTIVE	NOTCONFG
9.2	2			ACTIVE	INACTIVE	NOTCONFG
9.3	3			ACTIVE	INACTIVE	NOTCONFG
9.4	4			ACTIVE	INACTIVE	NOTCONFG
9.5	5			ACTIVE	INACTIVE	NOTCONFG
9.6	6			ACTIVE	INACTIVE	NOTCONFG
9.7	7			ACTIVE	INACTIVE	NOTCONFG
9.8	8			ACTIVE	INACTIVE	NOTCONFG

AM REGULATORY CONTROL RAMPSOAK ALGORITHM
(Continued)

AM88-663
Page 5 of 6
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY

20.0** NUMBER OF OUTPUT CONNECTIONS (NOCOPTS) 1

21.0*** OUTPUT CONNECTIONS

	OUTPUT	DESTINATION POINT_ID.PARAMETER CODSTN(N)	CONNECTION ACTIVITY STATUS COACTSTS(N)
21.1	1		ACTIVE INACTIVE NOTCONFIG
21.2	2		ACTIVE INACTIVE NOTCONFIG
21.3	3		ACTIVE INACTIVE NOTCONFIG
21.4	4		ACTIVE INACTIVE NOTCONFIG
21.5	5		ACTIVE INACTIVE NOTCONFIG
21.6	6		ACTIVE INACTIVE NOTCONFIG
21.7	7		ACTIVE INACTIVE NOTCONFIG
21.8	8		ACTIVE INACTIVE NOTCONFIG

AM REGULATORY CONTROL RAMPSOAK ALGORITHM
(Continued)

AM88-663
Page 6 of 6
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

22.0***	CV ENGINEERING UNITS HIGH (CVEUHI)	<table border="1"><tr><td>1</td><td>0</td><td>0</td><td>.</td><td>0</td><td></td><td></td><td></td></tr></table>	1	0	0	.	0			
1	0	0	.	0						
23.0***	CV ENGINEERING UNITS LOW (CVEULO)	<table border="1"><tr><td>0</td><td>.</td><td>0</td><td></td><td></td><td></td><td></td><td></td></tr></table>	0	.	0					
0	.	0								
24.0***	CONTROL OUTPUT (OP)	<table border="1"><tr><td>0</td><td>.</td><td>0</td><td></td><td></td><td></td><td></td><td></td></tr></table>	0	.	0					
0	.	0								
25.0	OP HIGH LIMIT VALUE IN % (OPHILM)	<table border="1"><tr><td>1</td><td>0</td><td>5</td><td>.</td><td>0</td><td></td><td></td><td></td></tr></table>	1	0	5	.	0			
1	0	5	.	0						
26.0	OP LOW LIMIT VALUE IN % (OPLOLM)	<table border="1"><tr><td>-</td><td>5</td><td>.</td><td>0</td><td></td><td></td><td></td><td></td></tr></table>	-	5	.	0				
-	5	.	0							
27.0	OP MINIMUM CHANGE IN % (OPMCHLM)	<table border="1"><tr><td>0</td><td>.</td><td>0</td><td></td><td></td><td></td><td></td><td></td></tr></table>	0	.	0					
0	.	0								
28.0	OP ROC LIMIT IN %/MIN (OPROCLM)	<table border="1"><tr><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td><td></td><td></td></tr></table>	-	-	-	-	-	-		
-	-	-	-	-	-					
29.0	OP TOLERANCE IN % (\$OPTOL)	<table border="1"><tr><td>0</td><td>.</td><td>0</td><td></td><td></td><td></td><td></td><td></td></tr></table>	0	.	0					
0	.	0								

AM REGULATORY CONTROL CL ALGORITHM

AM88-664
Page 1 of 3
12/00

• AM – REGULATORY CONTROL CL ALGORITHM DISPLAY

1.0	TYPE OF CV (CVTYPE)	ENGUNITS	PERCENT	
2.0	INITIALIZATION TYPE (INITTYPE)	EXT	INT	NONE
3.0	ANTI-RESET WINDUP DIRECTION (ARWDI)	DIRECT	REVERSE	

AM88-664
Page 2 of 3
12/00

10.0**	NUMBER OF OUTPUT CONNECTIONS (NOCOPTS)	1
--------	--	---

	OUTPUT	DESTINATION_POINT_ID.PARAMETER CODSTN(N)	CONNECTION_ACTIVITY COACTSTS(N)	STATUS	
11.1	1		ACTIVE	INACTIVE	NOTCONFIG
11.2	2		ACTIVE	INACTIVE	NOTCONFIG
11.3	3		ACTIVE	INACTIVE	NOTCONFIG
11.4	4		ACTIVE	INACTIVE	NOTCONFIG
11.5	5		ACTIVE	INACTIVE	NOTCONFIG
11.6	6		ACTIVE	INACTIVE	NOTCONFIG
11.7	7		ACTIVE	INACTIVE	NOTCONFIG
11.8	8		ACTIVE	INACTIVE	NOTCONFIG

AM REGULATORY CONTROL CL ALGORITHM_
(Continued)

AM88-664
Page 3 of 3
12/00

• AM - REGULATORY CONTROL OUTPUT CONNECTIONS DISPLAY (Continued)

12.0***	CV ENGINEERING UNITS HIGH (CVEUHI)	1 0 0 . 0
13.0***	CV ENGINEERING UNITS LOW (CVEULO)	0 . 0
14.0***	CONTROL OUTPUT (OP)	0 . 0
15.0	OP HIGH LIMIT VALUE IN % (OPHILM)	1 0 5 . 0
16.0	OP LOW LIMIT VALUE IN % (OPLOLM)	- 5 . 0
17.0	OP MINIMUM CHANGE IN % (OPMCHLM)	0 . 0
18.0	OP ROC LIMIT IN %/MIN (OPROCLM)	_ _ _ _ _ _
19.0	OP TOLERANCE IN % (\$OPTOL)	0 . 0

AM REGULATORY ALARMING AND DISTRIBUTION

AM88-670
Page 1 of 5
09/08

• AM - REGULATORY ALARMING DISPLAY

1.0	PV ALARM DEADBAND IN % (PVALDB)	HALF	ONE	TWO	THREE
		FOUR	FIVE	EU	
1.1	ALARM DEADBAND IN ENG. UNITS (PVALDBEU)	1	.	0	
2.0	PV ALARM HIGH TRIP POINT (PVHITP)				
3.0	PV ALARM LOW TRIP POINT (PVLOTP)				
4.0*	PV ALARM HIGH HIGH TRIP POINT (PVHHTP)				
5.0*	PV ALARM LOW LOW TRIP POINT (PVLLTP)				
6.0*	PV ROC POSITIVE TRIP POINT (PVROCPTP)				
7.0*	PV ROC NEGATIVE TRIP POINT (PVROCNTP)				
8.0*	PV SIG.CHANGE TRIP POINT (PVSGCHTP)				
9.0*	DEV ALARM HIGH TRIP POINT (DEVHITP)				
10.0*	DEV ALARM LOW TRIP POINT (DEVLOTP)				

AM REGULATORY ALARMING AND DISTRIBUTION
(Continued)

AM88-670
Page 2 of 5
09/08

• AM - REGULATORY ALARMING DISPLAY (Continued)

11.0	ALARM ENABLE STATE (ALENBST)	☒ ENABLE	☐ DISABLE	☐ INHIBIT
11.1	AUXILIARY UNIT (\$AUXUNIT)	☐ - ☐ -		
11.2	MULTIPLE PRIMMOD#1 (\$MPROD1)	☐	☐	☐
11.3	MULTIPLE PRIMMOD#2 (\$MPROD2)	☐	☐	☐
11.4	MULTIPLE PRIMMOD#3 (\$MPROD3)	☐	☐	☐
11.5	MULTIPLE PRIMMOD#4 (\$MPROD4)	☐	☐	☐
11.6	RE-ALARMING INTERVAL (\$REALARM)	☐ 0	☐ 0	☐ 0

AM REGULATORY ALARMING AND DISTRIBUTION
(Continued)

AM88-670
Page 3 of 5
09/08

• AM - REGULATORY-ALARMING DISPIAY (Continued)

12.0		<u>SEPARATE ALARM PRIORITIES</u>			
12.1	ADVISORY-DEVIATION (ADVDEVPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
12.2	BAD-CONTROL (BADCTLPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRNTNT	HIGH
12.3	BAD PV (BADPVPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
12.4	BACKGROUND CL ERROR (BCLEALPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
12.5	BACKGROUND CL FATAL ERROR (BCLFALPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
12.6	CL ERROR (CLEALMPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
12.7	CL FATAL ERROR (CLFALMPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
12.8	CONFIGURATION ERROR (CNFERRPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH

AM REGULATORY ALARMING AND DISTRIBUTION
(Continued)

AM88-670
Page 4 of 5
09/08

• AM - REGULATORY ALARMING DISPLAY (Continued)

12.9	DEVIATION HIGH (DEVHIPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
12.9A	DV HIGH SELECTIVE CUTOUT (\$DHSELCT)	CUTOUT	ALLOW		
12.10	DEVIATION LOW (DEVLOPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
12.10A	DV LOW SELECTIVE CUTOUT (\$DLSELCT)	CUTOUT	ALLOW		
12.11	PV HIGH HIGH (PVHHPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
12.11A	PV HIGH HIGH SELECTIVE CUTOUT (\$HHSELCT)	CUTOUT	ALLOW		
12.12	PV HIGH (PVHIPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
12.12A	PV HIGH SELECTIVE CUTOUT (\$HISELCT)	CUTOUT	ALLOW		
12.13	PV LOW LOW (PVLLPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
12.13A	PV LOW LOW SELECTIVE CUTOUT (\$LLSELCT)	CUTOUT	ALLOW		
12.14	PV LOW (PVLOPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
12.14A	PV LOW SELECTIVE CUTOUT (\$LOSELCT)	CUTOUT	ALLOW		
12.15	PV NEGATIVE RATE OF CHANGE (PVROCNPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
12.15A	PV NEGATIVE RATE OF CHANGE SELECTIVE CUTOUT (\$RNSELCT)	CUTOUT	ALLOW		

AM REGULATORY ALARMING AND DISTRIBUTION
(Continued)

AM88-670
Page 5 of 5
09/08

• AM - REGULATORY ALARMING DISPLAY (Continued)

12.16	PV POSITIVE RATE OF CHANGE (PVROCPPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
12.16A	PV POSITIVE RATE OF CHANGE SELECTIVE CUTOUT (\$RPSELECT)	CUTOUT	ALLOW		
12.17	SIGNIFICANT PV CHANGE (PVSGCHPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRIN T	HIGH
13.0*	CONTACT CUTOUT INPUT OPTION (CCINPT)	NO		YES**	
14.0***		<u>CONTACT CUTOUT CONNECTION</u>			

SOURCE POINT_ID.PARAMETER
(CCSRC)

CONNECTION ACTIVITY STATUS
CCACTSTS

	ACTIVE	INACTIVE	NOTCONFIG
--	--------	----------	-----------

GENERAL INPUT/OUTPUT CONNECTIONS AND CUSTOM DATA SEGMENTS

AM88-680
Page 1 of 5
12/00

***Fill in this form only with full disclosure selected on AM88-601.**

• AM - REGULATORY GENERAL 1/0 AND CUSTOM

1.0	NUMBER OF ASSOCIATED CL BLOCKS (CLSLOTS)	0
2.0**	NUMBER OF CUSTOM DATA PACKAGES (NOPKG)	0
3.0**	NUMBER OF SWITCHES (NUMSWITCH)	0
4.0**	NUMBER OF GENERAL INPUTS (NOGINPTS)	0
5.00**	NUMBER OF GENERAL OUTPUTS (NOGOPTS)	0

• AM - REGULATORY CUSTOM PACKAGE DISPLAY

10.0	CUSTOM DATA PACKAGE SOURCE FILE NAMES									
10.1	SOURCE FILE 1 NAME (PKGNAME [1])									
10.2	SOURCE FILE 2 NAME (PKGNAME [2])									
10.3	SOURCE FILE 3 NAME (PKGNAME [3])									
10.4	SOURCE FILE 4 NAME (PKGNAME [4])									
10.5	SOURCE FILE 5 NAME (PKGNAME [5])									
10.6	SOURCE FILE 6 NAME (PKGNAME [6])									
10.7	SOURCE FILE 7 NAME (PKGNAME [7])									
10.8	SOURCE FILE 8 NAME (PKGNAME [8])									
10.9	SOURCE FILE 9 NAME (PKGNAME [9])									
10.10	SOURCE FILE 10 NAME (PKGNAME [10])									

GENERAL INPUT/OUTPUT CONNECTIONS AND CUSTOM DATA SEGMENTS
(Continued)

AM88-680
Page 2 of 5
12/00

-
- AM - REGULATORY CUSTOM PACKAGE DISPLAY (TBS)
-

20.0

(This form is not used.)

GENERAL INPUT/OUTPUT CONNECTIONS AND CUSTOM DATA SEGMENTS
(Continued)

AM88-680
Page 3 of 5
12/00

• AM - REGULATORY SWITCH-SEGMENT DISPLAY

30.0		<u>SWITCH #1</u>									
30.1	NUMBER OF STATES (S1NSTATE)	2									
30.2	#1 STATE NAME (S1STATES (0))										
20.3	#2 STATE NAME (S1STATES (1))										
30.4	#3 STATE NAME (S1STATES (2))										
30.5	#4 STATE NAME (S1STATES (3))										
30.6	#5 STATE NAME (S1STATES (4))										
30.7	ACCESS LEVEL (S1ACCLVL)	OPERATOR		SUPERVIS		ENGINEER		PROGRAM			
30.8	INITIAL STATE (S1CURSTS)										
30.9	REQUESTED STATE (S1REQSTS)										
31.0		<u>SWITCH #2</u>									
31.1	NUMBER OF STATES (S2NSTATE)	2									
31.2	#1 STATE NAME (S2STATES 0])										
31.3	#2 STATE NAME (S2STATES 1])										
31.4	#3 STATE NAME (S2STATES 2])										
31.5	#4 STATE NAME (S2STATES 3])										
31.6	#5 STATE NAME (S2STATES 4])										
31.7	ACCESS LEVEL (S2ACCLVL)	OPERATOR		SUPERVIS		ENGINEER		PROGRAM			
31.8	INITIAL STATE (S2CURSTS)										
31.9	REQUESTED STATE (S2REQSTS)										

GENERAL INPUT/OUTPUT CONNECTIONS AND CUSTOM DATA SEGMENTS
(Continued)

AM88-680
Page 4 of 5
12/00

• AM - REGULATORY GENERAL INPUT CONNECTIONS DISPLAY

INPUT		SOURCE POINT_ID.PARAMETER GISRC(N)	DESTINATION PARAMETER GIDSTN(N)		ACTIVITY STATUS GIACTSTS(N)	
40.0	1			ACTIVE	INACTIVE	NOTCONFIG
41.0	2			ACTIVE	INACTIVE	NOTCONFIG
42.0	3			ACTIVE	INACTIVE	NOTCONFIG
43.0	4			ACTIVE	INACTIVE	NOTCONFIG
44.0	5			ACTIVE	INACTIVE	NOTCONFIG
45.0	6			ACTIVE	INACTIVE	NOTCONFIG
46.0	7			ACTIVE	INACTIVE	NOTCONFIG
47.0	8			ACTIVE	INACTIVE	NOTCONFIG

GENERAL INPUT/OUTPUT CONNECTIONS AND CUSTOM DATA SEGMENTS
(Continued)

AM88-680
Page 5 of 5
12/00

• AM - REGULATORY GENERAL OUTPUT CONNECTIONS DISPLAY

	INPUT	SOURCE PARAMETER GOSRC(N)	DESTINATION POINT_ID.PARAMETER GODSTN(N)		ACTIVITY STATUS GOACTSTS(N)	
50.0	1			ACTIVE	INACTIVE	NOTCONFG
51.0	2			ACTIVE	INACTIVE	NOTCONFG
52.0	3			ACTIVE	INACTIVE	NOTCONFG
53.0	4			ACTIVE	INACTIVE	NOTCONFG
54.0	5			ACTIVE	INACTIVE	NOTCONFG
55.0	6			ACTIVE	INACTIVE	NOTCONFG
56.0	7			ACTIVE	INACTIVE	NOTCONFG
57.0	8			ACTIVE	INACTIVE	NOTCONFG

AM FLAG DATA POINT CONFIGURATION

AM88-610
Page 1 of 2
09/08

• AM - FLAG POINT ASSIGNMENT DISPLAY

10.	TAG NAME (NAME)	
11.	UNIT ID (UNIT)	
12.	POINT DESCRIPTOR (PTDESC)	
13.	POINT KEYWORD (KEYWORD)	
14.	POINT ASSOCDSP (ASSOCDSP)	
14A.	POINT CUSTOM DISPLAY (\$CDETAIL)	Default = All Blanks
15.*	PRIMARY MODULE POINT ID (PRIMMOD)	

• AM - FLAG OPERATING CONFIGURATION DISPLAY

20.0	UPPER BOX TEXT (PVSTATES (1))	
21.0	LOWER BOX TEXT (PVSTATES (0))	
22.0	UPPER BOX COLOR (UBOXCLR)	RED GREEN WHITE BLACK CYAN YELLOW BLUE MAGENTA
23.0	LOWER BOX COLOR (LBOXCLR)	RED GREEN WHITE BLACK CYAN YELLOW BLUE MAGENTA
24.0**	OFF NORMAL ALARMING (OFFNRML)	OFF ON**

AM88-610
Page 2 of 2
09/08

[illegible]

AM NUMERIC DATA POINT CONFIGURATION

AM88-620A
Page 1 of 1
12/00

• AM - NUMERIC POINT ASSIGNMENT DISPLAY

10.	TAG NAME (NAME)	
11.	UNIT ID (UNIT)	
12.	POINT DESCRIPTOR (PTDESC)	
13.	POINT KEYWORD (KEYWORD)	
14	POINT ASSOCDSP (ASSOCDSP)	
14A.	POINT CUSTOM DISPLAY (\$CDETAIL)	Default = All Blanks
15	PRIMARY MODULE POINT ID (PRIMMOD)	

• AM - NUMERIC OPERATION CONFIGURATION DISPLAY

20.0	ENGR UNITS DESCRIPTOR (EUDESC)																	
21.0	PV RANGE HIGH (RANGEHI)																	
22.0	PV RANGE LOW (RANGELO)																	
23.0	PV DECIMAL PLACE FORMAT (PVFORMAT)	<table border="0"> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <td>D0</td> <td>D1</td> <td>D2</td> <td>D3</td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> </tr> <tr> <td>D4</td> <td>D5</td> <td>D6</td> <td></td> </tr> </table>					D0	D1	D2	D3					D4	D5	D6	
D0	D1	D2	D3															
D4	D5	D6																
24.0	PV (PV)																	

AM TIMER DATA POINT CONFIGURATION

AM88-630
Page 1 of 6
06/06

• AM - TIMER POINT ASSIGNMENT DISPLAY

10.0	TAG NAME (NAME)	
11.0	UNIT ID (UNIT)	
12.0	POINT DESCRIPTOR (PTDESC)	
13.0	ENGINEER UNITS DESCRIPTOR (EUDESC)	
14.0	POINT KEYWORD (KEYWORD)	
15.0	POINT ASSOCDSP (ASSOCDSP)	
15A.	POINT CUSTOM DISPLAY (\$CDETAIL)	Default = All Blanks
16.0	PRIMARY MODULE POINT ID (PRIMMOD)	
17.0	POINT DISCLOSURE (PTDISCL)	BRIEF FULL*

AM TIMER POINT CONFIGURATION

AM88-630
Page 2 of 6
06/06

• AM - TIMER SCHEDULING DISPLAY

20.0**	POINT ASSIGNED TO IPP (\$IPPASN)	ON	OFF		
21.0A***	POINT EXECUTION PERIOD (PERIOD) (\$IPPASN = OFF)	1 SEC	2 SEC	5 SEC	10 SEC
		15 SEC	30 SEC	1 MIN	2 MIN
		1S MIN	2S MIN	5 MIN	10 MIN
		15 MIN	30 MIN	1 HR	8 HR
		12 HR	24 HR	NOPERIOD	
21.0B***	POINT EXECUTION PERIOD (PERIOD) (\$IPPASN = ON)	5 SEC	10 SEC	15 SEC	30 SEC
		1 MIN	2 MIN	5 MIN	10 MIN
		15 MIN	30 MIN	1 HR	8 HR
		12 HR	24 HR	NOPERIOD	
22.0	BEFORE/AFTER CYCLE ASSIGNMENT (BEFAFT)	NO	BEFORE**	AFTER**	CYCLE**
23.0***	TAG NAME OF BEFORE/AFTER (BEFAFID)	_ _ _ _ _ _ _ _			
24.0***	ABSOLUTE CYCLE NUMBER (NORMCYCL)	_ _			

AM TIMER DATA POINT CONFIGURATION
(Continued)

AM88-630
Page 3 of 6
06/06

• AM - TIMER OPERATING CONFIGURATION DISPLAY

30.0	TIMER PERIOD (TIMEBASE)	SECONDS	MINUTES	HOURS
31.0	SET TIME (SP)	- - - - - -		
32.0	PERMIT OPERATOR CONTROL (CNTLLOCK)	PERMIT	NOTPERM	
33.0	PERMIT OPERATOR TO SET TIME (SPLOCK)	PERMIT	NOTPERM	
34.0**	TIME OUT ALARM (TIMOUTAL)	OFF	ON**	

AM TIMER DATA POINT CONFIGURATION
(Continued)

AM88-630
Page 4 of 6
06/06

• AM - TIMER ALARMING DISPLAY

40.0	ALARM ENABLE STATE (ALENBST)	☒ ENABLE	☐ DISABLE	☐ INHIBIT
40.1	AUXILIARY UNIT (\$AUXUNIT)	- -		
40.2	MULTIPLE PRIMMOD #1 (\$MPROD1)			
40.3	MULTIPLE PRIMMOD #2 (\$MPROD2)			
40.4	MULTIPLE PRIMMOD #3 (\$MPROD3)			
40.5	MULTIPLE PRIMMOD #4 (\$MPROD4)			
40.6	RE-ALARMING INTERVAL (\$REALARM)	0 0 0 0		
41.0	<u>SEPARATE ALARM PRIORITIES</u>			
41.1	CONFIGURATION ERROR (CNFERRPR) ALARM PRIORITY	☒ NOACTION (R670)	☐ JOURNAL	☐ LOW
		☐ EMERGNCY	☐ PRINTER	☐ JNLPRINT
41.2	TIMEOUT (TIMOUTPR) ALARM PRIORITY	☒ NOACTION (R670)	☐ JOURNAL	☐ LOW
		☐ EMERGNCY	☐ PRINTER	☐ JNLPRINT
42.0	<u>CONTACT CUTOUT CONNECTION</u>			
42.1***	CONTACT CUTOUT INPUT OPTION (CCINPT)	☒ NO	☐ YES**	
42.2***	SOURCE POINT ID.PARAMETER (CCSRC)	32.2***	CONNECTION ACTIVITY STATUS (CCACTSTS)	
		☒ ACTIVE	☐ INACTIVE	☐ NOTCONFIG

AM TIMER DATA POINT CONFIGURATION
(Continued)

AM88-630
Page 5 of 6
06/06

• AM GENERAL INPUT CONNECTIONS DISPLAY

*50.0** NUMBER OF GENERAL INPUTS (NOGINPTS)

0

51.0***

INPUT		SOURCE POINT_ID.PARAMETER GISRC(N)	DESTINATION PARAMETER GIDSTN(N)	CONNECTION ACTIVITY STATUS GIACTSTS(N)		
51.1	1			ACTIVE	INACTIVE	NOTCONFIG
51.2	2			ACTIVE	INACTIVE	NOTCONFIG
51.3	3			ACTIVE	INACTIVE	NOTCONFIG
51.4	4			ACTIVE	INACTIVE	NOTCONFIG
51.5	5			ACTIVE	INACTIVE	NOTCONFIG
51.6	6			ACTIVE	INACTIVE	NOTCONFIG
51.7	7			ACTIVE	INACTIVE	NOTCONFIG
51.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM TIMER DATA POINT CONFIGURATION
(Continued)

AM88-630
Page 6 of 6
06/06

• AM GENERAL OUTPUT CONNECTIONS DISPLAY

*60.0** NUMBER OF GENERAL OUTPUTS (NOGINPTS)

0

61.0***

		SOURCE PARAMETER GOSRC(N)	DESTINATION POINT_ID.PARAMETER GODSTN(N)	CONNECTION ACTIVITY STATUS GOACTSTS(N)		
61.1	1			ACTIVE	INACTIVE	NOTCONFIG
61.2	2			ACTIVE	INACTIVE	NOTCONFIG
61.3	3			ACTIVE	INACTIVE	NOTCONFIG
61.4	4			ACTIVE	INACTIVE	NOTCONFIG
61.5	5			ACTIVE	INACTIVE	NOTCONFIG
61.6	6			ACTIVE	INACTIVE	NOTCONFIG
61.7	7			ACTIVE	INACTIVE	NOTCONFIG
61.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM COUNTER DATA POINT CONFIGURATION

AM88-640
Page 1 of 10
09/08

• AM - COUNTER POINT ASSIGNMENT DISPLAY

10.0	TAG NAME (NAME)	
11.0	UNIT ID (UNIT)	
12.0	POINT DESCRIPTOR (PTDESC)	
13.0	ENGR UNITS DESCRIPTOR (EUDESC)	
14.0	POINT KEYWORD (KEYWORD)	
15.0	POINT ASSOCDSP (ASSOCDSP)	
15A.	POINT CUSTOM DISPLAY (\$CDETAIL)	Default = All Blanks
16.0	PRIMARY MODULE POINT ID (PRIMMOD)	Default: All Underbars
17.0	COUNTER ACCUMULATOR FUNCTIONS (ACCUM)	☐ OFF ☐ ON**
18.0	POINT DISCLOSURE (PTDISCL)	☐ BRIEF ☐ FULL*
19.0	<u>COUNTER INPUT SOURCE CONNECTION</u>	
	POINT_ID (CISRC)	CONNECTION ACTIVITY STATUS (CIACTSTS)
19.1		☐ ACTIVE ☐ INACTIVE ☐ NONCONFIG

AM COUNTER DATA POINT CONFIGURATION
(Continued)

AM88-640
Page 2 of 10
09/08

• AM - COUNTER SCHEDULING DISPLAY

20.0**	POINT EXECUTION PERIOD (\$IPPASN)	ON	OFF		
21.0A***	POINT EXECUTION PERIOD (PERIOD) (\$IPPASN = OFF)	1 SEC	2 SEC	5 SEC	10 SEC
		15 SEC	30 SEC	1 MIN	2 MIN
		1S MIN	2S MIN	5 MIN	10 MIN
		15 MIN	30 MIN	1 HR	8 HR
		12 HR	24 HR	NOPERIOD	
21.0B***	POINT EXECUTION PERIOD (PERIOD) (\$IPPASN = ON)	5 SEC	10 SEC	15 SEC	30 SEC
		1 MIN	2 MIN	5 MIN	10 MIN
		15 MIN	30 MIN	1 HR	8 HR
		12 HR	24 HR	NOPERIOD	
22.0***	BEFORE/AFTER/CYCLE ASSIGNMENT (BEFAFT)	NO	BEFORE**	AFTER**	CYCLE**
23.0***	TAG NAME OF BEFORE/AFTER (BEFAFTID)	_ _ _ _ _ _ _ _ _			
24.0***	ABSOLUTE CYCLE NUMBER (NORMCYCL)	_ _ _			

AM COUNTER DATA POINT CONFIGURATION
(Continued)

AM88-640
Page 3 of 10
09/08

• AM - COUNTER PV CONFIGURATION DISPLAY

30.0	RANGE HIGH (PVEUHI)	
31.0	RANGE LOW (PVEULO)	
32.0	RANGE EXTENSION HIGH (PVEXEUHI)	
33.0	RANGE EXTENSION LOW (PVEXEULO)	
34.0	PV AUTO EU CONVERSION FACTOR (PVCONV)	1 . 0
35.0**	SET POINT - PV TARGET VALUE (PVTV)	**See lines 46 and 47
36.0	DECIMAL PLACE FORMAT (PVFORMAT)	D0 D1 D2 D3 D4 D5 D6
37.0	CLAMPING OPTION (PVCLAMP)	CLAMP NO CLAMP
38.0**	PV SOURCE OPTIONS (PVSRCOPT)	ONLY AUTO ALL **
39.0	PV SOURCE (PVSOURCE)	AUTO MAN SUB
40.0	OVERVIEW VALUE (OVERVAL)	2 5

AM COUNTER DATA POINT CONFIGURATION
(Continued)

AM88-640
Page 4 of 10
09/08

• AM - COUNTER PV ALARMING DISPLAY

50.0**	PV ALARM HIGH ALARM TRIP POINT (PVHITP)	
51.0**	PV ALARM LOW ALARM TRIP POINT (PVLOTP)	
52.0	PV RATE OF CHANGE (+) ALARM TRIP POINT (PVROCPTP)	
53.0	RATE OF CHANGE(-) ALARM TRIP POINT (PVROCNTP)	
54.0***	PV HIGH HIGH ALARM TRIP POINT (PVHHTP)	
55.0***	PV LOW LOW ALARM TRIP POINT (PVLLTP)	
56.0***	PV DEVIATION HIGH ALARM TRIP POINT (DEVHITP)	
57.0***	PV DEVIATION LOW ALARM TRIP POINT (DEVLOTP)	
58.0***	PV SIGNIFICANT CHANGE ALARM TRIP POINT (PVSGCHTP)	

AM COUNTER DATA POINT CONFIGURATION
(Continued)

AM88-640
Page 5 of 10
09/08

• AM - COUNTER ALARM CONFIGURATION DISPLAY

60.0	PV ALARM DEADBAND IN % (PVALDB)	HALF	ONE	TWO	THREE
		FOUR	FIVE	EU	
60.1	PV ALARM DEADBAND IN ENG. UNITS (PVALDBEU)	1 . 0			
61.0	ALARM ENABLE STATE (ALENBST)	ENABLE	DISABLE	INHIBIT	
61.1	AUXILIARY UNIT (\$AUXUNIT)	- -			
61.2	MULTIPLE PRIMMOD #1 (\$MPROD1)				
61.3	MULTIPLE PRIMMOD #2 (\$MPROD2)				
61.4	MULTIPLE PRIMMOD #3 (\$MPROD3)				
61.5	MULTIPLE PRIMMOD #4 (\$MPROD4)				
61.6	RE-ALARMING INTERVAL (\$REALARM)	0 0 0 0			

AM COUNTER DATA POINT CONFIGURATION
(Continued)

AM88-640
Page 6 of 10
09/08

• AM - COUNTER ALARM CONFIGURATION DISPLAY

60.0	PV ALARM DEADBAND IN % (PVALDB)	HALF	ONE	TWO	THREE
		FOUR	FIVE	EU	
60.1	PV ALARM DEADBAND IN ENG. UNITS (PVALDBEU)	1 . 0			
61.0	ALARM ENABLE STATE (ALENBST)	ENABLE	DISABLE	INHIBIT	
62.0	<u>SEPARATE ALARM PRIORITIES</u>				
62.1	BAD CONTROL (BADCTLPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
62.2	BAD PV (BADPVPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
62.3	CONFIGURATION ERROR (CNFERRPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
62.4	DEVIATION HIGH (DEVHIPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
62.4A	DEVIATION HIGH SELECTIVE CUTOUT (\$DHSELCT)	CUTOUT	ALLOW		
62.5	DEVIATION LOW (DEVLOPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
62.5A	DEVIATION LOW SELECTIVE CUTOUT (\$DLSELCT)	CUTOUT	ALLOW		

AM COUNTER DATA POINT CONFIGURATION
(Continued)

AM88-640
Page 7 of 10
09/08

• AM - COUNTER ALARM CONFIGURATION DISPLAY

62.6	PRE-PRE-PRESET (PPRSTPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
62.7	PRESET (PRESETPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
62.8	PRE-PRESET (PRPRSTPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
62.9	PV HIGH HIGH (PVHHPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
62.9A	PV HIGH HIGH SELECTIVE CUTOUT (\$HHSELECT)	CUTOUT	ALLOW		
62.10	PV HIGH (PVHIPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
62.10A	PV HIGH SELECTIVE CUTOUT (\$HISELECT)	CUTOUT	ALLOW		
62.11	PV LOW LOW (PVLLPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
62.11A	PV LOW LOW SELECTIVE CUTOUT (\$LLSELECT)	CUTOUT	ALLOW		

AM COUNTER DATA POINT CONFIGURATION
(Continued)

AM88-640
Page 8 of 10
09/08

• AM - COUNTER ALARM CONFIGURATION DISPLAY

62.12	PV LOW (PVL0PR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
62.12A	PV LOW SELECTIVE CUTOFF (\$LOSELCT)	CUTOFF	ALLOW		
62.13	PV NEGATIVE RATE OF CHANGE (PVROCNPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
62.13A	PV NEGATIVE RATE OF CHANGE SELECTIVE CUTOFF (\$RNSELCT)	CUTOFF	ALLOW		
62.14	PV POSITIVE RATE OF CHANGE (PVROCPPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
62.14A	PV POSITIVE RATE OF CHANGE SELECTIVE CUTOFF (\$RPSELCT)	CUTOFF	ALLOW		
62.15	SIGNIFICANT PV CHANGE (PVSGCHPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH

63.0 CONTACT CUTOFF CONNECTION

63.1**	CONTACT CUTOFF INPUT OPTION (CCINPT)	NO	YES		
	SOURCE POINT_ID.PARAMETER (CCSRC)		CONNECTION ACTIVITY STATUS (CCACTSTS)		
63.2***		ACTIVE	INACTIVE	NOTCONFG	

AM COUNTER DATA POINT CONFIGURATION
(Continued)

AM88-640
Page 9 of 10
09/08

• AM GENERAL INPUT CONNECTIONS DISPLAY

70.0	EU CONVERSION FACTOR (AVCONV)	1 . 0
71.0	DECIMAL PLACE FORMAT (AVFORMAT)	D0 D1 D2 D3 D4 D5 D6
72.0**	ACCUMULATION TARGET VALUE (AVTV)	_ _ _ _ _ _
73.0	OPERATOR CONTROL CHANGE (CNTLLOCK)	PERMIT NOTPERM
74.0**	OPERATOR TARGET VALUE CHANGE (AVTVLOCK)	PERMIT NOTPERM
75.0***	1ST ACCUMULATORDEVIATION (AVDEV1TP)	_ _ _ _ _ _
76.0***	2ND ACCUMULATORDEVIATION (AVDEV2TP)	_ _ _ _ _ _
80.0**	NUMBER OF GENERAL INPUT CONNECTIONS (NOGINPTS)	0

81.0***

		SOURCE POINT_ID.PARAMETER GISRC(N)	DESTINATION PARAMETER GIDSTN(N)		CONNECTION ACTIVITY STATUS GIACSTSTS(N)	
81.1	1			ACTIVE	INACTIVE	NOTCONFIG
81.2	2			ACTIVE	INACTIVE	NOTCONFIG
81.3	3			ACTIVE	INACTIVE	NOTCONFIG
81.4	4			ACTIVE	INACTIVE	NOTCONFIG
81.5	5			ACTIVE	INACTIVE	NOTCONFIG
81.6	6			ACTIVE	INACTIVE	NOTCONFIG

AM COUNTER DATA POINT CONFIGURATION
(Continued)

AM88-640
Page 10 of 10
09/08

• AM GENERAL OUTPUT CONNECTIONS DISPLAY

81.7	7			ACTIVE	INACTIVE	NOTCONFIG
81.8	8			ACTIVE	INACTIVE	NOTCONFIG

90.0** NUMBER OF GENERAL OUTPUT CONNECTIONS (NOGOPTS)

91.0***

		SOURCE PARAMETER GOSRC(N)	DESTINATION POINT_ID.PARAMETER GODSTN(N)		CONNECTION ACTIVITY STATUS GOACTSTS(N)	
91.1	1			ACTIVE	INACTIVE	NOTCONFIG
91.2	2			ACTIVE	INACTIVE	NOTCONFIG
91.3	3			ACTIVE	INACTIVE	NOTCONFIG
91.4	4			ACTIVE	INACTIVE	NOTCONFIG
91.5	5			ACTIVE	INACTIVE	NOTCONFIG
91.6	6			ACTIVE	INACTIVE	NOTCONFIG
91.7	7			ACTIVE	INACTIVE	NOTCONFIG
91.8	8			ACTIVE	INACTIVE	NOTCONFIG

AM SWITCH DATA POINT CONFIGURATION

AM88-650
Page 1 of 7
06/06

• AM - SWITCH POINT ASSIGNMENT DISPLAY

10.0	TAG NAME (NAME)		
11.0	UNIT ID (UNIT)		
12.0	POINT DESCRIPTION (PTDESC)		
13.0	POINT KEYWORD (KEYWORD)		
14.0	NUMBER ASSOCIATED CL BLOCKS (CLSLOTS)		
15.0**	NUMBER CUSTOM DATA PACKAGES (NOPKG)		**See line 23
16.0**	NUMBER SWITCHES (NUMSWITCH)		**See lines 30 and 31
17.0	POINT ASSOCDSP (ASSOCDSP)		
17A.	POINT CUSTOM DISPLAY (\$CDETAIL)		Default = All Blanks
18.0	PRIMARY MODULE (PRIMMOD)		Default. All Underbars
19.0	ALARM 1 DESCRIPTION (SALMDSC1)		
19.1	ALARM 2 DESCRIPTION (SALMDSC2)		
19.2	ALARM 3 DESCRIPTION (SALMDSC3)		

AM SWITCH DATA POINT CONFIGURATION
(Continued)

AM88-650
Page 2 of 7
06/06

• AM - SWITCH POINT ASSIGNMENT DISPLAY

11.0	ALARM ENABLE STATE (ALENBST)	☒ ENABLE	☐ DISABLE	☐ INHIBIT
11.1	AUXILIARY UNIT (\$AUXUNIT)	☐ - ☐ -		
11.2	MULTIPLE PRIMMOD #1 (\$MPROD1)	☐	☐	☐
11.3	MULTIPLE PRIMMOD #2 (\$MPROD2)	☐	☐	☐
11.4	MULTIPLE PRIMMOD #3 (\$MPROD3)	☐	☐	☐
11.5	MULTIPLE PRIMMOD #4 (\$MPROD4)	☐	☐	☐
11.6	RE-ALARMING INTERVAL (\$REALARM)	☐ 0 ☐ 0 ☐ 0 ☐ 0		

AM SWITCH DATA POINT CONFIGURATION
(Continued)

AM88-650
Page 3 of 7
06/06

• AM - SWITCH POINT ASSIGNMENT DISPLAY

SEPARATE ALARM PRIORITIES

21.0	BACKGROUND CL ERROR (BCLEALPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
21.1	BACKGROUND CL FATAL ERROR (BCLFALPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
21.2	CL ERROR (CLEALMPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
21.3	CL FATAL ERROR (CLFALMPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
21.4	CONFIGURATION ERROR (CNFERRPR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
21.5	SWITCH ALARM 1 (SWALM1PR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
21.6	SWITCH ALARM 2 (SWALM2PR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
21.7	SWITCH ALARM 3 (SWALM3PR) ALARM PRIORITY	NOACTION (R670) EMERGNCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH

AM SWITCH DATA POINT CONFIGURATION
(Continued)

AM88-650
Page 4 of 7
06/06

• AM - SWITCH POINT ASSIGNMENT DISPLAY (Continued)

30.0 CUSTOM DATA PACKAGE SOURCE FILE NAMES

30.1	SOURCE FILE 1 NAME (PKGNAME (1))	
30.2	SOURCE FILE 2 NAME (PKGNAME (2))	
30.3	SOURCE FILE 3 NAME (PKGNAME (3))	
30.4	SOURCE FILE 4 NAME (PKGNAME (4))	
30.5	SOURCE FILE 5 NAME (PKGNAME (5))	
30.6	SOURCE FILE 6 NAME (PKGNAME (6))	
30.7	SOURCE FILE 7 NAME (PKGNAME (7))	
30.8	SOURCE FILE 8 NAME (PKGNAME (8))	
30.9	SOURCE FILE 9 NAME (PKGNAME (9))	
30.10	SOURCE FILE 10 NAME (PKGNAME (10))	

AM SWITCH DATA POINT CONFIGURATION
(Continued)

AM88-650
Page 5 of 7
06/06

• AM SWITCH SEGMENT DISPLAY

40.0

SWITCH #1

40.1 NUMBER OF STATES (S1NSTATE)

| 2 |

40.2 #1 STATE NAME (S1STATES (0))

| | | | | | | | |

40.3 #2 STATE NAME (S1STATES (1))

| | | | | | | | |

40.4 #3 STATE NAME (S1STATES (2))

| | | | | | | | |

40.5 #4 STATE NAME (S1STATES (3))

| | | | | | | | |

40.6 #5 STATE NAME (S1STATES (4))

| | | | | | | | |

40.7 ACCESS LEVEL (S1ACCLVL)

OPERATOR

SUPERVIS

ENGINEER

PROGRAM

40.8 INITIAL STATE (S1CURSTS)

| | | | | | | | |

40.9 REQUESTED STATE (S1REQSTS)

| | | | | | | | |

AM SWITCH DATA POINT CONFIGURATION
(Continued)

AM88-650
Page 6 of 7
06/06

• AM - SWITCH SEGMENT DISPLAY (Continued)

41.0***

SWITCH #2

41.1 NUMBER OF STATES (S2NSTATE)

| 2 |

41.2 #1 STATE NAME (S2STATES (0))

| | | | | | | | |

41.3 #2 STATE NAME (S2STATES (1))

| | | | | | | | |

41.4 #3 STATE NAME (S2STATES (2))

| | | | | | | | |

41.5 #4 STATE NAME (S2STATES (3))

| | | | | | | | |

41.6 #5 STATE NAME (S2STATES (4))

| | | | | | | | |

41.7 ACCESS LEVEL (S2ACCLVL)

OPERATOR

SUPERVIS

ENGINEER

PROGRAM

41.8 INITIAL STATE (S2CURSTS)

| | | | | | | | |

41.9 REQUESTED STATE (S2REQSTS)

| | | | | | | | |

AM SWITCH DATA POINT CONFIGURATION
(Continued)

AM88-650
Page 7 of 7
06/06

• AM - SWITCH SCHEDULING DISPLAY

50.0**	POINT ASSIGNED TO IPP (\$IPPASN)	ON	OFF		
51.0A***	POINT EXECUTION PERIOD (PERIOD) (\$IAPPASN = OFF)	1 SEC	2 SEC	5 SEC	10 SEC
		15 SEC	30 SEC	1 MIN	2 MIN
		1S MIN	2S MIN	5 MIN	10 MIN
		15 MIN	30 MIN	1 HR	8 HR
		12 HR	24 HR	NOPERIOD	
51.0B***	POINT EXECUTION PERIOD (PERIOD) (\$IAPPASN = ON)	5 SEC	10 SEC	15 SEC	30 SEC
		1 MIN	2 MIN	5 MIN	10 MIN
		15 MIN	30 MIN	1 HR	8 HR
		12 HR	24 HR	NOPERIOD	
52.0***	BEFORE/AFTER/CYCLE OPTION (BEFAFT)	NO	BEFORE**	AFTER**	CYCLE**
53.0***	TAG NAME OF BEFORE/AFTER (BEFAFTID)	_ _ _ _ _ _ _			
54.0***	ABSOLUTE CYCLE NUMBER (NORMCYCL)	_ _ _			

AM CUSTOM DATA POINT CONFIGURATION

AM88-660
Page 1 of 4
06/06

• AM - CUSTOM POINT ASSIGNMENT DISPLAY

10.0	TAG NAME (NAME)	
11.0	UNIT ID (UNIT)	
12.0	POINT DESCRIPTION (PTDESC)	
13.0	POINT KEYWORD (KEYWORD)	
14.0	NUMBER ASSOCIATED CL BLOCKS (CLSLOTS)	1
15.0**	NUMBER CUSTOM DATA PACKAGES (NOPKG)	0
16.0	POINT ASSOCDSP (ASSOCDSP)	Default: All Underbars
16A.	POINT CUSTOM DISPLAY (\$CDETAIL)	Default = All Blanks
16.1	PRIMARY MODULE (PRIMMOD)	-
11.2	ALARM STATE (ALENBST)	☒ ENABLE ☐ DISABLE ☐ INHIBIT
16.3	AUXILIARY UNIT (\$AUXUNIT)	-
16.4	MULTIPLE PRIMMOD #1(\$MPROD1)	
16.5	MULTIPLE PRIMMOD #2(\$MPROD2)	
16.6	MULTIPLE PRIMMOD #3(\$MPROD3)	
16.7	MULTIPLE PRIMMOD #4(\$MPROD4)	
16.8	RE-ALARMING INTERVAL (\$REALARM)	0

AM CUSTOM DATA POINT CONFIGURATION
(Continued)

AM88-660
Page 2 of 4
06/06

• AM - CUSTOM POINT ASSIGNMENT DISPLAY

18.0		<u>SEPARATE ALARM PRIORITIES</u>			
18.1	BACKGROUND CL ERROR (BCLEALPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
18.2	BACKGRPIMD FATA; CL; ERROR (BCLFALPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
18.3	CL ERROR (CLEALMPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
18.4	CL FATAL ERROR (CLFALMPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH
18.5	CONFIGURATION ERROR (CNFERRPR) ALARM PRIORITY	NOACTION (R670) EMERGENCY	JOURNAL PRINTER	LOW JNLPRINT	HIGH

AM CUSTOM DATA POINT CONFIGURATION
(Continued)

AM88-660
Page 3 of 4
06/06

• AM - CUSTOM POINT ASSIGNMENT DISPLAY

20.0 CUSTOM DATA PACKAGE SOURCE FILE NAMES

20.1	SOURCE FILE 1 NAME (PKGNAME (1))	
20.2	SOURCE FILE 2 NAME (PKGNAME (2))	
20.3	SOURCE FILE 3 NAME (PKGNAME (3))	
20.4	SOURCE FILE 4 NAME (PKGNAME (4))	
20.5	SOURCE FILE 5 NAME (PKGNAME (5))	
20.6	SOURCE FILE 6 NAME (PKGNAME (6))	
20.7	SOURCE FILE 7 NAME (PKGNAME (7))	
20.6	SOURCE FILE 8 NAME (PKGNAME (8))	
20.9	SOURCE FILE 9 NAME (PKGNAME (9))	
20.10	SOURCE FILE 10 NAME (PKGNAME (10))	

AM CUSTOM DATA POINT CONFIGURATION
(Continued)

AM88-660
Page 4 of 4
06/06

• AM - CUSTOM SCHEDULING DISPLAY

30.0***	POINT ASSIGNED TO IPP (\$IPPASN)	ON	OFF										
31.0A**	POINT EXECUTIONPERIOD (PERIOD) (\$IPPASN = OFF)	1 SEC	2 SEC	5 SEC	10 SEC								
		15 SEC	30 SEC	1 MIN	2 MIN								
		1S MIN	2S MIN	5 MIN	10 MIN								
		15 MIN	30 MIN	1 HR	8 HR								
		12 HR	24 HR	NOPERIOD									
31.0B**	POINT EXECUTIONPERIOD (PERIOD) (\$IAPPASN = ON)	5 SEC	10 SEC	15 SEC	30 SEC								
		1 MIN	2 MIN	5 MIN	10 MIN								
		15 MIN	30 MIN	1 HR	8 HR								
		12 HR	24 HR	NOPERIOD									
32.0***	BEFORE/AFTER/CYCLE OPTION (BEFAFT)	NO	BEFORE**	AFTER**	CYCLE**								
33.00**	TAG NAME OF BEFORE/AFTER (BEFAFTID)	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="width: 20px; height: 20px;"></td> <td style="width: 20px; height: 20px;"></td> <td style="width: 20px; height: 20px;"></td> <td style="width: 20px; height: 20px;"></td> <td style="width: 20px; height: 20px;"></td> <td style="width: 20px; height: 20px;"></td> <td style="width: 20px; height: 20px;"></td> <td style="width: 20px; height: 20px;"></td> </tr> </table>											
34.0***	ABSOLUTE CYCLE NUMBER (NORMCYCL)	<table border="1" style="display: inline-table; border-collapse: collapse;"> <tr> <td style="width: 20px; height: 20px;"></td> <td style="width: 20px; height: 20px;"></td> <td style="width: 20px; height: 20px;"></td> </tr> </table>											

Process Solutions

2500 West Union Hills Drive
Phoenix, Arizona 85027