5.3 A two-page front controller

We now turn the same application into a two-page site. A query parameter chooses which controller method runs. Both pages initially repeat HTML so we can see what the next refactoring removes. Keep the entry script unchanged.

Replace the Application class

Replace `src/Tutorials/Class5/Application.php` with:

```php
<?php
declare(strict_types=1);

namespace App\Tutorials\Class5;

use Twig\Environment;
use Twig\Loader\FilesystemLoader;

class Application
{
    private const PATH_TO_TEMPLATES = __DIR__ .
'/../../../templates/tutorials/class5';

    private Environment $twig;

    public function __construct()
    {
        $loader = new FilesystemLoader(self::PATH_TO_TEMPLATES);
        $this->twig = new Environment($loader, [
            'autoescape' => 'html',
            'strict_variables' => true,
        ]);
    }

    public function run(): void
    {
        $action = $_GET['action'] ?? 'home';
        if (!is_string($action)) {
            $action = 'home';
        }

        switch ($action) {
            case 'contact':
                $this->contact();
                break;
            case 'home':
            default:
                $this->home();
        }
    }
```

```
    private function home(): void
    {
        $template = 'home.html.twig';
        $args = ['pageTitle' => 'Home'];
        echo $this->twig->render($template, $args);
    }

    private function contact(): void
    {
        $template = 'contact.html.twig';
        $args = ['pageTitle' => 'Contact'];
        echo $this->twig->render($template, $args);
    }
}
```

The `run()` method acts as the front controller. The null-coalescing operator supplies a default when action is absent. The string check handles an array-shaped query such as `?action[]=contact`. The switch selects known methods; it never uses user input as a template filename. Like the chapter, unknown actions fall back to Home. A later application might deliberately return a 404 instead.

Add two templates

Create `templates/tutorials/class5/home.html.twig`:

```
<!doctype html>
<html lang="en">
<head>
    <meta charset="utf-8">
    <title>Campus Club: {{ pageTitle }}</title>
</head>
<body>
    <header>
        <p>Campus Club</p>
        <nav aria-label="Main navigation">
            <a href="index.php?action=home">Home</a>
            <a href="index.php?action=contact">Contact</a>
        </nav>
    </header>
    <h1>{{ pageTitle }}</h1>
    <p>Explore a new skill with classmates each week.</p>
</body>
</html>
```

Create `templates/tutorials/class5/contact.html.twig`:

```
<!doctype html>
<html lang="en">
<head>
```

```
    <meta charset="utf-8">
    <title>Campus Club: {{ pageTitle }}</title>
</head>
<body>
    <header>
        <p>Campus Club</p>
        <nav aria-label="Main navigation">
            <a href="index.php?action=home">Home</a>
            <a href="index.php?action=contact">Contact</a>
        </nav>
    </header>
    <h1>{{ pageTitle }}</h1>
    <p>Contact the club organizers.</p>
    <dl>
        <dt>Email</dt>
        <dd>club@example.com</dd>
        <dt>Meeting room</dt>
        <dd>Library 204</dd>
    </dl>
</body>
</html>
```

Verify the routes

Open `/tutorials/class5/index.php`, then follow Contact and Home. Expect different titles, headings, and main content with identical navigation. Try `?action=unknown` and `?action[]=contact`; both should show Home. The old hello and demo templates stay in the project, but this version of run no longer renders them.