

# BQSKit

An overview

---

Nate Stemen

Aug 31, 2022

Unitary Fund

## Robust and Resource-Efficient Quantum Circuit Approximation

Tirthak Patel

Northeastern University  
Boston, Massachusetts, USA

Ed Younis

Lawrence Berkeley National  
Laboratory  
Berkeley, California, USA

Costin Iancu

Lawrence Berkeley National  
Laboratory  
Berkeley, California, USA

Wibe de Jong

Lawrence Berkeley National  
Laboratory  
Berkeley, California, USA

Devesh Tiwari


Northeastern University  
Boston, Massachusetts, USA

<https://arxiv.org/abs/2108.12714>


*The Berkeley Quantum Synthesis Toolkit (BQSKit) is a superoptimizing quantum compiler and research vehicle that combines ideas from several projects at LBNL into an easily accessible and quickly extensible software suite.*

*The Berkeley Quantum Synthesis Toolkit (BQSKit) is a **superoptimizing quantum compiler** and research vehicle that combines ideas from several projects at LBNL into an easily accessible and quickly extensible software suite.*


# What is a compiler?




# What is “superoptimizing”?



# What is “superoptimizing”?



# What does Qiskit do?







## Problem Statement

Let  $G$  be a gate set (i.e. a finite collection of unitary operators), and  $U \in U(2^n)$  be the **target unitary**. Find a sequence of gates  $g_i \in G$  such that the target unitary  $U$  can be written as  $U = g_n \cdot g_{n-1} \cdots g_2 \cdot g_1$ .


- Need ways to “compare” the similarities of unitaries
- Hilbert-Schmidt inner product:  $\langle U, V \rangle \stackrel{\text{def}}{=} \text{tr}(UV^\dagger)$
- Can turn this into a normalized distance function as  $d_{\text{HS}}(U, V) \stackrel{\text{def}}{=} \sqrt{1 - \frac{|\langle U, V \rangle|}{2^{2n}}}$
- Total Variation Distance of probability distributions:  $\frac{1}{2} \sum_{k=1}^{2^n} |p_1(k) - p_2(k)|$ 
  - $p_1(k)$  is probability of state  $k$  after target unitary
  - $p_2(k)$  is probability of state  $k$  after synthesized unitary
- $d_{\text{HS}}$  scales poorly due to unitaries growing exponential with number of qubits



# Partitioning



# Approximate block synthesis



- Bottom up approach to synthesis
- Each layer consists of one CNOT, and two single-qubit rotations
- Tree is pruned every few layers for branch with best approximations to target unitary

- Synthesizing many, low-CNOT count circuits is easier than a single, but much more accurate one
- Averaging over multiple approximations can give an accurate representation of target unitary
- Dual annealing optimization:  $\min f = (\text{CNOT count} + \text{dissimilarity})/2$
- $d_{\text{HS}}(U, V) \leq \sum_{k=1}^K \varepsilon_k$  for  $V$  being a partitioned version of  $U$  with  $K$  blocks

# Summary

- BQSKit/QEST is a compiler primarily focused on reducing circuit depth via CNOT gate count reduction
- 30–80% CNOT gate count reduction on ideal systems

