



Quantum Wednesday

arXiv:2201.10672

Nate Stemen

Nov 16, 2022

Efficiently improving the performance of noisy quantum computers

Samuele Ferracin,^{1,2,*} Akel Hashim,^{3,4,*} Jean-Loup Ville,^{3,†} Ravi Naik,^{3,4} Arnaud Carignan-Dugas,¹ Hammam Qassim,¹ Alexis Morvan,^{3,4,‡} David I. Santiago,^{3,4} Irfan Siddiqi,^{3,4,5} and Joel J. Wallman^{1,2}

¹*Keysight Technologies Canada, Kanata, ON K2K 2W5, Canada*

²*Department of Applied Mathematics, University of Waterloo, Waterloo, Ontario N2L 3G1, Canada*

³*Quantum Nanoelectronics Laboratory, Dept. of Physics,*

University of California at Berkeley, Berkeley, CA 94720, USA

⁴*Computational Research Division, Lawrence Berkeley National Lab, Berkeley, CA 94720*

⁵*Materials Sciences Division, Lawrence Berkeley National Lab, Berkeley, CA 94720, USA*

(Dated: July 20, 2022)


<https://arxiv.org/abs/2201.10672>

- Noiseless Output Extrapolation (NOX)
- Pauli Error Cancellation (PEC)

- Noiseless Output Extrapolation (NOX)
- Pauli Error Cancellation (PEC)

Question


How are these different from Zero-Noise Extrapolation (ZNE) and Probabilistic Error Cancellation (PEC)?



- \mathcal{E}_i : single qubit cycles
- \mathcal{H}_i : Clifford two-qubit cycles

$$\mathcal{C} = \mathcal{E}_{m+1} \mathcal{H}_m \mathcal{E}_m \cdots \mathcal{E}_2 \mathcal{H}_1 \mathcal{E}_1 \quad (1)$$

$$=: \mathcal{E}_{m+1} \left(\bigcirc_{j=1}^m \mathcal{H}_j \mathcal{E}_j \right) \quad (2)$$




- \mathcal{E}_i : single qubit cycles
- \mathcal{H}_i : Clifford two-qubit cycles

$$\mathcal{C} = \mathcal{E}_{m+1} \mathcal{H}_m \mathcal{E}_m \cdots \mathcal{E}_2 \mathcal{H}_1 \mathcal{E}_1 \quad (1)$$

$$=: \mathcal{E}_{m+1} \left(\bigcirc_{j=1}^m \mathcal{H}_j \mathcal{E}_j \right) \quad (2)$$

Cycle Error Reconstruction¹ (CER)



¹Hashim et al., “Randomized Compiling for Scalable Quantum Computing on a Noisy Superconducting Quantum Processor”.

Assumptions:

1. Noise is Markovian and time stationary ($\mathcal{D}_{\mathcal{U}}\mathcal{U}$).
2. $\mathcal{D}_{\mathcal{U}} = \mathcal{D}$ when \mathcal{U} consists solely of single qubit gates ($\mathcal{D}_{\mathcal{E}_i}\mathcal{E}_i = \mathcal{D}\mathcal{E}_i$ for all i).

Noise processes $\mathcal{D}_{\mathcal{U}}$ taken to be a Pauli channels by Randomized Compiling.²

$$\mathcal{D}_{\mathcal{U}}(\rho) = \sum_{k=0}^{4^n-1} \epsilon_k^{(\mathcal{U})} \mathcal{P}_k(\rho)$$

$$\mathcal{P}_k \in \{\mathcal{I}, \mathcal{X}, \mathcal{Y}, \mathcal{Z}\}^{\otimes n}$$

$\epsilon_k^{(\mathcal{U})}$: Pauli error rates

²Wallman and Emerson, "Noise tailoring for scalable quantum computation via randomized compiling".

Assumptions:

1. Noise is Markovian and time stationary ($\mathcal{D}_{\mathcal{U}}\mathcal{U}$).
2. $\mathcal{D}_{\mathcal{U}} = \mathcal{D}$ when \mathcal{U} consists solely of single qubit gates ($\mathcal{D}_{\mathcal{E}_i}\mathcal{E}_i = \mathcal{D}\mathcal{E}_i$ for all i).

Noise processes $\mathcal{D}_{\mathcal{U}}$ taken to be a Pauli channels by Randomized Compiling.²

$$\mathcal{D}_{\mathcal{U}}(\rho) = \sum_{k=0}^{4^n-1} \epsilon_k^{(\mathcal{U})} \mathcal{P}_k(\rho)$$

$$\mathcal{P}_k \in \{\mathcal{I}, \mathcal{X}, \mathcal{Y}, \mathcal{Z}\}^{\otimes n}$$

$\epsilon_k^{(\mathcal{U})}$: Pauli error rates

²Wallman and Emerson, "Noise tailoring for scalable quantum computation via randomized compiling".

Assumptions:

1. Noise is Markovian and time stationary ($\mathcal{D}_{\mathcal{U}}\mathcal{U}$).
2. $\mathcal{D}_{\mathcal{U}} = \mathcal{D}$ when \mathcal{U} consists solely of single qubit gates ($\mathcal{D}_{\mathcal{E}_i}\mathcal{E}_i = \mathcal{D}\mathcal{E}_i$ for all i).

Noise processes $\mathcal{D}_{\mathcal{U}}$ taken to be a Pauli channels by Randomized Compiling.²

$$\mathcal{D}_{\mathcal{U}}(\rho) = \sum_{k=0}^{4^n-1} \epsilon_k^{(\mathcal{U})} \mathcal{P}_k(\rho)$$

$$\mathcal{P}_k \in \{\mathcal{I}, \mathcal{X}, \mathcal{Y}, \mathcal{Z}\}^{\otimes n}$$

$\epsilon_k^{(\mathcal{U})}$: Pauli error rates

²Wallman and Emerson, "Noise tailoring for scalable quantum computation via randomized compiling".

Assumptions:

1. Noise is Markovian and time stationary ($\mathcal{D}_{\mathcal{U}}\mathcal{U}$).
2. $\mathcal{D}_{\mathcal{U}} = \mathcal{D}$ when \mathcal{U} consists solely of single qubit gates ($\mathcal{D}_{\mathcal{E}_i}\mathcal{E}_i = \mathcal{D}\mathcal{E}_i$ for all i).

Noise processes $\mathcal{D}_{\mathcal{U}}$ taken to be a Pauli channels by Randomized Compiling.²

$$\mathcal{D}_{\mathcal{U}}(\rho) = \sum_{k=0}^{4^n-1} \epsilon_k^{(\mathcal{U})} \mathcal{P}_k(\rho)$$

$$\mathcal{P}_k \in \{\mathcal{I}, \mathcal{X}, \mathcal{Y}, \mathcal{Z}\}^{\otimes n}$$

$\epsilon_k^{(\mathcal{U})}$: Pauli error rates

²Wallman and Emerson, “Noise tailoring for scalable quantum computation via randomized compiling”.

Assumptions:

1. Noise is Markovian and time stationary ($\mathcal{D}_{\mathcal{U}}\mathcal{U}$).
2. $\mathcal{D}_{\mathcal{U}} = \mathcal{D}$ when \mathcal{U} consists solely of single qubit gates ($\mathcal{D}_{\mathcal{E}_i}\mathcal{E}_i = \mathcal{D}\mathcal{E}_i$ for all i).

Noise processes $\mathcal{D}_{\mathcal{U}}$ taken to be a Pauli channels by Randomized Compiling.²

$$\mathcal{D}_{\mathcal{U}}(\rho) = \sum_{k=0}^{4^n-1} \epsilon_k^{(\mathcal{U})} \mathcal{P}_k(\rho)$$

$$\mathcal{P}_k \in \{\mathcal{I}, \mathcal{X}, \mathcal{Y}, \mathcal{Z}\}^{\otimes n}$$

$\epsilon_k^{(\mathcal{U})}$: Pauli error rates

²Wallman and Emerson, “Noise tailoring for scalable quantum computation via randomized compiling”.

Noiseless Output Extrapolation

- Need a way to scale the noise: $\mathcal{D}_{\mathcal{H}_i} \mathcal{H}_i \rightarrow \mathcal{D}_{\mathcal{H}_i}^\alpha \mathcal{H}_i$
- ZNE uses pulse stretching, or unitary folding³: $\mathcal{H}_i(\mathcal{H}_i \mathcal{H}_i^{-1})^\alpha$
 1. \mathcal{H}_i and \mathcal{H}_i^{-1} have identical noise models
 2. $\mathcal{D}_{\mathcal{H}_i} \mathcal{H}_i = \mathcal{H}_i \mathcal{D}_{\mathcal{H}_i}$
- CER can detect when these assumptions apply
- Otherwise, scale noise from single cycle:

$$C'_{j,\alpha} = \mathcal{E}_{m+1} \mathcal{D}_{\mathcal{H}_m} \mathcal{H}_m \mathcal{E}_m \cdots (\mathcal{D}_{\mathcal{H}_j})^\alpha \mathcal{H}_j \cdots \mathcal{D}_{\mathcal{H}_1} \mathcal{H}_1 \mathcal{E}_1$$

$$\langle O \rangle \approx E_{\text{NOX}}(O) := E_{\text{noisy}}(O) + \sum_{j=1}^m \frac{E_{\text{noisy}}(O) - E_{j,\alpha}(O)}{\alpha - 1} \quad (3)$$

³This is referred to as "identity insertion" in the paper.

Noiseless Output Extrapolation

- Need a way to scale the noise: $\mathcal{D}_{\mathcal{H}_i} \mathcal{H}_i \rightarrow \mathcal{D}_{\mathcal{H}_i}^\alpha \mathcal{H}_i$
- ZNE uses pulse stretching, or unitary folding³: $\mathcal{H}_i(\mathcal{H}_i \mathcal{H}_i^{-1})^\alpha$
 1. \mathcal{H}_i and \mathcal{H}_i^{-1} have identical noise models
 2. $\mathcal{D}_{\mathcal{H}_i} \mathcal{H}_i = \mathcal{H}_i \mathcal{D}_{\mathcal{H}_i}$
- CER can detect when these assumptions apply
- Otherwise, scale noise from single cycle:

$$\mathcal{C}'_{j,\alpha} = \mathcal{E}_{m+1} \mathcal{D}_{\mathcal{H}_m} \mathcal{H}_m \mathcal{E}_m \cdots (\mathcal{D}_{\mathcal{H}_j})^\alpha \mathcal{H}_j \cdots \mathcal{D}_{\mathcal{H}_1} \mathcal{H}_1 \mathcal{E}_1$$

$$\langle O \rangle \approx E_{\text{NOX}}(O) := E_{\text{noisy}}(O) + \sum_{j=1}^m \frac{E_{\text{noisy}}(O) - E_{j,\alpha}(O)}{\alpha - 1} \quad (3)$$

³This is referred to as "identity insertion" in the paper.

Noiseless Output Extrapolation

- Need a way to scale the noise: $\mathcal{D}_{\mathcal{H}_i} \mathcal{H}_i \rightarrow \mathcal{D}_{\mathcal{H}_i}^\alpha \mathcal{H}_i$
- ZNE uses pulse stretching, or unitary folding³: $\mathcal{H}_i(\mathcal{H}_i \mathcal{H}_i^{-1})^\alpha$
 1. \mathcal{H}_i and \mathcal{H}_i^{-1} have identical noise models
 2. $\mathcal{D}_{\mathcal{H}_i} \mathcal{H}_i = \mathcal{H}_i \mathcal{D}_{\mathcal{H}_i}$

- CER can detect when these assumptions apply
- Otherwise, scale noise from single cycle:

$$\mathcal{C}'_{j,\alpha} = \mathcal{E}_{m+1} \mathcal{D}_{\mathcal{H}_m} \mathcal{H}_m \mathcal{E}_m \cdots (\mathcal{D}_{\mathcal{H}_j})^\alpha \mathcal{H}_j \cdots \mathcal{D}_{\mathcal{H}_1} \mathcal{H}_1 \mathcal{E}_1$$

$$\langle O \rangle \approx E_{\text{NOX}}(O) := E_{\text{noisy}}(O) + \sum_{j=1}^m \frac{E_{\text{noisy}}(O) - E_{j,\alpha}(O)}{\alpha - 1} \quad (3)$$

³This is referred to as "identity insertion" in the paper.

Noiseless Output Extrapolation

- Need a way to scale the noise: $\mathcal{D}_{\mathcal{H}_i} \mathcal{H}_i \rightarrow \mathcal{D}_{\mathcal{H}_i}^\alpha \mathcal{H}_i$
- ZNE uses pulse stretching, or unitary folding³: $\mathcal{H}_i(\mathcal{H}_i \mathcal{H}_i^{-1})^\alpha$
 1. \mathcal{H}_i and \mathcal{H}_i^{-1} have identical noise models
 2. $\mathcal{D}_{\mathcal{H}_i} \mathcal{H}_i = \mathcal{H}_i \mathcal{D}_{\mathcal{H}_i}$

- CER can detect when these assumptions apply
- Otherwise, scale noise from single cycle:

$$\mathcal{C}'_{j,\alpha} = \mathcal{E}_{m+1} \mathcal{D}_{\mathcal{H}_m} \mathcal{H}_m \mathcal{E}_m \cdots (\mathcal{D}_{\mathcal{H}_j})^\alpha \mathcal{H}_j \cdots \mathcal{D}_{\mathcal{H}_1} \mathcal{H}_1 \mathcal{E}_1$$

$$\langle O \rangle \approx E_{\text{NOX}}(O) := E_{\text{noisy}}(O) + \sum_{j=1}^m \frac{E_{\text{noisy}}(O) - E_{j,\alpha}(O)}{\alpha - 1} \quad (3)$$

³This is referred to as "identity insertion" in the paper.

Noiseless Output Extrapolation

- Need a way to scale the noise: $\mathcal{D}_{\mathcal{H}_i} \mathcal{H}_i \rightarrow \mathcal{D}_{\mathcal{H}_i}^\alpha \mathcal{H}_i$
- ZNE uses pulse stretching, or unitary folding³: $\mathcal{H}_i(\mathcal{H}_i \mathcal{H}_i^{-1})^\alpha$
 1. \mathcal{H}_i and \mathcal{H}_i^{-1} have identical noise models
 2. $\mathcal{D}_{\mathcal{H}_i} \mathcal{H}_i = \mathcal{H}_i \mathcal{D}_{\mathcal{H}_i}$
- CER can detect when these assumptions apply
- Otherwise, scale noise from single cycle:

$$C'_{j,\alpha} = \mathcal{E}_{m+1} \mathcal{D}_{\mathcal{H}_m} \mathcal{H}_m \mathcal{E}_m \cdots (\mathcal{D}_{\mathcal{H}_j})^\alpha \mathcal{H}_j \cdots \mathcal{D}_{\mathcal{H}_1} \mathcal{H}_1 \mathcal{E}_1$$

$$\langle O \rangle \approx E_{\text{NOX}}(O) := E_{\text{noisy}}(O) + \sum_{j=1}^m \frac{E_{\text{noisy}}(O) - E_{j,\alpha}(O)}{\alpha - 1} \quad (3)$$

³This is referred to as "identity insertion" in the paper.

Noiseless Output Extrapolation

- Need a way to scale the noise: $\mathcal{D}_{\mathcal{H}_i} \mathcal{H}_i \rightarrow \mathcal{D}_{\mathcal{H}_i}^\alpha \mathcal{H}_i$
- ZNE uses pulse stretching, or unitary folding³: $\mathcal{H}_i(\mathcal{H}_i \mathcal{H}_i^{-1})^\alpha$
 1. \mathcal{H}_i and \mathcal{H}_i^{-1} have identical noise models
 2. $\mathcal{D}_{\mathcal{H}_i} \mathcal{H}_i = \mathcal{H}_i \mathcal{D}_{\mathcal{H}_i}$
- CER can detect when these assumptions apply
- Otherwise, scale noise from single cycle:

$$\mathcal{C}'_{j,\alpha} = \mathcal{E}_{m+1} \mathcal{D}_{\mathcal{H}_m} \mathcal{H}_m \mathcal{E}_m \cdots (\mathcal{D}_{\mathcal{H}_j})^\alpha \mathcal{H}_j \cdots \mathcal{D}_{\mathcal{H}_1} \mathcal{H}_1 \mathcal{E}_1$$

$$\langle O \rangle \approx E_{\text{NOX}}(O) := E_{\text{noisy}}(O) + \sum_{j=1}^m \frac{E_{\text{noisy}}(O) - E_{j,\alpha}(O)}{\alpha - 1} \quad (3)$$

³This is referred to as "identity insertion" in the paper.

Noiseless Output Extrapolation

- Need a way to scale the noise: $\mathcal{D}_{\mathcal{H}_i} \mathcal{H}_i \rightarrow \mathcal{D}_{\mathcal{H}_i}^\alpha \mathcal{H}_i$
- ZNE uses pulse stretching, or unitary folding³: $\mathcal{H}_i(\mathcal{H}_i \mathcal{H}_i^{-1})^\alpha$
 1. \mathcal{H}_i and \mathcal{H}_i^{-1} have identical noise models
 2. $\mathcal{D}_{\mathcal{H}_i} \mathcal{H}_i = \mathcal{H}_i \mathcal{D}_{\mathcal{H}_i}$
- CER can detect when these assumptions apply
- Otherwise, scale noise from single cycle:

$$\mathcal{C}'_{j,\alpha} = \mathcal{E}_{m+1} \mathcal{D}_{\mathcal{H}_m} \mathcal{H}_m \mathcal{E}_m \cdots (\mathcal{D}_{\mathcal{H}_j})^\alpha \mathcal{H}_j \cdots \mathcal{D}_{\mathcal{H}_1} \mathcal{H}_1 \mathcal{E}_1$$

$$\langle O \rangle \approx E_{\text{NOX}}(O) := E_{\text{noisy}}(O) + \sum_{j=1}^m \frac{E_{\text{noisy}}(O) - E_{j,\alpha}(O)}{\alpha - 1} \quad (3)$$

³This is referred to as "identity insertion" in the paper.

Pauli Error Cancellation

- Like Prob. EC, start with quasiprobability distribution:

$$C_{\text{tot}} \sum_{i=1}^L s_i q_i \text{tr} \left(O \tilde{\mathcal{U}}_i(\rho_{\text{in}}) \right) = \text{tr} [O \mathcal{U}(\rho_{\text{in}})] + \delta$$

- $\tilde{\mathcal{U}}_i$: implementable operations
- $s_k = \pm 1$ depending on number of Pauli cycles
- r_k results from PEC circuits

$$C_{\text{tot}} = \prod_{j=1}^m \frac{1}{\left(\epsilon_0^{(\mathcal{H}_j)} \right)^2 - \sum_{k=1}^{4^n-1} \left(\epsilon_k^{(\mathcal{H}_j)} \right)^2} \quad (4)$$

$$\langle O \rangle \approx E_{\text{PEC}}(O) = C_{\text{tot}} \sum_{k=1}^N \frac{s_k r_k}{N} \quad (5)$$

Pauli Error Cancellation

- Like Prob. EC, start with quasiprobability distribution:


$$C_{\text{tot}} \sum_{i=1}^L s_i q_i \text{tr} \left(O \tilde{\mathcal{U}}_i(\rho_{\text{in}}) \right) = \text{tr} [O \mathcal{U}(\rho_{\text{in}})] + \delta$$

- $\tilde{\mathcal{U}}_i$: implementable operations
- $s_k = \pm 1$ depending on number of Pauli cycles
- r_k results from PEC circuits

$$C_{\text{tot}} = \prod_{j=1}^m \frac{1}{\left(\epsilon_0^{(\mathcal{H}_j)} \right)^2 - \sum_{k=1}^{4^n-1} \left(\epsilon_k^{(\mathcal{H}_j)} \right)^2} \quad (4)$$

$$\langle O \rangle \approx E_{\text{PEC}}(O) = C_{\text{tot}} \sum_{k=1}^N \frac{s_k r_k}{N} \quad (5)$$


Summary



	PEC	NOX	Unmit.
Runtime	$\frac{1}{(1-n\varepsilon)^{2m}}$	m^3	1
Bias	$\mathcal{O}(mn^2\varepsilon^2) + \delta_{\text{rec}}$	$\mathcal{O}(m^2n^2\varepsilon^2) + \delta_{\text{rec}}$	$\mathcal{O}(mn\varepsilon)$




- m circuit depth
- $n\varepsilon$ cycle error rate
- n number of qubits
- δ_{rec} accuracy of noise reconstruction

Summary



	PEC	NOX	Unmit.
Runtime	$\frac{1}{(1-n\varepsilon)^{2m}}$	m^3	1
Bias	$\mathcal{O}(mn^2\varepsilon^2) + \delta_{\text{rec}}$	$\mathcal{O}(m^2n^2\varepsilon^2) + \delta_{\text{rec}}$	$\mathcal{O}(mn\varepsilon)$

- m circuit depth
- $n\varepsilon$ cycle error rate
- n number of qubits
- δ_{rec} accuracy of noise reconstruction

-  Ferracin, Samuele et al. “Efficiently improving the performance of noisy quantum computers”. In: (Jan. 2022). arXiv: 2201.10672 [quant-ph].
-  Hashim, Akel et al. “Randomized Compiling for Scalable Quantum Computing on a Noisy Superconducting Quantum Processor”. In: *Phys. Rev. X* 11 (4 Nov. 2021), p. 041039. DOI: 10.1103/PhysRevX.11.041039.
-  Wallman, Joel J. and Joseph Emerson. “Noise tailoring for scalable quantum computation via randomized compiling”. In: *Phys. Rev. A* 94 (5 Nov. 2016), p. 052325. DOI: 10.1103/PhysRevA.94.052325.

Thank you!