ctz-euclide

Typst Port

Euclidean Geometry for Typst

A comprehensive geometry package built on CeTZ

Version 0.1.0

Nathan Scheinmann

Contents

1. Introduction 4
   1.1. Features 4
   1.2. Installation 4
   1.3. Basic Usage 4
2. Core Concepts 5
   2.1. The Point Registry 5
   2.2. Figure Scaling 5
   2.3. Coordinate Systems 5
3. Point Definitions 6
   3.1. Basic Points — `ctz-def-points` 6
   3.2. Midpoint — `ctz-def-midpoint` 6
   3.3. Regular Polygons — `ctz-def-regular-polygon` 6
   3.4. Named Polygons — `ctz-def-polygon` / `ctz-label-polygon` 6
   3.5. Linear Combination — `ctz-def-linear` 6
4. Line Constructions 8
   4.1. Perpendicular — `ctz-def-perp` 8
   4.2. Parallel — `ctz-def-para` 8
   4.3. Angle Bisector — `ctz-def-bisect` 8
   4.4. Perpendicular Bisector — `ctz-def-mediator` 9
5. Intersections 10
   5.1. Line–Line — `ctz-def-ll` 10
   5.2. Line–Circle — `ctz-def-lc` 10
   5.3. Circle–Circle — `ctz-def-cc` 10
6. Triangle Centers 12
   6.1. Basic Centers 12
      6.1.1. Centroid — `ctz-def-centroid` 12
      6.1.2. Circumcenter — `ctz-def-circumcenter` 12
      6.1.3. Incenter — `ctz-def-incenter` 13
      6.1.4. Orthocenter — `ctz-def-orthocenter` 13
   6.2. The Euler Line 13
   6.3. Right Triangles via Thales' Theorem 14
   6.4. Advanced Centers 15
7. Transformations 16
   7.1. Rotation — `rotate` 16
   7.2. Reflection — `ctz-def-reflect` 16
   7.3. Homothety (Scaling) — `scale` 16
   7.4. Projection — `ctz-def-project` 17
   7.5. Inversion — `ctz-def-inversion` 17
   7.6. Object Duplication — `ctz-duplicate` 18
   7.7. Polymorphic Rotation 18
8. Drawing & Styling 20
   8.1. Points — `ctz-draw-points` 20
   8.2. Unified Drawing — `ctz-draw` 20
      8.2.1. Drawing Named Objects 20
      8.2.2. Drawing Unnamed Constructs 20
         8.2.2.1. Points with Labels 20
         8.2.2.2. Paths and Polylines 20
         8.2.2.3. Circles 21
         8.2.2.4. Conics (Ellipses, Parabolas, Projectiles) 21
         8.2.2.5. Arcs and Semicircles 21
         8.2.2.6. Line Segments 21

8.2.3. Complete Example 22
8.3. Labels — ctz-draw-labels 22
8.4. Labels & Points — Unified API (Recommended) 22
8.5. Segments — ctz-draw-segment 23
8.6. Segment Measurements — ctz-draw-measure-segment 24
8.7. Paths — ctz-draw-path 25
8.8. Global Styling — ctz-style 26
8.9. Angle Marking — ctz-draw-angle 27
8.10. Right Angle Mark — ctz-draw-mark-right-angle 27
9. Circles 29
9.1. Named Circle — ctz-def-circle / ctz-draw-circle 29
9.2. Circumcircle — ctz-draw-circumcircle 29
9.3. Incircle — ctz-draw-incircle 29
10. Conics 30
10.1. Ellipse — ctz-def-ellipse / ctz-draw-ellipse 30
10.2. Parabola (Focus + Directrix) — ctz-def-parabola / ctz-draw-parabola 30
10.3. Parabola (Focus + p + Angle) — ctz-draw-parabola-focus 30
10.4. Projectile Trajectory — ctz-def-projectile / ctz-draw-projectile 30
10.5. Conic Tangents 30
10.6. Ellipse Helpers 30
10.7. Conics — Visual Example 31
10.8. Circle Through Point — ctz-draw-circle-through 32
10.9. Semicircle — ctz-draw-semicircle 32
11. Clipping 33
11.1. Set Clip Region — ctz-set-clip 33
11.2. Draw Clipped Line — ctz-draw-line-global-clip 33
11.3. Draw Clipped Segment — ctz-draw-seg-global-clip 33
12. Raw Algorithms 34
13. Function Reference 35
13.1. Point Definition 35
13.2. Line Constructions 35
13.3. Intersections 35
13.4. Triangle Centers 35
13.5. Special Triangles 35
13.6. Transformations 35
13.7. Drawing 35
13.8. Clipping 36
14. Gallery Examples 37
15. Advanced Examples 50

1. Introduction

`ctz-euclide` is a geometry package for Typst, a port of the LaTeX package `tkz-euclide`. Built on top of CeTZ (a powerful drawing library), it provides high-level constructions for Euclidean geometry.

1.1. Features

- **Point Registry**: Define points once, reference them by name throughout your figure
- **Geometric Constructions**: Perpendiculars, parallels, bisectors, mediators
- **Intersections**: Line–line, line–circle, circle–circle with multiple solution handling
- **Triangle Centers**: Centroid, circumcenter, incenter, orthocenter, and 10+ specialized centers
- **Special Triangles**: Medial, orthic, intouch triangles
- **Transformations**: Rotation, reflection, translation, homothety, projection, inversion
- **Drawing & Styling**: Points, labels, angles, segments with tick marks
- **Grid & Axes**: Coordinate systems with customizable appearance
- **Clipping**: Mathematical line clipping for clean bounded figures

1.2. Installation

Import the package in your Typst document:

```
#import "/src/lib.typ": *
```

All figures use the `ctz-canvas` function (re-exported from CeTZ):

```
#ctz-canvas({
  import cetz.draw: *
  ctz-init()

  // Your geometry code here
})
```

Naming notes:

- All public functions are prefixed with `ctz-` to avoid conflicts.
- Point creation and drawing use `ctz-def-points` and `ctz-draw-points`.
- Other constructors use `ctz-def-*`, and drawing utilities use `ctz-draw-*`.

The `ctz-init()` call initializes the point registry and coordinate resolver.

1.3. Basic Usage

Code

```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()


  // Define points
  ctz-def-points(A: (0, 0), B: (4, 0), C: (2, 3))

  // Draw triangle
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)

  // Find circumcenter and draw circumcircle
  ctz-def-circumcenter("O", "A", "B", "C")
  ctz-draw(circle-through: ("O", "A"), stroke: blue)

  // Draw and label points
  ctz-draw(points: ("A", "B", "C", "O"), labels: (
    A: "below left", B: "below right",
    C: "above", O: "below"))
})
```

Figure



2. Core Concepts

2.1. The Point Registry

The point registry is the heart of `ctz-euclide`. Once you define a point with a name, that name can be used directly in CeTZ drawing commands.

```
ctz-def-points(A: (0, 0), B: (3, 4))  // Register points A and B
ctz-draw(segment: ("A", "B"))              // Use them directly in CeTZ
```

Under the hood, `ctz-init()` installs a coordinate resolver that translates `"A"` to the stored coordinates.

2.2. Figure Scaling

Control the size of your figures using CeTZ's `length` parameter:

```
#ctz-canvas(length: 0.8cm, { ... })
```

This scales everything proportionally, including stroke widths. Typical values:

- `0.6cm` – small inline figures
- `0.8cm` – standard examples
- `1.0cm` – large detailed figures

2.3. Coordinate Systems

Points can be defined in multiple ways:

```
// Explicit coordinates
ctz-def-points(A: (2, 3))

// Using existing CeTZ coordinates
ctz-def-points(B: (rel: (1, 1), to: "A"))

// Mixed: numbers and existing points
ctz-def-points(C: (4, 0), D: "A", E: (3, 2))
```

3. Point Definitions

3.1. Basic Points — `ctz-def-points`

Define one or more points at specific coordinates:

```
ctz-def-points(A: (0, 0), B: (4, 0), C: (2, 3))
```

3.2. Midpoint — `ctz-def-midpoint`

Find the midpoint of a segment:


Code

```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (5, 3))
  ctz-def-midpoint("M", "A", "B")

  ctz-draw(segment: ("A", "B"), stroke: black)
  ctz-draw(points: ("A", "B", "M"), labels: (
    A: "left", B: "right", M: "above"))
})
```

Figure



3.3. Regular Polygons — `ctz-def-regular-polygon`

Generate vertices of a regular n-gon. If you pass a polygon name first, it is registered and can be drawn/labeled by name: You can also mark all sides during drawing with `mark` and optional `mark-opts`.


Code

```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(O: (0, 0), A: (3, 0))
  // O is the center; A is the starting vertex that
fixes the radius/angle.
  ctz-def-regular-polygon("Hex", ("A", "B", "C", "D",
"E", "F"), "O", "A")

  ctz-draw("Hex", stroke: blue)
  ctz-draw(points: ("A", "B", "C", "D", "E", "F",
"O"), labels: (O: "below"))
})
```

Figure



3.4. Named Polygons — `ctz-def-polygon` / `ctz-label-polygon`

Define a polygon once and draw/label it by name:

```
ctz-def-points(A: (0, 0), B: (4, 0), C: (4, 2), D: (0, 2))
ctz-def-polygon("P1", "A", "B", "C", "D")
ctz-draw("P1", stroke: black)
ctz-label-polygon("P1", $P_1$, pos: "center")
```

3.5. Linear Combination — `ctz-def-linear`

Define a point along a line: $P = A + k(B - A)$

```
ctz-def-linear("P", "A", "B", 0.3)  // P is 30% from A to B
ctz-def-linear("Q", "A", "B", 1.5)  // Q extends beyond B
```

4. Line Constructions

4.1. Perpendicular — `ctz-def-perp`

Construct a perpendicular line through a point:

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (5, 1), C: (2, 3))
  ctz-def-perp("P1", "P2", ("A", "B"), "C")
  ctz-def-project("H", "C", "A", "B")

  ctz-draw(segment: ("A", "B"), stroke: black)
  ctz-draw(segment: ("P1", "P2"), stroke: blue)
  ctz-draw-mark-right-angle("A", "H", "C", size: 0.3)

  ctz-draw(points: ("A", "B", "C"), labels: (
    A: "left", B: "right", C: "above"))
})
```

Figure



4.2. Parallel — `ctz-def-para`

Construct a parallel line through a point:

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (5, 1), C: (1, 2.5))
  ctz-def-para("P1", "P2", ("A", "B"), "C")

  ctz-set-clip(-0.5, -0.5, 5.5, 3.5)
  ctz-draw-line-global-clip("A", "B", add: (2, 2),
stroke: black)
  ctz-draw-line-global-clip("P1", "P2", add: (2, 2),
stroke: green)

  ctz-draw(points: ("A", "B", "C"), labels: (
    A: "below",
    B: "below",
    C: "above"
  ))
})
```

Figure



4.3. Angle Bisector — `ctz-def-bisect`

Construct the bisector of an angle:

Code


```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 0), C: (1, 3))
  ctz-def-bisect("D1", "D2", "C", "A", "B")

  ctz-set-clip(-0.5, -0.5, 4.5, 3.5)
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw-seg-global-clip("D1", "D2", stroke: red)

  ctz-draw-angle("A", "C", "B", radius: 0.5, stroke:
gray)
  ctz-draw(points: ("A", "B", "C"), labels: (
    A: "below",
    B: "below",
    C: "above"
  ))
})
```

Figure



4.4. Perpendicular Bisector — `ctz-def-mediator`

Construct the perpendicular bisector of a segment:

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (1, 1), B: (5, 3))
  ctz-def-mediator("M1", "M2", "A", "B")
  ctz-def-midpoint("M", "A", "B")

  ctz-draw(segment: ("A", "B"), stroke: black)
  ctz-draw(segment: ("M1", "M2"), stroke: purple)
  ctz-draw-mark-right-angle("M1", "M", "A", size:
0.25)

  ctz-draw(points: ("A", "B", "M"), labels: (
    A: "left",
    B: "right",
    M: "below"
  ))
})
```

Figure



5. Intersections

5.1. Line–Line — `ctz-def-ll`

Find the intersection of two lines:

Code


```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 3),
            C: (4, 0), D: (0, 2.5))
  ctz-def-line("L1", "A", "B")
  ctz-def-line("L2", "C", "D")
  ctz-def-ll("I", "L1", "L2")

  ctz-draw("L1", stroke: blue)
  ctz-draw("L2", stroke: red)

  ctz-draw(points: ("A", "B", "C", "D", "I"), labels:
(I: "above"))
})
```

Figure



5.2. Line–Circle — `ctz-def-lc`

Find intersections of a line with a circle:

Code


```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(O: (0, 0), R: (3, 0),
            A: (-2, 2), B: (4, 1))
  ctz-def-line("L1", "A", "B")
  ctz-def-circle("C1", "O", through: "R")
  ctz-def-lc(("I1", "I2"), "L1", "C1")

  ctz-draw("C1", stroke: blue)
  ctz-label-circle("C1", $C_1$, pos: "above", dist:
0.2)
  ctz-set-clip(-4, -4, 5, 4)
  ctz-draw-line-global-clip("A", "B", add: (2, 2),
stroke: red)

  ctz-draw(points: ("O", "I1", "I2"), labels: (
    O: "below",
    I1: "above left",
    I2: "above right"
  ))
})
```

Figure



Named line/circle form:

```
ctz-def-line("L1", "A", "B")
ctz-def-circle("C1", "O", radius: 3)
ctz-def-lc(("I1", "I2"), "L1", "C1")
```

5.3. Circle–Circle — `ctz-def-cc`

Find intersections of two circles:

Code


```
#ctz-canvas(length: 0.65cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(O1: (0, 0), O2: (3, 0),
            R1: (2.5, 0), R2: (5.5, 0))
  ctz-def-circle("C1", "O1", through: "R1")
  ctz-def-circle("C2", "O2", through: "R2")
  ctz-def-cc(("I1", "I2"), "C1", "C2")

  ctz-draw("C1", stroke: blue)
  ctz-draw("C2", stroke: red)
  ctz-label-circle("C1", $C_1$, pos: "above left",
dist: 0.2)
  ctz-label-circle("C2", $C_2$, pos: "above right",
dist: 0.2)

  ctz-draw(points: ("O1", "O2", "I1", "I2"), labels:
(
    I1: "above",
    I2: "below"
  ))
})
```

Figure



Named circle form:

```
ctz-def-circle("C1", "O1", through: "R1")
ctz-def-circle("C2", "O2", through: "R2")
ctz-def-cc(("I1", "I2"), "C1", "C2")
```

6. Triangle Centers

6.1. Basic Centers

6.1.1. Centroid — `ctz-def-centroid`

The intersection of medians (center of mass):

Code

```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()


  ctz-def-points(A: (0, 0), B: (5, 0), C: (2, 3.5))
  ctz-def-centroid("G", "A", "B", "C")

  // Draw medians
  ctz-def-midpoint("Ma", "B", "C")
  ctz-def-midpoint("Mb", "A", "C")
  ctz-def-midpoint("Mc", "A", "B")

  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw(segment: ("A", "Ma"), stroke: blue +
0.5pt)
  ctz-draw(segment: ("B", "Mb"), stroke: blue +
0.5pt)
  ctz-draw(segment: ("C", "Mc"), stroke: blue +
0.5pt)

  ctz-draw(points: ("A", "B", "C", "G"), labels: (
    A: "below left",
    B: "below right",
    C: "above",
    G: "above right"
  ))
})
```

Figure



6.1.2. Circumcenter — `ctz-def-circumcenter`

Center of the circumscribed circle:

Code

```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()


  ctz-def-points(A: (0, 0), B: (5, 0), C: (2, 3.5))
  ctz-def-circumcenter("O", "A", "B", "C")

  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw(circle-through: ("O", "A"), stroke: blue +
0.7pt)

  ctz-draw(segment: ("O", "A"), stroke: gray + 0.5pt)
  ctz-draw(segment: ("O", "B"), stroke: gray + 0.5pt)
  ctz-draw(segment: ("O", "C"), stroke: gray + 0.5pt)

  ctz-draw(points: ("A", "B", "C", "O"), labels: (
    A: "below left",
    B: "below right",
    C: "above",
    O: "below"
  ))
})
```

Figure



6.1.3. Incenter — `ctz-def-incenter`

Center of the inscribed circle:

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (5, 0), C: (2, 3.5))
  ctz-def-incenter("I", "A", "B", "C")

  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw(incircle: ("A", "B", "C"), stroke: green +
0.7pt)

  ctz-draw(points: ("A", "B", "C", "I"), labels: (
    A: "below left",
    B: "below right",
    C: "above",
    I: "below right"
  ))
})
```

Figure



6.1.4. Orthocenter — `ctz-def-orthocenter`

Intersection of altitudes:

Code

```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()


  ctz-def-points(A: (0, 0), B: (5, 0), C: (2, 3.5))
  ctz-def-orthocenter("H", "A", "B", "C")

  // Altitudes
  ctz-def-perp("Ha1", "Ha2", ("B", "C"), "A")
  ctz-def-perp("Hb1", "Hb2", ("A", "C"), "B")
  ctz-def-perp("Hc1", "Hc2", ("A", "B"), "C")

  ctz-set-clip(-0.5, -0.5, 5.5, 4)
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw-line-global-clip("A", "Ha1", add: (2, 2),
stroke: red + 0.5pt)
  ctz-draw-line-global-clip("B", "Hb1", add: (2, 2),
stroke: red + 0.5pt)
  ctz-draw-line-global-clip("C", "Hc1", add: (2, 2),
stroke: red + 0.5pt)

  ctz-draw(points: ("A", "B", "C", "H"), labels: (
    A: "left",
    B: "right",
    C: "above right",
    H: "below right"
  ))
})
```

Figure



6.2. The Euler Line

In any non-equilateral triangle, the orthocenter H, centroid G, and circumcenter O are collinear. This line is called the **Euler line**, and remarkably, G divides HO in the ratio $2:1$.

Code

```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()


  ctz-def-points(A: (0, 0), B: (5, 0), C: (1.5, 3.5))

  ctz-def-orthocenter("H", "A", "B", "C")
  ctz-def-centroid("G", "A", "B", "C")
  ctz-def-circumcenter("O", "A", "B", "C")

  ctz-set-clip(-0.5, -0.5, 5.5, 4)
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw-line-add("H", "O", add: 0.5, stroke:
(paint: red, dash: "dashed"))
  ctz-draw(circle-through: ("O", "A"), stroke: blue +
0.6pt)

  ctz-draw(points: ("A", "B", "C", "H", "G", "O"),
labels: (
    A: "below left",
    B: "below right",
    C: "above",
    H: "left",
    G: "below",
    O: "right"
  ))
})
```

Figure



6.3. Right Triangles via Thales' Theorem

Thales' theorem states that any triangle inscribed in a semicircle with the diameter as its base has a right angle at the opposite vertex. The `ctz-def-thales-triangle()` function creates such triangles.

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(O: (0, 0))
  ctz-def-thales-triangle("A", "B", "C", "O", 2.5,
    base-angle: 30, orientation: "left")

  ctz-draw(circle-r: (_pt("O"), 2.5), stroke: gray +
0.5pt)
  ctz-draw-path("A--B--C--A", stroke: black + 1pt)
  ctz-draw-mark-right-angle("A", "C", "B", color:
red)

  ctz-draw(points: ("A", "B", "C", "O"), labels: (
    A: "right",
    B: "left",
    C: "above",
    O: "below"
  ))
})
```

Figure



Parameters:

- `name-a, name-b`: Diameter endpoints (base of triangle)
- `name-c`: Vertex with the right angle
- `center`: Circle center
- `radius`: Circle radius
- `base-angle`: Rotation angle for the diameter (default: 0)
- `orientation`: "left" or "right" - position of right angle vertex

6.4. Advanced Centers

`ctz-euclide` supports 10+ specialized triangle centers:

- `ctz-def-lemoine` — Symmedian point (Lemoine point)
- `ctz-def-nagel` — Nagel point
- `ctz-def-gergonne` — Gergonne point
- `ctz-def-spieker` — Spieker center (incenter of medial triangle)
- `ctz-def-euler` — Nine-point circle center
- `ctz-def-feuerbach` — Feuerbach point
- `ctz-def-mittenpunkt` — Mittenpunkt
- `ctz-def-excenter` — Excenter (specify vertex: `"a"`, `"b"`, or `"c"`)

Example with Euler (nine-point) circle:

Code

```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (5, 0), C: (1.5, 3.5))
  ctz-def-euler("N", "A", "B", "C")


  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)

  // Nine-point circle passes through midpoints
  ctz-def-midpoint("Ma", "B", "C")
  ctz-def-midpoint("Mb", "A", "C")
  ctz-def-midpoint("Mc", "A", "B")

  ctz-draw(circle-through: ("N", "Ma"), stroke:
purple + 0.7pt)

  ctz-draw(points: ("A", "B", "C", "N", "Ma", "Mb",
"Mc"), labels: (
    N: "below"
  ))
})
```

Figure



7. Transformations

7.1. Rotation — `rotate`

Rotate a point around a center:

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(O: (2, 2), A: (5, 2))
  ctz-def-rotation("B", "A", "O", 60)
  ctz-def-rotation("C", "A", "O", 120)

  ctz-draw(circle-r: (_pt("O"), 3), stroke:
gray.lighten(50%))
  ctz-draw(segment: ("O", "A"), stroke: blue)
  ctz-draw(segment: ("O", "B"), stroke: blue)
  ctz-draw(segment: ("O", "C"), stroke: blue)
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)

  ctz-draw(points: ("O", "A", "B", "C"), labels: (
    O: "below left",
    A: "right",
    B: "above right",
    C: "left"
  ))
})
```

Figure



7.2. Reflection — `ctz-def-reflect`

Reflect a point across a line:

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 3), P: (3, 0))
  ctz-def-reflect("Pp", "P", "A", "B")

  ctz-draw(segment: ("A", "B"), stroke: gray)
  ctz-draw(path: "P--Pp", stroke: blue + 0.5pt, mark:
(end: ">"), points: false, labels: false)

  ctz-draw(points: ("A", "B", "P", "Pp"), labels: (
    P: "below",
    Pp: "above left"
  ))
})
```

Figure



7.3. Homothety (Scaling) — `scale`

Scale a point from a center:

Code


```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(O: (0, 0), A: (2, 1), B: (3, 2), C:
(1, 2.5))
  ctz-def-homothety("Ap", "A", "O", 2)
  ctz-def-homothety("Bp", "B", "O", 2)
  ctz-def-homothety("Cp", "C", "O", 2)

  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw(line: ("Ap", "Bp", "Cp", "Ap"), stroke:
blue)
  ctz-draw(segment: ("O", "Ap"), stroke: gray +
0.3pt)
  ctz-draw(segment: ("O", "Bp"), stroke: gray +
0.3pt)
  ctz-draw(segment: ("O", "Cp"), stroke: gray +
0.3pt)

  ctz-draw(points: ("O", "A", "B", "C", "Ap", "Bp",
"Cp"), labels: (
    O: "below left"
  ))
})
```

Figure



7.4. Projection — `ctz-def-project`

Project a point onto a line:

Code


```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (5, 1), P: (2, 3))
  ctz-def-project("H", "P", "A", "B")

  ctz-draw(segment: ("A", "B"), stroke: black)
  ctz-draw(segment: ("P", "H"), stroke: blue + 0.5pt)
  ctz-draw-mark-right-angle("A", "H", "P", size:
0.25)

  ctz-draw(points: ("A", "B", "P", "H"), labels: (
    P: "above",
    H: "below"
  ))
})
```

Figure



7.5. Inversion — `ctz-def-inversion`

Invert points, lines, or circles through a circle:

Code


```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  ctz-init()
  ctz-set-clip(-5, -4.5, 5, 4)

  ctz-def-points(O: (0, 0), A: (-4, -1), B: (4, -1),
C: (1.8, 1))
  ctz-def-line("L", "A", "B")
  ctz-def-circle("C1", "C", radius: 1.1)

  ctz-def-inversion("Li", "L", "O", 3)
  ctz-def-inversion("C1i", "C1", "O", 3)

  ctz-draw(circle-r: (_pt("O"), 3), stroke: black +
1pt)
  ctz-draw("L", stroke: gray + 0.7pt)
  ctz-draw("C1", stroke: gray + 0.7pt)
  ctz-draw("Li", stroke: blue + 1pt)
  ctz-draw("C1i", stroke: red + 1pt)
  ctz-draw(points: ("O"), labels: (O: "below left"))
})
```

Figure



7.6. Object Duplication — `ctz-duplicate`

Duplicate any geometric object. For polygons, explicit point names must be provided.


Code

```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  // Duplicate a circle
  ctz-def-circle("c1", (0, 0), radius: 1.5)
  ctz-duplicate("c2", "c1")
  ctz-draw("c1", stroke: blue)

  // Duplicate a polygon
  ctz-def-regular-polygon("tri", ("A","B","C"),
    (3, 0), (4, 0), n: 3)
  ctz-duplicate("tri2", "tri",
    points: ("A2", "B2", "C2"))
  ctz-draw("tri", stroke: green)
  ctz-draw(points: ("A", "B", "C"), labels: true)
})
```

Figure



For points, lines, and circles, duplication is straightforward. For polygons, you must provide explicit point names so the vertices can be referenced independently.

7.7. Polymorphic Rotation

The `ctz-def-rotation()` function works on all object types: points, lines, circles, and polygons.


Code

```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  // Rotate a circle
  ctz-def-points(O: (0, 0))
  ctz-def-circle("c1", (2, 0), radius: 1)
  ctz-def-rotation("c2", "c1", "O", 45)

  ctz-draw("c1", stroke: blue)
  ctz-draw("c2", stroke: red)
  ctz-draw(points: ("O"), labels: (
    O: "below"
  ))
})
```

Figure



For lines, both endpoints are rotated. For circles, the center is rotated while radius remains constant. For polygons, all constituent points are rotated in place.

8. Drawing & Styling

8.1. Points — `ctz-draw-points`

Draw points at named locations:

```
ctz-draw(points: ("A", "B", "C"))
```

8.2. Unified Drawing — `ctz-draw`

The `ctz-draw()` function provides a unified interface for drawing both **named objects** and **unnamed constructs**.

8.2.1. Drawing Named Objects

Use `ctz-draw()` to draw any object type without remembering type-specific commands. It automatically detects whether the object is a point, line, circle, polygon, or conic (ellipse/parabola/projectile).


Code

```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-circle("c1", (0, 0), radius: 1.5)
  ctz-def-line("l1", (-2, 0), (2, 0))
  ctz-def-polygon("tri", "A", "B", "C")
  ctz-def-points(A: (1, 2), B: (2, 0), C: (0, 1))

  ctz-draw("c1", stroke: blue, fill: none)
  ctz-draw("l1", stroke: red + 1.5pt)
  ctz-draw("tri", stroke: green)
  ctz-draw("A")
})
```

Figure



8.2.2. Drawing Unnamed Constructs

You can also use `ctz-draw()` to draw geometric objects directly without defining them first using named parameters.

8.2.2.1. Points with Labels


Draw multiple points at once, optionally with labels:

Code

```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()
  ctz-def-points(A: (0, 0), B: (2, 0), C: (2, 2), D:
(0, 2))

  // Draw points with custom label positions
  ctz-draw(points: ("A", "B", "C", "D"), labels: (
    A: "below left",
    B: "below right",
    C: "above right",
    D: "above left"
  ))
})
```

Figure



Use `labels: true` for default label positioning, or omit the `labels` parameter to draw points without labels.

8.2.2.2. Paths and Polylines

Draw paths using the `path:` parameter for CeTZ-style path syntax, or `line:` for polylines through points:

```
ctz-draw(path: "A--B--C--A", stroke: black)  // Close the path by repeating first point
ctz-draw(line: ("A", "B", "C", "D"), stroke: red)  // Open polyline
```

8.2.2.3. Circles

Draw circles without naming them:

```
// Circle through two points (center and point on circumference)
ctz-draw(circle-through: ("O", "A"), stroke: blue)

// Circle by center and radius
ctz-draw(circle-r: ((0, 0), 1.5), stroke: green)

// Circle by diameter endpoints
ctz-draw(circle-diameter: ("A", "B"), stroke: purple)

// Circumcircle of triangle
ctz-draw(circumcircle: ("A", "B", "C"), stroke: red)

// Incircle of triangle
ctz-draw(incircle: ("A", "B", "C"), stroke: teal)
```

8.2.2.4. Conics (Ellipses, Parabolas, Projectiles)

Draw conics without naming them:

```
// Ellipse by center, radii, and rotation angle
ctz-draw(ellipse: ((0, 0), 3, 2, 20deg), stroke: black)

// Parabola by focus + directrix (line or two points)
ctz-draw(parabola: ((0, 0), ((-2, -3), (-2, 3)), 4), stroke: black)

// Projectile by origin + velocity (optional gravity, vectors, etc.)
ctz-draw(projectile: (origin: (0, 0), velocity: (4, 6), y-floor: 0, vectors: true), stroke:
blue)
```

8.2.2.5. Arcs and Semicircles

```
// Arc by center and two points
ctz-draw(arc: (center: "O", start: "A", end: "B"), stroke: orange)

// Arc by center, radius, and angles (in degrees)
ctz-draw(arc-r: ((0, 0), 2, 0, 90), stroke: black)

// Semicircle by diameter endpoints
ctz-draw(semicircle: ("A", "B"), stroke: blue, fill: blue.lighten(80%))
```

8.2.2.6. Line Segments

```
ctz-draw(segment: ("A", "B"), stroke: maroon + 1.5pt)
```

8.2.3. Complete Example


Code

```
#ctz-canvas(length: 0.6cm, {
  import cetz.draw: *
  ctz-init()
  ctz-def-points(A: (0, 0), B: (3, 0), C: (1.5, 2))

  // Named circle
  ctz-def-circle("myCircle", (1.5, 1), radius: 2.5)
  ctz-draw("myCircle", stroke: gray + 0.5pt)

  // Unnamed constructs
  ctz-draw(path: "A--B--C--A", stroke: black)
  ctz-draw(circumcircle: ("A", "B", "C"), stroke:
blue)
  ctz-draw(incircle: ("A", "B", "C"), stroke: red)
  ctz-draw(points: ("A", "B", "C"), labels: true)
})
```

Figure



8.3. Labels — `ctz-draw-labels`

Add labels to points with positioning:

```
ctz-draw-labels("A", "B", "C",
  A: "below left",
  B: "below right",
  C: "above")
```

Positions: `"above"`, `"below"`, `"left"`, `"right"`, `"above left"`, etc.

Custom offset:

```
ctz-draw-labels("O", O: (pos: "below", offset: (0, -0.15)))
```

More placement controls (position, offset, distance):

```
ctz-draw-labels("A", "B", "C",
  A: (pos: "above", dist: 0.25),
  B: (pos: "right", offset: (0.1, 0)),
  C: (pos: "below left", offset: (-0.05, -0.05)))
```


8.4. Labels & Points — Unified API (Recommended)

The modern approach combines point drawing and labeling in a single call:

Code

```
#ctz-canvas(length: 0.75cm, {
  import cetz.draw: *
  ctz-init()
  ctz-def-points(A: (0, 0), B: (3, 0), C: (1.5, 2))
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw(points: ("A", "B", "C"), labels: (
    A: "below left",
    B: "below right",
    C: "above"
  ))
})
```

Figure



This unified API replaces separate `ctz-draw-points()` and `ctz-draw-labels()` calls. The old API remains supported for backward compatibility.

You can also label points that were drawn earlier:

```
ctz-draw(points: ("A", "B"))  // Draw points without labels
// ... other drawing commands ...
ctz-draw(labels: (A: "below", B: "above"))  // Add labels later
```

8.5. Segments — `ctz-draw-segment`

Draw a segment with optional arrow or bar tips and a dimension label:

```
ctz-draw-segment("A", "B", arrows: "|-|", dim: $5$, dim-pos: "above")
```

Supported `arrows`: `--` (none), `->`, `<-`, `<->`, `|-|`, `|->`, `<-|`.


Code

```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 0), C: (6, 1.5))

  ctz-draw-segment("A", "B", arrows: "|-|", dim: $5$,
dim-pos: "above")
  ctz-draw-segment("B", "C", arrows: "->", dim: $v$,
dim-pos: "below")
  ctz-draw(points: ("A", "B", "C"), labels: (A:
"below", B: "below", C: "above"))
})
```

Figure



Mark equal-length segments with ticks:

```
ctz-draw-mark-segment("A", "B", mark: 1)
ctz-draw-mark-segment("C", "D", mark: 2)
```

Code


```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 0), C: (4, 2.5),
D: (0, 2.5))
  ctz-draw(line: ("A", "B", "C", "D"), stroke: black)

  // Opposite sides equal
  ctz-draw-mark-segment("A", "B", mark: 1)
  ctz-draw-mark-segment("C", "D", mark: 1)
  ctz-draw-mark-segment("B", "C", mark: 2)
  ctz-draw-mark-segment("D", "A", mark: 2)

  ctz-draw(points: ("A", "B", "C", "D"), labels: (
    A: "below left",
    B: "below right",
    C: "above right",
    D: "above left"
  ))
})
```

Figure



Code

```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  ctz-init()


  ctz-def-points(O: (0, 0), A: (3, 0))
  ctz-def-regular-polygon("Hex", ("A", "B", "C", "D",
"E", "F"), "O", "A")

  ctz-draw-regular-polygon(("A", "B", "C", "D", "E",
"F"),
    stroke: black, mark: 1)

  // Mark all sides with the same tick
  // (use mark-opts to customize size/position)

  ctz-draw(points: ("A", "B", "C", "D", "E", "F"),
labels: (
    A: "right",
    B: "above right",
    C: "above left",
    D: "left",
    E: "below",
    F: "below"
  ))
})
```

Figure



8.6. Segment Measurements — `ctz-draw-measure-segment`

Draw an offset measurement line with dotted fences and a centered label. The line breaks around the label and uses open arrowheads by default.

```
ctz-draw-measure-segment("A", "B", label: $5$, offset: 0.3, side: "left")
```

Code


```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 1.2))
  ctz-draw-segment("A", "B", stroke: black + 1pt)

  // Minimal measurement example
  ctz-draw-measure-segment("A", "B", label: $ell$,
offset: 0.45, side: "left",
    fence-dash: "dotted")

  ctz-draw(points: ("A", "B"), labels: (
    A: "below",
    B: "below"
  ))
})
```

Figure



Code


```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (5, 0), C: (5, 3), D:
(0, 3))
  ctz-draw(line: ("A", "B", "C", "D"), stroke: black
+ 1pt)

  // Rectangle measurements (width and height)
  ctz-draw-measure-segment("A", "B", label: $w$,
offset: 0.45, side: "below")
  ctz-draw-measure-segment("C", "B", label: $h$,
offset: -0.45, side: "right")

  ctz-draw(points: ("A", "B", "C", "D"), labels: (
    A: "below left",
    B: "below right",
    C: "above right",
    D: "above left"
  ))
})
```

Figure



8.7. Paths — `ctz-draw-path`

Draw polylines with per-segment tips using a TikZ-like string:

```
ctz-draw-path("A--B->C|-|D", stroke: black)
```

Supported connectors: `--`, `->`, `<-`, `<->`, `|-|`, `|->`, `<-|`.

By default, `ctz-draw-path` draws points as crosses for normal segments and hides points that touch a bar connector (`|-|`, `|->`, `<-|`). Labels default to `below`. You can override per-point placements or point styles in the path with `{...}`, or via `label-overrides`.

Default behavior, label are placed below


Code

```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(
    A: (0, 0), B: (3, 0), C: (6, 1.5), D: (8, 0),
  )

  // Default labels below, default point styles
  ctz-draw-path("A--B->C|-|D", stroke: black)
})
```

Figure




Code

```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(
    A: (0, 0), B: (3, 0), C: (6, 1.5), D: (8, 0),
  )

  ctz-draw-path("A{below}--B{below}->C{above}|-|
D{below}", stroke: black)
})
```

Figure



Override placements using `label-overrides`:

```
ctz-draw-path("A--B->C|-|D",
  label-overrides: (A: "left", C: "above right"))
```

Customize point appearance or disable points/labels:

```
ctz-draw-path("A--B->C|-|D",
  point-style: "circle",
  point-color: red,
  label-pos: "above")
```

```
ctz-draw-path("A--B->C|-|D",
  points: false,
  labels: false)
```

Per-point overrides inside the path:

```
ctz-draw-path("A{below, style: circle}--B{below}->C{above, style: none}|-|D{below}",
  stroke: black)
```


Code

```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(
    A: (0, 0), B: (3, 0), C: (6, 1.5), D: (8, 0),
  )

  ctz-draw-path("A{below, style: circle}--B{below}-
>C{above}|-|D{below}",
    stroke: black)
})
```

Figure



8.8. Global Styling — `ctz-style`

Set default styles for points and labels:

Code


```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "dot", size: 0.1, fill:
red))

  ctz-def-points(A: (0, 0), B: (3, 0), C: (1.5, 2.5))
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)
  ctz-draw(points: ("A", "B", "C"))

  ctz-style(point: (shape: "cross", size: 0.15,
stroke: blue + 1.5pt))
  ctz-def-centroid("G", "A", "B", "C")
  ctz-draw(points: ("G"))

  ctz-draw(points: ("G"), labels: (
    A: "below left",
    B: "below right",
    C: "above",
    G: "right"
  ))
})
```

Figure



Point shapes: `"dot"`, `"cross"`, `"circle"`, `"square"`

8.9. Angle Marking — `ctz-draw-angle`

Mark and label angles:

Code


```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 0), C: (1, 3))
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black)

  ctz-draw-angle("A", "B", "C",
    label: $alpha$,
    radius: 0.7,
    fill: blue.lighten(70%),
    stroke: blue)

  ctz-draw(points: ("A", "B", "C"), labels: (
    A: "below left",
    B: "below right",
    C: "above"
  ))
})
```

Figure



8.10. Right Angle Mark — `ctz-draw-mark-right-angle`

Mark a right angle with a small square:

Code


```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (4, 0), C: (0, 3))
  ctz-draw(segment: ("A", "B"), stroke: black)
  ctz-draw(segment: ("A", "C"), stroke: black)

  ctz-draw-mark-right-angle("B", "A", "C", size: 0.4)

  ctz-draw(points: ("A", "B", "C"), labels: (
    A: "below left",
    B: "right",
    C: "above"
  ))
})
```

Figure



9. Circles

9.1. Named Circle — `ctz-def-circle` / `ctz-draw-circle`

Define a circle once and draw/label it by name. This uses the "define → draw → label" pattern:

- `ctz-def-circle` stores geometry under a name.
- `ctz-draw-circle` renders it later (you can style it each time).
- `ctz-label-circle` places text relative to the circle without recomputing center/radius.

```
ctz-def-points(O: (0, 0), A: (3, 0))
ctz-def-circle("C1", "O", through: "A")
ctz-draw("C1", stroke: gray)
ctz-label-circle("C1", $C_1$, pos: "above right", dist: 0.2)
```

More label placement controls:

```
ctz-label-circle("C1", $C_1$,
  pos: "above",
  dist: 0.25,
  offset: (0.1, 0))
```

9.2. Circumcircle — `ctz-draw-circumcircle`

Draw the circumscribed circle of a triangle:

```
ctz-draw(circumcircle: ("A", "B", "C"), stroke: blue + 1pt)
```

9.3. Incircle — `ctz-draw-incircle`

Draw the inscribed circle of a triangle:

```
ctz-draw(incircle: ("A", "B", "C"), stroke: green + 1pt)
```

10. Conics

10.1. Ellipse — `ctz-def-ellipse` / `ctz-draw-ellipse`

Define and draw ellipses:

- `ctz-def-ellipse(name, center, rx, ry, angle: 0deg)`
- `ctz-draw-ellipse(center, rx, ry, angle: 0deg, stroke: ..., fill: ...)`
- `ctz-draw(name, ...)` for named ellipses

10.2. Parabola (Focus + Directrix) — `ctz-def-parabola` / `ctz-draw-parabola`

Define and draw parabolas from focus and directrix:

- `ctz-def-parabola(name, focus, directrix, extent: auto, steps: 120)`
- `ctz-draw-parabola(focus, directrix, extent: auto, steps: 120, stroke: ...)`

10.3. Parabola (Focus + p + Angle) — `ctz-draw-parabola-focus`

Draw a parabola using the focus, parameter `p` (vertex-to-focus distance), and opening angle:

- `ctz-draw-parabola-focus(focus, p, angle: 0deg, extent: auto, steps: 120, stroke: ...)`

10.4. Projectile Trajectory — `ctz-def-projectile` / `ctz-draw-projectile`

Define and draw a projectile (parabolic) trajectory:

- `ctz-def-projectile(name, origin, velocity, gravity: 9.81, t-max: auto, steps: 80, y-floor: none, vectors: false, vector-count: 5, vector-scale: 0.12)`
- `ctz-draw-projectile(origin, velocity, gravity: 9.81, t-max: auto, steps: 80, y-floor: none, vectors: false, vector-count: 5, vector-scale: 0.12)`

10.5. Conic Tangents

Draw tangents for conics:

- `ctz-draw-ellipse-tangent(center, rx, ry, t, angle: 0deg, length: auto, stroke: ...)`
- `ctz-draw-parabola-tangent(focus, directrix, t, length: auto, stroke: ...)`
- `ctz-draw-parabola-tangents-from-point(focus, directrix, external, length: auto, stroke: ...)`

10.6. Ellipse Helpers

Descriptive-geometry helpers for ellipse constructions:

- `ctz-ellipse-project-point(center, rx, ry, point, angle: 0deg)` — project a point onto the ellipse along the ray from center
- `ctz-ellipse-tangents-from-point(center, rx, ry, point, angle: 0deg, length: auto)` — tangent lines from an external point
- `ctz-ellipse-circle-intersections(center, rx, ry, circle-center, r, angle: 0deg, steps: 360)` — intersections with a circle (numeric)

10.7. Conics — Visual Example

Code

```
#ctz-canvas(length: 0.6cm, {
  import cetz.draw: *
  ctz-init()


  // Ellipse with labeled points
  let C = (0, 0)
  let rx = 3
  let ry = 2
  let ang = 20deg
  let (F1, F2) = conic.ellipse-foci-raw(C, rx, ry,
angle: ang)
  let P0 = conic.ellipse-angpoint-raw(C, rx, ry,
angle: ang, theta: 0deg)
  let P90 = conic.ellipse-angpoint-raw(C, rx, ry,
angle: ang, theta: 90deg)

  // Register points for labeling
  ctz-def-points(C: C, F1: F1, F2: F2, P0: P0, P90:
P90)

  ctz-draw(ellipse: (C, rx, ry, ang), stroke: black)
  ctz-draw(points: ("C", "F1", "F2", "P0", "P90"),
labels: (
    C: (pos: "above left", offset: (-0.1, 0.1)),
    F1: (pos: "below right", offset: (0.1, -0.1)),
    F2: (pos: "below right", offset: (0.1, -0.1)),
    P0: (pos: "right", offset: (0.1, 0)),
    P90: (pos: "above left", offset: (-0.1, 0.1))
  ))

  // Parabola (focus + directrix)
  let F = (-6, -2)
  let D1 = (-8, -4)
  let D2 = (-8, 1)
  ctz-def-points(F: F)
  ctz-draw(parabola: (F, (D1, D2), 4), stroke: blue)
  ctz-draw(points: ("F",), labels: (F: (pos: "right",
offset: (0.1, 0.1))))
})
```

Figure



Code


```
#ctz-canvas(length: 0.6cm, {
  import cetz.draw: *
  ctz-init()

  // Parabola from focus + directrix
  ctz-draw(parabola: ((-3, 0), ((-4, -2), (-4, 2)),
3), stroke: black)
  ctz-draw(points: ((-3, 0),), labels: (P: "above"))

  // Parabola from focus + p + angle
  ctz-draw-parabola-focus((2, 0), 0.6, angle: 30deg,
extent: 3, stroke: blue)

  // Projectile with vectors
  ctz-draw(projectile: (origin: (0, -3), velocity:
(3, 5), y-floor: -3, vectors: true, vector-count: 5),
stroke: red)
})
```

Figure




Code

```
#ctz-canvas(length: 0.6cm, {
  import cetz.draw: *
  ctz-init()

  // Ellipse tangent
  ctz-draw(ellipse: ((0, 0), 3, 2, 15deg), stroke:
black)
  ctz-draw-ellipse-tangent((0, 0), 3, 2, 45deg,
angle: 15deg, stroke: red)

  // Parabola tangents from external point
  let F = (-4, 0)
  let D1 = (-6, -3)
  let D2 = (-6, 3)
  let P = (-1, 1)
  ctz-draw(parabola: (F, (D1, D2), 4), stroke: blue)
  ctz-draw-parabola-tangents-from-point(F, (D1, D2),
P, stroke: red)
  ctz-draw(points: (P,), labels: (P: "above"))
})
```

Figure



10.8. Circle Through Point — `ctz-draw-circle-through`

Draw a circle with given center passing through a point:

```
ctz-draw(circle-through: ("O", "A"), stroke: blue)
```

10.9. Semicircle — `ctz-draw-semicircle`

Draw a semicircle on a diameter:

```
ctz-draw(semicircle: ("A", "B"), stroke: blue)
```

11. Clipping

Lines that extend infinitely need to be clipped to the visible region.

11.1. Set Clip Region — `ctz-set-clip`

Define a rectangular clip boundary:

```
ctz-set-clip(xmin, ymin, xmax, ymax)
```

11.2. Draw Clipped Line — `ctz-draw-line-global-clip`

Draw a line that is automatically clipped:

```
ctz-draw-line-global-clip("A", "B", add: (2, 2), stroke: blue)
```

The `add` parameter extends the line beyond the two points before clipping.

11.3. Draw Clipped Segment — `ctz-draw-seg-global-clip`

Draw a segment with clipping:

```
ctz-draw-seg-global-clip("A", "B", stroke: red)
```

Code

```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  ctz-init()

  ctz-def-points(A: (0, 0), B: (2, 3))


  // Set clip boundary
  ctz-set-clip(-1, -1, 4, 5)

  // Draw extended line (clipped)
  ctz-draw-line-global-clip("A", "B", add: (5, 5),
stroke: blue)

  // Show clip boundary
  ctz-show-clip(stroke: gray + 0.5pt)

  ctz-draw(points: ("A", "B"), labels: (
    A: "below",
    B: "above left"
  ))
})
```

Figure



12. Raw Algorithms

For direct computation without the point registry, use the `raw` dictionary:

```
// Direct centroid calculation
let center = raw.ctz-def-centroid((0,0,0), (3,0,0), (1.5,2.5,0))

// Distance between points
let d = raw.dist((0,0,0), (3,4,0))  // Returns 5

// Line-line intersection
let pt = raw.line-line((0,0,0), (1,1,0), (0,1,0), (1,0,0), ray: true)
```

Available raw functions:

- **Intersections**: `line-line`, `line-circle`, `circle-circle`
- **Triangle centers**: `ctz-def-centroid`, `ctz-def-circumcenter`, `ctz-def-incenter`, `ctz-def-orthocenter`, `euler-center`, `ctz-def-lemoine`, etc.
- **Transformations**: `ctz-def-rotation`, `reflection`, `translation`, `ctz-def-homothety`, `projection`, `ctz-def-inversion`
- **Utilities**: `ctz-def-midpoint`, `dist`, `angle-at-vertex`, `triangle-area`, etc.

13. Function Reference

13.1. Point Definition

- `ctz-def-points(A: (x, y), ...)` — Define named points
- `ctz-def-line(name, a, b)` — Named line from two points
- `ctz-def-circle(name, center, radius|through)` — Named circle
- `ctz-def-polygon(name, a, b, c, ...)` — Named polygon
- `ctz-def-midpoint(name, a, b)` — Midpoint of segment
- `ctz-def-linear(name, a, b, k)` — Point at ratio k along line
- `ctz-def-regular-polygon([name,] names, center, first)` — Regular n-gon vertices (optionally register polygon name)
- `ctz-def-point-on-circle(name, center, radius, angle)` — Point on circle at angle
- `ctz-def-equilateral(name, a, b)` — Third vertex of equilateral triangle
- `ctz-def-golden(name, a, b)` — Golden ratio point

13.2. Line Constructions

- `ctz-def-perp(n1, n2, line, through)` — Perpendicular through point
- `ctz-def-para(n1, n2, line, through)` — Parallel through point
- `ctz-def-bisect(n1, n2, a, vertex, c)` — Angle bisector
- `ctz-def-mediator(n1, n2, a, b)` — Perpendicular bisector

13.3. Intersections

- `ctz-def-ll(name, line1, line2)` — Line-line intersection
- `ctz-def-lc(names, line, circle)` — Line-circle intersections
- `ctz-def-cc(names, circle1, circle2)` — Circle-circle intersections

13.4. Triangle Centers

- `ctz-def-centroid`, `ctz-def-circumcenter`, `ctz-def-incenter`, `ctz-def-orthocenter`
- `ctz-def-euler`, `ctz-def-lemoine`, `ctz-def-nagel`, `ctz-def-gergonne`, `ctz-def-spieker`
- `ctz-def-feuerbach`, `ctz-def-mittenpunkt`, `ctz-def-excenter`

13.5. Special Triangles

- `ctz-def-medial-triangle(na, nb, nc, a, b, c)` — Medial triangle
- `ctz-def-orthic-triangle(na, nb, nc, a, b, c)` — Orthic triangle
- `ctz-def-intouch-triangle(na, nb, nc, a, b, c)` — Intouch triangle
- `ctz-def-thales-triangle(na, nb, nc, center, radius, ...)` — Right triangle via Thales' theorem

13.6. Transformations

- `ctz-def-rotation(name, source, center, angle)` — Rotation (works on all object types)
- `ctz-def-reflect(name, source, line-a, line-b)` — Reflection
- `ctz-def-translate(name, source, vector)` — Translation
- `ctz-def-homothety(name, source, center, factor)` — Homothety
- `ctz-def-project(name, source, line-a, line-b)` — Projection
- `ctz-def-inversion(name, source, center, radius)` — Inversion (works on points, lines, circles, polygons)
- `ctz-duplicate(target, source, points: auto)` — Duplicate any geometric object

13.7. Drawing

- `ctz-draw(name, ...)` or `ctz-draw(points: ..., labels: ...)` — Draw any object type (polymorphic) or draw/label points using unified API
- `ctz-draw-points(names...)` — Draw points (legacy, prefer unified `ctz-draw()`)
- `ctz-draw-labels(names, placements)` — Label points (legacy, prefer unified `ctz-draw()`)
- `ctz-style(point: (...))` — Set styling
- `ctz-draw-angle(vertex, a, b, ...)` — Mark angle

- `ctz-draw-mark-right-angle(a, vertex, c, ...)` — Right angle mark
- `ctz-draw-segment(a, b, ...)` — Draw segment
- `ctz-draw-measure-segment(a, b, ...)` — Offset measurement with fences and label
- `ctz-draw-path(spec, ...)` — Draw path with per-segment tips
- `ctz-draw-polygon(points...)` — Draw polygon (triangle, quadrilateral, etc.)
- `ctz-draw-fill-polygon(points...)` — Fill polygon
- `ctz-draw-regular-polygon(names, ...)` — Draw regular polygon by vertex names
- `ctz-draw-fill-regular-polygon(names, ...)` — Fill regular polygon by vertex names
- `ctz-draw-circle(name, ...)` — Draw named circle
- `ctz-label-circle(name, label, ...)` — Label named circle
- `ctz-label-polygon(name, label, ...)` — Label named polygon
- `ctz-draw-circumcircle(a, b, c, ...)` — Circumscribed circle
- `ctz-draw-incircle(a, b, c, ...)` — Inscribed circle


13.8. Clipping

- `ctz-set-clip(xmin, ymin, xmax, ymax)` — Set clip region
- `ctz-clear-clip()` — Clear clip region
- `ctz-draw-line-global-clip(a, b, ...)` — Draw clipped line
- `ctz-draw-seg-global-clip(a, b, ...)` — Draw clipped segment

14. Gallery Examples

The following pages showcase advanced geometric constructions using ctz-euclide. Each example demonstrates different features and techniques.

Triangle Centers




```
#ctz-canvas(length: 0.95cm, {
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "dot", size: 0.07, fill: black))

  ctz-def-points(A: (0, 0), B: (7, 0.5), C: (2.5, 5))
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black + 1.5pt)

  ctz-def-centroid("G", "A", "B", "C")
  ctz-def-circumcenter("O", "A", "B", "C")
  ctz-def-incenter("I", "A", "B", "C")
  ctz-def-orthocenter("H", "A", "B", "C")


  // Euler line (H, G, O are collinear)
  ctz-draw(segment: ("H", "O"), stroke: (
    paint: red.darken(20%),
    dash: "dashed",
    thickness: 1.2pt
  ))

  // Circumcircle and incircle
  ctz-draw(circle-through: ("O", "A"), stroke: blue + 1pt)
  ctz-draw(incircle: ("A", "B", "C"), stroke: green.darken(20%) + 1pt)

  // Draw medians to centroid
  ctz-def-midpoint("Ma", "B", "C")
  ctz-def-midpoint("Mb", "A", "C")
  ctz-def-midpoint("Mc", "A", "B")
  ctz-draw(segment: ("A", "Ma"), stroke: gray + 0.7pt)
  ctz-draw(segment: ("B", "Mb"), stroke: gray + 0.7pt)
  ctz-draw(segment: ("C", "Mc"), stroke: gray + 0.7pt)

  ctz-draw(points: ("A", "B", "C", "G", "O", "I", "H"), labels: (
    A: "below left",
    B: "below right",
    C: "above",
    G: "right",
    O: "below",
    I: "right",
    H: "left"
  ))
})
```

Nine-Point Circle




```
#ctz-canvas(length: 0.9cm, {
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "circle", size: 0.06, stroke: black + 0.8pt, fill: white))

  ctz-def-points(A: (0, 0), B: (7, 0), C: (2, 5))
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black + 1.5pt)

  // Midpoints of sides
  ctz-def-midpoint("Ma", "B", "C")
  ctz-def-midpoint("Mb", "A", "C")
  ctz-def-midpoint("Mc", "A", "B")

  // Feet of altitudes
  ctz-def-project("Ha", "A", "B", "C")
  ctz-def-project("Hb", "B", "A", "C")
  ctz-def-project("Hc", "C", "A", "B")


  // Orthocenter and midpoints to vertices
  ctz-def-orthocenter("H", "A", "B", "C")
  ctz-def-midpoint("MHa", "H", "A")
  ctz-def-midpoint("MHb", "H", "B")
  ctz-def-midpoint("MHc", "H", "C")

  // Nine-point circle passes through all 9 points
  ctz-def-euler("N", "A", "B", "C")
  ctz-draw(circle-through: ("N", "Ma"), stroke: purple.darken(10%) + 1.2pt)

  // Draw altitudes
  ctz-draw(segment: ("A", "Ha"), stroke: blue.lighten(30%) + 0.7pt)
  ctz-draw(segment: ("B", "Hb"), stroke: blue.lighten(30%) + 0.7pt)
  ctz-draw(segment: ("C", "Hc"), stroke: blue.lighten(30%) + 0.7pt)

  ctz-draw(points: ("A", "B", "C", "N", "Ma", "Mb", "Mc", "Ha", "Hb", "Hc", "MHa", "MHb", "MHc", "H"), labels: (
    A: "left",
    B: "right",
    C: "above",
    N: "below"
  ))
})
```

Regular Pentagon




```
#ctz-canvas(length: 1cm, {
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "dot", size: 0.08, fill: black))

  ctz-def-points(O: (0, 0), V1: (4, 0))
  ctz-def-regular-polygon("Pent", ("A", "B", "C", "D", "E"), "O", "V1")


  // Pentagon
  ctz-draw("Pent", stroke: black + 1.5pt)

  // All diagonals
  ctz-draw(segment: ("A", "C"), stroke: blue + 0.8pt)
  ctz-draw(segment: ("A", "D"), stroke: blue + 0.8pt)
  ctz-draw(segment: ("B", "D"), stroke: red + 0.8pt)
  ctz-draw(segment: ("B", "E"), stroke: red + 0.8pt)
  ctz-draw(segment: ("C", "E"), stroke: green.darken(20%) + 0.8pt)

  // Center
  ctz-draw(circle-r: (_pt("O"), 4), stroke: gray.lighten(50%) + 0.5pt)

  ctz-draw(points: ("A", "B", "C", "D", "E", "O"), labels: (
    A: "right",
    B: (pos: "above right", offset: (0.1, 0.1),
    C: "above left",
    D: "below left",
    E: "below right",
    O: "below"
  ))
})
```

Inscribed Angle Theorem




```
#ctz-canvas(length: 1cm, {
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "cross", size: 0.11, stroke: black + 1.2pt))

  ctz-def-points(O: (0, 0), R: (4, 0))
  ctz-draw(circle-r: (_pt("O"), 4), stroke: black + 1.2pt)


  // Place points on circle
  ctz-def-rotation("A", "R", "O", 150)
  ctz-def-rotation("C", "R", "O", 30)
  ctz-def-rotation("B", "R", "O", 250)

  // Inscribed angle at B
  ctz-draw(segment: ("A", "B"), stroke: blue + 1.2pt)
  ctz-draw(segment: ("B", "C"), stroke: blue + 1.2pt)
  ctz-draw-angle("B", "A", "C", label: $alpha$, radius: 0.8,
    fill: blue.lighten(70%), stroke: blue)

  // Central angle at O (twice the inscribed angle)
  ctz-draw(segment: ("O", "A"), stroke: red + 1.2pt)
  ctz-draw(segment: ("O", "C"), stroke: red + 1.2pt)
  ctz-draw-angle("O", "A", "C", label: $2alpha$, radius: 1.2,
    fill: red.lighten(70%), stroke: red)

  ctz-draw(segment: ("A", "C"), stroke: gray.lighten(40%) + 0.8pt)
  ctz-draw(points: ("O", "A", "B", "C"), labels: (
    O: "below",
    A: "left",
    B: "right",
    C: "above"
  ))
})
```

Apollonius Circle




```
#ctz-canvas(length: 0.95cm, {
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "dot", size: 0.08, fill: black))

  ctz-def-points(A: (-3, 0), B: (3, 0))

  // Apollonius circle: locus of points P where PA/PB = k
  let k = 2

  // External and internal division points
  ctz-def-points(E: (-5, 0), I: (-1, 0))


  // Center is midpoint of E and I
  ctz-def-midpoint("O", "E", "I")
  ctz-draw(circle-through: ("O", "E"), stroke: purple.darken(10%) + 1.3pt)

  // Show some points on the circle
  ctz-def-rotation("P1", "E", "O", 60)
  ctz-def-rotation("P2", "E", "O", 120)
  ctz-def-rotation("P3", "E", "O", -60)
  ctz-def-rotation("P4", "E", "O", -120)

  // For P1: PA/PB = k = 2
  ctz-draw(segment: ("P1", "A"), stroke: blue + 0.8pt)
  ctz-draw(segment: ("P1", "B"), stroke: red + 0.8pt)
  ctz-draw(segment: ("A", "B"), stroke: black + 1pt)

  ctz-draw(points: ( "B", "O", "E", "I", "P1", "P2", "P3", "P4"), labels: (
    B: "below right",
    E: "left",
    I: "above right",
    P1: "above",
    O: "below"
  ))
})
```

Orthocenter and Altitudes




```
#ctz-canvas(length: 0.85cm, {
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "cross", size: 0.1, stroke: black + 1.2pt))

  ctz-def-points(A: (0, 0), B: (8, 0), C: (2.5, 5.5))
  ctz-set-clip(-1.5, -1.5, 9.5, 7)

  // Triangle
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black + 1.5pt)

  // Extended altitudes (automatically clipped)
  ctz-def-perp("Ha1", "Ha2", ("B", "C"), "A")
  ctz-def-perp("Hb1", "Hb2", ("A", "C"), "B")
  ctz-def-perp("Hc1", "Hc2", ("A", "B"), "C")

  ctz-draw-line-global-clip("A", "Ha1", add: (1, 1.5), stroke: blue + 1pt)
  ctz-draw-line-global-clip("B", "Hb1", add: (1, 1.5), stroke: red + 1pt)
  ctz-draw-line-global-clip("C", "Hc1", add: (1, 2.5), stroke: green.darken(20%) + 1pt)


  // Orthocenter (intersection of altitudes)
  ctz-def-orthocenter("H", "A", "B", "C")

  // Feet of altitudes
  ctz-def-project("Ha", "A", "B", "C")
  ctz-def-project("Hb", "B", "A", "C")
  ctz-def-project("Hc", "C", "A", "B")

  ctz-draw-mark-right-angle("A", "Ha", "B", size: 0.3)
  ctz-draw-mark-right-angle("B", "Hb", "C", size: 0.3)
  ctz-draw-mark-right-angle("C", "Hc", "A", size: 0.3)

  ctz-draw(points: ("A", "B", "C", "H", "Ha", "Hb", "Hc"), labels: (
    A: "left",
    B: "below",
    C: "above right",
    H: "right"
  ))
})
```

Equilateral Triangle Construction




```
#ctz-canvas({
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "cross", size: 0.1, stroke: black + 1.5pt))

  // Base of equilateral triangle
  ctz-def-points("A", (0, 0), "B", (5, 0))
  ctz-def-equilateral("C", "A", "B")

  // Draw triangle
  ctz-draw(line: ("A", "B", "C", "A"), stroke: blue + 1.5pt)

  // Mark 60° angles
  ctz-draw-angle("A", "B", "C", label: $60°$, radius: 0.6, stroke: green + 0.8pt)
  ctz-draw-angle("B", "C", "A", label: $60°$, radius: 0.6, stroke: green + 0.8pt)
  ctz-draw-angle("C", "A", "B", label: $60°$, radius: 0.8, stroke: orange + 0.8pt)


  // Draw circles at vertices
  ctz-draw(circle-r: (_pt("A"), 0.3), stroke: green + 1pt)
  ctz-draw(circle-r: (_pt("B"), 0.3), stroke: green + 1pt)
  ctz-draw(circle-r: (_pt("C"), 0.3), stroke: orange + 1pt)

  // In equilateral triangle, all centers coincide
  ctz-def-centroid("G", "A", "B", "C")

  // Draw medians/altitudes
  ctz-def-midpoint("Ma", "B", "C")
  ctz-def-midpoint("Mb", "A", "C")
  ctz-def-midpoint("Mc", "A", "B")
  ctz-draw(segment: ("A", "Ma"), stroke: (paint: purple, thickness: 0.6pt, dash: "dashed"))
  ctz-draw(segment: ("B", "Mb"), stroke: (paint: purple, thickness: 0.6pt, dash: "dashed"))
  ctz-draw(segment: ("C", "Mc"), stroke: (paint: purple, thickness: 0.6pt, dash: "dashed"))

  ctz-draw(points: ("A", "B", "C", "G"), labels: (
    A: "left",
    B: "right",
    C: "above",
    G: "below"
  ))
})
```

Perpendicular Bisectors and Circumcircle




```
#ctz-canvas({
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "dot", size: 0.08, fill: black))

  // Define triangle
  ctz-def-points("A", (0, 0), "B", (6, 0), "C", (2.5, 5))
  ctz-set-clip(-1, -1, 7, 6)

  // Calculate midpoints
  ctz-def-midpoint("Mab", "A", "B")
  ctz-def-midpoint("Mbc", "B", "C")
  ctz-def-midpoint("Mca", "C", "A")

  // Circumcenter is intersection of perpendicular bisectors
  ctz-def-circumcenter("O", "A", "B", "C")

  // Create perpendicular bisector lines
  ctz-def-mediator("Pab1", "Pab2", "A", "B")
  ctz-def-mediator("Pbc1", "Pbc2", "B", "C")
  ctz-def-mediator("Pca1", "Pca2", "C", "A")

  // Draw triangle
  ctz-draw(line: ("A", "B", "C", "A"), stroke: black + 1.5pt)

  // Draw perpendicular bisectors (clipped)
  ctz-draw-seg-global-clip("Pab1", "Pab2", stroke: blue + 0.8pt)
  ctz-draw-seg-global-clip("Pbc1", "Pbc2", stroke: red + 0.8pt)
  ctz-draw-seg-global-clip("Pca1", "Pca2", stroke: green + 0.8pt)


  // Draw circumcircle
  ctz-draw(circumcircle: ("A", "B", "C"), stroke: purple + 1.2pt)

  // Radii (equal length)
  ctz-draw(segment: ("O", "A"), stroke: gray + 0.4pt)
  ctz-draw(segment: ("O", "B"), stroke: gray + 0.4pt)
  ctz-draw(segment: ("O", "C"), stroke: gray + 0.4pt)

  ctz-draw-mark-right-angle("A", "Mab", "O", size: 0.3)
  ctz-draw-mark-right-angle("B", "Mbc", "O", size: 0.3)
  ctz-draw-mark-right-angle("C", "Mca", "O", size: 0.3)

  ctz-draw(points: ("A", "B", "C", "O", "Mab", "Mbc", "Mca"), labels: (
    A: "left",
    B: "right",
    C: "above",
    O: "below"
  ))
})
```

Thales' Theorem




```
#ctz-canvas({
  import cetz.draw: *
  ctz-init()
  ctz-style(point: (shape: "cross", size: 0.1, stroke: black + 1.5pt))

  // Circle with diameter AB
  ctz-def-points("O", (0, 0), "A", (-3, 0), "B", (3, 0))

  // Point C on circle
  ctz-def-point-on-circle("C", "O", 3, 110)

  // Draw circle and diameter
  ctz-draw(circle-r: (_pt("O"), 3), stroke: gray + 0.8pt)
  ctz-draw(segment: ("A", "B"), stroke: blue + 1.2pt)


  // Draw triangle ACB
  // By Thales' theorem: angle ACB = 90° (inscribed in semicircle)
  ctz-draw(line: ("A", "C", "B", "A"), stroke: black + 1.2pt)

  // Mark the right angle at C
  ctz-draw-mark-right-angle("A", "C", "B", size: 0.4)

  // Draw altitude from C to AB
  ctz-def-project("H", "C", "A", "B")
  ctz-draw(segment: ("C", "H"), stroke: (paint: green, thickness: 0.8pt, dash: "dashed"))

  ctz-draw(points: ("A", "B", "C", "O", "H"), labels: (
    A: "left",
    B: "right",
    C: "above",
    O: "below",
    H: "below left"
  ))
})
```

Inversion




```
#ctz-canvas({
  import cetz.draw: *
  ctz-init()

  ctz-set-clip(-6, -5, 6, 6)

  ctz-def-points(
    O: (0, 0),
    A: (-5, -1.5),
    B: (5, -1.5),
    C: (2, 1),
    D: (-2, 0),
  )

  ctz-def-line("l1", "A", "B")
  ctz-def-circle("c1", "C", radius: 1.2)
  ctz-def-circle("c2", "D", radius: 2)

  ctz-def-inversion("l1i", "l1", "O", 3)
  ctz-def-inversion("c1i", "c1", "O", 3)
  ctz-def-inversion("c2i", "c2", "O", 3)

  ctz-draw(circle-r: (_pt("O"), 3), stroke: black + 1pt)

  ctz-draw("l1", stroke: gray + 0.7pt)
  ctz-draw("c1", stroke: gray + 0.7pt)
  ctz-draw("c2", stroke: gray + 0.7pt)

  ctz-draw("l1i", stroke: blue + 1.1pt)
  ctz-draw("c1i", stroke: red + 1.1pt)
  ctz-draw("c2i", stroke: green.darken(20%) + 1.1pt)

  ctz-draw(points: ("O"), labels: (O: "below left"))
})
```

Inversion Packing



```
#ctz-canvas({
  import cetz.draw: *
  ctz-init()

  let n = 24

  // Inversion circle setup
  ctz-def-points(O: (-4.5, 0))
  ctz-def-line("l1", (-1, 0), (-1, 1))
  ctz-def-line("l2", (1, 0), (1, 1))


  ctz-def-inversion("l1i", "l1", "O", 1)
  ctz-def-inversion("l2i", "l2", "O", 1)

  // Draw inverted lines (outer boundary)
  ctz-draw("l1i", stroke: black + 0.5pt)
  ctz-draw("l2i", stroke: black + 0.5pt)

  // Invert a stack of circles to create the packing
  for i in range(-n, n + 1) {
    let name = "c" + str(i)
    let invname = "ci" + str(i)
    ctz-def-circle(name, (0, 2 * i), radius: 1)
    ctz-def-inversion(invname, name, "O", 1)

    ctz-draw(invname, fill: yellow, stroke: red + 0.4pt)
  }
})
```

Inversion Ladder



```
#ctz-canvas({
  import cetz.draw: *
  ctz-init()

  let O = (-4, 0)
  let R = 3
  let n = 6

  ctz-def-line("l1", (-1, 0), (-1, 1))
  ctz-def-line("l2", (1, 0), (1, 1))
  ctz-def-inversion("l1i", "l1", O, R)
  ctz-def-inversion("l2i", "l2", O, R)

  ctz-set-clip(-2, -2, 4, 8)

  ctz-draw-line-global-clip((-1, 0), (-1, 1), add: (10, 10), stroke: blue + 0.4pt)
  ctz-draw-line-global-clip((1, 0), (1, 1), add: (10, 10), stroke: green + 0.4pt)
  ctz-draw("l1i", stroke: blue + 0.4pt)
  ctz-draw("l2i", stroke: green + 0.4pt)

  for i in range(0, n + 1) {
    let cname = "C" + str(i)
    let cpname = "Cp" + str(i)
    ctz-def-circle(cname, (0, 2 * i), radius: 1)
    ctz-def-inversion(cpname, cname, O, R)
    ctz-draw(cpname, stroke: red + 0.4pt)


    if calc.abs(i) < 4 {
      ctz-draw(cname, stroke: red + 0.4pt)

      ctz-def-points(P1: (1, 2 * i), P2: (-1, 2 * i))
      ctz-def-inversion("P1i", "P1", O, R)
      ctz-def-inversion("P2i", "P2", O, R)

      ctz-draw(segment: ("P1", "P1i"), stroke: green + 0.4pt)
      ctz-draw(segment: ("P2", "P2i"), stroke: blue + 0.4pt)
    }
  }
})
```

15. Advanced Examples

Ellipse and Circles Tangency



```
#ctz-canvas(length: 0.8cm, {
  import cetz.draw: *
  ctz-init()

  let a = 3
  let b = 2

  let blue-stroke = (paint: blue, thickness: 0.8pt)
  let green-stroke = (paint: green, thickness: 0.8pt)
  let red-stroke = (paint: red, thickness: 0.8pt)

  // Axes
  ctz-def-points(O: (0, 0), X1: (-5, 0), X2: (5, 0), Y1: (0, -5), Y2: (0, 5))
  ctz-draw(line: ("X1", "X2"), stroke: (paint: black, thickness: 0.6pt))
  ctz-draw(line: ("Y1", "Y2"), stroke: (paint: black, thickness: 0.6pt))

  // Circles and ellipse
  ctz-def-circle("C", "O", radius: a)
  ctz-def-circle("Cp", "O", radius: b)
  ctz-draw("C", stroke: blue-stroke)
  ctz-draw("Cp", stroke: green-stroke)
  ctz-draw(ellipse: ("O", b, a, 0deg), stroke: red-stroke)

  // Key points H, H'
  ctz-def-points(H: (a / 2, 0), Hp: (0, -b / 2))

  // Lines through H and H'
  ctz-def-perp("L1a", "L1b", ("X1", "X2"), "H")
  ctz-def-para("L2a", "L2b", ("X1", "X2"), "Hp")

  // Intersections with circles
  ctz-def-lc(("M", "M2"), ("L1a", "L1b"), "C", near: "H")
  ctz-def-lc(("N", "N2"), ("L2a", "L2b"), "Cp", near: "Hp")

  // Project M, N onto ellipse
  ctz-def-ellipse-project("Mp", "O", b, a, "M")
  ctz-def-ellipse-project("Np", "O", b, a, "N")

  // Dashed construction
  ctz-draw(line: ("H", "M"), stroke: (paint: black, thickness: 0.6pt, dash: "dashed"))
  ctz-draw(line: ("Hp", "Np"), stroke: (paint: black, thickness: 0.6pt, dash: "dashed"))

  // Radii
  ctz-draw(line: ("O", "M"), stroke: blue-stroke)
  ctz-draw(line: ("O", "N"), stroke: green-stroke)

  // Tangents at M and N
  ctz-def-tangent-at("TgM1", "TgM2", "M", "O")
  ctz-def-tangent-at("TgN1", "TgN2", "N", "O")
  ctz-draw(line: ("TgM1", "TgM2"), stroke: blue-stroke)
  ctz-draw(line: ("TgN1", "TgN2"), stroke: green-stroke)


  // Intersections with axes
  ctz-def-ll("P", ("TgM1", "TgM2"), ("X1", "X2"))
  ctz-def-ll("Pp", ("TgN1", "TgN2"), ("Y1", "Y2"))

  // Perpendicular marks
  ctz-draw-mark-right-angle("TgM1", "M", "O", color: blue)
  ctz-draw-mark-right-angle("TgN1", "N", "O", color: green)

  // Ellipse tangents from P, P'
  ctz-def-ellipse-tangent-from("Tp1", "Tp2", "O", b, a, "P", "Mp")
  ctz-def-ellipse-tangent-from("Tpp1", "Tpp2", "O", b, a, "Pp", "Np")
  ctz-draw(line: ("Tp1", "Tp2"), stroke: red-stroke, mark: (end: ">", start: ">"))
  ctz-draw(line: ("Tpp1", "Tpp2"), stroke: red-stroke, mark: (end: ">", start: ">"))

  // Labels
  ctz-draw(points: ("O", "H", "Hp", "M", "Mp", "N", "Np", "P", "Pp"), labels: (
    O: (pos: "below left", offset: (-0.15, -0.15)),
    H: "below", Hp: "left", M: "above right", Mp: "above",
    N: "left", Np: "below left", P: "right", Pp: "below"
  ))
})
```

Parabola Tangents from Circle



```
#ctz-canvas(length: 0.7cm, {
  import cetz.draw: *
  import "/src/conic.typ" as conic
  ctz-init()

  let F = (0, 0)
  let p = 0.35
  let theta = 25deg

  ctz-set-clip(-4, -4, 12, 12)

  // Draw parabola
  ctz-draw-parabola-focus(F, p, angle: theta, extent: 2.8,
    stroke: (paint: black, thickness: 1pt))

  let (D1, D2, V) = conic.parabola-directrix-raw(F, p, angle: theta)

  // Circle positioned to be tangent to parabola
  let C = (V.at(0) + 10 * (V.at(0) - F.at(0)),
           V.at(1) + 10 * (V.at(1) - F.at(1)))
  let r = 1.4
  ctz-draw(circle-r: (C, r), stroke: (paint: black, thickness: 0.6pt))

  // Three points on circle
  let M1 = (C.at(0) + r * calc.cos(150deg), C.at(1) + r * calc.sin(150deg))
  let M2 = (C.at(0) + r * calc.cos(210deg), C.at(1) + r * calc.sin(210deg))
  let M3 = (C.at(0) + r * calc.cos(250deg), C.at(1) + r * calc.sin(250deg))

  // Draw tangent lines from each M point to parabola
  for M in (M1, M2, M3) {
    let tangents = conic.parabola-tangents-from-point-raw(
      F, D1, D2, M, length: 1.5)
    for t in tangents {
      let (p1, p2, tp) = t
      ctz-draw(line: (p1, p2), stroke: (paint: red, thickness: 0.8pt))
      ctz-draw(points: (tp,), style: (shape: "dot", size: 2pt, fill: blue))
    }
  }

  // Label points
  ctz-def-points(C: C, M1: M1, M2: M2, M3: M3)
  ctz-draw(points: ("C", "M1", "M2", "M3"), labels: (
    C: (pos: "below", offset: (0, -0.25)),
    M1: (pos: "above left", offset: (-0.2, 0.15)),
    M2: (pos: "left", offset: (-0.2, 0)),
    M3: (pos: "below right", offset: (0.2, -0.15)),
  ))
})
```