

taskize

Typst Package

Horizontal Columned Lists

A compact list layout for exercises and multiple-choice questions

Version 0.2.7

Nathan Scheinmann

Contents

- 1. Introduction 3
 - 1.1. Features 3
 - 1.2. Installation 3
 - 1.3. Quick Start 3
- 2. Basic Usage 3
 - 2.1. Column Counts 3
 - 2.2. Auto-Fit Columns 4
 - 2.3. Labels and Formats 4
 - 2.4. Column Spanning 4
 - 2.5. Flow Direction 4
- 3. Configuration 5
 - 3.1. Global Defaults 5
 - 3.2. Resume Numbering 5
- 4. Parameter Reference 5

1. Introduction

`taskize` is a Typst package for horizontal, columned task lists. Items flow left-to-right across columns, making it ideal for exercises, quizzes, and compact lists that need a tidy grid.

1.1. Features

- Indentation-independent parsing
- Horizontal or vertical flow directions
- Flexible column counts and column spanning
- Auto-fit column selection for the densest no-wrap layout
- Multiple label formats and custom label functions
- Resume numbering across task blocks
- Fine-grained spacing and alignment controls

1.2. Installation

Import the package in your Typst document:

```
#import "@preview/taskize:0.2.7": tasks
```

1.3. Quick Start

Code

```
#tasks[  
+ First item  
+ Second item  
+ Third item  
+ Fourth item  
]
```

Preview

a) First item	b) Second item
c) Third item	d) Fourth item

2. Basic Usage

2.1. Column Counts

Use `columns:` or shorthand functions (`tasks2`, `tasks3`, `tasks4`) for quick layouts.

Code

```
#tasks(columns: 3)[  
+ Option A  
+ Option B  
+ Option C  
+ Option D  
+ Option E  
+ Option F  
]
```

Preview

a) Option A	b) Option B	c) Option C
d) Option D	e) Option E	f) Option F

Code

```
#tasks3[  
+ Item 1  
+ Item 2  
+ Item 3  
+ Item 4  
+ Item 5  
+ Item 6  
]
```

Preview

a) Item 1	b) Item 2	c) Item 3
d) Item 4	e) Item 5	f) Item 6

2.2. Auto-Fit Columns

Use `columns: "auto-fit"` to select the largest column count that does not introduce a new item wrap or fixed-size content overflow. Limit the search with `max-columns:`.

Code

```
#tasks(columns: "auto-fit", max-columns: 4)[
+ Medium length task with detail
+ Short
+ Short
+ Short
]
```

Preview

- a) Medium length task with detail
- b) Short
- c) Short
- d) Short

By default, auto-fit uses `auto-fit-mode: "fill"`: span items such as `+( )` may use their full row while later rows remain dense. Use `auto-fit-mode: "uniform"` when every item must fit one ordinary column; in that mode, a wide full-row span can force the whole task block to one column. If an item already wraps in the one-column layout, auto-fit keeps one column, because no no-wrap multi-column layout exists.

2.3. Labels and Formats

Code

```
#tasks(label: "A") [+ Alpha + Beta + Gamma]
#tasks(label: "(1)") [+ One + Two + Three]
#tasks(label: n => "Q" + str(n) + ":") [
+ What is 2 + 2?
+ What is the capital of France?
+ What color is the sky?
]
```

Preview

A) Alpha + Beta + B) Beta
Gamma
C) Gamma
(1) One + Two + Three (2) Two
(3) Three
Q1: What is 2 + 2? Q2: 2?
Q3: What is the capital of France? Q4: What color is the sky?

2.4. Column Spanning

Use `(N)` to span N columns or `( )` to span all columns.

Code

```
#tasks(columns: 3)[
+ (2) Long statement spanning two columns
+ Short
+ ( ) Full width note across all columns
+ Another
]
```

Preview

- a) Long statement spanning two columns b) Short
- c) Full width note across all columns
- d) Another

2.5. Flow Direction

Horizontal is default. Use `flow: "vertical"` to fill columns top-to-bottom.

Code

```
#tasks(columns: 2, flow: "vertical")[
+ a
+ b
+ c
+ d
+ e
+ f
]
```

Preview

- a) a d) d
- b) b e) e
- c) c f) f

3. Configuration

3.1. Global Defaults

Use `tasks-setup()` to set defaults for the rest of the document.

Code

```
#tasks-setup(  
  columns: 3,  
  label-format: "1)",  
  column-gutter: 1.2em,  
  row-gutter: 0.7em,  
  label-weight: "bold",  
)  
  
#tasks[  
  + Item 1  
  + Item 2  
  + Item 3  
  + Item 4  
  + Item 5  
  + Item 6  
]
```

Preview

1) Item 1	2) Item 2	3) Item 3
4) Item 4	5) Item 5	6) Item 6

3.2. Resume Numbering

Code

```
#tasks[  
  + First  
  + Second  
  + Third  
]  
  
#tasks(resume: true)[  
  + Fourth  
  + Fifth  
]  
  
#tasks-reset()  
#tasks[  
  + Back to one  
  + Two again  
]
```

Preview

1) First	2) Second	3) Third
4) Fourth	5) Fifth	
1) Back to one	2) Two again	

4. Parameter Reference

The `tasks()` function supports the following parameters:

Parameter	Type	Default	Description
columns	int/string	2	Number of columns, or "auto-fit" for the largest no-wrap count
label	string/function	"a")	Label format shorthand
label-format	string/function	"a")	Explicit label format
start	int	1	Starting number
resume	bool	false	Continue numbering from previous tasks
column-gutter	length	1em	Space between columns

row-gutter	length	0.6em	Space between rows
max-columns	int/auto	auto	Maximum column count tested by auto-fit; auto means up to the number of items
auto-fit-mode	string	“fill”	"fill" measures spans at their rendered width; "uniform" requires every item to fit one ordinary column
auto-fit-tolerance	length	0.5pt	Measurement tolerance for auto-fit wrap detection
label-width	auto/length	auto	Reserved width for labels
label-align	alignment	right	Label alignment
label-baseline	string/length	“center”	Vertical alignment of labels. With "center" (default), inline content (text, math) shares the same paragraph line as the label for true baseline alignment. Use "top" , "bottom" , or a length offset to override.
label-weight	string	“regular”	Font weight for labels
indent-after-label	length	0.4em	Space after label
indent	length	0pt	Left indentation of the block
above	length	0.5em	Space before the block
below	length	0.5em	Space after the block
flow	string	“horizontal”	“horizontal” or “vertical” flow