

Diet

2025-11-07

Table of contents

Setting up in R	2
Load the data	2
Data cleaning	3
Total meat protein	6
Crohns' disease	6
Patient reported flare	6
Objective flare	8
Ulcerative colitis	10
Patient reported flare	10
Objective flare	12
Dietary Fibre	14
Crohn's disease	14
Patient reported flare	14
Objective flare	16
Ulcerative colitis	18
Patient reported flare	18
Objective flare	20
Polyunsaturated fatty acids	22
Crohn's disease	22
Patient reported flare	22
Objective flare	24
Ulcerative colitis	26
Patient reported flare	26
Objective flare	28
Ultra-processed food	30
Crohn's disease	30
Patient reported flare	30
Objective flare	32

Ulcerative colitis	34
Patient reported flare	34
Objective flare	36

Setting up in R

Load the data

```
library(splines)
library(patchwork)

source("Survival/utils.R")

# Setup analysis environment
analysis_setup <- setup_analysis()
paths <- analysis_setup$paths
demo <- analysis_setup$demo

flare.df <- readRDS(paste0(paths$outdir, "flares-biochem.RDS"))
flare.cd.df <- readRDS(paste0(paths$outdir, "flares-biochem-cd.RDS"))
flare.uc.df <- readRDS(paste0(paths$outdir, "flares-biochem-uc.RDS"))

summon_plot_broom_hr <- function(data){
  data %>%
    # Remove frailty
    dplyr::filter(!stringr::str_detect(term, "frailty")) %>%
    # Rename confidence intervals only if they don't already exist
    {if(!"conf.low" %in% names(.)) dplyr::rename(., conf.low = `2.5 %`, conf.high = `97.5 %`)}
    # Significance flag
    dplyr::mutate(
      significant = (p.value <= 0.05)
    ) %>%
    ggplot(aes(
      y = forcats::as_factor(term),
      x = estimate,
      xmin = conf.low,
      xmax = conf.high,
      colour = significant)) +
    geom_point() +
    geom_errorbarh() +
```

```

    geom_vline(xintercept = 1, linetype = "dashed") +
    xlab("Hazard Ratio (95% CI)") +
    ylab("") +
    scale_colour_manual(values = c("TRUE" = "red", "FALSE" = "black")) +
    theme_minimal()
}

```

Data cleaning

```

# FC has been logged twice - reverse
flare.df %<>%
  dplyr::mutate(FC = exp(FC))

flare.cd.df %<>%
  dplyr::mutate(FC = exp(FC))

flare.uc.df %<>%
  dplyr::mutate(FC = exp(FC))
# So now FC is the log of the FC measurement

# Transform age variable to decades
flare.df %<>%
  dplyr::mutate(
    age_decade = Age/10
  )

flare.cd.df %<>%
  dplyr::mutate(
    age_decade = Age/10
  )

flare.uc.df %<>%
  dplyr::mutate(
    age_decade = Age/10
  )

# Categorized continuous variables

# Categorize meat protein by quantiles
flare.cd.df <- categorize_by_quantiles(flare.cd.df, "Meat_sum", reference_data = flare.df)

```

```

flare.uc.df <- categorize_by_quantiles(flare.uc.df, "Meat_sum", reference_data = flare.df)

# Categorize dietary fibre by quantiles
flare.cd.df <- categorize_by_quantiles(flare.cd.df, "fibre", reference_data = flare.df)
flare.uc.df <- categorize_by_quantiles(flare.uc.df, "fibre", reference_data = flare.df)

# Categorize PUFA by quantiles
flare.cd.df <- categorize_by_quantiles(flare.cd.df, "PUFA_percEng", reference_data = flare.d
flare.uc.df <- categorize_by_quantiles(flare.uc.df, "PUFA_percEng", reference_data = flare.d

# Categorize UPF percentage by quantiles
flare.cd.df <- categorize_by_quantiles(flare.cd.df, "UPF_perc", reference_data = flare.df)
flare.uc.df <- categorize_by_quantiles(flare.uc.df, "UPF_perc", reference_data = flare.df)

# Smoking
# Reorder Smoke factor levels
flare.cd.df %<>%
  dplyr::mutate(
    Smoke = forcats::fct_relevel(Smoke, "Never", "Previous", "Current")
  )

flare.uc.df %<>%
  dplyr::mutate(
    Smoke = forcats::fct_relevel(Smoke, "Never", "Previous", "Current")
  )

# Missingness in smoking
# CD
flare.cd.df %>%
  dplyr::select(hardflare_time,
                hardflare,
                Sex,
                cat,
                IMD,
                dqi_tot,
                Meat_sum_cat,
                Smoke,
                SiteNo) %>%
  # Remove missing on all columns except smoke

```

```
dplyr::filter(!dplyr::if_any(
  .cols = -Smoke,
  .fns = is.na
)) %>%
dplyr::pull(Smoke) %>%
forcats::fct_count(prop = TRUE)
```

```
# A tibble: 4 x 3
  f           n     p
  <fct>    <int> <dbl>
1 Never      268 0.559
2 Previous   170 0.355
3 Current     31 0.0647
4 <NA>        10 0.0209
```

```
# UC
flare.uc.df %>%
  dplyr::select(hardflare_time,
    hardflare,
    Sex,
    cat,
    IMD,
    dqi_tot,
    Meat_sum_cat,
    Smoke,
    SiteNo) %>%
  # Remove missing on all columns except smoke
  dplyr::filter(!dplyr::if_any(
    .cols = -Smoke,
    .fns = is.na
  )) %>%
  dplyr::pull(Smoke) %>%
  forcats::fct_count(prop = TRUE)
```

```
# A tibble: 4 x 3
  f           n     p
  <fct>    <int> <dbl>
1 Never      268 0.541
2 Previous   184 0.372
3 Current     29 0.0586
4 <NA>        14 0.0283
```

Total meat protein

Crohns' disease

Patient reported flare

```
# Only select relevant columns for the imputation model
# Only imputing smoking so remove missing others
# Calculate cumulative hazard

# Soft flare
data_impute_meat_cd_soft <- flare.cd.df %>%
  dplyr::select(softflare_time,
                softflare,
                Sex,
                cat,
                IMD,
                dqi_tot,
                Meat_sum_cat,
                Smoke,
                SiteNo) %>%
  # Remove missing on all columns except smoke
  dplyr::filter(!dplyr::if_any(
    .cols = -Smoke,
    .fns = is.na
  )) %>%
  # Calculate Cumulative hazard
  dplyr::mutate(
    cumhaz = mice::nelsonaalen(
      data = .,
      timevar = softflare_time,
      statusvar = softflare
    )
  )

# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_meat_cd_soft)

pred_matrix[, 'softflare_time'] <- 0

# MICE with 10 imputations
mice_meat_cd_soft <- mice::mice(
  data = data_impute_meat_cd_soft,
```

```


predictorMatrix = pred_matrix,
m = 10,
maxit = 20,
seed = 73,
print = FALSE
)

```

```

# Fit pooled Cox model
with(
  mice_meat_cd_soft,
  coxph(
    Surv(softflare_time, softflare) ~
      Sex +
      cat +
      IMD +
      dqi_tot +
      Meat_sum_cat +
      Smoke +
      frailty(SiteNo)
  )
) %>%
mice::pool() %>%
summary(conf.int = TRUE,
  conf.level = 0.95,
  exponentiate = TRUE) %>%
summon_plot_broom_hr()

```



Objective flare

```
# Hard flare
data_impute_meat_cd_hard <- flare.cd.df %>%
  dplyr::select(hardflare_time,
    hardflare,
    Sex,
    cat,
    IMD,
    dqi_tot,
    Meat_sum_cat,
    Smoke,
    SiteNo) %>%
  # Remove missing on all columns except smoke
  dplyr::filter(!dplyr::if_any(
    .cols = -Smoke,
    .fns = is.na
  )) %>%
  # Calculate Cumulative hazard
  dplyr::mutate(
    cumhaz = mice::nelsonaalen(
      data = .,

```



```

    timevar = hardflare_time,
    statusvar = hardflare
  ))


# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_meat_cd_hard)

pred_matrix[, 'hardflare_time'] <- 0

# MICE with 10 imputations
mice_meat_cd_hard <- mice::mice(
  data = data_impute_meat_cd_hard,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)

# Fit pooled Cox model
with(
  mice_meat_cd_hard,
  coxph(
    Surv(hardflare_time, hardflare) ~
      Sex +
      cat +
      IMD +
      dqi_tot +
      Meat_sum_cat +
      Smoke +
      frailty(SiteNo)
  )
) %>%
mice::pool() %>%
summary(conf.int = TRUE,
  conf.level = 0.95,
  exponentiate = TRUE) %>%
summon_plot_broom_hr()

```



Ulcerative colitis

Patient reported flare

```
# Only select relevant columns for the imputation model
# Only imputing smoking so remove missing others
# Calculate cumulative hazard

# Soft flare
data_impute_meat_uc_soft <- flare.uc.df %>%
  dplyr::select(softflare_time,
                softflare,
                Sex,
                cat,
                IMD,
                dqi_tot,
                Meat_sum_cat,
                Smoke,
                SiteNo) %>%
  # Remove missing on all columns except smoke
  dplyr::filter(!dplyr::if_any(
    .cols = -Smoke,
```

```

    .fns = is.na
  )) %>%
  # Calculate Cumulative hazard
  dplyr::mutate(
    cumhaz = mice::nelsonaalen(
      data = .,
      timevar = softflare_time,
      statusvar = softflare
    )
  )

# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_meat_uc_soft)

pred_matrix[, 'softflare_time'] <- 0

# MICE with 10 imputations
mice_meat_uc_soft <- mice::mice(
  data = data_impute_meat_uc_soft,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)


# Fit pooled Cox model
with(
  mice_meat_uc_soft,
  coxph(
    Surv(softflare_time, softflare) ~
      Sex +
      cat +
      IMD +
      dqi_tot +
      Meat_sum_cat +
      Smoke +
      frailty(SiteNo)
  )
) %>%
mice::pool() %>%
summary(conf.int = TRUE,
  conf.level = 0.95,

```

```

    exponentiate = TRUE) %>%
summon_plot_broom_hr()

```



Objective flare

```

# Hard flare
data_impute_meat_uc_hard <- flare.uc.df %>%
  dplyr::select(hardflare_time,
                hardflare,
                Sex,
                cat,
                IMD,
                dqi_tot,
                Meat_sum_cat,
                Smoke,
                SiteNo) %>%
  # Remove missing on all columns except smoke
  dplyr::filter(!dplyr::if_any(
    .cols = -Smoke,
    .fns = is.na
  )) %>%

```

```

# Calculate Cumulative hazard
dplyr::mutate(
  cumhaz = mice::nelsonaalen(
    data = .,
    timevar = hardflare_time,
    statusvar = hardflare
  ))

# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_meat_uc_hard)

pred_matrix[, 'hardflare_time'] <- 0


# MICE with 10 imputations
mice_meat_uc_hard <- mice::mice(
  data = data_impute_meat_uc_hard,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)

```

```

# Fit pooled Cox model
with(
  mice_meat_uc_hard,
  coxph(
    Surv(hardflare_time, hardflare) ~
      Sex +
      cat +
      IMD +
      dqi_tot +
      Meat_sum_cat +
      Smoke +
      frailty(SiteNo)
  )
) %>%
mice::pool() %>%
summary(conf.int = TRUE,
  conf.level = 0.95,
  exponentiate = TRUE) %>%
summon_plot_broom_hr()

```



Dietary Fibre

Crohn's disease

Patient reported flare

```
# Only select relevant columns for the imputation model
# Only imputing smoking so remove missing others
# Calculate cumulative hazard

# Soft flare
data_impute_fibre_cd_soft <- flare.cd.df %>%
  dplyr::select(softflare_time,
                softflare,
                Sex,
                cat,
                IMD,
                dqi_tot,
                fibre_cat,
                Smoke,
                SiteNo) %>%
  # Remove missing on all columns except smoke
```

```

dplyr::filter(!dplyr::if_any(
  .cols = -Smoke,
  .fns = is.na
)) %>%
# Calculate Cumulative hazard
dplyr::mutate(
  cumhaz = mice::nelsonaalen(
    data = .,
    timevar = softflare_time,
    statusvar = softflare
  ))

# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_fibre_cd_soft)


pred_matrix[, 'softflare_time'] <- 0

# MICE with 10 imputations
mice_fibre_cd_soft <- mice::mice(
  data = data_impute_fibre_cd_soft,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)

# Fit pooled Cox model
with(
  mice_fibre_cd_soft,
  coxph(
    Surv(softflare_time, softflare) ~
      Sex +
      cat +
      IMD +
      dqi_tot +
      fibre_cat +
      Smoke +
      frailty(SiteNo)
  )
) %>%
mice::pool() %>%

```

```
summary(conf.int = TRUE,
        conf.level = 0.95,
        exponentiate = TRUE) %>%
summon_plot_broom_hr()
```



Objective flare

```
# Hard flare
data_impute_fibre_cd_hard <- flare.cd.df %>%
  dplyr::select(hardflare_time,
                hardflare,
                Sex,
                cat,
                IMD,
                dqi_tot,
                fibre_cat,
                Smoke,
                SiteNo) %>%
# Remove missing on all columns except smoke
dplyr::filter(!dplyr::if_any(
  .cols = -Smoke,
```



```

    .fns = is.na
  )) %>%
  # Calculate Cumulative hazard
  dplyr::mutate(
    cumhaz = mice::nelsonaalen(
      data = .,
      timevar = hardflare_time,
      statusvar = hardflare
    )
  )

# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_fibre_cd_hard)

pred_matrix[, 'hardflare_time'] <- 0

# MICE with 10 imputations
mice_fibre_cd_hard <- mice::mice(
  data = data_impute_fibre_cd_hard,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)


# Fit pooled Cox model
with(
  mice_fibre_cd_hard,
  coxph(
    Surv(hardflare_time, hardflare) ~
      Sex +
      cat +
      IMD +
      dqi_tot +
      fibre_cat +
      Smoke +
      frailty(SiteNo)
  )
) %>%
mice::pool() %>%
summary(conf.int = TRUE,
  conf.level = 0.95,

```

```

    exponentiate = TRUE) %>%
  summon_plot_broom_hr()

```



Ulcerative colitis

Patient reported flare

```

# Only select relevant columns for the imputation model
# Only imputing smoking so remove missing others
# Calculate cumulative hazard

# Soft flare
data_impute_fibre_uc_soft <- flare.uc.df %>%
  dplyr::select(softflare_time,
                softflare,
                Sex,
                cat,
                IMD,
                dqi_tot,
                fibre_cat,
                Smoke,

```

```

        SiteNo) %>%
# Remove missing on all columns except smoke
dplyr::filter(!dplyr::if_any(
  .cols = -Smoke,
  .fns = is.na
)) %>%
# Calculate Cumulative hazard
dplyr::mutate(
  cumhaz = mice::nelsonaalen(
    data = .,
    timevar = softflare_time,
    statusvar = softflare
  ))

# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_fibre_uc_soft)

pred_matrix[, 'softflare_time'] <- 0

# MICE with 10 imputations
mice_fibre_uc_soft <- mice::mice(
  data = data_impute_fibre_uc_soft,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)


# Fit pooled Cox model
with(
  mice_fibre_uc_soft,
  coxph(
    Surv(softflare_time, softflare) ~
      Sex +
      cat +
      IMD +
      dqi_tot +
      fibre_cat +
      Smoke +
      frailty(SiteNo)
  )
)

```

```

) %>%
mice::pool() %>%
summary(conf.int = TRUE,
        conf.level = 0.95,
        exponentiate = TRUE) %>%
summon_plot_broom_hr()

```



Objective flare

```

# Hard flare
data_impute_fibre_uc_hard <- flare.uc.df %>%
  dplyr::select(hardflare_time,
                hardflare,
                Sex,
                cat,
                IMD,
                dqi_tot,
                fibre_cat,
                Smoke,
                SiteNo) %>%
# Remove missing on all columns except smoke

```

```

dplyr::filter(!dplyr::if_any(
  .cols = -Smoke,
  .fns = is.na
)) %>%
# Calculate Cumulative hazard
dplyr::mutate(
  cumhaz = mice::nelsonaalen(
    data = .,
    timevar = hardflare_time,
    statusvar = hardflare
  ))

# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_fibre_uc_hard)


pred_matrix[, 'hardflare_time'] <- 0

# MICE with 10 imputations
mice_fibre_uc_hard <- mice::mice(
  data = data_impute_fibre_uc_hard,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)

# Fit pooled Cox model
with(
  mice_fibre_uc_hard,
  coxph(
    Surv(hardflare_time, hardflare) ~
      Sex +
      cat +
      IMD +
      dqi_tot +
      fibre_cat +
      Smoke +
      frailty(SiteNo)
  )
) %>%
mice::pool() %>%

```

```
summary(conf.int = TRUE,
        conf.level = 0.95,
        exponentiate = TRUE) %>%
summon_plot_broom_hr()
```



Polyunsaturated fatty acids

Crohn's disease

Patient reported flare

```
# Only select relevant columns for the imputation model
# Only imputing smoking so remove missing others
# Calculate cumulative hazard

# Soft flare
data_impute_pufa_cd_soft <- flare.cd.df %>%
  dplyr::select(softflare_time,
                softflare,
                Sex,
                cat,
```

```

        IMD,
        dqi_tot,
        PUFA_percEng_cat,
        Smoke,
        SiteNo) %>%
# Remove missing on all columns except smoke
dplyr::filter(!dplyr::if_any(
  .cols = -Smoke,
  .fns = is.na
)) %>%
# Calculate Cumulative hazard
dplyr::mutate(
  cumhaz = mice::nelsonaalen(
    data = .,
    timevar = softflare_time,
    statusvar = softflare
  ))

# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_pufa_cd_soft)

pred_matrix[, 'softflare_time'] <- 0

# MICE with 10 imputations
mice_pufa_cd_soft <- mice::mice(
  data = data_impute_pufa_cd_soft,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)


# Fit pooled Cox model
with(
  mice_pufa_cd_soft,
  coxph(
    Surv(softflare_time, softflare) ~
      Sex +
      cat +
      IMD +
      dqi_tot +

```

```

    PUFA_percEng_cat +
    Smoke +
    frailty(SiteNo)
  )
) %>%
mice::pool() %>%
summary(conf.int = TRUE,
        conf.level = 0.95,
        exponentiate = TRUE) %>%
summon_plot_broom_hr()

```



Objective flare

```

# Hard flare
data_impute_pufa_cd_hard <- flare.cd.df %>%
  dplyr::select(hardflare_time,
                hardflare,
                Sex,
                cat,
                IMD,
                dqi_tot,

```



```

        PUFA_percEng_cat,
        Smoke,
        SiteNo) %>%
# Remove missing on all columns except smoke
dplyr::filter(!dplyr::if_any(
  .cols = -Smoke,
  .fns = is.na
)) %>%
# Calculate Cumulative hazard
dplyr::mutate(
  cumhaz = mice::nelsonaalen(
    data = .,
    timevar = hardflare_time,
    statusvar = hardflare
  ))

# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_pufa_cd_hard)

pred_matrix[, 'hardflare_time'] <- 0

# MICE with 10 imputations
mice_pufa_cd_hard <- mice::mice(
  data = data_impute_pufa_cd_hard,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)


# Fit pooled Cox model
with(
  mice_pufa_cd_hard,
  coxph(
    Surv(hardflare_time, hardflare) ~
      Sex +
      cat +
      IMD +
      dqi_tot +
      PUFA_percEng_cat +
      Smoke +

```

```

    frailty(SiteNo)
  )
) %>%
mice::pool() %>%
summary(conf.int = TRUE,
        conf.level = 0.95,
        exponentiate = TRUE) %>%
summon_plot_broom_hr()

```



Ulcerative colitis

Patient reported flare

```

# Only select relevant columns for the imputation model
# Only imputing smoking so remove missing others
# Calculate cumulative hazard

# Soft flare
data_impute_pufa_uc_soft <- flare.uc.df %>%
  dplyr::select(softflare_time,
                softflare,

```

```

        Sex,
        cat,
        IMD,
        dqi_tot,
        PUFA_percEng_cat,
        Smoke,
        SiteNo) %>%
# Remove missing on all columns except smoke
dplyr::filter(!dplyr::if_any(
  .cols = -Smoke,
  .fns = is.na
)) %>%
# Calculate Cumulative hazard
dplyr::mutate(
  cumhaz = mice::nelsonaalen(
    data = .,
    timevar = softflare_time,
    statusvar = softflare
  ))

# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_pufa_uc_soft)

pred_matrix[, 'softflare_time'] <- 0

# MICE with 10 imputations
mice_pufa_uc_soft <- mice::mice(
  data = data_impute_pufa_uc_soft,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)


# Fit pooled Cox model
with(
  mice_pufa_uc_soft,
  coxph(
    Surv(softflare_time, softflare) ~
      Sex +
      cat +

```

```

    IMD +
    dqi_tot +
    PUFA_percEng_cat +
    Smoke +
    frailty(SiteNo)
  )
) %>%
mice::pool() %>%
summary(conf.int = TRUE,
        conf.level = 0.95,
        exponentiate = TRUE) %>%
summon_plot_broom_hr()

```



Objective flare

```

# Hard flare
data_impute_pufa_uc_hard <- flare.uc.df %>%
  dplyr::select(hardflare_time,
                hardflare,
                Sex,
                cat,

```

```

        IMD,
        dqi_tot,
        PUFA_percEng_cat,
        Smoke,
        SiteNo) %>%
# Remove missing on all columns except smoke
dplyr::filter(!dplyr::if_any(
  .cols = -Smoke,
  .fns = is.na
)) %>%
# Calculate Cumulative hazard
dplyr::mutate(
  cumhaz = mice::nelsonaalen(
    data = .,
    timevar = hardflare_time,
    statusvar = hardflare
  ))

# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_pufa_uc_hard)

pred_matrix[, 'hardflare_time'] <- 0

# MICE with 10 imputations
mice_pufa_uc_hard <- mice::mice(
  data = data_impute_pufa_uc_hard,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)


# Fit pooled Cox model
with(
  mice_pufa_uc_hard,
  coxph(
    Surv(hardflare_time, hardflare) ~
      Sex +
      cat +
      IMD +
      dqi_tot +

```

```

    PUFA_percEng_cat +
    Smoke +
    frailty(SiteNo)
  )
) %>%
mice::pool() %>%
summary(conf.int = TRUE,
        conf.level = 0.95,
        exponentiate = TRUE) %>%
summon_plot_broom_hr()

```



Ultra-processed food

Crohn's disease

Patient reported flare

```

# Only select relevant columns for the imputation model
# Only imputing smoking so remove missing others
# Calculate cumulative hazard

```

```

# Soft flare
data_impute_upf_cd_soft <- flare.cd.df %>%
  dplyr::select(softflare_time,
                softflare,
                Sex,
                cat,
                IMD,
                dqi_tot,
                UPF_perc_cat,
                Smoke,
                SiteNo) %>%
  # Remove missing on all columns except smoke
  dplyr::filter(!dplyr::if_any(
    .cols = -Smoke,
    .fns = is.na
  )) %>%
  # Calculate Cumulative hazard
  dplyr::mutate(
    cumhaz = mice::nelsonaalen(
      data = .,
      timevar = softflare_time,
      statusvar = softflare
    )
  )

# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_upf_cd_soft)

pred_matrix[, 'softflare_time'] <- 0

# MICE with 10 imputations
mice_upf_cd_soft <- mice::mice(
  data = data_impute_upf_cd_soft,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)


# Fit pooled Cox model
with(
  mice_upf_cd_soft,

```

```

coxph(
  Surv(softflare_time, softflare) ~
    Sex +
    cat +
    IMD +
    dqi_tot +
    UPF_perc_cat +
    Smoke +
    frailty(SiteNo)
) %>%
mice::pool() %>%
summary(conf.int = TRUE,
  conf.level = 0.95,
  exponentiate = TRUE) %>%
summon_plot_broom_hr()

```



Objective flare

```

# Hard flare
data_impute_upf_cd_hard <- flare.cd.df %>%

```



```

dplyr::select(hardflare_time,
              hardflare,
              Sex,
              cat,
              IMD,
              dqi_tot,
              UPF_perc_cat,
              Smoke,
              SiteNo) %>%
# Remove missing on all columns except smoke
dplyr::filter(!dplyr::if_any(
  .cols = -Smoke,
  .fns = is.na
)) %>%
# Calculate Cumulative hazard
dplyr::mutate(
  cumhaz = mice::nelsonaalen(
    data = .,
    timevar = hardflare_time,
    statusvar = hardflare
  ))

# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_upf_cd_hard)

pred_matrix[, 'hardflare_time'] <- 0

# MICE with 10 imputations
mice_upf_cd_hard <- mice::mice(
  data = data_impute_upf_cd_hard,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)


# Fit pooled Cox model
with(
  mice_upf_cd_hard,
  coxph(
    Surv(hardflare_time, hardflare) ~

```

```

Sex +
cat +
IMD +
dqi_tot +
UPF_perc_cat +
Smoke +
frailty(SiteNo)
)
) %>%
mice::pool() %>%
summary(conf.int = TRUE,
         conf.level = 0.95,
         exponentiate = TRUE) %>%
summon_plot_broom_hr()

```



Ulcerative colitis

Patient reported flare

```

# Only select relevant columns for the imputation model
# Only imputing smoking so remove missing others

```

```

# Calculate cumulative hazard

# Soft flare
data_impute_upf_uc_soft <- flare.uc.df %>%
  dplyr::select(softflare_time,
                softflare,
                Sex,
                cat,
                IMD,
                dqi_tot,
                UPF_perc_cat,
                Smoke,
                SiteNo) %>%
  # Remove missing on all columns except smoke
  dplyr::filter(!dplyr::if_any(
    .cols = -Smoke,
    .fns = is.na
  )) %>%
  # Calculate Cumulative hazard
  dplyr::mutate(
    cumhaz = mice::nelsonaalen(
      data = .,
      timevar = softflare_time,
      statusvar = softflare
    )
  )


# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_upf_uc_soft)

pred_matrix[, 'softflare_time'] <- 0

# MICE with 10 imputations
mice_upf_uc_soft <- mice::mice(
  data = data_impute_upf_uc_soft,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)

```

```
# Fit pooled Cox model
with(
  mice_upf_uc_soft,
  coxph(
    Surv(softflare_time, softflare) ~
      Sex +
      cat +
      IMD +
      dqi_tot +
      UPF_perc_cat +
      Smoke +
      frailty(SiteNo)
  )
) %>%
mice::pool() %>%
summary(conf.int = TRUE,
  conf.level = 0.95,
  exponentiate = TRUE) %>%
summon_plot_broom_hr()
```



Objective flare

```

# Hard flare
data_impute_upf_uc_hard <- flare.uc.df %>%
  dplyr::select(hardflare_time,
                hardflare,
                Sex,
                cat,
                IMD,
                dqi_tot,
                UPF_perc_cat,
                Smoke,
                SiteNo) %>%
  # Remove missing on all columns except smoke
  dplyr::filter(!dplyr::if_any(
    .cols = -Smoke,
    .fns = is.na
  )) %>%
  # Calculate Cumulative hazard
  dplyr::mutate(
    cumhaz = mice::nelsonaalen(
      data = .,
      timevar = hardflare_time,
      statusvar = hardflare
    )
  )

# Predictor matrix - need to exclude time from the model
pred_matrix <- mice::make.predictorMatrix(data_impute_upf_uc_hard)

pred_matrix[, 'hardflare_time'] <- 0

# MICE with 10 imputations
mice_upf_uc_hard <- mice::mice(
  data = data_impute_upf_uc_hard,
  predictorMatrix = pred_matrix,
  m = 10,
  maxit = 20,
  seed = 73,
  print = FALSE
)

# Fit pooled Cox model
with(
  mice_upf_uc_hard,

```

```

coxph(
  Surv(hardflare_time, hardflare) ~
    Sex +
    cat +
    IMD +
    dqi_tot +
    UPF_perc_cat +
    Smoke +
    frailty(SiteNo)
) %>%
mice::pool() %>%
summary(conf.int = TRUE,
  conf.level = 0.95,
  exponentiate = TRUE) %>%
summon_plot_broom_hr()

```

