

Analysis of Arbitration Methods in Decentralized Systems

Nathan Stephani

GitHub repo: <https://github.com/nathanstephani12/FinalProject>

CS-5833-001: Blockchains and Cryptocurrencies

1 Introduction

As decentralized technologies reshape the architecture of economic and organizational coordination, dispute resolution emerges as a foundational challenge in the governance of trustless systems. Smart contracts allow users to automate transactions without intermediaries, but when ambiguity, disagreement, or off-chain data is involved, code alone is insufficient. Disputes may arise over subjective interpretations, conflicting data, or failed assumptions: requiring mechanisms that balance decentralization, fairness, and security in resolving disagreements. Traditional legal institutions are neither scalable nor compatible with the pseudonymity and global reach of decentralized applications. Thus, decentralized arbitration systems have been developed to bridge the gap between deterministic computation and unpredictable human intent.

This report evaluates three leading arbitration protocols, Kleros, UMA, and Colony, each reflecting a distinct philosophy in the design of decentralized dispute resolution. Kleros applies game-theoretic principles and juror selection to simulate impartial judgment. UMA offers a model based on economically secured consensus over factual claims. Colony embeds arbitration within a broader system of contextual, reputation-weighted governance. These protocols serve as representative case studies for understanding the technical, economic, and governance trade-offs involved in

designing decentralized adjudication mechanisms.

The following analysis is informed by whitepaper review, smart contract logic, empiric data from on-chain events, and theoretical underpinnings drawn from cryptoeconomics and decentralized governance research. Each system is treated as a self-contained model, explored through its architecture, incentives, strengths, and vulnerabilities. The report culminates in a comparative analysis of the models' core features, such as scalability, security, cost, and expressiveness, and reflects on their implications for future developments in decentralized governance and protocol enforcement.

2 Background: Decentralized Arbitration Models

2.1 Kleros: Incentivized Juror-Based Arbitration

Kleros is a decentralized arbitration system designed to emulate the judgment function of traditional courts through economically incentivized crowd-sourced juries. At its core, Kleros selects a random subset of token holders, known as jurors, who stake PNK tokens, the native governance token of Kleros, to participate in a given dispute. The protocol organizes its decision-making into hierarchical subcourts, each optimized for specific subject areas, allowing specialization and modularity in resolving various types of conflicts [1].

Jurors in Kleros operate under Schelling Point logic: they are rewarded when their vote

aligns with the majority, incentivizing truthful judgment under the assumption that others will reason similarly. Votes follow a commit and reveal scheme to reduce manipulation and pre-coordination [1]. When a decision is finalized, arbitration fees are distributed to coherent jurors, and penalties are imposed on incoherent ones, promoting long-term alignment between economic incentives and truthful outcomes.

To defend against corruption or collusion, Kleros uses an appeal escalation system where each appeal stage increases both the cost and the number of jurors, raising the Cost of Corruption exponentially. This makes it economically infeasible for an attacker to manipulate all levels of the system. The Kleros protocol [1] is particularly suited for disputes that require subjective evaluation, such as moderation, curation, or qualitative assessment, where algorithmic resolution is impossible.

2.2 UMA: Economic Consensus Through Data Verification

UMA (Universal Market Access) approaches arbitration from a different angle. It resolves factual disputes over off-chain information using a Data Verification Mechanism (DVM). Rather than selecting jurors or requiring parties to stake tokens on subjective claims, UMA's model revolves around submitting data values to a decentralized oracle, which can be disputed within a given liveness window [2]. If challenged, the claim is escalated to a vote among UMA token holders.

The DVM functions by rewarding participants whose responses fall within a target statistical range, often the mode or interquartile range, depending on the data type [3]. UMA, like Kleros, draws on Schelling Point incentives: assuming that rational actors will converge on the correct value if they expect others to do the same. However, its focus is strictly on objective or verifiable claims, such as prices, timestamps, or event outcomes.

UMA's integrity depends on an economic inequality: the Cost of Corruption (CoC) must always exceed the Profit from Corruption (PfC). This assumption underpins its claim to security, as acquiring enough tokens to sway a vote should cost more than the value that could be captured by doing so. As described in its whitepaper, the system is designed to minimize actual dispute frequency and favor challenge-free finality in most cases [2][3]. Its arbitration model is best understood as a data validation mechanism for systems requiring verifiable truth, rather than human judgment.

2.3 Colony: Contextual, Reputation-Based Governance

Colony's arbitration model is deeply embedded in its reputation-based governance system, in which influence is proportional to a participant's demonstrated contributions. Rather than using juror selection or token-weighted voting, Colony assigns reputation scores across specific domains and skills, allowing arbitration outcomes to reflect contextual expertise. Disputes arise through motions, which must be backed and possibly contested, escalating the issue into a community-wide vote [4].

Votes in Colony also follow a commit and reveal scheme, and outcomes affect both token stakes and reputation scores [4]. Participants who align with the majority gain influence, while dissenters risk losing reputation and future decision-making power. Reputation decays over time, ensuring that recent participation is weighted more heavily than historical involvement, which discourages entrenched hierarchies.

According to the Colony whitepaper, this arbitration method offers a flexible governance model for resolving disputes within collaborative, trust-minimized systems. It emphasizes contextual judgment, peer familiarity, and governance through contribution, in contrast to the more randomized

or economically abstract approaches seen in Kleros or UMA [4].

3. Tools and Methodologies

This analysis draws primarily on the whitepapers and publicly available documentation of each arbitration protocol to establish a clear understanding of their design philosophies, dispute resolution workflows, and incentive structures. Particular attention was paid to how each system defines arbitration triggers, participant roles, voting mechanics, and finality conditions. The whitepapers were treated as primary sources of architectural intent. Key smart contracts of each model were analyzed to determine how events, such as juror draws or votes, were emitted and what constraints were imposed on the creation and handling of disputes.

To complement the protocol-level understanding, empirical data was collected from on-chain sources using blockchain explorers and governance event logs. Metrics such as the number of disputes processed, average time to resolution, participation rates, and appeal frequency were compiled to assess real-world protocol usage and efficiency. These data points were analyzed to evaluate how the systems perform in practice, highlighting throughput, decentralization in decision-making, and cost implications for users. Taken together, the whitepaper-grounded theory, contract implementation, and usage data enabled a holistic evaluation of how each arbitration system functions both in design and in operation.

4. Deep-Dive Analyses of Arbitration Models

4.1 Kleros Arbitration System

Kleros is a decentralized arbitration protocol that simulates judicial processes through token-incentivized, randomly selected juries. Disputes are resolved by jurors who stake PNK tokens in specific subcourts to be eligible for selection. Each subcourt specializes in a particular dispute domain and defines parameters such as number of jurors, cost per juror, and appeal structure. Jurors are rewarded for voting in accordance with the majority—a mechanism inspired by Schelling Point theory—and penalized if they deviate from the final ruling, fostering incentive-aligned truth discovery.



The dispute resolution process unfolds in multiple stages. Once a dispute is initiated and jurors selected, participants submit their vote using a commit-reveal scheme, mitigating risks of vote-buying or strategic influence. If a party disagrees with the verdict, they can trigger an appeal, which increases the number of jurors and arbitration cost. This escalation process is Kleros’s main defense against manipulation, making it prohibitively expensive to corrupt outcomes at higher levels of appeal.

Internally, the protocol is governed by several critical constants. The baseline number of jurors (`MIN_JURORS = 3`) provides a minimal threshold for decentralization and fairness while keeping costs manageable. `MAX_STAKE_PATHS = 4` limits the complexity of the juror selection algorithm based on a Sortition Sum Tree, preserving gas efficiency. Key fixed-point divisors (`ALPHA_DIVISOR`, `MULTIPLIER_DIVISOR`) allow for precise adjustment of slashing and reward rates during stake redistribution. Binary voting options (`AMOUNT_OF_CHOICES = 2`) standardize rulings, making outcomes legible and simplifying the decision-making interface.

for jurors. Together, these architectural choices make Kleros well-suited for scalable, low-cost arbitration, particularly in disputes that require subjective evaluation, where traditional oracles are insufficient.

Data collected from on-chain arbitration records reveals how Kleros operates in practice. Across the sampled disputes, the mean arbitration cost was approximately 0.245 ETH, with a median of 0.07 ETH, indicating that many disputes are low-cost, but outliers with expensive appeals inflate the mean. The cost per juror averaged 0.038 ETH, reinforcing the idea that minimal juror sets can keep dispute resolution economically accessible.

Dispute complexity was generally low: the mean juror count was 4.53, with the most frequent configuration being 3 jurors: consistent with the protocol’s MIN_JURORS setting. Appeals were relatively rare: over 89% of disputes had no appeals, and the mean appeal count was just 0.106. Nonetheless, regression analysis shows that appeals significantly increase both juror count (13.7 jurors per appeal) and cost (0.96 ETH per appeal), highlighting the system's exponential deterrent design. A strong correlation was observed between juror count and cost, validating the stake-based scaling mechanics of the protocol.



Juror behavior data underscores the practical feasibility and resilience of the system. The average number of votes per juror was 11.3, though the median was 2.0, indicating a small number of highly active participants and a broader set of occasional contributors. Crucially, the median participation rate was 98.7%, suggesting that once selected, jurors are highly likely to fulfill their responsibilities. This reliability is vital to ensuring verdict finality and maintaining the security assumptions of Schelling Point-based voting.

These findings support Kleros’s underlying design assumptions: that a decentralized pool of stake-incentivized jurors can produce coherent rulings at low cost, with minimal intervention or appeals. However, the record of disputes with high juror counts and costs also suggests that edge cases, such one dispute that involved 500 jurors, can rapidly become expensive, especially if escalated through multiple appeals.

4.2 UMA Dispute Resolution (DVM)

UMA (Universal Market Access) offers a decentralized arbitration model centered around its Optimistic Oracle (OO) and Data Verification Mechanism (DVM), which are designed to secure the integrity of off-chain assertions in a deterministic and cost-effective manner. Unlike juror-based systems, UMA uses a challenge-response structure: anyone can submit an assertion (e.g., “event X occurred”) and post a bond. The assertion enters a liveness

window, during which any party may dispute the claim by posting an equivalent bond. If no dispute occurs, the assertion is accepted as true; if it is disputed, the claim is escalated to a token-holder vote via the DVM.

The core assertion lifecycle is governed by tightly defined constants. The standard assertion liveness period is set to 7200 seconds (2 hours), providing a fixed window for dispute while keeping arbitration timely. UMA encodes binary truth values using numerical `True = 1e18`, a fixed-point convention that enables compatibility with price oracles and smart contracts. The system also supports a fallback string "Unresolvable" for ambiguous or expired claims. These mechanisms ensure a standardized resolution path across varying assertion types, from price disputes to governance decisions.


In addition to arbitration logic, UMA employs a modular architecture using the Finder pattern. Key components such as the oracle, identifier registry, and governance admin are abstracted through constant-based interfaces like "OptimisticOracleV3", "CollateralWhitelist", and "Registry". This design enhances maintainability, upgradeability, and contract composability, particularly as new oracle versions or dispute formats are introduced. Limits on ancillary data (8192 bytes minus a hard cap of 53 appended characters) keep oracle queries gas-efficient and readable, reinforcing UMA's orientation toward on-chain scalability and low-latency validation.

A review of UMA's dispute data reveals an exceptionally low dispute rate. Of 837 total assertions, only 5 (0.60%) were challenged, confirming the protocol's "optimistic" design assumption: that honest behavior dominates, and disputes are rare exceptions. The average bond posted for assertions was \$1,568 USD, rising to \$3,051 USD when a dispute occurred. This reflects the rational deterrence model—high enough economic risk discourages dishonest

assertions, while also compensating potential disputers for their costs.


The average time to dispute for challenged assertions was approximately 54,192 seconds (~15 hours), while settlement times averaged 134,811 seconds (~37 hours), with a median of 86,568 seconds (~24 hours). These timeframes align with the liveness structure and post-dispute voting windows built into the DVM. Notably, asserters won 99.52% of all settled cases, but only 20% of those that were disputed, suggesting that while disputes are rare, they are typically justified when they do occur. Disputers had an 80% win rate among challenged cases, demonstrating that UMA's economic challenge model is highly effective in filtering out invalid assertions.

Regression analysis further supports these dynamics: bond size correlated modestly with time to dispute ($R^2 = 0.35$), suggesting that more valuable assertions may attract earlier scrutiny. The correlation with settlement time was weaker ($R^2 = 0.08$), indicating that once a dispute is triggered, the process duration is relatively fixed regardless of bond size.



When disaggregated by collateral type, UMA's arbitration behavior shows meaningful divergence between USDC and WETH. USDC accounted for 649 assertions (the majority), while WETH accounted for 185. Despite its lower frequency, WETH disputes tended to involve significantly higher bond values: USDC average bond: \$662.03 USD (median: \$599.94, std dev: \$739.95) vs WETH average bond:

\$4,740.08 USD (median: \$3,689.40, std dev: \$3,882.47). This indicates that WETH-based assertions are often used in higher-value or higher-risk contexts, possibly reflecting different use cases or participant profiles. The higher bond requirements may also discourage casual assertion or challenge behavior, reinforcing UMA's preference for economically serious participation. These disparities show that while UMA maintains a unified arbitration mechanism, the collateral type can shape the practical cost and risk profile of assertions within the system.



4.3 Colony's Reputation Arbitration

Colony takes a fundamentally different approach to decentralized arbitration, emphasizing collaborative governance over adversarial challenge systems. Rather than relying on random jurors or economic bonding, Colony empowers participants to govern through domain-specific reputation, earned by contributing to the system through task completion, project involvement, or other forms of labor.

Arbitration in Colony is not separated from governance: it is embedded in how organizations internally resolve disputes, evaluate work, and make compensation decisions. When disagreements arise (e.g., over task quality, deadline fulfillment, or payment fairness), members initiate motions that can escalate into a structured commit-reveal vote,

with outcomes determined by weighted reputation rather than token holdings or external votes. This model assumes that the most qualified individuals to judge a dispute are those familiar with the context in which it occurred.

Importantly, reputation decays over time, implemented using an exponential decay model governed by the constants `DECAY_NUMERATOR` and `DECAY_DENOMINATOR`, applied once per `DECAY_PERIOD` (every hour). This decay ensures that voting power reflects recent, active participation, discouraging long-term power consolidation by inactive users. Combined with the binary vote encoding (`YAY` = 1, `NAY` = 0) and explicit voting stages (`SUBMIT_END`, `REVEAL_END`, `STAKE_END`), this system creates a flexible and fair arbitration process tailored to the evolving state of the organization [5].

Governance decisions can directly influence financial outcomes using `MAX_PAYOUT_MODIFIER` and `MIN_PAYOUT_MODIFIER`, enabling tasks to be rewarded or penalized based on performance assessments. Security roles (`PAUSER_ROLE`, `MINTER_ROLE`) protect administrative functions and ensure only authorized entities can perform sensitive operations. These constraints reinforce Colony's emphasis on dynamic, context-aware arbitration that reflects both recent contributions and organizational consensus [6].

While most of Colony's arbitration logic is off-chain or reputation-based, the EtherRouter smart contract plays a key role in maintaining on-chain flexibility and upgradeability. EtherRouter acts as a proxy dispatcher, forwarding function calls to implementation contracts defined in a separate registry (often maintained by a colony's governance) [6].

This structure allows colonies to upgrade modules like task management,

funding, or arbitration logic without disrupting the overall organization. Arbitration-related modules can be swapped or extended by governance votes while still interacting with a common routing layer. This architecture supports modular governance and arbitration evolution over time, one of Colony's strongest features for long-term organizations.

Unlike Kleros or UMA, Colony lacks a significant presence of arbitration-related transaction data on public chains. Much of its coordination and governance happens off-chain via platforms like Colony.io, which interface with the protocol through a combination of web-based clients, Gnosis Safe interactions, and meta-transactions.

Due to this off-chain orientation, direct empirical analysis (e.g., number of disputes, voting turnout) is difficult without backend data from the Colony client infrastructure. However, the protocol's architecture strongly favors ongoing, contextual, and community-driven arbitration, especially suited to teams or DAOs with sustained collaboration over time. This contrasts with Kleros and UMA, which are optimized for discrete, isolated dispute events.

5. Comparative Evaluation

The three arbitration systems analyzed—Kleros, UMA, and Colony—each embody a distinct structural paradigm for decentralized dispute resolution. Kleros is built around a formal, court-like architecture with randomly selected jurors who stake tokens for eligibility. It uses subcourts to allow for specialization, and its protocol enforces structured escalation through appeals, increasing juror count and cost with each round.

In contrast, UMA uses a minimalist challenge-response model. Assertions are submitted optimistically and only escalate into disputes when challenged, at which point UMA token holders vote via a decentralized oracle.

UMA relies heavily on economic deterrence and assumes most assertions will be resolved without intervention.

Colony, on the other hand, integrates arbitration directly into its broader organizational framework. Disputes are resolved through reputation-weighted voting within the relevant domain, reflecting contextual expertise and long-term collaboration rather than random selection or open token-holder governance.

Another major structural difference lies in system modularity and on-chain reliance. Kleros and UMA operate primarily through on-chain contracts with deterministic resolution paths, while Colony delegates much of its arbitration and governance logic to off-chain interfaces and modular routing (via the EtherRouter). This results in different levels of transparency, composability, and upgradeability—Colony favors flexibility and iterative change, whereas Kleros and UMA prioritize verifiability and immutability.

Functionally, these systems serve different niches within decentralized governance. Kleros excels at handling subjective, qualitative disputes, such as content moderation or service evaluation, where human judgment and collective reasoning are required. Its design encourages broad participation and enforces consistency through Schelling Point voting incentives.

UMA, by contrast, is tailored for objective, data-driven assertions—especially those tied to financial instruments. Its dispute mechanism functions more like a truth oracle than a deliberative process, ideal for confirming prices, timestamps, or binary conditions.

Colony focuses on collaborative governance and performance evaluation, embedding arbitration within its task and domain logic. It is particularly effective in long-term team settings, where contextual knowledge and accumulated reputation are more meaningful than external objectivity or random selection.

Dispute frequency also varies significantly: UMA disputes are rare and financially escalated, Kleros disputes are more common and explicitly incentivized, while Colony's arbitration is often implicit in ongoing governance activity. This affects not only how disputes arise but also who participates, how decisions are enforced, and how fairness is perceived by participants.

Each protocol makes deliberate tradeoffs between efficiency, expressiveness, and decentralization. Kleros offers robust subjectivity handling and resistance to manipulation, but its layered appeal process can introduce cost and latency. UMA prioritizes low-cost resolution and economic finality but is limited to verifiable facts and may underrepresent minority truths in borderline cases. Colony provides context-aware arbitration and governance cohesion but sacrifices on-chain transparency and global participation in favor of local expertise and off-chain coordination. These tradeoffs reflect their differing assumptions about what constitutes a fair dispute, who should decide, and how trust should be engineered in decentralized systems.

6. Conclusion

The study of Kleros, UMA, and Colony reveals a rich diversity of approaches to decentralized arbitration, each offering compelling solutions to different facets of the problem space. Kleros demonstrates that subjectivity can be managed through economic incentives and game theory, providing a scalable framework for crowd-sourced judgment. UMA shows that economically secure oracles can act as arbiters of truth for objective data, minimizing disputes through well-calibrated risk-reward structures. Colony, in contrast, reimagines arbitration as an embedded feature of collaborative governance, where trust emerges

not from randomness or stake but from accumulated reputation and contextual expertise.

Despite their successes, all three systems grapple with core challenges inherent to decentralized arbitration. Subjective disputes remain difficult to scale without introducing cost or complexity, as seen in Kleros's appeal system. Objective claims, while easier to automate, depend heavily on honest participation and high-value bonding, which can exclude smaller actors or edge cases, as UMA's data shows. Colony's reliance on reputation and off-chain infrastructure raises questions of transparency, verifiability, and accessibility, particularly for less established contributors or observers. More broadly, all three models must continually negotiate the balance between decentralization, efficiency, and legitimacy.

As the Ethereum ecosystem matures and Layer 2 solutions proliferate, the relevance of decentralized arbitration is only growing. Use cases are expanding, from DAO governance and insurance claims to identity verification and protocol upgrades, each demanding mechanisms for resolving ambiguity without centralized oversight. Innovations such as zk-SNARK-enabled privacy in voting, AI-assisted evidence filtering, and modular DAO frameworks are beginning to emerge, offering new design space for hybrid arbitration systems that can combine the strengths of multiple models.

Looking forward, the most effective arbitration solutions may not rely on a single design paradigm, but rather draw selectively from systems like Kleros, UMA, and Colony. Combining juror incentives with oracle-based truth verification or embedding dispute escalation within reputation-weighted governance could yield protocols that are both scalable and context-sensitive. As trustless coordination continues to evolve, so too must the systems that adjudicate its inevitable disagreements: building not just contracts, but consensus.

References

1. C. Lesaege, F. Ast, W. George. “Kleros Whitepaper.” Kleros.io. <https://kleros.io/whitepaper.pdf>
2. “UMA: A Decentralized Financial Contract Platform.”
<https://github.com/UMAprotocol/whitepaper/blob/master/UMA-whitepaper.pdf>
3. “UMA Data Verification Mechanism: Adding Economic Guarantees to Blockchain Oracles.”
<https://github.com/UMAprotocol/whitepaper/blob/master/UMA-DVM-oracle-whitepaper.pdf>
4. A. Rea, D. Kronovet, A. Fischer, J. Rose. “Colony Technical Whitepaper.” https://uploads-ssl.webflow.com/61840fafb9a4c433c1470856/639b50406de5d97564644805_whitepaper.pdf
5. ColonyNetwork. GitHub. <https://github.com/JoinColony/colonyNetwork>
6. “Welcome to Colony Docs.” Colony.io. <https://docs.colony.io/>