


# Improved Compression of the Okamura-Seymour Metric

---


Shay Mozes, Nathan Wallheimer, Oren Weimann

# The Okamura-Seymour Metric Compression Problem



- An undirected, unweighted planar graph  $G = (V, E)$ .
- A set  $S = \{s_1, s_2, \dots, s_k\}$  of  $k$  consecutive vertices on a face  $f_\infty$ .
- A set  $T \subseteq V$  of terminal vertices lying anywhere in the graph.

# The Okamura-Seymour Metric Compression Problem




- An undirected, unweighted planar graph  $G = (V, E)$ .
- A set  $S = \{s_1, s_2, \dots, s_k\}$  of  $k$  consecutive vertices on a face  $f_\infty$ .
- A set  $T \subseteq V$  of terminal vertices lying anywhere in the graph.

## The Okamura-Seymour Metric Compression Problem


Succinctly encode the  $T \times S$  distances to answer  $d(v, s_i)$  queries.

# Results




	Solution	Complexity
$T = S$	Unit-Monge [AGMW'18]	$\tilde{O}(k)$ space, $\tilde{O}(1)$ query
$T = V$	MSSP [Klein'05]	$O(n)$ space, $\tilde{O}(1)$ query
$T \subset V$	Naïve	$\tilde{O}( T  \cdot k)$ space, $O(1)$ query

# Results




	Solution	Complexity
$T = S$	Unit-Monge [AGMW'18]	$\tilde{O}(k)$ space, $\tilde{O}(1)$ query
$T = V$	MSSP [Klein'05]	$O(n)$ space, $\tilde{O}(1)$ query
$T \subset V$	Naïve	$\tilde{O}( T  \cdot k)$ space, $O(1)$ query
$T \subset V$	VC-dimension [LiParter'19]	$\tilde{O}( T  + k^4)$ space, $O(1)$ query

# Results




	Solution	Complexity
$T = S$	Unit-Monge [AGMW'18]	$\tilde{O}(k)$ space, $\tilde{O}(1)$ query
$T = V$	MSSP [Klein'05]	$O(n)$ space, $\tilde{O}(1)$ query
$T \subset V$	Naïve	$\tilde{O}( T  \cdot k)$ space, $O(1)$ query
$T \subset V$	VC-dimension [LiParter'19]	$\tilde{O}( T  + k^4)$ space, $O(1)$ query
$T \subset V$	<b>Today</b>	$\tilde{O}( T  + k^3)$ space, $\tilde{O}(1)$ query

# The Pattern of $v \in V$



$$p_v = \langle d(v, s_2) - d(v, s_1), d(v, s_3) - d(v, s_2), \dots, d(v, s_k) - d(v, s_{k-1}) \rangle$$

# The Pattern of $v \in V$




$$p_v = \langle d(v, s_2) - d(v, s_1), d(v, s_3) - d(v, s_2), \dots, d(v, s_k) - d(v, s_{k-1}) \rangle$$

- $p_v \in \{-1, 0, 1\}^{k-1}$  by the triangle inequality.
- $v$ -to- $s_i$  distances are determined by  $p_v$  and  $d(v, s_1)$ :

$$d(v, s_i) = d(v, s_1) + \underbrace{\sum_{j=1}^{i-1} p_v[j]}_{\text{prefix-sum}}$$



# The Pattern of $v \in V$




## Theorem (Li & Parter [STOC 2019])

There are only  $p_{\#} = O(k^3)$  distinct patterns among all vertices of the graph.

Huge improvement over the trivial  $O(3^k)$  bound. Proved using a VC-dimension argument.

# Li & Parter's Compression

1. One table with the  $O(k^3)$  distinct patterns and their prefix-sums.
2. Every  $v \in T$  stores  $d(v, s_1)$  and a pointer to  $p_v$  in the right table.



Space:  $\tilde{O}(|T| + k^4)$ , Query time:  $O(1)$ .

# Our Algorithmic Results


Let  $p_{\#}$  = the number of distinct patterns among all vertices of  $G$ .

- An  $\tilde{O}(|T| + p_{\#} + k)$  bits compression of the Okamura-Seymour metric, with query time  $\tilde{O}(1)$ .

# Our Algorithmic Results

Let  $p_{\#}$  = the number of distinct patterns among all vertices of  $G$ .


- An  $\tilde{O}(|T| + p_{\#} + k)$  bits compression of the Okamura-Seymour metric, with query time  $\tilde{O}(1)$ .
- An optimal  $\tilde{O}(|T| + k)$  bits compression with  $\tilde{O}(1)$  query for two special cases: (1)  $T$  induces a *connected* subgraph of  $G$ ,



# Our Algorithmic Results

Let  $p_{\#}$  = the number of distinct patterns among all vertices of  $G$ .


- An  $\tilde{O}(|T| + p_{\#} + k)$  bits compression of the Okamura-Seymour metric, with query time  $\tilde{O}(1)$ .
- An optimal  $\tilde{O}(|T| + k)$  bits compression with  $\tilde{O}(1)$  query for two special cases: (1)  $T$  induces a *connected* subgraph of  $G$ ,




# Our Algorithmic Results

Let  $p_{\#}$  = the number of distinct patterns among all vertices of  $G$ .

- An  $\tilde{O}(|T| + p_{\#} + k)$  bits compression of the Okamura-Seymour metric, with query time  $\tilde{O}(1)$ .
- An optimal  $\tilde{O}(|T| + k)$  bits compression with  $\tilde{O}(1)$  query for two special cases: (1)  $T$  induces a *connected* subgraph of  $G$ ,



and (2)  $T$  lies on a single face (not necessarily consecutively).




# Our Combinatorial Results


- An alternative  $p_{\#} = O(k^3)$  proof that exploits planarity beyond VC-dimension. Namely, planar duality and the fact that distances among vertices of  $S$  are bounded by  $k$ .

# Our Combinatorial Results

- An alternative  $p_{\#} = O(k^3)$  proof that exploits planarity beyond VC-dimension. Namely, planar duality and the fact that distances among vertices of  $S$  are bounded by  $k$ .
- In Halin graphs, we show that  $p_{\#} = \Theta(k^2)$ , whereas the VC-dimension argument is limited to showing  $O(k^3)$ .



Tree  $\cup$  Cycle




$\Omega(k^2)$  patterns




# Our Combinatorial Results

- An alternative  $p_{\#} = O(k^3)$  proof that exploits planarity beyond VC-dimension. Namely, planar duality and the fact that distances among vertices of  $S$  are bounded by  $k$ .
- In Halin graphs, we show that  $p_{\#} = \Theta(k^2)$ , whereas the VC-dimension argument is limited to showing  $O(k^3)$ .




Tree  $\cup$  Cycle




$\Omega(k^2)$  patterns

# Our Combinatorial Results

- An alternative  $p_{\#} = O(k^3)$  proof that exploits planarity beyond VC-dimension. Namely, planar duality and the fact that distances among vertices of  $S$  are bounded by  $k$ .
- In Halin graphs, we show that  $p_{\#} = \Theta(k^2)$ , whereas the VC-dimension argument is limited to showing  $O(k^3)$ .



Tree  $\cup$  Cycle





$\Omega(k^2)$  patterns

## Conjecture


The number of distinct patterns over all vertices of a planar graph is  $O(k^2)$ .

# Simplifying Assumption: Binary Patterns

Assume w.l.o.g. that the patterns are over  $\{-1, 1\}$  and not  $\{-1, 0, 1\}$ .  
This can be achieved by subdividing every edge:



# Our Framework: Bisectors




For every  $1 \leq i < k$ , define the following cuts:

$$A_i = \{v \in V \mid p_v[i] = -1\}$$

$$V \setminus A_i = \{v \in V \mid p_v[i] = 1\}$$

# Our Framework: Bisectors




For every  $1 \leq i < k$ , define the following cuts:

$$A_i = \{v \in V \mid p_v[i] = -1\}$$

$$V \setminus A_i = \{v \in V \mid p_v[i] = 1\}$$

A *bisector* is the set of dual arcs  $\beta_i := \{(uv)^* \mid u \in A_i, v \in V \setminus A_i\}$ .

# Our Framework: Bisectors



For every  $1 \leq i < k$ , define the following cuts:

$$A_i = \{v \in V \mid p_v[i] = -1\}$$

$$V \setminus A_i = \{v \in V \mid p_v[i] = 1\}$$

A *bisector* is the set of dual arcs  $\beta_i := \{(uv)^* \mid u \in A_i, v \in V \setminus A_i\}$ .


$\beta_i$  is a simple cycle in the dual graph (oriented counter-clockwise)

# Our Algorithmic Results

Let  $p_{\#}$  = the number of distinct patterns among all vertices of  $G$ .

- An  $\tilde{O}(|T| + p_{\#} + k)$  bits compression of the Okamura-Seymour metric, with query time  $\tilde{O}(1)$ .
- An optimal  $\tilde{O}(|T| + k)$  bits compression with  $\tilde{O}(1)$  query for two special cases: (1)  $T$  induces a *connected* subgraph of  $G$ , and (2)  $T$  lies on a single face (not necessarily consecutively).


# Every Two Bisectors are Arc-disjoint



This is a forbidden configuration!



# Every Two Bisectors are Arc-disjoint




This is a forbidden configuration!

However, it is possible that  $\beta_i$  contains *reversed* arcs of  $\beta_j$ :




# Patterns of Adjacent Vertices Differ in at Most Two Bits

For any  $\{u, v\} \in E(G)$ ,  $u$  and  $v$  are separated by at most two bisectors.



# Patterns of Adjacent Vertices Differ in at Most Two Bits


For any  $\{u, v\} \in E(G)$ ,  $u$  and  $v$  are separated by at most two bisectors.



Hence,  $p_u$  and  $p_v$  differ in at most two bits.

# Patterns of Adjacent Vertices Differ in at Most Two Bits

For any  $\{u, v\} \in E(G)$ ,  $u$  and  $v$  are separated by at most two bisectors.




Hence,  $p_u$  and  $p_v$  differ in at most two bits.

We can use this fact to get a compression of size  $\tilde{O}(|T| + p_{\#} + k)$ .

# Patterns of Adjacent Vertices Differ in at Most Two Bits

For any  $\{u, v\} \in E(G)$ ,  $u$  and  $v$  are separated by at most two bisectors.



Hence,  $p_u$  and  $p_v$  differ in at most two bits.


We can use this fact to get a compression of size  $\tilde{O}(|T| + p_{\#} + k)$ .

Idea:

1. Store one pattern explicitly using  $O(k)$  bits.

# Patterns of Adjacent Vertices Differ in at Most Two Bits

For any  $\{u, v\} \in E(G)$ ,  $u$  and  $v$  are separated by at most two bisectors.



Hence,  $p_u$  and  $p_v$  differ in at most two bits.

We can use this fact to get a compression of size  $\tilde{O}(|T| + p_{\#} + k)$ .

Idea:


1. Store one pattern explicitly using  $O(k)$  bits.
2. Traverse the graph and record the  $O(p_{\#})$  changes between different patterns using a persistent data structure for prefix-sums.

- An alternative  $p_{\#} = O(k^3)$  proof that exploits planarity beyond VC-dimension. Namely, planar duality and the fact that distances among vertices of  $S$  are bounded by  $k$ .
- In Halin graphs, we show that  $p_{\#} = \Theta(k^2)$ , whereas the VC-dimension argument is limited to showing  $O(k^3)$ .

# The Pattern Graph $G_{\mathcal{P}}$

## Definition

The *Pattern graph*  $G_{\mathcal{P}}$  is composed of the union of all the bisectors.






# The Pattern Graph $G_{\mathcal{P}}$

## Definition

The *Pattern graph*  $G_{\mathcal{P}}$  is composed of the union of all the bisectors.




Every  $u, v \in V$  embedded in the same face have the same pattern.

# The Pattern Graph $G_{\mathcal{P}}$

## Definition

The *Pattern graph*  $G_{\mathcal{P}}$  is composed of the union of all the bisectors.




Every  $u, v \in V$  embedded in the same face have the same pattern.

Idea: bound the number of faces of  $G_{\mathcal{P}}$ .

# The Pattern Graph $G_{\mathcal{P}}$

## Definition

The *Pattern graph*  $G_{\mathcal{P}}$  is composed of the union of all the bisectors.



Every  $u, v \in V$  embedded in the same face have the same pattern.


Idea: bound the number of faces of  $G_{\mathcal{P}}$ .

By Euler's formula, the number of faces in  $G_{\mathcal{P}}$  is bounded by the number of *crossings*.

# The Pattern Graph $G_{\mathcal{P}}$

## Definition

The *Pattern graph*  $G_{\mathcal{P}}$  is composed of the union of all the bisectors.




Every  $u, v \in V$  embedded in the same face have the same pattern.

Idea: bound the number of faces of  $G_{\mathcal{P}}$ .

By Euler's formula, the number of faces in  $G_{\mathcal{P}}$  is bounded by the number of *crossings*.

**Our main technical contribution:** every two bisectors can cross at most  $O(k)$  times, hence the number of crossings is  $O(k^3)$ .

# Every Two Bisectors Cross in Opposite Orientation




## Lemma

Let  $p_1, p_2, \dots, p_r$  be the crossing points of  $\beta_i$  and  $\beta_j$ , in the order they appear along  $\beta_i$ .

The crossing points along  $\beta_j$  are reversed  $p_r, p_{r-1}, \dots, p_1$ .


# Two Bisectors can Cross at Most $O(k)$ Times



## Lemma

The number of crossings between  $\beta_i$  and  $\beta_j$  is  $r = O(k)$ .

# Two Bisectors can Cross at Most $O(k)$ Times




## Lemma

*The number of crossings between  $\beta_i$  and  $\beta_j$  is  $r = O(k)$ .*

Idea: Look at the shortest paths from the vertices inside the “pockets”.

# Two Bisectors can Cross at Most $O(k)$ Times




## Lemma

*The number of crossings between  $\beta_i$  and  $\beta_j$  is  $r = O(k)$ .*

Idea: Look at the shortest paths from the vertices inside the “pockets”.



# Two Bisectors can Cross at Most $O(k)$ Times




## Lemma

*The number of crossings between  $\beta_i$  and  $\beta_j$  is  $r = O(k)$ .*

Idea: Look at the shortest paths from the vertices inside the “pockets”.

# Two Bisectors can Cross at Most $O(k)$ Times




## Lemma


*The number of crossings between  $\beta_i$  and  $\beta_j$  is  $r = O(k)$ .*

Idea: Look at the shortest paths from the vertices inside the “pockets”.

## Two Bisectors can Cross at Most $O(k)$ Times




## Two Bisectors can Cross at Most $O(k)$ Times




We get:  $A - B \geq E - F + 2$

# Two Bisectors can Cross at Most $O(k)$ Times




We get:  $A - B \geq E - F + 2 \geq H - G + 4$

## Two Bisectors can Cross at Most $O(k)$ Times



We get:  $A - B \geq E - F + 2 \geq H - G + 4 \geq \dots \geq \Omega(r)$

# Two Bisectors can Cross at Most $O(k)$ Times



We get:  $A - B \geq E - F + 2 \geq H - G + 4 \geq \dots \geq \Omega(r)$

Hence:

$$\Omega(r) \leq A - B \leq k$$

# Open Questions

1. There is a remaining gap between our example that achieves  $\Theta(k^2)$  patterns, and the  $O(k^3)$  upper bound.



# Open Questions

1. There is a remaining gap between our example that achieves  $\Theta(k^2)$  patterns, and the  $O(k^3)$  upper bound.

## Conjecture

The number of distinct patterns over all vertices of a planar graph is  $O(k^2)$ .

# Open Questions

1. There is a remaining gap between our example that achieves  $\Theta(k^2)$  patterns, and the  $O(k^3)$  upper bound.

## Conjecture

The number of distinct patterns over all vertices of a planar graph is  $O(k^2)$ .

2. We've shown how to compress the  $T \times S$  distances into  $\tilde{O}(|T| + p_{\#} + k)$  bits.

# Open Questions

1. There is a remaining gap between our example that achieves  $\Theta(k^2)$  patterns, and the  $O(k^3)$  upper bound.

## Conjecture

The number of distinct patterns over all vertices of a planar graph is  $O(k^2)$ .

2. We've shown how to compress the  $T \times S$  distances into  $\tilde{O}(|T| + p_{\#} + k)$  bits.
  - A simple argument shows that  $\Omega(|T| + k)$  bits are necessary. Are the additive  $\tilde{O}(p_{\#})$  bits in the construction necessary?

# Open Questions

1. There is a remaining gap between our example that achieves  $\Theta(k^2)$  patterns, and the  $O(k^3)$  upper bound.

## Conjecture

The number of distinct patterns over all vertices of a planar graph is  $O(k^2)$ .

2. We've shown how to compress the  $T \times S$  distances into  $\tilde{O}(|T| + p_{\#} + k)$  bits.
  - A simple argument shows that  $\Omega(|T| + k)$  bits are necessary. Are the additive  $\tilde{O}(p_{\#})$  bits in the construction necessary?
  - For small values of  $|T|$ , the naïve compression of  $\tilde{O}(|T| \cdot k)$  bits is still the best known. Can it be improved?

# Open Questions

1. There is a remaining gap between our example that achieves  $\Theta(k^2)$  patterns, and the  $O(k^3)$  upper bound.

## Conjecture

The number of distinct patterns over all vertices of a planar graph is  $O(k^2)$ .

2. We've shown how to compress the  $T \times S$  distances into  $\tilde{O}(|T| + p_{\#} + k)$  bits.
  - A simple argument shows that  $\Omega(|T| + k)$  bits are necessary. Are the additive  $\tilde{O}(p_{\#})$  bits in the construction necessary?
  - For small values of  $|T|$ , the naïve compression of  $\tilde{O}(|T| \cdot k)$  bits is still the best known. Can it be improved?

# Open Questions

1. There is a remaining gap between our example that achieves  $\Theta(k^2)$  patterns, and the  $O(k^3)$  upper bound.

## Conjecture

The number of distinct patterns over all vertices of a planar graph is  $O(k^2)$ .

2. We've shown how to compress the  $T \times S$  distances into  $\tilde{O}(|T| + p_{\#} + k)$  bits.
  - A simple argument shows that  $\Omega(|T| + k)$  bits are necessary. Are the additive  $\tilde{O}(p_{\#})$  bits in the construction necessary?
  - For small values of  $|T|$ , the naïve compression of  $\tilde{O}(|T| \cdot k)$  bits is still the best known. Can it be improved?

The End