

# Texas Covid Data Project

Codename: SHOUTCASE

Connor Bryson

Nathen Byford

Miguel Iglesias

11/11/2021

## Part 1: Data manipulation

```
tb <- read_xlsx(".\\data\\data.xlsx", skip = 2, n_max = 256)

cases <- tb |>
  rename(county = "County Name") |>
  gather(-1, key = "date", value = "cases") |>
  mutate(date = str_extract(date, "[0-9]{2}-[0-9]{2}-[0-9]{4}"),
         date = mdy(date)) |>
  arrange(county)
```

cases

```
## # A tibble: 157,335 x 3
##   county   date     cases
##   <chr>   <date>   <dbl>
## 1 Anderson 2020-03-04     0
## 2 Anderson 2020-03-05     0
## 3 Anderson 2020-03-06     0
## 4 Anderson 2020-03-07     0
## 5 Anderson 2020-03-08     0
## 6 Anderson 2020-03-09     0
## 7 Anderson 2020-03-10     0
## 8 Anderson 2020-03-11     0
## 9 Anderson 2020-03-12     0
## 10 Anderson 2020-03-13     0
## # ... with 157,325 more rows
```

## Part 2: Data merging

```
pop_dat <- read_csv(".\\data\\county-populations.csv")
```

```
## Rows: 255 Columns: 2
```

```
## -- Column specification -----
## Delimiter: ","
## chr (1): county
## dbl (1): population

##
## i Use 'spec()' to retrieve the full column specification for this data.
## i Specify the column types or set 'show_col_types = FALSE' to quiet this message.
```

```
cases <- left_join(cases, pop_dat)
```

```
## Joining, by = "county"
```


```
cases
```

```
## # A tibble: 157,335 x 4
##   county   date      cases population
##   <chr>   <date>   <dbl>      <dbl>
## 1 Anderson 2020-03-04     0      58199
## 2 Anderson 2020-03-05     0      58199
## 3 Anderson 2020-03-06     0      58199
## 4 Anderson 2020-03-07     0      58199
## 5 Anderson 2020-03-08     0      58199
## 6 Anderson 2020-03-09     0      58199
## 7 Anderson 2020-03-10     0      58199
## 8 Anderson 2020-03-11     0      58199
## 9 Anderson 2020-03-12     0      58199
## 10 Anderson 2020-03-13     0      58199
## # ... with 157,325 more rows
```

### part 3: Data visualization

```
# Find top 16 counties, and total.
top_count <- slice_max(pop_dat, order_by = population, n = 17) |> pull(county)

cases |> filter(county %in% top_count, county != "Total") |>
  group_by(county) |>
  mutate(new_cases = c(cases[1], diff(cases)),
         new_cases = slide_dbl(new_cases, mean, .before = 6)) |>
  ggplot(aes(x = date, y = new_cases, group = county)) +
  geom_line(aes(color = county), size = .7, alpha = .6) +
  scale_y_continuous(labels = scales::comma, limits = c(0, NA)) +
  scale_color_viridis_d() +
  labs(title = "Incident Cases",
       subtitle = "For 16 Largest Counties in Texas",
       y = "Cases",
       x = "Date")
```




## Part 4: Facet Graphics

```
cases |> filter(county %in% top_count, county != "Total") |>
  group_by(county) |>
  mutate(new_cases = c(cases[1], diff(cases)),
         new_cases = slide_dbl(new_cases, mean, .before = 6)) |>
  ggplot(aes(x = date, y = new_cases, group = county)) +
  geom_line(size = 0.7, alpha = .6) +
  scale_y_continuous(labels = scales::comma, limits = c(0, NA)) +
  labs(title = "Incident Cases",
       subtitle = "For 16 Largest Counties in Texas",
       x = "Date",
       y = "New Cases") +
  theme(legend.position = "none",
        axis.text.x = element_text(angle = 30, vjust = 1, hjust = 1),
        strip.text = element_text(size = 6)) +
  facet_wrap(~county, nrow = 4)
```


## Incident Cases

For 16 Largest Counties in Texas



## Part 5: Cases per 10k

```
cases |> filter(county %in% top_count, county != "Total") |>
  group_by(county) |>
  mutate(new_cases = c(cases[1], diff(cases)),
         new_cases = slide_dbl(new_cases, mean, .before = 6),
         cases_10k = (new_cases/population)*1e5) |>
  ggplot(aes(x = date, y = cases_10k, group = county)) +
  geom_line(aes(color = county), size = .7, alpha = .6) +
  scale_y_continuous(labels = scales::comma, limits = c(0, NA)) +
  scale_color_viridis_d() +
  labs(title = "Cases per 10k",
       subtitle = "For 16 Largest Counties in Texas",
       y = "Cases per 10k",
       x = "Date")
```



```
cases |> filter(county %in% top_count, county != "Total") |>
  group_by(county) |>
  mutate(new_cases = c(cases[1], diff(cases)),
         new_cases = slide_dbl(new_cases, mean, .before = 6),
         cases_10k = (new_cases/population)*1e5) |>
  ggplot(aes(x = date, y = cases_10k, group = county)) +
  geom_line(size = 0.7, alpha = .6) +
  scale_y_continuous(labels = scales::comma, limits = c(0,NA)) +
  labs(title = "Cases Per 10k",
       subtitle = "For 16 Largest Counties in Texas",
       x = "Date",
       y = "Cases per 10k") +
  theme(legend.position = "none",
        axis.text.x = element_text(angle = 30, vjust = 1, hjust = 1),
        strip.text = element_text(size = 6))+
  facet_wrap(~county, nrow = 4)
```

## Cases Per 10k

For 16 Largest Counties in Texas

