

InSpec


Compliance as Code



InSpec is compliance as code – a human-readable language for automating the continuous testing and compliance auditing of your entire infrastructure.

Compliance as Code

ACCELERATED CYCLE



ROLE OF THE COMPLIANCE OFFICER



One language, One workflow

SSH Control

SSH supports two different protocol versions. The original version, SSHv1, was subject to a number of security issues. Please use SSHv2 instead to avoid these.

Mapping Compliance Document to InSpec

6.2.1 Set SSH Protocol to 2 (Scored)

Profile Applicability:

- Level 1

Description:

SSH supports two different and incompatible protocols: SSH1 and SSH2. SSH1 was the original protocol and was subject to security issues. SSH2 is more advanced and secure.

Rationale:

SSH v1 suffers from insecurities that do not affect SSH v2.

Audit:


To verify the correct SSH setting, run the following command and verify that the output is as shown:

```
# grep "^Protocol" /etc/ssh/sshd_config
Protocol 2
```

Remediation:

Edit the /etc/ssh/sshd_config file to set the parameter as follows:

```
Protocol 2
```



Mapping Compliance Document to InSpec

6.2.1 Set SSH Protocol to 2 (Scored)

Profile Applicability:

- Level 1

Description:

SSH supports two different and incompatible protocols: SSH1 and SSH2. SSH1 was the original protocol and was subject to security issues. SSH2 is more advanced and secure.

Rationale:

SSH v1 suffers from insecurities that do not affect SSH v2.

Audit:

To verify the correct SSH setting, run the following command and verify that the output is as shown:

```
# grep "^Protocol" /etc/ssh/sshd_config
Protocol 2
```

Remediation:

Edit the /etc/ssh/sshd_config file to set the parameter as follows:

```
Protocol 2
```

control 'ssh-6.2.1' do

title 'Set SSH Protocol to 2'
desc "

SSH supports two different ...

"

end

Mapping Compliance Document to InSpec

6.2.1 Set SSH Protocol to 2 (Scored)

Profile Applicability:

- Level 1

Description:

SSH supports two different and incompatible protocols: SSH1 and SSH2. SSH1 was the original protocol and was subject to security issues. SSH2 is more advanced and secure.

Rationale:

SSH v1 suffers from insecurities that do not affect SSH v2.

Audit:

To verify the correct SSH setting, run the following command and verify that the output is as shown:

```
# grep "^Protocol" /etc/ssh/sshd_config  
Protocol 2
```

Remediation:

Edit the /etc/ssh/sshd_config file to set the parameter as follows:

```
Protocol 2
```

control 'ssh-6.2.1' do

title 'Set SSH Protocol to 2'
desc "

SSH supports two different ...

"

describe sshd_config do

its('Protocol') { should cmp('2') }

end

end

Mapping Compliance Document to InSpec

6.2.1 Set SSH Protocol to 2 (Scored)

Profile Applicability:

- Level 1

Description:

SSH supports two different and incompatible protocols: SSH1 and SSH2. SSH1 was the original protocol and was subject to security issues. SSH2 is more advanced and secure.

Rationale:

SSH v1 suffers from insecurities that do not affect SSH v2.

Audit:

To verify the correct SSH setting, run the following command and verify that the output is as shown:

```
# grep "^Protocol" /etc/ssh/sshd_config
Protocol 2
```

Remediation:

Edit the /etc/ssh/sshd_config file to set the parameter as follows:

```
Protocol 2
```

control 'ssh-6.2.1' do

impact 1.0

title 'Set SSH Protocol to 2'

desc "

SSH supports two different ...

"

describe sshd_config do

its('Protocol') { should cmp('2') }

end

end

Differences in verifying compliance policy

DOCUMENTATION

SSH supports two different protocol versions. The original version, SSHv1, was subject to a number of security issues. Please use SSHv2 instead to avoid these.

SCRIPTING TOOLS

```
> grep "^Protocol" /etc/ssh/
sshd_config | sed 's/Protocol //'
2
```

COMPLIANCE LANGUAGE

```
describe sshd_config do
  its('Protocol') { should eq 2 }
end
```

COMPLIANCE LANGUAGE

```
control 'ssh-1234' do
  impact 1.0
  title 'Server: Set protocol version to SSHv2'
  desc "
    Set the SSH protocol version to 2. Don't use legacy
    insecure SSHv1 connections anymore...
  "

  describe sshd_config do
    its('Protocol') { should eq 2 }
  end
end
```

InSpec

ONE LANGUAGE



Oracle Solaris 11



InSpec for Windows

```
control 'windows-base-201' do
  impact 1.0
  title 'Strong Windows NTLMv2 Authentication Enabled; Weak LM
        Disabled'

  desc '
    @link: http://support.microsoft.com/en-us/kb/823659
  '

  describe registry_key
    ('HKLM\System\CurrentControlSet\Control\Lsa') do
      it { should exist }
      its('LmCompatibilityLevel') { should eq 4 }
    end
  end
end
```

InSpec

ONE LANGUAGE



Oracle Solaris 11



- **Baremetal**
- **VMs**
- **Containers**

Different ways to run InSpec

Test your machine locally

```
> inspec exec test.rb
```

Test a machine remotely via SSH

```
> inspec exec test.rb -i identity.key -t ssh://root@172.17.0.1
```

No ruby/agent on the node

Test a machine remotely via WinRM

```
> inspec exec test.rb -t winrm://Admin@192.168.1.2 --password super
```

No ruby/agent on the node

Test Docker Container

```
> inspec exec test.rb -t docker://5cc8837bb6a8
```

no SSH/agent in the container

InSpec

ONE LANGUAGE



Oracle Solaris 11



- Baremetal
- VMs
- Containers
- **Databases**
- **API endpoints (e.g. cloud)**

Database Testing

```
describe mysql_session.query("SELECT
user,host FROM mysql.user WHERE host = '%'")
do
  its(:stdout) { should be empty }
end
```


Cloud Provider Testing

```
security_groups.each do |security_group|
  describe security_group do
    it { should_not
have_inbound_rule().with_source('0.0.0.0/0')
}
  end
end
```

InSpec


ONE WORKFLOW

Security meets operations




InSpec


Each team uses separate tools



Unified language



Continuous Workflow



InSpec

Turn security and compliance into code

- Translate **compliance** into Code
- **Clearly** express statements of policy
- Move risk to build/test from **runtime**
- Find issues **early**
- Write code **quickly**
- Run code **anywhere**
- **Inspect** machines, data, and APIs



PART OF A PROCESS OF CONTINUOUS COMPLIANCE



A SIMPLE EXAMPLE OF AN INSPEC CIS RULE

```
control 'cis-1.4.1' do
  title '1.4.1 Enable SELinux in /etc/grub.conf'
  desc '
    Do not disable SELinux and
    enforcing in your GRUB configuration. These are important
    security features that prevent attackers from escalating their
    access to your systems. For reference see ...
  '
  impact 1.0
  expect(grub_conf.param 'selinux').to_not eq '0'
  expect(grub_conf.param 'enforcing').to_not eq '0'
end
```