

Parameters	Unit	GIM3505-8
Winding method	Δ / Y	Y
Rated voltage	V	24
Driver board model	/	GDZ34
Voltage Range	V	12~40
Rated Power	W	37
Rated torque	N.M	0.67
Peak torque	N.M	1.79
Rated Speed after reduce	RPM	230
Max Speed after reduce	RPM	400
Rated current	A	1.53
Peak current	A	3.99
Phase-to-phase resistance	Ω	5.47
Phase-to-phase inductance	mH	0.48
Speed constant	rpm/v	16.67
Torque constant	N.M/A	0.44
Number of pole pairs	Pairs	11
Gear Rate	/	8:1
Gear type	/	Planetary
Reducer gear material	/	ALU
Reducer gear backlash	arcmin	15
Motor weight without driver	g	84.0
Motor weight with driver	g	97.0
Size without Driver	mm	Ø43*23.6
Size with Driver	mm	Ø43*30
Max.Axial load	N	75
Max.Radial load	N	300
Noise	dB	< 60
Communication	/	CAN&485
the second encoder on the output shaft	/	NO
Protection grade	/	IP54
Working temperature	°C	' -20~+80
Resolution of the encoder on the driver	Bit	14bit
Can support separate encoder or not	/	YES
Can support custom brakes	/	YES