

Parameters	Unit	GIM4310-10
Winding method	Δ / Y	Y
Rated voltage	V	24
Driver board model	/	GDZ34
Voltage Range	V	12~40
Rated Power	W	31
Rated torque	N.M	1.63
Peak torque	N.M	7.98
Rated Speed after reduce	RPM	101
Max Speed after reduce	RPM	212
Rated current	A	1.30
Peak current	A	10.67
Phase-to-phase resistance	Ω	1.96
Phase-to-phase inductance	mH	0.67
Speed constant	rpm/v	8.83
Torque constant	N.M/A	2.61
Number of pole pairs	Pairs	14
Gear Rate	/	10:1
Gear type	/	Planetary
Reducer gear material	/	STELL
Reducer gear backlash	arcmin	15
Motor weight without driver	g	217.0
Motor weight with driver	g	227.0
Size without Driver	mm	Ø53*32
Size with Driver	mm	Ø53*38
Max.Axial load	N	125
Max.Radial load	N	500
Noise	dB	< 60
Communication	/	CAN&485
the second encoder on the output shaft	/	NO
Protection grade	/	IP54
Working temperature	°C	' -20~+80
Resolution of the encoder on the driver	Bit	14bit
Can support separate encoder or not	/	YES
Can support custom brakes	/	YES