

Parameters	Unit	GIM6010-8	
Winding method	Δ / Y	Y	Y
Rated voltage	V	24	48
Driver board model	/	GDS68(SDC104)	GDZ468H
Voltage Range	V	12~56	12~48
Rated Power	W	252	138
Rated torque	N.M	5.00	4.20
Peak torque	N.M	11.00	11.27
Rated Speed after reduce	RPM	120	220
Max Speed after reduce	RPM	420	554
Rated current	A	10.50	2.87
Peak current	A	23.40	20.02
Phase-to-phase resistance	Ω	0.44	0.44
Phase-to-phase inductance	mH	0.23	0.23
Speed constant	rpm/v	11.54	11.54
Torque constant	N.M/A	0.47	0.65
Number of pole pairs	Pairs	14	14
Gear Rate	/	8:1	8:1
Gear type	/	Planetary	Planetary
Reducer gear material	/	STEEL	STEEL
Reducer gear backlash	arcmin	15	15
Motor weight without driver	g	370.0	370.0
Motor weight with driver	g	388.0	388.0
Size without Driver	mm	Ø80*29.5	Ø80*29.5
Size with Driver	mm	Ø80*40	Ø80*40
Max.Axial load	N	200	200
Max.Radial load	N	800	800
Noise	dB	< 60	< 60
Communication	/	CAN	CAN & 485
the second encoder on the output shaft	/	YES	YES
Protection grade	/	IP54	IP54
Working temperature	°C	'-20~+80	'-20~+80
Resolution of the encoder on the driver	Bit	16bit	16bit
Can support separate encoder or not	/	NO	NO
Can support custom brakes	/	YES	YES