

Parameters	Unit	GIM8115-9	
Winding method	Δ / Y	Δ	Y
Rated voltage	V	24	48
Driver board model	/	GDS810(SDC103)	GDZ810
Voltage Range	V	12~48	12~48
Rated Power	W	190	218
Rated torque	N.M	13.00	15.27
Peak torque	N.M	40.00	54.55
Rated Speed after reduce	RPM	100	120
Max Speed after reduce	RPM	129	125
Rated current	A	7.90	4.55
Peak current	A	24.69	25.21
Phase-to-phase resistance	Ω	0.28	1.05
Phase-to-phase inductance	mH	0.26	0.81
Speed constant	rpm/v	5.38	2.60
Torque constant	N.M/A	1.62	2.25
Number of pole pairs	Pairs	21	21
Gear Rate	/	9:1	9:1
Gear type	/	Planetary	Planetary
Reducer gear material	/	STEEL	STEEL
Reducer gear backlash	arcmin	15	15
Motor weight without driver	g	660.0	660.0
Motor weight with driver	g	705.0	705.0
Size without Driver	mm	Ø96*41	Ø96*41
Size with Driver	mm	Ø96*48.5	Ø96*48.5
Max.Axial load	N	225	225
Max.Radial load	N	900	900
Noise	dB	< 60	< 60
Communication	/	CAN	CAN & 485
the second encoder on the output shaft	/	NO	YES
Protection grade	/	IP54	IP54
Working temperature	°C	'-20~+80	'-20~+80
Resolution of the encoder on the driver	Bit	14bit	14bit
Can support separate encoder or not	/	NO	NO
Can support custom brakes or not	/	YES	YES