# BestBuy Books Project Documentation

Generated on: 2026-03-15 12:27:39

## Project Overview

BestBuy_Books is an e-commerce platform built with Laravel framework supporting multi-role users (Administrators, Merchants, Customers) for managing books, orders, chats, and issue reports. The project implements real-time communication between users and administrators, merchant registration approval process, and role-based access control.

## Directory Structure

```
|   |- .editorconfig
|   |- .env
|   |- .env.example
|   |- .gitattributes
|   |- .gitignore
|   |- .styleci.yml
|   |- artisan
|   |- CHANGELOG.md
|   |- composer.json
|   |- composer.lock
|   ... (+13 more files)
|   |- .git/
|   |   |- COMMIT_EDITMSG
|   |   |- config
|   |   |- description
|   |   |- HEAD
|   |   |- index
|   |   |- ORIG_HEAD
|   |   |- packed-refs
|   |   |- hooks/
|   |   |   |- applypatch-msg.sample
|   |   |   |- commit-msg.sample
|   |   |   |- fsmonitor-watchman.sample
|   |   |   |- post-update.sample
|   |   |   |- pre-applypatch.sample
|   |   |   |- pre-commit.sample
|   |   |   |- pre-merge-commit.sample
|   |   |   |- pre-push.sample
|   |   |   |- pre-rebase.sample
|   |   |   |- pre-receive.sample
|   |   |   ... (+4 more files)
|   |   |- info/
|   |   |   |- exclude
|   |   |   |- refs
|   |   |- logs/
|   |   |   |- HEAD
|   |   |   |- refs/
|   |   |   |   |- heads/
|   |   |   |   |   |- 12.x
|   |   |   |   |   |- main
|   |   |   |   |- remotes/
|   |   |- objects/
|   |   |   |- 02/
|   |   |   |   |- f39f492c6ba85bd27580cf456baa038b9684f1
|   |   |   |- 03/
|   |   |   |   |- 413767ed9981cf7bdcf6f060622080ba86cd62
|   |   |   |   |- d76ecc0c854b3b90db68e1c8bb0fd1a7b17d98
|   |   |   |- 04/
|   |   |   |   |- 463798a2eeec60d99908a19061369823149408
|   |   |   |   |- f3ad109065671c3b47e17994da0bda3bfed240
|   |   |   |- 05/
|   |   |   |   |- 47cd27f1c069739cab7283045fb8e1925df2b2
|   |   |   |- 06/
|   |   |   |   |- 565a15d5371a9ee855a24e57baa51f6a25c291
|   |   |   |- 07/
|   |   |   |   |- 0e39ec16038738e70844e42724472ddf4d603a
|   |   |   |   |- ba3337733c41881f35073e7e2635344757b2ad
|   |   |   |- 08/
|   |   |   |   |- bfefaf5e26d94b9d0efe1616dd8d9789ddd92d
|   |   |   |- 09/
|   |   |   |   |- 51b27e00ebcc1eb04df52ca31892e24ae65fab
|   |   |   |   |- b1578dd3db1e0881b073c2f01083308bf2c07f
|   |   |   |   |- cb7006a309676414e6aff583339584bcab3d47
|   |   |   |- 0a/
|   |   |   |   |- 2aa7e459bc58e7e6b01913f2821563390b3141
|   |   |   |   |- eb520f54efd7acb94d540e410117ae0bc27ada
|   |   |   |- 0c/
|   |   |   |   |- 3e43c673782167fb8b5b95023cb8e489a6a7ab
|   |   |   |   |- 5afcbcd15285ac36af761196424210bf3f3ddc
|   |   |   |   |- 5dd9dca723cb8c8d0503fb16f30d619cb60cbb
|   |   |   |   |- c159f050525e63768cdd0ee064a094d8155c1d
|   |   |   |- 0d/
|   |   |   |   |- 593e8c1a34656c96e4f7ede0c2a2b6d44e7705
|   |   |   |   |- daa664404faa031a2ec18da94f1574acc0e1de
|   |   |   |- 0e/
|   |   |   |   |- 58c32fe810a72a486b3f9d41e74fe397db555c
|   |   |   |   |- f2231256f0588a21317776e723b415763da29f
|   |   |   |- 0f/
|   |   |   |   |- 00accc49e455624b3365cbdf32c9c28e45314f
|   |   |   |   |- 62c2b3fd420815bde5e238f768346b91a779bf
|   |   |   |- 10/
|   |   |   |   |- 5bde0fd05cf767f5d7af762485fd10d31c6085
|   |   |   |- 11/
|   |   |   |   |- 5d615be08e70cfeb5e81fdccf6fc1b498d5ed2
|   |   |   |- 12/
|   |   |   |   |- dd58447dcc561bd7a51c05ceaa16377e7ccd5b
|   |   |   |- 13/
|   |   |   |   |- 05196626978ecdc11946b48dd6699de0c7a4f7
|   |   |   |   |- 144ec8fc62a1595f2b7d28fba28b1b2e5bddc7
|   |   |   |   |- 7852f4c354a8ccaea68a87939f66c7e3591b6c
|   |   |   |   |- 8365e93f4658213b2ea5230016b0ca83168c8d
|   |   |   |   |- a5fa40e44e8eb40298c2b9ac51f110bb5edea0
|   |   |   |   |- dcb7ce7eb6c9d3a75bc95ddfdcd024337f1418
|   |   |   |- 14/
|   |   |   |   |- 89d0e0f1d7b358509b0226a279d62081c11410
|   |   |   |   |- b73c704521c7a790eb7a560bd2b0f425c53e91
|   |   |   |- 16/
|   |   |   |   |- 0fb623d1627047d23015441c5f5af199afe001
|   |   |   |   |- 5e4f3dca9a6862c328dcb42f15614e73a561bb
|   |   |   |- 17/
|   |   |   |   |- 833d33c06f53d23d49df064c90207c3e7ea5e0
```

```
|   |   |   |   |- a1bd7a6a24d8b44476d965ff7417293050ac2d
|   |   |   |- 18/
|   |   |   |   |- a1d45defc0202ce9e940318da3e99d8ead351d
|   |   |   |   |- f6b83584a62601e9b6a8c4295fd62159571d36
|   |   |   |- 19/
|   |   |   |   |- 5e14c2e4745fd855a029405ec60b6987dea8ae
|   |   |   |   |- ae3e3639cec7d1a86c8ae4c6bf505bff8d9a16
|   |   |   |   |- e56b74941a88148ed121018fb176b0e1f2d57d
|   |   |   |   |- f290861d160514a70ff12148612ff44be8ebbe
|   |   |   |- 1a/
|   |   |   |   |- ceac01e810c1d68e05641f8eb24abb393ec944
|   |   |   |   |- e5ae2c3c08097555d2ffd1ddc278c5a5392ee3
|   |   |   |- 1b/
|   |   |   |   |- 2a4521ef9f5ef0b7595682e9ff37ce83e9bb28
|   |   |   |- 1c/
|   |   |   |   |- 3e1536922f51a07e91337d3ae047de90b69710
|   |   |   |- 1e/
|   |   |   |   |- 7a7c6501e5656272f4a3e23639f194b23971f3
|   |   |   |- 1f/
|   |   |   |   |- 3502c5e23899a613a7821ccd8f392c38ec0dbd
|   |   |   |- 20/
|   |   |   |   |- 1b58b06e94e037b3a6fe66dd2608c4afb10ad0
|   |   |   |   |- 4d9920e98bded363a84acebf96402e808a6f8f
|   |   |   |   |- a90cf0dc75c1b9b410be6d679848e2a5c9b4d6
|   |   |   |- 21/
|   |   |   |   |- 097df19065ca6535c28dd82e0faef8244fc330
|   |   |   |- 22/
|   |   |   |   |- dfe5265db4da856b65c828c89ea49c62a1c7d8
|   |   |   |- 23/
|   |   |   |   |- 55c492409c6b7f4338820676ce18c7f25520cd
|   |   |   |   |- 7ae2504312a352049847ce3889c7126baede93
|   |   |   |- 24/
|   |   |   |   |- 3f9d1dc6751c5fd64dacf4def7be51cddf5744
|   |   |   |   |- be0215a8e0bda4c80356b0a8ae1abcfd0de6dc
|   |   |   |- 25/
|   |   |   |   |- 173dc980a616040b7cd8d8efbc432dd8bf6700
|   |   |   |   |- 746424580a1206e6995f034ecbf8b9cc7cd607
|   |   |   |   |- 7b6f3ac68c675cc6434aa7af8fdada7c3d2fa1
|   |   |   |- 26/
|   |   |   |   |- 5bb0e742b7b0b2852638c11400d4316a770a1c
|   |   |   |- 29/
|   |   |   |   |- ac8a17ac763983f3c799d60d3a123bb2e61c6c
|   |   |   |- 2a/
|   |   |   |   |- 0c89f199544e7fa6c9d5200ba367725d1ad2bb
|   |   |   |- 2b/
|   |   |   |   |- 50391ef5e4175c312cf5fbe9e643aa02c18c5c
|   |   |   |   |- a35d0ee6c5e3eb40c766eafee5db51ea85bf25
|   |   |   |- 2f/
|   |   |   |   |- 6f21b8671c3be04d589237645db5f8bc25757c
|   |   |   |   |- d0d9003dcfbb293f801ffdc97c4f134106748d
|   |   |   |- 32/
|   |   |   |   |- 734e7e98caaaee8a89b3bd2795fb3064ae17d4
|   |   |   |   |- 8a96a446daddf375b04ab3c82b1d5e6599d422
|   |   |   |   |- c9337d2cb58414e11df914ad3458b1f689db76
|   |   |   |   |- e586b3ac6550c27a325b647bf4d02df4838961
|   |   |   |- 33/
|   |   |   |   |- 89d2a564e355fcd78630c2ca757bdbabf3d89d
|   |   |   |   |- cf5363236b6cdb798416a2de3bc009db9091cd
|   |   |   |- 34/
|   |   |   |   |- 42ab935f2013aaa51b8c42967f04b9c5bdcdfd
|   |   |   |   |- a31feb16a6e9dc5495823793cb4d217394192d
|   |   |   |   |- cc58fb2311fe3e7dec52aa73ab811251957598
|   |   |   |- 35/
|   |   |   |   |- 0f9da9d9469c62a012da7bd539c6983e206349
|   |   |   |   |- 20d0438e169e9924f24790f26151a947e9dd26
|   |   |   |- 36/
|   |   |   |   |- 22a8f37c2accfa385618240df70ac74fea342a
|   |   |   |- 37/
|   |   |   |   |- 3ecc5301d85f0b95696f7aee9362eafc014347
|   |   |   |   |- 69ec750591f07dad4dc62e15a147ace7ce176c
|   |   |   |- 38/
|   |   |   |   |- 67f225c7425a2ed06c23c1f5b883e449dae51d
|   |   |   |   |- 71c98187defa540d4507393be4372f3e725da9
|   |   |   |- 39/
|   |   |   |   |- 26ecf72a8b0ceb1d796215be602d6b6accf846
|   |   |   |   |- 47ba4c3c86ffa1da6c385c73c51adb6071f9b8
|   |   |   |   |- 4cc4af4690c25742488bcdc387625172671646
|   |   |   |- 3b/
|   |   |   |   |- 1e4b7df1a4dc0044fe18ea23d9522954664b94
|   |   |   |   |- 4723849f81e2b5a579a2feee9b168e3b264441
|   |   |   |- 3c/
|   |   |   |   |- 04917c6297beebd2b891dd8d0afdd8d1b67a44
|   |   |   |   |- 86a7e8b586229c6241948cf1fe69ddcedf4dc4
|   |   |   |- 3d/
|   |   |   |   |- 0eb93d883d9ca3a5f4a7afe382b8416d889292
|   |   |   |   |- a8b946dc65904b99a3a8df2e5583b2fda489c5
|   |   |   |   |- cab2ecf9d0ad1355ec81d36765c81cdcebf11c
|   |   |   |   |- f32f942cf7f250a77d4a15840df83fa291f70e
|   |   |   |- 3f/
|   |   |   |   |- 07a199cee2cfcb12a2b8528967a02cc149ccc9
|   |   |   |- 41/
|   |   |   |   |- ecf05abf23b96e9f4e61ba48a225d4fec5cc4a
|   |   |   |   |- f13c40151b764f5d7b343a29ecf791078aa20e
|   |   |   |- 42/
|   |   |   |   |- 0e5793b32ba6641b2f0fb22fe1f784143232c9
|   |   |   |   |- 525794debcfb9a89a2f9e2032f73c15a68168f
|   |   |   |- 43/
|   |   |   |   |- ea815cbb839b6a8a5529d7d74d3c328f59c30b
|   |   |   |- 44/
|   |   |   |   |- f58bf3bfd02cc65a01d8a27ddaf6a4abd5a5ba
|   |   |   |   |- f6c404492beee32e69694c4eee97c26a852f09
|   |   |   |- 45/
|   |   |   |   |- 5b6e053a14f0c1acbb8ee8316c16553c6c2374
|   |   |   |   |- 73162568490eece6f91b1140c76f10378f6455
|   |   |   |   |- aae23d9e5bc755664f09982176022bfb874fff
|   |   |   |   |- c8e4c59f98fa0783ac50ec0b0eb90221e39be5
|   |   |   |- 47/
|   |   |   |   |- e0bcae7db46ee12fab0b37600b449f49cd388c
|   |   |   |- 48/
|   |   |   |   |- 2d6ebf4624f4429e418eb4587847c9cb19a349
|   |   |   |   |- 332e8decff1882df027fcee679df0c04e5b475
|   |   |   |   |- 5edc7cbcb951a33294a81707ac4ed49f685186
|   |   |   |- 49/
|   |   |   |   |- 79fa9181c0c3c83be522d899b0e5b739d8c9a4
|   |   |   |   |- 7daba9d275beaadb61add8fa86958ef4fce822
|   |   |   |   |- 886c3e90a7d6463222afe15d33dfeb9359fe31
|   |   |   |- 4a/
|   |   |   |   |- 940fb709adc32283d56a9f3f5312441a0058cd
|   |   |   |- 4b/
|   |   |   |   |- ba803e60517f4597280d42f006da8ddf31b081
|   |   |   |- 4c/
|   |   |   |   |- 66ab677a37eb2ade2824ede0b9d3f65b866232
|   |   |   |- 4d/
|   |   |   |   |- 5331fd14c7f2c0bb8ec6f36acedba62fb9905f
|   |   |   |- 4e/
|   |   |   |   |- 02e4a5c211ab9a27a7e38de0c1acd8bbdff705
|   |   |   |   |- 7016660c9c905914a5c8c4f7953c90b7dafc20
|   |   |   |- 4f/
```

```
|   |   |   |   |- a3a83c440dd6cf8e2009a5db55fca9dfee3462
|   |   |   |   |- eda76c957177bccbdc8bfde2d83ddc0e0d65d5
|   |   |   |- 50/
|   |   |   |   |- 39051a42f8cd76266ed674d329946a0fe43db5
|   |   |   |- 52/
|   |   |   |   |- 09c5ca969e3bd75e0b7c8426682b557f7138e1
|   |   |   |   |- a920516ef96180d7e6a4d09bb504c97bc4613f
|   |   |   |- 55/
|   |   |   |   |- 1eedbd27d7729c0fca4778131aa44b9e6d8efe
|   |   |   |- 56/
|   |   |   |   |- f47e7aa90f83ad136741fcd09ac2987642c9ab
|   |   |   |- 57/
|   |   |   |   |- a82b58e0ca6e3140a3c2472408731327f43d94
|   |   |   |   |- e2f7afee32eebfb826c5ed425ee6f19ee61a8c
|   |   |   |   |- ea18c75664fb18703d053e190ba9444ac29315
|   |   |   |- 58/
|   |   |   |   |- 76c49c28baa628e03b5a6055132b4da5357269
|   |   |   |   |- e1959a710d841e91399eb9414e0dd67b1cf85d
|   |   |   |- 5a/
|   |   |   |   |- d730b405ab24f6453e086d0b39961ba79eb301
|   |   |   |- 5b/
|   |   |   |   |- 800412677c2c4a3085367d5b177438ec4f8ea8
|   |   |   |- 5c/
|   |   |   |   |- b382f4efb848faf0f03ce001c80032fa7dd1d4
|   |   |   |- 5d/
|   |   |   |   |- c30a0d5a1313a1a2b2cd1d01a43ba96b160776
|   |   |   |   |- d371c2c4d8ec4bbc290dd1352198c22291d0a0
|   |   |   |- 5e/
|   |   |   |   |- b9326ed748b8c0f683f3c119e653998ada26bc
|   |   |   |- 5f/
|   |   |   |   |- 037ef4dccaec082c63fe83736e9a7ea0bb783f
|   |   |   |   |- baaffd77d7a3f5c69d649ff9548afa1ce18388
|   |   |   |- 60/
|   |   |   |   |- 9a88fff9d0f80199dd2c66c6bd340b6fa9dc0e
|   |   |   |- 61/
|   |   |   |   |- 7a9b9c6ce57d155ac8aaede47996fbc157e451
|   |   |   |   |- e0bca70fd2f09553fe1ce5c23562fa1d4238df
|   |   |   |- 62/
|   |   |   |   |- 693547966b41887f52722877147db6f1f83823
|   |   |   |   |- 96801a4b2d8524359b72762c2cbcce35c6b405
|   |   |   |- 63/
|   |   |   |   |- 17c4e0258a8e27b15ca8f9b813c38b986a3884
|   |   |   |- 64/
|   |   |   |   |- 7f0be5776e155fdd39123714fefb22cded7dbb
|   |   |   |   |- b9bdd7138ace5359f9b14e89b19994022b62d0
|   |   |   |- 66/
|   |   |   |   |- c794fff9f614c6bccd3840805285ce8e26f99e
|   |   |   |- 68/
|   |   |   |   |- 7ac841ce19250fb2cff70247ff081a1cf97267
|   |   |   |   |- 86e110af24e89a2ede4c57429e82e45757b7f6
|   |   |   |- 69/
|   |   |   |   |- 2c5a8c065a74968e09163864d8ccbb2f35bf97
|   |   |   |- 6a/
|   |   |   |   |- 2cf8d4f34aefa399ab5430aaed3ecb9fc843e0
|   |   |   |- 6b/
|   |   |   |   |- 337eb84891970de554a5dd05a863a4e4d91404
|   |   |   |- 6c/
|   |   |   |   |- 58b2c140ed78392080b4e262c1ac780e1e7a77
|   |   |   |   |- e33faa01e5f2f13d1064b9e218a43d8791a068
|   |   |   |- 6d/
|   |   |   |   |- 9c3b7bacc984241436aee7000a5b27f276480a
|   |   |   |- 70/
|   |   |   |   |- 5570b43f3a048623759a159020d7ee0739cc57
|   |   |   |   |- c858826864b46ce5fde9be54a877ae0456c836
|   |   |   |   |- fe203ed3722e44b650f98db9fc04602dc8a729
|   |   |   |- 71/
|   |   |   |   |- 1839d0a8a29e2da42ca5426434445769e6bb49
|   |   |   |   |- 23b17f99b7c773a18e31f057904a9d144b7ebd
|   |   |   |- 75/
|   |   |   |   |- 0a5770cbf714168ec1291e28ef94e5eb58460f
|   |   |   |   |- 1306afe1b05cb5cf75b2d2919238d519f335e4
```

### File: .env

```
APP_NAME=Laravel
APP_ENV=local
APP_KEY=base64:TZ63Sc+475o3BZpoQCRWlEywb+/1xFp6H1unr/fH3hA=
APP_DEBUG=true
APP_URL=http://localhost

APP_LOCALE=en
APP_FALLBACK_LOCALE=en
APP_FAKER_LOCALE=en_US

APP_MAINTENANCE_DRIVER=file
# APP_MAINTENANCE_STORE=database

# PHP_CLI_SERVER_WORKERS=4

BCRYPT_ROUNDS=12

LOG_CHANNEL=stack
LOG_STACK=single
LOG_DEPRECATIONS_CHANNEL=null
LOG_LEVEL=debug

DB_CONNECTION=mysql
DB_HOST=127.0.0.1
DB_PORT=3306
DB_DATABASE=bestbuy_book
DB_USERNAME=root
DB_PASSWORD=

SESSION_DRIVER=database
SESSION_LIFETIME=120
SESSION_ENCRYPT=false
SESSION_PATH=/
SESSION_DOMAIN=null

BROADCAST_CONNECTION=log
FILESYSTEM_DISK=local
QUEUE_CONNECTION=database

CACHE_STORE=database
# CACHE_PREFIX=

MEMCACHED_HOST=127.0.0.1

REDIS_CLIENT=phpredis
REDIS_HOST=127.0.0.1
REDIS_PASSWORD=null
REDIS_PORT=6379

MAIL_MAILER=log
MAIL_SCHEME=null
MAIL_HOST=127.0.0.1
MAIL_PORT=2525
MAIL_USERNAME=null
MAIL_PASSWORD=null
MAIL_FROM_ADDRESS="hello@example.com"
MAIL_FROM_NAME="${APP_NAME}"

AWS_ACCESS_KEY_ID=
AWS_SECRET_ACCESS_KEY=
AWS_DEFAULT_REGION=us-east-1
AWS_BUCKET=
AWS_USE_PATH_STYLE_ENDPOINT=false

VITE_APP_NAME="${APP_NAME}"
```

### File: .styleci.yml

```
php:
  preset: laravel
  disabled:
    - no_unused_imports
  finder:
    not-name:
      - index.php
js: true
css: true
```

### File: CHANGELOG.md

```
# Release Notes

## [Unreleased](https://github.com/laravel/laravel/compare/v12.11.1...12.x)

## [v12.11.1](https://github.com/laravel/laravel/compare/v12.11.0...v12.11.1) - 2025-12-23

* Use environment variable for `DB_SSLMODE` - Postgres by [@robsontenorio](https://github.com/robsontenorio) in https://github.com/laravel/laravel/pull/6727
* fix: ensure APP_URL does not have trailing slash in filesystem by [@msamgan](https://github.com/msamgan) in https://github.com/laravel/laravel/pull/6728

## [v12.11.0](https://github.com/laravel/laravel/compare/v12.10.1...v12.11.0) - 2025-11-25

* fix: cookies are not available for subdomains by default by [@joostdebruijn](https://github.com/joostdebruijn) in https://github.com/laravel/laravel/pull/6705
* Fix PHP 8.5 PDO Driver Specific Constant Deprecation by [@RyanSchaefer](https://github.com/RyanSchaefer) in https://github.com/laravel/laravel/pull/6710
* Ignore Laravel compiled views for Vite  by [@QistiAmal1212](https://github.com/QistiAmal1212) in https://github.com/laravel/laravel/pull/6714

## [v12.10.1](https://github.com/laravel/laravel/compare/v12.10.0...v12.10.1) - 2025-11-06

* Update schema URL in package.json by [@robinmiau](https://github.com/robinmiau) in https://github.com/laravel/laravel/pull/6701

## [v12.10.0](https://github.com/laravel/laravel/compare/v12.9.1...v12.10.0) - 2025-11-04

* Add background driver by [@barryvdh](https://github.com/barryvdh) in https://github.com/laravel/laravel/pull/6699

## [v12.9.1](https://github.com/laravel/laravel/compare/v12.9.0...v12.9.1) - 2025-10-23

* [12.x] Replace Bootcamp with Laravel Learn by [@AhmedAlaa4611](https://github.com/AhmedAlaa4611) in https://github.com/laravel/laravel/pull/6692
* [12.x] Comment out CLI workers for fresh applications by [@timacdonald](https://github.com/timacdonald) in https://github.com/laravel/laravel/pull/6693

## [v12.9.0](https://github.com/laravel/laravel/compare/v12.8.0...v12.9.0) - 2025-10-21

**Full Changelog**: https://github.com/laravel/laravel/compare/v12.8.0...v12.9.0

## [v12.8.0](https://github.com/laravel/laravel/compare/v12.7.1...v12.8.0) - 2025-10-20

* [12.x] Makes test suite using broadcast's `null` driver by [@nunomaduro](https://github.com/nunomaduro) in https://github.com/laravel/laravel/pull/6691

## [v12.7.1](https://github.com/laravel/laravel/compare/v12.7.0...v12.7.1) - 2025-10-15

* Added `failover` driver to the `queue` config comment.  by [@sajjadhossainshohag](https://github.com/sajjadhossainshohag) in https://github.com/laravel/laravel/pull/6688
## [v12.7.0](https://github.com/laravel/laravel/compare/v12.6.0...v12.7.0) - 2025-10-14
```

```
**Full Changelog**: https://github.com/laravel/laravel/compare/v12.6.0...v12.7.0

## [v12.6.0](https://github.com/laravel/laravel/compare/v12.5.0...v12.6.0) - 2025-10-02

* Fix setup script by [@goldmont](https://github.com/goldmont) in https://github.com/laravel/laravel/pull/6682

## [v12.5.0](https://github.com/laravel/laravel/compare/v12.4.0...v12.5.0) - 2025-09-30

* [12.x] Fix type casting for environment variables in config files by [@AhmedAlaa4611](https://github.com/AhmedAlaa4611) in https://github.com/laravel/laravel/pull/6670
* Fix CVEs affecting vite by [@faissaloux](https://github.com/faissaloux) in https://github.com/laravel/laravel/pull/6672
* Update .editorconfig to target compose.yaml by [@fredikaputra](https://github.com/fredikaputra) in https://github.com/laravel/laravel/pull/6679
* Add pre-package-uninstall script to composer.json by [@cosmastech](https://github.com/cosmastech) in https://github.com/laravel/laravel/pull/6681

## [v12.4.0](https://github.com/laravel/laravel/compare/v12.3.1...v12.4.0) - 2025-08-29

* [12.x] Add default Redis retry configuration by [@mateusjatenee](https://github.com/mateusjatenee) in https://github.com/laravel/laravel/pull/6666

## [v12.3.1](https://github.com/laravel/laravel/compare/v12.3.0...v12.3.1) - 2025-08-21

* [12.x] Bump Pint version by [@AhmedAlaa4611](https://github.com/AhmedAlaa4611) in https://github.com/laravel/laravel/pull/6653
* [12.x] Making sure all related processed are closed when terminating the currently command by [@AhmedAlaa4611](https://github.com/AhmedAlaa4611) in https://github.com/larave
* [12.x] Use application name from configuration by [@AhmedAlaa4611](https://github.com/AhmedAlaa4611) in https://github.com/laravel/laravel/pull/6655
* Bring back postAutoloadDump script by [@jasonvarga](https://github.com/jasonvarga) in https://github.com/laravel/laravel/pull/6662

## [v12.3.0](https://github.com/laravel/laravel/compare/v12.2.0...v12.3.0) - 2025-08-03

* Fix Critical Security Vulnerability in form-data Dependency by [@izzygld](https://github.com/izzygld) in https://github.com/laravel/laravel/pull/6645
* Revert "fix" by [@RobertBoes](https://github.com/RobertBoes) in https://github.com/laravel/laravel/pull/6646
* Change composer post-autoload-dump script to Artisan command by [@lmjhs](https://github.com/lmjhs) in https://github.com/laravel/laravel/pull/6647

## [v12.2.0](https://github.com/laravel/laravel/compare/v12.1.0...v12.2.0) - 2025-07-11

* Add Vite 7 support by [@timacdonald](https://github.com/timacdonald) in https://github.com/laravel/laravel/pull/6639

## [v12.1.0](https://github.com/laravel/laravel/compare/v12.0.11...v12.1.0) - 2025-07-03

* [12.x] Disable nightwatch in testing by [@laserhybiz](https://github.com/laserhybiz) in https://github.com/laravel/laravel/pull/6632
* [12.x] Reorder environment variables in phpunit.xml for logical grouping by [@AhmedAlaa4611](https://github.com/AhmedAlaa4611) in https://github.com/laravel/laravel/pull/663
* Change to hyphenate prefixes and cookie names by [@u01jmg3](https://github.com/u01jmg3) in https://github.com/laravel/laravel/pull/6636
* [12.x] Fix type casting for environment variables in config files by [@AhmedAlaa4611](https://github.com/AhmedAlaa4611) in https://github.com/laravel/laravel/pull/6637

## [v12.0.11](https://github.com/laravel/laravel/compare/v12.0.10...v12.0.11) - 2025-06-10

**Full Changelog**: https://github.com/laravel/laravel/compare/v12.0.10...v12.0.11

## [v12.0.10](https://github.com/laravel/laravel/compare/v12.0.9...v12.0.10) - 2025-06-09

* fix alphabetical order by [@Khuthaily](https://github.com/Khuthaily) in https://github.com/laravel/laravel/pull/6627
* [12.x] Reduce redundancy and keeps the .gitignore file cleaner by [@AhmedAlaa4611](https://github.com/AhmedAlaa4611) in https://github.com/laravel/laravel/pull/6629
* [12.x] Fix: Add void return type to satisfy Rector analysis by [@Aluisio-Pires](https://github.com/Aluisio-Pires) in https://github.com/laravel/laravel/pull/6628

## [v12.0.9](https://github.com/laravel/laravel/compare/v12.0.8...v12.0.9) - 2025-05-26

* [12.x] Remove apc by [@AhmedAlaa4611](https://github.com/AhmedAlaa4611) in https://github.com/laravel/laravel/pull/6611
* [12.x] Add JSON Schema to package.json by [@martinbean](https://github.com/martinbean) in https://github.com/laravel/laravel/pull/6613
* Minor language update by [@woganmay](https://github.com/woganmay) in https://github.com/laravel/laravel/pull/6615
* Enhance .gitignore to exclude common OS and log files by [@mohammadRezaei1380](https://github.com/mohammadRezaei1380) in https://github.com/laravel/laravel/pull/6619

## [v12.0.8](https://github.com/laravel/laravel/compare/v12.0.7...v12.0.8) - 2025-05-12

* [12.x] Clean up URL formatting in README by [@AhmedAlaa4611](https://github.com/AhmedAlaa4611) in https://github.com/laravel/laravel/pull/6601

## [v12.0.7](https://github.com/laravel/laravel/compare/v12.0.6...v12.0.7) - 2025-04-15

* Add `composer run test` command by [@crynobone](https://github.com/crynobone) in https://github.com/laravel/laravel/pull/6598
* Partner Directory Changes in ReadME by [@joshcirre](https://github.com/joshcirre) in https://github.com/laravel/laravel/pull/6599

## [v12.0.6](https://github.com/laravel/laravel/compare/v12.0.5...v12.0.6) - 2025-04-08

**Full Changelog**: https://github.com/laravel/laravel/compare/v12.0.5...v12.0.6

## [v12.0.5](https://github.com/laravel/laravel/compare/v12.0.4...v12.0.5) - 2025-04-02

* [12.x] Update `config/mail.php` to match the latest core configuration by [@AhmedAlaa4611](https://github.com/AhmedAlaa4611) in https://github.com/laravel/laravel/pull/6594

## [v12.0.4](https://github.com/laravel/laravel/compare/v12.0.3...v12.0.4) - 2025-03-31

* Bump vite from 6.0.11 to 6.2.3 - Vulnerability patch by [@abdel-aouby](https://github.com/abdel-aouby) in https://github.com/laravel/laravel/pull/6586
* Bump vite from 6.2.3 to 6.2.4 by [@thinkverse](https://github.com/thinkverse) in https://github.com/laravel/laravel/pull/6590

## [v12.0.3](https://github.com/laravel/laravel/compare/v12.0.2...v12.0.3) - 2025-03-17

* Remove reverted change from CHANGELOG.md by [@AJenbo](https://github.com/AJenbo) in https://github.com/laravel/laravel/pull/6565
* Improves clarity in app.css file by [@AhmedAlaa4611](https://github.com/AhmedAlaa4611) in https://github.com/laravel/laravel/pull/6569
* [12.x] Refactor: Structural improvement for clarity by [@AhmedAlaa4611](https://github.com/AhmedAlaa4611) in https://github.com/laravel/laravel/pull/6574
* Bump axios from 1.7.9 to 1.8.2 - Vulnerability patch by [@abdel-aouby](https://github.com/abdel-aouby) in https://github.com/laravel/laravel/pull/6572
* [12.x] Remove Unnecessarily [@source](https://github.com/source) by [@AhmedAlaa4611](https://github.com/AhmedAlaa4611) in https://github.com/laravel/laravel/pull/6584

## [v12.0.2](https://github.com/laravel/laravel/compare/v12.0.1...v12.0.2) - 2025-03-04

* Make the github test action run out of the box independent of the choice of testing framework by [@ndeblauw](https://github.com/ndeblauw) in https://github.com/laravel/larav

## [v12.0.1](https://github.com/laravel/laravel/compare/v12.0.0...v12.0.1) - 2025-02-24

* [12.x] prefer stable stability by [@pataar](https://github.com/pataar) in https://github.com/laravel/laravel/pull/6548

## [v12.0.0 (2025-??-??)](https://github.com/laravel/laravel/compare/v11.0.2...v12.0.0)

Laravel 12 includes a variety of changes to the application skeleton. Please consult the diff to see what's new.
```

### File: composer.json

```
{
    "$schema": "https://getcomposer.org/schema.json",
    "name": "laravel/laravel",
    "type": "project",
    "description": "The skeleton application for the Laravel framework.",
    "keywords": ["laravel", "framework"],
    "license": "MIT",
    "require": {
        "php": "^8.2",
        "inertiajs/inertia-laravel": "^2.0",
        "laravel/framework": "^12.0",
        "laravel/sanctum": "^4.0",
        "laravel/tinker": "^2.10.1",
        "tightenco/ziggy": "^2.0"
    },
    "require-dev": {
        "fakerphp/faker": "^1.23",
        "laravel/breeze": "*",
        "laravel/pail": "^1.2.2",
        "laravel/pint": "^1.24",
        "laravel/sail": "^1.41",
        "mockery/mockery": "^1.6",
        "nunomaduro/collision": "^8.6",
```

```
        "phpunit/phpunit": "^11.5.3"
    },
    "autoload": {
        "psr-4": {
            "App\\": "app/",
            "Database\\Factories\\": "database/factories/",
            "Database\\Seeders\\": "database/seeders/"
        }
    },
    "autoload-dev": {
        "psr-4": {
            "Tests\\": "tests/"
        }
    },
    "scripts": {
        "setup": [
            "composer install",
            "@php -r \"file_exists('.env') || copy('.env.example', '.env');\"",
            "@php artisan key:generate",
            "@php artisan migrate --force",
            "npm install",
            "npm run build"
        ],
        "dev": [
            "Composer\\Config::disableProcessTimeout",
            "npx concurrently -c \"#93c5fd,#c4b5fd,#fb7185,#fdba74\" \"php artisan serve\" \"php artisan queue:listen --tries=1 --timeout=0\" \"php artisan pail --timeout=0\"
        ],
        "test": [
            "@php artisan config:clear --ansi",
            "@php artisan test"
        ],
        "post-autoload-dump": [
            "Illuminate\\Foundation\\ComposerScripts::postAutoloadDump",
            "@php artisan package:discover --ansi"
        ],
        "post-update-cmd": [
            "@php artisan vendor:publish --tag=laravel-assets --ansi --force"
        ],
        "post-root-package-install": [
            "@php -r \"file_exists('.env') || copy('.env.example', '.env');\""
        ],
        "post-create-project-cmd": [
            "@php artisan key:generate --ansi",
            "@php -r \"file_exists('database/database.sqlite') || touch('database/database.sqlite');\"",
            "@php artisan migrate --graceful --ansi"
        ],
        "pre-package-uninstall": [
            "Illuminate\\Foundation\\ComposerScripts::prePackageUninstall"
        ]
    },
    "extra": {
        "laravel": {
            "dont-discover": []
        }
    },
    "config": {
        "optimize-autoloader": true,
        "preferred-install": "dist",
        "sort-packages": true,
        "allow-plugins": {
            "pestphp/pest-plugin": true,
            "php-http/discovery": true
        }
    },
    "minimum-stability": "stable",
    "prefer-stable": true
}
```

***File: generate_compact_pdf.py***

```
from reportlab.lib.pagesizes import A4
from reportlab.platypus import SimpleDocTemplate, Paragraph, Spacer, Preformatted, PageBreak
from reportlab.lib.styles import getSampleStyleSheet, ParagraphStyle
from reportlab.lib.enums import TA_LEFT, TA_CENTER
from reportlab.lib import colors
import os
from datetime import datetime

def generate_compact_project_pdf():
    """
    Generates a compact PDF containing the project code and directory structure,
    keeping the file size under 10MB as per project specifications.
    """
    # Output PDF file
    output_path = "bestbuy_books_project_documentation.pdf"
    doc = SimpleDocTemplate(
        output_path,
        pagesize=A4,
        rightMargin=30,
        leftMargin=30,
        topMargin=30,
        bottomMargin=30
    )

    # Get styles
    styles = getSampleStyleSheet()

    # Compact styles
    title_style = ParagraphStyle(
        'CompactTitle',
        parent=styles['Heading1'],
        fontSize=14,
        spaceAfter=8,
        alignment=TA_CENTER,
        textColor=(0.2, 0.2, 0.6)
    )

    subtitle_style = ParagraphStyle(
        'CompactSubtitle',
        parent=styles['Normal'],
        fontSize=8,
        spaceAfter=8,
        alignment=TA_CENTER,
        textColor=(0.3, 0.3, 0.3)
    )

    header_style = ParagraphStyle(
        'CompactHeader',
        parent=styles['Heading2'],
        fontSize=10,
        spaceAfter=6
    )

    file_header_style = ParagraphStyle(
        'CompactFileHeader',
```

```
    parent=styles['Heading3'],
    fontSize=7,
    spaceAfter=2,
    borderWidth=0.5,
    borderColor='gray',
    borderPadding=1,
    backColor=colors.lightgrey
)

code_style = ParagraphStyle(
    'CompactCode',
    parent=styles['Code'],
    fontSize=5,
    leading=6  # Very tight spacing for code
)

truncate_style = ParagraphStyle(
    'CompactTruncateNote',
    parent=styles['Normal'],
    fontSize=5,
    textColor=colors.red
)

# Create story
story = []

# Title
story.append(Paragraph('BestBuy Books Project Documentation', title_style))
story.append(Paragraph(f'Generated on: {datetime.now().strftime("%Y-%m-%d %H:%M:%S")}', subtitle_style))
story.append(Spacer(1, 10))

# Project overview
story.append(Paragraph('Project Overview', header_style))
story.append(Paragraph(
    'BestBuy_Books is an e-commerce platform built with Laravel framework supporting multi-role users '
    '(Administrators, Merchants, Customers) for managing books, orders, chats, and issue reports. '
    'The project implements real-time communication between users and administrators, merchant '
    'registration approval process, and role-based access control.',
    ParagraphStyle(
        'CompactNormal',
        parent=styles['Normal'],
        fontSize=6,
        leading=7
    )
))
story.append(Spacer(1, 10))

# Directory structure
story.append(Paragraph('Directory Structure', header_style))
story.append(Spacer(1, 6))

# Generate directory tree
dir_tree = generate_directory_tree(r"c:\xampp\htdocs\BestBuy_Books")
story.append(Preformatted(dir_tree, code_style))
story.append(PageBreak())

# Process files with strict size limits as per project specifications
dirs_to_exclude = [
    'vendor', 'node_modules', '.git', 'storage', 'tests',
    'bootstrap/cache', 'storage/framework', 'public/build',
    'resources/js', 'resources/css', 'database/factories',
    'database/seeders', '__pycache__', '.vscode', '.idea',
    '.venv', 'env'
]

extensions_to_include = [
    '.php', '.blade.php', '.py', '.txt', '.env', '.sql',
    '.xml', '.yml', '.yaml', '.md', '.json', '.js', '.jsx'
]

# Process core application files with size limits per specification
root_path = r"c:\xampp\htdocs\BestBuy_Books"
total_chars_added = 0
files_processed = 0
skipped_files = 0

for root, dirs, files in os.walk(root_path):
    # Remove excluded directories
    dirs[:] = [d for d in dirs if d not in dirs_to_exclude]

    for file in files:
        if any(file.lower().endswith(ext) for ext in extensions_to_include):
            file_path = os.path.join(root, file)

            # Calculate relative path
            rel_path = os.path.relpath(file_path, root_path)

            # Skip very large files per specification (>50KB)
            try:
                file_size = os.path.getsize(file_path)
                if file_size > 50000:  # Skip files larger than 50KB
                    skipped_files += 1
                    continue
            except OSError:
                continue

            # Check if we're approaching size limit to stay under 10MB
            if total_chars_added > 850000:  # Stop before reaching 10MB
                story.append(Paragraph(
                    'Document size limit reached. Remaining files not included.',
                    ParagraphStyle('LimitNote', parent=styles['Normal'], fontSize=6, textColor=colors.red)
                ))
                break

            # Add file header
            story.append(Paragraph(f'File: {rel_path}', file_header_style))

            # Read and add file content with limit per specification (max 15KB per file)
            try:
                with open(file_path, 'r', encoding='utf-8', errors='replace') as f:
                    content = f.read(15000)  # Limit to first 15k chars per file per spec

                    # Add content
                    story.append(Preformatted(content, code_style))

                    # Add size warning if needed
                    if len(content) >= 15000:
                        story.append(Paragraph(
                            '(Content truncated due to size - showing first 15KB)',
                            truncate_style
                        ))

                    total_chars_added += len(content)
                    files_processed += 1

            except Exception as e:
                story.append(Paragraph(
                    f'[Could not read file: {str(e)}]',
```

```
                        ParagraphStyle('ErrorNote', parent=styles['Normal'], fontSize=6, textColor=colors.red)
                    ))

                story.append(Spacer(1, 4))  # Compact spacing
                # Add page break every 10 files to prevent extremely long sections
                if files_processed % 10 == 0:
                    story.append(PageBreak())

        if total_chars_added > 850000:  # Stop before reaching 10MB
            break

    # Add summary
    story.append(PageBreak())
    story.append(Paragraph('Summary', header_style))
    story.append(Paragraph(f'Total files processed: {files_processed}',
                           ParagraphStyle('CompactNormal', parent=styles['Normal'], fontSize=8)))
    story.append(Paragraph(f'Skipped large files: {skipped_files}',
                           ParagraphStyle('CompactNormal', parent=styles['Normal'], fontSize=8)))
    story.append(Paragraph(f'Total characters added: {total_chars_added:,}',
                           ParagraphStyle('CompactNormal', parent=styles['Normal'], fontSize=8)))
    story.append(Paragraph(f'Estimated PDF size: {total_chars_added/100000:.2f} MB',
                           ParagraphStyle('CompactNormal', parent=styles['Normal'], fontSize=8)))

    # Build document
    doc.build(story)
    print(f"Compact Project PDF generated successfully at {output_path}")
    actual_size = os.path.getsize(output_path) / (1024*1024)
    print(f"Actual file size: {actual_size:.2f} MB")
    print(f"Files processed: {files_processed}")
    print(f"Large files skipped: {skipped_files}")

    if actual_size < 10.0:
        print("✓ File size is under 10MB as required")
    else:
        print("■ File size exceeded 10MB target")


def generate_directory_tree(startpath):
    """
    Generate a compact tree-like representation of the directory structure
    with depth and file count limits to keep the PDF compact
    """
    output = []
    # Normalize path separators
    startpath = os.path.normpath(startpath)
    for root, dirs, files in os.walk(startpath):
        # Limit depth to prevent extremely deep trees
        depth = root.replace(startpath, '').count(os.sep)
        if depth > 4:  # Limit depth to 4 levels
            continue

        # Get the level by counting path separators
        level = depth
        indent = ' |  ' * level  # Compact indentation

        # Get basename of the folder
        folder_name = os.path.basename(root)
        if folder_name and root != startpath:  # Skip empty names and root
            output.append(f'{indent} |- {folder_name}/')

        subindent = ' |  ' * (level + 1)
        count = 0
        for file in files:
            if count >= 10:  # Limit files listed per directory to keep compact
                output.append(f'{subindent} ... (+{len(files)-count} more files)')
                break
            output.append(f'{subindent} |- {file}')
            count += 1

    return '\n'.join(output[:300])  # Limit to prevent huge outputs


if __name__ == "__main__":
    generate_compact_project_pdf()
```

### *File: generate_pdf.py*

```
from reportlab.lib.pagesizes import letter, A4
from reportlab.platypus import SimpleDocTemplate, Paragraph, Spacer, Preformatted, PageBreak
from reportlab.lib.styles import getSampleStyleSheet, ParagraphStyle
from reportlab.lib.units import inch
from reportlab.platypus.tables import Table
from reportlab.platypus.tableofcontents import TableOfContents
from reportlab.lib.enums import TA_LEFT, TA_CENTER
from reportlab.lib import colors
import os
import time
from datetime import datetime

def generate_project_pdf():
    # Output PDF file
    output_path = "project_documentation.pdf"
    doc = SimpleDocTemplate(
        output_path,
        pagesize=A4,
        rightMargin=72,
        leftMargin=72,
        topMargin=72,
        bottomMargin=72
    )

    # Get styles
    styles = getSampleStyleSheet()
    title_style = ParagraphStyle(
        'CustomTitle',
        parent=styles['Heading1'],
        fontSize=24,
        spaceAfter=30,
        alignment=TA_CENTER,
        textColor=(0.2, 0.2, 0.6)
    )

    subtitle_style = ParagraphStyle(
        'Subtitle',
        parent=styles['Normal'],
        fontSize=14,
        spaceAfter=20,
        alignment=TA_CENTER,
        textColor=(0.3, 0.3, 0.3)
    )

    header_style = ParagraphStyle(
        'Header',
        parent=styles['Heading2'],
        fontSize=16,
```

```
    spaceAfter=12,
    borderWidth=1,
    borderColor='black',
    borderPadding=10
)

file_header_style = ParagraphStyle(
    'FileHeader',
    parent=styles['Heading3'],
    fontSize=12,
    spaceAfter=6,
    borderWidth=1,
    borderColor='gray',
    borderPadding=6,
    backColor=colors.lightgrey
)

# Create story
story = []

# Title
story.append(Paragraph('BestBuy Books Project Documentation', title_style))
story.append(Paragraph(f'Generated on: {datetime.now().strftime("%Y-%m-%d %H:%M:%S")}', subtitle_style))
story.append(Spacer(1, 20))

# Project overview
story.append(Paragraph('Project Overview', header_style))
story.append(Paragraph(
    'BestBuy_Books is an e-commerce platform built with Laravel framework supporting multi-role users '
    '(Administrators, Merchants, Customers) for managing books, orders, chats, and issue reports. '
    'The project implements real-time communication between users and administrators, merchant '
    'registration approval process, and role-based access control.',
    styles['Normal']
))
story.append(Spacer(1, 20))

# Directory structure
story.append(Paragraph('Directory Structure', header_style))
story.append(Spacer(1, 12))

# Generate directory tree
dir_tree = generate_directory_tree(r"c:\xampp\htdocs\BestBuy_Books - Copy")
story.append(Preformatted(dir_tree, styles['Code']))
story.append(PageBreak())

# Add table of contents placeholder
toc = TableOfContents()
toc.levelStyles = [
    ParagraphStyle(
        fontName='Times-Bold',
        fontSize=14,
        name='TOCHeading1',
        leftIndent=20,
        firstLineIndent=-20,
        spaceBefore=10,
        leading=16
    ),
    ParagraphStyle(
        fontName='Times-Roman',
        fontSize=12,
        name='TOCHeading2',
        leftIndent=40,
        firstLineIndent=-20,
        spaceBefore=5,
        leading=12
    )
]
story.append(toc)
story.append(PageBreak())

# Process files with size limits
dirs_to_exclude = [
    'vendor', 'node_modules', '.git', 'storage', 'tests',
    'bootstrap/cache', 'storage/framework', 'public/build',
    'resources/js', 'resources/css', 'database/factories',
    'database/seeders'
]

extensions_to_include = [
    '.php', '.blade.php', '.js', '.jsx', '.json', '.md',
    '.css', '.py', '.txt', '.env', '.sql', '.xml', '.yml',
    '.yaml', '.html', '.twig'
]

# Process core application files
root_path = r"c:\xampp\htdocs\BestBuy_Books - Copy"
for root, dirs, files in os.walk(root_path):
    # Remove excluded directories
    dirs[:] = [d for d in dirs if d not in dirs_to_exclude]

    for file in files:
        if any(file.lower().endswith(ext) for ext in extensions_to_include):
            file_path = os.path.join(root, file)

            # Calculate relative path
            rel_path = os.path.relpath(file_path, root_path)

            # Skip very large files
            try:
                file_size = os.path.getsize(file_path)
                if file_size > 100000:  # Skip files larger than 100KB
                    continue
            except OSError:
                continue

            # Add file header
            story.append(Paragraph(f'File: {rel_path}', file_header_style))

            # Read and add file content with limit
            try:
                with open(file_path, 'r', encoding='utf-8', errors='replace') as f:
                    content = f.read(50000)  # Limit to first 50k chars per file

                    # Add content
                    story.append(Preformatted(content, styles['Code']))

                    # Add size warning if needed
                    if len(content) >= 50000:
                        story.append(Paragraph('(Content truncated due to size)',
                                               ParagraphStyle(
                                                   'TruncateNote',
                                                   parent=styles['Normal'],
                                                   fontSize=8,
                                                   textColor='red'
                                               )))
            except Exception as e:
                story.append(Paragraph(f'[Could not read file: {str(e)}]',
                                       ParagraphStyle(
```

```
                                            'ErrorNote',
                                            parent=styles['Normal'],
                                            textColor='red'
                                        )))

                story.append(Spacer(1, 20))

    # Build document
    doc.multiBuild(story)
    print(f"PDF generated successfully at {output_path}")
    print(f"File size: {os.path.getsize(output_path) / (1024*1024):.2f} MB")


def generate_directory_tree(startpath):
    """Generate a tree-like representation of the directory structure"""
    output = []
    # Normalize path separators
    startpath = os.path.normpath(startpath)
    for root, dirs, files in os.walk(startpath):
        # Get the level by counting path separators
        level = root.replace(startpath, '').count(os.sep)
        indent = ' ■   ' * level

        # Get basename of the folder
        folder_name = os.path.basename(root)
        output.append(f'{indent} ■■ {folder_name}/')

        subindent = ' ■   ' * (level + 1)
        for i, file in enumerate(files):
            if i == len(files) - 1:
                output.append(f'{subindent} ■■ {file}')
            else:
                output.append(f'{subindent} ■■ {file}')

    return '\n'.join(output[:1000])  # Limit to prevent huge outputs


def split_large_content(content, max_chars_per_part=50000):
    """Split large content into smaller parts"""
    parts = []
    for i in range(0, len(content), max_chars_per_part):
        parts.append(content[i:i+max_chars_per_part])
    return parts


if __name__ == "__main__":
    generate_project_pdf()
```

### *File: generate_pdf_optimized.py*

```
from reportlab.lib.pagesizes import A4
from reportlab.platypus import SimpleDocTemplate, Paragraph, Spacer, Preformatted, PageBreak
from reportlab.lib.styles import getSampleStyleSheet, ParagraphStyle
from reportlab.lib.enums import TA_LEFT, TA_CENTER
from reportlab.lib import colors
import os
from datetime import datetime

def generate_project_pdf_optimized():
    # Output PDF file
    output_path = "project_documentation_optimized.pdf"
    doc = SimpleDocTemplate(
        output_path,
        pagesize=A4,
        rightMargin=50,
        leftMargin=50,
        topMargin=50,
        bottomMargin=50
    )

    # Get styles
    styles = getSampleStyleSheet()
    title_style = ParagraphStyle(
        'CustomTitle',
        parent=styles['Heading1'],
        fontSize=18,
        spaceAfter=20,
        alignment=TA_CENTER,
        textColor=(0.2, 0.2, 0.6)
    )

    subtitle_style = ParagraphStyle(
        'Subtitle',
        parent=styles['Normal'],
        fontSize=12,
        spaceAfter=15,
        alignment=TA_CENTER,
        textColor=(0.3, 0.3, 0.3)
    )

    header_style = ParagraphStyle(
        'Header',
        parent=styles['Heading2'],
        fontSize=14,
        spaceAfter=10
    )

    file_header_style = ParagraphStyle(
        'FileHeader',
        parent=styles['Heading3'],
        fontSize=10,
        spaceAfter=5,
        borderWidth=0.5,
        borderColor='gray',
        borderPadding=3,
        backColor=colors.lightgrey
    )

    code_style = ParagraphStyle(
        'Code',
        parent=styles['Code'],
        fontSize=8,
        leading=10
    )

    # Create story
    story = []

    # Title
    story.append(Paragraph('BestBuy Books Project Documentation', title_style))
    story.append(Paragraph(f'Generated on: {datetime.now().strftime("%Y-%m-%d %H:%M:%S")}', subtitle_style))
    story.append(Spacer(1, 15))

    # Project overview
    story.append(Paragraph('Project Overview', header_style))
```

```
    story.append(Paragraph(
        'BestBuy_Books is an e-commerce platform built with Laravel framework supporting multi-role users '
        '(Administrators, Merchants, Customers) for managing books, orders, chats, and issue reports. '
        'The project implements real-time communication between users and administrators, merchant '
        'registration approval process, and role-based access control.',
        styles['Normal']
    ))
    story.append(Spacer(1, 15))

    # Directory structure
    story.append(Paragraph('Directory Structure', header_style))
    story.append(Spacer(1, 10))

    # Generate directory tree
    dir_tree = generate_directory_tree(r"c:\xampp\htdocs\BestBuy_Books - Copy")
    story.append(Preformatted(dir_tree, code_style))
    story.append(PageBreak())

    # Process files with stricter size limits
    dirs_to_exclude = [
        'vendor', 'node_modules', '.git', 'storage', 'tests',
        'bootstrap/cache', 'storage/framework', 'public/build',
        'resources/js', 'resources/css', 'database/factories',
        'database/seeders', '__pycache__', '.vscode', '.idea'
    ]

    extensions_to_include = [
        '.php', '.blade.php', '.py', '.txt', '.env', '.sql',
        '.xml', '.yml', '.yaml', '.md', '.json'
    ]

    # Process core application files with stricter limits
    root_path = r"c:\xampp\htdocs\BestBuy_Books - Copy"
    total_chars_added = 0

    for root, dirs, files in os.walk(root_path):
        # Remove excluded directories
        dirs[:] = [d for d in dirs if d not in dirs_to_exclude]

        for file in files:
            if any(file.lower().endswith(ext) for ext in extensions_to_include):
                file_path = os.path.join(root, file)

                # Calculate relative path
                rel_path = os.path.relpath(file_path, root_path)

                # Skip very large files
                try:
                    file_size = os.path.getsize(file_path)
                    if file_size > 50000:  # Skip files larger than 50KB
                        continue
                except OSError:
                    continue

                # Check if we're approaching size limit
                if total_chars_added > 800000:  # Stop before reaching 10MB
                    story.append(Paragraph('Document size limit reached. Remaining files not included.',
                                           ParagraphStyle('LimitNote', parent=styles['Normal'], textColor='red')))
                    break

                # Add file header
                story.append(Paragraph(f'File: {rel_path}', file_header_style))

                # Read and add file content with stricter limit
                try:
                    with open(file_path, 'r', encoding='utf-8', errors='replace') as f:
                        content = f.read(20000)  # Limit to first 20k chars per file

                        # Add content
                        story.append(Preformatted(content, code_style))

                        # Add size warning if needed
                        if len(content) >= 20000:
                            story.append(Paragraph('(Content truncated due to size)',
                                                   ParagraphStyle(
                                                       'TruncateNote',
                                                       parent=styles['Normal'],
                                                       fontSize=6,
                                                       textColor='red'
                                                   )))

                        total_chars_added += len(content)

                except Exception as e:
                    story.append(Paragraph(f'[Could not read file: {str(e)}]',
                                           ParagraphStyle(
                                               'ErrorNote',
                                               parent=styles['Normal'],
                                               textColor='red'
                                           )))

                story.append(Spacer(1, 10))

        if total_chars_added > 800000:  # Stop before reaching 10MB
            break

    # Build document
    doc.build(story)
    print(f"Optimized PDF generated successfully at {output_path}")
    print(f"File size: {os.path.getsize(output_path) / (1024*1024):.2f} MB")


def generate_directory_tree(startpath):
    """Generate a tree-like representation of the directory structure"""
    output = []
    for root, dirs, files in os.walk(startpath):
        # Limit depth to prevent extremely deep trees
        depth = root.replace(startpath, '').count(os.sep)
        if depth > 5:  # Limit depth to 5 levels
            continue

        # Get the level by counting path separators
        level = depth
        indent = ' ■   ' * level

        # Get basename of the folder
        folder_name = os.path.basename(root)
        if folder_name:  # Skip empty names
            output.append(f'{indent} ■■ {folder_name}/')

        subindent = ' ■   ' * (level + 1)
        count = 0
        for file in files:
            if count >= 20:  # Limit files listed per directory
                output.append(f'{subindent} ... and more files')
                break
            output.append(f'{subindent} ■■ {file}')
            count += 1
```

```
    return '\n'.join(output[:500])  # Limit to prevent huge outputs


if __name__ == "__main__":
    generate_project_pdf_optimized()
```

### File: generate_project_pdf.py

```
from reportlab.lib.pagesizes import A4
from reportlab.platypus import SimpleDocTemplate, Paragraph, Spacer, Preformatted, PageBreak
from reportlab.lib.styles import getSampleStyleSheet, ParagraphStyle
from reportlab.lib.enums import TA_LEFT, TA_CENTER
from reportlab.lib import colors
import os
from datetime import datetime

def generate_project_pdf():
    """
    Generates a PDF containing the project code and directory structure,
    keeping the file size under 10MB as per project specifications.
    """
    # Output PDF file
    output_path = "project_documentation.pdf"
    doc = SimpleDocTemplate(
        output_path,
        pagesize=A4,
        rightMargin=50,
        leftMargin=50,
        topMargin=50,
        bottomMargin=50
    )

    # Get styles
    styles = getSampleStyleSheet()

    # Custom styles for better compactness
    title_style = ParagraphStyle(
        'CustomTitle',
        parent=styles['Heading1'],
        fontSize=16,
        spaceAfter=15,
        alignment=TA_CENTER,
        textColor=(0.2, 0.2, 0.6)
    )

    subtitle_style = ParagraphStyle(
        'Subtitle',
        parent=styles['Normal'],
        fontSize=10,
        spaceAfter=12,
        alignment=TA_CENTER,
        textColor=(0.3, 0.3, 0.3)
    )

    header_style = ParagraphStyle(
        'Header',
        parent=styles['Heading2'],
        fontSize=12,
        spaceAfter=8
    )

    file_header_style = ParagraphStyle(
        'FileHeader',
        parent=styles['Heading3'],
        fontSize=9,
        spaceAfter=4,
        borderWidth=0.5,
        borderColor='gray',
        borderPadding=2,
        backColor=colors.lightgrey
    )

    code_style = ParagraphStyle(
        'Code',
        parent=styles['Code'],
        fontSize=7,
        leading=9
    )

    truncate_style = ParagraphStyle(
        'TruncateNote',
        parent=styles['Normal'],
        fontSize=6,
        textColor=colors.red
    )

    # Create story
    story = []

    # Title
    story.append(Paragraph('BestBuy Books Project Documentation', title_style))
    story.append(Paragraph(f'Generated on: {datetime.now().strftime("%Y-%m-%d %H:%M:%S")}', subtitle_style))
    story.append(Spacer(1, 15))

    # Project overview
    story.append(Paragraph('Project Overview', header_style))
    story.append(Paragraph(
        'BestBuy_Books is an e-commerce platform built with Laravel framework supporting multi-role users '
        '(Administrators, Merchants, Customers) for managing books, orders, chats, and issue reports. '
        'The project implements real-time communication between users and administrators, merchant '
        'registration approval process, and role-based access control.',
        styles['Normal']
    ))
    story.append(Spacer(1, 15))

    # Directory structure
    story.append(Paragraph('Directory Structure', header_style))
    story.append(Spacer(1, 10))

    # Generate directory tree
    dir_tree = generate_directory_tree(r"c:\xampp\htdocs\BestBuy_Books - Copy")
    story.append(Preformatted(dir_tree, code_style))
    story.append(PageBreak())

    # Process files with strict size limits as per project specifications
    dirs_to_exclude = [
        'vendor', 'node_modules', '.git', 'storage', 'tests',
        'bootstrap/cache', 'storage/framework', 'public/build',
        'resources/js', 'resources/css', 'database/factories',
        'database/seeders', '__pycache__', '.vscode', '.idea'
    ]

    extensions_to_include = [
        '.php', '.blade.php', '.py', '.txt', '.env', '.sql',
        '.xml', '.yml', '.yaml', '.md', '.json'
```

```
    ]

    # Process core application files with size limits per specification
    root_path = r"c:\xampp\htdocs\BestBuy_Books - Copy"
    total_chars_added = 0
    files_processed = 0

    for root, dirs, files in os.walk(root_path):
        # Remove excluded directories
        dirs[:] = [d for d in dirs if d not in dirs_to_exclude]

        for file in files:
            if any(file.lower().endswith(ext) for ext in extensions_to_include):
                file_path = os.path.join(root, file)

                # Calculate relative path
                rel_path = os.path.relpath(file_path, root_path)

                # Skip very large files per specification (>50KB)
                try:
                    file_size = os.path.getsize(file_path)
                    if file_size > 50000:  # Skip files larger than 50KB
                        continue
                except OSError:
                    continue

                # Check if we're approaching size limit to stay under 10MB
                if total_chars_added > 800000:  # Stop before reaching 10MB
                    story.append(Paragraph(
                        'Document size limit reached. Remaining files not included.',
                        ParagraphStyle('LimitNote', parent=styles['Normal'], textColor=colors.red)
                    ))
                    break

                # Add file header
                story.append(Paragraph(f'File: {rel_path}', file_header_style))

                # Read and add file content with limit per specification (max 20KB)
                try:
                    with open(file_path, 'r', encoding='utf-8', errors='replace') as f:
                        content = f.read(20000)  # Limit to first 20k chars per file per spec

                        # Add content
                        story.append(Preformatted(content, code_style))

                        # Add size warning if needed
                        if len(content) >= 20000:
                            story.append(Paragraph(
                                '(Content truncated due to size - showing first 20KB)',
                                truncate_style
                            ))

                        total_chars_added += len(content)
                        files_processed += 1

                except Exception as e:
                    story.append(Paragraph(
                        f'[Could not read file: {str(e)}]',
                        ParagraphStyle('ErrorNote', parent=styles['Normal'], textColor=colors.red)
                    ))

                story.append(Spacer(1, 8))

        if total_chars_added > 800000:  # Stop before reaching 10MB
            break

    # Add summary
    story.append(PageBreak())
    story.append(Paragraph('Summary', header_style))
    story.append(Paragraph(f'Total files processed: {files_processed}', styles['Normal']))
    story.append(Paragraph(f'Total characters added: {total_chars_added:,}', styles['Normal']))

    # Build document
    doc.build(story)
    print(f"Project PDF generated successfully at {output_path}")
    print(f"File size: {os.path.getsize(output_path) / (1024*1024):.2f} MB")
    print(f"Files processed: {files_processed}")


def generate_directory_tree(startpath):
    """
    Generate a tree-like representation of the directory structure
    with depth and file count limits to keep the PDF compact
    """
    output = []
    for root, dirs, files in os.walk(startpath):
        # Limit depth to prevent extremely deep trees
        depth = root.replace(startpath, '').count(os.sep)
        if depth > 5:  # Limit depth to 5 levels
            continue

        # Get the level by counting path separators
        level = depth
        indent = ' ■   ' * level

        # Get basename of the folder
        folder_name = os.path.basename(root)
        if folder_name:  # Skip empty names
            output.append(f'{indent} ■■ {folder_name}/')

        subindent = ' ■   ' * (level + 1)
        count = 0
        for file in files:
            if count >= 15:  # Limit files listed per directory to keep compact
                output.append(f'{subindent} ... and more files')
                break
            output.append(f'{subindent} ■■ {file}')
            count += 1

    return '\n'.join(output[:500])  # Limit to prevent huge outputs


if __name__ == "__main__":
    generate_project_pdf()
```

### *File: jsconfig.json*

```
{
    "compilerOptions": {
        "baseUrl": ".",
        "paths": {
            "@/*": ["resources/js/*"],
            "ziggy-js": ["./vendor/tightenco/ziggy"]
        }
    },
```

```
    "exclude": ["node_modules", "public"]
}
```

***File: package.json***

```
{
    "$schema": "https://www.schemastore.org/package.json",
    "private": true,
    "type": "module",
    "scripts": {
        "build": "vite build",
        "dev": "vite"
    },
    "devDependencies": {
        "@headlessui/react": "^2.0.0",
        "@inertiajs/react": "^2.0.0",
        "@tailwindcss/forms": "^0.5.3",
        "@tailwindcss/vite": "^4.0.0",
        "@vitejs/plugin-react": "^4.2.0",
        "autoprefixer": "^10.4.12",
        "axios": "^1.11.0",
        "concurrently": "^9.0.1",
        "laravel-vite-plugin": "^2.0.0",
        "postcss": "^8.4.31",
        "react": "^18.2.0",
        "react-dom": "^18.2.0",
        "tailwindcss": "^3.2.1",
        "vite": "^7.0.7"
    }
}
```

### File: phpunit.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<phpunit xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
         xsi:noNamespaceSchemaLocation="vendor/phpunit/phpunit/phpunit.xsd"
         bootstrap="vendor/autoload.php"
         colors="true"
>
    <testsuites>
        <testsuite name="Unit">
            <directory>tests/Unit</directory>
        </testsuite>
        <testsuite name="Feature">
            <directory>tests/Feature</directory>
        </testsuite>
    </testsuites>
    <source>
        <include>
            <directory>app</directory>
        </include>
    </source>
    <php>
        <env name="APP_ENV" value="testing"/>
        <env name="APP_MAINTENANCE_DRIVER" value="file"/>
        <env name="BCRYPT_ROUNDS" value="4"/>
        <env name="BROADCAST_CONNECTION" value="null"/>
        <env name="CACHE_STORE" value="array"/>
        <env name="DB_CONNECTION" value="sqlite"/>
        <env name="DB_DATABASE" value=":memory:"/>
        <env name="MAIL_MAILER" value="array"/>
        <env name="QUEUE_CONNECTION" value="sync"/>
        <env name="SESSION_DRIVER" value="array"/>
        <env name="PULSE_ENABLED" value="false"/>
        <env name="TELESCOPE_ENABLED" value="false"/>
        <env name="NIGHTWATCH_ENABLED" value="false"/>
    </php>
</phpunit>
```

### File: postcss.config.js

```
export default {
    plugins: {
        tailwindcss: {},
        autoprefixer: {},
    },
};
```

### File: README.md

```
<p align="center"><a href="https://laravel.com" target="_blank"><img src="https://raw.githubusercontent.com/laravel/art/master/logo-lockup/5%20SVG/2%20CMYK/1%20Full%20Color/la

<p align="center">
<a href="https://github.com/laravel/framework/actions"><img src="https://github.com/laravel/framework/workflows/tests/badge.svg" alt="Build Status"></a>
<a href="https://packagist.org/packages/laravel/framework"><img src="https://img.shields.io/packagist/dt/laravel/framework" alt="Total Downloads"></a>
<a href="https://packagist.org/packages/laravel/framework"><img src="https://img.shields.io/packagist/v/laravel/framework" alt="Latest Stable Version"></a>
<a href="https://packagist.org/packages/laravel/framework"><img src="https://img.shields.io/packagist/l/laravel/framework" alt="License"></a>
</p>

## About Laravel

Laravel is a web application framework with expressive, elegant syntax. We believe development must be an enjoyable and creative experience to be truly fulfilling. Laravel tak

- [Simple, fast routing engine](https://laravel.com/docs/routing).
- [Powerful dependency injection container](https://laravel.com/docs/container).
- Multiple back-ends for [session](https://laravel.com/docs/session) and [cache](https://laravel.com/docs/cache) storage.
- Expressive, intuitive [database ORM](https://laravel.com/docs/eloquent).
- Database agnostic [schema migrations](https://laravel.com/docs/migrations).
- [Robust background job processing](https://laravel.com/docs/queues).
- [Real-time event broadcasting](https://laravel.com/docs/broadcasting).

Laravel is accessible, powerful, and provides tools required for large, robust applications.

## Learning Laravel

Laravel has the most extensive and thorough [documentation](https://laravel.com/docs) and video tutorial library of all modern web application frameworks, making it a breeze t

If you don't feel like reading, [Laracasts](https://laracasts.com) can help. Laracasts contains thousands of video tutorials on a range of topics including Laravel, modern PHP

## Laravel Sponsors

We would like to extend our thanks to the following sponsors for funding Laravel development. If you are interested in becoming a sponsor, please visit the [Laravel Partners p

### Premium Partners

- **[Vehikl](https://vehikl.com)**
- **[Tighten Co.](https://tighten.co)**
- **[Kirschbaum Development Group](https://kirschbaumdevelopment.com)**
- **[64 Robots](https://64robots.com)**
- **[Curotec](https://www.curotec.com/services/technologies/laravel)**
- **[DevSquad](https://devsquad.com/hire-laravel-developers)**
- **[Redberry](https://redberry.international/laravel-development)**
- **[Active Logic](https://activelogic.com)**

## Contributing

Thank you for considering contributing to the Laravel framework! The contribution guide can be found in the [Laravel documentation](https://laravel.com/docs/contributions).

## Code of Conduct

In order to ensure that the Laravel community is welcoming to all, please review and abide by the [Code of Conduct](https://laravel.com/docs/contributions#code-of-conduct).

## Security Vulnerabilities

If you discover a security vulnerability within Laravel, please send an e-mail to Taylor Otwell via [taylor@laravel.com](mailto:taylor@laravel.com). All security vulnerabilit

## License

The Laravel framework is open-sourced software licensed under the [MIT license](https://opensource.org/licenses/MIT).
"# BestBuy_Books"
"# BestBuy_Books"
```

### File: reset_superadmin_password.php

```
<?php

require __DIR__ . '/vendor/autoload.php';

$app = require __DIR__ . '/bootstrap/app.php';
$app->make(Illuminate\Contracts\Console\Kernel::class)->bootstrap();
$user = App\Models\User::where('email', 'superadmin@bookhub.com')->first();
```

```
if (! $user) {
    echo "Superadmin not found\n";
    exit(1);
}

$user->password = Illuminate\Support\Facades\Hash::make('Admin@123');
$user->save();

echo "Superadmin password reset to Admin@123\n";
```

### File: tailwind.config.js

```
import defaultTheme from 'tailwindcss/defaultTheme';
import forms from '@tailwindcss/forms';

/** @type {import('tailwindcss').Config} */
export default {
    content: [
        './vendor/laravel/framework/src/Illuminate/Pagination/resources/views/*.blade.php',
        './storage/framework/views/*.php',
        './resources/views/**/*.blade.php',
        './resources/js/**/*.jsx',
    ],

    theme: {
        extend: {
            fontFamily: {
                sans: ['Figtree', ...defaultTheme.fontFamily.sans],
            },
        },
    },

    plugins: [forms],
};
```

### File: vite.config.js

```
import { defineConfig } from 'vite';
import laravel from 'laravel-vite-plugin';
import react from '@vitejs/plugin-react';

export default defineConfig({
    plugins: [
        laravel({
            input: 'resources/js/app.jsx',
            refresh: true,
        }),
        react(),
    ],
});
```

### File: .github\workflows\issues.yml

```
name: Issues

on:
  issues:
    types: [labeled]

permissions:
  issues: write

jobs:
  help-wanted:
    uses: laravel/.github/.github/workflows/issues.yml@main
```

### File: .github\workflows\pull-requests.yml

```
name: Pull Requests

on:
  pull_request_target:
    types: [opened]

permissions:
  pull-requests: write

jobs:
  uneditable:
    uses: laravel/.github/.github/workflows/pull-requests.yml@main
```

### File: .github\workflows\tests.yml

```
name: Tests

on:
  push:
    branches:
      - master
      - '*.x'
  pull_request:
  schedule:
    - cron: '0 0 * * *'

permissions:
  contents: read

jobs:
  tests:
    runs-on: ubuntu-latest

    strategy:
      fail-fast: true
      matrix:
        php: [8.2, 8.3, 8.4]

    name: PHP ${{ matrix.php }}

    steps:
      - name: Checkout code
        uses: actions/checkout@v6

      - name: Setup PHP
        uses: shivammathur/setup-php@v2
        with:
          php-version: ${{ matrix.php }}
```

```
          extensions: dom, curl, libxml, mbstring, zip, pcntl, pdo, sqlite, pdo_sqlite
          coverage: none

      - name: Install Composer dependencies
        run: composer install --prefer-dist --no-interaction --no-progress

      - name: Copy environment file
        run: cp .env.example .env

      - name: Generate app key
        run: php artisan key:generate

      - name: Execute tests
        run: php artisan test
```

### *File: .github\workflows\update-changelog.yml*

```
name: Update Changelog

on:
  release:
    types: [released]

permissions: {}

jobs:
  update:
    permissions:
      contents: write
    uses: laravel/.github/.github/workflows/update-changelog.yml@main
```

### File: app\Http\Controllers\AdminChatController.php

```php
<?php

namespace App\Http\Controllers;

use App\Models\ChatConversation;
use App\Models\ChatMessage;
use Illuminate\Http\Request;

class AdminChatController extends Controller
{
    public function index(Request $request)
    {
        $user = $request->user();
        $conversations = ChatConversation::query()
            ->with(['customer', 'latestMessage', 'assignedAdmin'])
            ->withCount([
                'messages as unread_count' => function ($query) use ($user) {
                    $query->whereNull('read_at')
                        ->where('sender_id', '!=', $user->id);
                },
            ])
            ->latest('updated_at')
            ->get();

        return view('admin.chats.index', ['conversations' => $conversations]);
    }

    public function show(Request $request, ChatConversation $conversation)
    {
        $user = $request->user();

        $conversation->messages()
            ->whereNull('read_at')
            ->where('sender_id', '!=', $user->id)
            ->update(['read_at' => now()]);

        $conversation->load(['customer', 'messages.sender', 'assignedAdmin']);

        return view('admin.chats.show', [
            'conversation' => $conversation,
            'messages' => $conversation->messages,
        ]);
    }

    public function sendMessage(Request $request, ChatConversation $conversation)
    {
        $user = $request->user();
        $data = $request->validate([
            'message' => 'required|string|max:2000',
        ]);

        ChatMessage::create([
            'conversation_id' => $conversation->id,
            'sender_id' => $user->id,
            'sender_role' => $user->account_type,
            'message' => $data['message'],
        ]);

        $conversation->update([
            'last_message_at' => now(),
            'assigned_admin_id' => $conversation->assigned_admin_id ?? $user->id,
        ]);

        return redirect()
            ->route('admin.chats.show', $conversation)
            ->with('status', 'Reply sent.');
    }

    public function unreadCount(Request $request)
    {
        $user = $request->user();
        $count = ChatMessage::query()
            ->whereNull('read_at')
            ->where('sender_id', '!=', $user->id)
            ->count();

        return response()->json(['count' => $count]);
    }
}
```

### File: app\Http\Controllers\AdminDashboardController.php

```php
<?php

namespace App\Http\Controllers;

use App\Models\ChatConversation;
use App\Models\IssueReport;
use App\Models\User;
use Illuminate\Http\Request;

class AdminDashboardController extends Controller
{
    public function index(Request $request)
    {
        $openReports = IssueReport::query()
            ->where('status', 'open')
            ->count();

        $openChats = ChatConversation::query()
            ->where('status', 'open')
            ->count();

        $adminCount = User::query()
            ->whereIn('account_type', ['sub_admin', 'super_admin'])
            ->count();

        // Return Blade view, not Inertia
        return view('admin.dashboard', [
            'openReports' => $openReports,
            'openChats' => $openChats,
            'adminCount' => $adminCount,
            'user' => $request->user(),
        ]);
    }
}
```

### File: app\Http\Controllers\AdminIssueReportController.php

```php
<?php
```

```php
namespace App\Http\Controllers;

use App\Models\IssueReport;
use App\Models\User;
use Illuminate\Http\Request;

class AdminIssueReportController extends Controller
{
    public function index(Request $request)
    {
        $query = IssueReport::with(['user', 'reportedUser', 'assignedAdmin']);

        if ($request->filled('status')) {
            $query->where('status', $request->status);
        }

        if ($request->filled('priority')) {
            $query->where('priority', $request->priority);
        }

        $reports = $query->latest()->get();

        return view('admin.issue_reports.index', compact('reports'));
    }

    public function show(IssueReport $issueReport)
    {
        $issueReport->load(['user', 'reportedUser', 'assignedAdmin']);
        $admins = User::whereIn('account_type', ['sub_admin', 'super_admin'])
            ->orderBy('name')
            ->get();

        return view('admin.issue_reports.show', [
            'report' => $issueReport,
            'admins' => $admins,
        ]);
    }

    public function update(Request $request, IssueReport $issueReport)
    {
        $data = $request->validate([
            'status'           => 'required|in:open,in_review,resolved,closed',
            'assigned_admin_id'=> 'nullable|exists:users,id',
            'admin_notes'      => 'nullable|string|max:2000',
        ]);

        $issueReport->update([
            'status'            => $data['status'],
            'assigned_admin_id' => $data['assigned_admin_id'] ?? $issueReport->assigned_admin_id,
            'admin_notes'       => $data['admin_notes'] ?? $issueReport->admin_notes,
        ]);

        return redirect()
            ->route('admin.issue-reports.show', $issueReport)
            ->with('status', 'Issue report updated.');
    }

    /**
     * Ban the reported user from the report page.
     */
    public function banUser(Request $request, IssueReport $issueReport)
    {
        $request->validate(['reason' => 'required|string|max:500']);

        $target = $issueReport->reportedUser ?? $issueReport->user;
        if (!$target) {
            return redirect()->back()->with('error', 'No user found to ban.');
        }

        $target->update([
            'is_banned'  => true,
            'ban_reason' => $request->reason,
            'banned_at'  => now(),
        ]);

        $issueReport->update(['status' => 'resolved', 'admin_notes' => "User banned: {$request->reason}"]);

        return redirect()->route('admin.issue-reports.show', $issueReport)
            ->with('status', "{$target->name} has been banned.");
    }

    /**
     * Warn the reported user.
     */
    public function warnUser(IssueReport $issueReport)
    {
        $target = $issueReport->reportedUser ?? $issueReport->user;
        if (!$target) {
            return redirect()->back()->with('error', 'No user found to warn.');
        }

        $target->increment('warning_count');
        $issueReport->update(['admin_notes' => ($issueReport->admin_notes ?? '') . "\nWarning #{$target->warning_count} issued."]);

        return redirect()->route('admin.issue-reports.show', $issueReport)
            ->with('status', "Warning issued to {$target->name}. Total warnings: {$target->warning_count}.");
    }

    /**
     * Restrict the reported user for N days.
     */
    public function restrictUser(Request $request, IssueReport $issueReport)
    {
        $request->validate(['days' => 'required|integer|min:1|max:365']);

        $target = $issueReport->reportedUser ?? $issueReport->user;
        if (!$target) {
            return redirect()->back()->with('error', 'No user found to restrict.');
        }

        $target->update([
            'is_restricted'    => true,
            'restricted_until' => now()->addDays($request->days),
        ]);

        $issueReport->update(['status' => 'in_review']);

        return redirect()->route('admin.issue-reports.show', $issueReport)
            ->with('status', "{$target->name} has been restricted for {$request->days} day(s).");
    }

    /**
     * Mark issue as resolved/finished.
     */
    public function resolve(IssueReport $issueReport)
    {
        $issueReport->update(['status' => 'resolved']);
        return redirect()->route('admin.issue-reports.show', $issueReport)
```

```
            ->with('status', 'Issue marked as resolved.');
    }
}
```

### File: app\Http\Controllers\AdminUserController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Hash;
use Illuminate\Validation\Rules;

class AdminUserController extends Controller
{
    public function index()
    {
        $admins = User::whereIn('account_type', ['sub_admin', 'super_admin'])
            ->orderBy('account_type')
            ->orderBy('name')
            ->get();

        return view('admin.admins.index', compact('admins'));
    }

    public function create()
    {
        return view('admin.admins.create');
    }

    public function store(Request $request)
    {
        $data = $request->validate([
            'name'         => 'required|string|max:255',
            'email'        => 'required|string|lowercase|email|max:255|unique:' . User::class,
            'password'     => ['required', 'confirmed', Rules\Password::defaults()],
            'account_type' => 'required|in:sub_admin,super_admin',
        ]);

        User::create([
            'name'         => $data['name'],
            'email'        => $data['email'],
            'password'     => Hash::make($data['password']),
            'account_type' => $data['account_type'],
            'is_active'    => true,
        ]);

        return redirect()
            ->route('admin.admins.index')
            ->with('status', 'Admin account created.');
    }

    public function edit(User $admin)
    {
        // Only super_admin can edit admins
        if (auth()->user()->account_type !== 'super_admin') {
            abort(403);
        }

        return view('admin.admins.edit', compact('admin'));
    }

    public function update(Request $request, User $admin)
    {
        if (auth()->user()->account_type !== 'super_admin') {
            abort(403);
        }

        // Prevent demoting self
        if ($admin->id === auth()->id() && $request->account_type !== 'super_admin') {
            return redirect()->back()->with('error', 'You cannot change your own role.');
        }

        $rules = [
            'name'         => 'required|string|max:255',
            'email'        => 'required|email|max:255|unique:users,email,' . $admin->id,
            'account_type' => 'required|in:sub_admin,super_admin',
            'is_active'    => 'boolean',
        ];

        if ($request->filled('password')) {
            $rules['password'] = ['confirmed', Rules\Password::defaults()];
        }

        $data = $request->validate($rules);

        $updateData = [
            'name'         => $data['name'],
            'email'        => $data['email'],
            'account_type' => $data['account_type'],
            'is_active'    => $request->boolean('is_active', true),
        ];

        if ($request->filled('password')) {
            $updateData['password'] = Hash::make($request->password);
        }

        $admin->update($updateData);

        return redirect()
            ->route('admin.admins.index')
            ->with('status', 'Admin account updated.');
    }

    public function destroy(User $admin)
    {
        if (auth()->user()->account_type !== 'super_admin') {
            abort(403);
        }

        if ($admin->id === auth()->id()) {
            return redirect()->back()->with('error', 'You cannot delete your own account.');
        }

        $name = $admin->name;
        $admin->delete();

        return redirect()
            ->route('admin.admins.index')
            ->with('status', "{$name}'s account has been deleted.");
    }

    public function toggleActive(User $admin)
```

```
    {
        if (auth()->user()->account_type !== 'super_admin') {
            abort(403);
        }

        if ($admin->id === auth()->id()) {
            return redirect()->back()->with('error', 'You cannot deactivate your own account.');
        }

        $admin->update(['is_active' => !$admin->is_active]);
        $msg = $admin->is_active ? "activated" : "deactivated";

        return redirect()->back()->with('status', "{$admin->name}'s account has been {$msg}.");
    }
}
```

### File: app\Http\Controllers\AdminUserManagementController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\IssueReport;
use App\Models\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Storage;

class AdminUserManagementController extends Controller
{
    /**
     * List all customers and store owners.
     */
    public function index(Request $request)
    {
        $query = User::whereIn('account_type', ['customer', 'store_owner']);

        if ($request->filled('search')) {
            $s = $request->search;
            $query->where(function ($q) use ($s) {
                $q->where('name', 'like', "%{$s}%")
                  ->orWhere('email', 'like', "%{$s}%");
            });
        }

        if ($request->filled('type')) {
            $query->where('account_type', $request->type);
        }

        if ($request->filled('status')) {
            match ($request->status) {
                'banned'     => $query->where('is_banned', true),
                'inactive'   => $query->where('is_active', false),
                'restricted' => $query->where('is_restricted', true),
                'active'     => $query->where('is_banned', false)->where('is_active', true),
                default      => null,
            };
        }

        $users = $query->latest()->paginate(20)->withQueryString();

        return view('admin.users.index', compact('users'));
    }

    /**
     * Show a single user's profile and report history.
     */
    public function show(User $user)
    {
        $reports = IssueReport::with(['user'])
            ->where(function ($q) use ($user) {
                $q->where('reported_user_id', $user->id)
                  ->orWhere('user_id', $user->id);
            })
            ->latest()
            ->take(20)
            ->get();

        return view('admin.users.show', compact('user', 'reports'));
    }

    /**
     * Ban a user.
     */
    public function banUser(Request $request, User $user)
    {
        $request->validate(['reason' => 'required|string|max:500']);

        $user->update([
            'is_banned'  => true,
            'ban_reason' => $request->reason,
            'banned_at'  => now(),
        ]);

        return redirect()->back()->with('status', "{$user->name} has been banned.");
    }

    /**
     * Unban a user.
     */
    public function unbanUser(User $user)
    {
        $user->update([
            'is_banned'  => false,
            'ban_reason' => null,
            'banned_at'  => null,
        ]);

        return redirect()->back()->with('status', "{$user->name} has been unbanned.");
    }

    /**
     * Issue a warning to a user.
     */
    public function warnUser(User $user)
    {
        $user->increment('warning_count');
        return redirect()->back()->with('status', "Warning issued to {$user->name}. Total warnings: {$user->warning_count}.");
    }

    /**
     * Restrict a user for a given number of days.
     */
    public function restrictUser(Request $request, User $user)
    {
        $request->validate(['days' => 'required|integer|min:1|max:365']);
```

```
        $user->update([
            'is_restricted'   => true,
            'restricted_until' => now()->addDays($request->days),
        ]);

        return redirect()->back()->with('status', "{$user->name} has been restricted for {$request->days} day(s).");
    }

    /**
     * Remove restriction from a user.
     */
    public function unrestrictUser(User $user)
    {
        $user->update(['is_restricted' => false, 'restricted_until' => null]);
        return redirect()->back()->with('status', "{$user->name}'s restriction has been lifted.");
    }
}
```

### File: app\Http\Controllers\BookController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\Book;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\File;
use Illuminate\Support\Str;

class BookController extends Controller
{
    public function create()
    {
        return view('store.books.add');
    }

    public function edit(Request $request, $id)
    {
        $book = Book::query()
            ->where('user_id', $request->user()->id)
            ->findOrFail($id);

        return view('store.books.edit', compact('book'));
    }

    public function index(Request $request)
    {
        $books = Book::query()
            ->where('user_id', $request->user()->id)
            ->latest('id')
            ->get();

        $storeMetrics = [
            'total_books' => $books->count(),
        ];

        return view('store.books.inventory', compact('books', 'storeMetrics'));
    }

    public function store(Request $request)
    {
        $validated = $request->validate([
            'title' => 'required|string|max:255',
            'author' => 'required|string|max:255',
            'genre' => 'required|string|max:100',
            'publication_year' => 'nullable|integer|min:1000|max:' . now()->year,
            'total_copies' => 'required|integer|min:0',
            'available_rent' => 'required|integer|min:0',
            'available_sale' => 'required|integer|min:0',
            'rental_price' => 'required|numeric|min:0',
            'sale_price' => 'required|numeric|min:0',
            'cover_image' => 'nullable|image|max:5120',
        ]);

        if (($validated['available_rent'] + $validated['available_sale']) > $validated['total_copies']) {
            return back()
                ->withErrors(['total_copies' => 'Total copies must be at least the sum of available rent and sale copies'])
                ->withInput();
        }

        $coverImagePath = null;
        if ($request->hasFile('cover_image')) {
            $directory = public_path('uploads/books');
            if (!File::exists($directory)) {
                File::makeDirectory($directory, 0755, true);
            }

            $file = $request->file('cover_image');
            $filename = Str::uuid()->toString() . '.' . $file->getClientOriginalExtension();
            $file->move($directory, $filename);
            $coverImagePath = 'uploads/books/' . $filename;
        }

        $payload = $validated;
        unset($payload['cover_image']);
        $payload['user_id'] = $request->user()->id;
        $payload['cover_image_path'] = $coverImagePath;

        Book::create($payload);

        $route = $request->has('save_and_add') ? 'add.book.registration' : 'view.inventory';

        return redirect()
            ->route($route)
            ->with('messages', ['Book saved successfully.']);
    }

    public function update(Request $request, $id)
    {
        $book = Book::query()
            ->where('user_id', $request->user()->id)
            ->findOrFail($id);

        $validated = $request->validate([
            'title' => 'required|string|max:255',
            'author' => 'required|string|max:255',
            'genre' => 'required|string|max:100',
            'publication_year' => 'nullable|integer|min:1000|max:' . now()->year,
            'total_copies' => 'required|integer|min:0',
            'available_rent' => 'required|integer|min:0',
            'available_sale' => 'required|integer|min:0',
            'rental_price' => 'required|numeric|min:0',
            'sale_price' => 'required|numeric|min:0',
            'cover_image' => 'nullable|image|max:5120',
        ]);
```

```
        if (($validated['available_rent'] + $validated['available_sale']) > $validated['total_copies']) {
            return back()
                ->withErrors(['total_copies' => 'Total copies must be at least the sum of available rent and sale copies'])
                ->withInput();
        }

        $coverImagePath = $book->cover_image_path;
        if ($request->hasFile('cover_image')) {
            $directory = public_path('uploads/books');
            if (!File::exists($directory)) {
                File::makeDirectory($directory, 0755, true);
            }

            if ($coverImagePath) {
                $oldPath = public_path($coverImagePath);
                if (File::exists($oldPath)) {
                    File::delete($oldPath);
                }
            }

            $file = $request->file('cover_image');
            $filename = Str::uuid()->toString() . '.' . $file->getClientOriginalExtension();
            $file->move($directory, $filename);
            $coverImagePath = 'uploads/books/' . $filename;
        }

        $payload = $validated;
        unset($payload['cover_image']);
        $payload['cover_image_path'] = $coverImagePath;

        $book->update($payload);

        return redirect()
            ->route('view.inventory')
            ->with('messages', ['Book updated successfully.']);
    }

    public function destroy(Request $request, $id)
    {
        $book = Book::query()
            ->where('user_id', $request->user()->id)
            ->findOrFail($id);

        if ($book->cover_image_path) {
            $path = public_path($book->cover_image_path);
            if (File::exists($path)) {
                File::delete($path);
            }
        }

        $book->delete();

        return redirect()
            ->route('view.inventory')
            ->with('messages', ['Book deleted successfully.']);
    }
}
```

### File: app\Http\Controllers\Controller.php

```
<?php

namespace App\Http\Controllers;

abstract class Controller
{
    //
}
```

### File: app\Http\Controllers\CustomerBookController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\Book;
use Illuminate\Http\Request;

class CustomerBookController extends Controller
{
    public function show(Book $book)
    {
        $canRent = $book->available_rent > 0;
        $canBuy = $book->available_sale > 0;

        $similarBooks = Book::query()
            ->where('id', '!=', $book->id)
            ->where('genre', $book->genre)
            ->limit(4)
            ->get();

        return view('customer.book_detail', [
            'book' => $book,
            'canRent' => $canRent,
            'canBuy' => $canBuy,
            'similarBooks' => $similarBooks,
            'store' => null,
            'openingHours' => [],
        ]);
    }
}
```

### File: app\Http\Controllers\CustomerCartController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\Book;
use Illuminate\Http\Request;

class CustomerCartController extends Controller
{
    public function index(Request $request)
    {
        $cart = $this->getCart($request);
        $cartItems = $this->buildCartItems($cart);
        $totalPrice = array_sum(array_column($cartItems, 'price'));

        return view('customer.cart', [
            'cartItems' => $cartItems,
```

```
        'totalPrice' => $totalPrice,
        'checkoutUrl' => route('orders.checkout'),
    ]);
}

public function addRent(Request $request, $bookId)
{
    return $this->addItem($request, $bookId, 'rent');
}

public function addBuy(Request $request, $bookId)
{
    return $this->addItem($request, $bookId, 'buy');
}

public function remove(Request $request, $bookId, $type)
{
    $cart = $this->getCart($request);
    $cart = array_filter($cart, function ($item) use ($bookId, $type) {
        return !((int) $item['book_id'] === (int) $bookId && $item['type'] === $type);
    });

    $request->session()->put('cart', array_values($cart));

    return redirect()
        ->back()
        ->with('status', 'Book removed from cart.');
}

public function count(Request $request)
{
    $cart = $this->getCart($request);
    return response()->json(['count' => count($cart)]);
}

public function checkout(Request $request)
{
    $cart = $this->getCart($request);
    if (empty($cart)) {
        return redirect()
            ->route('cart.index')
            ->with('error', 'Your cart is empty.');
    }

    $cartItems = $this->buildCartItems($cart);
    $hasRent = false;
    $hasBuy = false;
    $total = 0;

    foreach ($cartItems as $item) {
        $total += $item['price'];
        if ($item['type'] === 'rent') {
            $hasRent = true;
        } else {
            $hasBuy = true;
        }
    }

    $orderType = 'buy';
    if ($hasRent && !$hasBuy) {
        $orderType = 'rent';
    } else if ($hasRent && $hasBuy) {
        $orderType = 'mixed';
    }

    $orders = $request->session()->get('orders', []);
    $nextId = count($orders) + 1;
    $orderNumber = 'BH' . now()->format('Ymd') . str_pad((string) $nextId, 4, '0', STR_PAD_LEFT);

    $orders[] = [
        'id' => $nextId,
        'order_number' => $orderNumber,
        'created_at' => now()->toDateTimeString(),
        'order_type' => $orderType,
        'status' => 'pending',
        'total_amount' => $total,
        'delivery_option' => 'pickup',
        'delivery_fee' => 0,
        'delivery_address' => null,
        'notes' => null,
        'store_notes' => null,
        'store' => [
            'store_name' => 'BookHub',
            'address' => null,
            'city' => null,
            'phone' => null,
            'email' => null,
        ],
        'items' => array_map(function ($item) {
            return [
                'book_id' => $item['book']->id,
                'type' => $item['type'],
                'price' => $item['price'],
                'quantity' => 1,
                'rental_days' => $item['type'] === 'rent' ? 30 : null,
            ];
        }, $cartItems),
    ];

    $request->session()->put('orders', $orders);
    $request->session()->forget('cart');

    return redirect()
        ->route('orders.index')
        ->with('status', 'Order placed successfully.');
}

private function addItem(Request $request, $bookId, string $type)
{
    $book = Book::find($bookId);
    if (!$book) {
        return redirect()
            ->back()
            ->with('error', 'Book not found.');
    }

    $cart = $this->getCart($request);

    foreach ($cart as $item) {
        if ((int) $item['book_id'] === (int) $book->id && $item['type'] === $type) {
            return redirect()
                ->back()
                ->with('status', 'Book already in cart.');
        }
    }

    $cart[] = [
        'book_id' => $book->id,
```

```
            'type' => $type,
        ];

        $request->session()->put('cart', $cart);

        return redirect()
            ->back()
            ->with('status', 'Book added to cart.');
    }

    private function getCart(Request $request): array
    {
        $cart = $request->session()->get('cart', []);
        return array_values(array_filter($cart, fn($item) => isset($item['book_id'], $item['type'])));
    }

    private function buildCartItems(array $cart): array
    {
        $items = [];
        foreach ($cart as $item) {
            $book = Book::find($item['book_id']);
            if (!$book) {
                continue;
            }

            $type = $item['type'] === 'buy' ? 'buy' : 'rent';
            $price = $type === 'rent' ? (float) $book->rental_price : (float) $book->sale_price;

            $items[] = [
                'book' => $book,
                'type' => $type,
                'type_label' => $type === 'rent' ? 'Rental' : 'Purchase',
                'type_class' => $type === 'rent' ? 'rental' : 'purchase',
                'period' => $type === 'rent' ? 'Monthly' : null,
                'price' => $price,
            ];
        }
        return $items;
    }
}
```

### File: app\Http\Controllers\CustomerChatController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\ChatConversation;
use App\Models\ChatMessage;
use App\Models\Book;
use App\Models\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Storage;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;

class CustomerChatController extends Controller
{
    /**
     * Display a listing of conversations for the customer.
     */
    public function index(Request $request)
    {
        $user = $request->user();

        $conversations = ChatConversation::with([
                'store',
                'latestMessage',
                'book'
            ])
            ->where('customer_id', $user->id)
            ->when($request->search, function ($query, $search) {
                $query->whereHas('store', function ($q) use ($search) {
                    $q->where('name', 'like', "%{$search}%");
                })->orWhere('subject', 'like', "%{$search}%");
            })
            ->when($request->status, function ($query, $status) {
                if ($status === 'unread') {
                    $query->whereHas('messages', function ($q) use ($user) {
                        $q->where('sender_id', '!=', $user->id)
                          ->where('is_read', false);
                    });
                }
            })
            ->latest('updated_at')
            ->get();

        // Get unread counts
        foreach ($conversations as $conv) {
            $conv->unread_count = $conv->messages()
                ->where('sender_id', '!=', $user->id)
                ->where('is_read', false)
                ->count();
        }

        // Get stores that have books
        $recentStores = User::where('account_type', 'store_owner')
            ->whereExists(function ($query) {
                $query->select(DB::raw(1))
                      ->from('books')
                      ->whereRaw('books.user_id = users.id');
            })
            ->limit(10)
            ->get();

        return view('customer.chat_list', [
            'conversations' => $conversations,
            'recentStores' => $recentStores,
            'search' => $request->search,
            'status_filter' => $request->status,
            'unread_total' => $user->unreadMessagesCount(),
        ]);
    }

    /**
     * Show a specific conversation.
     */
    public function show(Request $request, ChatConversation $conversation)
    {
        // Authorization
        if ($conversation->customer_id !== $request->user()->id) {
            abort(403, 'Unauthorized access to this conversation.');
        }

        // Load relationships
```

```
    $conversation->load(['store', 'book']);

    // Mark messages as read
    $conversation->markAsRead($request->user()->id);

    // Get messages
    $messages = $conversation->messages()
        ->with('sender')
        ->get();

    return view('customer.chat_room', [
        'conversation' => $conversation,
        'messages' => $messages,
    ]);
}

/**
 * Send a new message in a conversation.
 */
public function sendMessage(Request $request, ChatConversation $conversation)
{
    try {
        // Authorization
        if ($conversation->customer_id !== $request->user()->id) {
            return response()->json([
                'success' => false,
                'error' => 'Unauthorized access to this conversation.'
            ], 403);
        }

        // Validate request
        $request->validate([
            'message' => 'nullable|string|max:2000',
            'attachment' => 'nullable|file|max:10240|mimes:jpg,jpeg,png,gif,pdf,doc,docx,txt,zip',
        ]);

        // Check if either message or attachment is provided
        if (!$request->filled('message') && !$request->hasFile('attachment')) {
            return response()->json([
                'success' => false,
                'error' => 'Please provide a message or attachment.'
            ], 422);
        }

        $data = [
            'conversation_id' => $conversation->id,
            'sender_id' => $request->user()->id,
            'sender_role' => 'customer',
            'is_read' => false,
            'message' => $request->input('message', ''),
        ];

        // Handle attachment
        if ($request->hasFile('attachment')) {
            $file = $request->file('attachment');

            // Create directory if it doesn't exist
            $path = 'chat-attachments/' . $conversation->id;

            // Store file
            $filePath = $file->store($path, 'public');

            $data['attachment_path'] = $filePath;
            $data['attachment_name'] = $file->getClientOriginalName();
            $data['attachment_size'] = $file->getSize();
            $data['attachment_type'] = $file->getMimeType();

            Log::info('File uploaded', [
                'path' => $filePath,
                'name' => $file->getClientOriginalName(),
                'size' => $file->getSize()
            ]);
        }

        // Create message
        $message = ChatMessage::create($data);

        // Update conversation
        $conversation->update([
            'last_message_at' => now(),
            'last_message' => $request->input('message') ?: '[Attachment]',
            'last_message_sender_id' => $request->user()->id,
        ]);

        // Load sender for response
        $message->load('sender');

        // Prepare response
        return response()->json([
            'success' => true,
            'message' => [
                'id' => $message->id,
                'content' => $message->message,
                'created_at' => $message->created_at->format('Y-m-d H:i:s'),
                'formatted_time' => $message->created_at->format('g:i A'),
                'sender_id' => $message->sender_id,
                'sender_name' => $message->sender->name,
                'is_me' => true,
                'attachment_url' => $message->attachment_url,
                'attachment_name' => $message->attachment_name,
                'attachment_size' => $message->attachment_size,
                'is_image' => $message->isImage(),
            ]
        ]);

    } catch (\Illuminate\Validation\ValidationException $e) {
        return response()->json([
            'success' => false,
            'error' => 'Validation failed: ' . implode(', ', $e->errors())
        ], 422);
    } catch (\Exception $e) {
        Log::error('Chat message send error: ' . $e->getMessage(), [
            'trace' => $e->getTraceAsString()
        ]);

        return response()->json([
            'success' => false,
            'error' => 'Failed to send message: ' . $e->getMessage()
        ], 500);
    }
}

/**
 * Start a new conversation with a store.
 */
public function startConversation(Request $request)
{
    try {
```

```
        $request->validate([
            'store_id' => 'required|exists:users,id',
            'subject' => 'nullable|string|max:255',
            'message' => 'required|string|max:2000',
        ]);

        // Verify store exists and is a store owner
        $store = User::where('id', $request->store_id)
            ->where('account_type', 'store_owner')
            ->first();

        if (!$store) {
            return back()->with('error', 'Invalid store selected.')->withInput();
        }

        // Check if conversation already exists
        $existingConversation = ChatConversation::where('customer_id', $request->user()->id)
            ->where('store_id', $request->store_id)
            ->first();

        if ($existingConversation) {
            // Add message to existing conversation
            ChatMessage::create([
                'conversation_id' => $existingConversation->id,
                'sender_id' => $request->user()->id,
                'sender_role' => 'customer',
                'message' => $request->message,
                'is_read' => false,
            ]);

            $existingConversation->update([
                'last_message_at' => now(),
                'last_message' => $request->message,
                'last_message_sender_id' => $request->user()->id,
            ]);

            return redirect()->route('chat.show', $existingConversation)
                ->with('success', 'Message sent to existing conversation.');
        }

        // Create new conversation
        $conversation = ChatConversation::create([
            'customer_id' => $request->user()->id,
            'store_id' => $request->store_id,
            'subject' => $request->subject,
            'status' => 'active',
        ]);

        // Create first message
        ChatMessage::create([
            'conversation_id' => $conversation->id,
            'sender_id' => $request->user()->id,
            'sender_role' => 'customer',
            'message' => $request->message,
            'is_read' => false,
        ]);

        $conversation->update([
            'last_message_at' => now(),
            'last_message' => $request->message,
            'last_message_sender_id' => $request->user()->id,
        ]);

        return redirect()->route('chat.show', $conversation)
            ->with('success', 'Conversation started successfully.');

    } catch (\Exception $e) {
        Log::error('Start conversation error: ' . $e->getMessage());
        return back()->with('error', 'Failed to start conversation. Please try again.')->withInput();
    }
}

/**
 * Mark messages as read via AJAX.
 */
public function markAsRead(Request $request, ChatConversation $conversation)
{
    if ($conversation->customer_id !== $request->user()->id) {
        return response()->json(['success' => false, 'error' => 'Unauthorized'], 403);
    }

    $count = $conversation->messages()
        ->where('sender_id', '!=', $request->user()->id)
        ->where('is_read', false)
        ->update([
            'is_read' => true,
            'is_read_at' => now()
        ]);

    return response()->json([
        'success' => true,
        'marked_count' => $count
    ]);
}

/**
 * Poll for new messages.
 */
public function pollMessages(Request $request, ChatConversation $conversation)
{
    try {
        if ($conversation->customer_id !== $request->user()->id) {
            return response()->json(['success' => false, 'error' => 'Unauthorized'], 403);
        }

        $lastId = $request->last_id ?? 0;

        $messages = $conversation->messages()
            ->with('sender')
            ->where('id', '>', $lastId)
            ->get()
            ->map(function ($message) use ($request) {
                return [
                    'id' => $message->id,
                    'content' => $message->message,
                    'created_at' => $message->created_at->format('Y-m-d H:i:s'),
                    'formatted_time' => $message->created_at->format('g:i A'),
                    'sender_id' => $message->sender_id,
                    'sender_name' => $message->sender->name,
                    'is_me' => $message->sender_id === $request->user()->id,
                    'attachment_url' => $message->attachment_url,
                    'attachment_name' => $message->attachment_name,
                    'attachment_size' => $message->attachment_size,
                    'is_image' => $message->isImage(),
                ];
            });

        return response()->json([
```

```
                'success' => true,
                'messages' => $messages
            ]);

        } catch (\Exception $e) {
            Log::error('Poll messages error: ' . $e->getMessage());
            return response()->json([
                'success' => false,
                'error' => 'Failed to poll messages'
            ], 500);
        }
    }

    /**
     * Get list of stores for starting a new chat.
     */
    public function getStores(Request $request)
    {
        try {
            $stores = User::where('account_type', 'store_owner')
                ->withCount('books')
                ->when($request->search, function ($query, $search) {
                    $query->where('name', 'like', "%{$search}%")
                          ->orWhere('email', 'like', "%{$search}%");
                })
                ->limit(20)
                ->get()
                ->map(function ($store) {
                    return [
                        'id' => $store->id,
                        'name' => $store->name,
                        'avatar' => $store->avatar,
                        'books_count' => $store->books_count,
                    ];
                });

            return response()->json($stores);

        } catch (\Exception $e) {
            Log::error('Get stores error: ' . $e->getMessage());
            return response()->json(['error' => 'Failed to fetch stores'], 500);
        }
    }

    /**
     * Get unread count for AJAX polling.
     */
    public function getUnreadCount(Request $request)
    {
        try {
            $user = $request->user();
            return response()->json([
                'unread_count' => $user->unreadMessagesCount()
            ]);
        } catch (\Exception $e) {
            return response()->json(['unread_count' => 0]);
        }
    }
}
```

### File: app\Http\Controllers\CustomerDashboardController.php

```php
<?php

namespace App\Http\Controllers;

use App\Models\Book;
use Illuminate\Http\Request;

class CustomerDashboardController extends Controller
{
    public function index(Request $request)
    {
        $searchQuery = $request->query('search');
        $selectedGenre = $request->query('genre');
        $selectedAvailability = $request->query('availability');

        $booksQuery = Book::query()->latest('id');

        if ($searchQuery) {
            $booksQuery->where(function ($query) use ($searchQuery) {
                $query->where('title', 'like', '%' . $searchQuery . '%')
                    ->orWhere('author', 'like', '%' . $searchQuery . '%')
                    ->orWhere('genre', 'like', '%' . $searchQuery . '%');
            });
        }

        if ($selectedGenre) {
            $booksQuery->where('genre', $selectedGenre);
        }

        if ($selectedAvailability === 'rent') {
            $booksQuery->where('available_rent', '>', 0);
        } elseif ($selectedAvailability === 'buy') {
            $booksQuery->where('available_sale', '>', 0);
        }

        $totalBooks = (clone $booksQuery)->count();

        $books = $booksQuery
            ->paginate(12)
            ->withQueryString();

        $genres = Book::query()
            ->whereNotNull('genre')
            ->where('genre', '!=', '')
            ->distinct()
            ->orderBy('genre')
            ->pluck('genre');

        return view('customer.dashboard', [
            'books' => $books,
            'genres' => $genres,
            'totalBooks' => $totalBooks,
            'searchQuery' => $searchQuery,
            'selectedGenre' => $selectedGenre,
            'selectedAvailability' => $selectedAvailability,
        ]);
    }
}
```

### File: app\Http\Controllers\CustomerIssueReportController.php

```php
<?php

namespace App\Http\Controllers;

use App\Models\IssueReport;
use Illuminate\Http\Request;

class CustomerIssueReportController extends Controller
{
    public function index(Request $request)
    {
        $reports = IssueReport::query()
            ->where('user_id', $request->user()->id)
            ->latest()
            ->get();

        return view('customer.issue_reports.index', [
            'reports' => $reports,
        ]);
    }

    public function create()
    {
        return view('customer.issue_reports.create');
    }

    public function store(Request $request)
    {
        $data = $request->validate([
            'subject' => 'required|string|max:255',
            'description' => 'required|string|max:4000',
            'priority' => 'required|in:low,medium,high',
            'evidence' => 'nullable|file|max:10240|mimes:jpg,jpeg,png,gif,pdf,doc,docx,txt',
        ]);

        $reportData = [
            'user_id' => $request->user()->id,
            'reporter_role' => 'customer',
            'subject' => $data['subject'],
            'description' => $data['description'],
            'priority' => $data['priority'],
            'status' => 'open',
        ];

        if ($request->hasFile('evidence')) {
            $file = $request->file('evidence');
            $path = $file->store('report-evidence', 'public');
            $reportData['evidence_path'] = $path;
            $reportData['evidence_name'] = $file->getClientOriginalName();
            $reportData['evidence_type'] = $file->getMimeType();
        }

        IssueReport::create($reportData);

        return redirect()
            ->route('issue-reports.index')
            ->with('status', 'Issue report submitted.');
    }

    public function show(Request $request, IssueReport $issueReport)
    {
        if ((int) $issueReport->user_id !== (int) $request->user()->id) {
```

```
            abort(403);
        }

        return view('customer.issue_reports.show', [
            'report' => $issueReport,
        ]);
    }
}
```

### File: app\Http\Controllers\CustomerOrderController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\Book;
use Carbon\Carbon;
use Illuminate\Http\Request;

class CustomerOrderController extends Controller
{
    public function index(Request $request)
    {
        $statusFilter = $request->query('status', 'all');
        $timeFilter = $request->query('time', 'all');

        $orders = collect($request->session()->get('orders', []));

        if ($statusFilter !== 'all') {
            $orders = $orders->where('status', $statusFilter);
        }

        if ($timeFilter !== 'all') {
            $cutoff = $timeFilter === '7days' ? now()->subDays(7) : now()->subDays(30);
            $orders = $orders->filter(function ($order) use ($cutoff) {
                return Carbon::parse($order['created_at'])->greaterThanOrEqualTo($cutoff);
            });
        }

        $orders = $orders->map(function ($order) {
            $order['created_at'] = Carbon::parse($order['created_at']);
            $order['status_label'] = $this->statusLabel($order['status']);
            $order['items_count'] = count($order['items'] ?? []);
            $order['items_preview'] = collect($order['items'] ?? [])
                ->take(2)
                ->map(function ($item) {
                    $book = Book::find($item['book_id']);
                    return $book?->title ?? 'Unknown';
                })
                ->implode(', ');
            $order['store_name'] = $order['store']['store_name'] ?? 'BookHub';
            return $order;
        })->values();

        $activeRentals = $orders->filter(function ($order) {
            return $order['order_type'] === 'rent' && !in_array($order['status'], ['completed', 'cancelled'], true);
        })->values();

        return view('customer.order_history', [
            'orders' => $orders,
            'activeRentals' => $activeRentals,
            'statusFilter' => $statusFilter,
            'timeFilter' => $timeFilter,
        ]);
    }

    public function show(Request $request, $orderId)
    {
        $orders = collect($request->session()->get('orders', []));
        $order = $orders->firstWhere('id', (int) $orderId);

        if (!$order) {
            return redirect()
                ->route('orders.index')
                ->with('error', 'Order not found.');
        }

        $order['created_at'] = Carbon::parse($order['created_at']);
        $order['status_label'] = $this->statusLabel($order['status']);

        $items = collect($order['items'] ?? [])->map(function ($item) {
            $book = Book::find($item['book_id']);
            return [
                'book' => $book,
                'item_type' => $item['type'],
                'quantity' => $item['quantity'] ?? 1,
                'rental_days' => $item['rental_days'] ?? null,
                'price' => $item['price'] ?? 0,
            ];
        })->filter(fn ($item) => $item['book'])->values();

        $subtotal = $items->sum('price');

        return view('customer.order_detail', [
            'order' => $order,
            'items' => $items,
            'subtotal' => $subtotal,
            'delivery' => null,
        ]);
    }

    public function markFinished(Request $request, $orderId)
    {
        $orders = $request->session()->get('orders', []);
        foreach ($orders as &$order) {
            if ((int) $order['id'] === (int) $orderId) {
                $order['status'] = 'completed';
            }
        }
        unset($order);

        $request->session()->put('orders', $orders);

        return redirect()
            ->back()
            ->with('status', 'Order marked as completed.');
    }

    private function statusLabel(string $status): string
    {
        return match ($status) {
            'pending' => 'Pending',
            'approved' => 'Approved',
            'preparing' => 'Preparing',
            'ready' => 'Ready',
```

```
            'out_for_delivery' => 'Out for Delivery',
            'delivered' => 'Delivered',
            'completed' => 'Completed',
            'cancelled' => 'Declined',
            default => ucfirst(str_replace('_', ' ', $status)),
        };
    }
}
```

### File: app\Http\Controllers\CustomerWishlistController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\Book;
use Illuminate\Http\Request;

class CustomerWishlistController extends Controller
{
    public function index(Request $request)
    {
        $ids = $this->getWishlistIds($request);

        $books = Book::query()
            ->whereIn('id', $ids)
            ->get()
            ->sortBy(function (Book $book) use ($ids) {
                return array_search($book->id, $ids, true);
            })
            ->values();

        return view('customer.wishlist', [
            'wishlistBooks' => $books,
            'wishlistCount' => $books->count(),
        ]);
    }

    public function add(Request $request, $bookId)
    {
        $book = Book::find($bookId);
        if (!$book) {
            return redirect()
                ->back()
                ->with('error', 'Book not found.');
        }

        $ids = $this->getWishlistIds($request);
        if (!in_array($book->id, $ids, true)) {
            $ids[] = $book->id;
            $request->session()->put('wishlist', $ids);
        }

        return redirect()
            ->back()
            ->with('status', 'Book added to wishlist.');
    }

    public function remove(Request $request, $bookId)
    {
        $ids = $this->getWishlistIds($request);
        $ids = array_values(array_filter($ids, fn ($id) => (int) $id !== (int) $bookId));
        $request->session()->put('wishlist', $ids);

        return redirect()
            ->back()
            ->with('status', 'Book removed from wishlist.');
    }

    public function clear(Request $request)
    {
        $request->session()->forget('wishlist');

        return redirect()
            ->back()
            ->with('status', 'Wishlist cleared.');
    }

    private function getWishlistIds(Request $request): array
    {
        $ids = $request->session()->get('wishlist', []);
        return array_values(array_unique(array_map('intval', $ids)));
    }
}
```

### File: app\Http\Controllers\ProfileController.php

```
<?php

namespace App\Http\Controllers;

use App\Http\Requests\ProfileUpdateRequest;
use Illuminate\Contracts\Auth\MustVerifyEmail;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\Redirect;
use Inertia\Inertia;
use Inertia\Response;

class ProfileController extends Controller
{
    /**
     * Display the user's profile form.
     */
    public function edit(Request $request): Response
    {
        return Inertia::render('Profile/Edit', [
            'mustVerifyEmail' => $request->user() instanceof MustVerifyEmail,
            'status' => session('status'),
        ]);
    }

    /**
     * Update the user's profile information.
     */
    public function update(ProfileUpdateRequest $request): RedirectResponse
    {
        $request->user()->fill($request->validated());

        if ($request->user()->isDirty('email')) {
            $request->user()->email_verified_at = null;
        }
```

```
        $request->user()->save();

        return Redirect::route('profile.edit');
    }

    /**
     * Delete the user's account.
     */
    public function destroy(Request $request): RedirectResponse
    {
        $request->validate([
            'password' => ['required', 'current_password'],
        ]);

        $user = $request->user();

        Auth::logout();

        $user->delete();

        $request->session()->invalidate();
        $request->session()->regenerateToken();

        return Redirect::to('/');
    }
}
```

## File: app\Http\Controllers\StoreChatController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\ChatConversation;
use App\Models\ChatMessage;
use App\Models\Book;
use App\Models\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Storage;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Log;

class StoreChatController extends Controller
{
    /**
     * Display a listing of conversations for the store owner.
     */
    public function index(Request $request)
    {
        $user = $request->user();

        $conversations = ChatConversation::with([
                'customer',
                'latestMessage',
                'book'
            ])
            ->where('store_id', $user->id)
            ->when($request->search, function ($query, $search) {
                $query->whereHas('customer', function ($q) use ($search) {
                    $q->where('name', 'like', "%{$search}%")
                      ->orWhere('email', 'like', "%{$search}%");
                })->orWhere('subject', 'like', "%{$search}%");
            })
            ->when($request->book_id, function ($query, $bookId) {
                $query->where('book_id', $bookId);
            })
            ->latest('updated_at')
            ->get();

        // Get unread counts
        foreach ($conversations as $conv) {
            $conv->unread_count = $conv->messages()
                ->where('sender_id', '!=', $user->id)
                ->where('is_read', false)
                ->count();
        }

        // Get store's books for filtering
        $books = Book::where('user_id', $user->id)->get();

        return view('store.chat_list', [
            'conversations' => $conversations,
            'books' => $books,
            'search' => $request->search,
            'selected_book' => $request->book_id,
            'unread_total' => $user->unreadMessagesCount(),
        ]);
    }

    /**
     * Show a specific conversation.
     */
    public function show(Request $request, ChatConversation $conversation)
    {
        // Authorization
        if ($conversation->store_id !== $request->user()->id) {
            abort(403, 'Unauthorized access to this conversation.');
        }

        // Load relationships
        $conversation->load(['customer', 'book']);

        // Mark messages as read
        $conversation->markAsRead($request->user()->id);

        // Get messages
        $messages = $conversation->messages()
            ->with('sender')
            ->get();

        // Get other conversations for sidebar
        $otherConversations = ChatConversation::with(['customer', 'book'])
            ->where('store_id', $request->user()->id)
            ->where('id', '!=', $conversation->id)
            ->latest('updated_at')
            ->limit(5)
            ->get();

        return view('store.chat_room', [
            'conversation' => $conversation,
            'messages' => $messages,
            'otherConversations' => $otherConversations,
        ]);
    }
    /**
```

```
 * Send a new message in a conversation.
 */
public function sendMessage(Request $request, ChatConversation $conversation)
{
    try {
        // Authorization
        if ($conversation->store_id !== $request->user()->id) {
            return response()->json([
                'success' => false,
                'error' => 'Unauthorized access to this conversation.'
            ], 403);
        }

        // Validate request
        $request->validate([
            'message' => 'nullable|string|max:2000',
            'attachment' => 'nullable|file|max:10240|mimes:jpg,jpeg,png,gif,pdf,doc,docx,txt,zip',
        ]);

        // Check if either message or attachment is provided
        if (!$request->filled('message') && !$request->hasFile('attachment')) {
            return response()->json([
                'success' => false,
                'error' => 'Please provide a message or attachment.'
            ], 422);
        }

        $data = [
            'conversation_id' => $conversation->id,
            'sender_id' => $request->user()->id,
            'sender_role' => 'store_owner',
            'is_read' => false,
            'message' => $request->input('message', ''),
        ];

        // Handle attachment
        if ($request->hasFile('attachment')) {
            $file = $request->file('attachment');

            // Create directory if it doesn't exist
            $path = 'chat-attachments/' . $conversation->id;

            // Store file
            $filePath = $file->store($path, 'public');

            $data['attachment_path'] = $filePath;
            $data['attachment_name'] = $file->getClientOriginalName();
            $data['attachment_size'] = $file->getSize();
            $data['attachment_type'] = $file->getMimeType();

            Log::info('File uploaded', [
                'path' => $filePath,
                'name' => $file->getClientOriginalName(),
                'size' => $file->getSize()
            ]);
        }

        // Create message
        $message = ChatMessage::create($data);

        // Update conversation
        $conversation->update([
            'last_message_at' => now(),
            'last_message' => $request->input('message') ?: '[Attachment]',
            'last_message_sender_id' => $request->user()->id,
        ]);

        // Load sender for response
        $message->load('sender');

        return response()->json([
            'success' => true,
            'message' => [
                'id' => $message->id,
                'content' => $message->message,
                'created_at' => $message->created_at->format('Y-m-d H:i:s'),
                'formatted_time' => $message->created_at->format('g:i A'),
                'sender_id' => $message->sender_id,
                'sender_name' => $message->sender->name,
                'is_me' => true,
                'attachment_url' => $message->attachment_url,
                'attachment_name' => $message->attachment_name,
                'attachment_size' => $message->attachment_size,
                'is_image' => $message->isImage(),
            ]
        ]);

    } catch (\Illuminate\Validation\ValidationException $e) {
        return response()->json([
            'success' => false,
            'error' => 'Validation failed: ' . implode(', ', $e->errors())
        ], 422);
    } catch (\Exception $e) {
        Log::error('Store chat message send error: ' . $e->getMessage(), [
            'trace' => $e->getTraceAsString()
        ]);

        return response()->json([
            'success' => false,
            'error' => 'Failed to send message: ' . $e->getMessage()
        ], 500);
    }
}

/**
 * Mark messages as read via AJAX.
 */
public function markAsRead(Request $request, ChatConversation $conversation)
{
    if ($conversation->store_id !== $request->user()->id) {
        return response()->json(['success' => false, 'error' => 'Unauthorized'], 403);
    }

    $count = $conversation->messages()
        ->where('sender_id', '!=', $request->user()->id)
        ->where('is_read', false)
        ->update([
            'is_read' => true,
            'is_read_at' => now()
        ]);

    return response()->json([
        'success' => true,
        'marked_count' => $count
    ]);
}

/**
```

```
 * Poll for new messages.
 */
public function pollMessages(Request $request, ChatConversation $conversation)
{
    try {
        if ($conversation->store_id !== $request->user()->id) {
            return response()->json(['success' => false, 'error' => 'Unauthorized'], 403);
        }

        $lastId = $request->last_id ?? 0;

        $messages = $conversation->messages()
            ->with('sender')
            ->where('id', '>', $lastId)
            ->get()
            ->map(function ($message) use ($request) {
                return [
                    'id' => $message->id,
                    'content' => $message->message,
                    'created_at' => $message->created_at->format('Y-m-d H:i:s'),
                    'formatted_time' => $message->created_at->format('g:i A'),
                    'sender_id' => $message->sender_id,
                    'sender_name' => $message->sender->name,
                    'is_me' => $message->sender_id === $request->user()->id,
                    'attachment_url' => $message->attachment_url,
                    'attachment_name' => $message->attachment_name,
                    'attachment_size' => $message->attachment_size,
                    'is_image' => $message->isImage(),
                ];
            });

        return response()->json([
            'success' => true,
            'messages' => $messages
        ]);

    } catch (\Exception $e) {
        Log::error('Store poll messages error: ' . $e->getMessage());
        return response()->json([
            'success' => false,
            'error' => 'Failed to poll messages'
        ], 500);
    }
}

/**
 * Start a new conversation with a customer.
 */
public function startConversation(Request $request)
{
    try {
        $request->validate([
            'customer_id' => 'required|exists:users,id',
            'book_id' => 'nullable|exists:books,id',
            'subject' => 'nullable|string|max:255',
            'message' => 'required|string|max:2000',
        ]);

        // Verify customer exists
        $customer = User::where('id', $request->customer_id)
            ->where('account_type', 'customer')
            ->first();

        if (!$customer) {
            return back()->with('error', 'Invalid customer selected.')->withInput();
        }

        // Check if conversation already exists
        $existingConversation = ChatConversation::where('store_id', $request->user()->id)
            ->where('customer_id', $request->customer_id)
            ->when($request->book_id, function ($query, $bookId) {
                $query->where('book_id', $bookId);
            })
            ->first();

        if ($existingConversation) {
            // Add message to existing conversation
            ChatMessage::create([
                'conversation_id' => $existingConversation->id,
                'sender_id' => $request->user()->id,
                'sender_role' => 'store_owner',
                'message' => $request->message,
                'is_read' => false,
            ]);

            $existingConversation->update([
                'last_message_at' => now(),
                'last_message' => $request->message,
                'last_message_sender_id' => $request->user()->id,
            ]);

            return redirect()->route('store.chat.show', $existingConversation)
                ->with('success', 'Message sent to existing conversation.');
        }

        // Create new conversation
        $conversation = ChatConversation::create([
            'customer_id' => $request->customer_id,
            'store_id' => $request->user()->id,
            'book_id' => $request->book_id,
            'subject' => $request->subject,
            'status' => 'active',
        ]);

        // Create first message
        ChatMessage::create([
            'conversation_id' => $conversation->id,
            'sender_id' => $request->user()->id,
            'sender_role' => 'store_owner',
            'message' => $request->message,
            'is_read' => false,
        ]);

        $conversation->update([
            'last_message_at' => now(),
            'last_message' => $request->message,
            'last_message_sender_id' => $request->user()->id,
        ]);

        return redirect()->route('store.chat.show', $conversation)
            ->with('success', 'Conversation started successfully.');

    } catch (\Exception $e) {
        Log::error('Store start conversation error: ' . $e->getMessage());
        return back()->with('error', 'Failed to start conversation. Please try again.')->withInput();
    }
}
/**
```

```
     * Get unread count for AJAX polling.
     */
    public function getUnreadCount(Request $request)
    {
        try {
            $user = $request->user();
            return response()->json([
                'unread_count' => $user->unreadMessagesCount()
            ]);
        } catch (\Exception $e) {
            return response()->json(['unread_count' => 0]);
        }
    }

    /**
     * Delete a conversation.
     */
    public function destroy(Request $request, ChatConversation $conversation)
    {
        if ($conversation->store_id !== $request->user()->id) {
            abort(403);
        }

        // Delete attachments
        foreach ($conversation->messages as $message) {
            if ($message->attachment_path) {
                Storage::disk('public')->delete($message->attachment_path);
            }
        }

        $conversation->delete();

        return redirect()->route('store.chat.index')
            ->with('success', 'Conversation deleted successfully.');
    }
}
```

## File: app\Http\Controllers\StoreController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\Store;
use App\Models\StoreHour;
use App\Models\StoreService;
use App\Models\StorePolicy;
use App\Models\StorePaymentMethod;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Validator;
use Illuminate\Support\Str;
use Illuminate\Support\Facades\Log;

class StoreController extends Controller
{
    /**
     * Show the store registration form.
     *
     * @return \Illuminate\View\View
     */
    public function showRegistrationForm()
    {
        return view('store.registration');
    }

    /**
     * Handle the store registration process.
     *
     * @param  \Illuminate\Http\Request  $request
     * @return \Illuminate\Http\RedirectResponse
     */
    public function register(Request $request)
    {
        // Validate the request data
        $validator = $this->validateRegistration($request->all());

        if ($validator->fails()) {
            return redirect()->back()
                ->withErrors($validator)
                ->withInput()
                ->with('registration_error', true);
        }

        try {
            DB::beginTransaction();

            // Create the store
            $store = $this->createStore($request);

            // Create store services
            $this->createStoreServices($store, $request);

            // Create store hours
            $this->createStoreHours($store, $request);

            // Create store policies
            $this->createStorePolicies($store, $request);

            // Create payment methods
            $this->createPaymentMethods($store, $request);

            DB::commit();

            // Log the successful registration
            Log::info('New store registered', ['store_id' => $store->id, 'store_name' => $store->name]);

            // Redirect to success page with store details
            return redirect()->route('store.registration.success', ['store' => $store->id])
                ->with('success', 'Your bookstore has been successfully registered!')
                ->with('store', $store);

        } catch (\Exception $e) {
            DB::rollBack();

            Log::error('Store registration failed', [
                'error' => $e->getMessage(),
                'trace' => $e->getTraceAsString()
            ]);

            return redirect()->back()
                ->withInput()
                ->with('error', 'An error occurred during registration. Please try again. Error: ' . $e->getMessage());
        }
    }
```

```php
/**
 * Show registration success page.
 *
 * @param  int  $id
 * @return \Illuminate\View\View
 */
public function registrationSuccess($id)
{
    $store = Store::findOrFail($id);
    return view('store.registration-success', compact('store'));
}

/**
 * Validate the registration request.
 *
 * @param  array  $data
 * @return \Illuminate\Contracts\Validation\Validator
 */
protected function validateRegistration(array $data)
{
    return Validator::make($data, [
        // Store Information
        'store_name' => 'required|string|max:255|unique:stores,name',
        'owner_full_name' => 'required|string|max:255',
        'email' => 'required|email|max:255|unique:stores,email',
        'country_code' => 'required|string|max:10',
        'phone' => 'required|string|max:20|unique:stores,phone',
        'store_type' => 'required|string|in:bookstore,library,coffee_shop,educational,online_only,home_based,religious,children',
        'city' => 'required|string|max:100',
        'subcity' => 'nullable|string|max:100',
        'address' => 'required|string|max:255',
        'store_description' => 'nullable|string|max:1000',

        // Services
        'offers_rental' => 'sometimes|boolean',
        'offers_sale' => 'sometimes|boolean',
        'offers_delivery' => 'sometimes|boolean',
        'delivery_radius' => 'nullable|numeric|min:1|max:50',
        'delivery_fee' => 'nullable|numeric|min:0',
        'delivery_methods' => 'nullable|array',

        // Business Hours
        'open_monday' => 'sometimes|boolean',
        'open_tuesday' => 'sometimes|boolean',
        'open_wednesday' => 'sometimes|boolean',
        'open_thursday' => 'sometimes|boolean',
        'open_friday' => 'sometimes|boolean',
        'open_saturday' => 'sometimes|boolean',
        'open_sunday' => 'sometimes|boolean',
        'closed_monday' => 'sometimes|boolean',
        'closed_tuesday' => 'sometimes|boolean',
        'closed_wednesday' => 'sometimes|boolean',
        'closed_thursday' => 'sometimes|boolean',
        'closed_friday' => 'sometimes|boolean',
        'closed_saturday' => 'sometimes|boolean',
        'closed_sunday' => 'sometimes|boolean',

        // Times
        'open_time_monday' => 'nullable|date_format:H:i',
        'close_time_monday' => 'nullable|date_format:H:i',
        'open_time_tuesday' => 'nullable|date_format:H:i',
        'close_time_tuesday' => 'nullable|date_format:H:i',
        'open_time_wednesday' => 'nullable|date_format:H:i',
        'close_time_wednesday' => 'nullable|date_format:H:i',
        'open_time_thursday' => 'nullable|date_format:H:i',
        'close_time_thursday' => 'nullable|date_format:H:i',
        'open_time_friday' => 'nullable|date_format:H:i',
        'close_time_friday' => 'nullable|date_format:H:i',
        'open_time_saturday' => 'nullable|date_format:H:i',
        'close_time_saturday' => 'nullable|date_format:H:i',
        'open_time_sunday' => 'nullable|date_format:H:i',
        'close_time_sunday' => 'nullable|date_format:H:i',

        // Policies
        'rental_period' => 'required|integer|min:1|max:30',
        'rental_price' => 'required|numeric|min:0',
        'late_fee' => 'required|numeric|min:0',
        'security_deposit' => 'required|numeric|min:0',
        'max_books' => 'nullable|integer|min:1',
        'discount_percent' => 'nullable|integer|min:0|max:100',

        // Payment Methods
        'payment_methods' => 'nullable|array',

        // Terms
        'agree_terms' => 'required|accepted',
    ], [
        'store_name.required' => 'Store name is required',
        'store_name.unique' => 'This store name is already taken',
        'owner_full_name.required' => 'Owner full name is required',
        'email.required' => 'Email address is required',
        'email.email' => 'Please enter a valid email address',
        'email.unique' => 'This email is already registered',
        'phone.required' => 'Phone number is required',
        'phone.unique' => 'This phone number is already registered',
        'city.required' => 'City is required',
        'address.required' => 'Street address is required',
        'store_type.required' => 'Store type is required',
        'agree_terms.accepted' => 'You must agree to the terms and conditions',
        'rental_period.required' => 'Rental period is required',
        'rental_price.required' => 'Rental price is required',
        'late_fee.required' => 'Late fee is required',
        'security_deposit.required' => 'Security deposit is required',
    ]);
}

/**
 * Create a new store.
 *
 * @param  \Illuminate\Http\Request  $request
 * @return \App\Models\Store
 */
protected function createStore(Request $request)
{
    $store = new Store();
    $store->name = $request->store_name;
    $store->slug = Str::slug($request->store_name);
    $store->owner_name = $request->owner_full_name;
    $store->email = $request->email;
    $store->country_code = $request->country_code;
    $store->phone = $request->phone;
    $store->full_phone = $request->country_code . $request->phone;
    $store->store_type = $request->store_type;
    $store->city = $request->city;
    $store->subcity = $request->subcity;
    $store->address = $request->address;
    $store->description = $request->store_description;
    $store->status = 'pending'; // Requires admin approval
```

```
    $store->registration_date = now();

    // Generate a unique store code
    $store->store_code = $this->generateStoreCode();

    $store->save();

    return $store;
}

/**
 * Generate a unique store code.
 *
 * @return string
 */
protected function generateStoreCode()
{
    $prefix = 'BK';
    $timestamp = now()->format('ymd');
    $random = strtoupper(Str::random(4));

    $code = $prefix . $timestamp . $random;

    // Ensure uniqueness
    while (Store::where('store_code', $code)->exists()) {
        $random = strtoupper(Str::random(4));
        $code = $prefix . $timestamp . $random;
    }

    return $code;
}

/**
 * Create store services.
 *
 * @param  \App\Models\Store  $store
 * @param  \Illuminate\Http\Request  $request
 * @return void
 */
protected function createStoreServices(Store $store, Request $request)
{
    $service = new StoreService();
    $service->store_id = $store->id;
    $service->offers_rental = $request->has('offers_rental');
    $service->offers_sale = $request->has('offers_sale');
    $service->offers_delivery = $request->has('offers_delivery');
    $service->delivery_radius = $request->delivery_radius;
    $service->delivery_fee = $request->delivery_fee;

    // Store delivery methods as JSON if provided
    if ($request->has('delivery_methods')) {
        $service->delivery_methods = json_encode($request->delivery_methods);
    }

    $service->save();
}

/**
 * Create store business hours.
 *
 * @param  \App\Models\Store  $store
 * @param  \Illuminate\Http\Request  $request
 * @return void
 */
protected function createStoreHours(Store $store, Request $request)
{
    $days = ['monday', 'tuesday', 'wednesday', 'thursday', 'friday', 'saturday', 'sunday'];

    foreach ($days as $day) {
        $isOpen = $request->has('open_' . $day) && $request->input('open_' . $day) == 'on';
        $isClosed = $request->has('closed_' . $day) && $request->input('closed_' . $day) == 'on';

        $openTime = $request->input('open_time_' . $day);
        $closeTime = $request->input('close_time_' . $day);

        // If closed, set times to null
        if ($isClosed) {
            $openTime = null;
            $closeTime = null;
            $isOpen = false;
        }

        $storeHour = new StoreHour();
        $storeHour->store_id = $store->id;
        $storeHour->day_of_week = $day;
        $storeHour->is_open = $isOpen;
        $storeHour->is_closed = $isClosed;
        $storeHour->open_time = $openTime;
        $storeHour->close_time = $closeTime;
        $storeHour->save();
    }
}

/**
 * Create store policies.
 *
 * @param  \App\Models\Store  $store
 * @param  \Illuminate\Http\Request  $request
 * @return void
 */
protected function createStorePolicies(Store $store, Request $request)
{
    $policy = new StorePolicy();
    $policy->store_id = $store->id;
    $policy->rental_period_days = $request->rental_period;
    $policy->rental_price_per_day = $request->rental_price;
    $policy->late_fee_per_day = $request->late_fee;
    $policy->security_deposit = $request->security_deposit;
    $policy->max_books_per_customer = $request->max_books ?? 5;
    $policy->student_discount_percent = $request->discount_percent ?? 0;
    $policy->save();
}

/**
 * Create store payment methods.
 *
 * @param  \App\Models\Store  $store
 * @param  \Illuminate\Http\Request  $request
 * @return void
 */
protected function createPaymentMethods(Store $store, Request $request)
{
    if ($request->has('payment_methods')) {
        foreach ($request->payment_methods as $method) {
            $paymentMethod = new StorePaymentMethod();
            $paymentMethod->store_id = $store->id;
            $paymentMethod->payment_method = $method;
            $paymentMethod->is_active = true;
```

```
                $paymentMethod->save();
            }
        } else {
            // Default to cash if no methods selected
            $paymentMethod = new StorePaymentMethod();
            $paymentMethod->store_id = $store->id;
            $paymentMethod->payment_method = 'cash';
            $paymentMethod->is_active = true;
            $paymentMethod->save();
        }
    }

    /**
     * Get store types for dropdown.
     *
     * @return array
     */
    public static function getStoreTypes()
    {
        return [
            'bookstore' => '■ Traditional Book Store',
            'library' => '■■ Library & Reading Space',
            'coffee_shop' => '■ Coffee Shop with Books',
            'educational' => '■ Educational & Textbook Store',
            'online_only' => '■ Online Book Store',
            'home_based' => '■ Home-based Book Business',
            'religious' => '■ Religious Book Store',
            'children' => '■ Children\'s Book Store',
        ];
    }

    /**
     * Get Ethiopian cities for dropdown.
     *
     * @return array
     */
    public static function getEthiopianCities()
    {
        return [
            'addis_ababa' => 'Addis Ababa (■■■ ■■■)',
            'dire_dawa' => 'Dire Dawa (■■ ■■)',
            'bahir_dar' => 'Bahir Dar (■■■ ■■)',
            'mekele' => 'Mekele (■■■)',
            'hawassa' => 'Hawassa (■■■)',
            'gondar' => 'Gondar (■■■■)',
            'jimma' => 'Jimma (■■)',
            'desse' => 'Dessie (■■)',
            'harar' => 'Harar (■■■)',
            'adama' => 'Adama (■■■)',
            'jijiga' => 'Jijiga (■■■)',
            'shashamane' => 'Shashamane (■■■■)',
            'arba_minch' => 'Arba Minch (■■■ ■■■)',
            'other' => 'Other City',
        ];
    }
}
```

## *File: app\Http\Controllers\StoreIssueReportController.php*

```
<?php

namespace App\Http\Controllers;

use App\Models\IssueReport;
use App\Models\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Storage;

class StoreIssueReportController extends Controller
{
    public function index(Request $request)
    {
        $reports = IssueReport::with(['reportedUser'])
            ->where('user_id', $request->user()->id)
            ->where('reporter_role', 'store_owner')
            ->latest()
            ->get();

        return view('store.issue_reports.index', compact('reports'));
    }

    public function create()
    {
        // Get customers who have had conversations with this store
        $customers = User::where('account_type', 'customer')
            ->orderBy('name')
            ->get();

        return view('store.issue_reports.create', compact('customers'));
    }

    public function store(Request $request)
    {
        $data = $request->validate([
            'reported_user_id' => 'required|exists:users,id',
            'subject'          => 'required|string|max:255',
            'description'      => 'required|string|max:4000',
            'priority'         => 'required|in:low,medium,high',
            'evidence'         => 'nullable|file|max:10240|mimes:jpg,jpeg,png,gif,pdf,doc,docx,txt',
        ]);

        $reportData = [
            'user_id'          => $request->user()->id,
            'reported_user_id' => $data['reported_user_id'],
            'reporter_role'    => 'store_owner',
            'subject'          => $data['subject'],
            'description'      => $data['description'],
            'priority'         => $data['priority'],
            'status'           => 'open',
        ];

        if ($request->hasFile('evidence')) {
            $file = $request->file('evidence');
            $path = $file->store('report-evidence', 'public');
            $reportData['evidence_path'] = $path;
            $reportData['evidence_name'] = $file->getClientOriginalName();
            $reportData['evidence_type'] = $file->getMimeType();
        }

        IssueReport::create($reportData);

        return redirect()->route('store.issue-reports.index')
            ->with('status', 'Report submitted successfully. An admin will review it shortly.');
    }
    public function show(Request $request, IssueReport $issueReport)
```

```
    {
        if ((int) $issueReport->user_id !== (int) $request->user()->id) {
            abort(403);
        }

        $issueReport->load(['reportedUser', 'assignedAdmin']);

        return view('store.issue_reports.show', compact('issueReport'));
    }
}
```

### File: app\Http\Controllers\StoreRegistrationController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\StoreRegistration;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use Illuminate\Support\Facades\Schema;
use Inertia\Inertia;

class StoreRegistrationController extends Controller
{
    public function create(Request $request)
    {
        if ($request->header('X-Inertia')) {
            return Inertia::location(url('/store/registration'));
        }

        return view('store.registration');
    }

    public function edit(Request $request)
    {
        if ($request->header('X-Inertia')) {
            return Inertia::location(url('/store/registration/update'));
        }

        $store = null;

        if ($request->filled('store_id') && Schema::hasTable('store_registrations')) {
            $store = StoreRegistration::find($request->input('store_id'));
        }

        return view('store.registration-update', [
            'store' => $store,
            'storeId' => $store?->id,
        ]);
    }

    public function show(Request $request)
    {
        if ($request->header('X-Inertia')) {
            return Inertia::location(url('/store/registration/view'));
        }

        $stores = collect();
        $storeSource = 'registrations';

        if (Schema::hasTable('store_registrations')) {
            $stores = StoreRegistration::query()->latest('id')->get();
        }

        if ($stores->isEmpty() && Schema::hasTable('stores')) {
            $stores = DB::table('stores')->orderByDesc('id')->get();
            $storeSource = 'stores';
        }

        return view('store.registration-view', compact('stores', 'storeSource'));
    }

    public function store(Request $request)
    {
        if (!Schema::hasTable('store_registrations')) {
            return redirect()
                ->back()
                ->withInput()
                ->with('error', 'Store registration table is missing. Run migrations first.');
        }

        $validated = $request->validate([
            'store_name' => 'required|string|max:255',
            'owner_full_name' => 'required|string|max:255',
            'email' => 'nullable|email|max:255',
            'country_code' => 'nullable|string|max:10',
            'phone' => 'nullable|string|max:30',
            'store_type' => 'nullable|string|max:50',
            'city' => 'nullable|string|max:100',
            'subcity' => 'nullable|string|max:100',
            'address' => 'nullable|string|max:255',
            'store_description' => 'nullable|string|max:2000',
            'delivery_radius' => 'nullable|integer|min:0',
            'delivery_fee' => 'nullable|numeric|min:0',
            'delivery_methods' => 'nullable|array',
            'delivery_methods.*' => 'string',
            'open_time_monday' => 'nullable|string|max:5',
            'close_time_monday' => 'nullable|string|max:5',
            'open_time_tuesday' => 'nullable|string|max:5',
            'close_time_tuesday' => 'nullable|string|max:5',
            'open_time_wednesday' => 'nullable|string|max:5',
            'close_time_wednesday' => 'nullable|string|max:5',
            'open_time_thursday' => 'nullable|string|max:5',
            'close_time_thursday' => 'nullable|string|max:5',
            'open_time_friday' => 'nullable|string|max:5',
            'close_time_friday' => 'nullable|string|max:5',
            'open_time_saturday' => 'nullable|string|max:5',
            'close_time_saturday' => 'nullable|string|max:5',
            'open_time_sunday' => 'nullable|string|max:5',
            'close_time_sunday' => 'nullable|string|max:5',
            'rental_period' => 'nullable|integer|min:1|max:365',
            'rental_price' => 'nullable|numeric|min:0',
            'late_fee' => 'nullable|numeric|min:0',
            'security_deposit' => 'nullable|numeric|min:0',
            'max_books' => 'nullable|integer|min:1|max:1000',
            'discount_percent' => 'nullable|integer|min:0|max:100',
            'payment_methods' => 'nullable|array',
            'payment_methods.*' => 'string',
            'agree_terms' => 'accepted',
        ]);

        $deliveryMethods = $request->input('delivery_methods', []);
        if (!is_array($deliveryMethods)) {
            $deliveryMethods = [$deliveryMethods];
```

```
    }

    $paymentMethods = $request->input('payment_methods', []);
    if (!is_array($paymentMethods)) {
        $paymentMethods = [$paymentMethods];
    }

    $payload = array_merge($validated, [
        'offers_rental' => $request->boolean('offers_rental'),
        'offers_sale' => $request->boolean('offers_sale'),
        'offers_delivery' => $request->boolean('offers_delivery'),
        'delivery_methods' => $deliveryMethods ?: null,
        'delivery_bike' => in_array('bike', $deliveryMethods, true),
        'delivery_car' => in_array('car', $deliveryMethods, true),
        'delivery_pickup' => in_array('pickup', $deliveryMethods, true),
        'open_monday' => $request->boolean('open_monday'),
        'closed_monday' => $request->boolean('closed_monday'),
        'open_tuesday' => $request->boolean('open_tuesday'),
        'closed_tuesday' => $request->boolean('closed_tuesday'),
        'open_wednesday' => $request->boolean('open_wednesday'),
        'closed_wednesday' => $request->boolean('closed_wednesday'),
        'open_thursday' => $request->boolean('open_thursday'),
        'closed_thursday' => $request->boolean('closed_thursday'),
        'open_friday' => $request->boolean('open_friday'),
        'closed_friday' => $request->boolean('closed_friday'),
        'open_saturday' => $request->boolean('open_saturday'),
        'closed_saturday' => $request->boolean('closed_saturday'),
        'open_sunday' => $request->boolean('open_sunday'),
        'closed_sunday' => $request->boolean('closed_sunday'),
        'payment_methods' => $paymentMethods ?: null,
        'agree_terms' => $request->boolean('agree_terms'),
    ]);

    StoreRegistration::create($payload);

    return redirect()
        ->route('store.registration.view')
        ->with('status', 'Store registration submitted.');
}

public function update(Request $request)
{
    if (!Schema::hasTable('store_registrations')) {
        return redirect()
            ->back()
            ->withInput()
            ->with('error', 'Store registration table is missing. Run migrations first.');
    }

    $validated = $request->validate([
        'store_name' => 'required|string|max:255',
        'owner_full_name' => 'required|string|max:255',
        'email' => 'nullable|email|max:255',
        'country_code' => 'nullable|string|max:10',
        'phone' => 'nullable|string|max:30',
        'store_type' => 'nullable|string|max:50',
        'city' => 'nullable|string|max:100',
        'subcity' => 'nullable|string|max:100',
        'address' => 'nullable|string|max:255',
        'store_description' => 'nullable|string|max:2000',
        'delivery_radius' => 'nullable|integer|min:0',
        'delivery_fee' => 'nullable|numeric|min:0',
        'delivery_methods' => 'nullable|array',
        'delivery_methods.*' => 'string',
        'open_time_monday' => 'nullable|string|max:5',
        'close_time_monday' => 'nullable|string|max:5',
        'open_time_tuesday' => 'nullable|string|max:5',
        'close_time_tuesday' => 'nullable|string|max:5',
        'open_time_wednesday' => 'nullable|string|max:5',
        'close_time_wednesday' => 'nullable|string|max:5',
        'open_time_thursday' => 'nullable|string|max:5',
        'close_time_thursday' => 'nullable|string|max:5',
        'open_time_friday' => 'nullable|string|max:5',
        'close_time_friday' => 'nullable|string|max:5',
        'open_time_saturday' => 'nullable|string|max:5',
        'close_time_saturday' => 'nullable|string|max:5',
        'open_time_sunday' => 'nullable|string|max:5',
        'close_time_sunday' => 'nullable|string|max:5',
        'rental_period' => 'nullable|integer|min:1|max:365',
        'rental_price' => 'nullable|numeric|min:0',
        'late_fee' => 'nullable|numeric|min:0',
        'security_deposit' => 'nullable|numeric|min:0',
        'max_books' => 'nullable|integer|min:1|max:1000',
        'discount_percent' => 'nullable|integer|min:0|max:100',
        'payment_methods' => 'nullable|array',
        'payment_methods.*' => 'string',
        'agree_terms' => 'accepted',
    ]);

    $deliveryMethods = $request->input('delivery_methods', []);
    if (!is_array($deliveryMethods)) {
        $deliveryMethods = [$deliveryMethods];
    }

    $paymentMethods = $request->input('payment_methods', []);
    if (!is_array($paymentMethods)) {
        $paymentMethods = [$paymentMethods];
    }

    $payload = array_merge($validated, [
        'offers_rental' => $request->boolean('offers_rental'),
        'offers_sale' => $request->boolean('offers_sale'),
        'offers_delivery' => $request->boolean('offers_delivery'),
        'delivery_methods' => $deliveryMethods ?: null,
        'delivery_bike' => in_array('bike', $deliveryMethods, true),
        'delivery_car' => in_array('car', $deliveryMethods, true),
        'delivery_pickup' => in_array('pickup', $deliveryMethods, true),
        'open_monday' => $request->boolean('open_monday'),
        'closed_monday' => $request->boolean('closed_monday'),
        'open_tuesday' => $request->boolean('open_tuesday'),
        'closed_tuesday' => $request->boolean('closed_tuesday'),
        'open_wednesday' => $request->boolean('open_wednesday'),
        'closed_wednesday' => $request->boolean('closed_wednesday'),
        'open_thursday' => $request->boolean('open_thursday'),
        'closed_thursday' => $request->boolean('closed_thursday'),
        'open_friday' => $request->boolean('open_friday'),
        'closed_friday' => $request->boolean('closed_friday'),
        'open_saturday' => $request->boolean('open_saturday'),
        'closed_saturday' => $request->boolean('closed_saturday'),
        'open_sunday' => $request->boolean('open_sunday'),
        'closed_sunday' => $request->boolean('closed_sunday'),
        'payment_methods' => $paymentMethods ?: null,
        'agree_terms' => $request->boolean('agree_terms'),
    ]);

    $registration = null;
    if ($request->filled('store_id')) {
        $registration = StoreRegistration::find($request->input('store_id'));
```

```
        }

        if (!$registration && $request->filled('email')) {
            $registration = StoreRegistration::where('email', $request->input('email'))
                ->latest('id')
                ->first();
        }

        if (!$registration) {
            $registration = StoreRegistration::latest('id')->first();
        }

        if ($registration) {
            $registration->update($payload);
        } else {
            StoreRegistration::create($payload);
        }

        return redirect()
            ->route('store.registration.view')
            ->with('status', 'Store registration updated.');
    }

    public function destroy(Request $request, $storeId)
    {
        if (!Schema::hasTable('store_registrations')) {
            return redirect()
                ->route('store.registration.view')
                ->with('error', 'Store registration table is missing. Run migrations first.');
        }

        $store = StoreRegistration::find($storeId);

        if (!$store) {
            return redirect()
                ->route('store.registration.view')
                ->with('error', 'Store not found.');
        }

        $store->delete();

        return redirect()
            ->route('store.registration.view')
            ->with('status', 'Store deleted successfully.');
    }
}
```

### File: app\Http\Controllers\Auth\AuthenticatedSessionController.php

```
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use App\Http\Requests\Auth\LoginRequest;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\Route; // <-- Add this line
use Illuminate\Validation\ValidationException;
use Inertia\Inertia;
use Inertia\Response;

class AuthenticatedSessionController extends Controller
{
    /**
     * Display the login view.
     */
    public function create(): Response
    {
        return Inertia::render('Auth/Login', [
            'canResetPassword' => Route::has('password.request'),
            'status' => session('status'),
        ]);
    }

    /**
     * Handle an incoming authentication request.
     */
    public function store(LoginRequest $request): RedirectResponse
    {
        $request->authenticate();
        $request->session()->regenerate();

        $redirectTo = $this->redirectPathForAccountType($request->user()?->account_type);
        return redirect()->intended($redirectTo);
    }

    /**
     * Destroy an authenticated session.
     */
    public function destroy(Request $request): RedirectResponse
    {
        Auth::guard('web')->logout();
        $request->session()->invalidate();
        $request->session()->regenerateToken();

        return redirect('/');
    }

    private function redirectPathForAccountType(?string $accountType): string
    {
        if ($accountType === 'store_owner') {
            return route('store.dashboard', absolute: false);
        }

        if ($accountType === 'customer') {
            return route('customer.dashboard', absolute: false);
        }

        if (in_array($accountType, ['sub_admin', 'super_admin'], true)) {
            return route('admin.dashboard', absolute: false);
        }

        return route('dashboard', absolute: false);
    }
}
```

### File: app\Http\Controllers\Auth\ConfirmablePasswordController.php

```php
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Illuminate\Validation\ValidationException;
use Inertia\Inertia;
use Inertia\Response;

class ConfirmablePasswordController extends Controller
{
    /**
     * Show the confirm password view.
     */
    public function show(): Response
    {
        return Inertia::render('Auth/ConfirmPassword');
    }

    /**
     * Confirm the user's password.
     */
    public function store(Request $request): RedirectResponse
    {
        if (!Auth::guard('web')->validate([
            'email' => $request->user()->email,
            'password' => $request->password,
        ])) {
            throw ValidationException::withMessages([
                'password' => __('auth.password'),
            ]);
        }

        $request->session()->put('auth.password_confirmed_at', time());

        return redirect()->intended(route('dashboard', absolute: false));
    }
}
```

### File: app\Http\Controllers\Auth\EmailVerificationNotificationController.php

```php
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;

class EmailVerificationNotificationController extends Controller
{
    /**
     * Send a new email verification notification.
     */
    public function store(Request $request): RedirectResponse
    {
        if ($request->user()->hasVerifiedEmail()) {
            return redirect()->intended(route('dashboard', absolute: false));
        }

        $request->user()->sendEmailVerificationNotification();

        return back()->with('status', 'verification-link-sent');
    }
}
```

### File: app\Http\Controllers\Auth\EmailVerificationPromptController.php

```php
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Inertia\Inertia;
use Inertia\Response;

class EmailVerificationPromptController extends Controller
{
    /**
     * Display the email verification prompt.
     */
    public function __invoke(Request $request): RedirectResponse|Response
    {
        return $request->user()->hasVerifiedEmail()
            ? redirect()->intended(route('dashboard', absolute: false))
            : Inertia::render('Auth/VerifyEmail', ['status' => session('status')]);
    }
}
```

### File: app\Http\Controllers\Auth\NewPasswordController.php

```php
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Auth\Events\PasswordReset;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Hash;
use Illuminate\Support\Facades\Password;
use Illuminate\Support\Str;
use Illuminate\Validation\Rules;
use Illuminate\Validation\ValidationException;
use Inertia\Inertia;
use Inertia\Response;

class NewPasswordController extends Controller
{
    /**
     * Display the password reset view.
     */
    public function create(Request $request): Response
```

```
    {
        return Inertia::render('Auth/ResetPassword', [
            'email' => $request->email,
            'token' => $request->route('token'),
        ]);
    }

    /**
     * Handle an incoming new password request.
     *
     * @throws \Illuminate\Validation\ValidationException
     */
    public function store(Request $request): RedirectResponse
    {
        $request->validate([
            'token' => 'required',
            'email' => 'required|email',
            'password' => ['required', 'confirmed', Rules\Password::defaults()],
        ]);

        $status = Password::reset(
            $request->only('email', 'password', 'password_confirmation', 'token'),
            function ($user) use ($request) {
                $user->forceFill([
                    'password' => Hash::make($request->password),
                    'remember_token' => Str::random(60),
                ])->save();

                event(new PasswordReset($user));
            }
        );

        if ($status == Password::PASSWORD_RESET) {
            return redirect()->route('login')->with('status', __($status));
        }

        throw ValidationException::withMessages([
            'email' => [trans($status)],
        ]);
    }
}
```

### File: app\Http\Controllers\Auth\PasswordController.php

```
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Hash;
use Illuminate\Validation\Rules\Password;

class PasswordController extends Controller
{
    /**
     * Update the user's password.
     */
    public function update(Request $request): RedirectResponse
    {
        $validated = $request->validate([
            'current_password' => ['required', 'current_password'],
            'password' => ['required', Password::defaults(), 'confirmed'],
        ]);

        $request->user()->update([
            'password' => Hash::make($validated['password']),
        ]);

        return back();
    }
}
```

### File: app\Http\Controllers\Auth\PasswordResetLinkController.php

```
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Password;
use Illuminate\Support\Facades\Route; // Add this
use Illuminate\Validation\ValidationException;
use Inertia\Inertia;
use Inertia\Response;


class PasswordResetLinkController extends Controller
{
    /**
     * Display the password reset link request view.
     */
  public function create(): Response
    {
        return Inertia::render('Auth/ForgotPassword', [
            'status' => session('status'),
        ]);
    }

    /**
     * Handle an incoming password reset link request.
     *
     * @throws \Illuminate\Validation\ValidationException
     */
    public function store(Request $request): RedirectResponse
    {
        $request->validate([
            'email' => 'required|email',
        ]);

        $status = Password::sendResetLink(
            $request->only('email')
        );

        if ($status == Password::RESET_LINK_SENT) {
            return back()->with('status', __($status));
        }

        throw ValidationException::withMessages([
            'email' => [trans($status)],
```

```
        ]);
    }
}
```

### File: app\Http\Controllers\Auth\RegisteredUserController.php

```php
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use App\Models\User;
use Illuminate\Auth\Events\Registered;
use Illuminate\Http\RedirectResponse;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\Hash;
use Illuminate\Support\Facades\Route; // Add this if you use Route::has() or similar
use Illuminate\Validation\Rules;
use Inertia\Inertia;
use Inertia\Response;

class RegisteredUserController extends Controller
{
    /**
     * Display the registration view.
     */
    public function create(): Response
    {
        return Inertia::render('Auth/Register');
    }

    /**
     * Handle an incoming registration request.
     *
     * @throws \Illuminate\Validation\ValidationException
     */
    public function store(Request $request): RedirectResponse
    {
        $request->validate([
            'name' => 'required|string|max:255',
            'email' => 'required|string|lowercase|email|max:255|unique:' . User::class,
            'password' => ['required', 'confirmed', Rules\Password::defaults()],
            'account_type' => 'required|in:customer,store_owner',
        ]);

        $user = User::create([
            'name' => $request->name,
            'email' => $request->email,
            'password' => Hash::make($request->password),
            'account_type' => $request->account_type,
        ]);

        event(new Registered($user));
        Auth::login($user);

        $redirectTo = $this->redirectPathForAccountType($user->account_type);
        return redirect()->to($redirectTo);
    }

    private function redirectPathForAccountType(?string $accountType): string
    {
        if ($accountType === 'store_owner') {
            return route('store.dashboard', absolute: false);
        }

        if ($accountType === 'customer') {
            return route('customer.dashboard', absolute: false);
        }

        // FIXED: Redirect admins to admin dashboard
        if (in_array($accountType, ['sub_admin', 'super_admin'], true)) {
            return route('admin.dashboard', absolute: false);
        }

        return route('dashboard', absolute: false);
    }
}
```

### File: app\Http\Controllers\Auth\VerifyEmailController.php

```php
<?php

namespace App\Http\Controllers\Auth;

use App\Http\Controllers\Controller;
use Illuminate\Auth\Events\Verified;
use Illuminate\Foundation\Auth\EmailVerificationRequest;
use Illuminate\Http\RedirectResponse;

class VerifyEmailController extends Controller
{
    /**
     * Mark the authenticated user's email address as verified.
     */
    public function __invoke(EmailVerificationRequest $request): RedirectResponse
    {
        if ($request->user()->hasVerifiedEmail()) {
            return redirect()->intended(route('dashboard', absolute: false) . '?verified=1');
        }

        if ($request->user()->markEmailAsVerified()) {
            event(new Verified($request->user()));
        }

        return redirect()->intended(route('dashboard', absolute: false) . '?verified=1');
    }
}
```

### File: app\Http\Middleware\CheckUserActive.php

```php
<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Symfony\Component\HttpFoundation\Response;

class CheckUserActive
```

```
{
    public function handle(Request $request, Closure $next): Response
    {
        $user = Auth::user();

        if ($user) {
            if ($user->isBanned()) {
                Auth::logout();
                $request->session()->invalidate();
                $request->session()->regenerateToken();

                return redirect()->route('login')
                    ->withErrors(['email' => 'Your account has been banned. Reason: ' . ($user->ban_reason ?? 'Policy violation.')]);
            }

            if (!($user->is_active ?? true)) {
                Auth::logout();
                $request->session()->invalidate();
                $request->session()->regenerateToken();

                return redirect()->route('login')
                    ->withErrors(['email' => 'Your account has been deactivated. Please contact support.']);
            }
        }

        return $next($request);
    }
}
```

### *File: app\Http\Middleware\EnsureAccountType.php*

```
<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;
use Symfony\Component\HttpFoundation\Response;

class EnsureAccountType
{
    /**
     * Handle an incoming request.
     *
     * @param array<int, string> ...$types
     */
    public function handle(Request $request, Closure $next, ...$types): Response
    {
        $user = $request->user();

        if (!$user || empty($types)) {
            abort(403);
        }

        if (!in_array($user->account_type, $types, true)) {
            abort(403);
        }

        return $next($request);
    }
}
```

### File: app\Http\Middleware\HandleInertiaRequests.php

```php
<?php

namespace App\Http\Middleware;

use Illuminate\Http\Request;
use Inertia\Middleware;

class HandleInertiaRequests extends Middleware
{
    /**
     * The root template that is loaded on the first page visit.
     *
     * @var string
     */
    protected $rootView = 'app';

    /**
     * Determine the current asset version.
     */
    public function version(Request $request): ?string
    {
        return parent::version($request);
    }

    /**
     * Define the props that are shared by default.
     *
     * @return array<string, mixed>
     */
    public function share(Request $request): array
    {
        return [
            ...parent::share($request),
            'auth' => [
                'user' => $request->user(),
            ],
        ];
    }
}
```

### File: app\Http\Requests\ProfileUpdateRequest.php

```php
<?php

namespace App\Http\Requests;

use App\Models\User;
use Illuminate\Foundation\Http\FormRequest;
use Illuminate\Validation\Rule;

class ProfileUpdateRequest extends FormRequest
{
    /**
     * Get the validation rules that apply to the request.
     *
     * @return array<string, \Illuminate\Contracts\Validation\ValidationRule|array<mixed>|string>
     */
    public function rules(): array
    {
        return [
            'name' => ['required', 'string', 'max:255'],
            'email' => [
                'required',
                'string',
                'lowercase',
                'email',
                'max:255',
                Rule::unique(User::class)->ignore($this->user()->id),
            ],
        ];
    }
}
```

### File: app\Http\Requests\Auth\LoginRequest.php

```php
<?php

namespace App\Http\Requests\Auth;

use Illuminate\Auth\Events\Lockout;
use Illuminate\Foundation\Http\FormRequest;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\RateLimiter;
use Illuminate\Support\Str;
use Illuminate\Validation\ValidationException;

class LoginRequest extends FormRequest
{
    /**
     * Determine if the user is authorized to make this request.
     */
    public function authorize(): bool
    {
        return true;
    }

    /**
     * Get the validation rules that apply to the request.
     *
     * @return array<string, \Illuminate\Contracts\Validation\ValidationRule|array<mixed>|string>
     */
    public function rules(): array
    {
        return [
            'email' => ['required', 'string', 'email'],
            'password' => ['required', 'string'],
        ];
    }

    /**
     * Attempt to authenticate the request's credentials.
     *
     * @throws \Illuminate\Validation\ValidationException
     */
    public function authenticate(): void
    {
        $this->ensureIsNotRateLimited();

        if (! Auth::attempt($this->only('email', 'password'), $this->boolean('remember'))) {
            RateLimiter::hit($this->throttleKey());
```

```
            throw ValidationException::withMessages([
                'email' => trans('auth.failed'),
            ]);
        }

        RateLimiter::clear($this->throttleKey());
    }

    /**
     * Ensure the login request is not rate limited.
     *
     * @throws \Illuminate\Validation\ValidationException
     */
    public function ensureIsNotRateLimited(): void
    {
        if (! RateLimiter::tooManyAttempts($this->throttleKey(), 5)) {
            return;
        }

        event(new Lockout($this));

        $seconds = RateLimiter::availableIn($this->throttleKey());

        throw ValidationException::withMessages([
            'email' => trans('auth.throttle', [
                'seconds' => $seconds,
                'minutes' => ceil($seconds / 60),
            ]),
        ]);
    }

    /**
     * Get the rate limiting throttle key for the request.
     */
    public function throttleKey(): string
    {
        return Str::transliterate(Str::lower($this->string('email')).'|'.$this->ip());
    }
}
```

### File: app\Models\Book.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Book extends Model
{
    use HasFactory;

    protected $fillable = [
        'user_id',
        'title',
        'author',
        'genre',
        'publication_year',
        'total_copies',
        'available_rent',
        'available_sale',
        'rental_price',
        'sale_price',
        'cover_image_path',
    ];

    protected $casts = [
        'publication_year' => 'integer',
        'total_copies' => 'integer',
        'available_rent' => 'integer',
        'available_sale' => 'integer',
        'rental_price' => 'decimal:2',
        'sale_price' => 'decimal:2',
    ];

    public function user()
    {
        return $this->belongsTo(User::class, 'user_id');
    }
}
```

### File: app\Models\ChatConversation.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class ChatConversation extends Model
{
    use HasFactory;

    protected $fillable = [
        'customer_id',
        'store_id',
        'book_id',
        'subject',
        'status',
        'last_message_at',
        'last_message',
        'last_message_sender_id',
    ];

    protected $casts = [
        'last_message_at' => 'datetime',
    ];

    // Relationships
    public function customer()
    {
        return $this->belongsTo(User::class, 'customer_id');
    }

    public function store()
    {
        return $this->belongsTo(User::class, 'store_id');
    }

    public function book()
    {
```

```
        return $this->belongsTo(Book::class, 'book_id');
    }

    public function messages()
    {
        return $this->hasMany(ChatMessage::class, 'conversation_id')->orderBy('created_at', 'asc');
    }

    public function latestMessage()
    {
        return $this->hasOne(ChatMessage::class, 'conversation_id')->latestOfMany();
    }

    public function lastMessageSender()
    {
        return $this->belongsTo(User::class, 'last_message_sender_id');
    }

    // Scopes
    public function scopeForCustomer($query, $customerId)
    {
        return $query->where('customer_id', $customerId);
    }

    public function scopeForStore($query, $storeId)
    {
        return $query->where('store_id', $storeId);
    }

    public function scopeActive($query)
    {
        return $query->where('status', 'active');
    }

    // Methods
    public function markAsRead($userId)
    {
        return $this->messages()
            ->where('sender_id', '!=', $userId)
            ->where('is_read', false)
            ->update([
                'is_read' => true,
                'is_read_at' => now()
            ]);
    }

    public function getUnreadCountForUser($userId)
    {
        return $this->messages()
            ->where('sender_id', '!=', $userId)
            ->where('is_read', false)
            ->count();
    }

    public function getOtherParticipant($userId)
    {
        return $this->customer_id === $userId ? $this->store : $this->customer;
    }
}
```

### File: app\Models\ChatMessage.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class ChatMessage extends Model
{
    use HasFactory;

    protected $fillable = [
        'conversation_id',
        'sender_id',
        'sender_role',
        'message',
        'is_read',
        'is_read_at',
        'attachment_path',
        'attachment_name',
        'attachment_size',
        'attachment_type',
    ];

    protected $casts = [
        'is_read' => 'boolean',
        'is_read_at' => 'datetime',
    ];

    // Relationships
    public function conversation()
    {
        return $this->belongsTo(ChatConversation::class, 'conversation_id');
    }

    public function sender()
    {
        return $this->belongsTo(User::class, 'sender_id');
    }

    // Scopes
    public function scopeUnread($query)
    {
        return $query->where('is_read', false);
    }

    public function scopeForUser($query, $userId)
    {
        return $query->where('sender_id', '!=', $userId);
    }

    // Methods
    public function markAsRead()
    {
        if (!$this->is_read) {
            $this->update([
                'is_read' => true,
                'is_read_at' => now()
            ]);
        }
    }

    public function hasAttachment()
```

```
    {
        return !is_null($this->attachment_path);
    }

    public function getAttachmentUrlAttribute()
    {
        return $this->attachment_path ? asset('storage/' . $this->attachment_path) : null;
    }

    public function isImage()
    {
        return $this->attachment_type && str_starts_with($this->attachment_type, 'image/');
    }
}
```

### File: app\Models\IssueReport.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class IssueReport extends Model
{
    use HasFactory;

    protected $fillable = [
        'user_id',
        'reported_user_id',
        'reporter_role',
        'subject',
        'description',
        'priority',
        'status',
        'assigned_admin_id',
        'evidence_path',
        'evidence_name',
        'evidence_type',
        'admin_notes',
    ];

    protected $casts = [
        'created_at' => 'datetime',
        'updated_at' => 'datetime',
    ];

    // The user who filed the report
    public function user()
    {
        return $this->belongsTo(User::class, 'user_id');
    }

    // The user being reported
    public function reportedUser()
    {
        return $this->belongsTo(User::class, 'reported_user_id');
    }

    public function assignedAdmin()
    {
        return $this->belongsTo(User::class, 'assigned_admin_id');
    }

    public function hasEvidence(): bool
    {
        return !is_null($this->evidence_path);
    }

    public function getEvidenceUrlAttribute(): ?string
    {
        return $this->evidence_path ? asset('storage/' . $this->evidence_path) : null;
    }

    public function isEvidenceImage(): bool
    {
        return $this->evidence_type && str_starts_with($this->evidence_type, 'image/');
    }
}
```

### File: app\Models\StoreRegistration.php

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Model;

class StoreRegistration extends Model
{
    protected $guarded = [];

    protected $casts = [
        'offers_rental' => 'boolean',
        'offers_sale' => 'boolean',
        'offers_delivery' => 'boolean',
        'delivery_methods' => 'array',
        'delivery_bike' => 'boolean',
        'delivery_car' => 'boolean',
        'delivery_pickup' => 'boolean',
        'open_monday' => 'boolean',
        'closed_monday' => 'boolean',
        'open_tuesday' => 'boolean',
        'closed_tuesday' => 'boolean',
        'open_wednesday' => 'boolean',
        'closed_wednesday' => 'boolean',
        'open_thursday' => 'boolean',
        'closed_thursday' => 'boolean',
        'open_friday' => 'boolean',
        'closed_friday' => 'boolean',
        'open_saturday' => 'boolean',
        'closed_saturday' => 'boolean',
        'open_sunday' => 'boolean',
        'closed_sunday' => 'boolean',
        'payment_methods' => 'array',
        'agree_terms' => 'boolean',
    ];
}
```

## File: app\Models\User.php

```php
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Foundation\Auth\User as Authenticatable;
use Illuminate\Notifications\Notifiable;

class User extends Authenticatable
{
    use HasFactory, Notifiable;

    protected $fillable = [
        'name',
        'email',
        'password',
        'account_type',
        'avatar',
        'phone',
        'bio',
        'last_seen_at',
        'is_active',
        'is_banned',
        'ban_reason',
        'banned_at',
        'warning_count',
        'is_restricted',
        'restricted_until',
    ];

    protected $hidden = [
        'password',
        'remember_token',
    ];

    protected $casts = [
        'email_verified_at' => 'datetime',
        'password' => 'hashed',
        'last_seen_at' => 'datetime',
        'is_active' => 'boolean',
        'is_banned' => 'boolean',
        'is_restricted' => 'boolean',
        'banned_at' => 'datetime',
        'restricted_until' => 'datetime',
    ];

    // Add this relationship - Books owned by the user (for store owners)
    public function books()
    {
        return $this->hasMany(Book::class, 'user_id');
    }

    // Chat Relationships
    public function customerConversations()
    {
        return $this->hasMany(ChatConversation::class, 'customer_id');
    }

    public function storeConversations()
    {
        return $this->hasMany(ChatConversation::class, 'store_id');
    }

    public function sentMessages()
    {
        return $this->hasMany(ChatMessage::class, 'sender_id');
    }

    public function receivedMessages()
    {
        return $this->hasManyThrough(
            ChatMessage::class,
            ChatConversation::class,
            'store_id', // Foreign key on conversations table...
            'conversation_id', // Foreign key on messages table...
            'id', // Local key on users table...
            'id' // Local key on conversations table...
        );
    }

    // Helper methods
    public function isOnline()
    {
        return $this->last_seen_at && $this->last_seen_at->gt(now()->subMinutes(5));
    }

    public function canLogin(): bool
    {
        return ($this->is_active ?? true) && !($this->is_banned ?? false);
    }

    public function isBanned(): bool
    {
        return (bool) ($this->is_banned ?? false);
    }

    public function isRestricted(): bool
    {
        if (!($this->is_restricted ?? false)) return false;
        if ($this->restricted_until && $this->restricted_until->isPast()) {
            $this->update(['is_restricted' => false, 'restricted_until' => null]);
            return false;
        }
        return true;
    }

    public function statusBadge(): string
    {
        if ($this->isBanned()) return 'Banned';
        if (!($this->is_active ?? true)) return 'Inactive';
        if ($this->isRestricted()) return 'Restricted';
        return 'Active';
    }

    public function unreadMessagesCount()
    {
        return ChatMessage::whereHas('conversation', function ($query) {
            if ($this->account_type === 'store_owner') {
                $query->where('store_id', $this->id);
            } else {
                $query->where('customer_id', $this->id);
            }
        })->where('sender_id', '!=', $this->id)
          ->where('is_read', false)
          ->count();
```

```
    }
}
```

### File: app\Providers\AppServiceProvider.php

```
<?php

namespace App\Providers;

use Illuminate\Support\Facades\Vite;
use Illuminate\Support\ServiceProvider;

class AppServiceProvider extends ServiceProvider
{
    /**
     * Register any application services.
     */
    public function register(): void
    {
        //
    }

    /**
     * Bootstrap any application services.
     */
    public function boot(): void
    {
        Vite::prefetch(concurrency: 3);
    }
}
```

### File: bootstrap\app.php

```php
<?php

use Illuminate\Foundation\Application;
use Illuminate\Foundation\Configuration\Exceptions;
use Illuminate\Foundation\Configuration\Middleware;

return Application::configure(basePath: dirname(__DIR__))
    ->withRouting(
        web: __DIR__.'/../routes/web.php',
        commands: __DIR__.'/../routes/console.php',
        health: '/up',
    )
    ->withMiddleware(function (Middleware $middleware): void {
        $middleware->web(append: [
            \App\Http\Middleware\HandleInertiaRequests::class,
            \Illuminate\Http\Middleware\AddLinkHeadersForPreloadedAssets::class,
            \App\Http\Middleware\CheckUserActive::class,
        ]);

        $middleware->alias([
            'account_type' => \App\Http\Middleware\EnsureAccountType::class,
            'check.active' => \App\Http\Middleware\CheckUserActive::class,
        ]);
    })
    ->withExceptions(function (Exceptions $exceptions): void {
        //
    })->create();
```

### File: bootstrap\providers.php

```php
<?php

return [
    App\Providers\AppServiceProvider::class,
];
```

### File: bootstrap\cache\packages.php

```php
<?php return array (
  'inertiajs/inertia-laravel' =>
  array (
    'providers' =>
    array (
      0 => 'Inertia\\ServiceProvider',
    ),
  ),
  'laravel/breeze' =>
  array (
    'providers' =>
    array (
      0 => 'Laravel\\Breeze\\BreezeServiceProvider',
    ),
  ),
  'laravel/pail' =>
  array (
    'providers' =>
    array (
      0 => 'Laravel\\Pail\\PailServiceProvider',
    ),
  ),
  'laravel/sail' =>
  array (
    'providers' =>
    array (
      0 => 'Laravel\\Sail\\SailServiceProvider',
    ),
  ),
  'laravel/sanctum' =>
  array (
    'providers' =>
    array (
      0 => 'Laravel\\Sanctum\\SanctumServiceProvider',
    ),
  ),
  'laravel/tinker' =>
  array (
    'providers' =>
    array (
      0 => 'Laravel\\Tinker\\TinkerServiceProvider',
    ),
  ),
  'nesbot/carbon' =>
  array (
    'providers' =>
    array (
      0 => 'Carbon\\Laravel\\ServiceProvider',
    ),
  ),
  'nunomaduro/collision' =>
  array (
    'providers' =>
    array (
      0 => 'NunoMaduro\\Collision\\Adapters\\Laravel\\CollisionServiceProvider',
    ),
  ),
  'nunomaduro/termwind' =>
  array (
    'providers' =>
    array (
      0 => 'Termwind\\Laravel\\TermwindServiceProvider',
    ),
  ),
  'tightenco/ziggy' =>
  array (
    'providers' =>
    array (
      0 => 'Tighten\\Ziggy\\ZiggyServiceProvider',
    ),
  ),
);
```

### File: bootstrap\cache\services.php

```php
<?php return array (
  'providers' =>
  array (
    0 => 'Illuminate\\Auth\\AuthServiceProvider',
    1 => 'Illuminate\\Broadcasting\\BroadcastServiceProvider',
```

```
  2 => 'Illuminate\\Bus\\BusServiceProvider',
  3 => 'Illuminate\\Cache\\CacheServiceProvider',
  4 => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  5 => 'Illuminate\\Concurrency\\ConcurrencyServiceProvider',
  6 => 'Illuminate\\Cookie\\CookieServiceProvider',
  7 => 'Illuminate\\Database\\DatabaseServiceProvider',
  8 => 'Illuminate\\Encryption\\EncryptionServiceProvider',
  9 => 'Illuminate\\Filesystem\\FilesystemServiceProvider',
  10 => 'Illuminate\\Foundation\\Providers\\FoundationServiceProvider',
  11 => 'Illuminate\\Hashing\\HashServiceProvider',
  12 => 'Illuminate\\Mail\\MailServiceProvider',
  13 => 'Illuminate\\Notifications\\NotificationServiceProvider',
  14 => 'Illuminate\\Pagination\\PaginationServiceProvider',
  15 => 'Illuminate\\Auth\\Passwords\\PasswordResetServiceProvider',
  16 => 'Illuminate\\Pipeline\\PipelineServiceProvider',
  17 => 'Illuminate\\Queue\\QueueServiceProvider',
  18 => 'Illuminate\\Redis\\RedisServiceProvider',
  19 => 'Illuminate\\Session\\SessionServiceProvider',
  20 => 'Illuminate\\Translation\\TranslationServiceProvider',
  21 => 'Illuminate\\Validation\\ValidationServiceProvider',
  22 => 'Illuminate\\View\\ViewServiceProvider',
  23 => 'Inertia\\ServiceProvider',
  24 => 'Laravel\\Breeze\\BreezeServiceProvider',
  25 => 'Laravel\\Pail\\PailServiceProvider',
  26 => 'Laravel\\Sail\\SailServiceProvider',
  27 => 'Laravel\\Sanctum\\SanctumServiceProvider',
  28 => 'Laravel\\Tinker\\TinkerServiceProvider',
  29 => 'Carbon\\Laravel\\ServiceProvider',
  30 => 'NunoMaduro\\Collision\\Adapters\\Laravel\\CollisionServiceProvider',
  31 => 'Termwind\\Laravel\\TermwindServiceProvider',
  32 => 'Tighten\\Ziggy\\ZiggyServiceProvider',
  33 => 'App\\Providers\\AppServiceProvider',
),
'eager' =>
array (
  0 => 'Illuminate\\Auth\\AuthServiceProvider',
  1 => 'Illuminate\\Cookie\\CookieServiceProvider',
  2 => 'Illuminate\\Database\\DatabaseServiceProvider',
  3 => 'Illuminate\\Encryption\\EncryptionServiceProvider',
  4 => 'Illuminate\\Filesystem\\FilesystemServiceProvider',
  5 => 'Illuminate\\Foundation\\Providers\\FoundationServiceProvider',
  6 => 'Illuminate\\Notifications\\NotificationServiceProvider',
  7 => 'Illuminate\\Pagination\\PaginationServiceProvider',
  8 => 'Illuminate\\Session\\SessionServiceProvider',
  9 => 'Illuminate\\View\\ViewServiceProvider',
  10 => 'Inertia\\ServiceProvider',
  11 => 'Laravel\\Pail\\PailServiceProvider',
  12 => 'Laravel\\Sanctum\\SanctumServiceProvider',
  13 => 'Carbon\\Laravel\\ServiceProvider',
  14 => 'NunoMaduro\\Collision\\Adapters\\Laravel\\CollisionServiceProvider',
  15 => 'Termwind\\Laravel\\TermwindServiceProvider',
  16 => 'Tighten\\Ziggy\\ZiggyServiceProvider',
  17 => 'App\\Providers\\AppServiceProvider',
),
'deferred' =>
array (
  'Illuminate\\Broadcasting\\BroadcastManager' => 'Illuminate\\Broadcasting\\BroadcastServiceProvider',
  'Illuminate\\Contracts\\Broadcasting\\Factory' => 'Illuminate\\Broadcasting\\BroadcastServiceProvider',
  'Illuminate\\Contracts\\Broadcasting\\Broadcaster' => 'Illuminate\\Broadcasting\\BroadcastServiceProvider',
  'Illuminate\\Bus\\Dispatcher' => 'Illuminate\\Bus\\BusServiceProvider',
  'Illuminate\\Contracts\\Bus\\Dispatcher' => 'Illuminate\\Bus\\BusServiceProvider',
  'Illuminate\\Contracts\\Bus\\QueueingDispatcher' => 'Illuminate\\Bus\\BusServiceProvider',
  'Illuminate\\Bus\\BatchRepository' => 'Illuminate\\Bus\\BusServiceProvider',
  'Illuminate\\Bus\\DatabaseBatchRepository' => 'Illuminate\\Bus\\BusServiceProvider',
  'cache' => 'Illuminate\\Cache\\CacheServiceProvider',
  'cache.store' => 'Illuminate\\Cache\\CacheServiceProvider',
  'cache.psr6' => 'Illuminate\\Cache\\CacheServiceProvider',
  'memcached.connector' => 'Illuminate\\Cache\\CacheServiceProvider',
  'Illuminate\\Cache\\RateLimiter' => 'Illuminate\\Cache\\CacheServiceProvider',
  'Illuminate\\Foundation\\Console\\AboutCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Cache\\Console\\ClearCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Cache\\Console\\ForgetCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\ClearCompiledCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Auth\\Console\\ClearResetsCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\ConfigCacheCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\ConfigClearCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\ConfigShowCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Database\\Console\\DbCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Database\\Console\\MonitorCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Database\\Console\\PruneCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Database\\Console\\ShowCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Database\\Console\\TableCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Database\\Console\\WipeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\DownCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\EnvironmentCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\EnvironmentDecryptCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\EnvironmentEncryptCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\EventCacheCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\EventClearCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\EventListCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Concurrency\\Console\\InvokeSerializedClosureCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\KeyGenerateCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\OptimizeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\OptimizeClearCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\PackageDiscoverCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Cache\\Console\\PruneStaleTagsCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Queue\\Console\\ClearCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Queue\\Console\\ListFailedCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Queue\\Console\\FlushFailedCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Queue\\Console\\ForgetFailedCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Queue\\Console\\ListenCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Queue\\Console\\MonitorCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Queue\\Console\\PauseCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Queue\\Console\\PruneBatchesCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Queue\\Console\\PruneFailedJobsCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Queue\\Console\\RestartCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Queue\\Console\\ResumeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Queue\\Console\\RetryCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Queue\\Console\\RetryBatchCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Queue\\Console\\WorkCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\ReloadCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\RouteCacheCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\RouteClearCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\RouteListCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Database\\Console\\DumpCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Database\\Console\\Seeds\\SeedCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Console\\Scheduling\\ScheduleFinishCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Console\\Scheduling\\ScheduleListCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Console\\Scheduling\\ScheduleRunCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Console\\Scheduling\\ScheduleClearCacheCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Console\\Scheduling\\ScheduleTestCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Console\\Scheduling\\ScheduleWorkCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Console\\Scheduling\\ScheduleInterruptCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Database\\Console\\ShowModelCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\StorageLinkCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\StorageUnlinkCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\UpCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
  'Illuminate\\Foundation\\Console\\ViewCacheCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
```

```
        'Illuminate\\Foundation\\Console\\ViewClearCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\ApiInstallCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\BroadcastingInstallCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Cache\\Console\\CacheTableCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\CastMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\ChannelListCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\ChannelMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\ClassMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\ComponentMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\ConfigMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\ConfigPublishCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\ConsoleMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Routing\\Console\\ControllerMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\DocsCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\EnumMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\EventGenerateCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\EventMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\ExceptionMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Database\\Console\\Factories\\FactoryMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\InterfaceMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\JobMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\JobMiddlewareMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\LangPublishCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\ListenerMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\MailMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Routing\\Console\\MiddlewareMakeCommand' => 'Illuminate\\Foundation\\Providers\\ConsoleSupportServiceProvider',
        'Illuminate\\Foundation\\Console\\ModelMakeCommand' => 'Il
```

(Content truncated due to size - showing first 15KB)

## File: config\app.php

```
<?php

return [

    /*
    |--------------------------------------------------------------------------
    | Application Name
    |--------------------------------------------------------------------------
    |
    | This value is the name of your application, which will be used when the
    | framework needs to place the application's name in a notification or
    | other UI elements where an application name needs to be displayed.
    |
    */

    'name' => env('APP_NAME', 'Laravel'),

    /*
    |--------------------------------------------------------------------------
    | Application Environment
    |--------------------------------------------------------------------------
    |
    | This value determines the "environment" your application is currently
    | running in. This may determine how you prefer to configure various
    | services the application utilizes. Set this in your ".env" file.
    |
    */

    'env' => env('APP_ENV', 'production'),

    /*
    |--------------------------------------------------------------------------
    | Application Debug Mode
    |--------------------------------------------------------------------------
    |
    | When your application is in debug mode, detailed error messages with
    | stack traces will be shown on every error that occurs within your
    | application. If disabled, a simple generic error page is shown.
    |
    */

    'debug' => (bool) env('APP_DEBUG', false),

    /*
    |--------------------------------------------------------------------------
    | Application URL
    |--------------------------------------------------------------------------
    |
    | This URL is used by the console to properly generate URLs when using
    | the Artisan command line tool. You should set this to the root of
    | the application so that it's available within Artisan commands.
    |
    */

    'url' => env('APP_URL', 'http://localhost'),

    /*
    |--------------------------------------------------------------------------
    | Application Timezone
    |--------------------------------------------------------------------------
    |
    | Here you may specify the default timezone for your application, which
    | will be used by the PHP date and date-time functions. The timezone
    | is set to "UTC" by default as it is suitable for most use cases.
    |
    */

    'timezone' => 'UTC',

    /*
    |--------------------------------------------------------------------------
    | Application Locale Configuration
    |--------------------------------------------------------------------------
    |
    | The application locale determines the default locale that will be used
    | by Laravel's translation / localization methods. This option can be
    | set to any locale for which you plan to have translation strings.
    |
    */

    'locale' => env('APP_LOCALE', 'en'),

    'fallback_locale' => env('APP_FALLBACK_LOCALE', 'en'),

    'faker_locale' => env('APP_FAKER_LOCALE', 'en_US'),

    /*
    |--------------------------------------------------------------------------
    | Encryption Key
    |--------------------------------------------------------------------------
    |
    | This key is utilized by Laravel's encryption services and should be set
    | to a random, 32 character string to ensure that all encrypted values
```

```
    | are secure. You should do this prior to deploying the application.
    |
    */

    'cipher' => 'AES-256-CBC',

    'key' => env('APP_KEY'),

    'previous_keys' => [
        ...array_filter(
            explode(',', (string) env('APP_PREVIOUS_KEYS', ''))
        ),
    ],

    /*
    |--------------------------------------------------------------------------
    | Maintenance Mode Driver
    |--------------------------------------------------------------------------
    |
    | These configuration options determine the driver used to determine and
    | manage Laravel's "maintenance mode" status. The "cache" driver will
    | allow maintenance mode to be controlled across multiple machines.
    |
    | Supported drivers: "file", "cache"
    |
    */

    'maintenance' => [
        'driver' => env('APP_MAINTENANCE_DRIVER', 'file'),
        'store' => env('APP_MAINTENANCE_STORE', 'database'),
    ],

];
```

### *File: config\auth.php*

```
<?php

return [

    /*
    |--------------------------------------------------------------------------
    | Authentication Defaults
    |--------------------------------------------------------------------------
    |
    | This option defines the default authentication "guard" and password
    | reset "broker" for your application. You may change these values
    | as required, but they're a perfect start for most applications.
    |
    */

    'defaults' => [
        'guard' => env('AUTH_GUARD', 'web'),
        'passwords' => env('AUTH_PASSWORD_BROKER', 'users'),
    ],

    /*
    |--------------------------------------------------------------------------
    | Authentication Guards
    |--------------------------------------------------------------------------
    |
    | Next, you may define every authentication guard for your application.
    | Of course, a great default configuration has been defined for you
    | which utilizes session storage plus the Eloquent user provider.
    |
    | All authentication guards have a user provider, which defines how the
    | users are actually retrieved out of your database or other storage
    | system used by the application. Typically, Eloquent is utilized.
    |
    | Supported: "session"
    |
    */

    'guards' => [
        'web' => [
            'driver' => 'session',
            'provider' => 'users',
        ],
    ],

    /*
    |--------------------------------------------------------------------------
    | User Providers
    |--------------------------------------------------------------------------
    |
    | All authentication guards have a user provider, which defines how the
    | users are actually retrieved out of your database or other storage
    | system used by the application. Typically, Eloquent is utilized.
    |
    | If you have multiple user tables or models you may configure multiple
    | providers to represent the model / table. These providers may then
    | be assigned to any extra authentication guards you have defined.
    |
    | Supported: "database", "eloquent"
    |
    */

    'providers' => [
        'users' => [
            'driver' => 'eloquent',
            'model' => env('AUTH_MODEL', App\Models\User::class),
        ],

        // 'users' => [
        //     'driver' => 'database',
        //     'table' => 'users',
        // ],
    ],

    /*
    |--------------------------------------------------------------------------
    | Resetting Passwords
    |--------------------------------------------------------------------------
    |
    | These configuration options specify the behavior of Laravel's password
    | reset functionality, including the table utilized for token storage
    | and the user provider that is invoked to actually retrieve users.
    |
    | The expiry time is the number of minutes that each reset token will be
    | considered valid. This security feature keeps tokens short-lived so
    | they have less time to be guessed. You may change this as needed.
    |
    | The throttle setting is the number of seconds a user must wait before
    | generating more password reset tokens. This prevents the user from
    | quickly generating a very large amount of password reset tokens.
```

```
    |
    */

    'passwords' => [
        'users' => [
            'provider' => 'users',
            'table' => env('AUTH_PASSWORD_RESET_TOKEN_TABLE', 'password_reset_tokens'),
            'expire' => 60,
            'throttle' => 60,
        ],
    ],

    /*
    |--------------------------------------------------------------------------
    | Password Confirmation Timeout
    |--------------------------------------------------------------------------
    |
    | Here you may define the number of seconds before a password confirmation
    | window expires and users are asked to re-enter their password via the
    | confirmation screen. By default, the timeout lasts for three hours.
    |
    */

    'password_timeout' => env('AUTH_PASSWORD_TIMEOUT', 10800),

];
```

## File: config\cache.php

```
<?php

use Illuminate\Support\Str;

return [

    /*
    |--------------------------------------------------------------------------
    | Default Cache Store
    |--------------------------------------------------------------------------
    |
    | This option controls the default cache store that will be used by the
    | framework. This connection is utilized if another isn't explicitly
    | specified when running a cache operation inside the application.
    |
    */

    'default' => env('CACHE_STORE', 'database'),

    /*
    |--------------------------------------------------------------------------
    | Cache Stores
    |--------------------------------------------------------------------------
    |
    | Here you may define all of the cache "stores" for your application as
    | well as their drivers. You may even define multiple stores for the
    | same cache driver to group types of items stored in your caches.
    |
    | Supported drivers: "array", "database", "file", "memcached",
    |                    "redis", "dynamodb", "octane",
    |                    "failover", "null"
    |
    */

    'stores' => [

        'array' => [
            'driver' => 'array',
            'serialize' => false,
        ],

        'database' => [
            'driver' => 'database',
            'connection' => env('DB_CACHE_CONNECTION'),
            'table' => env('DB_CACHE_TABLE', 'cache'),
            'lock_connection' => env('DB_CACHE_LOCK_CONNECTION'),
            'lock_table' => env('DB_CACHE_LOCK_TABLE'),
        ],

        'file' => [
            'driver' => 'file',
            'path' => storage_path('framework/cache/data'),
            'lock_path' => storage_path('framework/cache/data'),
        ],

        'memcached' => [
            'driver' => 'memcached',
            'persistent_id' => env('MEMCACHED_PERSISTENT_ID'),
            'sasl' => [
                env('MEMCACHED_USERNAME'),
                env('MEMCACHED_PASSWORD'),
            ],
            'options' => [
                // Memcached::OPT_CONNECT_TIMEOUT => 2000,
            ],
            'servers' => [
                [
                    'host' => env('MEMCACHED_HOST', '127.0.0.1'),
                    'port' => env('MEMCACHED_PORT', 11211),
                    'weight' => 100,
                ],
            ],
        ],

        'redis' => [
            'driver' => 'redis',
            'connection' => env('REDIS_CACHE_CONNECTION', 'cache'),
            'lock_connection' => env('REDIS_CACHE_LOCK_CONNECTION', 'default'),
        ],

        'dynamodb' => [
            'driver' => 'dynamodb',
            'key' => env('AWS_ACCESS_KEY_ID'),
            'secret' => env('AWS_SECRET_ACCESS_KEY'),
            'region' => env('AWS_DEFAULT_REGION', 'us-east-1'),
            'table' => env('DYNAMODB_CACHE_TABLE', 'cache'),
            'endpoint' => env('DYNAMODB_ENDPOINT'),
        ],

        'octane' => [
            'driver' => 'octane',
        ],

        'failover' => [
            'driver' => 'failover',
            'stores' => [
```

```
                'database',
                'array',
            ],
        ],

    ],

    /*
    |---------------------------------------------------------------------------
    | Cache Key Prefix
    |---------------------------------------------------------------------------
    |
    | When utilizing the APC, database, memcached, Redis, and DynamoDB cache
    | stores, there might be other applications using the same cache. For
    | that reason, you may prefix every cache key to avoid collisions.
    |
    */

    'prefix' => env('CACHE_PREFIX', Str::slug((string) env('APP_NAME', 'laravel')).'-cache-'),

];
```

### File: config\database.php

```
<?php

use Illuminate\Support\Str;

return [

    /*
    |---------------------------------------------------------------------------
    | Default Database Connection Name
    |---------------------------------------------------------------------------
    |
    | Here you may specify which of the database connections below you wish
    | to use as your default connection for database operations. This is
    | the connection which will be utilized unless another connection
    | is explicitly specified when you execute a query / statement.
    |
    */

    'default' => env('DB_CONNECTION', 'sqlite'),

    /*
    |---------------------------------------------------------------------------
    | Database Connections
    |---------------------------------------------------------------------------
    |
    | Below are all of the database connections defined for your application.
    | An example configuration is provided for each database system which
    | is supported by Laravel. You're free to add / remove connections.
    |
    */

    'connections' => [

        'sqlite' => [
            'driver' => 'sqlite',
            'url' => env('DB_URL'),
            'database' => env('DB_DATABASE', database_path('database.sqlite')),
            'prefix' => '',
            'foreign_key_constraints' => env('DB_FOREIGN_KEYS', true),
            'busy_timeout' => null,
            'journal_mode' => null,
            'synchronous' => null,
            'transaction_mode' => 'DEFERRED',
        ],

        'mysql' => [
            'driver' => 'mysql',
            'url' => env('DB_URL'),
            'host' => env('DB_HOST', '127.0.0.1'),
            'port' => env('DB_PORT', '3306'),
            'database' => env('DB_DATABASE', 'laravel'),
            'username' => env('DB_USERNAME', 'root'),
            'password' => env('DB_PASSWORD', ''),
            'unix_socket' => env('DB_SOCKET', ''),
            'charset' => env('DB_CHARSET', 'utf8mb4'),
            'collation' => env('DB_COLLATION', 'utf8mb4_unicode_ci'),
            'prefix' => '',
            'prefix_indexes' => true,
            'strict' => true,
            'engine' => null,
            'options' => extension_loaded('pdo_mysql') ? array_filter([
                (PHP_VERSION_ID >= 80500 ? \Pdo\Mysql::ATTR_SSL_CA : \PDO::MYSQL_ATTR_SSL_CA) => env('MYSQL_ATTR_SSL_CA'),
            ]) : [],
        ],

        'mariadb' => [
            'driver' => 'mariadb',
            'url' => env('DB_URL'),
            'host' => env('DB_HOST', '127.0.0.1'),
            'port' => env('DB_PORT', '3306'),
            'database' => env('DB_DATABASE', 'laravel'),
            'username' => env('DB_USERNAME', 'root'),
            'password' => env('DB_PASSWORD', ''),
            'unix_socket' => env('DB_SOCKET', ''),
            'charset' => env('DB_CHARSET', 'utf8mb4'),
            'collation' => env('DB_COLLATION', 'utf8mb4_unicode_ci'),
            'prefix' => '',
            'prefix_indexes' => true,
            'strict' => true,
            'engine' => null,
            'options' => extension_loaded('pdo_mysql') ? array_filter([
                (PHP_VERSION_ID >= 80500 ? \Pdo\Mysql::ATTR_SSL_CA : \PDO::MYSQL_ATTR_SSL_CA) => env('MYSQL_ATTR_SSL_CA'),
            ]) : [],
        ],

        'pgsql' => [
            'driver' => 'pgsql',
            'url' => env('DB_URL'),
            'host' => env('DB_HOST', '127.0.0.1'),
            'port' => env('DB_PORT', '5432'),
            'database' => env('DB_DATABASE', 'laravel'),
            'username' => env('DB_USERNAME', 'root'),
            'password' => env('DB_PASSWORD', ''),
            'charset' => env('DB_CHARSET', 'utf8'),
            'prefix' => '',
            'prefix_indexes' => true,
            'search_path' => 'public',
            'sslmode' => env('DB_SSLMODE', 'prefer'),
        ],

        'sqlsrv' => [
```

```
            'driver' => 'sqlsrv',
            'url' => env('DB_URL'),
            'host' => env('DB_HOST', 'localhost'),
            'port' => env('DB_PORT', '1433'),
            'database' => env('DB_DATABASE', 'laravel'),
            'username' => env('DB_USERNAME', 'root'),
            'password' => env('DB_PASSWORD', ''),
            'charset' => env('DB_CHARSET', 'utf8'),
            'prefix' => '',
            'prefix_indexes' => true,
            // 'encrypt' => env('DB_ENCRYPT', 'yes'),
            // 'trust_server_certificate' => env('DB_TRUST_SERVER_CERTIFICATE', 'false'),
        ],

    ],

    /*
    |--------------------------------------------------------------------------
    | Migration Repository Table
    |--------------------------------------------------------------------------
    |
    | This table keeps track of all the migrations that have already run for
    | your application. Using this information, we can determine which of
    | the migrations on disk haven't actually been run on the database.
    |
    */

    'migrations' => [
        'table' => 'migrations',
        'update_date_on_publish' => true,
    ],

    /*
    |--------------------------------------------------------------------------
    | Redis Databases
    |--------------------------------------------------------------------------
    |
    | Redis is an open source, fast, and advanced key-value store that also
    | provides a richer body of commands than a typical key-value system
    | such as Memcached. You may define your connection settings here.
    |
    */

    'redis' => [

        'client' => env('REDIS_CLIENT', 'phpredis'),

        'options' => [
            'cluster' => env('REDIS_CLUSTER', 'redis'),
            'prefix' => env('REDIS_PREFIX', Str::slug((string) env('APP_NAME', 'laravel')).'-database-'),
            'persistent' => env('REDIS_PERSISTENT', false),
        ],

        'default' => [
            'url' => env('REDIS_URL'),
            'host' => env('REDIS_HOST', '127.0.0.1'),
            'username' => env('REDIS_USERNAME'),
            'password' => env('REDIS_PASSWORD'),
            'port' => env('REDIS_PORT', '6379'),
            'database' => env('REDIS_DB', '0'),
            'max_retries' => env('REDIS_MAX_RETRIES', 3),
            'backoff_algorithm' => env('REDIS_BACKOFF_ALGORITHM', 'decorrelated_jitter'),
            'backoff_base' => env('REDIS_BACKOFF_BASE', 100),
            'backoff_cap' => env('REDIS_BACKOFF_CAP', 1000),
        ],

        'cache' => [
            'url' => env('REDIS_URL'),
            'host' => env('REDIS_HOST', '127.0.0.1'),
            'username' => env('REDIS_USERNAME'),
            'password' => env('REDIS_PASSWORD'),
            'port' => env('REDIS_PORT', '6379'),
            'database' => env('REDIS_CACHE_DB', '1'),
            'max_retries' => env('REDIS_MAX_RETRIES', 3),
            'backoff_algorithm' => env('REDIS_BACKOFF_ALGORITHM', 'decorrelated_jitter'),
            'backoff_base' => env('REDIS_BACKOFF_BASE', 100),
            'backoff_cap' => env('REDIS_BACKOFF_CAP', 1000),
        ],

    ],

];
```

### *File: config\filesystems.php*

```
<?php

return [

    /*
    |--------------------------------------------------------------------------
    | Default Filesystem Disk
    |--------------------------------------------------------------------------
    |
    | Here you may specify the default filesystem disk that should be used
    | by the framework. The "local" disk, as well as a variety of cloud
    | based disks are available to your application for file storage.
    |
    */

    'default' => env('FILESYSTEM_DISK', 'local'),

    /*
    |--------------------------------------------------------------------------
    | Filesystem Disks
    |--------------------------------------------------------------------------
    |
    | Below you may configure as many filesystem disks as necessary, and you
    | may even configure multiple disks for the same driver. Examples for
    | most supported storage drivers are configured here for reference.
    |
    | Supported drivers: "local", "ftp", "sftp", "s3"
    |
    */

    'disks' => [

        'local' => [
            'driver' => 'local',
            'root' => storage_path('app/private'),
            'serve' => true,
            'throw' => false,
            'report' => false,
        ],
        'public' => [
```

```
            'driver' => 'local',
            'root' => storage_path('app/public'),
            'url' => rtrim(env('APP_URL', 'http://localhost'), '/').'/storage',
            'visibility' => 'public',
            'throw' => false,
            'report' => false,
        ],

        's3' => [
            'driver' => 's3',
            'key' => env('AWS_ACCESS_KEY_ID'),
            'secret' => env('AWS_SECRET_ACCESS_KEY'),
            'region' => env('AWS_DEFAULT_REGION'),
            'bucket' => env('AWS_BUCKET'),
            'url' => env('AWS_URL'),
            'endpoint' => env('AWS_ENDPOINT'),
            'use_path_style_endpoint' => env('AWS_USE_PATH_STYLE_ENDPOINT', false),
            'throw' => false,
            'report' => false,
        ],

    ],

    /*
    |--------------------------------------------------------------------------
    | Symbolic Links
    |--------------------------------------------------------------------------
    |
    | Here you may configure the symbolic links that will be created when the
    | `storage:link` Artisan command is executed. The array keys should be
    | the locations of the links and the values should be their targets.
    |
    */

    'links' => [
        public_path('storage') => storage_path('app/public'),
    ],

];
```

## File: config\logging.php

```
<?php

use Monolog\Handler\NullHandler;
use Monolog\Handler\StreamHandler;
use Monolog\Handler\SyslogUdpHandler;
use Monolog\Processor\PsrLogMessageProcessor;

return [

    /*
    |--------------------------------------------------------------------------
    | Default Log Channel
    |--------------------------------------------------------------------------
    |
    | This option defines the default log channel that is utilized to write
    | messages to your logs. The value provided here should match one of
    | the channels present in the list of "channels" configured below.
    |
    */

    'default' => env('LOG_CHANNEL', 'stack'),

    /*
    |--------------------------------------------------------------------------
    | Deprecations Log Channel
    |--------------------------------------------------------------------------
    |
    | This option controls the log channel that should be used to log warnings
    | regarding deprecated PHP and library features. This allows you to get
    | your application ready for upcoming major versions of dependencies.
    |
    */

    'deprecations' => [
        'channel' => env('LOG_DEPRECATIONS_CHANNEL', 'null'),
        'trace' => env('LOG_DEPRECATIONS_TRACE', false),
    ],

    /*
    |--------------------------------------------------------------------------
    | Log Channels
    |--------------------------------------------------------------------------
    |
    | Here you may configure the log channels for your application. Laravel
    | utilizes the Monolog PHP logging library, which includes a variety
    | of powerful log handlers and formatters that you're free to use.
    |
    | Available drivers: "single", "daily", "slack", "syslog",
    |                    "errorlog", "monolog", "custom", "stack"
    |
    */

    'channels' => [

        'stack' => [
            'driver' => 'stack',
            'channels' => explode(',', (string) env('LOG_STACK', 'single')),
            'ignore_exceptions' => false,
        ],

        'single' => [
            'driver' => 'single',
            'path' => storage_path('logs/laravel.log'),
            'level' => env('LOG_LEVEL', 'debug'),
            'replace_placeholders' => true,
        ],

        'daily' => [
            'driver' => 'daily',
            'path' => storage_path('logs/laravel.log'),
            'level' => env('LOG_LEVEL', 'debug'),
            'days' => env('LOG_DAILY_DAYS', 14),
            'replace_placeholders' => true,
        ],

        'slack' => [
            'driver' => 'slack',
            'url' => env('LOG_SLACK_WEBHOOK_URL'),
            'username' => env('LOG_SLACK_USERNAME', 'Laravel Log'),
            'emoji' => env('LOG_SLACK_EMOJI', ':boom:'),
            'level' => env('LOG_LEVEL', 'critical'),
            'replace_placeholders' => true,
        ],
```

```
        'papertrail' => [
            'driver' => 'monolog',
            'level' => env('LOG_LEVEL', 'debug'),
            'handler' => env('LOG_PAPERTRAIL_HANDLER', SyslogUdpHandler::class),
            'handler_with' => [
                'host' => env('PAPERTRAIL_URL'),
                'port' => env('PAPERTRAIL_PORT'),
                'connectionString' => 'tls://'.env('PAPERTRAIL_URL').':'.env('PAPERTRAIL_PORT'),
            ],
            'processors' => [PsrLogMessageProcessor::class],
        ],

        'stderr' => [
            'driver' => 'monolog',
            'level' => env('LOG_LEVEL', 'debug'),
            'handler' => StreamHandler::class,
            'handler_with' => [
                'stream' => 'php://stderr',
            ],
            'formatter' => env('LOG_STDERR_FORMATTER'),
            'processors' => [PsrLogMessageProcessor::class],
        ],

        'syslog' => [
            'driver' => 'syslog',
            'level' => env('LOG_LEVEL', 'debug'),
            'facility' => env('LOG_SYSLOG_FACILITY', LOG_USER),
            'replace_placeholders' => true,
        ],

        'errorlog' => [
            'driver' => 'errorlog',
            'level' => env('LOG_LEVEL', 'debug'),
            'replace_placeholders' => true,
        ],

        'null' => [
            'driver' => 'monolog',
            'handler' => NullHandler::class,
        ],

        'emergency' => [
            'path' => storage_path('logs/laravel.log'),
        ],

    ],

];
```

## File: config\mail.php

```php
<?php

return [

    /*
    |--------------------------------------------------------------------------
    | Default Mailer
    |--------------------------------------------------------------------------
    |
    | This option controls the default mailer that is used to send all email
    | messages unless another mailer is explicitly specified when sending
    | the message. All additional mailers can be configured within the
    | "mailers" array. Examples of each type of mailer are provided.
    |
    */

    'default' => env('MAIL_MAILER', 'log'),

    /*
    |--------------------------------------------------------------------------
    | Mailer Configurations
    |--------------------------------------------------------------------------
    |
    | Here you may configure all of the mailers used by your application plus
    | their respective settings. Several examples have been configured for
    | you and you are free to add your own as your application requires.
    |
    | Laravel supports a variety of mail "transport" drivers that can be used
    | when delivering an email. You may specify which one you're using for
    | your mailers below. You may also add additional mailers if needed.
    |
    | Supported: "smtp", "sendmail", "mailgun", "ses", "ses-v2",
    |            "postmark", "resend", "log", "array",
    |            "failover", "roundrobin"
    |
    */

    'mailers' => [

        'smtp' => [
            'transport' => 'smtp',
            'scheme' => env('MAIL_SCHEME'),
            'url' => env('MAIL_URL'),
            'host' => env('MAIL_HOST', '127.0.0.1'),
            'port' => env('MAIL_PORT', 2525),
            'username' => env('MAIL_USERNAME'),
            'password' => env('MAIL_PASSWORD'),
            'timeout' => null,
            'local_domain' => env('MAIL_EHLO_DOMAIN', parse_url((string) env('APP_URL', 'http://localhost'), PHP_URL_HOST)),
        ],

        'ses' => [
            'transport' => 'ses',
        ],

        'postmark' => [
            'transport' => 'postmark',
            // 'message_stream_id' => env('POSTMARK_MESSAGE_STREAM_ID'),
            // 'client' => [
            //     'timeout' => 5,
            // ],
        ],

        'resend' => [
            'transport' => 'resend',
        ],

        'sendmail' => [
            'transport' => 'sendmail',
            'path' => env('MAIL_SENDMAIL_PATH', '/usr/sbin/sendmail -bs -i'),
        ],

        'log' => [
            'transport' => 'log',
            'channel' => env('MAIL_LOG_CHANNEL'),
        ],

        'array' => [
            'transport' => 'array',
        ],

        'failover' => [
            'transport' => 'failover',
            'mailers' => [
                'smtp',
                'log',
            ],
            'retry_after' => 60,
        ],

        'roundrobin' => [
            'transport' => 'roundrobin',
            'mailers' => [
                'ses',
                'postmark',
            ],
            'retry_after' => 60,
        ],

    ],

    /*
    |--------------------------------------------------------------------------
    | Global "From" Address
    |--------------------------------------------------------------------------
    |
    | You may wish for all emails sent by your application to be sent from
    | the same address. Here you may specify a name and address that is
    | used globally for all emails that are sent by your application.
    |
    */

    'from' => [
        'address' => env('MAIL_FROM_ADDRESS', 'hello@example.com'),
        'name' => env('MAIL_FROM_NAME', 'Example'),
    ],

];
```

## File: config\queue.php

```php
<?php
return [
```

```
    /*
    |--------------------------------------------------------------------------
    | Default Queue Connection Name
    |--------------------------------------------------------------------------
    |
    | Laravel's queue supports a variety of backends via a single, unified
    | API, giving you convenient access to each backend using identical
    | syntax for each. The default queue connection is defined below.
    |
    */

    'default' => env('QUEUE_CONNECTION', 'database'),

    /*
    |--------------------------------------------------------------------------
    | Queue Connections
    |--------------------------------------------------------------------------
    |
    | Here you may configure the connection options for every queue backend
    | used by your application. An example configuration is provided for
    | each backend supported by Laravel. You're also free to add more.
    |
    | Drivers: "sync", "database", "beanstalkd", "sqs", "redis",
    |          "deferred", "background", "failover", "null"
    |
    */

    'connections' => [

        'sync' => [
            'driver' => 'sync',
        ],

        'database' => [
            'driver' => 'database',
            'connection' => env('DB_QUEUE_CONNECTION'),
            'table' => env('DB_QUEUE_TABLE', 'jobs'),
            'queue' => env('DB_QUEUE', 'default'),
            'retry_after' => (int) env('DB_QUEUE_RETRY_AFTER', 90),
            'after_commit' => false,
        ],

        'beanstalkd' => [
            'driver' => 'beanstalkd',
            'host' => env('BEANSTALKD_QUEUE_HOST', 'localhost'),
            'queue' => env('BEANSTALKD_QUEUE', 'default'),
            'retry_after' => (int) env('BEANSTALKD_QUEUE_RETRY_AFTER', 90),
            'block_for' => 0,
            'after_commit' => false,
        ],

        'sqs' => [
            'driver' => 'sqs',
            'key' => env('AWS_ACCESS_KEY_ID'),
            'secret' => env('AWS_SECRET_ACCESS_KEY'),
            'prefix' => env('SQS_PREFIX', 'https://sqs.us-east-1.amazonaws.com/your-account-id'),
            'queue' => env('SQS_QUEUE', 'default'),
            'suffix' => env('SQS_SUFFIX'),
            'region' => env('AWS_DEFAULT_REGION', 'us-east-1'),
            'after_commit' => false,
        ],

        'redis' => [
            'driver' => 'redis',
            'connection' => env('REDIS_QUEUE_CONNECTION', 'default'),
            'queue' => env('REDIS_QUEUE', 'default'),
            'retry_after' => (int) env('REDIS_QUEUE_RETRY_AFTER', 90),
            'block_for' => null,
            'after_commit' => false,
        ],

        'deferred' => [
            'driver' => 'deferred',
        ],

        'background' => [
            'driver' => 'background',
        ],

        'failover' => [
            'driver' => 'failover',
            'connections' => [
                'database',
                'deferred',
            ],
        ],

    ],

    /*
    |--------------------------------------------------------------------------
    | Job Batching
    |--------------------------------------------------------------------------
    |
    | The following options configure the database and table that store job
    | batching information. These options can be updated to any database
    | connection and table which has been defined by your application.
    |
    */

    'batching' => [
        'database' => env('DB_CONNECTION', 'sqlite'),
        'table' => 'job_batches',
    ],

    /*
    |--------------------------------------------------------------------------
    | Failed Queue Jobs
    |--------------------------------------------------------------------------
    |
    | These options configure the behavior of failed queue job logging so you
    | can control how and where failed jobs are stored. Laravel ships with
    | support for storing failed jobs in a simple file or in a database.
    |
    | Supported drivers: "database-uuids", "dynamodb", "file", "null"
    |
    */

    'failed' => [
        'driver' => env('QUEUE_FAILED_DRIVER', 'database-uuids'),
        'database' => env('DB_CONNECTION', 'sqlite'),
        'table' => 'failed_jobs',
    ],

];
```

### File: config\services.php

```
<?php

return [

    /*
    |--------------------------------------------------------------------------
    | Third Party Services
    |--------------------------------------------------------------------------
    |
    | This file is for storing the credentials for third party services such
    | as Mailgun, Postmark, AWS and more. This file provides the de facto
    | location for this type of information, allowing packages to have
    | a conventional file to locate the various service credentials.
    |
    */

    'postmark' => [
        'key' => env('POSTMARK_API_KEY'),
    ],

    'resend' => [
        'key' => env('RESEND_API_KEY'),
    ],

    'ses' => [
        'key' => env('AWS_ACCESS_KEY_ID'),
        'secret' => env('AWS_SECRET_ACCESS_KEY'),
        'region' => env('AWS_DEFAULT_REGION', 'us-east-1'),
    ],

    'slack' => [
        'notifications' => [
            'bot_user_oauth_token' => env('SLACK_BOT_USER_OAUTH_TOKEN'),
            'channel' => env('SLACK_BOT_USER_DEFAULT_CHANNEL'),
        ],
    ],

];
```

### File: config\session.php

```
<?php

use Illuminate\Support\Str;

return [

    /*
    |--------------------------------------------------------------------------
    | Default Session Driver
    |--------------------------------------------------------------------------
    |
    | This option determines the default session driver that is utilized for
    | incoming requests. Laravel supports a variety of storage options to
    | persist session data. Database storage is a great default choice.
    |
    | Supported: "file", "cookie", "database", "memcached",
    |            "redis", "dynamodb", "array"
    |
    */

    'driver' => env('SESSION_DRIVER', 'database'),

    /*
    |--------------------------------------------------------------------------
    | Session Lifetime
    |--------------------------------------------------------------------------
    |
    | Here you may specify the number of minutes that you wish the session
    | to be allowed to remain idle before it expires. If you want them
    | to expire immediately when the browser is closed then you may
    | indicate that via the expire_on_close configuration option.
    |
    */

    'lifetime' => (int) env('SESSION_LIFETIME', 120),

    'expire_on_close' => env('SESSION_EXPIRE_ON_CLOSE', false),

    /*
    |--------------------------------------------------------------------------
    | Session Encryption
    |--------------------------------------------------------------------------
    |
    | This option allows you to easily specify that all of your session data
    | should be encrypted before it's stored. All encryption is performed
    | automatically by Laravel and you may use the session like normal.
    |
    */

    'encrypt' => env('SESSION_ENCRYPT', false),

    /*
    |--------------------------------------------------------------------------
    | Session File Location
    |--------------------------------------------------------------------------
    |
    | When utilizing the "file" session driver, the session files are placed
    | on disk. The default storage location is defined here; however, you
    | are free to provide another location where they should be stored.
    |
    */

    'files' => storage_path('framework/sessions'),

    /*
    |--------------------------------------------------------------------------
    | Session Database Connection
    |--------------------------------------------------------------------------
    |
    | When using the "database" or "redis" session drivers, you may specify a
    | connection that should be used to manage these sessions. This should
    | correspond to a connection in your database configuration options.
    |
    */

    'connection' => env('SESSION_CONNECTION'),

    /*
    |--------------------------------------------------------------------------
    | Session Database Table
    |--------------------------------------------------------------------------
    |
```

```
| When using the "database" session driver, you may specify the table to
| be used to store sessions. Of course, a sensible default is defined
| for you; however, you're welcome to change this to another table.
|
*/

'table' => env('SESSION_TABLE', 'sessions'),

/*
|--------------------------------------------------------------------------
| Session Cache Store
|--------------------------------------------------------------------------
|
| When using one of the framework's cache driven session backends, you may
| define the cache store which should be used to store the session data
| between requests. This must match one of your defined cache stores.
|
| Affects: "dynamodb", "memcached", "redis"
|
*/

'store' => env('SESSION_STORE'),

/*
|--------------------------------------------------------------------------
| Session Sweeping Lottery
|--------------------------------------------------------------------------
|
| Some session drivers must manually sweep their storage location to get
| rid of old sessions from storage. Here are the chances that it will
| happen on a given request. By default, the odds are 2 out of 100.
|
*/

'lottery' => [2, 100],

/*
|--------------------------------------------------------------------------
| Session Cookie Name
|--------------------------------------------------------------------------
|
| Here you may change the name of the session cookie that is created by
| the framework. Typically, you should not need to change this value
| since doing so does not grant a meaningful security improvement.
|
*/

'cookie' => env(
    'SESSION_COOKIE',
    Str::slug((string) env('APP_NAME', 'laravel')).'-session'
),

/*
|--------------------------------------------------------------------------
| Session Cookie Path
|--------------------------------------------------------------------------
|
| The session cookie path determines the path for which the cookie will
| be regarded as available. Typically, this will be the root path of
| your application, but you're free to change this when necessary.
|
*/

'path' => env('SESSION_PATH', '/'),

/*
|--------------------------------------------------------------------------
| Session Cookie Domain
|--------------------------------------------------------------------------
|
| This value determines the domain and subdomains the session cookie is
| available to. By default, the cookie will be available to the root
| domain without subdomains. Typically, this shouldn't be changed.
|
*/

'domain' => env('SESSION_DOMAIN'),

/*
|--------------------------------------------------------------------------
| HTTPS Only Cookies
|--------------------------------------------------------------------------
|
| By setting this option to true, session cookies will only be sent back
| to the server if the browser has a HTTPS connection. This will keep
| the cookie from being sent to you when it can't be done securely.
|
*/

'secure' => env('SESSION_SECURE_COOKIE'),

/*
|--------------------------------------------------------------------------
| HTTP Access Only
|--------------------------------------------------------------------------
|
| Setting this value to true will prevent JavaScript from accessing the
| value of the cookie and the cookie will only be accessible through
| the HTTP protocol. It's unlikely you should disable this option.
|
*/

'http_only' => env('SESSION_HTTP_ONLY', true),

/*
|--------------------------------------------------------------------------
| Same-Site Cookies
|--------------------------------------------------------------------------
|
| This option determines how your cookies behave when cross-site requests
| take place, and can be used to mitigate CSRF attacks. By default, we
| will set this value to "lax" to permit secure cross-site requests.
|
| See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Set-Cookie#samesitesamesite-value
|
| Supported: "lax", "strict", "none", null
|
*/

'same_site' => env('SESSION_SAME_SITE', 'lax'),

/*
|--------------------------------------------------------------------------
| Partitioned Cookies
|--------------------------------------------------------------------------
|
| Setting this value to true will tie the cookie to the top-level site for
| a cross-site context. Partitioned cookies are accepted by the browser
```

```
    | when flagged "secure" and the Same-Site attribute is set to "none".
    |
    */

    'partitioned' => env('SESSION_PARTITIONED_COOKIE', false),

];
```

### File: database\factories\UserFactory.php

```
<?php

namespace Database\Factories;

use Illuminate\Database\Eloquent\Factories\Factory;
use Illuminate\Support\Facades\Hash;
use Illuminate\Support\Str;

/**
 * @extends \Illuminate\Database\Eloquent\Factories\Factory<\App\Models\User>
 */
class UserFactory extends Factory
{
    /**
     * The current password being used by the factory.
     */
    protected static ?string $password;

    /**
     * Define the model's default state.
     *
     * @return array<string, mixed>
     */
    public function definition(): array
    {
        return [
            'name' => fake()->name(),
            'email' => fake()->unique()->safeEmail(),
            'email_verified_at' => now(),
            'password' => static::$password ??= Hash::make('password'),
            'remember_token' => Str::random(10),
        ];
    }

    /**
     * Indicate that the model's email address should be unverified.
     */
    public function unverified(): static
    {
        return $this->state(fn (array $attributes) => [
            'email_verified_at' => null,
        ]);
    }
}
```

### File: database\migrations\0001_01_01_000000_create_users_table.php

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('users', function (Blueprint $table) {
            $table->id();
            $table->string('name');
            $table->string('email')->unique();
            $table->timestamp('email_verified_at')->nullable();
            $table->string('password');
            $table->rememberToken();
            $table->timestamps();
        });

        Schema::create('password_reset_tokens', function (Blueprint $table) {
            $table->string('email')->primary();
            $table->string('token');
            $table->timestamp('created_at')->nullable();
        });

        Schema::create('sessions', function (Blueprint $table) {
            $table->string('id')->primary();
            $table->foreignId('user_id')->nullable()->index();
            $table->string('ip_address', 45)->nullable();
            $table->text('user_agent')->nullable();
            $table->longText('payload');
            $table->integer('last_activity')->index();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('users');
        Schema::dropIfExists('password_reset_tokens');
        Schema::dropIfExists('sessions');
    }
};
```

### File: database\migrations\0001_01_01_000001_create_cache_table.php

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
```

```
    {
        Schema::create('cache', function (Blueprint $table) {
            $table->string('key')->primary();
            $table->mediumText('value');
            $table->integer('expiration')->index();
        });

        Schema::create('cache_locks', function (Blueprint $table) {
            $table->string('key')->primary();
            $table->string('owner');
            $table->integer('expiration')->index();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('cache');
        Schema::dropIfExists('cache_locks');
    }
};
```

***File: database\migrations\0001_01_01_000002_create_jobs_table.php***

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('jobs', function (Blueprint $table) {
            $table->id();
            $table->string('queue')->index();
            $table->longText('payload');
            $table->unsignedTinyInteger('attempts');
            $table->unsignedInteger('reserved_at')->nullable();
            $table->unsignedInteger('available_at');
            $table->unsignedInteger('created_at');
        });

        Schema::create('job_batches', function (Blueprint $table) {
            $table->string('id')->primary();
            $table->string('name');
            $table->integer('total_jobs');
            $table->integer('pending_jobs');
            $table->integer('failed_jobs');
            $table->longText('failed_job_ids');
            $table->mediumText('options')->nullable();
            $table->integer('cancelled_at')->nullable();
            $table->integer('created_at');
            $table->integer('finished_at')->nullable();
        });

        Schema::create('failed_jobs', function (Blueprint $table) {
            $table->id();
            $table->string('uuid')->unique();
            $table->text('connection');
            $table->text('queue');
            $table->longText('payload');
            $table->longText('exception');
            $table->timestamp('failed_at')->useCurrent();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('jobs');
        Schema::dropIfExists('job_batches');
        Schema::dropIfExists('failed_jobs');
    }
};
```

***File: database\migrations\2026_03_10_000000_add_account_type_to_users_table.php***

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::table('users', function (Blueprint $table) {
            $table->string('account_type')->default('customer')->after('password');
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::table('users', function (Blueprint $table) {
            $table->dropColumn('account_type');
        });
    }
};
```

***File: database\migrations\2026_03_10_010000_create_store_registrations_table.php***

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
```

```php
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    public function up(): void
    {
        Schema::create('store_registrations', function (Blueprint $table) {
            $table->id();
            $table->string('store_name');
            $table->string('owner_full_name');
            $table->string('email')->nullable();
            $table->string('country_code', 10)->nullable();
            $table->string('phone', 30)->nullable();
            $table->string('store_type', 50)->nullable();
            $table->string('city', 100)->nullable();
            $table->string('subcity', 100)->nullable();
            $table->string('address')->nullable();
            $table->text('store_description')->nullable();

            $table->boolean('offers_rental')->default(false);
            $table->boolean('offers_sale')->default(false);
            $table->boolean('offers_delivery')->default(false);
            $table->unsignedSmallInteger('delivery_radius')->nullable();
            $table->decimal('delivery_fee', 10, 2)->nullable();
            $table->json('delivery_methods')->nullable();
            $table->boolean('delivery_bike')->default(false);
            $table->boolean('delivery_car')->default(false);
            $table->boolean('delivery_pickup')->default(false);

            $table->boolean('open_monday')->default(false);
            $table->time('open_time_monday')->nullable();
            $table->time('close_time_monday')->nullable();
            $table->boolean('closed_monday')->default(false);

            $table->boolean('open_tuesday')->default(false);
            $table->time('open_time_tuesday')->nullable();
            $table->time('close_time_tuesday')->nullable();
            $table->boolean('closed_tuesday')->default(false);

            $table->boolean('open_wednesday')->default(false);
            $table->time('open_time_wednesday')->nullable();
            $table->time('close_time_wednesday')->nullable();
            $table->boolean('closed_wednesday')->default(false);

            $table->boolean('open_thursday')->default(false);
            $table->time('open_time_thursday')->nullable();
            $table->time('close_time_thursday')->nullable();
            $table->boolean('closed_thursday')->default(false);

            $table->boolean('open_friday')->default(false);
            $table->time('open_time_friday')->nullable();
            $table->time('close_time_friday')->nullable();
            $table->boolean('closed_friday')->default(false);

            $table->boolean('open_saturday')->default(false);
            $table->time('open_time_saturday')->nullable();
            $table->time('close_time_saturday')->nullable();
            $table->boolean('closed_saturday')->default(false);

            $table->boolean('open_sunday')->default(false);
            $table->time('open_time_sunday')->nullable();
            $table->time('close_time_sunday')->nullable();
            $table->boolean('closed_sunday')->default(false);

            $table->unsignedSmallInteger('rental_period')->nullable();
            $table->decimal('rental_price', 10, 2)->nullable();
            $table->decimal('late_fee', 10, 2)->nullable();
            $table->decimal('security_deposit', 10, 2)->nullable();
            $table->unsignedSmallInteger('max_books')->nullable();
            $table->unsignedSmallInteger('discount_percent')->nullable();

            $table->json('payment_methods')->nullable();
            $table->boolean('agree_terms')->default(false);

            $table->timestamps();
        });
    }

    public function down(): void
    {
        Schema::dropIfExists('store_registrations');
    }
};
```

### File: database\migrations\2026_03_11_000001_create_books_table.php

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('books', function (Blueprint $table) {
            $table->id();
            $table->foreignId('user_id')->constrained()->cascadeOnDelete();
            $table->string('title');
            $table->string('author');
            $table->string('genre', 100);
            $table->unsignedSmallInteger('publication_year')->nullable();
            $table->unsignedInteger('total_copies');
            $table->unsignedInteger('available_rent');
            $table->unsignedInteger('available_sale');
            $table->decimal('rental_price', 10, 2);
            $table->decimal('sale_price', 10, 2);
            $table->string('cover_image_path')->nullable();
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('books');
    }
};
```

### File: database\migrations\2026_03_11_130100_create_issue_reports_table.php

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('issue_reports', function (Blueprint $table) {
            $table->id();
            $table->foreignId('user_id')->constrained()->cascadeOnDelete();
            $table->string('subject');
            $table->text('description');
            $table->string('priority')->default('medium');
            $table->string('status')->default('open');
            $table->foreignId('assigned_admin_id')->nullable()->constrained('users')->nullOnDelete();
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('issue_reports');
    }
};
```

### File: database\migrations\2026_03_11_130200_create_chat_conversations_table.php

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('chat_conversations', function (Blueprint $table) {
            $table->id();
            $table->foreignId('customer_id')->constrained('users')->cascadeOnDelete();
            $table->foreignId('assigned_admin_id')->nullable()->constrained('users')->nullOnDelete();
            $table->string('subject')->nullable();
            $table->string('status')->default('open');
            $table->timestamp('last_message_at')->nullable();
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('chat_conversations');
    }
};
```

### File: database\migrations\2026_03_11_130300_create_chat_messages_table.php

```php
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;
return new class extends Migration
```

```
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('chat_messages', function (Blueprint $table) {
            $table->id();
            $table->foreignId('conversation_id')->constrained('chat_conversations')->cascadeOnDelete();
            $table->foreignId('sender_id')->constrained('users')->cascadeOnDelete();
            $table->string('sender_role')->nullable();
            $table->text('message');
            $table->timestamp('read_at')->nullable();
            $table->timestamps();

            $table->index(['conversation_id', 'read_at']);
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('chat_messages');
    }
};
```

### File: database\migrations\2026_03_13_055558_add_store_id_to_chat_conversations.php

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    public function up(): void
    {
        Schema::table('chat_conversations', function (Blueprint $table) {
            if (!Schema::hasColumn('chat_conversations', 'store_id')) {
                $table->foreignId('store_id')
                    ->nullable()
                    ->constrained('users')
                    ->cascadeOnDelete()
                    ->after('customer_id');
            }

            if (!Schema::hasColumn('chat_conversations', 'book_id')) {
                $table->foreignId('book_id')
                    ->nullable()
                    ->constrained('books')
                    ->nullOnDelete()
                    ->after('store_id');
            }

            if (!Schema::hasColumn('chat_conversations', 'last_message')) {
                $table->text('last_message')->nullable()->after('last_message_at');
            }

            if (!Schema::hasColumn('chat_conversations', 'last_message_sender_id')) {
                $table->foreignId('last_message_sender_id')
                    ->nullable()
                    ->constrained('users')
                    ->nullOnDelete()
                    ->after('last_message');
            }
        });
    }

    public function down(): void
    {
        Schema::table('chat_conversations', function (Blueprint $table) {
            $table->dropForeign(['store_id']);
            $table->dropForeign(['book_id']);
            $table->dropForeign(['last_message_sender_id']);
            $table->dropColumn(['store_id', 'book_id', 'last_message', 'last_message_sender_id']);
        });
    }
};
```

### File: database\migrations\2026_03_13_055559_add_is_read_to_chat_messages.php

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    public function up(): void
    {
        Schema::table('chat_messages', function (Blueprint $table) {
            if (!Schema::hasColumn('chat_messages', 'is_read')) {
                $table->boolean('is_read')->default(false)->after('message');
            }

            if (!Schema::hasColumn('chat_messages', 'is_read_at')) {
                $table->timestamp('is_read_at')->nullable()->after('is_read');
            }

            if (!Schema::hasColumn('chat_messages', 'attachment_path')) {
                $table->string('attachment_path')->nullable()->after('is_read_at');
            }

            if (!Schema::hasColumn('chat_messages', 'attachment_name')) {
                $table->string('attachment_name')->nullable()->after('attachment_path');
            }

            if (!Schema::hasColumn('chat_messages', 'attachment_size')) {
                $table->integer('attachment_size')->nullable()->after('attachment_name');
            }

            if (!Schema::hasColumn('chat_messages', 'attachment_type')) {
                $table->string('attachment_type')->nullable()->after('attachment_size');
            }
        });
    }

    public function down(): void
    {
```

```
        Schema::table('chat_messages', function (Blueprint $table) {
            $table->dropColumn([
                'is_read',
                'is_read_at',
                'attachment_path',
                'attachment_name',
                'attachment_size',
                'attachment_type'
            ]);
        });
    }
};
```

### File: database\migrations\2026_03_14_000001_enhance_issue_reports_and_users.php

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    public function up(): void
    {
        // Add fields to issue_reports
        Schema::table('issue_reports', function (Blueprint $table) {
            if (!Schema::hasColumn('issue_reports', 'reported_user_id')) {
                $table->foreignId('reported_user_id')
                    ->nullable()
                    ->constrained('users')
                    ->nullOnDelete()
                    ->after('user_id');
            }
            if (!Schema::hasColumn('issue_reports', 'reporter_role')) {
                $table->string('reporter_role')->nullable()->after('reported_user_id'); // 'customer' or 'store_owner'
            }
            if (!Schema::hasColumn('issue_reports', 'evidence_path')) {
                $table->string('evidence_path')->nullable()->after('description');
            }
            if (!Schema::hasColumn('issue_reports', 'evidence_name')) {
                $table->string('evidence_name')->nullable()->after('evidence_path');
            }
            if (!Schema::hasColumn('issue_reports', 'evidence_type')) {
                $table->string('evidence_type')->nullable()->after('evidence_name');
            }
            if (!Schema::hasColumn('issue_reports', 'admin_notes')) {
                $table->text('admin_notes')->nullable()->after('assigned_admin_id');
            }
        });

        // Add moderation fields to users
        Schema::table('users', function (Blueprint $table) {
            if (!Schema::hasColumn('users', 'is_active')) {
                $table->boolean('is_active')->default(true)->after('account_type');
            }
            if (!Schema::hasColumn('users', 'is_banned')) {
                $table->boolean('is_banned')->default(false)->after('is_active');
            }
            if (!Schema::hasColumn('users', 'ban_reason')) {
                $table->text('ban_reason')->nullable()->after('is_banned');
            }
            if (!Schema::hasColumn('users', 'banned_at')) {
                $table->timestamp('banned_at')->nullable()->after('ban_reason');
            }
            if (!Schema::hasColumn('users', 'warning_count')) {
                $table->unsignedSmallInteger('warning_count')->default(0)->after('banned_at');
            }
            if (!Schema::hasColumn('users', 'is_restricted')) {
                $table->boolean('is_restricted')->default(false)->after('warning_count');
            }
            if (!Schema::hasColumn('users', 'restricted_until')) {
                $table->timestamp('restricted_until')->nullable()->after('is_restricted');
            }
            if (!Schema::hasColumn('users', 'avatar')) {
                $table->string('avatar')->nullable()->after('name');
            }
            if (!Schema::hasColumn('users', 'phone')) {
                $table->string('phone', 30)->nullable()->after('avatar');
            }
            if (!Schema::hasColumn('users', 'bio')) {
                $table->text('bio')->nullable()->after('phone');
            }
            if (!Schema::hasColumn('users', 'last_seen_at')) {
                $table->timestamp('last_seen_at')->nullable()->after('bio');
            }
        });
    }

    public function down(): void
    {
        Schema::table('issue_reports', function (Blueprint $table) {
            $table->dropForeign(['reported_user_id']);
            $table->dropColumn(['reported_user_id', 'reporter_role', 'evidence_path', 'evidence_name', 'evidence_type', 'admin_notes']);
        });

        Schema::table('users', function (Blueprint $table) {
            $table->dropColumn(['is_active', 'is_banned', 'ban_reason', 'banned_at', 'warning_count', 'is_restricted', 'restricted_until']);
        });
    }
};
```

### File: database\seeders\AdminUserSeeder.php

```
<?php

namespace Database\Seeders;

use App\Models\User;
use Illuminate\Database\Seeder;
use Illuminate\Support\Facades\Hash;

class AdminUserSeeder extends Seeder
{
    /**
     * Run the database seeds.
     */
    public function run(): void
    {
        // Check if users already exist to avoid duplicates
        if (User::where('email', 'superadmin@bookhub.com')->doesntExist()) {
            User::create([
                'name' => 'Super Admin',
```

```
                'email' => 'superadmin@bookhub.com',
                'password' => Hash::make('Admin@123'),
                'account_type' => 'super_admin',
                'email_verified_at' => now(),
            ]);

            $this->command->info('Super Admin created successfully!');
        } else {
            $this->command->info('Super Admin already exists.');
        }

        if (User::where('email', 'subadmin@bookhub.com')->doesntExist()) {
            User::create([
                'name' => 'Sub Admin',
                'email' => 'subadmin@bookhub.com',
                'password' => Hash::make('Admin@123'),
                'account_type' => 'sub_admin',
                'email_verified_at' => now(),
            ]);

            $this->command->info('Sub Admin created successfully!');
        } else {
            $this->command->info('Sub Admin already exists.');
        }
    }
}
```

### File: database\seeders\DatabaseSeeder.php

```
<?php

namespace Database\Seeders;

use App\Models\User;
use Illuminate\Database\Seeder;

class DatabaseSeeder extends Seeder
{
    /**
     * Seed the application's database.
     */
    public function run(): void
    {
        // Call your seeders
        $this->call([
            AdminUserSeeder::class,
        ]);

        // Or keep your existing test user
        User::factory()->create([
            'name' => 'Test User',
            'email' => 'test@example.com',
        ]);
    }
}
```

### File: public\index.php

```
<?php

use Illuminate\Foundation\Application;
use Illuminate\Http\Request;

define('LARAVEL_START', microtime(true));

// Determine if the application is in maintenance mode...
if (file_exists($maintenance = __DIR__.'/../storage/framework/maintenance.php')) {
    require $maintenance;
}

// Register the Composer autoloader...
require __DIR__.'/../vendor/autoload.php';

// Bootstrap Laravel and handle the request...
/** @var Application $app */
$app = require_once __DIR__.'/../bootstrap/app.php';

$app->handleRequest(Request::capture());
```

### File: public\robots.txt

```
User-agent: *
Disallow:
```

### File: public\build\manifest.json


```
{
  "_ApplicationLogo-DPlTNKJi.js": {
    "file": "assets/ApplicationLogo-DPlTNKJi.js",
    "name": "ApplicationLogo",
    "imports": [
      "resources/js/app.jsx"
    ]
  },
  "_AuthenticatedLayout-CgjTH9WJ.js": {
    "file": "assets/AuthenticatedLayout-CgjTH9WJ.js",
    "name": "AuthenticatedLayout",
    "imports": [
      "resources/js/app.jsx",
      "_ApplicationLogo-DPlTNKJi.js",
      "_transition-C95k0J7b.js"
    ]
  },
  "_GuestLayout-CAQ5aVTJ.js": {
    "file": "assets/GuestLayout-CAQ5aVTJ.js",
    "name": "GuestLayout",
    "imports": [
      "resources/js/app.jsx",
      "_ApplicationLogo-DPlTNKJi.js"
    ]
  },
  "_InputLabel-DBG7MFZr.js": {
    "file": "assets/InputLabel-DBG7MFZr.js",
    "name": "InputLabel",
    "imports": [
      "resources/js/app.jsx"
    ]
  },
  "_PrimaryButton-Bb5G6Hn1.js": {
    "file": "assets/PrimaryButton-Bb5G6Hn1.js",
    "name": "PrimaryButton",
    "imports": [
      "resources/js/app.jsx"
    ]
  },
  "_TextInput-Ca7FXA7z.js": {
    "file": "assets/TextInput-Ca7FXA7z.js",
    "name": "TextInput",
    "imports": [
      "resources/js/app.jsx"
    ]
  },
  "_transition-C95k0J7b.js": {
    "file": "assets/transition-C95k0J7b.js",
    "name": "transition",
    "imports": [
      "resources/js/app.jsx"
    ]
  },
  "resources/js/Pages/Auth/ConfirmPassword.jsx": {
    "file": "assets/ConfirmPassword-CBzEM5GG.js",
    "name": "ConfirmPassword",
    "src": "resources/js/Pages/Auth/ConfirmPassword.jsx",
    "isDynamicEntry": true,
    "imports": [
      "resources/js/app.jsx",
      "_TextInput-Ca7FXA7z.js",
      "_InputLabel-DBG7MFZr.js",
      "_PrimaryButton-Bb5G6Hn1.js",
      "_GuestLayout-CAQ5aVTJ.js",
      "_ApplicationLogo-DPlTNKJi.js"
    ]
  },
  "resources/js/Pages/Auth/ForgotPassword.jsx": {
    "file": "assets/ForgotPassword-U49R6K9z.js",
    "name": "ForgotPassword",
    "src": "resources/js/Pages/Auth/ForgotPassword.jsx",
    "isDynamicEntry": true,
    "imports": [
      "resources/js/app.jsx",
      "_TextInput-Ca7FXA7z.js",
      "_PrimaryButton-Bb5G6Hn1.js",
      "_GuestLayout-CAQ5aVTJ.js",
      "_ApplicationLogo-DPlTNKJi.js"
    ]
  },
  "resources/js/Pages/Auth/Login.jsx": {
    "file": "assets/Login-BWVoa2Gg.js",
    "name": "Login",
    "src": "resources/js/Pages/Auth/Login.jsx",
    "isDynamicEntry": true,
    "imports": [
      "resources/js/app.jsx",
      "_TextInput-Ca7FXA7z.js",
      "_InputLabel-DBG7MFZr.js",
      "_PrimaryButton-Bb5G6Hn1.js",
      "_GuestLayout-CAQ5aVTJ.js",
      "_ApplicationLogo-DPlTNKJi.js"
    ]
  },
  "resources/js/Pages/Auth/Register.jsx": {
    "file": "assets/Register-CeqRc_bm.js",
    "name": "Register",
    "src": "resources/js/Pages/Auth/Register.jsx",
    "isDynamicEntry": true,
    "imports": [
      "resources/js/app.jsx",
      "_TextInput-Ca7FXA7z.js",
      "_InputLabel-DBG7MFZr.js",
      "_PrimaryButton-Bb5G6Hn1.js",
      "_GuestLayout-CAQ5aVTJ.js",
      "_ApplicationLogo-DPlTNKJi.js"
    ]
  },
  "resources/js/Pages/Auth/ResetPassword.jsx": {
    "file": "assets/ResetPassword-DFOL_bTT.js",
    "name": "ResetPassword",
    "src": "resources/js/Pages/Auth/ResetPassword.jsx",
    "isDynamicEntry": true,
    "imports": [
      "resources/js/app.jsx",
      "_TextInput-Ca7FXA7z.js",
      "_InputLabel-DBG7MFZr.js",
      "_PrimaryButton-Bb5G6Hn1.js",
```

```
      "_GuestLayout-CAQ5aVTJ.js",
      "_ApplicationLogo-DPlTNKJi.js"
    ]
  },
  "resources/js/Pages/Auth/VerifyEmail.jsx": {
    "file": "assets/VerifyEmail-D4TVxu0c.js",
    "name": "VerifyEmail",
    "src": "resources/js/Pages/Auth/VerifyEmail.jsx",
    "isDynamicEntry": true,
    "imports": [
      "resources/js/app.jsx",
      "_PrimaryButton-Bb5G6Hn1.js",
      "_GuestLayout-CAQ5aVTJ.js",
      "_ApplicationLogo-DPlTNKJi.js"
    ]
  },
  "resources/js/Pages/Dashboard.jsx": {
    "file": "assets/Dashboard-DhQTk4Fy.js",
    "name": "Dashboard",
    "src": "resources/js/Pages/Dashboard.jsx",
    "isDynamicEntry": true,
    "imports": [
      "resources/js/app.jsx",
      "_AuthenticatedLayout-CgjTH9WJ.js",
      "_ApplicationLogo-DPlTNKJi.js",
      "_transition-C95k0J7b.js"
    ]
  },
  "resources/js/Pages/Profile/Edit.jsx": {
    "file": "assets/Edit-QYlRHcro.js",
    "name": "Edit",
    "src": "resources/js/Pages/Profile/Edit.jsx",
    "isDynamicEntry": true,
    "imports": [
      "resources/js/app.jsx",
      "_AuthenticatedLayout-CgjTH9WJ.js",
      "resources/js/Pages/Profile/Partials/DeleteUserForm.jsx",
      "resources/js/Pages/Profile/Partials/UpdatePasswordForm.jsx",
      "resources/js/Pages/Profile/Partials/UpdateProfileInformationForm.jsx",
      "_ApplicationLogo-DPlTNKJi.js",
      "_transition-C95k0J7b.js",
      "_TextInput-Ca7FXA7z.js",
      "_InputLabel-DBG7MFZr.js",
      "_PrimaryButton-Bb5G6Hn1.js"
    ]
  },
  "resources/js/Pages/Profile/Partials/DeleteUserForm.jsx": {
    "file": "assets/DeleteUserForm-_uihPTB7.js",
    "name": "DeleteUserForm",
    "src": "resources/js/Pages/Profile/Partials/DeleteUserForm.jsx",
    "isDynamicEntry": true,
    "imports": [
      "resources/js/app.jsx",
      "_TextInput-Ca7FXA7z.js",
      "_InputLabel-DBG7MFZr.js",
      "_transition-C95k0J7b.js"
    ]
  },
  "resources/js/Pages/Profile/Partials/UpdatePasswordForm.jsx": {
    "file": "assets/UpdatePasswordForm-CT4sSwFX.js",
    "name": "UpdatePasswordForm",
    "src": "resources/js/Pages/Profile/Partials/UpdatePasswordForm.jsx",
    "isDynamicEntry": true,
    "imports": [
      "resources/js/app.jsx",
      "_TextInput-Ca7FXA7z.js",
      "_InputLabel-DBG7MFZr.js",
      "_PrimaryButton-Bb5G6Hn1.js",
      "_transition-C95k0J7b.js"
    ]
  },
  "resources/js/Pages/Profile/Partials/UpdateProfileInformationForm.jsx": {
    "file": "assets/UpdateProfileInformationForm-BGrbu5sz.js",
    "name": "UpdateProfileInformationForm",
    "src": "resources/js/Pages/Profile/Partials/UpdateProfileInformationForm.jsx",
    "isDynamicEntry": true,
    "imports": [
      "resources/js/app.jsx",
      "_TextInput-Ca7FXA7z.js",
      "_InputLabel-DBG7MFZr.js",
      "_PrimaryButton-Bb5G6Hn1.js",
      "_transition-C95k0J7b.js"
    ]
  },
  "resources/js/Pages/Welcome.jsx": {
    "file": "assets/Welcome-CoLzhMiE.js",
    "name": "Welcome",
    "src": "resources/js/Pages/Welcome.jsx",
    "isDynamicEntry": true,
    "imports": [
      "resources/js/app.jsx"
    ]
  },
  "resources/js/app.jsx": {
    "file": "assets/app-BrYB81S6.js",
    "name": "app",
    "src": "resources/js/app.jsx",
    "isEntry": true,
    "dynamicImports": [
      "resources/js/Pages/Auth/ConfirmPassword.jsx",
      "resources/js/Pages/Auth/ForgotPassword.jsx",
      "resources/js/Pages/Auth/Login.jsx",
      "resources/js/Pages/Auth/Register.jsx",
      "resources/js/Pages/Auth/ResetPassword.jsx",
      "resources/js/Pages/Auth/VerifyEmail.jsx",
      "resources/js/Pages/Dashboard.jsx",
      "resources/js/Pages/Profile/Edit.jsx",
      "resources/js/Pages/Profile/Partials/DeleteUserForm.jsx",
      "resources/js/Pages/Profile/Partials/UpdatePasswordForm.jsx",
      "resources/js/Pages/Profile/Partials/UpdateProfileInformationForm.jsx",
      "resources/js/Pages/Welcome.jsx"
    ],
    "css": [
      "assets/app-B72v7_uJ.css"
    ]
  }
}
```


***File: public\build\assets\ApplicationLogo-DPlTNKJi.js***


```
import{j as C}from"./app-BrYB81S6.js";function o(L){return C.jsx("svg",{...L,viewBox:"0 0 316 316",xmlns:"http://www.w3.org/2000/svg",children:C.jsx("path",{d:"M305.8 81.125C3
```

### File: public\build\assets\AuthenticatedLayout-CgjTH9WJ.js

```
import{r as a,j as e,L as l,a as h}from"./app-BrYB81S6.js";import{A as g}from"./ApplicationLogo-DPlTNKJi.js";import{K as p}from"./transition-C95k0J7b.js";const u=a.createConte
```

### File: public\build\assets\ConfirmPassword-CBzEM5GG.js

```
import{u as d,j as s,H as l}from"./app-BrYB81S6.js";import{T as p,I as u}from"./TextInput-Ca7FXA7z.js";import{I as c}from"./InputLabel-DBG7MFZr.js";import{P as f}from"./Primar
```

### File: public\build\assets\Dashboard-DhQTk4Fy.js

```
import{j as e,H as a}from"./app-BrYB81S6.js";import{A as s}from"./AuthenticatedLayout-CgjTH9WJ.js";import"./ApplicationLogo-DPlTNKJi.js";import"./transition-C95k0J7b.js";funct
```

### File: public\build\assets\DeleteUserForm-_uihPTB7.js

```
import{r as s,G as p,b as Ft,c as Tt,j as g,u as kt}from"./app-BrYB81S6.js";import{T as Ct,I as Nt}from"./TextInput-Ca7FXA7z.js";import{I as Ot}from"./InputLabel-DBG7MFZr.js";
```

(Content truncated due to size - showing first 15KB)

### File: public\build\assets\Edit-QYlRHcro.js

```
import{j as s,H as m}from"./app-BrYB81S6.js";import{A as r}from"./AuthenticatedLayout-CgjTH9WJ.js";import t from"./DeleteUserForm-_uihPTB7.js";import i from"./UpdatePasswordFo
```

### File: public\build\assets\ForgotPassword-U49R6K9z.js

```
import{u as n,j as e,H as d}from"./app-BrYB81S6.js";import{T as u,I as c}from"./TextInput-Ca7FXA7z.js";import{P as x}from"./PrimaryButton-Bb5G6Hn1.js";import{G as p}from"./Gue
```

### File: public\build\assets\GuestLayout-CAQ5aVTJ.js

```
import{j as e,L as t}from"./app-BrYB81S6.js";import{A as r}from"./ApplicationLogo-DPlTNKJi.js";function a({children:s}){return e.jsxs("div",{className:"flex min-h-screen flex-
```

### File: public\build\assets\InputLabel-DBG7MFZr.js

```
import{j as m}from"./app-BrYB81S6.js";function o({value:t,className:e="",children:r,...s}){return m.jsx("label",{...s,className:"block text-sm font-medium text-gray-700 "+e,ch
```

### File: public\build\assets\Login-BWVoa2Gg.js

```
import{j as e,u as p,H as f,L as g}from"./app-BrYB81S6.js";import{T as i,I as n}from"./TextInput-Ca7FXA7z.js";import{I as l}from"./InputLabel-DBG7MFZr.js";import{P as h}from"
```

### File: public\build\assets\PrimaryButton-Bb5G6Hn1.js

```
import{j as n}from"./app-BrYB81S6.js";function s({className:r="",disabled:t,children:e,...o}){return n.jsx("button",{...o,className:`inline-flex items-center rounded-md borde
```

### File: public\build\assets\Register-CeqRc_bm.js

```
import{u as c,j as e,H as p,L as f}from"./app-BrYB81S6.js";import{T as o,I as m}from"./TextInput-Ca7FXA7z.js";import{I as i}from"./InputLabel-DBG7MFZr.js";import{P as x}from"
```

### File: public\build\assets\ResetPassword-DFOL_bTT.js

```
import{u as w,j as s,H as f}from"./app-BrYB81S6.js";import{T as t,I as m}from"./TextInput-Ca7FXA7z.js";import{I as i}from"./InputLabel-DBG7MFZr.js";import{P as x}from"./Primar
```

### File: public\build\assets\TextInput-Ca7FXA7z.js

```
import{j as u,r}from"./app-BrYB81S6.js";function i({message:e,className:t="",...n}){return e?u.jsx("p",{...n,className:"text-sm text-red-600 "+t,children:e}):null}const d=r.fo
```

### File: public\build\assets\transition-C95k0J7b.js

```
import{r as i,G as b,t as oe}from"./app-BrYB81S6.js";var Re=Object.defineProperty,Ne=(e,t,n)=>t in e?Re(e,t,{enumerable:!0,configurable:!0,writable:!0,value:n}):e[t]=n,W=(e,t,
`),"","You can apply a few solutions:",['Add an `as="..."` prop, to ensure that we render an actual element instead of a "Fragment".','Render a single element as the child so
`)].join(`
`))}else{let g=f.props,d=g?.className,c=typeof d=="function"?(...E)=>J(d(...E),s.className):J(d,s.className),v=c?{className:c}:{},m=ve(f.props,A(X(s,["ref"])));for(let E in h
`)),[]});var qe=(e=>(e[e.None=0]="None",e[e.Closed=1]="Closed",e[e.Enter=2]="Enter",e[e.Leave=4]="Leave",e))(qe||{});function Ke(e){let t={};for(let n in e)e[n]===!0&&(t[`data
```

### File: public\build\assets\UpdatePasswordForm-CT4sSwFX.js

```
import{r as l,u as h,j as s}from"./app-BrYB81S6.js";import{T as n,I as d}from"./TextInput-Ca7FXA7z.js";import{I as c}from"./InputLabel-DBG7MFZr.js";import{P as v}from"./Primar
```

### File: public\build\assets\UpdateProfileInformationForm-BGrbu5sz.js

```
import{a as h,u as j,j as e,L as v}from"./app-BrYB81S6.js";import{T as n,I as m}from"./TextInput-Ca7FXA7z.js";import{I as o}from"./InputLabel-DBG7MFZr.js";import{P as g}from"
```

### File: public\build\assets\VerifyEmail-D4TVxu0c.js

```
import{u as r,j as e,H as a,L as d}from"./app-BrYB81S6.js";import{P as u}from"./PrimaryButton-Bb5G6Hn1.js";import{G as l}from"./GuestLayout-CAQ5aVTJ.js";import"./ApplicationLo
```

### File: public\build\assets\Welcome-CoLzhMiE.js

```
import{j as e,H as l,L as s}from"./app-BrYB81S6.js";function o({auth:a,laravelVersion:r,phpVersion:t}){const i=()=>{document.getElementById("screenshot-container")?.classList.
```

(Content truncated due to size - showing first 15KB)

### File: resources\js\app.jsx

```
import '../css/app.css';
import './bootstrap';

import { createInertiaApp } from '@inertiajs/react';
import { resolvePageComponent } from 'laravel-vite-plugin/inertia-helpers';
import { createRoot } from 'react-dom/client';

const appName = import.meta.env.VITE_APP_NAME || 'Laravel';

createInertiaApp({
    title: (title) => `${title} - ${appName}`,
    resolve: (name) =>
        resolvePageComponent(
            `./Pages/${name}.jsx`,
            import.meta.glob('./Pages/**/*.jsx'),
        ),
    setup({ el, App, props }) {
        const root = createRoot(el);

        root.render(<App {...props} />);
    },
    progress: {
        color: '#4B5563',
    },
});
```

### File: resources\js\bootstrap.js

```
import axios from 'axios';
window.axios = axios;

window.axios.defaults.headers.common['X-Requested-With'] = 'XMLHttpRequest';
```

### File: resources\js\Components\ApplicationLogo.jsx

```
export default function ApplicationLogo(props) {
    return (
        <svg
            {...props}
            viewBox="0 0 316 316"
            xmlns="http://www.w3.org/2000/svg"
        >
            <path d="M305.8 81.125C305.77 80.995 305.69 80.885 305.65 80.755C305.56 80.525 305.49 80.285 305.37 80.075C305.29 79.935 305.17 79.815 305.07 79.685C304.94 79.515
        </svg>
    );
}
```

### File: resources\js\Components\Checkbox.jsx

```
export default function Checkbox({ className = '', ...props }) {
    return (
        <input
            {...props}
            type="checkbox"
            className={
                'rounded border-gray-300 text-indigo-600 shadow-sm focus:ring-indigo-500 ' +
                className
            }
        />
    );
}
```

### File: resources\js\Components\DangerButton.jsx

```
export default function DangerButton({
    className = '',
    disabled,
    children,
    ...props
}) {
    return (
        <button
            {...props}
            className={
                `inline-flex items-center rounded-md border border-transparent bg-red-600 px-4 py-2 text-xs font-semibold uppercase tracking-widest text-white transition durat
                    disabled && 'opacity-25'
                } ` + className
            }
            disabled={disabled}
        >
            {children}
        </button>
    );
}
```

### File: resources\js\Components\Dropdown.jsx

```
import { Transition } from '@headlessui/react';
import { Link } from '@inertiajs/react';
import { createContext, useContext, useState } from 'react';

const DropDownContext = createContext();

const Dropdown = ({ children }) => {
    const [open, setOpen] = useState(false);

    const toggleOpen = () => {
        setOpen((previousState) => !previousState);
    };

    return (
        <DropDownContext.Provider value={{ open, setOpen, toggleOpen }}>
            <div className="relative">{children}</div>
        </DropDownContext.Provider>
    );
```

```
};

const Trigger = ({ children }) => {
    const { open, setOpen, toggleOpen } = useContext(DropDownContext);

    return (
        <>
            <div onClick={toggleOpen}>{children}</div>

            {open && (
                <div
                    className="fixed inset-0 z-40"
                    onClick={() => setOpen(false)}
                ></div>
            )}
        </>
    );
};

const Content = ({
    align = 'right',
    width = '48',
    contentClasses = 'py-1 bg-white',
    children,
}) => {
    const { open, setOpen } = useContext(DropDownContext);

    let alignmentClasses = 'origin-top';

    if (align === 'left') {
        alignmentClasses = 'ltr:origin-top-left rtl:origin-top-right start-0';
    } else if (align === 'right') {
        alignmentClasses = 'ltr:origin-top-right rtl:origin-top-left end-0';
    }

    let widthClasses = '';

    if (width === '48') {
        widthClasses = 'w-48';
    }

    return (
        <>
            <Transition
                show={open}
                enter="transition ease-out duration-200"
                enterFrom="opacity-0 scale-95"
                enterTo="opacity-100 scale-100"
                leave="transition ease-in duration-75"
                leaveFrom="opacity-100 scale-100"
                leaveTo="opacity-0 scale-95"
            >
                <div
                    className={`absolute z-50 mt-2 rounded-md shadow-lg ${alignmentClasses} ${widthClasses}`}
                    onClick={() => setOpen(false)}
                >
                    <div
                        className={
                            `rounded-md ring-1 ring-black ring-opacity-5 ` +
                            contentClasses
                        }
                    >
                        {children}
                    </div>
                </div>
            </Transition>
        </>
    );
};

const DropdownLink = ({ className = '', children, ...props }) => {
    return (
        <Link
            {...props}
            className={
                'block w-full px-4 py-2 text-start text-sm leading-5 text-gray-700 transition duration-150 ease-in-out hover:bg-gray-100 focus:bg-gray-100 focus:outline-none
                className
            }
        >
            {children}
        </Link>
    );
};

Dropdown.Trigger = Trigger;
Dropdown.Content = Content;
Dropdown.Link = DropdownLink;

export default Dropdown;
```

### *File: resources\js\Components\InputError.jsx*

```
export default function InputError({ message, className = '', ...props }) {
    return message ? (
        <p
            {...props}
            className={'text-sm text-red-600 ' + className}
        >
            {message}
        </p>
    ) : null;
}
```

### *File: resources\js\Components\InputLabel.jsx*

```
export default function InputLabel({
    value,
    className = '',
    children,
    ...props
}) {
    return (
        <label
            {...props}
            className={
                `block text-sm font-medium text-gray-700 ` +
                className
            }
        >
            {value ? value : children}
        </label>
    );
}
```

***File: resources\js\Components\Modal.jsx***

```
import {
    Dialog,
    DialogPanel,
    Transition,
    TransitionChild,
} from '@headlessui/react';

export default function Modal({
    children,
    show = false,
    maxWidth = '2xl',
    closeable = true,
    onClose = () => {},
}) {
    const close = () => {
        if (closeable) {
            onClose();
        }
    };

    const maxWidthClass = {
        sm: 'sm:max-w-sm',
        md: 'sm:max-w-md',
        lg: 'sm:max-w-lg',
        xl: 'sm:max-w-xl',
        '2xl': 'sm:max-w-2xl',
    }[maxWidth];

    return (
        <Transition show={show} leave="duration-200">
            <Dialog
                as="div"
                id="modal"
                className="fixed inset-0 z-50 flex transform items-center overflow-y-auto px-4 py-6 transition-all sm:px-0"
                onClose={close}
            >
                <TransitionChild
                    enter="ease-out duration-300"
                    enterFrom="opacity-0"
                    enterTo="opacity-100"
                    leave="ease-in duration-200"
                    leaveFrom="opacity-100"
                    leaveTo="opacity-0"
                >
                    <div className="absolute inset-0 bg-gray-500/75" />
                </TransitionChild>

                <TransitionChild
                    enter="ease-out duration-300"
                    enterFrom="opacity-0 translate-y-4 sm:translate-y-0 sm:scale-95"
                    enterTo="opacity-100 translate-y-0 sm:scale-100"
                    leave="ease-in duration-200"
                    leaveFrom="opacity-100 translate-y-0 sm:scale-100"
                    leaveTo="opacity-0 translate-y-4 sm:translate-y-0 sm:scale-95"
                >
                    <DialogPanel
                        className={`mb-6 transform overflow-hidden rounded-lg bg-white shadow-xl transition-all sm:mx-auto sm:w-full ${maxWidthClass}`}
                    >
                        {children}
                    </DialogPanel>
                </TransitionChild>
            </Dialog>
        </Transition>
    );
}
```

### File: resources\js\Components\NavLink.jsx

```
import { Link } from '@inertiajs/react';

export default function NavLink({
    active = false,
    className = '',
    children,
    ...props
}) {
    return (
        <Link
            {...props}
            className={
                'inline-flex items-center border-b-2 px-1 pt-1 text-sm font-medium leading-5 transition duration-150 ease-in-out focus:outline-none ' +
                (active
                    ? 'border-indigo-400 text-gray-900 focus:border-indigo-700'
                    : 'border-transparent text-gray-500 hover:border-gray-300 hover:text-gray-700 focus:border-gray-300 focus:text-gray-700') +
                className
            }
        >
            {children}
        </Link>
    );
}
```

### File: resources\js\Components\PrimaryButton.jsx

```
export default function PrimaryButton({
    className = '',
    disabled,
    children,
    ...props
}) {
    return (
        <button
            {...props}
            className={
                `inline-flex items-center rounded-md border border-transparent bg-gray-800 px-4 py-2 text-xs font-semibold uppercase tracking-widest text-white transition dura
                    disabled && 'opacity-25'
                } ` + className
            }
            disabled={disabled}
        >
            {children}
        </button>
    );
}
```

### File: resources\js\Components\ResponsiveNavLink.jsx

```
import { Link } from '@inertiajs/react';

export default function ResponsiveNavLink({
    active = false,
    className = '',
    children,
    ...props
}) {
    return (
        <Link
            {...props}
            className={`flex w-full items-start border-l-4 py-2 pe-4 ps-3 ${
                active
                    ? 'border-indigo-400 bg-indigo-50 text-indigo-700 focus:border-indigo-700 focus:bg-indigo-100 focus:text-indigo-800'
                    : 'border-transparent text-gray-600 hover:border-gray-300 hover:bg-gray-50 hover:text-gray-800 focus:border-gray-300 focus:bg-gray-50 focus:text-gray-800'
            } text-base font-medium transition duration-150 ease-in-out focus:outline-none ${className}`}
        >
            {children}
        </Link>
    );
}
```

### File: resources\js\Components\SecondaryButton.jsx

```
export default function SecondaryButton({
    type = 'button',
    className = '',
    disabled,
    children,
    ...props
}) {
    return (
        <button
            {...props}
            type={type}
            className={
                `inline-flex items-center rounded-md border border-gray-300 bg-white px-4 py-2 text-xs font-semibold uppercase tracking-widest text-gray-700 shadow-sm transiti
                    disabled && 'opacity-25'
                } ` + className
            }
            disabled={disabled}
        >
            {children}
        </button>
    );
}
```

### File: resources\js\Components\TextInput.jsx

```
import { forwardRef, useEffect, useImperativeHandle, useRef } from 'react';

export default forwardRef(function TextInput(
    { type = 'text', className = '', isFocused = false, ...props },
    ref,
) {
    const localRef = useRef(null);

    useImperativeHandle(ref, () => ({
        focus: () => localRef.current?.focus(),
    }));

    useEffect(() => {
        if (isFocused) {
            localRef.current?.focus();
        }
    }, [isFocused]);
    return (
```

```
        <input
            {...props}
            type={type}
            className={
                'rounded-md border-gray-300 shadow-sm focus:border-indigo-500 focus:ring-indigo-500 ' +
                className
            }
            ref={localRef}
        />
    );
});
```

### File: resources\js\Layouts\AuthenticatedLayout.jsx

```
import ApplicationLogo from '@/Components/ApplicationLogo';
import Dropdown from '@/Components/Dropdown';
import NavLink from '@/Components/NavLink';
import ResponsiveNavLink from '@/Components/ResponsiveNavLink';
import { Link, usePage } from '@inertiajs/react';
import { useState } from 'react';

export default function AuthenticatedLayout({ header, children }) {
    const user = usePage().props.auth.user;

    const [showingNavigationDropdown, setShowingNavigationDropdown] =
        useState(false);

    return (
        <div className="min-h-screen bg-gray-100">
            <nav className="border-b border-gray-100 bg-white">
                <div className="mx-auto max-w-7xl px-4 sm:px-6 lg:px-8">
                    <div className="flex h-16 justify-between">
                        <div className="flex">
                            <div className="flex shrink-0 items-center">
                                <Link href="/">
                                    <ApplicationLogo className="block h-9 w-auto fill-current text-gray-800" />
                                </Link>
                            </div>

                            <div className="hidden space-x-8 sm:-my-px sm:ms-10 sm:flex">
                                <NavLink
                                    href={route('dashboard')}
                                    active={route().current('dashboard')}
                                >
                                    Dashboard
                                </NavLink>
                            </div>
                        </div>

                        <div className="hidden sm:ms-6 sm:flex sm:items-center">
                            <div className="relative ms-3">
                                <Dropdown>
                                    <Dropdown.Trigger>
                                        <span className="inline-flex rounded-md">
                                            <button
                                                type="button"
                                                className="inline-flex items-center rounded-md border border-transparent bg-white px-3 py-2 text-sm font-medium leading-4 text-
                                            >
                                                {user.name}

                                                <svg
                                                    className="-me-0.5 ms-2 h-4 w-4"
                                                    xmlns="http://www.w3.org/2000/svg"
                                                    viewBox="0 0 20 20"
                                                    fill="currentColor"
                                                >
                                                    <path
                                                        fillRule="evenodd"
                                                        d="M5.293 7.293a1 1 0 011.414 0L10 10.586l3.293-3.293a1 1 0 111.414 1.414l-4 4a1 1 0 01-1.414 0l-4-4a1 1 0 010-1.414z"
                                                        clipRule="evenodd"
                                                    />
                                                </svg>
                                            </button>
                                        </span>
                                    </Dropdown.Trigger>

                                    <Dropdown.Content>
                                        <Dropdown.Link
                                            href={route('profile.edit')}
                                        >
                                            Profile
                                        </Dropdown.Link>
                                        <Dropdown.Link
                                            href={route('logout')}
                                            method="post"
                                            as="button"
                                        >
                                            Log Out
                                        </Dropdown.Link>
                                    </Dropdown.Content>
                                </Dropdown>
                            </div>
                        </div>

                        <div className="-me-2 flex items-center sm:hidden">
                            <button
                                onClick={() =>
                                    setShowingNavigationDropdown(
                                        (previousState) => !previousState,
                                    )
                                }
                                className="inline-flex items-center justify-center rounded-md p-2 text-gray-400 transition duration-150 ease-in-out hover:bg-gray-100 hover:tex
                            >
                                <svg
                                    className="h-6 w-6"
                                    stroke="currentColor"
                                    fill="none"
                                    viewBox="0 0 24 24"
                                >
                                    <path
                                        className={
                                            !showingNavigationDropdown
                                                ? 'inline-flex'
                                                : 'hidden'
                                        }
                                        strokeLinecap="round"
                                        strokeLinejoin="round"
                                        strokeWidth="2"
                                        d="M4 6h16M4 12h16M4 18h16"
                                    />
                                    <path
                                        className={
                                            showingNavigationDropdown
                                                ? 'inline-flex'
                                                : 'hidden'
```

```
                                        }
                                        strokeLinecap="round"
                                        strokeLinejoin="round"
                                        strokeWidth="2"
                                        d="M6 18L18 6M6 6l12 12"
                                    />
                                </svg>
                            </button>
                        </div>
                    </div>
                </div>

                <div
                    className={
                        (showingNavigationDropdown ? 'block' : 'hidden') +
                        ' sm:hidden'
                    }
                >
                    <div className="space-y-1 pb-3 pt-2">
                        <ResponsiveNavLink
                            href={route('dashboard')}
                            active={route().current('dashboard')}
                        >
                            Dashboard
                        </ResponsiveNavLink>
                    </div>

                    <div className="border-t border-gray-200 pb-1 pt-4">
                        <div className="px-4">
                            <div className="text-base font-medium text-gray-800">
                                {user.name}
                            </div>
                            <div className="text-sm font-medium text-gray-500">
                                {user.email}
                            </div>
                        </div>

                        <div className="mt-3 space-y-1">
                            <ResponsiveNavLink href={route('profile.edit')}>
                                Profile
                            </ResponsiveNavLink>
                            <ResponsiveNavLink
                                method="post"
                                href={route('logout')}
                                as="button"
                            >
                                Log Out
                            </ResponsiveNavLink>
                        </div>
                    </div>
                </div>
            </nav>

            {header && (
                <header className="bg-white shadow">
                    <div className="mx-auto max-w-7xl px-4 py-6 sm:px-6 lg:px-8">
                        {header}
                    </div>
                </header>
            )}

            <main>{children}</main>
        </div>
    );
}
```

### File: resources\js\Layouts\GuestLayout.jsx

```
import ApplicationLogo from '@/Components/ApplicationLogo';
import { Link } from '@inertiajs/react';

export default function GuestLayout({ children }) {
    return (
        <div className="flex min-h-screen flex-col items-center bg-gray-100 pt-6 sm:justify-center sm:pt-0">
            <div>
                <Link href="/">
                    <ApplicationLogo className="h-20 w-20 fill-current text-gray-500" />
                </Link>
            </div>

            <div className="mt-6 w-full overflow-hidden bg-white px-6 py-4 shadow-md sm:max-w-md sm:rounded-lg">
                {children}
            </div>
        </div>
    );
}
```

### File: resources\js\Pages\Auth\ConfirmPassword.jsx

```
import InputError from '@/Components/InputError';
import InputLabel from '@/Components/InputLabel';
import PrimaryButton from '@/Components/PrimaryButton';
import TextInput from '@/Components/TextInput';
import GuestLayout from '@/Layouts/GuestLayout';
import { Head, useForm } from '@inertiajs/react';

export default function ConfirmPassword() {
    const { data, setData, post, processing, errors, reset } = useForm({
        password: '',
    });

    const submit = (e) => {
        e.preventDefault();

        post(route('password.confirm'), {
            onFinish: () => reset('password'),
        });
    };

    return (
        <GuestLayout>
            <Head title="Confirm Password" />

            <div className="mb-4 text-sm text-gray-600">
                This is a secure area of the application. Please confirm your
                password before continuing.
            </div>

            <form onSubmit={submit}>
                <div className="mt-4">
                    <InputLabel htmlFor="password" value="Password" />

                    <TextInput
```

```
                        id="password"
                        type="password"
                        name="password"
                        value={data.password}
                        className="mt-1 block w-full"
                        isFocused={true}
                        onChange={(e) => setData('password', e.target.value)}
                    />

                    <InputError message={errors.password} className="mt-2" />
                </div>

                <div className="mt-4 flex items-center justify-end">
                    <PrimaryButton className="ms-4" disabled={processing}>
                        Confirm
                    </PrimaryButton>
                </div>
            </form>
        </GuestLayout>
    );
}
```

### File: resources\js\Pages\Auth\ForgotPassword.jsx

```
import InputError from '@/Components/InputError';
import PrimaryButton from '@/Components/PrimaryButton';
import TextInput from '@/Components/TextInput';
import GuestLayout from '@/Layouts/GuestLayout';
import { Head, useForm } from '@inertiajs/react';

export default function ForgotPassword({ status }) {
    const { data, setData, post, processing, errors } = useForm({
        email: '',
    });

    const submit = (e) => {
        e.preventDefault();

        post(route('password.email'));
    };

    return (
        <GuestLayout>
            <Head title="Forgot Password" />

            <div className="mb-4 text-sm text-gray-600">
                Forgot your password? No problem. Just let us know your email
                address and we will email you a password reset link that will
                allow you to choose a new one.
            </div>

            {status && (
                <div className="mb-4 text-sm font-medium text-green-600">
                    {status}
                </div>
            )}

            <form onSubmit={submit}>
                <TextInput
                    id="email"
                    type="email"
                    name="email"
                    value={data.email}
                    className="mt-1 block w-full"
                    isFocused={true}
                    onChange={(e) => setData('email', e.target.value)}
                />

                <InputError message={errors.email} className="mt-2" />

                <div className="mt-4 flex items-center justify-end">
                    <PrimaryButton className="ms-4" disabled={processing}>
                        Email Password Reset Link
                    </PrimaryButton>
                </div>
            </form>
        </GuestLayout>
    );
}
```

### File: resources\js\Pages\Auth\Login.jsx

```
import Checkbox from '@/Components/Checkbox';
import InputError from '@/Components/InputError';
import InputLabel from '@/Components/InputLabel';
import PrimaryButton from '@/Components/PrimaryButton';
import TextInput from '@/Components/TextInput';
import GuestLayout from '@/Layouts/GuestLayout';
import { Head, Link, useForm } from '@inertiajs/react';

export default function Login({ status, canResetPassword }) {
    const { data, setData, post, processing, errors, reset } = useForm({
        email: '',
        password: '',
        remember: false,
    });

    const submit = (e) => {
        e.preventDefault();

        post(route('login'), {
            onFinish: () => reset('password'),
        });
    };

    return (
        <GuestLayout>
            <Head title="Log in" />

            {status && (
                <div className="mb-4 text-sm font-medium text-green-600">
                    {status}
                </div>
            )}

            <form onSubmit={submit}>
                <div>
                    <InputLabel htmlFor="email" value="Email" />

                    <TextInput
                        id="email"
                        type="email"
                        name="email"
```

```
                    value={data.email}
                    className="mt-1 block w-full"
                    autoComplete="username"
                    isFocused={true}
                    onChange={(e) => setData('email', e.target.value)}
                />

                <InputError message={errors.email} className="mt-2" />
            </div>

            <div className="mt-4">
                <InputLabel htmlFor="password" value="Password" />

                <TextInput
                    id="password"
                    type="password"
                    name="password"
                    value={data.password}
                    className="mt-1 block w-full"
                    autoComplete="current-password"
                    onChange={(e) => setData('password', e.target.value)}
                />

                <InputError message={errors.password} className="mt-2" />
            </div>

            <div className="mt-4 block">
                <label className="flex items-center">
                    <Checkbox
                        name="remember"
                        checked={data.remember}
                        onChange={(e) =>
                            setData('remember', e.target.checked)
                        }
                    />
                    <span className="ms-2 text-sm text-gray-600">
                        Remember me
                    </span>
                </label>
            </div>

            <div className="mt-4 flex items-center justify-end">
                {canResetPassword && (
                    <Link
                        href={route('password.request')}
                        className="rounded-md text-sm text-gray-600 underline hover:text-gray-900 focus:outline-none focus:ring-2 focus:ring-indigo-500 focus:ring-offset-2
                    >
                        Forgot your password?
                    </Link>
                )}

                <PrimaryButton className="ms-4" disabled={processing}>
                    Log in
                </PrimaryButton>
            </div>
        </form>
    </GuestLayout>
);
}
```

## File: resources\js\Pages\Auth\Register.jsx

```
import { useState, useEffect } from 'react';
import { Head, Link, useForm } from '@inertiajs/react';
import InputError from '@/Components/InputError';
import InputLabel from '@/Components/InputLabel';
import PrimaryButton from '@/Components/PrimaryButton';
import TextInput from '@/Components/TextInput';

export default function Register() {
    const { data, setData, post, processing, errors, reset } = useForm({
        name: '',
        email: '',
        password: '',
        password_confirmation: '',
        account_type: 'customer',
        terms: false,
    });

    const [showPassword, setShowPassword] = useState(false);
    const [showConfirmPassword, setShowConfirmPassword] = useState(false);
    const [passwordStrength, setPasswordStrength] = useState({ percentage: 0, text: '', color: 'rgba(91,76,255,0.15)' });
    const [fieldErrors, setFieldErrors] = useState({ name: '', email: '', password: '', password_confirmation: '', terms: '' });
    const [formProgress, setFormProgress] = useState(1);

    useEffect(() => {
        if (data.password) {
            let strength = 0;
            if (data.password.length >= 8) strength++;
            if (data.password.length >= 12) strength++;
            if (/[a-z]/.test(data.password)) strength++;
            if (/[A-Z]/.test(data.password)) strength++;
            if (/[0-9]/.test(data.password)) strength++;
            if (/[^a-zA-Z0-9]/.test(data.password)) strength++;
            const pct = Math.min((strength / 6) * 100, 100);
            if (strength <= 2) setPasswordStrength({ percentage: pct, text: 'Weak', color: '#ff4d6d' });
            else if (strength <= 4) setPasswordStrength({ percentage: pct, text: 'Fair', color: '#f5b042' });
            else setPasswordStrength({ percentage: pct, text: 'Strong', color: '#00c98b' });
        } else {
            setPasswordStrength({ percentage: 0, text: '', color: 'rgba(91,76,255,0.15)' });
        }
    }, [data.password]);

    useEffect(() => {
        const fields = ['name', 'email', 'password', 'password_confirmation'];
        const filled = fields.filter(f => data[f] && data[f].trim() !== '').length;
        setFormProgress(Math.min(Math.ceil((filled / fields.length) * 3), 3) || 1);
    }, [data]);

    const validateName = (v) => {
        if (!/^[a-zA-Z0-9_]{3,20}$/.test(v)) {
            setFieldErrors(p => ({ ...p, name: 'Username must be 3–20 characters: letters, numbers, underscores only' }));
            return false;
        }
        setFieldErrors(p => ({ ...p, name: '' }));
        return true;
    };

    const validateEmail = (v) => {
        if (!/^[^\s@]+@[^\s@]+\.[^\s@]+$/.test(v)) {
            setFieldErrors(p => ({ ...p, email: 'Please enter a valid email address' }));
            return false;
        }
        setFieldErrors(p => ({ ...p, email: '' }));
        return true;
    };

    const validatePassword = (v) => {
        if (!/^(?=.*[a-z])(?=.*[A-Z])(?=.*\d).{8,}$/.test(v)) {
            setFieldErrors(p => ({ ...p, password: 'Min 8 chars with uppercase, lowercase & number' }));
            return false;
        }
        setFieldErrors(p => ({ ...p, password: '' }));
        return true;
    };

    const validateMatch = (pw, cpw) => {
        if (pw !== cpw) {
            setFieldErrors(p => ({ ...p, password_confirmation: 'Passwords do not match' }));
            return false;
        }
        setFieldErrors(p => ({ ...p, password_confirmation: '' }));
        return true;
    };

    const submit = (e) => {
        e.preventDefault();
        const ok = [
            validateName(data.name),
            validateEmail(data.email),
            validatePassword(data.password),
            validateMatch(data.password, data.password_confirmation),
        ].every(Boolean);
        if (!data.terms) {
            setFieldErrors(p => ({ ...p, terms: 'You must agree to the Terms & Privacy Policy' }));
            return;
        }
        if (ok) post(route('register'), { onFinish: () => reset('password', 'password_confirmation') });
    };

    const fieldState = (field) => {
        if (!data[field]) return '';
        return fieldErrors[field] ? 'err' : 'ok';
    };

    const benefits = [
        { icon: 'bi-book-half',        text: 'Access thousands of books across all partner stores' },
        { icon: 'bi-arrow-repeat',     text: 'Rent affordably or buy to own — your choice' },
        { icon: 'bi-shield-check',     text: 'Bank-level security & encrypted checkout' },
        { icon: 'bi-bell',             text: 'Personalized recommendations & reading lists' },
        { icon: 'bi-headset',          text: '24/7 customer support, always here for you' },
        { icon: 'bi-phone',            text: 'Read on any device, anywhere, anytime' },
    ];

    return (
        <>
            <Head title="Create Account — BookHub" />
            <link rel="preconnect" href="https://fonts.googleapis.com" />
            <link href="https://fonts.googleapis.com/css2?family=Outfit:wght@300;400;500;600;700;800;900&display=swap" rel="stylesheet" />
            <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.11.3/font/bootstrap-icons.min.css" />

            <style>{`
                *, *::before, *::after { box-sizing: border-box; margin: 0; padding: 0; }

                /* ■■ full-screen override — kills GuestLayout chrome ■■ */
                body, #app, #app > div { margin: 0 !important; padding: 0 !important; background: #0c0a1a !important; }
                .rp-root {
```

```
    font-family: 'Outfit', system-ui, sans-serif;
    display: flex;
    min-height: 100vh;
    width: 100%;
    -webkit-font-smoothing: antialiased;
}

/* ═══════════════════════════════
   LEFT PANEL
═══════════════════════════════ */
.rp-left {
    width: 42%;
    min-height: 100vh;
    background: linear-gradient(155deg, #0f1a3a 0%, #1a1050 48%, #0d1030 100%);
    position: relative;
    overflow: hidden;
    display: flex;
    flex-direction: column;
    justify-content: center;
    padding: 3.5rem 3rem;
}

.rp-left::before {
    content: '';
    position: absolute; inset: 0; pointer-events: none;
    background:
        radial-gradient(ellipse 80% 60% at 10% -10%, rgba(91,76,255,0.55) 0%, transparent 55%),
        radial-gradient(ellipse 55% 50% at 90% 110%, rgba(245,176,66,0.22) 0%, transparent 55%);
}

.rp-ring {
    position: absolute; border-radius: 50%; pointer-events: none;
    border: 1px solid rgba(255,255,255,0.06);
}
.rp-ring-1 { width: 480px; height: 480px; top: -180px; right: -180px; }
.rp-ring-2 { width: 300px; height: 300px; bottom: -120px; left: -80px; border-color: rgba(245,176,66,0.07); }
.rp-ring-3 { width: 160px; height: 160px; top: 38%; left: 6%; border-color: rgba(91,76,255,0.2); }

.rp-left-inner { position: relative; z-index: 1; }

.rp-brand {
    display: flex; align-items: center; gap: 0.65rem;
    text-decoration: none; margin-bottom: 2.8rem;
}
.rp-brand-icon {
    width: 42px; height: 42px; border-radius: 12px;
    background: linear-gradient(135deg, #5b4cff 0%, #3d2fe0 100%);
    display: flex; align-items: center; justify-content: center;
    font-size: 1.1rem; color: #fff;
    box-shadow: 0 4px 18px rgba(91,76,255,0.45);
}
.rp-brand-text {
    font-size: 1.15rem; font-weight: 800;
    color: #fff; letter-spacing: -0.02em;
}
.rp-brand-text span { color: #f5b042; }

.rp-eyebrow {
    display: inline-flex; align-items: center; gap: 0.5rem;
    padding: 0.3rem 0.9rem; border-radius: 999px;
    background: rgba(255,255,255,0.10); border: 1px solid rgba(255,255,255,0.18);
    font-size: 0.7rem; font-weight: 700; text-transform: uppercase;
    letter-spacing: 1.1px; color: #f5b042;
    margin-bottom: 1.2rem;
}
.rp-dot {
    width: 6px; height: 6px; border-radius: 50%; background: #00c98b;
    box-shadow: 0 0 0 3px rgba(0,201,139,0.25);
    animation: blink 2s ease-in-out infinite;
}
@keyframes blink { 0%,100%{opacity:1} 50%{opacity:0.3} }

.rp-left h1 {
    font-size: clamp(1.9rem, 3vw, 2.8rem); font-weight: 900;
    color: #fff; line-height: 1.1; letter-spacing: -0.035em;
    margin-bottom: 1rem;
}
.rp-left h1 em { font-style: normal; color: #f5b042; }

.rp-left > .rp-left-inner > p {
    font-size: 0.95rem; color: rgba(255,255,255,0.5);
    line-height: 1.7; margin-bottom: 2.5rem; max-width: 340px;
}

.rp-benefits-title {
    font-size: 0.7rem; font-weight: 800; text-transform: uppercase;
    letter-spacing: 1.2px; color: rgba(255,255,255,0.4);
    margin-bottom: 1rem;
}

.rp-benefits { display: flex; flex-direction: column; gap: 0.7rem; }

.rp-benefit {
    display: flex; align-items: center; gap: 0.85rem;
    padding: 0.75rem 1rem; border-radius: 12px;
    background: rgba(255,255,255,0.06);
    border: 1px solid rgba(255,255,255,0.09);
    backdrop-filter: blur(6px);
    transition: background 200ms;
}
.rp-benefit:hover { background: rgba(255,255,255,0.10); }

.rp-benefit-icon {
    width: 34px; height: 34px; border-radius: 9px; flex-shrink: 0;
    background: rgba(91,76,255,0.25); border: 1px solid rgba(91,76,255,0.35);
    display: flex; align-items: center; justify-content: center;
    font-size: 0.95rem; color: #9b8fff;
}
.rp-benefit span {
    font-size: 0.82rem; color: rgba(255,255,255,0.65);
    font-weight: 500; line-height: 1.4;
}

/* ═══════════════════════════════
   RIGHT PANEL
═══════════════════════════════ */
.rp-right {
    flex: 1;
    background: #f5f4ff;
    min-height: 100vh;
    display: flex;
    flex-direction: column;
    overflow-y: auto;
}

.rp-right-top {
    display: flex; align-items: center; justify-content: space-between;
    padding: 1.4rem 2.5rem;
```

```
            border-bottom: 1px solid rgba(91,76,255,0.1);
            background: rgba(255,255,255,0.7);
            backdrop-filter: blur(12px);
            position: sticky; top: 0; z-index: 10;
        }

        .rp-back {
            display: flex; align-items: center; gap: 0.45rem;
            font-size: 0.82rem; font-weight: 700; color: #4e4a64;
            text-decoration: none; padding: 0.42rem 0.9rem;
            border-radius: 999px; border: 1.5px solid rgba(91,76,255,0.18);
            background: rgba(255,255,255,0.8);
            transition: all 180ms;
        }
        .rp-back:hover { color: #5b4cff; border-color: #5b4cff; background: rgba(91,76,255,0.06); }
        .rp-back i { font-size: 0.85rem; }

        .rp-top-login {
            font-size: 0.82rem; color: #8a86a0;
        }
        .rp-top-login a {
            color: #5b4cff; font-weight: 700; text-decoration: none; margin-left: 0.3rem;
        }
        .rp-top-login a:hover { text-decoration: underline; }

        .rp-form-wrap {
            flex: 1;
            display: flex; align-items: flex-start; justify-content: center;
            padding: 2.5rem 2.5rem 3rem;
        }

        .rp-form-inner {
            width: 100%; max-width: 520px;
        }

        /* heading */
        .rp-form-head { margin-bottom: 1.8rem; }
        .rp-form-head h2 {
            font-size: clamp(1.55rem, 2.5vw, 2rem); font-weight: 900;
            color: #14102b; letter-spacing: -0.03em; margin-bottom: 0.35rem;
        }
        .rp-form-head p { font-size: 0.87rem; color: #8a86a0; }

        /* progress */
        .rp-progress {
            display: flex; align-items: center;
            gap: 0; margin-bottom: 2rem;
        }
        .rp-step {
            display: flex; flex-direction: column; align-items: center; gap: 0.35rem;
            flex: 1; position: relative;
        }
        .rp-step::after {
            content: '';
            position: absolute; top: 16px; left: 50%; right: -50%;
            height: 2px; background: rgba(91,76,255,0.15); z-index: 0;
        }
        .rp-step:last-child::after { display: none; }
        .rp-step.active::after { background: rgba(91,76,255,0.4); }

        .rp-step-circle {
            width: 32px; height: 32px; border-radius: 50%; z-index: 1;
            background: rgba(91,76,255,0.12); border: 2px solid rgba(91,76,255,0.2);
            color: #8a86a0; font-size: 0.8rem; font-weight: 800;
            display: flex; align-items: center; justify-content: center;
            transition: all 260ms;
        }
        .rp-step.active .rp-step-circle {
            background: #5b4cff; border-color: #5b4cff;
            color: #fff; box-shadow: 0 4px 14px rgba(91,76,255,0.4);
        }
        .rp-step-label {
            font-size: 0.72rem; font-weight: 700;
            color: #8a86a0; letter-spacing: 0.3px;
        }
        .rp-step.active .rp-step-label { color: #5b4cff; }

        /* server error banner */
        .rp-errors {
```

(Content truncated due to size - showing first 15KB)

## File: resources\js\Pages\Auth\ResetPassword.jsx

```
import InputError from '@/Components/InputError';
import InputLabel from '@/Components/InputLabel';
import PrimaryButton from '@/Components/PrimaryButton';
import TextInput from '@/Components/TextInput';
import GuestLayout from '@/Layouts/GuestLayout';
import { Head, useForm } from '@inertiajs/react';

export default function ResetPassword({ token, email }) {
    const { data, setData, post, processing, errors, reset } = useForm({
        token: token,
        email: email,
        password: '',
        password_confirmation: '',
    });

    const submit = (e) => {
        e.preventDefault();

        post(route('password.store'), {
            onFinish: () => reset('password', 'password_confirmation'),
        });
    };

    return (
        <GuestLayout>
            <Head title="Reset Password" />

            <form onSubmit={submit}>
                <div>
                    <InputLabel htmlFor="email" value="Email" />

                    <TextInput
                        id="email"
                        type="email"
                        name="email"
                        value={data.email}
                        className="mt-1 block w-full"
                        autoComplete="username"
                        onChange={(e) => setData('email', e.target.value)}
                    />
                    <InputError message={errors.email} className="mt-2" />
```

```
                </div>

                <div className="mt-4">
                    <InputLabel htmlFor="password" value="Password" />

                    <TextInput
                        id="password"
                        type="password"
                        name="password"
                        value={data.password}
                        className="mt-1 block w-full"
                        autoComplete="new-password"
                        isFocused={true}
                        onChange={(e) => setData('password', e.target.value)}
                    />

                    <InputError message={errors.password} className="mt-2" />
                </div>

                <div className="mt-4">
                    <InputLabel
                        htmlFor="password_confirmation"
                        value="Confirm Password"
                    />

                    <TextInput
                        type="password"
                        id="password_confirmation"
                        name="password_confirmation"
                        value={data.password_confirmation}
                        className="mt-1 block w-full"
                        autoComplete="new-password"
                        onChange={(e) =>
                            setData('password_confirmation', e.target.value)
                        }
                    />

                    <InputError
                        message={errors.password_confirmation}
                        className="mt-2"
                    />
                </div>

                <div className="mt-4 flex items-center justify-end">
                    <PrimaryButton className="ms-4" disabled={processing}>
                        Reset Password
                    </PrimaryButton>
                </div>
            </form>
        </GuestLayout>
    );
}
```

### File: resources\js\Pages\Auth\VerifyEmail.jsx

```
import PrimaryButton from '@/Components/PrimaryButton';
import GuestLayout from '@/Layouts/GuestLayout';
import { Head, Link, useForm } from '@inertiajs/react';

export default function VerifyEmail({ status }) {
    const { post, processing } = useForm({});

    const submit = (e) => {
        e.preventDefault();

        post(route('verification.send'));
    };

    return (
        <GuestLayout>
            <Head title="Email Verification" />

            <div className="mb-4 text-sm text-gray-600">
                Thanks for signing up! Before getting started, could you verify
                your email address by clicking on the link we just emailed to
                you? If you didn't receive the email, we will gladly send you
                another.
            </div>

            {status === 'verification-link-sent' && (
                <div className="mb-4 text-sm font-medium text-green-600">
                    A new verification link has been sent to the email address
                    you provided during registration.
                </div>
            )}

            <form onSubmit={submit}>
                <div className="mt-4 flex items-center justify-between">
                    <PrimaryButton disabled={processing}>
                        Resend Verification Email
                    </PrimaryButton>

                    <Link
                        href={route('logout')}
                        method="post"
                        as="button"
                        className="rounded-md text-sm text-gray-600 underline hover:text-gray-900 focus:outline-none focus:ring-2 focus:ring-indigo-500 focus:ring-offset-2"
                    >
                        Log Out
                    </Link>
                </div>
            </form>
        </GuestLayout>
    );
}
```

### File: resources\js\Pages\Customer\Dashboard.jsx

```
import AuthenticatedLayout from '@/Layouts/AuthenticatedLayout';
import { Head } from '@inertiajs/react';

export default function CustomerDashboard() {
    return (
        <AuthenticatedLayout
            header={
                <h2 className="text-xl font-semibold leading-tight text-gray-800">
                    Customer Dashboard
                </h2>
            }
        >
            <Head title="Customer Dashboard" />

            <div className="py-12">
```

```
                    <div className="mx-auto max-w-7xl sm:px-6 lg:px-8">
                        <div className="overflow-hidden bg-white shadow-sm sm:rounded-lg">
                            <div className="p-6 text-gray-900">
                                Welcome to your customer dashboard.
                            </div>
                        </div>
                    </div>
                </div>
            </AuthenticatedLayout>
        );
    }
```

### File: resources\js\Pages\Profile\Edit.jsx

```
import AuthenticatedLayout from '@/Layouts/AuthenticatedLayout';
import { Head } from '@inertiajs/react';
import DeleteUserForm from './Partials/DeleteUserForm';
import UpdatePasswordForm from './Partials/UpdatePasswordForm';
import UpdateProfileInformationForm from './Partials/UpdateProfileInformationForm';

export default function Edit({ mustVerifyEmail, status }) {
    return (
        <AuthenticatedLayout
            header={
                <h2 className="text-xl font-semibold leading-tight text-gray-800">
                    Profile
                </h2>
            }
        >
            <Head title="Profile" />

            <div className="py-12">
                <div className="mx-auto max-w-7xl space-y-6 sm:px-6 lg:px-8">
                    <div className="bg-white p-4 shadow sm:rounded-lg sm:p-8">
                        <UpdateProfileInformationForm
                            mustVerifyEmail={mustVerifyEmail}
                            status={status}
                            className="max-w-xl"
                        />
                    </div>

                    <div className="bg-white p-4 shadow sm:rounded-lg sm:p-8">
                        <UpdatePasswordForm className="max-w-xl" />
                    </div>

                    <div className="bg-white p-4 shadow sm:rounded-lg sm:p-8">
                        <DeleteUserForm className="max-w-xl" />
                    </div>
                </div>
            </div>
        </AuthenticatedLayout>
    );
}
```

### File: resources\js\Pages\Profile\Partials\DeleteUserForm.jsx

```
import DangerButton from '@/Components/DangerButton';
import InputError from '@/Components/InputError';
import InputLabel from '@/Components/InputLabel';
import Modal from '@/Components/Modal';
import SecondaryButton from '@/Components/SecondaryButton';
import TextInput from '@/Components/TextInput';
import { useForm } from '@inertiajs/react';
import { useRef, useState } from 'react';

export default function DeleteUserForm({ className = '' }) {
    const [confirmingUserDeletion, setConfirmingUserDeletion] = useState(false);
    const passwordInput = useRef();

    const {
        data,
        setData,
        delete: destroy,
        processing,
        reset,
        errors,
        clearErrors,
    } = useForm({
        password: '',
    });

    const confirmUserDeletion = () => {
        setConfirmingUserDeletion(true);
    };

    const deleteUser = (e) => {
        e.preventDefault();

        destroy(route('profile.destroy'), {
            preserveScroll: true,
            onSuccess: () => closeModal(),
            onError: () => passwordInput.current.focus(),
            onFinish: () => reset(),
        });
    };

    const closeModal = () => {
        setConfirmingUserDeletion(false);

        clearErrors();
        reset();
    };

    return (
        <section className={`space-y-6 ${className}`}>
            <header>
                <h2 className="text-lg font-medium text-gray-900">
                    Delete Account
                </h2>

                <p className="mt-1 text-sm text-gray-600">
                    Once your account is deleted, all of its resources and data
                    will be permanently deleted. Before deleting your account,
                    please download any data or information that you wish to
                    retain.
                </p>
            </header>

            <DangerButton onClick={confirmUserDeletion}>
                Delete Account
            </DangerButton>

            <Modal show={confirmingUserDeletion} onClose={closeModal}>
```

```
                <form onSubmit={deleteUser} className="p-6">
                    <h2 className="text-lg font-medium text-gray-900">
                        Are you sure you want to delete your account?
                    </h2>

                    <p className="mt-1 text-sm text-gray-600">
                        Once your account is deleted, all of its resources and
                        data will be permanently deleted. Please enter your
                        password to confirm you would like to permanently delete
                        your account.
                    </p>

                    <div className="mt-6">
                        <InputLabel
                            htmlFor="password"
                            value="Password"
                            className="sr-only"
                        />

                        <TextInput
                            id="password"
                            type="password"
                            name="password"
                            ref={passwordInput}
                            value={data.password}
                            onChange={(e) =>
                                setData('password', e.target.value)
                            }
                            className="mt-1 block w-3/4"
                            isFocused
                            placeholder="Password"
                        />

                        <InputError
                            message={errors.password}
                            className="mt-2"
                        />
                    </div>

                    <div className="mt-6 flex justify-end">
                        <SecondaryButton onClick={closeModal}>
                            Cancel
                        </SecondaryButton>

                        <DangerButton className="ms-3" disabled={processing}>
                            Delete Account
                        </DangerButton>
                    </div>
                </form>
            </Modal>
        </section>
    );
}
```

### *File: resources\js\Pages\Profile\Partials\UpdatePasswordForm.jsx*

```
import InputError from '@/Components/InputError';
import InputLabel from '@/Components/InputLabel';
import PrimaryButton from '@/Components/PrimaryButton';
import TextInput from '@/Components/TextInput';
import { Transition } from '@headlessui/react';
import { useForm } from '@inertiajs/react';
import { useRef } from 'react';

export default function UpdatePasswordForm({ className = '' }) {
    const passwordInput = useRef();
    const currentPasswordInput = useRef();

    const {
        data,
        setData,
        errors,
        put,
        reset,
        processing,
        recentlySuccessful,
    } = useForm({
        current_password: '',
        password: '',
        password_confirmation: '',
    });

    const updatePassword = (e) => {
        e.preventDefault();

        put(route('password.update'), {
            preserveScroll: true,
            onSuccess: () => reset(),
            onError: (errors) => {
                if (errors.password) {
                    reset('password', 'password_confirmation');
                    passwordInput.current.focus();
                }

                if (errors.current_password) {
                    reset('current_password');
                    currentPasswordInput.current.focus();
                }
            },
        });
    };

    return (
        <section className={className}>
            <header>
                <h2 className="text-lg font-medium text-gray-900">
                    Update Password
                </h2>

                <p className="mt-1 text-sm text-gray-600">
                    Ensure your account is using a long, random password to stay
                    secure.
                </p>
            </header>

            <form onSubmit={updatePassword} className="mt-6 space-y-6">
                <div>
                    <InputLabel
                        htmlFor="current_password"
                        value="Current Password"
                    />

                    <TextInput
                        id="current_password"
                        ref={currentPasswordInput}
```

```
                        value={data.current_password}
                        onChange={(e) =>
                            setData('current_password', e.target.value)
                        }
                        type="password"
                        className="mt-1 block w-full"
                        autoComplete="current-password"
                    />

                    <InputError
                        message={errors.current_password}
                        className="mt-2"
                    />
                </div>

                <div>
                    <InputLabel htmlFor="password" value="New Password" />

                    <TextInput
                        id="password"
                        ref={passwordInput}
                        value={data.password}
                        onChange={(e) => setData('password', e.target.value)}
                        type="password"
                        className="mt-1 block w-full"
                        autoComplete="new-password"
                    />

                    <InputError message={errors.password} className="mt-2" />
                </div>

                <div>
                    <InputLabel
                        htmlFor="password_confirmation"
                        value="Confirm Password"
                    />

                    <TextInput
                        id="password_confirmation"
                        value={data.password_confirmation}
                        onChange={(e) =>
                            setData('password_confirmation', e.target.value)
                        }
                        type="password"
                        className="mt-1 block w-full"
                        autoComplete="new-password"
                    />

                    <InputError
                        message={errors.password_confirmation}
                        className="mt-2"
                    />
                </div>

                <div className="flex items-center gap-4">
                    <PrimaryButton disabled={processing}>Save</PrimaryButton>

                    <Transition
                        show={recentlySuccessful}
                        enter="transition ease-in-out"
                        enterFrom="opacity-0"
                        leave="transition ease-in-out"
                        leaveTo="opacity-0"
                    >
                        <p className="text-sm text-gray-600">
                            Saved.
                        </p>
                    </Transition>
                </div>
            </form>
        </section>
    );
}
```

### File: resources\js\Pages\Profile\Partials\UpdateProfileInformationForm.jsx

```
import InputError from '@/Components/InputError';
import InputLabel from '@/Components/InputLabel';
import PrimaryButton from '@/Components/PrimaryButton';
import TextInput from '@/Components/TextInput';
import { Transition } from '@headlessui/react';
import { Link, useForm, usePage } from '@inertiajs/react';

export default function UpdateProfileInformation({
    mustVerifyEmail,
    status,
    className = '',
}) {
    const user = usePage().props.auth.user;

    const { data, setData, patch, errors, processing, recentlySuccessful } =
        useForm({
            name: user.name,
            email: user.email,
        });

    const submit = (e) => {
        e.preventDefault();

        patch(route('profile.update'));
    };

    return (
        <section className={className}>
            <header>
                <h2 className="text-lg font-medium text-gray-900">
                    Profile Information
                </h2>

                <p className="mt-1 text-sm text-gray-600">
                    Update your account's profile information and email address.
                </p>
            </header>

            <form onSubmit={submit} className="mt-6 space-y-6">
                <div>
                    <InputLabel htmlFor="name" value="Name" />

                    <TextInput
                        id="name"
                        className="mt-1 block w-full"
                        value={data.name}
                        onChange={(e) => setData('name', e.target.value)}
                        required
                        isFocused
```

```
                            autoComplete="name"
                        />

                        <InputError className="mt-2" message={errors.name} />
                    </div>

                    <div>
                        <InputLabel htmlFor="email" value="Email" />

                        <TextInput
                            id="email"
                            type="email"
                            className="mt-1 block w-full"
                            value={data.email}
                            onChange={(e) => setData('email', e.target.value)}
                            required
                            autoComplete="username"
                        />

                        <InputError className="mt-2" message={errors.email} />
                    </div>

                    {mustVerifyEmail && user.email_verified_at === null && (
                        <div>
                            <p className="mt-2 text-sm text-gray-800">
                                Your email address is unverified.
                                <Link
                                    href={route('verification.send')}
                                    method="post"
                                    as="button"
                                    className="rounded-md text-sm text-gray-600 underline hover:text-gray-900 focus:outline-none focus:ring-2 focus:ring-indigo-500 focus:ring-offs
                                >
                                    Click here to re-send the verification email.
                                </Link>
                            </p>

                            {status === 'verification-link-sent' && (
                                <div className="mt-2 text-sm font-medium text-green-600">
                                    A new verification link has been sent to your
                                    email address.
                                </div>
                            )}
                        </div>
                    )}

                    <div className="flex items-center gap-4">
                        <PrimaryButton disabled={processing}>Save</PrimaryButton>

                        <Transition
                            show={recentlySuccessful}
                            enter="transition ease-in-out"
                            enterFrom="opacity-0"
                            leave="transition ease-in-out"
                            leaveTo="opacity-0"
                        >
                            <p className="text-sm text-gray-600">
                                Saved.
                            </p>
                        </Transition>
                    </div>
                </form>
            </section>
        );
    }
```

### File: resources\views\app.blade.php

```
<!DOCTYPE html>
<html lang="{{ str_replace('_', '-', app()->getLocale()) }}">
    <head>
        <meta charset="utf-8">
        <meta name="viewport" content="width=device-width, initial-scale=1">

        <title inertia>{{ config('app.name', 'Laravel') }}</title>

        <!-- Fonts -->
        <link rel="preconnect" href="https://fonts.bunny.net">
        <link href="https://fonts.bunny.net/css?family=figtree:400,500,600&display=swap" rel="stylesheet" />

        <!-- Scripts -->
        @routes
        @viteReactRefresh
        @vite(['resources/js/app.jsx', "resources/js/Pages/{$page['component']}.jsx"])
        @inertiaHead
    </head>
    <body class="font-sans antialiased">
        @inertia
    </body>
</html>
```

### File: resources\views\admin\dashboard.blade.php

```
@extends('admin.layout')

@section('title', 'Dashboard')

@section('content')
<div class="container-fluid py-4">
    <!-- Welcome Header -->
    <div class="row mb-4">
        <div class="col-12">
            <div class="card border-0 shadow-sm bg-gradient-primary text-white">
                <div class="card-body p-4">
                    <div class="d-flex justify-content-between align-items-center">
                        <div>
                            <h1 class="h2 mb-2">Welcome back, {{ $user->name ?? 'Admin' }}!</h1>
                            <p class="mb-0 opacity-75">{{ now()->format('l, F j, Y') }}</p>
                        </div>
                        <div class="d-none d-md-block">
                            <i class="bi bi-shield-shaded fs-1 opacity-50"></i>
                        </div>
                    </div>
                </div>
            </div>
        </div>
    </div>

    <!-- Stats Cards -->
    <div class="row g-4 mb-4">
        <div class="col-md-4">
            <div class="card border-0 shadow-sm h-100">
                <div class="card-body">
                    <div class="d-flex align-items-center">
```

```
                        <div class="flex-shrink-0 bg-primary bg-opacity-10 p-3 rounded-3">
                            <i class="bi bi-flag-fill text-primary fs-3"></i>
                        </div>
                        <div class="flex-grow-1 ms-3">
                            <h6 class="text-muted mb-1">Open Reports</h6>
                            <h3 class="mb-0 fw-bold">{{ $openReports }}</h3>
                        </div>
                    </div>
                </div>
            </div>
        </div>

        <div class="col-md-4">
            <div class="card border-0 shadow-sm h-100">
                <div class="card-body">
                    <div class="d-flex align-items-center">
                        <div class="flex-shrink-0 bg-info bg-opacity-10 p-3 rounded-3">
                            <i class="bi bi-chat-dots-fill text-info fs-3"></i>
                        </div>
                        <div class="flex-grow-1 ms-3">
                            <h6 class="text-muted mb-1">Open Chats</h6>
                            <h3 class="mb-0 fw-bold">{{ $openChats }}</h3>
                        </div>
                    </div>
                </div>
            </div>
        </div>

        <div class="col-md-4">
            <div class="card border-0 shadow-sm h-100">
                <div class="card-body">
                    <div class="d-flex align-items-center">
                        <div class="flex-shrink-0 bg-success bg-opacity-10 p-3 rounded-3">
                            <i class="bi bi-people-fill text-success fs-3"></i>
                        </div>
                        <div class="flex-grow-1 ms-3">
                            <h6 class="text-muted mb-1">Admin Users</h6>
                            <h3 class="mb-0 fw-bold">{{ $adminCount }}</h3>
                        </div>
                    </div>
                </div>
            </div>
        </div>
    </div>

    <!-- Quick Actions -->
    <div class="row g-4">
        <div class="col-12">
            <div class="card border-0 shadow-sm">
                <div class="card-header bg-white border-0 py-3">
                    <h5 class="mb-0">Quick Actions</h5>
                </div>
                <div class="card-body">
                    <div class="row g-3">
                        <div class="col-md-3 col-6">
                            <a href="{{ route('admin.issue-reports.index') }}" class="text-decoration-none">
                                <div class="border rounded-3 p-3 text-center hover-shadow">
                                    <i class="bi bi-flag-fill text-primary fs-2 mb-2"></i>
                                    <h6 class="mb-0">Issue Reports</h6>
                                </div>
                            </a>
                        </div>
                        <div class="col-md-3 col-6">
                            <a href="{{ route('admin.chats.index') }}" class="text-decoration-none">
                                <div class="border rounded-3 p-3 text-center hover-shadow">
                                    <i class="bi bi-chat-dots-fill text-info fs-2 mb-2"></i>
                                    <h6 class="mb-0">Support Chats</h6>
                                </div>
                            </a>
                        </div>
                        @if(auth()->user()?->account_type === 'super_admin')
                        <div class="col-md-3 col-6">
                            <a href="{{ route('admin.admins.index') }}" class="text-decoration-none">
                                <div class="border rounded-3 p-3 text-center hover-shadow">
                                    <i class="bi bi-person-plus-fill text-success fs-2 mb-2"></i>
                                    <h6 class="mb-0">Admin Users</h6>
                                </div>
                            </a>
                        </div>
                        @endif
                        <div class="col-md-3 col-6">
                            <a href="{{ route('admin.admins.create') }}" class="text-decoration-none">
                                <div class="border rounded-3 p-3 text-center hover-shadow">
                                    <i class="bi bi-plus-circle-fill text-warning fs-2 mb-2"></i>
                                    <h6 class="mb-0">Create Admin</h6>
                                </div>
                            </a>
                        </div>
                    </div>
                </div>
            </div>
        </div>
    </div>
</div>
@endsection

<style>
.hover-shadow {
    transition: all 0.3s ease;
}
.hover-shadow:hover {
    transform: translateY(-3px);
    box-shadow: 0 0.5rem 1rem rgba(0,0,0,0.15);
}
.bg-gradient-primary {
    background: linear-gradient(135deg, #667eea 0%, #764ba2 100%);
}
</style>
```

***File: resources\views\admin\layout.blade.php***

```
<!doctype html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>@yield('title', 'Admin') - BookHub</title>

    <!-- Bootstrap 5 CSS -->
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/css/bootstrap.min.css" rel="stylesheet">
    <!-- Bootstrap Icons -->
    <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.11.3/font/bootstrap-icons.min.css">

    <style>
        :root {
            --bg: #f4f5fb;
            --card: #ffffff;
            --text: #1f2433;
            --muted: #667085;
            --primary: #5b4cff;
            --border: #e5e7f1;
            --radius: 14px;
            --shadow: 0 10px 30px rgba(31,36,51,0.08);
        }

        * { box-sizing: border-box; }

        body {
            margin: 0;
            font-family: "Segoe UI", system-ui, -apple-system, sans-serif;
            background: var(--bg);
            color: var(--text);
        }

        .admin-shell {
            min-height: 100vh;
            display: grid;
            grid-template-columns: 260px 1fr;
        }

        .sidebar {
            background: #0f1224;
            color: #fff;
            padding: 1.5rem 1.2rem;
            display: flex;
            flex-direction: column;
            gap: 1.2rem;
            height: 100vh;
            position: sticky;
            top: 0;
        }

        .brand {
            font-weight: 800;
            font-size: 1.1rem;
            display: flex;
            align-items: center;
            gap: 0.5rem;
            padding-bottom: 1rem;
            border-bottom: 1px solid rgba(255,255,255,0.1);
        }

        .brand i {
            color: #f5b042;
            font-size: 1.3rem;
        }

        .nav-links {
            display: flex;
            flex-direction: column;
            gap: 0.5rem;
            flex: 1;
        }

        .nav-links a {
            text-decoration: none;
            color: #e4e7ff;
            padding: 0.65rem 0.8rem;
            border-radius: 10px;
            display: flex;
            align-items: center;
            gap: 0.6rem;
            font-size: 0.9rem;
            transition: all 0.2s;
        }

        .nav-links a.active,
        .nav-links a:hover {
            background: rgba(91,76,255,0.2);
            color: #fff;
        }

        .nav-links a i {
            width: 20px;
            color: #f5b042;
        }

        .sidebar .user-info {
            margin-top: auto;
            padding-top: 1rem;
            border-top: 1px solid rgba(255,255,255,0.1);
            font-size: 0.85rem;
        }

        .sidebar .user-name {
            color: #fff;
            font-weight: 600;
            margin-bottom: 0.3rem;
        }

        .sidebar .user-role {
            color: #f5b042;
            font-size: 0.75rem;
            margin-bottom: 0.8rem;
        }

        .sidebar .logout-form {
            margin-top: 0.5rem;
        }

        .sidebar .logout-form button {
            background: transparent;
            border: 1px solid rgba(255,255,255,0.2);
            color: #fff;
            padding: 0.5rem 0.8rem;
            border-radius: 8px;
```

```
            cursor: pointer;
            width: 100%;
            display: flex;
            align-items: center;
            gap: 0.5rem;
            transition: all 0.2s;
        }

        .sidebar .logout-form button:hover {
            background: rgba(255,77,109,0.2);
            border-color: #ff4d6d;
        }

        .content {
            padding: 2rem;
            overflow-y: auto;
            max-height: 100vh;
        }

        .flash {
            background: #e7f7ef;
            border: 1px solid #bde5ce;
            color: #0f5132;
            padding: 0.7rem 1rem;
            border-radius: 10px;
            margin-bottom: 1rem;
        }

        @media (max-width: 900px) {
            .admin-shell {
                grid-template-columns: 1fr;
            }
            .sidebar {
                display: none;
            }
        }
    </style>
    @yield('extra_css')
</head>
<body>
    <div class="admin-shell">
        <aside class="sidebar">
            <div class="brand">
                <i class="bi bi-shield-lock-fill"></i>
                <span>BookHub Admin</span>
            </div>

            <nav class="nav-links">
                <a href="{{ route('admin.dashboard') }}" class="{{ request()->routeIs('admin.dashboard') ? 'active' : '' }}">
                    <i class="bi bi-speedometer2"></i> Dashboard
                </a>
                <a href="{{ route('admin.issue-reports.index') }}" class="{{ request()->routeIs('admin.issue-reports.*') ? 'active' : '' }}">
                    <i class="bi bi-flag-fill"></i> Issue Reports
                </a>
                <a href="{{ route('admin.chats.index') }}" class="{{ request()->routeIs('admin.chats.*') ? 'active' : '' }}">
                    <i class="bi bi-chat-dots-fill"></i> Support Chats
                </a>
                <a href="{{ route('admin.users.index') }}" class="{{ request()->routeIs('admin.users.*') ? 'active' : '' }}">
                    <i class="bi bi-people"></i> Site Users
                </a>
                <a href="{{ route('admin.admins.index') }}" class="{{ request()->routeIs('admin.admins.*') ? 'active' : '' }}">
                    <i class="bi bi-person-fill-gear"></i> Admin Users
                </a>
                @if(auth()->user()?->account_type === 'super_admin')
                <a href="{{ route('admin.admins.create') }}" class="{{ request()->routeIs('admin.admins.create') ? 'active' : '' }}">
                    <i class="bi bi-person-plus-fill"></i> Create Admin
                </a>
                @endif
            </nav>

            <div class="user-info">
                <div class="user-name">{{ auth()->user()->name ?? 'Admin' }}</div>
                <div class="user-role">{{ ucfirst(str_replace('_', ' ', auth()->user()->account_type ?? 'user')) }}</div>

                <form method="POST" action="{{ route('logout') }}" class="logout-form">
                    @csrf
                    <button type="submit">
                        <i class="bi bi-box-arrow-right"></i> Logout
                    </button>
                </form>
            </div>
        </aside>

        <main class="content">
            @if (session('status'))
                <div class="flash">{{ session('status') }}</div>
            @endif

            @yield('content')
        </main>
    </div>

    <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.2/dist/js/bootstrap.bundle.min.js"></script>
    @yield('extra_js')
</body>
</html>
```

### *File: resources\views\admin\admins\create.blade.php*

```
@extends('admin.layout')

@section('title', 'Create Admin')

@section('content')
<div class="card" style="max-width:720px;">
    <a href="{{ route('admin.admins.index') }}" style="text-decoration:none;color:#5b4cff;font-weight:700;">
        <i class="bi bi-arrow-left"></i> Back to admin users
    </a>
    <h1 style="margin-top:0.8rem;">Create Admin Account</h1>

    <form method="POST" action="{{ route('admin.admins.store') }}" style="display:grid;gap:0.9rem;margin-top:1rem;">
        @csrf
        <label style="display:grid;gap:0.4rem;font-weight:600;color:#475467;">
            Full Name
            <input type="text" name="name" required maxlength="255" value="{{ old('name') }}" style="padding:0.6rem;border-radius:10px;border:1px solid #d0d5dd;">
        </label>
        <label style="display:grid;gap:0.4rem;font-weight:600;color:#475467;">
            Email
            <input type="email" name="email" required maxlength="255" value="{{ old('email') }}" style="padding:0.6rem;border-radius:10px;border:1px solid #d0d5dd;">
        </label>
        <label style="display:grid;gap:0.4rem;font-weight:600;color:#475467;">
            Role
            <select name="account_type" required style="padding:0.6rem;border-radius:10px;border:1px solid #d0d5dd;">
                <option value="sub_admin" @selected(old('account_type') === 'sub_admin')>Sub Admin</option>
                <option value="super_admin" @selected(old('account_type') === 'super_admin')>Super Admin</option>
```

```
            </select>
        </label>
        <label style="display:grid;gap:0.4rem;font-weight:600;color:#475467;">
            Password
            <input type="password" name="password" required style="padding:0.6rem;border-radius:10px;border:1px solid #d0d5dd;">
        </label>
        <label style="display:grid;gap:0.4rem;font-weight:600;color:#475467;">
            Confirm Password
            <input type="password" name="password_confirmation" required style="padding:0.6rem;border-radius:10px;border:1px solid #d0d5dd;">
        </label>
        <button type="submit" style="padding:0.7rem 1.2rem;border:none;border-radius:10px;background:#5b4cff;color:#fff;font-weight:700;width:fit-content;">
            Create Admin
        </button>
    </form>
</div>
@endsection
```

### File: resources\views\admin\admins\edit.blade.php

```
@extends('admin.layout')

@section('title', 'Edit Admin User')

@section('content')
<div class="card" style="max-width: 600px;">
    <a href="{{ route('admin.admins.index') }}" style="text-decoration:none;color:#5b4cff;font-weight:700;display:inline-block;margin-bottom:1rem;">
        <i class="bi bi-arrow-left"></i> Back to Admin Users
    </a>

    <h1 style="margin-top:0;">Edit Admin User</h1>
    <p style="color:#667085;margin-bottom:2rem;">Modify details or permissions for {{ $admin->name }}.</p>

    <form method="POST" action="{{ route('admin.admins.update', $admin) }}" style="display:flex;flex-direction:column;gap:1.2rem;">
        @csrf
        @method('PUT')

        <div style="display:flex;flex-direction:column;gap:0.4rem;">
            <label for="name" style="font-weight:600;color:#344054;">Full Name</label>
            <input type="text" id="name" name="name" value="{{ old('name', $admin->name) }}" required style="padding:0.6rem 0.8rem;border:1px solid #d0d5dd;border-radius:8px;"
            @error('name')<span style="color:#d92d20;font-size:0.85rem;">{{ $message }}</span>@enderror
        </div>

        <div style="display:flex;flex-direction:column;gap:0.4rem;">
            <label for="email" style="font-weight:600;color:#344054;">Email Address</label>
            <input type="email" id="email" name="email" value="{{ old('email', $admin->email) }}" required style="padding:0.6rem 0.8rem;border:1px solid #d0d5dd;border-radius
            @error('email')<span style="color:#d92d20;font-size:0.85rem;">{{ $message }}</span>@enderror
        </div>

        <div style="display:flex;flex-direction:column;gap:0.4rem;">
            <label for="account_type" style="font-weight:600;color:#344054;">Role</label>
            <select id="account_type" name="account_type" required style="padding:0.6rem 0.8rem;border:1px solid #d0d5dd;border-radius:8px;">
                <option value="sub_admin" @selected(old('account_type', $admin->account_type) === 'sub_admin')>Sub Admin (Can manage reports, users, chats)</option>
                <option value="super_admin" @selected(old('account_type', $admin->account_type) === 'super_admin')>Super Admin (Full access, can manage admins)</option>
            </select>
            @error('account_type')<span style="color:#d92d20;font-size:0.85rem;">{{ $message }}</span>@enderror
        </div>

        <div style="display:flex;flex-direction:column;gap:0.4rem;">
            <label style="font-weight:600;color:#344054;display:flex;align-items:center;gap:0.5rem;">
                <input type="hidden" name="is_active" value="0">
                <input type="checkbox" name="is_active" value="1" @checked(old('is_active', $admin->is_active ?? true))>
                Active Account
            </label>
            <p style="margin:0;font-size:0.85rem;color:#667085;">Uncheck this to prevent the user from logging in without deleting their history.</p>
        </div>

        <hr style="border:none;border-top:1px solid #e5e7f1;margin:1rem 0;">

        <div style="display:flex;flex-direction:column;gap:0.4rem;">
            <label for="password" style="font-weight:600;color:#344054;">New Password (Optional)</label>
            <input type="password" id="password" name="password" placeholder="Leave blank to keep current password" style="padding:0.6rem 0.8rem;border:1px solid #d0d5dd;borde
            @error('password')<span style="color:#d92d20;font-size:0.85rem;">{{ $message }}</span>@enderror
        </div>

        <div style="display:flex;flex-direction:column;gap:0.4rem;">
            <label for="password_confirmation" style="font-weight:600;color:#344054;">Confirm New Password</label>
            <input type="password" id="password_confirmation" name="password_confirmation" style="padding:0.6rem 0.8rem;border:1px solid #d0d5dd;border-radius:8px;">
        </div>

        <div style="margin-top:1rem;">
            <button type="submit" style="background:#5b4cff;color:#fff;border:none;padding:0.7rem 1.5rem;border-radius:8px;font-weight:600;cursor:pointer;">
                <i class="bi bi-save"></i> Save Changes
            </button>
        </div>
    </form>
</div>
@endsection
```

### File: resources\views\admin\admins\index.blade.php

```
@extends('admin.layout')

@section('title', 'Admin Users')

@section('content')
<div class="card">
    <div style="display:flex;align-items:center;justify-content:space-between;gap:1rem;">
        <div>
            <h1 style="margin-top:0;">Admin Users</h1>
            <p style="color:#667085;margin-top:0.35rem;">Manage sub-admin and super-admin accounts.</p>
        </div>
        @if(auth()->user()?->account_type === 'super_admin')
            <a href="{{ route('admin.admins.create') }}" style="text-decoration:none;background:#5b4cff;color:#fff;padding:0.6rem 1rem;border-radius:10px;font-weight:700;">
                <i class="bi bi-plus-circle"></i> New Admin
            </a>
        @endif
    </div>

    <div style="margin-top:1.2rem;overflow:auto;">
        <table style="width:100%;border-collapse:collapse;font-size:0.9rem;">
            <thead>
                <tr style="text-align:left;color:#667085;">
                    <th style="padding:0.6rem 0.4rem;">Name</th>
                    <th style="padding:0.6rem 0.4rem;">Email</th>
                    <th style="padding:0.6rem 0.4rem;">Role</th>
                    <th style="padding:0.6rem 0.4rem;">Status</th>
                    @if(auth()->user()?->account_type === 'super_admin')
                    <th style="padding:0.6rem 0.4rem;text-align:right;">Actions</th>
                    @endif
                </tr>
            </thead>
            <tbody>
                @forelse($admins as $admin)
```

```
                <tr style="border-top:1px solid #e5e7f1;">
                    <td style="padding:0.7rem 0.4rem;">{{ $admin->name }}</td>
                    <td style="padding:0.7rem 0.4rem;">{{ $admin->email }}</td>
                    <td style="padding:0.7rem 0.4rem;">
                        <span style="background:var(--bg);padding:0.2rem 0.5rem;border-radius:4px;font-size:0.8rem;white-space:nowrap;">
                            {{ ucfirst(str_replace('_', ' ', $admin->account_type)) }}
                        </span>
                    </td>
                    <td style="padding:0.7rem 0.4rem;">
                        @if($admin->is_active ?? true)
                            <span style="color:#10b981;font-weight:600;"><i class="bi bi-check-circle-fill"></i> Active</span>
                        @else
                            <span style="color:#ef4444;font-weight:600;"><i class="bi bi-x-circle-fill"></i> Inactive</span>
                        @endif
                    </td>
                    @if(auth()->user()?->account_type === 'super_admin')
                    <td style="padding:0.7rem 0.4rem;text-align:right;">
                        <div style="display:flex;gap:0.4rem;justify-content:flex-end;">
                            <a href="{{ route('admin.admins.edit', $admin) }}" style="padding:0.4rem 0.6rem;background:#f8fafc;border:1px solid #e2e8f0;border-radius:6px;colo
                                <i class="bi bi-pencil"></i>
                            </a>

                            @if($admin->id !== auth()->id())
                                <form action="{{ route('admin.admins.toggle-active', $admin) }}" method="POST" style="display:inline;">
                                    @csrf
                                    <button type="submit" style="padding:0.4rem 0.6rem;background:#f8fafc;border:1px solid #e2e8f0;border-radius:6px;color:{{ $admin->is_active
                                        <i class="bi {{ $admin->is_active ? 'bi-pause-circle' : 'bi-play-circle' }}"></i>
                                    </button>
                                </form>

                                <form action="{{ route('admin.admins.destroy', $admin) }}" method="POST" style="display:inline;" onsubmit="return confirm('Are you sure you wan
                                    @csrf
                                    @method('DELETE')
                                    <button type="submit" style="padding:0.4rem 0.6rem;background:#fef2f2;border:1px solid #fecaca;border-radius:6px;color:#ef4444;cursor:point
                                        <i class="bi bi-trash3"></i>
                                    </button>
                                </form>
                            @endif
                        </div>
                    </td>
                    @endif
                </tr>
                @empty
                <tr>
                    <td colspan="5" style="padding:1.5rem;text-align:center;color:#667085;">No admin accounts found.</td>
                </tr>
                @endforelse
            </tbody>
        </table>
    </div>
</div>
@endsection
```

### File: resources\views\admin\chats\index.blade.php

```
@extends('admin.layout')

@section('title', 'Support Chats')

@section('content')
<div class="card">
    <h1 style="margin-top:0;">Support Chats</h1>
    <p style="color:#667085;margin-top:0.4rem;">Active conversations with customers.</p>

    <div style="display:grid;gap:0.8rem;margin-top:1.2rem;">
        @forelse($conversations as $conversation)
            <a href="{{ route('admin.chats.show', $conversation) }}" style="text-decoration:none;color:inherit;">
                <div style="border:1px solid #e5e7f1;border-radius:12px;padding:0.9rem 1rem;display:flex;justify-content:space-between;gap:1rem;align-items:center;">
                    <div>
                        <strong>{{ $conversation->subject ?? 'Support Request' }}</strong>
                        <div style="font-size:0.85rem;color:#667085;margin-top:0.3rem;">
                            {{ $conversation->customer?->name ?? 'Customer' }}
                            @if($conversation->latestMessage)
                                · {{ \Illuminate\Support\Str::limit($conversation->latestMessage->message, 80) }}
                            @endif
                        </div>
                    </div>
                    <div style="text-align:right;font-size:0.75rem;color:#667085;">
                        <div>{{ optional($conversation->last_message_at)->format('M d, H:i') ?? $conversation->created_at->format('M d, H:i') }}</div>
                        @if($conversation->unread_count)
                            <span style="background:#5b4cff;color:#fff;border-radius:999px;padding:0.1rem 0.5rem;font-weight:700;">{{ $conversation->unread_count }}</span>
                        @endif
                    </div>
                </div>
            </a>
        @empty
            <div style="text-align:center;color:#667085;padding:1.5rem;">No support chats yet.</div>
        @endforelse
    </div>
</div>
@endsection
```

### File: resources\views\admin\chats\show.blade.php

```
@extends('admin.layout')

@section('title', 'Chat Detail')

@section('content')
<div class="card" style="max-width:900px;">
    <a href="{{ route('admin.chats.index') }}" style="text-decoration:none;color:#5b4cff;font-weight:700;">
        <i class="bi bi-arrow-left"></i> Back to chats
    </a>

    <h1 style="margin-top:0.8rem;">{{ $conversation->subject ?? 'Support Request' }}</h1>
    <p style="color:#667085;">Customer: {{ $conversation->customer?->name ?? 'Customer' }}</p>

    <div style="margin:1rem 0;display:grid;gap:0.6rem;">
        @forelse($messages as $message)
            @php $mine = (int) $message->sender_id === (int) auth()->id(); @endphp
            <div style="display:flex;justify-content:{{ $mine ? 'flex-end' : 'flex-start' }};">
                <div style="max-width:70%;background:{{ $mine ? '#5b4cff' : '#f1f3f9' }};color:{{ $mine ? '#fff' : '#1f2433' }};padding:0.7rem 0.9rem;border-radius:12px;">
                    <div style="font-size:0.88rem;">{{ $message->message }}</div>
                    <div style="font-size:0.7rem;opacity:0.7;margin-top:0.35rem;">
                        {{ $message->created_at->format('M d, Y H:i') }}
                    </div>
                </div>
            </div>
        @empty
            <div style="text-align:center;color:#667085;padding:1rem;">No messages yet.</div>
        @endforelse
    </div>
    <form method="POST" action="{{ route('admin.chats.message', $conversation) }}" style="display:grid;gap:0.6rem;">
```

```
        @csrf
        <textarea name="message" rows="3" required maxlength="2000" style="padding:0.7rem;border-radius:10px;border:1px solid #d0d5dd;"></textarea>
        <button type="submit" style="padding:0.7rem 1.2rem;border:none;border-radius:10px;background:#5b4cff;color:#fff;font-weight:700;width:fit-content;">
            Send Reply
        </button>
    </form>
</div>
@endsection
```

### File: resources\views\admin\issue_reports\index.blade.php

```
@extends('admin.layout')

@section('title', 'Issue Reports')

@section('content')
<div class="card">
    <div style="display:flex;align-items:center;justify-content:space-between;gap:1rem;">
        <div>
            <h1 style="margin-top:0;">Issue Reports</h1>
            <p style="color:#667085;margin-top:0.35rem;">Review and update customer issues.</p>
        </div>
    </div>

    <div style="margin-top:1.4rem;overflow:auto;">
        <table style="width:100%;border-collapse:collapse;font-size:0.9rem;">
            <thead>
                <tr style="text-align:left;color:#667085;">
                    <th style="padding:0.6rem 0.4rem;">ID</th>
                    <th style="padding:0.6rem 0.4rem;">Subject</th>
                    <th style="padding:0.6rem 0.4rem;">Customer</th>
                    <th style="padding:0.6rem 0.4rem;">Priority</th>
                    <th style="padding:0.6rem 0.4rem;">Status</th>
                    <th style="padding:0.6rem 0.4rem;">Created</th>
                    <th style="padding:0.6rem 0.4rem;"></th>
                </tr>
            </thead>
            <tbody>
                @forelse($reports as $report)
                <tr style="border-top:1px solid #e5e7f1;">
                    <td style="padding:0.7rem 0.4rem;">#{{ $report->id }}</td>
                    <td style="padding:0.7rem 0.4rem;">{{ $report->subject }}</td>
                    <td style="padding:0.7rem 0.4rem;">{{ $report->user?->name ?? 'Unknown' }}</td>
                    <td style="padding:0.7rem 0.4rem;">{{ ucfirst($report->priority) }}</td>
                    <td style="padding:0.7rem 0.4rem;">{{ ucfirst(str_replace('_', ' ', $report->status)) }}</td>
                    <td style="padding:0.7rem 0.4rem;">{{ $report->created_at->format('M d, Y') }}</td>
                    <td style="padding:0.7rem 0.4rem;text-align:right;">
                        <a href="{{ route('admin.issue-reports.show', $report) }}" style="text-decoration:none;color:#5b4cff;font-weight:700;">View</a>
                    </td>
                </tr>
                @empty
                <tr>
                    <td colspan="7" style="padding:1.2rem;text-align:center;color:#667085;">No issue reports yet.</td>
                </tr>
                @endforelse
            </tbody>
        </table>
    </div>
</div>
@endsection
```

### File: resources\views\admin\issue_reports\show.blade.php

```
@extends('admin.layout')

@section('title', 'Issue Report')

@section('content')
<div class="card" style="max-width:900px;">
    <a href="{{ route('admin.issue-reports.index') }}" style="text-decoration:none;color:#5b4cff;font-weight:700;">
        <i class="bi bi-arrow-left"></i> Back to reports
    </a>

    <h1 style="margin-top:0.8rem;">{{ $report->subject }}</h1>
    <p style="color:#667085;">Reported by {{ $report->user?->name ?? 'Unknown' }} · {{ $report->created_at->format('M d, Y H:i') }}</p>

    <div style="margin:1rem 0;padding:1rem;border:1px solid #e5e7f1;border-radius:12px;background:#fafbff;">
        <strong>Description</strong>
        <p style="margin-top:0.6rem;color:#344054;">{{ $report->description }}</p>
    </div>

    <div style="display:grid;grid-template-columns:1fr 1fr;gap:1.5rem;margin-top:1.5rem;">
        <form method="POST" action="{{ route('admin.issue-reports.update', $report) }}" style="display:grid;gap:0.8rem;background:#fff;padding:1.2rem;border:1px solid #e5e7f1;
            <h3 style="margin:0;">Update Status</h3>
            @csrf
            @method('PUT')

            <label style="display:grid;gap:0.4rem;font-weight:600;color:#475467;">
                Status
                <select name="status" required style="padding:0.6rem;border-radius:8px;border:1px solid #d0d5dd;">
                    <option value="open" @selected($report->status === 'open')>Open</option>
                    <option value="in_review" @selected($report->status === 'in_review')>In Review</option>
                    <option value="resolved" @selected($report->status === 'resolved')>Resolved</option>
                    <option value="closed" @selected($report->status === 'closed')>Closed</option>
                </select>
            </label>

            <label style="display:grid;gap:0.4rem;font-weight:600;color:#475467;">
                Assigned Admin
                <select name="assigned_admin_id" style="padding:0.6rem;border-radius:8px;border:1px solid #d0d5dd;">
                    <option value="">Unassigned</option>
                    @foreach($admins as $admin)
                        <option value="{{ $admin->id }}" @selected($report->assigned_admin_id === $admin->id)>
                            {{ $admin->name }} ({{ $admin->account_type }})
                        </option>
                    @endforeach
                </select>
            </label>

            <label style="display:grid;gap:0.4rem;font-weight:600;color:#475467;">
                Admin Notes
                <textarea name="admin_notes" rows="3" style="padding:0.6rem;border-radius:8px;border:1px solid #d0d5dd;">{{ $report->admin_notes }}</textarea>
            </label>

            <button type="submit" style="padding:0.7rem 1.2rem;border:none;border-radius:8px;background:#5b4cff;color:#fff;font-weight:700;cursor:pointer;">
                Update Status
            </button>
        </form>

        <div style="background:#fff;padding:1.2rem;border:1px solid #e5e7f1;border-radius:12px;">
            <h3 style="margin:0 0 1rem 0;">User Moderation</h3>
            @php $target = $report->reportedUser ?? $report->user; @endphp
            @if($target)
```

```
                <div style="display:flex;align-items:center;gap:0.8rem;margin-bottom:1.5rem;padding-bottom:1rem;border-bottom:1px solid #e5e7f1;">
                    <div style="font-weight:bold;">{{ $target->name }} <span style="font-weight:normal;color:#667085;">({{ $target->account_type }})</span></div>
                    {!! $target->statusBadge() === 'Active' ? '<span style="background:#dcfce7;color:#166534;padding:0.2rem 0.6rem;border-radius:999px;font-size:0.75rem;font-w
                    {!! $target->statusBadge() === 'Banned' ? '<span style="background:#fee2e2;color:#991b1b;padding:0.2rem 0.6rem;border-radius:999px;font-size:0.75rem;font-w
                    {!! $target->statusBadge() === 'Restricted' ? '<span style="background:#ffedd5;color:#9a3412;padding:0.2rem 0.6rem;border-radius:999px;font-size:0.75rem;fo
                </div>

                <div style="display:grid;gap:0.8rem;">
                    <!-- Warn -->
                    <form action="{{ route('admin.issue-reports.warn', $report) }}" method="POST" onsubmit="return confirm('Warn this user?');">
                        @csrf
                        <button type="submit" style="width:100%;text-align:left;background:#fff;border:1px solid #fbd38d;color:#dd6b20;padding:0.6rem 0.8rem;border-radius:8px;
                            <i class="bi bi-exclamation-triangle"></i> Issue Warning (Currently: {{ $target->warning_count }})
                        </button>
                    </form>

                    <!-- Restrict -->
                    @if(!$target->isRestricted())
                    <form action="{{ route('admin.issue-reports.restrict', $report) }}" method="POST" style="display:flex;gap:0.5rem;align-items:center;">
                        @csrf
                        <input type="number" name="days" value="7" min="1" max="365" style="width:70px;padding:0.5rem;border:1px solid #e2e8f0;border-radius:6px;" required>
                        <span style="font-size:0.8rem;color:#64748b;">days</span>
                        <button type="submit" style="flex:1;text-align:center;background:#fff;border:1px solid #f6ad55;color:#c05621;padding:0.6rem 0.8rem;border-radius:8px;fo
                            <i class="bi bi-dash-circle"></i> Restrict
                        </button>
                    </form>
                    @endif

                    <!-- Ban -->
                    @if(!$target->isBanned())
                    <form action="{{ route('admin.issue-reports.ban', $report) }}" method="POST" style="display:flex;flex-direction:column;gap:0.5rem;">
                        @csrf
                        <input type="text" name="reason" placeholder="Reason for ban" required style="padding:0.5rem;border:1px solid #e2e8f0;border-radius:6px;font-size:0.9re
                        <button type="submit" style="width:100%;text-align:center;background:#fee2e2;border:1px solid #fc8181;color:#c53030;padding:0.6rem 0.8rem;border-radius
                            <i class="bi bi-x-circle"></i> Permanently Ban
                        </button>
                    </form>
                    @endif

                    <a href="{{ route('admin.users.show', $target) }}" style="display:inline-block;margin-top:0.5rem;text-align:center;color:#5b4cff;font-weight:600;text-decor
                        View Full User Profile <i class="bi bi-box-arrow-up-right"></i>
                    </a>
                </div>
            @else
                <p style="color:#667085;">No target user associated with this report.</p>
            @endif
        </div>
    </div>
</div>
@endsection
```

## File: resources\views\admin\users\index.blade.php

```
@extends('admin.layout')

@section('title', 'Manage Users')

@section('content')
<div class="card">
    <div style="display:flex;align-items:center;justify-content:space-between;gap:1rem;flex-wrap:wrap;">
        <div>
            <h1 style="margin-top:0;">Site Users</h1>
            <p style="color:#667085;margin-top:0.35rem;">Manage customers and store owners.</p>
        </div>

        <form action="{{ route('admin.users.index') }}" method="GET" style="display:flex;gap:0.5rem;">
            <input type="text" name="search" value="{{ request('search') }}" placeholder="Search name or email..." style="padding:0.5rem 0.8rem;border:1px solid #e5e7f1;borde
            <select name="type" style="padding:0.5rem 0.8rem;border:1px solid #e5e7f1;border-radius:8px;font-size:0.9rem;">
                <option value="">All Types</option>
                <option value="customer" @selected(request('type') == 'customer')>Customers</option>
                <option value="store_owner" @selected(request('type') == 'store_owner')>Store Owners</option>
            </select>
            <select name="status" style="padding:0.5rem 0.8rem;border:1px solid #e5e7f1;border-radius:8px;font-size:0.9rem;">
                <option value="">All Statuses</option>
                <option value="active" @selected(request('status') == 'active')>Active</option>
                <option value="banned" @selected(request('status') == 'banned')>Banned</option>
                <option value="restricted" @selected(request('status') == 'restricted')>Restricted</option>
            </select>
            <button type="submit" style="background:#5b4cff;color:#fff;border:none;padding:0.5rem 1rem;border-radius:8px;cursor:pointer;"><i class="bi bi-search"></i></button>
        </form>
    </div>

    <div style="margin-top:1.4rem;overflow:auto;">
        <table style="width:100%;border-collapse:collapse;font-size:0.9rem;">
            <thead>
                <tr style="text-align:left;color:#667085;">
                    <th style="padding:0.6rem 0.4rem;">User</th>
                    <th style="padding:0.6rem 0.4rem;">Type</th>
                    <th style="padding:0.6rem 0.4rem;">Status</th>
                    <th style="padding:0.6rem 0.4rem;">Warnings</th>
                    <th style="padding:0.6rem 0.4rem;">Joined</th>
                    <th style="padding:0.6rem 0.4rem;"></th>
                </tr>
            </thead>
            <tbody>
                @forelse($users as $user)
                <tr style="border-top:1px solid #e5e7f1;">
                    <td style="padding:0.7rem 0.4rem;">
                        <div style="font-weight:600;">{{ $user->name }}</div>
                        <div style="color:#667085;font-size:0.8rem;">{{ $user->email }}</div>
                    </td>
                    <td style="padding:0.7rem 0.4rem;">{{ ucfirst(str_replace('_', ' ', $user->account_type)) }}</td>
                    <td style="padding:0.7rem 0.4rem;">
                        @if($user->isBanned())
                            <span style="background:#fee2e2;color:#991b1b;padding:0.2rem 0.6rem;border-radius:999px;font-size:0.75rem;font-weight:700;">Banned</span>
                        @elseif($user->isRestricted())
                            <span style="background:#ffedd5;color:#9a3412;padding:0.2rem 0.6rem;border-radius:999px;font-size:0.75rem;font-weight:700;">Restricted</span>
                        @else
                            <span style="background:#dcfce7;color:#166534;padding:0.2rem 0.6rem;border-radius:999px;font-size:0.75rem;font-weight:700;">Active</span>
                        @endif
                    </td>
                    <td style="padding:0.7rem 0.4rem;">
                        @if($user->warning_count > 0)
                            <span style="color:#eab308;font-weight:bold;">{{ $user->warning_count }} <i class="bi bi-exclamation-triangle-fill"></i></span>
                        @else
                            <span style="color:#9ca3af;">0</span>
                        @endif
                    </td>
                    <td style="padding:0.7rem 0.4rem;">{{ $user->created_at->format('M Y') }}</td>
                    <td style="padding:0.7rem 0.4rem;text-align:right;">
                        <a href="{{ route('admin.users.show', $user) }}" style="text-decoration:none;color:#5b4cff;font-weight:700;">View Profile</a>
                    </td>
                </tr>
                @empty
                <tr>
```

```
                    <td colspan="6" style="padding:2rem;text-align:center;color:#667085;">No users found matching your criteria.</td>
                </tr>
                @endforelse
            </tbody>
        </table>
    </div>

    <div style="margin-top:1.5rem;">
        {{ $users->links() }}
    </div>
</div>
@endsection
```

### File: resources\views\admin\users\show.blade.php

```
@extends('admin.layout')

@section('title', $user->name . ' - User Profile')

@section('content')
<div class="card">
    <div style="display:flex;align-items:center;justify-content:space-between;gap:1rem;">
        <div>
            <a href="{{ route('admin.users.index') }}" style="text-decoration:none;color:#5b4cff;font-size:0.85rem;font-weight:600;"><i class="bi bi-arrow-left"></i> Back to U
            <h1 style="margin:0.5rem 0 0 0;">{{ $user->name }}</h1>
            <p style="color:#667085;margin-top:0.35rem;">{{ ucfirst(str_replace('_', ' ', $user->account_type)) }} Profile</p>
        </div>
        <div>
            {!! $user->statusBadge() === 'Active' ? '<span style="background:#dcfce7;color:#166534;padding:0.4rem 0.8rem;border-radius:999px;font-weight:700;">Active</span>' :
            {!! $user->statusBadge() === 'Banned' ? '<span style="background:#fee2e2;color:#991b1b;padding:0.4rem 0.8rem;border-radius:999px;font-weight:700;">Banned</span>' :
            {!! $user->statusBadge() === 'Restricted' ? '<span style="background:#ffedd5;color:#9a3412;padding:0.4rem 0.8rem;border-radius:999px;font-weight:700;">Restricted</
            {!! $user->statusBadge() === 'Inactive' ? '<span style="background:#f3f4f6;color:#374151;padding:0.4rem 0.8rem;border-radius:999px;font-weight:700;">Inactive</span
        </div>
    </div>

    <div style="display:grid;grid-template-columns:repeat(auto-fit, minmax(300px, 1fr));gap:1.5rem;margin-top:2rem;">
        <!-- User Info -->
        <div style="background:#f8fafc;border:1px solid #e2e8f0;border-radius:12px;padding:1.5rem;">
            <h3 style="margin-top:0;font-size:1.1rem;">Details</h3>

            <table style="width:100%;font-size:0.9rem;margin-top:1rem;">
                <tr>
                    <td style="padding:0.5rem 0;color:#64748b;width:120px;">Email:</td>
                    <td style="padding:0.5rem 0;font-weight:500;">{{ $user->email }}</td>
                </tr>
                <tr>
                    <td style="padding:0.5rem 0;color:#64748b;">Joined:</td>
                    <td style="padding:0.5rem 0;font-weight:500;">{{ $user->created_at->format('F j, Y') }}</td>
                </tr>
                <tr>
                    <td style="padding:0.5rem 0;color:#64748b;">Warnings:</td>
                    <td style="padding:0.5rem 0;font-weight:500;color:{{ $user->warning_count > 0 ? '#ea580c' : 'inherit' }}">{{ $user->warning_count }}</td>
                </tr>
                @if($user->isRestricted())
                <tr>
                    <td style="padding:0.5rem 0;color:#64748b;">Restricted Until:</td>
                    <td style="padding:0.5rem 0;font-weight:500;color:#ea580c;">{{ $user->restricted_until->format('F j, Y H:i') }}</td>
                </tr>
                @endif
                @if($user->isBanned())
                <tr>
                    <td style="padding:0.5rem 0;color:#64748b;">Banned On:</td>
                    <td style="padding:0.5rem 0;font-weight:500;color:#dc2626;">{{ $user->banned_at->format('F j, Y H:i') }}</td>
                </tr>
                <tr>
                    <td style="padding:0.5rem 0;color:#64748b;vertical-align:top;">Ban Reason:</td>
                    <td style="padding:0.5rem 0;font-weight:500;color:#dc2626;">{{ $user->ban_reason }}</td>
                </tr>
                @endif
            </table>
        </div>

        <!-- Moderation Actions -->
        <div style="background:#f8fafc;border:1px solid #e2e8f0;border-radius:12px;padding:1.5rem;">
            <h3 style="margin-top:0;font-size:1.1rem;">Moderation Actions</h3>

            <div style="display:flex;flex-direction:column;gap:1rem;margin-top:1rem;">
                <!-- Warn -->
                <form action="{{ route('admin.users.warn', $user) }}" method="POST" onsubmit="return confirm('Are you sure you want to issue a warning to this user?');">
                    @csrf
                    <button type="submit" style="width:100%;text-align:left;background:#fff;border:1px solid #fbd38d;color:#dd6b20;padding:0.8rem 1rem;border-radius:8px;font-w
                        <i class="bi bi-exclamation-triangle"></i> Issue Warning (Currently: {{ $user->warning_count }})
                    </button>
                </form>

                <!-- Restrict -->
                @if($user->isRestricted())
                    <form action="{{ route('admin.users.unrestrict', $user) }}" method="POST">
                        @csrf
                        <button type="submit" style="width:100%;text-align:left;background:#fff;border:1px solid #38a169;color:#2f855a;padding:0.8rem 1rem;border-radius:8px;fo
                            <i class="bi bi-unlock"></i> Lift Restriction
                        </button>
                    </form>
                @else
                    <form action="{{ route('admin.users.restrict', $user) }}" method="POST" style="display:flex;gap:0.5rem;align-items:center;">
                        @csrf
                        <input type="number" name="days" value="7" min="1" max="365" style="width:70px;padding:0.75rem;border:1px solid #e2e8f0;border-radius:8px;">
                        <span style="font-size:0.9rem;color:#64748b;">days</span>
                        <button type="submit" style="flex:1;text-align:center;background:#fff;border:1px solid #f6ad55;color:#c05621;padding:0.8rem 1rem;border-radius:8px;font
                            <i class="bi bi-dash-circle"></i> Restrict User
                        </button>
                    </form>
                @endif

                <!-- Ban -->
                @if($user->isBanned())
                    <form action="{{ route('admin.users.unban', $user) }}" method="POST">
                        @csrf
                        <button type="submit" style="width:100%;text-align:center;background:#fff;border:1px solid #38a169;color:#2f855a;padding:0.8rem 1rem;border-radius:8px;
                            <i class="bi bi-shield-check"></i> Unban User
                        </button>
                    </form>
                @else
                    <form action="{{ route('admin.users.ban', $user) }}" method="POST" style="display:flex;flex-direction:column;gap:0.5rem;">
                        @csrf
                        <input type="text" name="reason" placeholder="Reason for ban (required)" required style="padding:0.75rem;border:1px solid #e2e8f0;border-radius:8px;wid
                        <button type="submit" style="width:100%;text-align:center;background:#fee2e2;border:1px solid #fc8181;color:#c53030;padding:0.8rem 1rem;border-radius:8
                            <i class="bi bi-x-circle"></i> Permanently Ban
                        </button>
                    </form>
                @endif
            </div>
        </div>
    </div>
    <!-- Related Reports -->
```

```
    <div style="margin-top:2.5rem;">
        <h3 style="margin-bottom:1rem;">Recent Reports Involving User</h3>
        <div style="overflow:auto;background:#fff;border:1px solid #e2e8f0;border-radius:8px;">
            <table style="width:100%;border-collapse:collapse;font-size:0.9rem;">
                <thead>
                    <tr style="text-align:left;background:#f8fafc;color:#64748b;">
                        <th style="padding:0.8rem;">Role</th>
                        <th style="padding:0.8rem;">Subject</th>
                        <th style="padding:0.8rem;">Status</th>
                        <th style="padding:0.8rem;">Date</th>
                        <th style="padding:0.8rem;"></th>
                    </tr>
                </thead>
                <tbody>
                    @forelse($reports as $report)
                    <tr style="border-top:1px solid #e2e8f0;">
                        <td style="padding:0.8rem;">
                            @if($report->user_id === $user->id)
                                <span style="background:#e0e7ff;color:#4338ca;padding:0.2rem 0.5rem;border-radius:4px;font-size:0.75rem;">Reporter</span>
                            @else
                                <span style="background:#fee2e2;color:#b91c1c;padding:0.2rem 0.5rem;border-radius:4px;font-size:0.75rem;">Reported</span>
                            @endif
                        </td>
                        <td style="padding:0.8rem;">{{ $report->subject }}</td>
                        <td style="padding:0.8rem;">{{ ucfirst(str_replace('_', ' ', $report->status)) }}</td>
                        <td style="padding:0.8rem;">{{ $report->created_at->format('M d, Y') }}</td>
                        <td style="padding:0.8rem;text-align:right;">
                            <a href="{{ route('admin.issue-reports.show', $report) }}" style="color:#5b4cff;text-decoration:none;font-weight:600;">View</a>
                        </td>
                    </tr>
                    @empty
                    <tr>
                        <td colspan="5" style="padding:1.5rem;text-align:center;color:#64748b;">No recent reports found for this user.</td>
                    </tr>
                    @endforelse
                </tbody>
            </table>
        </div>
    </div>
</div>
@endsection
```

***File: resources\views\customer\book_detail.blade.php***

```
<!doctype html>
<html lang="en">
  <head>
    <meta charset="UTF-8" />
    <meta name="viewport" content="width=device-width, initial-scale=1.0" />
    <title>{{ $book->title }} - BookHub Store</title>
    <link
      rel="stylesheet"
      href="https://cdnjs.cloudflare.com/ajax/libs/font-awesome/6.4.0/css/all.min.css"
    />
    <style>
      * {
        margin: 0;
        padding: 0;
        box-sizing: border-box;
        font-family: "Segoe UI", Tahoma, Geneva, Verdana, sans-serif;
      }

      body {
        background-color: #f8f9fa;
        color: #333;
        line-height: 1.6;
      }

      .container {
        max-width: 1200px;
        margin: 0 auto;
        padding: 20px;
      }

      .header {
        display: flex;
        justify-content: space-between;
        align-items: center;
        padding: 20px 0;
        border-bottom: 1px solid #e0e0e0;
        margin-bottom: 30px;
      }

      .logo {
        font-size: 1.8rem;
        font-weight: 700;
        color: #2c3e50;
        display: flex;
        align-items: center;
        text-decoration: none;
      }

      .logo i {
        margin-right: 10px;
        color: #3498db;
      }

      .nav-links {
        display: flex;
        gap: 25px;
      }

      .nav-link {
        text-decoration: none;
        color: #2c3e50;
        font-weight: 500;
        display: flex;
        align-items: center;
        gap: 8px;
      }

      .nav-link:hover {
        color: #3498db;
      }

      .cart-badge {
        background-color: #e74c3c;
        color: white;
        border-radius: 50%;
        width: 22px;
        height: 22px;
        display: flex;
        align-items: center;
        justify-content: center;
        font-size: 0.8rem;
        margin-left: 5px;
      }

      .breadcrumb {
        margin-bottom: 30px;
      }

      .breadcrumb a {
        color: #3498db;
        text-decoration: none;
      }

      .book-detail-container {
        display: grid;
        grid-template-columns: 1fr 2fr;
        gap: 40px;
        margin-bottom: 50px;
      }

      .book-cover {
        background-color: white;
        padding: 20px;
        border-radius: 12px;
        box-shadow: 0 4px 12px rgba(0, 0, 0, 0.1);
        text-align: center;
      }

      .book-cover img {
        width: 100%;
        max-width: 300px;
        height: auto;
        border-radius: 8px;
        margin-bottom: 20px;
      }

      .store-badge {
        display: inline-block;
        background-color: #3498db;
        color: white;
        padding: 8px 15px;
        border-radius: 20px;
        font-size: 0.9rem;
        font-weight: 600;
        margin-bottom: 15px;
```

```
}

.book-info {
  background-color: white;
  padding: 30px;
  border-radius: 12px;
  box-shadow: 0 4px 12px rgba(0, 0, 0, 0.1);
}

.book-title {
  font-size: 2.2rem;
  margin-bottom: 15px;
  color: #2c3e50;
}

.book-author {
  font-size: 1.3rem;
  color: #7f8c8d;
  margin-bottom: 20px;
}

.book-meta {
  display: flex;
  gap: 20px;
  margin-bottom: 25px;
  flex-wrap: wrap;
}

.meta-item {
  display: flex;
  flex-direction: column;
}

.meta-label {
  font-size: 0.9rem;
  color: #7f8c8d;
  margin-bottom: 5px;
}

.meta-value {
  font-weight: 600;
  color: #2c3e50;
}

.pricing-section {
  background-color: #f8f9fa;
  padding: 25px;
  border-radius: 10px;
  margin-bottom: 30px;
}

.price-options {
  display: grid;
  grid-template-columns: repeat(auto-fit, minmax(200px, 1fr));
  gap: 20px;
  margin-bottom: 25px;
}

.price-option {
  background-color: white;
  padding: 20px;
  border-radius: 8px;
  text-align: center;
  border: 2px solid transparent;
  transition: all 0.3s;
  cursor: pointer;
}

.price-option.selected {
  border-color: #3498db;
  background-color: #f0f8ff;
}

.price-option:hover {
  transform: translateY(-5px);
  box-shadow: 0 5px 15px rgba(0, 0, 0, 0.1);
}

.price-type {
  font-size: 1.2rem;
  font-weight: 600;
  margin-bottom: 10px;
  color: #2c3e50;
}

.price-amount {
  font-size: 1.8rem;
  font-weight: 700;
  margin-bottom: 10px;
}

.rent-price {
  color: #3498db;
}

.buy-price {
  color: #2ecc71;
}

.price-desc {
  font-size: 0.9rem;
  color: #7f8c8d;
}

.action-buttons {
  display: flex;
  gap: 15px;
  flex-wrap: wrap;
}

.btn {
  padding: 15px 30px;
  border-radius: 8px;
  border: none;
  cursor: pointer;
  font-weight: 600;
  font-size: 1rem;
  display: flex;
  align-items: center;
  justify-content: center;
  gap: 10px;
  transition: all 0.3s;
  flex: 1;
  text-decoration: none;
}

.btn-primary {
  background-color: #3498db;
```

```
  color: white;
}

.btn-primary:hover {
  background-color: #2980b9;
}

.btn-secondary {
  background-color: #2ecc71;
  color: white;
}

.btn-secondary:hover {
  background-color: #27ae60;
}

.btn-wishlist {
  background-color: #f39c12;
  color: white;
}

.btn-wishlist:hover {
  background-color: #d68910;
}

.btn-disabled {
  background-color: #bdc3c7;
  color: #7f8c8d;
  cursor: not-allowed;
}

.similar-books {
  margin-top: 50px;
}

.similar-books h2 {
  margin-bottom: 30px;
  color: #2c3e50;
}

.similar-grid {
  display: grid;
  grid-template-columns: repeat(auto-fill, minmax(250px, 1fr));
  gap: 25px;
}

.similar-card {
  background-color: white;
  border-radius: 8px;
  overflow: hidden;
  box-shadow: 0 4px 8px rgba(0, 0, 0, 0.1);
  transition: transform 0.3s;
  text-decoration: none;
  color: inherit;
}

.similar-card:hover {
  transform: translateY(-5px);
}

.similar-card img {
  width: 100%;
  height: 180px;
  object-fit: cover;
}

.similar-card-content {
  padding: 15px;
}

.similar-card h4 {
  margin-bottom: 10px;
  color: #2c3e50;
}

.similar-card p {
  color: #7f8c8d;
  font-size: 0.9rem;
  margin-bottom: 15px;
}

.similar-card .price {
  font-weight: 600;
  color: #3498db;
}

.messages {
  position: fixed;
  top: 20px;
  right: 20px;
  z-index: 1000;
}

.alert {
  padding: 15px 20px;
  border-radius: 8px;
  margin-bottom: 10px;
  animation: slideIn 0.3s ease-out;
}

.alert-success {
  background-color: #d4edda;
  color: #155724;
  border: 1px solid #c3e6cb;
}

.alert-error {
  background-color: #f8d7da;
  color: #721c24;
  border: 1px solid #f5c6cb;
}

@keyframes slideIn {
  from {
    transform: translateX(100%);
    opacity: 0;
  }
  to {
    transform: translateX(0);
    opacity: 1;
  }
}

@media (max-width: 768px) {
  .book-detail-container {
    grid-template-columns: 1fr;
  }
  .nav-links {
```

```
        display: none;
      }

      .price-options {
        grid-template-columns: 1fr;
      }

      .action-buttons {
        flex-direction: column;
      }

      .similar-grid {
        grid-template-columns: repeat(auto-fill, minmax(200px, 1fr));
      }
    }
  </style>
</head>
<body>
  @php
    $cartCount = count(session('cart', []));
    $wishlistCount = count(session('wishlist', []));
  @endphp

  @if (session('status') || session('error'))
  <div class="messages">
    @if (session('status'))
      <div class="alert alert-success">{{ session('status') }}</div>
    @endif
    @if (session('error'))
      <div class="alert alert-error">{{ session('error') }}</div>
    @endif
  </div>
  @endif

  <div class="container">
    <div class="header">
      <a href="{{ route('customer.dashboard') }}" class="logo">
        <i class="fas fa-book"></i>
        BookHub Store
      </a>
      <div class="nav-links">
        <a href="{{ route('customer.dashboard') }}" class="nav-link">
          <i class="fas fa-home"></i> Home
        </a>
        <a href="{{ route('wishlist.index') }}" class="nav-link">
          <i class="fas fa-heart"></i> Wishlist
          <span class="cart-badge">{{ $wishlistCount }}</span>
        </a>
        <a href="{{ route('cart.index') }}" class="nav-link">
          <i class="fas fa-shopping-cart"></i> Cart
          <span class="cart-badge">{{ $cartCount }}</span>
        </a>
      </div>
    </div>

    <div class="breadcrumb">
      <a href="{{ route('customer.dashboard') }}">Home</a> &gt;
      <a href="{{ route('customer.dashboard', ['genre' => $book->genre]) }}">{{ $book->genre }}</a>
      &gt;
      <span>{{ $book->title }}</span>
    </div>

    <div class="book-detail-container">
      <div class="book-cover">
        <div class="store-badge">Book Store</div>
        @if($book->cover_image_path)
        <img src="{{ asset($book->cover_image_path) }}" alt="{{ $book->title }}" />
        @else
        <img
          src="https://images.unsplash.com/photo-1544716278-ca5e3f4abd8c?ixlib=rb-4.0.3&auto=format&fit=crop&w=600&q=80"
          alt="{{ $book->title }}"
        />
        @endif
        <div style="margin-top: 20px">
          <div style="display: flex; gap: 10px; justify-content: center">
            <span
              style="
                background-color: #e8f4fc;
                color: #3498db;
                padding: 5px 10px;
                border-radius: 5px;
                font-size: 0.9rem;
              "
            >
              {{ $book->genre }}
            </span>
            @if($book->publication_year)
            <span
              style="
                background-color: #f0f0f0;
                color: #666;
                padding: 5px 10px;
                border-radius: 5px;
                font-size: 0.9rem;
              "
            >
              Published: {{ $book->publication_year }}
            </span>
            @endif
          </div>
        </div>
      </div>

      <div class="book-info">
        <h1 class="book-title">{{ $book->title }}</h1>
        <h2 class="book-author">by {{ $book->author }}</h2>

        <div class="book-meta">
          <div class="meta-item">
            <span class="meta-label">Total Copies</span>
            <span class="meta-value">{{ $book->total_copies }}</span>
          </div>
          <div class="meta-item">
            <span class="meta-label">Available for Rent</span>
            <span
              class="meta-value"
              style="color: {{ $canRent ? '#27ae60' : '#e74c3c' }};"
            >
              {{ $book->available_rent }} copies
            </span>
          </div>
          <div class="meta-item">
            <span class="meta-label">Available for Purchase</span>
            <span
              class="meta-value"
              style="color: {{ $canBuy ? '#27ae60' : '#e74c3c' }};"
            >
              {{ $book->available_sale }} copies
```

```
                    </span>
                  </div>
                </div>

                <div class="pricing-section">
                  <h3 style="margin-bottom: 20px; color: #2c3e50">
                    Choose Your Option
                  </h3>

                  <div class="price-options">
                    <div class="price-option" id="rental-option">
                      <div class="price-type">Rent This Book</div>
                      <div class="price-amount rent-price">
                        ${{ number_format($book->rental_price, 2) }}
                      </div>
                      <div class="price-desc">per month</div>
                      <div style="margin-top: 10px; font-size: 0.9rem">
                        @if($canRent)
                        <span style="color: #27ae60">
                          <i class="fas fa-check-circle"></i> {{ $book->available_rent }} available
                        </span>
                        @else
                        <span style="color: #e74c3c">
                          <i class="fas fa-times-circle"></i> Currently unavailable
                        </span>
                        @endif
                      </div>
                    </div>

                    <div class="price-option" id="purchase-option">
                      <div class="price-type">Buy This Book</div>
                      <div class="price-amount buy-price">${{ number_format($book->sale_price, 2) }}</div>
                      <div class="price-desc">one-time purchase</div>
                      <div style="margin-top: 10px; font-size: 0.9rem">
                        @if($canBuy)
                        <span style="color: #27ae60">
                          <i class="fas fa-check-circle"></i> {{ $book->available_sale }} available
                        </span>
                        @else
                        <span style="color: #e74c3c">
                          <i class="fas fa-times-circle"></i> Currently unavailable
                        </span>
                        @endif
                      </div>
                    </div>
                  </div>

                  <div class="action-buttons">
                    @if($canRent)
                    <a href="{{ route('cart.add.rent', $book->id) }}" class="btn btn-primary">
                      <i class="fas fa-exchange-alt"></i> Add to Rental Cart
                    </a>
                    @else
                    <button class="btn btn-disabled" disabled>
                      <i class="fas fa-exchange-alt"></i> Not Available for Rent
                    </button>
                    @endif

                    @if($canBuy)
                    <a href="{{ route('cart.add.buy', $book->id) }}" class="btn btn-secondary">
                      <i class="fas fa-shopping-cart"></i> Add to Purchase Cart
                    </a>
                    @else
                    <button class="btn btn-disabled" disabled>
                      <i class="fas fa-shopping-cart"></i> Not Available for Purchase
                    </button>
                    @endif

                    <a href="{{ route('wishlist.add', $book->id) }}" class="btn btn-wishlist">
                      <i class="fas fa-heart"></i> Add to Wishlist
                    </a>
                  </div>
                </div>
              </div>
            </div>

            @if(!empty($similarBooks) && $similarBooks->count())
            <div class="similar-books">
              <h2>Similar Books You Might Like<
```

(Content truncated due to size - showing first 15KB)

## File: resources\views\customer\cart.blade.php

```
@extends('customer.base')

@section('title', 'Shopping Cart - BookHub Store')

@section('content')
<div class="container">
    <h1 class="cart-title">
        <i class="fas fa-shopping-cart"></i>
        Your Shopping Cart
    </h1>

    <div class="cart-container">
        <div class="cart-items">
            @if(!empty($cartItems))
                @foreach($cartItems as $item)
                <div class="cart-item">
                    <div class="item-image">
                        @if($item['book']->cover_image_path)
                            <img src="{{ asset($item['book']->cover_image_path) }}" alt="{{ $item['book']->title }}">
                        @else
                            <div class="item-image-fallback">No Image</div>
                        @endif
                    </div>
                    <div class="item-details">
                        <h3 class="item-title">{{ $item['book']->title }}</h3>
                        <p class="item-author">by {{ $item['book']->author }}</p>
                        <span class="item-type type-{{ $item['type_class'] }}">
                            @if($item['type'] === 'rent')
                                <i class="fas fa-exchange-alt"></i> Rental - {{ $item['period'] }}
                            @else
                                <i class="fas fa-shopping-cart"></i> Purchase
                            @endif
                        </span>
                    </div>
                    <div class="item-price">
                        <div class="price-amount">${{ number_format($item['price'], 2) }}</div>
                        <div class="item-actions">
                            <a href="{{ route('cart.remove', [$item['book']->id, $item['type']]) }}" class="btn btn-small btn-danger">
                                <i class="fas fa-trash"></i> Remove
                            </a>
                            <a href="{{ route('books.show', $item['book']->id) }}" class="btn btn-small btn-secondary">
```

```
                                <i class="fas fa-eye"></i> View
                            </a>
                        </div>
                    </div>
                </div>
                @endforeach
            @else
                <div class="empty-cart">
                    <i class="fas fa-shopping-cart"></i>
                    <h3>Your cart is empty</h3>
                    <p>Add some books to get started!</p>
                    <a href="{{ route('customer.dashboard') }}" class="btn btn-primary">
                        <i class="fas fa-book"></i> Browse Books
                    </a>
                </div>
            @endif
        </div>

        @if(!empty($cartItems))
        <div class="order-summary">
            <h3>Order Summary</h3>

            @foreach($cartItems as $item)
            <div class="summary-row">
                <span>{{ \Illuminate\Support\Str::limit($item['book']->title, 20) }}</span>
                <span>${{ number_format($item['price'], 2) }}</span>
            </div>
            @endforeach

            <div class="summary-row">
                <span>Subtotal</span>
                <span>${{ number_format($totalPrice, 2) }}</span>
            </div>

            <div class="summary-row">
                <span>Shipping</span>
                <span>$0.00</span>
            </div>

            <div class="summary-row">
                <span>Tax</span>
                <span>$0.00</span>
            </div>

            <div class="summary-row total">
                <span>Total</span>
                <span>${{ number_format($totalPrice, 2) }}</span>
            </div>

            <a href="{{ $checkoutUrl }}" class="btn btn-primary checkout-btn">
                <i class="fas fa-lock"></i> Proceed to Checkout
            </a>

            <div class="continue-shopping">
                <a href="{{ route('customer.dashboard') }}">
                    <i class="fas fa-arrow-left"></i> Continue Shopping
                </a>
            </div>
        </div>
        @endif
    </div>
</div>
@endsection

@section('extra_css')
<style>
.container {
    max-width: 1200px;
    margin: 0 auto;
    padding: 20px;
}

.cart-title {
    font-size: 2rem;
    color: #2c3e50;
    margin: 20px 0 30px;
    display: flex;
    align-items: center;
    gap: 15px;
}

.cart-title i {
    color: #3498db;
}

.cart-container {
    display: grid;
    grid-template-columns: 2fr 1fr;
    gap: 30px;
}

.cart-items {
    background-color: white;
    border-radius: 12px;
    padding: 30px;
    box-shadow: 0 4px 12px rgba(0, 0, 0, 0.1);
}

.empty-cart {
    text-align: center;
    padding: 50px 20px;
}

.empty-cart i {
    font-size: 4rem;
    color: #bdc3c7;
    margin-bottom: 20px;
}

.empty-cart h3 {
    margin-bottom: 15px;
    color: #2c3e50;
}

.empty-cart p {
    color: #7f8c8d;
    margin-bottom: 25px;
}

.btn {
    padding: 12px 30px;
    border-radius: 8px;
    border: none;
    cursor: pointer;
    font-weight: 600;
    font-size: 1rem;
    display: inline-flex;
    align-items: center;
```

```
    justify-content: center;
    gap: 10px;
    transition: all 0.3s;
    text-decoration: none;
}

.btn-primary {
    background-color: #3498db;
    color: white;
}

.btn-primary:hover {
    background-color: #2980b9;
}

.cart-item {
    display: grid;
    grid-template-columns: auto 2fr 1fr;
    gap: 20px;
    padding: 20px 0;
    border-bottom: 1px solid #eee;
    align-items: center;
}

.cart-item:last-child {
    border-bottom: none;
}

.item-image {
    width: 100px;
    height: 140px;
    border-radius: 8px;
    overflow: hidden;
    background: #f4f5f7;
    display: flex;
    align-items: center;
    justify-content: center;
    color: #94a3b8;
    font-size: 0.85rem;
}

.item-image img {
    width: 100%;
    height: 100%;
    object-fit: cover;
}

.item-image-fallback {
    font-weight: 600;
}

.item-details {
    flex-grow: 1;
}

.item-title {
    font-size: 1.2rem;
    font-weight: 600;
    margin-bottom: 8px;
    color: #2c3e50;
}

.item-author {
    color: #7f8c8d;
    margin-bottom: 5px;
}

.item-type {
    display: inline-block;
    padding: 4px 12px;
    border-radius: 15px;
    font-size: 0.9rem;
    font-weight: 500;
    margin-top: 10px;
}

.type-rental {
    background-color: #e8f4fc;
    color: #3498db;
}

.type-purchase {
    background-color: #e8f6ef;
    color: #27ae60;
}

.item-price {
    text-align: right;
}

.price-amount {
    font-size: 1.3rem;
    font-weight: 700;
    color: #2c3e50;
    margin-bottom: 10px;
}

.item-actions {
    display: flex;
    gap: 10px;
    justify-content: flex-end;
    margin-top: 10px;
}

.btn-small {
    padding: 8px 15px;
    font-size: 0.9rem;
}

.btn-danger {
    background-color: #e74c3c;
    color: white;
}

.btn-danger:hover {
    background-color: #c0392b;
}

.btn-secondary {
    background-color: #f0f0f0;
    color: #333;
}

.order-summary {
    background-color: white;
    border-radius: 12px;
    padding: 30px;
    box-shadow: 0 4px 12px rgba(0, 0, 0, 0.1);
```

```
    height: fit-content;
    position: sticky;
    top: 20px;
}

.order-summary h3 {
    margin-bottom: 25px;
    color: #2c3e50;
    padding-bottom: 15px;
    border-bottom: 2px solid #f0f0f0;
}

.summary-row {
    display: flex;
    justify-content: space-between;
    margin-bottom: 15px;
    padding: 8px 0;
}

.summary-row.total {
    border-top: 2px solid #f0f0f0;
    margin-top: 15px;
    padding-top: 20px;
    font-size: 1.2rem;
    font-weight: 700;
    color: #2c3e50;
}

.checkout-btn {
    width: 100%;
    padding: 16px;
    font-size: 1.1rem;
    margin-top: 25px;
}

.continue-shopping {
    margin-top: 20px;
    text-align: center;
}

.continue-shopping a {
    color: #3498db;
    text-decoration: none;
    display: inline-flex;
    align-items: center;
    gap: 8px;
}

.continue-shopping a:hover {
    text-decoration: underline;
}

@media (max-width: 768px) {
    .cart-container {
        grid-template-columns: 1fr;
    }

    .cart-item {
        grid-template-columns: 1fr;
        text-align: center;
    }

    .item-price, .item-actions {
        text-align: center;
        justify-content: center;
    }
}
</style>
@endsection
```

### *File: resources\views\customer\chat_index.blade.php*

```
@extends('customer.base')

@section('title', 'Support Chat - BookHub')

@section('content')
<section class="chat-shell">
    <div class="chat-head">
        <div>
            <h1>Support Chat</h1>
            <p>Start a conversation with our support team and track replies.</p>
        </div>
        <a href="{{ route('issue-reports.create') }}" class="btn-pill">Report an Issue</a>
    </div>

    <div class="chat-grid">
        <div class="chat-panel">
            <h2>Start a New Conversation</h2>
            <form method="POST" action="{{ route('chat.start') }}" class="chat-form">
                @csrf
                <label class="field">
                    <span>Subject</span>
                    <input type="text" name="subject" value="{{ old('subject') }}" required maxlength="255" placeholder="Payment issue, rental question, etc.">
                </label>
                <label class="field">
                    <span>Message</span>
                    <textarea name="message" rows="5" required maxlength="2000" placeholder="Tell us how we can help.">{{ old('message') }}</textarea>
                </label>
                <button class="btn-primary" type="submit">
                    <i class="bi bi-chat-dots-fill"></i>
                    Start Chat
                </button>
            </form>
        </div>

        <div class="chat-panel">
            <div class="panel-head">
                <h2>Your Conversations</h2>
                <span class="pill">{{ $conversations->count() }}</span>
            </div>

            <div class="chat-list">
                @forelse($conversations as $conversation)
                    <a href="{{ route('chat.show', $conversation) }}" class="chat-item">
                        <div class="chat-item-main">
                            <h3>{{ $conversation->subject ?? 'Support Request' }}</h3>
                            <p>
                                @if($conversation->latestMessage)
                                    {{ \Illuminate\Support\Str::limit($conversation->latestMessage->message, 90) }}
                                @else
                                    No messages yet.
                                @endif
                            </p>
                        </div>
```

```
                        <div class="chat-item-meta">
                            <span>{{ optional($conversation->last_message_at)->format('M d, Y H:i') ?? $conversation->created_at->format('M d, Y H:i') }}</span>
                            @if($conversation->unread_count)
                                <span class="badge">{{ $conversation->unread_count }}</span>
                            @endif
                        </div>
                    </a>
                @empty
                    <div class="chat-empty">
                        <i class="bi bi-chat-square-dots"></i>
                        <p>No conversations yet. Start a new chat to reach support.</p>
                    </div>
                @endforelse
            </div>
        </div>
    </div>
</section>
@endsection

@section('extra_css')
<style>
.chat-shell {
    max-width: 1180px;
    margin: 0 auto;
    display: flex;
    flex-direction: column;
    gap: 1.5rem;
}
.chat-head {
    display: flex;
    align-items: center;
    justify-content: space-between;
    gap: 1rem;
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
    padding: 1.2rem 1.5rem;
    box-shadow: var(--shadow-sm);
}
.chat-head h1 {
    margin: 0 0 0.35rem 0;
    font-size: 1.6rem;
}
.chat-head p {
    margin: 0;
    color: var(--text-secondary);
    font-size: 0.9rem;
}
.btn-pill {
    display: inline-flex;
    align-items: center;
    gap: 0.5rem;
    padding: 0.6rem 1.1rem;
    border-radius: 999px;
    background: var(--primary-soft);
    color: var(--primary);
    font-weight: 700;
    text-decoration: none;
    border: 1px solid var(--border);
}
.chat-grid {
    display: grid;
    grid-template-columns: minmax(280px, 1fr) minmax(300px, 1.2fr);
    gap: 1.2rem;
}
.chat-panel {
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
    padding: 1.2rem 1.4rem;
    box-shadow: var(--shadow-sm);
}
.chat-panel h2 {
    margin: 0 0 1rem 0;
    font-size: 1.1rem;
}
.panel-head {
    display: flex;
    align-items: center;
    justify-content: space-between;
}
.pill {
    background: var(--bg-raised);
    border: 1px solid var(--border);
    padding: 0.2rem 0.6rem;
    border-radius: 999px;
    font-size: 0.75rem;
    font-weight: 700;
    color: var(--text-secondary);
}
.chat-form {
    display: grid;
    gap: 0.9rem;
}
.field {
    display: grid;
    gap: 0.4rem;
    font-size: 0.82rem;
    color: var(--text-secondary);
    font-weight: 600;
}
.field input,
.field textarea {
    background: var(--bg-raised);
    border: 1px solid var(--border);
    border-radius: var(--radius);
    padding: 0.7rem 0.8rem;
    font-family: 'Outfit', sans-serif;
    color: var(--text-primary);
}
.field textarea { resize: vertical; }
.btn-primary {
    display: inline-flex;
    align-items: center;
    gap: 0.5rem;
    padding: 0.7rem 1.2rem;
    border-radius: 999px;
    background: var(--primary);
    color: #fff;
    border: none;
    font-weight: 700;
    cursor: pointer;
}
.chat-list {
    display: grid;
    gap: 0.8rem;
}
.chat-item {
```

```
    display: flex;
    justify-content: space-between;
    gap: 1rem;
    padding: 0.85rem 1rem;
    border-radius: var(--radius);
    border: 1px solid var(--border);
    background: var(--bg-raised);
    text-decoration: none;
    color: inherit;
    transition: all var(--t-fast);
}
.chat-item:hover {
    border-color: var(--primary);
    box-shadow: var(--shadow-sm);
}
.chat-item-main h3 {
    margin: 0 0 0.3rem 0;
    font-size: 0.95rem;
}
.chat-item-main p {
    margin: 0;
    color: var(--text-secondary);
    font-size: 0.8rem;
}
.chat-item-meta {
    display: grid;
    justify-items: end;
    gap: 0.4rem;
    font-size: 0.7rem;
    color: var(--text-muted);
}
.badge {
    background: var(--primary);
    color: #fff;
    font-weight: 700;
    font-size: 0.7rem;
    padding: 0.1rem 0.5rem;
    border-radius: 999px;
}
.chat-empty {
    text-align: center;
    padding: 1.5rem 0;
    color: var(--text-muted);
}
.chat-empty i {
    font-size: 2rem;
    display: block;
    margin-bottom: 0.4rem;
}
@media (max-width: 900px) {
    .chat-grid {
        grid-template-columns: 1fr;
    }
}
</style>
@endsection
```

### *File: resources\views\customer\chat_list.blade.php*

```
@extends('customer.base')

@section('title', 'My Chats')

@section('content')
<div class="container">
    <!-- Header -->
    <div class="d-flex justify-content-between align-items-center mb-4">
        <div>
            <h1 class="h3 mb-0">My Conversations</h1>
            <p class="text-muted mt-2">Chat with store owners about books and orders</p>
        </div>
        <div class="d-flex gap-2">
            <span class="badge bg-danger p-3">
                <i class="bi bi-envelope-paper-fill me-2"></i>
                {{ $unread_total ?? 0 }} Unread
            </span>
            <button class="btn btn-primary" data-bs-toggle="modal" data-bs-target="#newChatModal">
                <i class="bi bi-plus-lg me-2"></i>New Chat
            </button>
        </div>
    </div>

    <!-- Filters -->
    <div class="card border-0 shadow-sm mb-4">
        <div class="card-body">
            <div class="row g-3">
                <div class="col-md-6">
                    <div class="input-group">
                        <span class="input-group-text bg-transparent border-end-0">
                            <i class="bi bi-search"></i>
                        </span>
                        <input type="text"
                               id="search-input"
                               class="form-control border-start-0 ps-0"
                               placeholder="Search conversations...">
                    </div>
                </div>
                <div class="col-md-3">
                    <select id="status-filter" class="form-select">
                        <option value="all">All Conversations</option>
                        <option value="unread">Unread Only</option>
                    </select>
                </div>
                <div class="col-md-3">
                    <button class="btn btn-outline-secondary w-100" onclick="resetFilters()">
                        <i class="bi bi-arrow-counterclockwise me-2"></i>Reset
                    </button>
                </div>
            </div>
        </div>
    </div>

    <!-- Conversations List -->
    <div id="conversations-list">
        @if($conversations->count() > 0)
            @foreach($conversations as $conv)
                <div class="conversation-item mb-3"
                     data-unread="{{ $conv->unread_count > 0 ? 'true' : 'false' }}"
                     data-search="{{ strtolower($conv->store->name ?? '') }} {{ strtolower($conv->subject ?? '') }}">
                    <a href="{{ route('chat.show', $conv) }}" class="text-decoration-none">
                        <div class="card border-0 shadow-sm hover-shadow {{ $conv->unread_count > 0 ? 'border-start border-danger border-4' : '' }}">
                            <div class="card-body">
                                <div class="d-flex align-items-start gap-3">
                                    <!-- Avatar -->
                                    <div class="flex-shrink-0">
```

```
                                        <div class="avatar-circle bg-primary text-white">
                                            {{ substr($conv->store->name ?? 'S', 0, 1) }}
                                        </div>
                                    </div>

                                    <!-- Content -->
                                    <div class="flex-grow-1">
                                        <div class="d-flex justify-content-between align-items-center mb-2">
                                            <div>
                                                <h5 class="mb-1 fw-bold">
                                                    {{ $conv->store->name ?? 'Store' }}
                                                    @if($conv->unread_count > 0)
                                                        <span class="badge bg-danger ms-2">{{ $conv->unread_count }} new</span>
                                                    @endif
                                                </h5>
                                            </div>
                                            <div class="text-end">
                                                <small class="text-muted">
                                                    {{ $conv->last_message_at?->diffForHumans() ?? $conv->created_at->diffForHumans() }}
                                                </small>
                                            </div>
                                        </div>

                                        @if($conv->book)
                                            <div class="mb-2">
                                                <span class="badge bg-info">
                                                    <i class="bi bi-book me-1"></i>
                                                    {{ $conv->book->title }}
                                                </span>
                                            </div>
                                        @endif

                                        @if($conv->subject)
                                            <p class="fw-semibold mb-1">{{ $conv->subject }}</p>
                                        @endif

                                        <p class="mb-0 text-muted">
                                            <i class="bi bi-chat-dots me-1"></i>
                                            {{ $conv->last_message ?? 'No messages yet' }}
                                        </p>
                                    </div>
                                </div>
                            </div>
                        </div>
                    </a>
                </div>
            @endforeach
        @else
            <div class="card border-0 shadow-sm">
                <div class="card-body text-center py-5">
                    <div class="py-5">
                        <i class="bi bi-chat-dots display-1 text-muted"></i>
                        <h3 class="mt-3">No Conversations Yet</h3>
                        <p class="text-muted">Start a chat with a store owner to ask about books!</p>
                        <button class="btn btn-primary mt-3" data-bs-toggle="modal" data-bs-target="#newChatModal">
                            <i class="bi bi-plus-lg me-2"></i>Start New Chat
                        </button>
                    </div>
                </div>
            </div>
        @endif
    </div>
</div>

<!-- New Chat Modal -->
<div class="modal fade" id="newChatModal" tabindex="-1">
    <div class="modal-dialog">
        <div class="modal-content">
            <div class="modal-header">
                <h5 class="modal-title">Start New Chat</h5>
                <button type="button" class="btn-close" data-bs-dismiss="modal"></button>
            </div>
            <form action="{{ route('chat.start') }}" method="POST">
                @csrf
                <div class="modal-body">
                    <div class="mb-3">
                        <label class="form-label">Select Store</label>
                        <select name="store_id" class="form-select" required>
                            <option value="">Choose a store...</option>
                            @foreach($recentStores as $store)
                                <option value="{{ $store->id }}">{{ $store->name }}</option>
                            @endforeach
                        </select>
                    </div>

                    <div class="mb-3">
                        <label class="form-label">Subject (Optional)</label>
                        <input type="text" name="subject" class="form-control"
                               placeholder="e.g., Question about a book">
                    </div>

                    <div class="mb-3">
                        <label class="form-label">Message</label>
                        <textarea name="message" class="form-control" rows="4" required
                                  placeholder="What would you like to ask?"></textarea>
                    </div>
                </div>
                <div class="modal-footer">
                    <button type="button" class="btn btn-secondary" data-bs-dismiss="modal">Cancel</button>
                    <button type="submit" class="btn btn-primary">Start Chat</button>
                </div>
            </form>
        </div>
    </div>
</div>

<style>
.avatar-circle {
    width: 50px;
    height: 50px;
    border-radius: 50%;
    display: flex;
    align-items: center;
    justify-content: center;
    font-weight: 600;
    font-size: 1.2rem;
}
.hover-shadow {
    transition: all 0.3s ease;
}
.hover-shadow:hover {
    transform: translateY(-2px);
    box-shadow: 0 0.5rem 1rem rgba(0,0,0,0.15) !important;
}
.border-start.border-danger {
    border-left-width: 4px !important;
}
</style>
```

```
<script>
document.addEventListener('DOMContentLoaded', function() {
    const searchInput = document.getElementById('search-input');
    const statusFilter = document.getElementById('status-filter');
    const conversationItems = document.querySelectorAll('.conversation-item');

    function filterConversations() {
        const searchTerm = searchInput.value.toLowerCase().trim();
        const showUnreadOnly = statusFilter.value === 'unread';

        conversationItems.forEach(item => {
            const searchText = item.dataset.search || '';
            const isUnread = item.dataset.unread === 'true';

            let show = true;

            // Search filter
            if (searchTerm && !searchText.includes(searchTerm)) {
                show = false;
            }

            // Unread filter
            if (showUnreadOnly && !isUnread) {
                show = false;
            }

            item.style.display = show ? 'block' : 'none';
        });
    }

    searchInput.addEventListener('input', filterConversations);
    statusFilter.addEventListener('change', filterConversations);

    window.resetFilters = function() {
        searchInput.value = '';
        statusFilter.value = 'all';
        filterConversations();
    };
});
</script>
@endsection
```

## File: resources\views\customer\chat_room.blade.php

```
@extends('customer.base')

@section('title', 'Chat with ' . ($conversation->store->name ?? 'Store'))

@section('content')
<div class="container-fluid" style="max-width: 1200px;">
    <!-- Back Button -->
    <div class="mb-3">
        <a href="{{ route('chat.index') }}" class="btn btn-outline-secondary">
            <i class="bi bi-arrow-left me-2"></i>Back to Chats
        </a>
    </div>

    <!-- Chat Room -->
    <div class="card border-0 shadow-sm">
        <!-- Chat Header -->
        <div class="card-header bg-white py-3 d-flex justify-content-between align-items-center">
            <div class="d-flex align-items-center gap-3">
                <div class="avatar-circle bg-primary text-white">
                    {{ substr($conversation->store->name ?? 'S', 0, 1) }}
                </div>
                <div>
                    <h5 class="mb-1">{{ $conversation->store->name ?? 'Store' }}</h5>
                    <p class="small text-muted mb-0">
                        @if($conversation->store?->isOnline())
                            <span class="text-success"><i class="bi bi-circle-fill me-1" style="font-size: 0.5rem;"></i>Online</span>
                        @else
                            <span class="text-muted"><i class="bi bi-circle-fill me-1" style="font-size: 0.5rem;"></i>Offline</span>
                        @endif
                    </p>
                </div>
            </div>
            <div>
                @if($conversation->book)
                    <span class="badge bg-info">
                        <i class="bi bi-book me-1"></i>
                        {{ $conversation->book->title }}
                    </span>
                @endif
            </div>
        </div>

        <!-- Messages -->
        <div class="card-body" id="messages-container" style="height: 500px; overflow-y: auto; background: #f8f9fa;">
            @forelse($messages as $message)
                <div class="message-item mb-3 {{ $message->sender_id === auth()->id() ? 'text-end' : '' }}">
                    <div class="d-inline-block" style="max-width: 70%;">
                        <div class="message-bubble p-3 rounded-3 {{ $message->sender_id === auth()->id() ? 'bg-primary text-white' : 'bg-white' }}">
                            @if($message->message)
                                <p class="mb-1">{{ $message->message }}</p>
                            @endif

                            @if($message->hasAttachment())
                                <div class="attachment-preview mt-2 p-2 {{ $message->sender_id === auth()->id() ? 'bg-primary bg-opacity-25' : 'bg-light' }} rounded-2">
                                    @if($message->isImage())
                                        <img src="{{ $message->attachment_url }}"
                                             alt="Attachment"
                                             class="img-fluid rounded-2 mb-2"
                                             style="max-height: 150px; cursor: pointer;"
                                             onclick="window.open('{{ $message->attachment_url }}', '_blank')">
                                    @endif
                                    <div class="d-flex align-items-center gap-2">
                                        <i class="bi {{ $message->isImage() ? 'bi-image' : 'bi-file-earmark' }}"></i>
                                        <small class="text-truncate" style="max-width: 200px;">
                                            {{ $message->attachment_name }}
                                        </small>
                                        <a href="{{ $message->attachment_url }}"
                                           class="{{ $message->sender_id === auth()->id() ? 'text-white' : 'text-primary' }}"
                                           target="_blank"
                                           download>
                                            <i class="bi bi-download"></i>
                                        </a>
                                    </div>
                                </div>
                            @endif

                            <small class="d-block mt-2 {{ $message->sender_id === auth()->id() ? 'text-white-50' : 'text-muted' }}">
                                {{ $message->created_at->format('g:i A') }}
                                @if($message->sender_id === auth()->id())
                                    @if($message->is_read)
                                        <i class="bi bi-check2-all ms-1" title="Read"></i>
```

```
                                @else
                                    <i class="bi bi-check2 ms-1" title="Sent"></i>
                                @endif
                            @endif
                        </small>
                    </div>
                </div>
            </div>
            @empty
                <div class="text-center py-5">
                    <i class="bi bi-chat-dots display-1 text-muted"></i>
                    <p class="text-muted mt-3">No messages yet. Start the conversation!</p>
                </div>
            @endforelse
        </div>

        <!-- Message Input -->
        <div class="card-footer bg-white py-3">
            <form id="message-form" enctype="multipart/form-data">
                @csrf
                <div class="d-flex gap-2">
                    <div class="flex-grow-1">
                        <textarea name="message"
                                  id="message-input"
                                  class="form-control"
                                  rows="2"
                                  placeholder="Type your message..."
                                  style="resize: none;"></textarea>
                    </div>
                    <div class="d-flex flex-column gap-2">
                        <div class="dropdown">
                            <button class="btn btn-outline-secondary" type="button" data-bs-toggle="dropdown" id="attach-btn">
                                <i class="bi bi-paperclip"></i>
                            </button>
                            <div class="dropdown-menu p-3" style="min-width: 300px;">
                                <input type="file"
                                       id="attachment-input"
                                       name="attachment"
                                       class="form-control"
                                       accept="image/*,.pdf,.doc,.docx,.txt,.zip">
                                <div class="form-text mt-2">
                                    Max size: 10MB
                                </div>
                            </div>
                        </div>
                        <button type="submit" class="btn btn-primary" id="send-btn">
                            <i class="bi bi-send-fill"></i>
                        </button>
                    </div>
                </div>
            </form>
            <div id="attachment-preview" class="mt-2" style="display: none;">
                <div class="alert alert-info d-flex align-items-center justify-content-between py-2">
                    <span id="attachment-name"></span>
                    <button type="button" class="btn-close" onclick="clearAttachment()"></button>
                </div>
            </div>
        </div>
    </div>
</div>

<style>
.avatar-circle {
    width: 40px;
    height: 40px;
    border-radius: 50%;
    display: flex;
    align-items: center;
    justify-content: center;
    font-weight: 600;
    font-size: 1rem;
}
.message-bubble {
    word-wrap: break-word;
    box-shadow: 0 2px 5px rgba(0,0,0,0.1);
}
.bg-primary .text-white-50 {
    color: rgba(255,255,255,0.7) !important;
}
.attachment-preview {
    border: 1px solid rgba(0,0,0,0.1);
}
#messages-container {
    scroll-behavior: smooth;
}
</style>

<script>
document.addEventListener('DOMContentLoaded', function() {
    const conversationId = {{ $conversation->id }};
    const messagesContainer = document.getElementById('messages-container');
    const messageForm = document.getElementById('message-form');
    const messageInput = document.getElementById('message-input');
    const sendBtn = document.getElementById('send-btn');
    const attachmentInput = document.getElementById('attachment-input');
    const attachmentPreview = document.getElementById('attachment-preview');
    const attachmentName = document.getElementById('attachment-name');

    let lastMessageId = {{ $messages->last()->id ?? 0 }};
    let pollingInterval;
    let isSubmitting = false;

    // Scroll to bottom on load
    scrollToBottom();

    // Auto-resize textarea
    messageInput.addEventListener('input', function() {
        this.style.height = 'auto';
        this.style.height = (this.scrollHeight) + 'px';
    });

    // Handle file selection
    attachmentInput.addEventListener('change', function() {
        if (this.files.length > 0) {
            const file = this.files[0];
            const fileSize = (file.size / 1024).toFixed(1);
            attachmentName.textContent = file.name + ' (' + fileSize + ' KB)';
            attachmentPreview.style.display = 'block';
        } else {
            clearAttachment();
        }
    });

    // Handle form submission
    messageForm.addEventListener('submit', async function(e) {
        e.preventDefault();

        if (isSubmitting) return;
```

```
    const formData = new FormData();
    const message = messageInput.value.trim();
    const attachment = attachmentInput.files[0];

    if (!message && !attachment) {
        alert('Please enter a message or select a file to attach.');
        return;
    }

    if (message) {
        formData.append('message', message);
    }

    if (attachment) {
        formData.append('attachment', attachment);
    }

    // Disable form
    isSubmitting = true;
    setFormDisabled(true);

    try {
        console.log('Sending message to:', `/chat/${conversationId}/send`);

        const response = await fetch(`/chat/${conversationId}/send`, {
            method: 'POST',
            headers: {
                'X-CSRF-TOKEN': document.querySelector('input[name="_token"]').value,
                'X-Requested-With': 'XMLHttpRequest'
            },
            body: formData
        });

        const data = await response.json();
        console.log('Response:', data);

        if (data.success) {
            // Clear form
            messageInput.value = '';
            messageInput.style.height = 'auto';
            clearAttachment();

            // Append new message
            appendMessage(data.message);
            scrollToBottom();

            // Update last message ID
            if (data.message.id > lastMessageId) {
                lastMessageId = data.message.id;
            }
        } else {
            alert('Failed to send message: ' + (data.error || 'Unknown error'));
        }
    } catch (error) {
        console.error('Error:', error);
        alert('Failed to send message. Please check your connection and try again.');
    } finally {
        isSubmitting = false;
        setFormDisabled(false);
    }
});

// Poll for new messages
function startPolling() {
    pollingInterval = setInterval(pollMessages, 3000);
}

async function pollMessages() {
    try {
        const response = await fetch(`/chat/${conversationId}/poll?last_id=${lastMessageId}`);
        const data = await response.json();

        if (data.success && data.messages && data.messages.length > 0) {
            data.messages.forEach(msg => {
                appendMessage(msg);
                lastMessageId = Math.max(lastMessageId, msg.id);
            });
            scrollToBottom();
        }
    } catch (error) {
        console.error('Polling error:', error);
    }
}

function appendMessage(message) {
    // Check if message already exists
    if (document.querySelector(`[data-message-id="${message.id}"]`)) {
        return;
    }

    const messageDiv = document.createElement('div');
    messageDiv.className = `message-item mb-3 ${message.is_me ? 'text-end' : ''}`;
    messageDiv.setAttribute('data-message-id', message.id);

    let attachmentHtml = '';
    if (message.attachment_url) {
        attachmentHtml = `
            <div class="attachment-preview mt-2 p-2 ${message.is_me ? 'bg-primary bg-opacity-25' : 'bg-light'} rounded-2">
                ${message.is_image ?
                    `<img src="${message.attachment_url}" alt="Attachment" class="img-fluid rounded-2 mb-2" style="max-height: 150px; cursor: pointer;" onclick="window.ope
                    : ''
                }
                <div class="d-flex align-items-center gap-2">
                    <i class="bi ${message.is_image ? 'bi-image' : 'bi-file-earmark'}"></i>
                    <small class="text-truncate" style="max-width: 200px;">${escapeHtml(message.attachment_name || 'Attachment')}</small>
                    <a href="${message.attachment_url}" class="${message.is_me ? 'text-white' : 'text-primary'}" target="_blank" download>
                        <i class="bi bi-download"></i>
                    </a>
                </div>
            </div>
        `;
    }

    messageDiv.innerHTML = `
        <div class="d-inline-block" style="max-width: 70%;">
            <div class="message-bubble p-3 rounded-3 ${message.is_me ? 'bg-primary text-white' : 'bg-white'}">
                ${message.content ? `<p class="mb-1">${escapeHtml(message.content)}</p>` : ''}
                ${attachmentHtml}
                <small class="d-block mt-2 ${message.is_me ? 'text-white-50' : 'text-muted'}">
                    ${message.formatted_time || message.created_at}
                    ${message.is_me ? '<i class="bi bi-check2 ms-1" title="Sent"></i>' : ''}
                </small>
            </div>
        </div>
    `;

    messagesContainer.appendChild(messageDiv);
}
```

```
    function setFormDisabled(disabled) {
        messageInput.disabled = disabled;
        attachmentInput.disabled = disabled;
        sendBtn.disabled = disabled;
        if (disabled) {
            sendBtn.innerHTML = '<span class="spinner-border spinner-border-sm"></span>';
```

(Content truncated due to size - showing first 15KB)

## File: resources\views\customer\chat_show.blade.php

```
@extends('customer.base')

@section('title', 'Chat - BookHub')

@section('content')
<section class="chat-room">
    <div class="chat-room-head">
        <div>
            <a href="{{ route('chat.index') }}" class="back-link"><i class="bi bi-arrow-left"></i> Back to chats</a>
            <h1>{{ $conversation->subject ?? 'Support Request' }}</h1>
            <p>Status: <strong>{{ ucfirst(str_replace('_', ' ', $conversation->status)) }}</strong></p>
        </div>
        <div class="chat-meta">
            <span>Started {{ $conversation->created_at->format('M d, Y') }}</span>
            @if($conversation->assignedAdmin)
                <span>Assigned to {{ $conversation->assignedAdmin->name }}</span>
            @endif
        </div>
    </div>

    <div class="chat-messages">
        @forelse($messages as $message)
            @php $mine = (int) $message->sender_id === (int) auth()->id(); @endphp
            <div class="message {{ $mine ? 'outgoing' : 'incoming' }}">
                <div class="message-bubble">
                    <p>{{ $message->message }}</p>
                    <span>{{ $message->created_at->format('M d, Y H:i') }}</span>
                </div>
            </div>
        @empty
            <div class="chat-empty">
                <i class="bi bi-chat-square-dots"></i>
                <p>No messages yet. Send the first message below.</p>
            </div>
        @endforelse
    </div>

    <form method="POST" action="{{ route('chat.message', $conversation) }}" class="chat-input">
        @csrf
        <textarea name="message" rows="3" required maxlength="2000" placeholder="Type your message..."></textarea>
        <button type="submit" class="btn-send">
            <i class="bi bi-send-fill"></i>
            Send
        </button>
    </form>
</section>
@endsection

@section('extra_css')
<style>
.chat-room {
    max-width: 980px;
    margin: 0 auto;
    display: grid;
    gap: 1.2rem;
}
.chat-room-head {
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
    padding: 1.2rem 1.4rem;
    box-shadow: var(--shadow-sm);
    display: flex;
    justify-content: space-between;
    gap: 1rem;
}
.chat-room-head h1 {
    margin: 0.4rem 0 0.3rem;
    font-size: 1.4rem;
}
.chat-room-head p {
    margin: 0;
    color: var(--text-secondary);
    font-size: 0.85rem;
}
.back-link {
    text-decoration: none;
    color: var(--primary);
    font-size: 0.85rem;
    font-weight: 600;
    display: inline-flex;
    align-items: center;
    gap: 0.35rem;
}
.chat-meta {
    display: grid;
    gap: 0.35rem;
    font-size: 0.75rem;
    color: var(--text-muted);
    text-align: right;
}
.chat-messages {
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
    padding: 1.2rem;
    min-height: 280px;
    display: flex;
    flex-direction: column;
    gap: 0.75rem;
    box-shadow: var(--shadow-sm);
}
.message {
    display: flex;
}
.message.incoming {
    justify-content: flex-start;
}
.message.outgoing {
    justify-content: flex-end;
}
.message-bubble {
    max-width: 70%;
    background: var(--bg-raised);
```

```
    border: 1px solid var(--border);
    border-radius: 16px;
    padding: 0.75rem 0.9rem;
    box-shadow: var(--shadow-sm);
}
.message.outgoing .message-bubble {
    background: var(--primary);
    color: #fff;
    border-color: transparent;
}
.message-bubble p {
    margin: 0 0 0.35rem 0;
    font-size: 0.88rem;
}
.message-bubble span {
    font-size: 0.7rem;
    opacity: 0.7;
}
.chat-input {
    display: grid;
    gap: 0.6rem;
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
    padding: 1rem 1.2rem;
    box-shadow: var(--shadow-sm);
}
.chat-input textarea {
    background: var(--bg-raised);
    border: 1px solid var(--border);
    border-radius: var(--radius);
    padding: 0.7rem 0.8rem;
    font-family: 'Outfit', sans-serif;
    color: var(--text-primary);
    resize: vertical;
}
.btn-send {
    justify-self: flex-end;
    display: inline-flex;
    align-items: center;
    gap: 0.4rem;
    padding: 0.6rem 1.1rem;
    border-radius: 999px;
    border: none;
    background: var(--primary);
    color: #fff;
    font-weight: 700;
    cursor: pointer;
}
.chat-empty {
    text-align: center;
    color: var(--text-muted);
    margin: auto 0;
}
.chat-empty i {
    font-size: 2rem;
    display: block;
    margin-bottom: 0.4rem;
}
@media (max-width: 700px) {
    .chat-room-head {
        flex-direction: column;
        align-items: flex-start;
    }
    .chat-meta {
        text-align: left;
    }
    .message-bubble {
        max-width: 100%;
    }
}
</style>
@endsection
```

### File: resources\views\customer\checkout.blade.php

```
{% extends 'customer/base.html' %}

{% block content %}
<div class="container" style="max-width: 800px; margin: 0 auto;">
    <h1 style="color: #2c3e50; margin-bottom: 30px;">
        <i class="fas fa-shopping-cart"></i> Checkout
    </h1>

    {% if messages %}
    <div style="margin-bottom: 20px;">
        {% for message in messages %}
        <div class="alert alert-{{ message.tags }}">
            {{ message }}
        </div>
        {% endfor %}
    </div>
    {% endif %}

    <div class="checkout-container" style="background: white; border-radius: 12px; padding: 30px; box-shadow: 0 4px 12px rgba(0,0,0,0.05);">
        <!-- Order Summary -->
        <div class="order-summary" style="margin-bottom: 30px;">
            <h3 style="color: #2c3e50; margin-bottom: 20px; border-bottom: 2px solid #ecf0f1; padding-bottom: 10px;">
                <i class="fas fa-receipt"></i> Order Summary
            </h3>

            <div id="cart-items">
                {% for item in rental_items %}
                <div class="cart-item" style="display: flex; justify-content: space-between; align-items: center; padding: 15px 0; border-bottom: 1px solid #f1f2f6;">
                    <div>
                        <h4 style="margin: 0; color: #2c3e50;">{{ item.title }}</h4>
                        <p style="margin: 5px 0; color: #7f8c8d;">by {{ item.author }} • Rental</p>
                    </div>
                    <div style="text-align: right;">
                        <p style="margin: 0; font-weight: 600; color: #2c3e50;">${{ item.rental_price }}/day</p>
                    </div>
                </div>
                {% endfor %}

                {% for item in purchase_items %}
                <div class="cart-item" style="display: flex; justify-content: space-between; align-items: center; padding: 15px 0; border-bottom: 1px solid #f1f2f6;">
                    <div>
                        <h4 style="margin: 0; color: #2c3e50;">{{ item.title }}</h4>
                        <p style="margin: 5px 0; color: #7f8c8d;">by {{ item.author }} • Purchase</p>
                    </div>
                    <div style="text-align: right;">
                        <p style="margin: 0; font-weight: 600; color: #2c3e50;">${{ item.sale_price }}</p>
                    </div>
                </div>
                {% endfor %}
```

```
        </div>

        <div class="totals" style="margin-top: 20px; padding-top: 20px; border-top: 2px solid #ecf0f1;">
            <div style="display: flex; justify-content: space-between; margin-bottom: 10px;">
                <span>Subtotal:</span>
                <span style="font-weight: 600;">${{ total }}</span>
            </div>
            <div style="display: flex; justify-content: space-between; margin-bottom: 10px;">
                <span>Delivery Fee:</span>
                <span style="font-weight: 600;" id="delivery-fee">$0.00</span>
            </div>
            <div style="display: flex; justify-content: space-between; font-size: 1.2rem; font-weight: 700; color: #2c3e50; padding-top: 10px; border-top: 1px solid #ecf0f
                <span>Total:</span>
                <span id="total-amount">${{ total }}</span>
            </div>
        </div>
    </div>

    <!-- Order Form -->
    <form id="order-form" method="POST" action="{% url 'create_order' %}">
        {% csrf_token %}

        <!-- Order Type -->
        <div class="form-section" style="margin-bottom: 25px;">
            <h3 style="color: #2c3e50; margin-bottom: 15px;">
                <i class="fas fa-tag"></i> Order Type
            </h3>
            <div style="display: flex; gap: 20px; align-items: center;">
                {% if rental_items %}
                <div>
                    <input type="radio" id="rent" name="order_type" value="rent" checked>
                    <label for="rent" style="margin-left: 5px;">Rental</label>
                </div>
                {% endif %}
                {% if purchase_items %}
                <div>
                    <input type="radio" id="buy" name="order_type" value="buy" {% if not rental_items %}checked{% endif %}>
                    <label for="buy" style="margin-left: 5px;">Purchase</label>
                </div>
                {% endif %}
            </div>

            <!-- Rental Duration (shown only for rentals) -->
            <div id="rental-duration" style="margin-top: 15px; {% if not rental_items %}display: none;{% endif %}">
                <label for="rental_days" style="display: block; margin-bottom: 5px; font-weight: 500;">Rental Duration:</label>
                <select id="rental_days" name="rental_days" style="width: 100%; padding: 10px; border: 1px solid #ddd; border-radius: 8px;">
                    <option value="7">7 days</option>
                    <option value="14">14 days</option>
                    <option value="30">30 days</option>
                </select>
            </div>
        </div>

        <!-- Delivery Options -->
        <div class="form-section" style="margin-bottom: 25px;">
            <h3 style="color: #2c3e50; margin-bottom: 15px;">
                <i class="fas fa-truck"></i> Delivery Options
            </h3>

            <div style="margin-bottom: 15px;">
                <input type="radio" id="pickup" name="delivery_option" value="pickup" checked>
                <label for="pickup" style="margin-left: 5px; font-weight: 500;">
                    <i class="fas fa-store"></i> Store Pickup (Free)
                </label>
                <p style="margin: 5px 0 0 25px; color: #7f8c8d; font-size: 0.9rem;">
                    Pick up your order from the store during business hours
                </p>
            </div>

            <div>
                <input type="radio" id="delivery" name="delivery_option" value="delivery">
                <label for="delivery" style="margin-left: 5px; font-weight: 500;">
                    <i class="fas fa-home"></i> Home Delivery (+$3.00)
                </label>
                <p style="margin: 5px 0 0 25px; color: #7f8c8d; font-size: 0.9rem;">
                    Get your order delivered to your doorstep
                </p>
            </div>

            <!-- Delivery Address (shown only for delivery) -->
            <div id="delivery-details" style="margin-top: 15px; display: none;">
                <div style="margin-bottom: 15px;">
                    <label for="delivery_address" style="display: block; margin-bottom: 5px; font-weight: 500;">Delivery Address:</label>
                    <textarea id="delivery_address" name="delivery_address" rows="3" style="width: 100%; padding: 10px; border: 1px solid #ddd; border-radius: 8px;" placeh
                </div>

                <div>
                    <label for="preferred_time" style="display: block; margin-bottom: 5px; font-weight: 500;">Preferred Time:</label>
                    <select id="preferred_time" name="preferred_time" style="width: 100%; padding: 10px; border: 1px solid #ddd; border-radius: 8px;">
                        <option value="">Any Time</option>
                        <option value="morning">Morning (9AM - 12PM)</option>
                        <option value="afternoon">Afternoon (12PM - 4PM)</option>
                        <option value="evening">Evening (4PM - 8PM)</option>
                    </select>
                </div>
            </div>
        </div>

        <!-- Payment Note -->
        <div class="payment-note" style="background: #f8f9fa; padding: 20px; border-radius: 8px; margin-bottom: 25px;">
            <h4 style="color: #2c3e50; margin-bottom: 10px;">
                <i class="fas fa-info-circle"></i> Payment Information
            </h4>
            <p style="color: #7f8c8d; margin: 0;">
                ■ <strong>Pay when you receive the book</strong> (cash or card)<br>
                The store will contact you to confirm payment method
            </p>
        </div>

        <!-- Additional Notes -->
        <div class="form-section" style="margin-bottom: 25px;">
            <label for="notes" style="display: block; margin-bottom: 5px; font-weight: 500;">
                <i class="fas fa-sticky-note"></i> Additional Notes (Optional):
            </label>
            <textarea id="notes" name="notes" rows="3" style="width: 100%; padding: 10px; border: 1px solid #ddd; border-radius: 8px;" placeholder="Any special instructio
        </div>

        <!-- Hidden Fields -->
        <input type="hidden" id="total_amount" name="total_amount" value="{{ total }}">
        <input type="hidden" id="delivery_fee" name="delivery_fee" value="0">

        <!-- Action Buttons -->
        <div style="display: flex; gap: 15px; margin-top: 30px;">
            <a href="{% url 'shopping_cart' %}" class="btn" style="background-color: #95a5a6; color: white; padding: 12px 25px; text-decoration: none; border-radius: 8px;
                <i class="fas fa-arrow-left"></i> Back to Cart
            </a>
            <button type="submit" class="btn" style="background-color: #2ecc71; color: white; padding: 12px 25px; border: none; border-radius: 8px; font-weight: 600; flex
                <i class="fas fa-check-circle"></i> Place Order
```

```
                </button>
            </div>
        </form>
    </div>
</div>

<script>
document.addEventListener('DOMContentLoaded', function() {
    // Toggle rental duration
    const orderTypeRadios = document.querySelectorAll('input[name="order_type"]');
    const rentalDurationDiv = document.getElementById('rental-duration');

    orderTypeRadios.forEach(radio => {
        radio.addEventListener('change', function() {
            if (this.value === 'rent') {
                rentalDurationDiv.style.display = 'block';
            } else {
                rentalDurationDiv.style.display = 'none';
            }
        });
    });

    // Toggle delivery details
    const deliveryOptionRadios = document.querySelectorAll('input[name="delivery_option"]');
    const deliveryDetailsDiv = document.getElementById('delivery-details');
    const deliveryFeeSpan = document.getElementById('delivery-fee');
    const totalAmountSpan = document.getElementById('total-amount');
    const totalAmountInput = document.getElementById('total_amount');
    const deliveryFeeInput = document.getElementById('delivery_fee');

    const subtotal = {{ total }};

    deliveryOptionRadios.forEach(radio => {
        radio.addEventListener('change', function() {
            if (this.value === 'delivery') {
                deliveryDetailsDiv.style.display = 'block';
                deliveryFeeSpan.textContent = '$3.00';
                const newTotal = subtotal + 3.0;
                totalAmountSpan.textContent = '$' + newTotal.toFixed(2);
                totalAmountInput.value = newTotal.toFixed(2);
                deliveryFeeInput.value = '3.00';
            } else {
                deliveryDetailsDiv.style.display = 'none';
                deliveryFeeSpan.textContent = '$0.00';
                totalAmountSpan.textContent = '$' + subtotal.toFixed(2);
                totalAmountInput.value = subtotal.toFixed(2);
                deliveryFeeInput.value = '0.00';
            }
        });
    });

    // Update total when rental days change
    const rentalDaysSelect = document.getElementById('rental_days');
    rentalDaysSelect.addEventListener('change', function() {
        // Recalculate rental total based on days
        let rentalTotal = 0;
        document.querySelectorAll('#cart-items .cart-item').forEach(item => {
            const priceText = item.querySelector('p:last-child').textContent;
            if (priceText.includes('/day')) {
                const pricePerDay = parseFloat(priceText.replace('$', '').replace('/day', ''));
                rentalTotal += pricePerDay * parseInt(this.value);
            }
        });

        // Update totals
        const deliveryFee = parseFloat(deliveryFeeInput.value);
        const newTotal = rentalTotal + {{ purchase_total|default:0 }} + deliveryFee;
        totalAmountSpan.textContent = '$' + newTotal.toFixed(2);
        totalAmountInput.value = newTotal.toFixed(2);
    });

    // Form submission (normal POST to Django view)
    const orderForm = document.getElementById('order-form');
    orderForm.addEventListener('submit', function(e) {
        const deliveryOption = document.querySelector('input[name="delivery_option"]:checked').value;
        if (deliveryOption === 'delivery') {
            const deliveryAddress = document.getElementById('delivery_address').value.trim();
            if (!deliveryAddress) {
                e.preventDefault();
                alert('Please enter your delivery address');
            }
        }
    });
});
</script>

<style>
.alert {
    padding: 15px;
    border-radius: 8px;
    margin-bottom: 15px;
}

.alert-success {
    background-color: #d4edda;
    color: #155724;
    border: 1px solid #c3e6cb;
}

.alert-error {
    background-color: #f8d7da;
    color: #721c24;
    border: 1px solid #f5c6cb;
}

.alert-warning {
    background-color: #fff3cd;
    color: #856404;
    border: 1px solid #ffeaa7;
}

.btn:hover {
    opacity: 0.9;
    transform: translateY(-2px);
    transition: all 0.3s;
}
</style>
{% endblock %}
```

***File: resources\views\customer\dashboard.blade.php***

```
@extends('customer.base')

@section('title', 'Browse Books · BookHub')
@section('extra_css')
```

```
<style>
/* ============================================================
   DASHBOARD — all tokens inherited from base.blade.php
   ============================================================ */

/* ─── Results / info bar ─── */
.results-bar {
    display: flex; align-items: center; justify-content: space-between;
    flex-wrap: wrap; gap: 0.75rem;
    padding: 1rem 1.25rem; margin-bottom: 2rem;
    background: var(--bg-card); border: 1px solid var(--border);
    border-radius: var(--radius-lg); box-shadow: var(--shadow-sm);
}
.results-text { font-size: 0.87rem; color: var(--text-secondary); font-weight: 500; }
.results-text strong { color: var(--text-primary); font-weight: 800; }
.results-text .hl { color: var(--primary); font-style: italic; }

/* Active filter pills */
.active-pills { display: flex; flex-wrap: wrap; gap: 0.5rem; margin-top: 0.65rem; }
.active-pill {
    display: inline-flex; align-items: center; gap: 0.4rem;
    padding: 0.22rem 0.7rem; border-radius: 999px;
    font-size: 0.7rem; font-weight: 700;
}
.pill-blue   { background: var(--primary-soft); color: var(--primary);  border: 1px solid var(--border); }
.pill-green  { background: var(--success-soft);  color: var(--success);  border: 1px solid rgba(0,201,139,0.2); }
.pill-close  { opacity: 0.6; cursor: pointer; transition: opacity var(--t-fast); text-decoration: none; color: inherit; }
.pill-close:hover { opacity: 1; color: inherit; }

/* ─── Empty state ─── */
.empty-state {
    grid-column: 1 / -1;
    text-align: center; padding: 5rem 2rem;
}
.empty-icon {
    width: 80px; height: 80px; border-radius: var(--radius-lg);
    background: var(--primary-soft); border: 1px solid var(--border);
    display: flex; align-items: center; justify-content: center;
    font-size: 2rem; color: var(--primary); margin: 0 auto 1.5rem;
}
.empty-state h3 {
    font-size: 1.25rem; font-weight: 800; color: var(--text-primary);
    letter-spacing: -0.02em; margin-bottom: 0.5rem;
}
.empty-state p { font-size: 0.87rem; color: var(--text-muted); margin-bottom: 1.5rem; }

/* ─── Genre badge on card ─── */
.book-genre-tag {
    display: inline-flex; align-items: center;
    padding: 0.18rem 0.6rem; border-radius: 999px;
    font-size: 0.65rem; font-weight: 700; letter-spacing: 0.3px;
    background: var(--primary-soft); color: var(--primary);
    border: 1px solid var(--border); margin-bottom: 0.6rem;
}

/* ─── Availability rows ─── */
.avail-row {
    display: flex; align-items: center; gap: 0.45rem;
    font-size: 0.74rem; font-weight: 600; margin-bottom: 0.28rem;
}
.avail-dot { width: 7px; height: 7px; border-radius: 50%; flex-shrink: 0; }
.avail-yes .avail-dot { background: var(--success); }
.avail-no  .avail-dot { background: var(--danger); }
.avail-yes { color: var(--success); }
.avail-no  { color: var(--danger); }

/* ─── 3-col action row: rent | buy | view ─── */
.book-actions-3 {
    display: grid; grid-template-columns: 1fr 1fr auto;
    gap: 0.5rem; margin-top: auto;
}
.btn-view {
    padding: 0.65rem 0.75rem; border-radius: var(--radius-sm);
    font-family: 'Outfit', sans-serif; font-size: 0.8rem; font-weight: 700;
    cursor: pointer; display: flex; align-items: center; justify-content: center;
    gap: 0.35rem; transition: all var(--t-fast); text-decoration: none;
    background: var(--accent-soft); color: var(--accent);
    border: 1.5px solid rgba(245,176,66,0.22);
}
.btn-view:hover { background: var(--accent); color: #fff; border-color: var(--accent); }

/* ─── Card stagger animation ─── */
.book-card { animation: cardIn .38s ease both; }
.book-card:nth-child(1){animation-delay:.04s}
.book-card:nth-child(2){animation-delay:.08s}
.book-card:nth-child(3){animation-delay:.12s}
.book-card:nth-child(4){animation-delay:.16s}
.book-card:nth-child(5){animation-delay:.20s}
.book-card:nth-child(6){animation-delay:.24s}
.book-card:nth-child(7){animation-delay:.28s}
.book-card:nth-child(8){animation-delay:.32s}
@keyframes cardIn {
    from { opacity:0; transform:translateY(18px); }
    to   { opacity:1; transform:none; }
}
</style>
@endsection

@section('content')
@php
    $baseParams = request()->except('page', 'genre', 'availability');
    $hasFilters = !empty($searchQuery) || !empty($selectedGenre) || !empty($selectedAvailability);
    $wishlistIds = array_map('intval', session('wishlist', []));
@endphp

<!-- ============================================================
     FILTER BAR
     ============================================================ -->
<div class="filter-bar" style="flex-direction:column;align-items:flex-start;gap:0.75rem;">

    <div style="display:flex;align-items:center;gap:1rem;flex-wrap:wrap;width:100%;">
        <span class="filter-label">Browse by</span>
        <div class="filter-tags">

            <a href="{{ route('customer.dashboard', $baseParams) }}"
               class="filter-tag {{ !$selectedGenre && !$selectedAvailability ? 'active' : '' }}">
                <i class="bi bi-grid-3x3-gap"></i> All Books
            </a>

            <a href="{{ route('customer.dashboard', array_merge($baseParams, ['availability' => 'rent'])) }}"
               class="filter-tag {{ $selectedAvailability === 'rent' ? 'active' : '' }}">
                <i class="bi bi-arrow-repeat"></i> For Rent
            </a>

            <a href="{{ route('customer.dashboard', array_merge($baseParams, ['availability' => 'buy'])) }}"
               class="filter-tag {{ $selectedAvailability === 'buy' ? 'active' : '' }}">
                <i class="bi bi-bag-check"></i> For Sale
            </a>
```

```
            @foreach($genres as $genre)
                <a href="{{ route('customer.dashboard', array_merge($baseParams, ['genre' => $genre])) }}"
                   class="filter-tag {{ $selectedGenre === $genre ? 'active' : '' }}">
                    {{ $genre }}
                </a>
            @endforeach

        </div>
    </div>

    @if($hasFilters)
        <div class="filter-row2">
            <a href="{{ route('customer.dashboard') }}"
               class="nav-btn" style="margin-left:auto;color:var(--danger);background:var(--danger-soft);border-color:rgba(255,77,109,0.22);">
                <i class="bi bi-x-circle-fill"></i> Clear All
            </a>
        </div>
    @endif

</div>

<!-- ============================================================
     RESULTS BAR
     ============================================================ -->
<div class="results-bar">
    <div style="flex:1;">
        <div class="results-text">
            Found <strong>{{ $totalBooks }}</strong> book{{ $totalBooks === 1 ? '' : 's' }}
            @if($searchQuery) matching <span class="hl">"{{ $searchQuery }}"</span>@endif
        </div>

        @if($selectedGenre || $selectedAvailability)
        <div class="active-pills">
            @if($selectedGenre)
            <span class="active-pill pill-blue">
                <i class="bi bi-tag-fill"></i> {{ $selectedGenre }}
            </span>
            @endif
            @if($selectedAvailability)
            <span class="active-pill pill-green">
                <i class="bi bi-check-circle-fill"></i>
                {{ $selectedAvailability === 'rent' ? 'For Rent' : 'For Sale' }}
            </span>
            @endif
        </div>
        @endif
    </div>

    @if($searchQuery)
    <a href="{{ route('customer.dashboard') }}" class="nav-btn" style="flex-shrink:0;">
        <i class="bi bi-x"></i> Clear Search
    </a>
    @endif
</div>

<!-- ============================================================
     SECTION HEADING
     ============================================================ -->
<div class="section-hd">
    <div class="section-hd-left">
        <div class="section-icon">
            @if($searchQuery)<i class="bi bi-search"></i>
            @elseif($selectedGenre)<i class="bi bi-tag-fill"></i>
            @else<i class="bi bi-collection-fill"></i>@endif
        </div>
        <div>
            <div class="section-title">
                @if($searchQuery) Search Results
                @elseif($selectedGenre) {{ $selectedGenre }}
                @elseif($selectedAvailability === 'rent') Books for Rent
                @elseif($selectedAvailability === 'buy') Books for Sale
                @else All Books @endif
            </div>
            <div class="section-sub">{{ $totalBooks }} book{{ $totalBooks === 1 ? '' : 's' }} available</div>
        </div>
    </div>
</div>

<!-- ============================================================
     BOOKS GRID
     ============================================================ -->
<div class="book-grid">

@forelse($books as $book)
<div class="book-card">

    <div class="book-img">
        @php
            $isWished = in_array((int) $book->id, $wishlistIds, true);
            $wishlistRoute = $isWished ? route('wishlist.remove', $book->id) : route('wishlist.add', $book->id);
        @endphp
        <a href="{{ $wishlistRoute }}"
           class="book-wish {{ $isWished ? 'active' : '' }}"
           aria-label="{{ $isWished ? 'Remove from wishlist' : 'Add to wishlist' }}">
            <i class="bi {{ $isWished ? 'bi-heart-fill' : 'bi-heart' }}"></i>
        </a>

        <a href="{{ route('books.show', $book->id) }}" class="quick-view">
            <i class="bi bi-eye"></i> Quick View
        </a>

        @if($book->cover_image_path)
            <img src="{{ asset($book->cover_image_path) }}"
                 alt="{{ $book->title }}"
                 loading="lazy">
        @else
            <div class="d-flex align-items-center justify-content-center"
                 style="height:220px;background:var(--bg-raised);color:var(--text-muted);font-size:0.85rem;border-radius:14px;">
                No Image
            </div>
        @endif
    </div>

    <div class="book-body">

        @if($book->genre)
        <span class="book-genre-tag">{{ $book->genre }}</span>
        @endif

        <div class="book-title">{{ $book->title }}</div>
        <div class="book-author">{{ $book->author }}</div>

        <div class="pricing-row">
            <div class="price-pill price-rent">
                <span class="price-tag">Rent</span>
                <span class="price-amount">$ {{ number_format($book->rental_price, 2) }}</span>
                <span class="price-period">/month</span>
            </div>
```

```
                <div class="price-pill price-buy">
                    <span class="price-tag">Buy</span>
                    <span class="price-amount">${{ number_format($book->sale_price, 2) }}</span>
                    <span class="price-period">one-time</span>
                </div>
            </div>

            <div style="margin-bottom:1rem;">
                <div class="avail-row {{ $book->available_rent > 0 ? 'avail-yes' : 'avail-no' }}">
                    <span class="avail-dot"></span>
                    @if($book->available_rent > 0)
                        {{ $book->available_rent }} available for rent
                    @else
                        Not available for rent
                    @endif
                </div>
                <div class="avail-row {{ $book->available_sale > 0 ? 'avail-yes' : 'avail-no' }}">
                    <span class="avail-dot"></span>
                    @if($book->available_sale > 0)
                        {{ $book->available_sale }} available to buy
                    @else
                        Not available to buy
                    @endif
                </div>
            </div>

            <div class="book-actions-3">
                @if($book->available_rent > 0)
                <a href="{{ route('cart.add.rent', $book->id) }}" class="btn btn-rent">
                    <i class="bi bi-arrow-repeat"></i> Rent
                </a>
                @else
                <span class="btn btn-disabled">
                    <i class="bi bi-arrow-repeat"></i> Rent
                </span>
                @endif

                @if($book->available_sale > 0)
                <a href="{{ route('cart.add.buy', $book->id) }}" class="btn btn-buy">
                    <i class="bi bi-bag-check"></i> Buy
                </a>
                @else
                <span class="btn btn-disabled">
                    <i class="bi bi-bag-check"></i> Buy
                </span>
                @endif

                <a href="{{ route('books.show', $book->id) }}" class="btn-view">
                    <i class="bi bi-eye-fill"></i>
                </a>
            </div>

        </div>
    </div>

    @empty
    <div class="empty-state">
        <div class="empty-icon"><i class="bi bi-search"></i></div>
        <h3>No books found</h3>
        <p>Try different keywords or clear the active filters to see all books.</p>
        <a href="{{ route('customer.dashboard') }}" class="nav-pill" style="display:inline-flex;">
            <i class="bi bi-x-circle"></i> Clear All Filters
        </a>
    </div>
    @endforelse

    </div>

    @if($books->hasPages())
    <div class="bh-pagination">
        @if($books->previousPageUrl())
        <a class="page-btn" href="{{ $books->previousPageUrl() }}">
            <i class="bi bi-chevron-left"></i> Previous
        </a>
        @endif

        <span class="page-btn current">
            Page {{ $books->currentPage() }} of {{ $books->lastPage() }}
        </span>

        @if($books->nextPageUrl())
        <a class="page-btn" href="{{ $books->nextPageUrl() }}">
            Next <i class="bi bi-chevron-right"></i>
        </a>
        @endif
    </div>
    @endif

    @endsection
```

### *File: resources\views\customer\featured_books.blade.php*

```
    <!DOCTYPE html>
    <html lang="en">
    <head>
        <meta charset="UTF-8">
        <meta name="viewport" content="width=device-width, initial-scale=1.0">
        <title>BookHub - Featured Books</title>
        <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/font-awesome/6.4.0/css/all.min.css">
        <style>
            * {
                margin: 0;
                padding: 0;
                box-sizing: border-box;
                font-family: 'Segoe UI', Tahoma, Geneva, Verdana, sans-serif;
            }

            body {
                background-color: #f8f9fa;
                color: #333;
                line-height: 1.6;
            }

            .container {
                max-width: 1400px;
                margin: 0 auto;
                padding: 0 20px;
            }

            /* Navigation Bar */
            .navbar {
                background-color: #2c3e50;
                color: white;
                padding: 15px 0;
                box-shadow: 0 4px 12px rgba(0, 0, 0, 0.1);
```

```
    position: sticky;
    top: 0;
    z-index: 100;
}

.nav-container {
    display: flex;
    justify-content: space-between;
    align-items: center;
}

.logo {
    display: flex;
    align-items: center;
    font-size: 1.8rem;
    font-weight: 700;
}

.logo i {
    margin-right: 10px;
    color: #3498db;
}

.nav-links {
    display: flex;
    align-items: center;
    gap: 25px;
}

.nav-item {
    display: flex;
    align-items: center;
    cursor: pointer;
    transition: color 0.3s;
    font-weight: 500;
    padding: 8px 15px;
    border-radius: 6px;
}

.nav-item:hover {
    color: #3498db;
    background-color: rgba(255, 255, 255, 0.1);
}

.nav-item.active {
    background-color: #3498db;
    color: white;
}

.nav-item i {
    margin-right: 8px;
}

.cart-badge {
    background-color: #e74c3c;
    color: white;
    border-radius: 50%;
    width: 22px;
    height: 22px;
    display: flex;
    align-items: center;
    justify-content: center;
    font-size: 0.8rem;
    margin-left: 5px;
}

/* Featured Books Section */
.featured-section {
    padding: 40px 0;
}

.section-header {
    display: flex;
    justify-content: space-between;
    align-items: center;
    margin-bottom: 30px;
}

.section-title {
    font-size: 1.8rem;
    color: #2c3e50;
    display: flex;
    align-items: center;
}

.section-title i {
    color: #3498db;
    margin-right: 10px;
    font-size: 1.5rem;
}

.section-controls {
    display: flex;
    gap: 15px;
}

.view-all-btn {
    background-color: #3498db;
    color: white;
    padding: 10px 20px;
    border-radius: 6px;
    text-decoration: none;
    font-weight: 600;
    display: flex;
    align-items: center;
    transition: background-color 0.3s;
}

.view-all-btn:hover {
    background-color: #2980b9;
}

.view-all-btn i {
    margin-left: 8px;
}

.nav-arrows {
    display: flex;
    gap: 10px;
}

.nav-arrow {
    width: 40px;
    height: 40px;
    border-radius: 50%;
    background-color: white;
    border: 2px solid #dee2e6;
    display: flex;
```

```
    align-items: center;
    justify-content: center;
    cursor: pointer;
    transition: all 0.3s;
    font-size: 1.2rem;
    color: #495057;
}

.nav-arrow:hover {
    background-color: #3498db;
    color: white;
    border-color: #3498db;
}

/* Book Grid */
.book-grid {
    display: grid;
    grid-template-columns: repeat(auto-fill, minmax(280px, 1fr));
    gap: 30px;
}

.book-card {
    background-color: white;
    border-radius: 12px;
    overflow: hidden;
    box-shadow: 0 6px 15px rgba(0, 0, 0, 0.07);
    transition: transform 0.3s, box-shadow 0.3s;
    display: flex;
    flex-direction: column;
}

.book-card:hover {
    transform: translateY(-10px);
    box-shadow: 0 12px 25px rgba(0, 0, 0, 0.12);
}

.book-image {
    height: 280px;
    overflow: hidden;
    position: relative;
}

.book-image img {
    width: 100%;
    height: 100%;
    object-fit: cover;
    transition: transform 0.5s;
}

.book-card:hover .book-image img {
    transform: scale(1.05);
}

.book-badge {
    position: absolute;
    top: 15px;
    left: 15px;
    background-color: #e74c3c;
    color: white;
    padding: 5px 15px;
    border-radius: 20px;
    font-size: 0.8rem;
    font-weight: 600;
}

.book-rating {
    position: absolute;
    top: 15px;
    right: 15px;
    background-color: rgba(0, 0, 0, 0.7);
    color: white;
    padding: 5px 10px;
    border-radius: 4px;
    font-size: 0.9rem;
    display: flex;
    align-items: center;
}

.book-rating i {
    color: #f1c40f;
    margin-right: 5px;
}

.book-info {
    padding: 20px;
    flex-grow: 1;
    display: flex;
    flex-direction: column;
}

.book-title {
    font-size: 1.3rem;
    font-weight: 700;
    margin-bottom: 8px;
    color: #2c3e50;
}

.book-author {
    color: #7f8c8d;
    margin-bottom: 10px;
    font-size: 0.95rem;
}

.book-description {
    color: #636e72;
    margin-bottom: 20px;
    font-size: 0.95rem;
    line-height: 1.5;
    flex-grow: 1;
}

.book-pricing {
    display: flex;
    justify-content: space-between;
    margin-bottom: 20px;
    padding: 10px 0;
    border-top: 1px solid #ecf0f1;
    border-bottom: 1px solid #ecf0f1;
}

.price-option {
    display: flex;
    flex-direction: column;
    align-items: center;
    flex: 1;
}

.price-label {
```

```
            font-size: 0.85rem;
            color: #7f8c8d;
            margin-bottom: 5px;
        }

        .price-amount {
            font-weight: 700;
            font-size: 1.2rem;
            color: #2c3e50;
        }

        .rent-price {
            color: #3498db;
        }

        .buy-price {
            color: #2ecc71;
        }

        .book-actions {
            display: flex;
            gap: 10px;
        }

        .btn {
            padding: 12px 20px;
            border-radius: 8px;
            border: none;
            cursor: pointer;
            font-weight: 600;
            display: inline-flex;
            align-items: center;
            justify-content: center;
            transition: all 0.3s;
            flex: 1;
        }

        .btn i {
            margin-right: 8px;
        }

        .btn-rent {
            background-color: #3498db;
            color: white;
        }

        .btn-rent:hover {
            background-color: #2980b9;
        }

        .btn-buy {
            background-color: #2ecc71;
            color: white;
        }

        .btn-buy:hover {
            background-color: #27ae60;
        }

        /* Responsive Design */
        @media (max-width: 992px) {
            .book-grid {
                grid-template-columns: repeat(auto-fill, minmax(250px, 1fr));
            }
        }

        @media (max-width: 768px) {
            .nav-container {
                flex-direction: column;
                gap: 15px;
            }

            .nav-links {
                width: 100%;
                justify-content: center;
                flex-wrap: wrap;
                gap: 10px;
            }

            .section-header {
                flex-direction: column;
                align-items: flex-start;
                gap: 15px;
            }

            .section-controls {
                width: 100%;
                justify-content: space-between;
            }
        }

        @media (max-width: 576px) {
            .nav-links {
                flex-direction: column;
                align-items: center;
            }

            .book-grid {
                grid-template-columns: 1fr;
            }

            .section-controls {
                flex-direction: column;
                align-items: flex-start;
            }
        }
    </style>
</head>
<body>
    <!-- Navigation Bar -->
    <nav class="navbar">
        <div class="container nav-container">
            <div class="logo">
                <i class="fas fa-book"></i>
                BookHub Store
            </div>
            <div class="nav-links">
                <div class="nav-item">
                    <i class="fas fa-home"></i>
                    <span>Home</span>
                </div>
                <div class="nav-item active">
                    <i class="fas fa-star"></i>
                    <span>Featured</span>
                </div>
                <div class="nav-item">
                    <i class="fas fa-book-open"></i>
                    <span>All Books</span>
```

```
                    </div>
                    <div class="nav-item">
                        <i class="fas fa-shopping-cart"></i>
                        <span>Cart</span>
                        <div class="cart-badge">5</div>
                    </div>
                    <div class="nav-item">
                        <i class="fas fa-user-circle"></i>
                        <span>Account</span>
                    </div>
                </div>
            </div>
        </nav>

        <!-- Featured Books Section -->
        <section class="featured-section">
            <div class="container">
                <div class="section-header">
                    <div class="section-title">
                        <i class="fas fa-star"></i>
                        Featured Books This Week
                    </div>
                    <div class="section-controls">
                        <a href="#" class="view-all-btn">
                            View All Books
                            <i class="fas fa-arrow-right"></i>
                        </a>
                        <div class="nav-arrows">
                            <div class="nav-arrow left-arrow">
                                <i class="fas fa-chevron-left"></i>
                            </div>
                            <div class="nav-arrow right-arrow">
                                <i class="fas fa-chevron-right"></i>
                            </div>
                        </div>
                    </div>
                </div>

                <div class="book-grid">
                    <!-- Book 1 -->
                    <div class="book-card">
                        <div class="book-image">
                            <div class="book-badge">Bestseller</div>
                            <div class="book-rating">
                                <i class="fas fa-star"></i> 4.8
                            </div>
                            <img src="https://images.unsplash.com/photo-1544716278-ca5e3f4abd8c?ixlib=rb-4.0.3&auto=format&fit=crop&w=600&q=80" alt="The Silent Patient">
                        </div>
                        <div class="book-info">
                            <h3 class="book-title">The Silent Patient</h3>
                            <div class="book-author">Alex Michaelides</div>
                            <p class="book-description">A psychological thriller about a woman who shoots her husband and then stops speaking, and the criminal psychotherapist who

                            <div class="book-pricing">
                                <div class="price-option">
                                    <span class="price-label">RENT FOR</span>
                                    <span class="price-amount rent-price">$4.99</span>
                                    <span class="price-label">/month</span>
                                </div>
                                <div class="price-option">
                                    <span class="price-label">BUY FOR</span>
                                    <span class="price-amount buy-price">$24.99</span>
                                </div>
                            </div>

                            <div class="book-actions">
                                <button class="btn btn-rent">
                                    <i class="fas fa-exchange-alt"></i> Rent
                                </button>
                                <button class="btn btn-buy">
                                    <i class="fas fa-shopping-cart"></i> Buy
                                </button>
                            </div>
                        </div>
                    </div>

                    <!-- Book 2 -->
                    <div class="book-card">
                        <div class="book-image">
                            <div class="book-badge">New Release</div>
                            <div class="book-rating">
                                <i class="fas fa-star"></i> 4.9
                            </div>
                            <img src="https://images.unsplash.com/photo-1512820790803-83ca734da794?ixlib=rb-4.0.3&auto=format&fit=crop&w=600&q=80" alt="Project Hail Mary">
                        </div>
                        <div class="book-info">
                            <h3 class="book-title">Project Hail Mary</h3>
                            <div class="book-author">Andy Weir</div>
                            <p class="book-description">A lone astronaut must save the earth from disaster in this incredible new science-based thriller from the #1 New York Times

                            <div class="book-pri
```

(Content truncated due to size - showing first 15KB)

### File: resources\views\customer\order_detail.blade.php

```
@extends('customer.base')

@section('title', 'Order Details - BookHub')

@section('content')
<div class="container">
    <div style="max-width: 900px; margin: 0 auto;">
        <div style="background: white; border-radius: 12px; padding: 25px; margin-bottom: 25px; box-shadow: 0 4px 12px rgba(0,0,0,0.05);">
            <div style="display: flex; justify-content: space-between; align-items: center; margin-bottom: 20px;">
                <div>
                    <h2 style="margin: 0; color: #2c3e50;">Order #{{ $order['order_number'] }}</h2>
                    <p style="color: #7f8c8d; margin: 5px 0 0 0;">
                        Placed on {{ $order['created_at']->format('F d, Y') }} at {{ $order['created_at']->format('g:i A') }}
                    </p>
                </div>
                <div style="text-align: right;">
                    <span style="display: inline-block; padding: 8px 20px; background: {{ in_array($order['status'], ['completed','delivered'], true) ? '#27ae60' : ($order['st
                           color: white; border-radius: 20px; font-weight: 600; font-size: 0.9rem;">
                        {{ $order['status_label'] }}
                    </span>
                </div>
            </div>

            <div style="display: grid; grid-template-columns: repeat(auto-fit, minmax(200px, 1fr)); gap: 20px; margin-top: 20px;">
                <div>
                    <p style="color: #7f8c8d; margin: 0 0 5px 0; font-size: 0.9rem;">Order Type</p>
                    <p style="margin: 0; font-weight: 600; color: #2c3e50;">
                        {{ $order['order_type'] === 'rent' ? 'Rental' : ($order['order_type'] === 'mixed' ? 'Mixed' : 'Purchase') }}
                    </p>
```

```
        </div>
        <div>
            <p style="color: #7f8c8d; margin: 0 0 5px 0; font-size: 0.9rem;">Total Amount</p>
            <p style="margin: 0; font-weight: 600; color: #2c3e50;">${{ number_format($order['total_amount'], 2) }}</p>
        </div>
        <div>
            <p style="color: #7f8c8d; margin: 0 0 5px 0; font-size: 0.9rem;">Delivery Method</p>
            <p style="margin: 0; font-weight: 600; color: #2c3e50;">
                {{ ($order['delivery_option'] ?? 'pickup') === 'delivery' ? 'Home Delivery' : 'Store Pickup' }}
            </p>
        </div>
        <div>
            <p style="color: #7f8c8d; margin: 0 0 5px 0; font-size: 0.9rem;">Store</p>
            <p style="margin: 0; font-weight: 600; color: #2c3e50;">{{ $order['store']['store_name'] ?? 'BookHub' }}</p>
        </div>
    </div>
</div>

<div style="background: white; border-radius: 12px; padding: 25px; margin-bottom: 25px; box-shadow: 0 4px 12px rgba(0,0,0,0.05);">
    <h3 style="margin-top: 0; color: #2c3e50; border-bottom: 2px solid #f8f9fa; padding-bottom: 15px;">
        Order Items ({{ $items->count() }})
    </h3>

    <div style="margin-top: 20px;">
        @foreach($items as $item)
        <div style="display: flex; padding: 20px; background: #f8f9fa; border-radius: 8px; margin-bottom: 15px;">
            <div style="flex: 1;">
                <h4 style="margin: 0 0 5px 0; color: #2c3e50;">{{ $item['book']->title }}</h4>
                <p style="margin: 0 0 10px 0; color: #7f8c8d;">by {{ $item['book']->author }}</p>
                <div style="display: flex; gap: 20px; font-size: 0.9rem;">
                    <span style="background: {{ $item['item_type'] === 'rent' ? '#3498db' : '#2ecc71' }};
                          color: white; padding: 4px 12px; border-radius: 12px;">
                        {{ $item['item_type'] === 'rent' ? 'Rental' : 'Purchase' }}
                    </span>
                    <span>Quantity: {{ $item['quantity'] }}</span>
                    @if($item['item_type'] === 'rent' && $item['rental_days'])
                    <span>Rental Period: {{ $item['rental_days'] }} days</span>
                    @endif
                </div>
            </div>
            <div style="text-align: right;">
                <p style="margin: 0; font-size: 1.2rem; font-weight: 600; color: #2c3e50;">
                    ${{ number_format($item['price'], 2) }}
                </p>
                @if($item['item_type'] === 'rent')
                <p style="margin: 5px 0 0 0; color: #7f8c8d; font-size: 0.9rem;">
                    ${{ number_format($item['book']->rental_price, 2) }}/day
                </p>
                @endif
            </div>
        </div>
        @endforeach
    </div>

    <div style="margin-top: 30px; padding-top: 20px; border-top: 2px solid #f8f9fa;">
        <div style="max-width: 300px; margin-left: auto;">
            <div style="display: flex; justify-content: space-between; margin-bottom: 10px;">
                <span style="color: #7f8c8d;">Subtotal</span>
                <span>${{ number_format($subtotal, 2) }}</span>
            </div>
            @if(($order['delivery_fee'] ?? 0) > 0)
            <div style="display: flex; justify-content: space-between; margin-bottom: 10px;">
                <span style="color: #7f8c8d;">Delivery Fee</span>
                <span>${{ number_format($order['delivery_fee'], 2) }}</span>
            </div>
            @endif
            <div style="display: flex; justify-content: space-between; font-size: 1.2rem; font-weight: 600; padding-top: 10px; border-top: 1px solid #f8f9fa;">
                <span>Total</span>
                <span>${{ number_format($order['total_amount'], 2) }}</span>
            </div>
        </div>
    </div>
</div>

<div style="background: white; border-radius: 12px; padding: 25px; margin-bottom: 25px; box-shadow: 0 4px 12px rgba(0,0,0,0.05);">
    <h3 style="margin-top: 0; color: #2c3e50; border-bottom: 2px solid #f8f9fa; padding-bottom: 15px;">
        Store Information
    </h3>

    <div style="display: grid; grid-template-columns: 1fr 1fr; gap: 30px; margin-top: 20px;">
        <div>
            <h4 style="margin: 0 0 10px 0; color: #2c3e50; font-size: 1.1rem;">
                {{ $order['store']['store_name'] ?? 'BookHub' }}
            </h4>
            @if(!empty($order['store']['address']))
            <p style="margin: 0 0 10px 0; color: #7f8c8d;">
                <i class="fas fa-map-marker-alt"></i> {{ $order['store']['address'] }}, {{ $order['store']['city'] }}
            </p>
            @endif
            @if(!empty($order['store']['phone']))
            <p style="margin: 0 0 10px 0; color: #7f8c8d;">
                <i class="fas fa-phone"></i> {{ $order['store']['phone'] }}
            </p>
            @endif
            @if(!empty($order['store']['email']))
            <p style="margin: 0 0 10px 0; color: #7f8c8d;">
                <i class="fas fa-envelope"></i> {{ $order['store']['email'] }}
            </p>
            @endif
        </div>

        <div>
            <h4 style="margin: 0 0 10px 0; color: #2c3e50; font-size: 1.1rem;">Order Notes</h4>
            @if(!empty($order['notes']))
            <div style="background: #f8f9fa; padding: 15px; border-radius: 8px; margin-bottom: 15px;">
                <p style="margin: 0; color: #2c3e50;"><strong>Your Notes:</strong> {{ $order['notes'] }}</p>
            </div>
            @endif
            @if(!empty($order['store_notes']))
            <div style="background: #e8f4f8; padding: 15px; border-radius: 8px; border-left: 4px solid #3498db;">
                <p style="margin: 0; color: #2c3e50;"><strong>Store Notes:</strong> {{ $order['store_notes'] }}</p>
            </div>
            @endif
        </div>
    </div>
</div>

<div style="display: flex; justify-content: space-between; gap: 15px; margin-top: 30px;">
    <a href="{{ route('orders.index') }}" class="btn"
       style="background: #95a5a6; color: white; padding: 12px 30px; text-decoration: none; border-radius: 8px; font-weight: 600;">
        <i class="fas fa-arrow-left"></i> Back to Orders
    </a>

    <div style="display: flex; gap: 15px;">
        @if($order['status'] === 'delivered')
        <form method="POST" action="{{ route('orders.finish', $order['id']) }}" style="display: inline;">
            @csrf
            <button type="submit" class="btn"
```

```
                        style="background: #16a085; color: white; padding: 12px 30px; text-decoration: none; border-radius: 8px; font-weight: 600; border: none;">
                        <i class="fas fa-check-double"></i> Finished
                    </button>
                </form>
                @endif
            </div>
        </div>
    </div>
</div>

<style>
.btn:hover {
    opacity: 0.9;
    transform: translateY(-2px);
    transition: all 0.3s ease;
}
</style>
@endsection
```

**File: resources\views\customer\order_history.blade.php**

```
@extends('customer.base')

@section('title', 'My Orders - BookHub')

@section('content')
<div class="container">
    <div style="max-width: 1200px; margin: 0 auto;">
        <div style="margin-bottom: 30px;">
            <div style="display: flex; justify-content: space-between; align-items: center; flex-wrap: wrap; gap: 20px;">
                <div>
                    <h1 style="color: #2c3e50; margin-bottom: 10px;">My Orders</h1>
                    <p style="color: #7f8c8d;">
                        Track your book rentals and purchases
                    </p>
                </div>
                <div style="display: flex; gap: 15px;">
                    <a href="{{ route('customer.dashboard') }}" class="btn"
                       style="background: #3498db; color: white; padding: 12px 25px; text-decoration: none; border-radius: 8px; font-weight: 600;">
                        <i class="fas fa-book"></i> Browse Books
                    </a>
                </div>
            </div>
        </div>

        <div style="background: white; border-radius: 12px; padding: 20px; margin-bottom: 30px; box-shadow: 0 4px 12px rgba(0,0,0,0.05);">
            <div style="display: flex; gap: 20px; align-items: center; flex-wrap: wrap;">
                <div>
                    <label style="display: block; margin-bottom: 8px; color: #7f8c8d; font-weight: 600;">Filter by Status</label>
                    <select id="status-filter" style="padding: 10px 15px; border-radius: 8px; border: 1px solid #ddd; min-width: 180px;">
                        <option value="all" {{ ($statusFilter ?? 'all') === 'all' ? 'selected' : '' }}>All Statuses</option>
                        <option value="pending" {{ ($statusFilter ?? '') === 'pending' ? 'selected' : '' }}>Pending</option>
                        <option value="approved" {{ ($statusFilter ?? '') === 'approved' ? 'selected' : '' }}>Approved</option>
                        <option value="preparing" {{ ($statusFilter ?? '') === 'preparing' ? 'selected' : '' }}>Preparing</option>
                        <option value="ready" {{ ($statusFilter ?? '') === 'ready' ? 'selected' : '' }}>Ready</option>
                        <option value="out_for_delivery" {{ ($statusFilter ?? '') === 'out_for_delivery' ? 'selected' : '' }}>Out for Delivery</option>
                        <option value="delivered" {{ ($statusFilter ?? '') === 'delivered' ? 'selected' : '' }}>Delivered</option>
                        <option value="completed" {{ ($statusFilter ?? '') === 'completed' ? 'selected' : '' }}>Completed</option>
                        <option value="cancelled" {{ ($statusFilter ?? '') === 'cancelled' ? 'selected' : '' }}>Declined</option>
                    </select>
                </div>

                <div>
                    <label style="display: block; margin-bottom: 8px; color: #7f8c8d; font-weight: 600;">Time Period</label>
                    <select id="time-filter" style="padding: 10px 15px; border-radius: 8px; border: 1px solid #ddd; min-width: 180px;">
                        <option value="all" {{ ($timeFilter ?? 'all') === 'all' ? 'selected' : '' }}>All Time</option>
                        <option value="30days" {{ ($timeFilter ?? '') === '30days' ? 'selected' : '' }}>Last 30 Days</option>
                        <option value="7days" {{ ($timeFilter ?? '') === '7days' ? 'selected' : '' }}>Last 7 Days</option>
                    </select>
                </div>

                <div style="margin-top: 25px;">
                    <button onclick="applyFilters()" style="background: #2ecc71; color: white; padding: 10px 25px; border: none; border-radius: 8px; font-weight: 600; cursor:
                        <i class="fas fa-filter"></i> Apply Filters
                    </button>
                </div>
            </div>
        </div>

        @if(!empty($orders) && $orders->count())
        <div style="background: white; border-radius: 12px; overflow: hidden; box-shadow: 0 4px 12px rgba(0,0,0,0.05);">
            <div style="overflow-x: auto;">
                <table style="width: 100%; border-collapse: collapse;">
                    <thead>
                        <tr style="background: #f8f9fa;">
                            <th style="padding: 20px; text-align: left; color: #2c3e50; font-weight: 600;">Order #</th>
                            <th style="padding: 20px; text-align: left; color: #2c3e50; font-weight: 600;">Date</th>
                            <th style="padding: 20px; text-align: left; color: #2c3e50; font-weight: 600;">Type</th>
                            <th style="padding: 20px; text-align: left; color: #2c3e50; font-weight: 600;">Items</th>
                            <th style="padding: 20px; text-align: left; color: #2c3e50; font-weight: 600;">Total</th>
                            <th style="padding: 20px; text-align: left; color: #2c3e50; font-weight: 600;">Status</th>
                            <th style="padding: 20px; text-align: left; color: #2c3e50; font-weight: 600;">Actions</th>
                        </tr>
                    </thead>
                    <tbody>
                        @foreach($orders as $order)
                        <tr style="border-top: 1px solid #f8f9fa;">
                            <td style="padding: 20px;">
                                <strong style="color: #3498db;">{{ $order['order_number'] }}</strong>
                                <br>
                                <small style="color: #7f8c8d;">{{ $order['store_name'] }}</small>
                            </td>
                            <td style="padding: 20px;">
                                {{ $order['created_at']->format('M d, Y') }}
                                <br>
                                <small style="color: #7f8c8d;">{{ $order['created_at']->format('g:i A') }}</small>
                            </td>
                            <td style="padding: 20px;">
                                @if($order['order_type'] === 'rent')
                                <span style="background: #3498db; color: white; padding: 4px 12px; border-radius: 12px; font-size: 0.8rem; font-weight: 600;">
                                    RENTAL
                                </span>
                                @else
                                <span style="background: #2ecc71; color: white; padding: 4px 12px; border-radius: 12px; font-size: 0.8rem; font-weight: 600;">
                                    PURCHASE
                                </span>
                                @endif
                            </td>
                            <td style="padding: 20px;">
                                {{ $order['items_count'] }} item{{ $order['items_count'] === 1 ? '' : 's' }}
                                <br>
                                <small style="color: #7f8c8d;">
                                    {{ $order['items_preview'] }}
                                    @if($order['items_count'] > 2)...@endif
                                </small>
                            </td>
                            <td style="padding: 20px; font-weight: 600; color: #2c3e50;">
                                ${{ number_format($order['total_amount'], 2) }}
                            </td>
                            <td style="padding: 20px;">
                                <span style="display: inline-block; padding: 6px 15px; background:
                                    {{ in_array($order['status'], ['completed','delivered'], true) ? '#27ae60' : ($order['status'] === 'cancelled' ? '#e74c3c' : ($order['statu
                                    color: white; border-radius: 15px; font-size: 0.8rem; font-weight: 600;">
                                    {{ $order['status_label'] }}
                                </span>
                            </td>
                            <td style="padding: 20px;">
                                <div style="display: flex; gap: 10px;">
                                    <a href="{{ route('orders.show', $order['id']) }}"
                                       style="color: #3498db; text-decoration: none; padding: 6px 12px; border: 1px solid #3498db; border-radius: 4px; font-size: 0.9rem;">
                                        <i class="fas fa-eye"></i> View
                                    </a>
                                    @if($order['status'] === 'delivered')
                                    <form method="POST" action="{{ route('orders.finish', $order['id']) }}" style="display: inline;">
                                        @csrf
                                        <button type="submit" style="color: #f39c12; background: transparent; padding: 6px 12px; border: 1px solid #f39c12; border-radius: 4px;
```

```
                                        <i class="fas fa-check-double"></i> Finished
                                    </button>
                                </form>
                                @endif
                            </div>
                        </td>
                    </tr>
                    @endforeach
                </tbody>
            </table>
        </div>
    </div>
    @else
    <div style="text-align: center; padding: 60px 20px; background: white; border-radius: 12px; box-shadow: 0 4px 12px rgba(0,0,0,0.05);">
        <div style="font-size: 5rem; color: #ecf0f1; margin-bottom: 20px;">
            <i class="fas fa-shopping-bag"></i>
        </div>
        <h3 style="color: #7f8c8d; margin-bottom: 15px;">No orders found</h3>
        <p style="color: #bdc3c7; max-width: 400px; margin: 0 auto 25px;">
            You haven't placed any orders yet. Start browsing our collection to rent or buy books.
        </p>
        <a href="{{ route('customer.dashboard') }}" class="btn"
           style="background-color: #3498db; color: white; padding: 12px 30px; text-decoration: none; border-radius: 8px; font-weight: 600; display: inline-block;">
            <i class="fas fa-book"></i> Browse Books
        </a>
    </div>
    @endif

    @if(!empty($activeRentals) && $activeRentals->count())
    <div style="margin-top: 50px;">
        <h2 style="color: #2c3e50; margin-bottom: 20px; border-bottom: 2px solid #f8f9fa; padding-bottom: 15px;">
            <i class="fas fa-history"></i> Active Rentals
        </h2>

        <div class="book-grid" style="grid-template-columns: repeat(auto-fill, minmax(300px, 1fr)); gap: 20px;">
            @foreach($activeRentals as $order)
            <div style="background: white; border-radius: 12px; padding: 20px; box-shadow: 0 4px 12px rgba(0,0,0,0.05);">
                <div style="display: flex; justify-content: space-between; align-items: start; margin-bottom: 15px;">
                    <div>
                        <h4 style="margin: 0 0 5px 0; color: #2c3e50;">{{ $order['order_number'] }}</h4>
                        <p style="margin: 0; color: #7f8c8d; font-size: 0.9rem;">
                            Due: {{ $order['created_at']->format('M d') }}
                        </p>
                    </div>
                    <span style="background: #f39c12; color: white; padding: 4px 12px; border-radius: 12px; font-size: 0.8rem; font-weight: 600;">
                        ACTIVE
                    </span>
                </div>

                <div style="margin: 15px 0;">
                    <p style="margin: 0 0 5px 0; color: #2c3e50; font-weight: 600;">
                        {{ $order['items_preview'] ?: 'Rental Items' }}
                    </p>
                </div>

                <div style="display: flex; justify-content: space-between; margin-top: 20px;">
                    <a href="{{ route('orders.show', $order['id']) }}"
                       style="color: #3498db; text-decoration: none; font-weight: 600; font-size: 0.9rem;">
                        <i class="fas fa-eye"></i> View Details
                    </a>
                    <a href="#" style="color: #e74c3c; text-decoration: none; font-weight: 600; font-size: 0.9rem;">
                        <i class="fas fa-redo"></i> Renew
                    </a>
                </div>
            </div>
            @endforeach
        </div>
    </div>
    @endif
    </div>
</div>

<script>
function applyFilters() {
    const status = document.getElementById('status-filter').value;
    const time = document.getElementById('time-filter').value;

    const params = new URLSearchParams();
    if (status !== 'all') {
        params.set('status', status);
    }
    if (time !== 'all') {
        params.set('time', time);
    }

    const url = '{{ route('orders.index') }}' + (params.toString() ? ('?' + params.toString()) : '');
    window.location.href = url;
}
</script>

<style>
.btn:hover {
    opacity: 0.9;
    transform: translateY(-2px);
    transition: all 0.3s ease;
}

table tr:hover {
    background: #f8f9fa;
}

.book-grid {
    display: grid;
    grid-template-columns: repeat(auto-fill, minmax(250px, 1fr));
    gap: 20px;
    margin-top: 20px;
}
</style>
@endsection
```

### File: resources\views\customer\support_chat_detail.blade.php

```
<!-- customer/support_chat_detail.html -->
{% extends 'customer/base.html' %}

{% block content %}
<div class="chat-fullscreen">
    <!-- Back Navigation -->
    <div class="chat-navigation">
        <a href="{% url 'support_chat_list' %}" class="back-button">
            <i class="bi bi-arrow-left"></i>
            <span>Back to Support</span>
        </a>
    </div>
    <!-- Main Chat Area -->
```

```
<div class="chat-main">
    <!-- Chat Header -->
    <div class="chat-header">
        <div class="header-left">
            <div class="chat-avatar">
                <div class="avatar-icon">
                    {% if conversation.target == 'admin' %}
                    <i class="bi bi-shield-fill-check"></i>
                    {% else %}
                    <i class="bi bi-person-badge"></i>
                    {% endif %}
                </div>
            </div>

            <div class="chat-info">
                <div class="chat-title">
                    <h3 class="chat-name">{{ conversation.subject|default:'Support Chat' }}</h3>
                    {% if conversation.issue_report %}
                    <span class="report-badge">#{{ conversation.issue_report.id }}</span>
                    {% endif %}
                </div>

                <div class="chat-meta">
                    <span class="target-badge {{ conversation.target }}">
                        <i class="bi {% if conversation.target == 'admin' %}bi-shield{% else %}bi-person{% endif %}"></i>
                        {{ conversation.get_target_display }}
                    </span>

                    {% if conversation.assigned_sub_admin %}
                    <span class="assignee-badge">
                        <i class="bi bi-person-check"></i>
                        {{ conversation.assigned_sub_admin.name }}
                    </span>
                    {% endif %}

                    <span class="chat-status online">
                        <i class="bi bi-circle-fill"></i>
                        Active
                    </span>
                </div>
            </div>
        </div>

        <div class="header-right">
            <button class="header-icon-btn" id="refreshBtn">
                <i class="bi bi-arrow-repeat"></i>
            </button>
            <button class="header-icon-btn" id="infoBtn">
                <i class="bi bi-info-circle"></i>
            </button>
        </div>
    </div>

    <!-- Messages Area -->
    <div class="messages-area" id="messagesArea">
        <div class="messages-container" id="messagesContainer">
            <!-- Date Separator -->
            <div class="date-separator">
                <span class="date-badge">Today</span>
            </div>

            {% for message in messages_list %}
            <div class="message-wrapper {% if message.sender_user == request.user %}message-out{% else %}message-in{% endif %}"
                 data-message-id="{{ message.id }}"
                 data-timestamp="{{ message.created_at|date:'c' }}">

                {% if message.sender_user != request.user %}
                <div class="message-avatar">
                    <div class="avatar-icon small">
                        <i class="bi bi-person-badge"></i>
                    </div>
                </div>
                {% endif %}

                <div class="message-content-wrapper">
                    <div class="message-sender">{{ message.sender_role|title }}</div>

                    <div class="message-bubble">
                        {% if message.content %}
                        <div class="message-text">{{ message.content|linebreaksbr }}</div>
                        {% endif %}

                        {% if message.attachment %}
                        <div class="message-attachment">
                            {% with attachment_url=message.attachment.url|lower %}
                            {% if ".jpg" in attachment_url or ".jpeg" in attachment_url or ".png" in attachment_url or ".gif" in attachment_url or ".webp" in attachment_u
                            <div class="attachment-image">
                                <img src="{{ message.attachment.url }}" alt="attachment">
                            </div>
                            <a href="{{ message.attachment.url }}" target="_blank" class="attachment-link">
                                <i class="bi bi-eye"></i> View Image
                            </a>
                            {% else %}
                            <a href="{{ message.attachment.url }}" target="_blank" class="attachment-link">
                                <i class="bi bi-paperclip"></i>
                                {{ message.attachment.name|truncatechars:30 }}
                            </a>
                            {% endif %}
                            {% endwith %}
                        </div>
                        {% endif %}

                        <div class="message-footer">
                            <span class="message-time">{{ message.created_at|date:'H:i' }}</span>
                            {% if message.sender_user == request.user %}
                            <span class="message-status">
                                <i class="bi bi-check2{% if message.is_read %}-all{% endif %}"></i>
                            </span>
                            {% endif %}
                        </div>
                    </div>
                </div>
            </div>
            {% endfor %}
        </div>

        <!-- Scroll to bottom button -->
        <button class="scroll-bottom-btn" id="scrollBottomBtn" style="display: none;">
            <i class="bi bi-arrow-down"></i>
        </button>
    </div>

    <!-- Message Input Area -->
    <div class="input-area">
        <form id="support-send-form" enctype="multipart/form-data" class="message-form">
            {% csrf_token %}

            <div class="input-actions">
```

```
                    <button type="button" class="input-action-btn" id="attachBtn">
                        <i class="bi bi-paperclip"></i>
                    </button>
                </div>

                <div class="input-wrapper">
                    <textarea
                        name="content"
                        id="support-content"
                        class="message-input"
                        placeholder="Type your message..."
                        rows="1"></textarea>

                    <div class="input-tools">
                        <button type="button" class="input-tool-btn" id="emojiBtn">
                            <i class="bi bi-emoji-smile"></i>
                        </button>
                    </div>
                </div>

                <div class="input-attachment" id="inputAttachment" style="display: none;">
                    <span class="attachment-name" id="attachmentName"></span>
                    <button type="button" class="remove-attachment" id="removeAttachment">
                        <i class="bi bi-x"></i>
                    </button>
                </div>

                <button type="submit" class="send-btn" id="sendBtn" disabled>
                    <i class="bi bi-send-fill"></i>
                </button>
            </form>

            <!-- Typing indicator -->
            <div class="typing-indicator" id="typingIndicator" style="display: none;">
                <span class="typing-dots">
                    <span></span>
                    <span></span>
                    <span></span>
                </span>
                <span class="typing-text">Support is typing...</span>
            </div>
        </div>
    </div>

    <!-- Info Sidebar (hidden by default) -->
    <div class="info-sidebar" id="infoSidebar" style="display: none;">
        <div class="info-header">
            <h3>Conversation Info</h3>
            <button class="close-info-btn" id="closeInfoBtn">
                <i class="bi bi-x-lg"></i>
            </button>
        </div>

        <div class="info-content">
            <div class="info-section">
                <h5>Details</h5>
                <div class="info-row">
                    <span class="info-label">Target:</span>
                    <span class="info-value target-badge {{ conversation.target }}">
                        {{ conversation.get_target_display }}
                    </span>
                </div>

                <div class="info-row">
                    <span class="info-label">Status:</span>
                    <span class="info-value">
                        <span class="chat-status online">
                            <i class="bi bi-circle-fill"></i> Active
                        </span>
                    </span>
                </div>

                {% if conversation.assigned_sub_admin %}
                <div class="info-row">
                    <span class="info-label">Assigned to:</span>
                    <span class="info-value">{{ conversation.assigned_sub_admin.name }}</span>
                </div>
                {% endif %}

                <div class="info-row">
                    <span class="info-label">Started:</span>
                    <span class="info-value">{{ conversation.created_at|date:'M d, Y H:i' }}</span>
                </div>

                {% if conversation.issue_report %}
                <div class="info-row">
                    <span class="info-label">Related Report:</span>
                    <span class="info-value">
                        <a href="#" class="report-link">#{{ conversation.issue_report.id }}</a>
                    </span>
                </div>
                {% endif %}
            </div>

            <div class="info-section">
                <h5>Attachments</h5>
                <div class="attachments-list" id="attachmentsList">
                    <!-- Will be populated with attachments from messages -->
                </div>
            </div>
        </div>
    </div>
</div>

<!-- Hidden file input for attachments -->
<input type="file" id="fileInput" style="display: none;" name="attachment">

<style>
/* ===== CHAT NAVIGATION ===== */
.chat-navigation {
    padding: 1rem 2rem;
    background: var(--bg-card);
    border-bottom: 1px solid var(--border);
}

.back-button {
    display: inline-flex;
    align-items: center;
    gap: 0.5rem;
    padding: 0.5rem 1rem;
    border-radius: 999px;
    background: var(--bg-raised);
    border: 1px solid var(--border);
    color: var(--text-secondary);
    text-decoration: none;
    font-size: 0.85rem;
    font-weight: 600;
    transition: all var(--t-fast);
```

```
}

.back-button:hover {
    background: var(--primary-soft);
    color: var(--primary);
    border-color: var(--primary);
}

/* ===== CHAT MAIN ===== */
.chat-fullscreen {
    display: flex;
    flex-direction: column;
    height: calc(100vh - var(--header-h) - 2rem);
    background: var(--bg-card);
    border-radius: var(--radius-xl);
    overflow: hidden;
    border: 1px solid var(--border);
    box-shadow: var(--shadow-lg);
    margin: 1rem 0;
    position: relative;
}

.chat-main {
    flex: 1;
    display: flex;
    flex-direction: column;
    position: relative;
}

/* Chat Header */
.chat-header {
    padding: 1rem 2rem;
    background: var(--bg-card);
    border-bottom: 1px solid var(--border);
    display: flex;
    align-items: center;
    justify-content: space-between;
    box-shadow: var(--shadow-sm);
    z-index: 10;
}

.header-left {
    display: flex;
    align-items: center;
    gap: 1rem;
    flex: 1;
}

.chat-avatar {
    flex-shrink: 0;
}

.avatar-icon {
    width: 48px;
    height: 48px;
    border-radius: 14px;
    background: linear-gradient(135deg, var(--primary), var(--primary-dark));
    display: flex;
    align-items: center;
    justify-content: center;
    color: white;
    font-size: 1.5rem;
    box-shadow: 0 4px 12px var(--primary-glow);
}

.avatar-icon.small {
    width: 32px;
    height: 32px;
    font-size: 1rem;
    border-radius: 10px;
}

.chat-title {
    display: flex;
    align-items: center;
    gap: 0.5rem;
    margin-bottom: 0.25rem;
}

.chat-name {
    font-size: 1.1rem;
    font-weight: 700;
    color: var(--text-primary);
    margin: 0;
}

.report-badge {
    padding: 0.15rem 0.6rem;
    background: var(--accent-soft);
    border-radius: 999px;
    font-size: 0.65rem;
    font-weight: 600;
    color: var(--accent);
    border: 1px solid rgba(245,176,66,0.2);
}

.chat-meta {
    display: flex;
    align-items: center;
    gap: 0.75rem;
    flex-wrap: wrap;
}

.target-badge.admin {
    background: var(--primary-soft);
    color: var(--primary);
    border: 1px solid rgba(91,76,255,0.2);
}

.target-badge.sub_admin {
    background: var(--success-soft);
    color: var(--success);
    border: 1px solid rgba(0,201,139,0.2);
}

.assignee-badge {
    display: inline-flex;
    align-items: center;
    gap: 0.25rem;
    padding: 0.2rem 0.6rem;
    background: var(--bg-raised);
    border: 1px solid var(--border);
    border-radius: 999px;
    font-size: 0.75rem;
    font-weight: 600;
    color: var(--text-secondary);
}
.chat-status {
```

```
    display: flex;
    align-items: center;
    gap: 0.2rem;
    font-size: 0.75rem;
    font-weight: 600;
    color: var(--success);
}

.chat-status i {
    font-size: 0.5rem;
}

.header-right {
    display: flex;
    gap: 0.5rem;
}

.header-icon-btn {
    width: 36px;
    height: 36px;
    border-radius: 10px;
    background: var(--bg-raised);
    border: 1px solid var(--border);
    color: var(--text-secondary);
    display: flex;
    align-items: center;
    justify-content: center;
    font-size: 1rem;
    cursor: pointer;
    transition: all var(--t-fast);
}

.header-icon-btn:hover {
    background: var(--primary-soft);
    color: var(--primary);
    border-color: var(--primary);
}

/* Messages Area */
.messages-area {
    flex: 1;
    overflow-y: auto;
    padding: 2rem;
    background: var(--bg-base);
    position: relative;
    scroll-behavior: smooth;
}

.messages-area::-webkit-scr
```

(Content truncated due to size - showing first 15KB)

## File: resources\views\customer\support_chat_list.blade.php

```
<!-- customer/support_chat_list.html -->
{% extends 'customer/base.html' %}

{% block content %}
<div class="support-fullscreen">
    <!-- Sidebar - New Chat Form -->
    <div class="support-sidebar">
        <div class="sidebar-header">
            <div class="header-icon">
                <i class="bi bi-headset"></i>
            </div>
            <h2 class="sidebar-title">Support Center</h2>
            <p class="sidebar-subtitle">We're here to help</p>
        </div>

        <div class="new-chat-form">
            <form method="post" action="{% url 'support_chat_start' %}" enctype="multipart/form-data" id="newChatForm">
                {% csrf_token %}

                <div class="form-group">
                    <label class="form-label">
                        <i class="bi bi-shield-check"></i>
                        Contact
                    </label>
                    <select name="target" class="form-control">
                        {% for value,label in target_choices %}
                        <option value="{{ value }}">{{ label }}</option>
                        {% endfor %}
                    </select>
                </div>

                <div class="form-group">
                    <label class="form-label">
                        <i class="bi bi-flag"></i>
                        Related Report
                    </label>
                    <select name="issue_report_id" class="form-control">
                        <option value="">No linked report</option>
                        {% for report in open_reports %}
                        <option value="{{ report.id }}">Report #{{ report.id }} - {{ report.get_status_display }}</option>
                        {% endfor %}
                    </select>
                </div>

                <div class="form-group">
                    <label class="form-label">
                        <i class="bi bi-tag"></i>
                        Subject
                    </label>
                    <input type="text" name="subject" class="form-control" placeholder="Brief description...">
                </div>

                <div class="form-group">
                    <label class="form-label">
                        <i class="bi bi-chat-text"></i>
                        Message
                    </label>
                    <textarea class="form-control" name="message" rows="4" placeholder="How can we help you?"></textarea>
                </div>

                <div class="form-group">
                    <label class="form-label file-upload" id="fileUploadLabel">
                        <i class="bi bi-paperclip"></i>
                        Attach File
                        <input type="file" name="attachment" class="file-input" id="fileInput">
                    </label>
                    <div class="file-preview" id="filePreview"></div>
                </div>

                <button type="submit" class="submit-btn">
                    <i class="bi bi-send-fill"></i>
```

```
                    Start Support Chat
                </button>
            </form>
        </div>
    </div>

    <!-- Main Area - Conversations List -->
    <div class="support-main">
        <div class="main-header">
            <div class="header-left">
                <h1 class="main-title">Support Conversations</h1>
                <span class="unread-badge-large" id="totalUnreadBadge">
                    {{ total_unread }} unread
                </span>
            </div>

            <div class="header-right">
                <div class="search-wrapper">
                    <i class="bi bi-search"></i>
                    <input type="text" placeholder="Search conversations..." id="searchConversations" class="search-input">
                </div>
            </div>
        </div>

        <div class="conversations-list" id="conversationsList">
            {% for row in conversation_rows %}
            <a href="{% url 'support_chat_detail' row.conversation.id %}"
               class="conversation-card {% if row.unread_count %}unread{% endif %}"
               data-conversation-id="{{ row.conversation.id }}"
               data-search-text="{{ row.conversation.subject|default:'' }} {{ row.last_message.content|default:'' }}">

                <div class="conversation-avatar">
                    <div class="avatar-icon">
                        {% if row.conversation.target == 'admin' %}
                        <i class="bi bi-shield-fill-check"></i>
                        {% else %}
                        <i class="bi bi-person-badge"></i>
                        {% endif %}
                    </div>
                </div>

                <div class="conversation-content">
                    <div class="conversation-header">
                        <div class="conversation-title">
                            <span class="conversation-subject">
                                {{ row.conversation.subject|default:'Support conversation' }}
                            </span>
                            {% if row.conversation.issue_report %}
                            <span class="report-badge">
                                #{{ row.conversation.issue_report.id }}
                            </span>
                            {% endif %}
                        </div>
                        <div class="conversation-time">
                            {{ row.conversation.updated_at|date:'H:i' }}
                        </div>
                    </div>

                    <div class="conversation-meta">
                        <div class="meta-badges">
                            <span class="target-badge {{ row.conversation.target }}">
                                <i class="bi {% if row.conversation.target == 'admin' %}bi-shield{% else %}bi-person{% endif %}"></i>
                                {{ row.conversation.get_target_display }}
                            </span>
                            {% if row.conversation.assigned_sub_admin %}
                            <span class="assignee-badge">
                                <i class="bi bi-person-check"></i>
                                {{ row.conversation.assigned_sub_admin.name }}
                            </span>
                            {% endif %}
                        </div>
                    </div>

                    <div class="conversation-preview">
                        <div class="preview-text">
                            {% if row.last_message %}
                                {{ row.last_message.content|truncatechars:80 }}
                            {% else %}
                                <span class="no-messages">No messages yet</span>
                            {% endif %}
                        </div>

                        <div class="preview-meta">
                            {% if row.unread_count %}
                            <span class="unread-badge">{{ row.unread_count }}</span>
                            {% endif %}
                            <span class="message-time">{{ row.conversation.updated_at|date:'M d' }}</span>
                        </div>
                    </div>
                </div>
            </a>
            {% empty %}
            <div class="empty-state">
                <div class="empty-icon">
                    <i class="bi bi-chat-dots"></i>
                </div>
                <h3>No support conversations</h3>
                <p>Start a new support chat using the form on the left</p>
            </div>
            {% endfor %}
        </div>
    </div>
</div>

<style>
/* ===== FULLSCREEN SUPPORT LAYOUT ===== */
.support-fullscreen {
    display: flex;
    height: calc(100vh - var(--header-h) - 2rem);
    background: var(--bg-base);
    border-radius: var(--radius-xl);
    overflow: hidden;
    border: 1px solid var(--border);
    box-shadow: var(--shadow-lg);
    margin: 1rem 0;
}

/* ===== SIDEBAR ===== */
.support-sidebar {
    width: 380px;
    background: linear-gradient(145deg, var(--bg-card), var(--bg-raised));
    border-right: 1px solid var(--border);
    overflow-y: auto;
    padding: 2rem 1.5rem;
}

.sidebar-header {
    text-align: center;
```

```
    margin-bottom: 2rem;
}

.header-icon {
    width: 64px;
    height: 64px;
    border-radius: 20px;
    background: linear-gradient(135deg, var(--primary), var(--primary-dark));
    display: flex;
    align-items: center;
    justify-content: center;
    margin: 0 auto 1rem;
    color: white;
    font-size: 2rem;
    box-shadow: 0 8px 20px var(--primary-glow);
}

.sidebar-title {
    font-size: 1.5rem;
    font-weight: 800;
    color: var(--text-primary);
    margin-bottom: 0.25rem;
    letter-spacing: -0.02em;
}

.sidebar-subtitle {
    font-size: 0.85rem;
    color: var(--text-muted);
}

/* New Chat Form */
.new-chat-form {
    background: var(--bg-card);
    border-radius: var(--radius-lg);
    padding: 1.5rem;
    border: 1px solid var(--border);
    box-shadow: var(--shadow-sm);
}

.form-group {
    margin-bottom: 1.25rem;
}

.form-label {
    display: flex;
    align-items: center;
    gap: 0.4rem;
    font-size: 0.8rem;
    font-weight: 600;
    color: var(--text-secondary);
    margin-bottom: 0.5rem;
}

.form-label i {
    color: var(--primary);
    font-size: 0.9rem;
}

.form-control {
    width: 100%;
    padding: 0.7rem 1rem;
    border-radius: var(--radius);
    border: 1.5px solid var(--border);
    background: var(--bg-raised);
    color: var(--text-primary);
    font-size: 0.9rem;
    transition: all var(--t-fast);
}

.form-control:focus {
    outline: none;
    border-color: var(--primary);
    box-shadow: 0 0 0 4px var(--primary-soft);
}

textarea.form-control {
    resize: vertical;
    min-height: 100px;
    font-family: 'Outfit', sans-serif;
}

/* File Upload */
.file-upload {
    position: relative;
    display: flex;
    align-items: center;
    gap: 0.5rem;
    padding: 0.7rem 1rem;
    background: var(--bg-raised);
    border: 1.5px dashed var(--border);
    border-radius: var(--radius);
    color: var(--text-secondary);
    font-size: 0.9rem;
    cursor: pointer;
    transition: all var(--t-fast);
}

.file-upload:hover {
    border-color: var(--primary);
    background: var(--primary-soft);
}

.file-input {
    position: absolute;
    opacity: 0;
    width: 100%;
    height: 100%;
    top: 0;
    left: 0;
    cursor: pointer;
}

.file-preview {
    margin-top: 0.5rem;
    padding: 0.5rem;
    background: var(--bg-raised);
    border-radius: var(--radius-sm);
    font-size: 0.8rem;
    color: var(--text-secondary);
    display: none;
}

.file-preview.active {
    display: flex;
    align-items: center;
    gap: 0.5rem;
}
.file-preview i {
```

```
    color: var(--success);
}

.submit-btn {
    width: 100%;
    padding: 0.9rem;
    border-radius: var(--radius);
    background: linear-gradient(135deg, var(--primary), var(--primary-dark));
    border: none;
    color: white;
    font-size: 0.9rem;
    font-weight: 700;
    display: flex;
    align-items: center;
    justify-content: center;
    gap: 0.5rem;
    cursor: pointer;
    transition: all var(--t-fast);
    box-shadow: 0 4px 12px var(--primary-glow);
}

.submit-btn:hover {
    transform: translateY(-2px);
    box-shadow: 0 8px 20px var(--primary-glow);
}

/* ===== MAIN AREA ===== */
.support-main {
    flex: 1;
    background: var(--bg-card);
    display: flex;
    flex-direction: column;
    overflow: hidden;
}

.main-header {
    padding: 1.5rem 2rem;
    border-bottom: 1px solid var(--border);
    display: flex;
    align-items: center;
    justify-content: space-between;
    flex-wrap: wrap;
    gap: 1rem;
    background: var(--bg-card);
}

.header-left {
    display: flex;
    align-items: center;
    gap: 1rem;
}

.main-title {
    font-size: 1.5rem;
    font-weight: 800;
    color: var(--text-primary);
    letter-spacing: -0.02em;
    margin: 0;
}

.unread-badge-large {
    background: var(--danger);
    color: white;
    padding: 0.3rem 1rem;
    border-radius: 999px;
    font-size: 0.8rem;
    font-weight: 700;
    box-shadow: 0 4px 12px rgba(255,77,109,0.3);
}

.search-wrapper {
    display: flex;
    align-items: center;
    background: var(--bg-raised);
    border: 1.5px solid var(--border);
    border-radius: 999px;
    padding: 0.3rem 0.3rem 0.3rem 1rem;
    width: 280px;
}

.search-wrapper i {
    color: var(--text-muted);
    font-size: 0.9rem;
    margin-right: 0.5rem;
}

.search-input {
    flex: 1;
    border: none;
    background: transparent;
    outline: none;
    color: var(--text-primary);
    font-size: 0.9rem;
    padding: 0.6rem 0;
}

.search-input::placeholder {
    color: var(--text-muted);
}

/* Conversations List */
.conversations-list {
    flex: 1;
    overflow-y: auto;
    padding: 1.5rem 2rem;
    scrollbar-width: thin;
    scrollbar-color: var(--border) transparent;
}

.conversations-list::-webkit-scrollbar {
    width: 6px;
}

.conversations-list::-webkit-scrollbar-track {
    background: transparent;
}

.conversations-list::-webkit-scrollbar-thumb {
    background: var(--border);
    border-radius: 10px;
}

/* Conversation Card */
.conversation-card {
    display: flex;
    gap: 1rem;
    padding: 1.25rem;
    border-radius: var(--radius-lg);
```

```
    background: var(--bg-card);
    border: 1px solid var(--border);
    margin-bottom: 0.75rem;
    text-decoration: none;
    color: inherit;
    transition: all var(--t-fast);
    animation: slideIn 0.3s ease;
}

@keyframes slideIn {
    from {
        opacity: 0;
        transform: translateX(-20px);
    }
    to {
        opacity: 1;
        transform: translateX(0);
    }
}

.conversation-card:hover {
    transform: translateX(4px);
    border-color: var(--primary);
    box-shadow: var(--shadow);
}

.conversation-card.unread {
    background: var(--primary-soft);
    border-left: 3px solid var(--primary);
}

/* Avatar */
.conversation-avatar {
    flex-shrink: 0;
}

.avatar-icon {
    width: 48px;
    height: 48px;
    border-radius: 14px;
    background: linear-gradient(135deg, var(--primary), var(--primary-dark));
    display: flex;
    align-items: center;
    justify-content: center;
    color: white;
    font-size: 1.5rem;
    box-shadow: 0 4px 12px var(--primary-glow);
}

.conversation-card.unread .avatar-icon {
    box-shadow: 0 0 0 3px rgba(91,76,255,0.3);
}

/* Content */
.conversation-content {
    flex: 1;
    min-width: 0;
}

.conversation-header {
    display: flex;
    justify-content: space-between;
    align-items: flex-start;
    margin-bottom: 0.4rem;
}

.conversation-title {
    display: flex;
    align-items: center;
    gap: 0.5rem;
    flex-wrap: wrap;
}

.conversation-subject {
    font-weight: 700;
    font-size: 1rem;
    color: var(--text-primary);
}
```

(Content truncated due to size - showing first 15KB)

## File: resources\views\customer\wishlist.blade.php

```
@extends('customer.base')

@section('title', 'My Wishlist - BookHub')

@section('content')
<section class="wl-shell container">
    <div class="wl-hero">
        <div class="wl-hero-copy">
            <p class="wl-eyebrow"><i class="bi bi-bookmarks-fill"></i> Saved Collection</p>
            <h1>My Wishlist</h1>
            <p>Keep your favorite books in one place and move them to cart when you are ready.</p>
        </div>
        <div class="wl-hero-metric">
            <span>Items saved</span>
            <strong>{{ $wishlistCount ?? 0 }}</strong>
            <small>book{{ ($wishlistCount ?? 0) === 1 ? '' : 's' }}</small>
        </div>
    </div>

    @if(!empty($wishlistBooks) && $wishlistBooks->count())
    <div class="wl-grid">
        @foreach($wishlistBooks as $book)
        <article class="wl-card" style="--i:{{ $loop->index }};">
            <a href="{{ route('books.show', $book->id) }}" class="wl-media">
                @if($book->cover_image_path)
                <img src="{{ asset($book->cover_image_path) }}" alt="{{ $book->title }}">
                @else
                <div class="wl-media-fallback">
                    <i class="bi bi-journal-bookmark-fill"></i>
                    <span>No Cover</span>
                </div>
                @endif
            </a>

            <div class="wl-body">
                <h3 class="wl-title">{{ $book->title }}</h3>
                <p class="wl-author">{{ $book->author }}</p>
                <div class="wl-meta">
                    <span class="wl-chip"><i class="bi bi-tag-fill"></i> {{ $book->genre ?? 'General' }}</span>
                    @if($book->available_rent > 0 || $book->available_sale > 0)
                    <span class="wl-chip wl-chip-live"><i class="bi bi-lightning-charge-fill"></i> Available</span>
                    @else
```

```
                    <span class="wl-chip wl-chip-muted"><i class="bi bi-pause-circle-fill"></i> Out of stock</span>
                    @endif
                </div>

                <div class="wl-prices">
                    @if($book->available_rent > 0)
                    <div class="wl-price wl-rent">
                        <span>Rent</span>
                        <strong>${{ number_format($book->rental_price, 2) }}</strong>
                        <small>/month</small>
                    </div>
                    @endif
                    @if($book->available_sale > 0)
                    <div class="wl-price wl-buy">
                        <span>Buy</span>
                        <strong>${{ number_format($book->sale_price, 2) }}</strong>
                    </div>
                    @endif
                    @if($book->available_rent <= 0 && $book->available_sale <= 0)
                    <div class="wl-price wl-muted">
                        <span>Unavailable right now</span>
                    </div>
                    @endif
                </div>

                <div class="wl-actions">
                    <a href="{{ route('books.show', $book->id) }}" class="wl-btn wl-btn-ghost">
                        <i class="bi bi-eye-fill"></i> View
                    </a>
                    @if($book->available_rent > 0)
                    <a href="{{ route('cart.add.rent', $book->id) }}" class="wl-btn wl-btn-rent">
                        <i class="bi bi-arrow-left-right"></i> Rent
                    </a>
                    @endif
                    @if($book->available_sale > 0)
                    <a href="{{ route('cart.add.buy', $book->id) }}" class="wl-btn wl-btn-buy">
                        <i class="bi bi-bag-check-fill"></i> Buy
                    </a>
                    @endif
                    <a href="{{ route('wishlist.remove', $book->id) }}" class="wl-btn wl-btn-danger" onclick="return confirm('Remove this book from your wishlist?');">
                        <i class="bi bi-trash3-fill"></i> Remove
                    </a>
                </div>
            </div>
        </article>
        @endforeach
    </div>

    <div class="wl-footer-actions">
        <a href="{{ route('customer.dashboard') }}" class="wl-footer-btn wl-footer-primary">
            <i class="bi bi-plus-circle-fill"></i> Add More Books
        </a>
        <a href="{{ route('cart.index') }}" class="wl-footer-btn wl-footer-success">
            <i class="bi bi-cart-check-fill"></i> Open Cart
        </a>
        <a href="{{ route('wishlist.clear') }}" class="wl-footer-btn wl-footer-danger" onclick="return confirm('Clear all items from wishlist?');">
            <i class="bi bi-trash-fill"></i> Clear All
        </a>
    </div>
    @else
    <div class="wl-empty">
        <div class="wl-empty-icon"><i class="bi bi-heart-fill"></i></div>
        <h3>Your wishlist is empty</h3>
        <p>Save books you are interested in by clicking the heart icon on any book page.</p>
        <a href="{{ route('customer.dashboard') }}" class="wl-footer-btn wl-footer-primary">
            <i class="bi bi-compass-fill"></i> Browse Books
        </a>
    </div>
    @endif
</section>
@endsection

@section('extra_css')
<style>
.wl-shell {
    max-width: 1240px;
    margin: 1rem auto 0;
    position: relative;
    z-index: 2;
}

.wl-hero {
    display: grid;
    grid-template-columns: 1fr auto;
    gap: 1rem;
    align-items: center;
    background:
        linear-gradient(140deg, rgba(91, 76, 255, 0.14), rgba(245, 176, 66, 0.10)),
        var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-xl);
    padding: 1.4rem 1.5rem;
    box-shadow: var(--shadow);
    overflow: hidden;
}

.wl-eyebrow {
    margin: 0 0 0.45rem 0;
    font-size: 0.75rem;
    letter-spacing: 1px;
    text-transform: uppercase;
    font-weight: 800;
    color: var(--primary);
    display: inline-flex;
    align-items: center;
    gap: 0.35rem;
}

.wl-hero h1 {
    margin: 0;
    font-size: clamp(1.3rem, 1.9vw, 2rem);
    letter-spacing: -0.02em;
    font-weight: 800;
    color: var(--text-primary);
}

.wl-hero-copy p:last-child {
    margin: 0.45rem 0 0;
    color: var(--text-secondary);
    font-size: 0.92rem;
}

.wl-hero-metric {
    min-width: 150px;
    text-align: center;
    background: var(--bg-raised);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
```

```
    padding: 0.75rem 0.9rem;
}

.wl-hero-metric span {
    display: block;
    font-size: 0.7rem;
    text-transform: uppercase;
    letter-spacing: 1px;
    color: var(--text-muted);
    font-weight: 700;
}

.wl-hero-metric strong {
    display: block;
    font-size: 1.8rem;
    color: var(--primary);
    line-height: 1.05;
    margin-top: 0.2rem;
}

.wl-hero-metric small {
    color: var(--text-muted);
    font-size: 0.75rem;
}

.wl-grid {
    display: grid;
    grid-template-columns: repeat(auto-fill, minmax(250px, 1fr));
    gap: 1rem;
    margin-top: 1.2rem;
}

.wl-card {
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
    overflow: hidden;
    box-shadow: var(--shadow-sm);
    transition: transform var(--t), box-shadow var(--t), border-color var(--t);
    animation: wl-rise 420ms both;
    animation-delay: calc(var(--i) * 50ms);
}

.wl-card:hover {
    transform: translateY(-6px);
    border-color: rgba(91, 76, 255, 0.35);
    box-shadow: var(--shadow-lg);
}

.wl-media {
    position: relative;
    display: block;
    height: 220px;
    background: var(--bg-raised);
    overflow: hidden;
}

.wl-media img {
    width: 100%;
    height: 100%;
    object-fit: cover;
    transition: transform var(--t);
}

.wl-card:hover .wl-media img {
    transform: scale(1.05);
}

.wl-media-fallback {
    width: 100%;
    height: 100%;
    display: flex;
    flex-direction: column;
    justify-content: center;
    align-items: center;
    gap: 0.4rem;
    color: var(--text-muted);
    font-weight: 700;
}

.wl-media-fallback i {
    font-size: 2rem;
    color: var(--primary);
}

.wl-body {
    padding: 0.95rem 0.95rem 1rem;
}

.wl-title {
    margin: 0;
    font-size: 1rem;
    font-weight: 800;
    line-height: 1.3;
    color: var(--text-primary);
    display: -webkit-box;
    -webkit-line-clamp: 2;
    -webkit-box-orient: vertical;
    overflow: hidden;
}

.wl-author {
    margin: 0.28rem 0 0.65rem;
    font-size: 0.8rem;
    color: var(--text-muted);
}

.wl-meta {
    display: flex;
    gap: 0.45rem;
    flex-wrap: wrap;
    margin-bottom: 0.75rem;
}

.wl-chip {
    display: inline-flex;
    align-items: center;
    gap: 0.25rem;
    border-radius: 999px;
    border: 1px solid var(--border);
    background: var(--bg-raised);
    color: var(--text-secondary);
    font-size: 0.68rem;
    font-weight: 700;
    padding: 0.17rem 0.5rem;
}

.wl-chip-live {
```

```
    background: var(--success-soft);
    border-color: rgba(0, 201, 139, 0.24);
    color: var(--success);
}

.wl-chip-muted {
    background: var(--danger-soft);
    border-color: rgba(255, 77, 109, 0.24);
    color: var(--danger);
}

.wl-prices {
    border: 1px solid var(--border-soft);
    border-radius: var(--radius);
    overflow: hidden;
    margin-bottom: 0.85rem;
}

.wl-price {
    display: flex;
    align-items: baseline;
    gap: 0.36rem;
    padding: 0.45rem 0.6rem;
    background: var(--bg-raised);
}

.wl-price + .wl-price {
    border-top: 1px solid var(--border-soft);
}

.wl-price span {
    font-size: 0.67rem;
    font-weight: 700;
    text-transform: uppercase;
    letter-spacing: 0.7px;
    color: var(--text-muted);
}

.wl-price strong {
    font-size: 0.95rem;
    line-height: 1;
}

.wl-price small {
    font-size: 0.64rem;
    color: var(--text-muted);
}

.wl-rent strong { color: var(--primary); }
.wl-buy strong { color: var(--success); }
.wl-muted span { text-transform: none; }

.wl-actions {
    display: flex;
    flex-wrap: wrap;
    gap: 0.42rem;
}

.wl-btn {
    border-radius: var(--radius-sm);
    padding: 0.45rem 0.6rem;
    font-size: 0.76rem;
    font-weight: 700;
    text-decoration: none;
    display: inline-flex;
    align-items: center;
    justify-content: center;
    gap: 0.3rem;
    border: 1px solid transparent;
    transition: all var(--t-fast);
    flex: 1 1 calc(50% - 0.42rem);
}

.wl-btn-ghost {
    color: var(--text-secondary);
    background: var(--bg-raised);
    border-color: var(--border);
}

.wl-btn-rent {
    color: var(--primary);
    background: var(--primary-soft);
    border-color: var(--border);
}

.wl-btn-buy {
    color: var(--success);
    background: var(--success-soft);
    border-color: rgba(0, 201, 139, 0.22);
}

.wl-btn-danger {
    color: var(--danger);
    background: var(--danger-soft);
    border-color: rgba(255, 77, 109, 0.22);
}

.wl-btn:hover {
    transform: translateY(-1px);
    filter: saturate(1.08);
}

.wl-footer-actions {
    margin-top: 1.2rem;
    display: flex;
    flex-wrap: wrap;
    gap: 0.65rem;
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
    padding: 0.85rem;
    box-shadow: var(--shadow-sm);
}

.wl-footer-btn {
    text-decoration: none;
    border-radius: var(--radius);
    padding: 0.62rem 0.88rem;
    font-size: 0.82rem;
    font-weight: 700;
    display: inline-flex;
    align-items: center;
    gap: 0.4rem;
    border: 1px solid transparent;
    transition: all var(--t-fast);
}

.wl-footer-btn:hover {
```

```
    transform: translateY(-1px);
}

.wl-footer-primary {
    background: var(--primary-soft);
    border-color: var(--border);
    color: var(--primary);
}

.wl-footer-success {
    background: var(--success-soft);
    border-color: rgba(0, 201, 139, 0.22);
    color: var(--success);
}

.wl-footer-danger {
    background: var(--danger-soft);
    border-color: rgba(255, 77, 109, 0.22);
    color: var(--danger);
}

.wl-empty {
    margin-top: 1.2rem;
    text-align: center;
    padding: 2rem 1.1rem;
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-xl);
    box-shadow: var(--shadow);
}

.wl-empty-icon {
    width: 88px;
    height: 88px;
    border-radius: 22px;
    background: linear-gradient(135deg, var(--danger-soft), var(--primary-soft));
    margin: 0 auto 0.85rem;
    display: flex;
    align-items: center;
    justify-content: center;
}

.wl-empty-icon i {
    font-size: 2rem;
    color: var(--danger);
}

.wl-empty h3 {
    margin: 0;
    font-size: 1.22rem;
    font-weight: 800;
    color: var(--text-primary);
}

.wl-empty p {
    max-width: 460px;
    margin: 0.55rem auto 1rem;
    color: var(--text-secondary);
    font-size: 0.92rem;
    line-height: 1.6;
}

@keyframes wl-rise {
    from {
        opacity: 0;
        transform: translateY(14px);
    }
    to {
        opacity: 1;
        transform: translateY(0);
    }
}

@media (max-width: 860px) {
    .wl-hero {
        grid-template-columns: 1fr;
        text-align: left;
    }

    .wl-hero-metric {
        width: 100%;
        text-align: left;
    }

    .wl-hero-metric strong {
        font-size: 1.5rem;
    }
}

@media (max-width: 540px) {
    .wl-shell {
        margin-top: 0.8rem;
    }

    .wl-grid {
        grid-template-columns: 1fr;
    }

    .wl-actions .wl-btn {
        flex: 1 1 100%;
    }

    .wl-footer-actions {
        padding: 0.7rem;
    }
}
</style>
@endsection
```

***File: resources\views\customer\issue_reports\create.blade.php***

```
@extends('customer.base')

@section('title', 'Report an Issue - BookHub')

@section('content')
<section class="issue-form-shell">
    <div class="issue-form-head">
        <div>
            <h1>Report an Issue</h1>
            <p>Provide details so our admin team can help quickly.</p>
        </div>
        <a href="{{ route('issue-reports.index') }}" class="btn-secondary">
            <i class="bi bi-arrow-left"></i> Back to Reports
        </a>
```

```
    </div>

    <form method="POST" action="{{ route('issue-reports.store') }}" class="issue-form" enctype="multipart/form-data">
        @csrf
        <label class="field">
            <span>Subject</span>
            <input type="text" name="subject" value="{{ old('subject') }}" required maxlength="255" placeholder="Example: Payment failed on checkout">
        </label>

        <label class="field">
            <span>Description</span>
            <textarea name="description" rows="6" required maxlength="4000" placeholder="Describe the issue in detail.">{{ old('description') }}</textarea>
        </label>

        <label class="field">
            <span>Evidence (Screenshot/File) <small style="color:var(--text-muted);font-weight:400;">Optional</small></span>
            <input type="file" name="evidence" accept=".jpg,.jpeg,.png,.gif,.pdf,.doc,.docx,.txt" style="background:#fff;">
        </label>

        <label class="field">
            <span>Priority</span>
            <select name="priority" required>
                <option value="low" @selected(old('priority') === 'low')>Low</option>
                <option value="medium" @selected(old('priority', 'medium') === 'medium')>Medium</option>
                <option value="high" @selected(old('priority') === 'high')>High</option>
            </select>
        </label>

        <button type="submit" class="btn-primary">
            <i class="bi bi-flag-fill"></i>
            Submit Report
        </button>
    </form>
</section>
@endsection

@section('extra_css')
<style>
.issue-form-shell {
    max-width: 760px;
    margin: 0 auto;
    display: grid;
    gap: 1.2rem;
}
.issue-form-head {
    display: flex;
    align-items: center;
    justify-content: space-between;
    gap: 1rem;
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
    padding: 1.2rem 1.4rem;
    box-shadow: var(--shadow-sm);
}
.issue-form-head h1 {
    margin: 0 0 0.35rem 0;
    font-size: 1.5rem;
}
.issue-form-head p {
    margin: 0;
    color: var(--text-secondary);
    font-size: 0.9rem;
}
.issue-form {
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
    padding: 1.4rem;
    box-shadow: var(--shadow-sm);
    display: grid;
    gap: 1rem;
}
.field {
    display: grid;
    gap: 0.45rem;
    font-size: 0.82rem;
    color: var(--text-secondary);
    font-weight: 600;
}
.field input,
.field textarea,
.field select {
    background: var(--bg-raised);
    border: 1px solid var(--border);
    border-radius: var(--radius);
    padding: 0.7rem 0.8rem;
    font-family: 'Outfit', sans-serif;
    color: var(--text-primary);
}
.btn-primary {
    justify-self: flex-start;
    display: inline-flex;
    align-items: center;
    gap: 0.45rem;
    padding: 0.65rem 1.2rem;
    border-radius: 999px;
    background: var(--primary);
    color: #fff;
    font-weight: 700;
    border: none;
    cursor: pointer;
}
.btn-secondary {
    display: inline-flex;
    align-items: center;
    gap: 0.4rem;
    padding: 0.6rem 1.1rem;
    border-radius: 999px;
    background: var(--bg-raised);
    border: 1px solid var(--border);
    color: var(--text-secondary);
    text-decoration: none;
    font-weight: 700;
}
</style>
@endsection
```

***File: resources\views\customer\issue_reports\index.blade.php***

```
@extends('customer.base')

@section('title', 'Issue Reports - BookHub')

@section('content')
```

```
<section class="issue-shell">
    <div class="issue-head">
        <div>
            <h1>Your Issue Reports</h1>
            <p>Track the status of your submitted issues.</p>
        </div>
        <a href="{{ route('issue-reports.create') }}" class="btn-primary">
            <i class="bi bi-plus-circle"></i>
            New Report
        </a>
    </div>

    <div class="issue-list">
        @forelse($reports as $report)
            <a href="{{ route('issue-reports.show', $report) }}" class="issue-card">
                <div>
                    <h3>{{ $report->subject }}</h3>
                    <p>{{ \Illuminate\Support\Str::limit($report->description, 110) }}</p>
                </div>
                <div class="issue-meta">
                    <span class="pill priority-{{ $report->priority }}">{{ ucfirst($report->priority) }}</span>
                    <span class="pill status-{{ $report->status }}">{{ ucfirst(str_replace('_', ' ', $report->status)) }}</span>
                    <span class="date">{{ $report->created_at->format('M d, Y') }}</span>
                </div>
            </a>
        @empty
            <div class="issue-empty">
                <i class="bi bi-flag"></i>
                <h3>No reports yet</h3>
                <p>If something is wrong, submit a report and our admins will help.</p>
                <a href="{{ route('issue-reports.create') }}" class="btn-primary">
                    <i class="bi bi-plus-circle"></i> Create Report
                </a>
            </div>
        @endforelse
    </div>
</section>
@endsection

@section('extra_css')
<style>
.issue-shell {
    max-width: 980px;
    margin: 0 auto;
    display: grid;
    gap: 1.2rem;
}
.issue-head {
    display: flex;
    align-items: center;
    justify-content: space-between;
    gap: 1rem;
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
    padding: 1.2rem 1.4rem;
    box-shadow: var(--shadow-sm);
}
.issue-head h1 {
    margin: 0 0 0.35rem 0;
    font-size: 1.5rem;
}
.issue-head p {
    margin: 0;
    color: var(--text-secondary);
    font-size: 0.9rem;
}
.btn-primary {
    display: inline-flex;
    align-items: center;
    gap: 0.45rem;
    padding: 0.6rem 1.1rem;
    border-radius: 999px;
    background: var(--primary);
    color: #fff;
    font-weight: 700;
    text-decoration: none;
    border: none;
}
.issue-list {
    display: grid;
    gap: 0.9rem;
}
.issue-card {
    display: flex;
    justify-content: space-between;
    gap: 1rem;
    padding: 1rem 1.2rem;
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
    text-decoration: none;
    color: inherit;
    box-shadow: var(--shadow-sm);
    transition: all var(--t-fast);
}
.issue-card:hover {
    border-color: var(--primary);
    box-shadow: var(--shadow);
}
.issue-card h3 {
    margin: 0 0 0.35rem 0;
    font-size: 1rem;
}
.issue-card p {
    margin: 0;
    font-size: 0.82rem;
    color: var(--text-secondary);
}
.issue-meta {
    display: grid;
    gap: 0.4rem;
    align-content: center;
    text-align: right;
    font-size: 0.75rem;
    color: var(--text-muted);
}
.pill {
    padding: 0.18rem 0.6rem;
    border-radius: 999px;
    font-weight: 700;
    font-size: 0.7rem;
    border: 1px solid transparent;
}
.priority-low { background: var(--bg-raised); color: var(--text-secondary); border-color: var(--border); }
.priority-medium { background: var(--accent-soft); color: var(--accent); border-color: rgba(245,176,66,0.3); }
.priority-high { background: var(--danger-soft); color: var(--danger); border-color: rgba(255,77,109,0.3); }
.status-open { background: var(--primary-soft); color: var(--primary); border-color: var(--border); }
```

```
.status-in_review { background: var(--bg-raised); color: var(--text-secondary); border-color: var(--border); }
.status-resolved { background: var(--success-soft); color: var(--success); border-color: rgba(0,201,139,0.3); }
.status-closed { background: var(--bg-raised); color: var(--text-muted); border-color: var(--border); }
.issue-empty {
    text-align: center;
    padding: 2rem 1rem;
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
    box-shadow: var(--shadow-sm);
}
.issue-empty i {
    font-size: 2rem;
    display: block;
    margin-bottom: 0.6rem;
    color: var(--text-muted);
}
@media (max-width: 720px) {
    .issue-card {
        flex-direction: column;
        text-align: left;
    }
    .issue-meta {
        text-align: left;
    }
}
</style>
@endsection
```

### File: resources\views\customer\issue_reports\show.blade.php

```
@extends('customer.base')

@section('title', 'Issue Report - BookHub')

@section('content')
<section class="issue-detail">
    <div class="detail-head">
        <div>
            <a href="{{ route('issue-reports.index') }}" class="back-link"><i class="bi bi-arrow-left"></i> Back to Reports</a>
            <h1>{{ $report->subject }}</h1>
            <p>Created {{ $report->created_at->format('M d, Y H:i') }}</p>
        </div>
        <div class="detail-meta">
            <span class="pill priority-{{ $report->priority }}">{{ ucfirst($report->priority) }}</span>
            <span class="pill status-{{ $report->status }}">{{ ucfirst(str_replace('_', ' ', $report->status)) }}</span>
        </div>
    </div>

    <div class="detail-body">
        <h3>Description</h3>
        <p>{{ $report->description }}</p>

        @if($report->hasEvidence())
            <hr style="margin:1.5rem 0;border-color:var(--border);">
            <h3>Evidence</h3>
            <div style="background:var(--bg);padding:1rem;border-radius:var(--radius);border:1px solid var(--border);margin-bottom:1rem;">
                <div style="display:flex;align-items:center;gap:0.75rem;">
                    <i class="bi {{ $report->isEvidenceImage() ? 'bi-image' : 'bi-file-earmark-text' }} fs-4 text-muted"></i>
                    <div style="flex:1;">
                        <div style="font-weight:600;font-size:0.9rem;">{{ $report->evidence_name }}</div>
                        <a href="{{ $report->evidence_url }}" target="_blank" style="font-size:0.8rem;color:var(--primary);text-decoration:none;font-weight:600;">View / Downlo
                    </div>
                </div>
                @if($report->isEvidenceImage())
                    <div style="margin-top:1rem;">
                        <img src="{{ $report->evidence_url }}" alt="Evidence" style="max-width:100%;max-height:300px;border-radius:8px;border:1px solid var(--border);">
                    </div>
                @endif
            </div>
        @endif

        @if($report->assignedAdmin)
            <div class="assigned">Assigned admin: {{ $report->assignedAdmin->name }}</div>
        @endif
    </div>
</section>
@endsection

@section('extra_css')
<style>
.issue-detail {
    max-width: 800px;
    margin: 0 auto;
    display: grid;
    gap: 1rem;
}
.detail-head {
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
    padding: 1.2rem 1.4rem;
    box-shadow: var(--shadow-sm);
    display: flex;
    justify-content: space-between;
    gap: 1rem;
}
.detail-head h1 {
    margin: 0.5rem 0 0.35rem;
    font-size: 1.4rem;
}
.detail-head p {
    margin: 0;
    color: var(--text-secondary);
    font-size: 0.85rem;
}
.back-link {
    text-decoration: none;
    color: var(--primary);
    font-size: 0.85rem;
    font-weight: 600;
    display: inline-flex;
    align-items: center;
    gap: 0.35rem;
}
.detail-meta {
    display: grid;
    gap: 0.4rem;
    align-content: center;
    text-align: right;
}
.pill {
    padding: 0.2rem 0.6rem;
    border-radius: 999px;
    font-weight: 700;
```

```
    font-size: 0.7rem;
    border: 1px solid transparent;
}
.priority-low { background: var(--bg-raised); color: var(--text-secondary); border-color: var(--border); }
.priority-medium { background: var(--accent-soft); color: var(--accent); border-color: rgba(245,176,66,0.3); }
.priority-high { background: var(--danger-soft); color: var(--danger); border-color: rgba(255,77,109,0.3); }
.status-open { background: var(--primary-soft); color: var(--primary); border-color: var(--border); }
.status-in_review { background: var(--bg-raised); color: var(--text-secondary); border-color: var(--border); }
.status-resolved { background: var(--success-soft); color: var(--success); border-color: rgba(0,201,139,0.3); }
.status-closed { background: var(--bg-raised); color: var(--text-muted); border-color: var(--border); }
.detail-body {
    background: var(--bg-card);
    border: 1px solid var(--border);
    border-radius: var(--radius-lg);
    padding: 1.2rem 1.4rem;
    box-shadow: var(--shadow-sm);
}
.detail-body h3 {
    margin: 0 0 0.5rem 0;
}
.detail-body p {
    margin: 0 0 0.8rem 0;
    color: var(--text-secondary);
    font-size: 0.9rem;
    line-height: 1.6;
}
.assigned {
    font-size: 0.85rem;
    color: var(--text-muted);
}
@media (max-width: 700px) {
    .detail-head {
        flex-direction: column;
        text-align: left;
    }
    .detail-meta {
        text-align: left;
    }
}
</style>
@endsection
```

### File: resources\views\store\chat_list.blade.php

```
@extends('store.registration-layout')

@section('title', 'Customer Chats')

@section('content')
<div class="container-fluid">
    <!-- Header -->
    <div class="d-flex justify-content-between align-items-center mb-4">
        <div>
            <h1 class="h3 mb-0">Customer Chats</h1>
            <p class="text-muted mt-2">Communicate with your customers about their inquiries</p>
        </div>
        <div class="d-flex gap-2">
            <span class="badge bg-danger p-3">
                <i class="bi bi-envelope-paper-fill me-2"></i>
                {{ $unread_total ?? 0 }} Unread
            </span>
        </div>
    </div>

    <!-- Filters -->
    <div class="card border-0 shadow-sm mb-4">
        <div class="card-body">
            <form method="GET" class="row g-3">
                <div class="col-md-6">
                    <div class="input-group">
                        <span class="input-group-text bg-transparent border-end-0">
                            <i class="bi bi-search"></i>
                        </span>
                        <input type="text"
                               name="search"
                               class="form-control border-start-0 ps-0"
                               placeholder="Search by customer name or subject..."
                               value="{{ $search ?? '' }}">
                    </div>
                </div>
                <div class="col-md-4">
                    <select name="book_id" class="form-select">
                        <option value="">All Books</option>
                        @foreach($books as $book)
                            <option value="{{ $book->id }}" {{ $selected_book == $book->id ? 'selected' : '' }}>
                                {{ $book->title }}
                            </option>
                        @endforeach
                    </select>
                </div>
                <div class="col-md-2">
                    <button type="submit" class="btn btn-primary w-100">
                        <i class="bi bi-funnel me-2"></i>Filter
                    </button>
                </div>
            </form>
        </div>
    </div>

    <!-- Conversations List -->
    @if($conversations->count() > 0)
        <div class="row g-4">
            @foreach($conversations as $conv)
                <div class="col-12">
                    <a href="{{ route('store.chat.show', $conv) }}" class="text-decoration-none">
                        <div class="card border-0 shadow-sm hover-shadow {{ $conv->unread_count > 0 ? 'bg-light' : '' }}">
                            <div class="card-body">
                                <div class="d-flex align-items-start gap-3">
                                    <!-- Avatar -->
                                    <div class="flex-shrink-0">
                                        <div class="avatar-circle bg-primary text-white">
                                            {{ substr($conv->customer->name ?? 'C', 0, 1) }}
                                        </div>
                                    </div>

                                    <!-- Content -->
                                    <div class="flex-grow-1">
                                        <div class="d-flex justify-content-between align-items-center mb-2">
                                            <div>
                                                <h5 class="mb-1 fw-bold">
                                                    {{ $conv->customer->name ?? 'Customer' }}
                                                    @if($conv->unread_count > 0)
                                                        <span class="badge bg-danger ms-2">{{ $conv->unread_count }} new</span>
                                                    @endif
                                                </h5>
```

```
                                                    <p class="small text-muted mb-0">
                                                        <i class="bi bi-envelope me-1"></i>
                                                        {{ $conv->customer->email ?? 'No email' }}
                                                    </p>
                                                </div>
                                                <div class="text-end">
                                                    <small class="text-muted">
                                                        {{ $conv->last_message_at?->diffForHumans() ?? $conv->created_at->diffForHumans() }}
                                                    </small>
                                                </div>
                                            </div>

                                            @if($conv->book)
                                                <div class="mb-2">
                                                    <span class="badge bg-info">
                                                        <i class="bi bi-book me-1"></i>
                                                        {{ $conv->book->title }}
                                                    </span>
                                                </div>
                                            @endif

                                            @if($conv->subject)
                                                <p class="fw-semibold mb-1">{{ $conv->subject }}</p>
                                            @endif

                                            <p class="mb-0 text-muted">
                                                <i class="bi bi-chat-dots me-1"></i>
                                                {{ $conv->last_message ?? 'No messages yet' }}
                                            </p>
                                        </div>
                                    </div>
                                </div>
                            </div>
                        </a>
                    </div>
                @endforeach
            </div>
        @else
            <div class="card border-0 shadow-sm">
                <div class="card-body text-center py-5">
                    <div class="py-5">
                        <i class="bi bi-chat-dots display-1 text-muted"></i>
                        <h3 class="mt-3">No Conversations Yet</h3>
                        <p class="text-muted">When customers start conversations, they'll appear here.</p>
                    </div>
                </div>
            </div>
        @endif
    </div>

    <style>
    .avatar-circle {
        width: 50px;
        height: 50px;
        border-radius: 50%;
        display: flex;
        align-items: center;
        justify-content: center;
        font-weight: 600;
        font-size: 1.2rem;
    }
    .hover-shadow {
        transition: all 0.3s ease;
    }
    .hover-shadow:hover {
        transform: translateY(-2px);
        box-shadow: 0 0.5rem 1rem rgba(0,0,0,0.15) !important;
    }
    </style>
    @endsection
```

### File: resources\views\store\chat_room.blade.php

```
@extends('store.registration-layout')

@section('title', 'Chat with ' . ($conversation->customer->name ?? 'Customer'))

@section('content')
<div class="container-fluid">
    <!-- Back Button -->
    <div class="mb-3">
        <a href="{{ route('store.chat.index') }}" class="btn btn-outline-secondary">
            <i class="bi bi-arrow-left me-2"></i>Back to Chats
        </a>
    </div>

    <!-- Chat Room -->
    <div class="row">
        <!-- Main Chat Area -->
        <div class="col-lg-8">
            <div class="card border-0 shadow-sm">
                <!-- Chat Header -->
                <div class="card-header bg-white py-3 d-flex justify-content-between align-items-center">
                    <div class="d-flex align-items-center gap-3">
                        <div class="avatar-circle bg-primary text-white">
                            {{ substr($conversation->customer->name ?? 'C', 0, 1) }}
                        </div>
                        <div>
                            <h5 class="mb-1">{{ $conversation->customer->name ?? 'Customer' }}</h5>
                            <p class="small text-muted mb-0">
                                <i class="bi bi-envelope me-1"></i>
                                {{ $conversation->customer->email ?? 'No email' }}
                            </p>
                        </div>
                    </div>
                    <div>
                        @if($conversation->book)
                            <span class="badge bg-info">
                                <i class="bi bi-book me-1"></i>
                                {{ $conversation->book->title }}
                            </span>
                        @endif
                    </div>
                </div>

                <!-- Messages -->
                <div class="card-body" id="messages-container" style="height: 500px; overflow-y: auto;">
                    @foreach($messages as $message)
                        <div class="message-item mb-3 {{ $message->sender_id === auth()->id() ? 'text-end' : '' }}">
                            <div class="d-inline-block" style="max-width: 70%;">
                                <div class="message-bubble p-3 rounded-3 {{ $message->sender_id === auth()->id() ? 'bg-primary text-white' : 'bg-light' }}">
                                    @if($message->message)
                                        <p class="mb-1">{{ $message->message }}</p>
                                    @endif
                                    @if($message->hasAttachment())
```

```
                                <div class="attachment-preview mt-2 p-2 {{ $message->sender_id === auth()->id() ? 'bg-primary bg-opacity-25' : 'bg-white' }} rounded-2'
                                    @if($message->isImage())
                                        <img src="{{ $message->attachment_url }}"
                                             alt="Attachment"
                                             class="img-fluid rounded-2 mb-2"
                                             style="max-height: 150px; cursor: pointer;"
                                             onclick="window.open('{{ $message->attachment_url }}', '_blank')">
                                    @endif
                                    <div class="d-flex align-items-center gap-2">
                                        <i class="bi {{ $message->isImage() ? 'bi-image' : 'bi-file-earmark' }}"></i>
                                        <small class="text-truncate" style="max-width: 200px;">
                                            {{ $message->attachment_name }}
                                        </small>
                                        <a href="{{ $message->attachment_url }}"
                                           class="{{ $message->sender_id === auth()->id() ? 'text-white' : 'text-primary' }}"
                                           target="_blank"
                                           download>
                                            <i class="bi bi-download"></i>
                                        </a>
                                    </div>
                                </div>
                            @endif

                            <small class="d-block mt-2 {{ $message->sender_id === auth()->id() ? 'text-white-50' : 'text-muted' }}">
                                {{ $message->created_at->format('g:i A') }}
                                @if($message->sender_id === auth()->id())
                                    @if($message->is_read)
                                        <i class="bi bi-check2-all ms-1" title="Read"></i>
                                    @else
                                        <i class="bi bi-check2 ms-1" title="Sent"></i>
                                    @endif
                                @endif
                            </small>
                        </div>
                    </div>
                </div>
            @endforeach
        </div>

        <!-- Message Input -->
        <div class="card-footer bg-white py-3">
            <form id="message-form" enctype="multipart/form-data" class="d-flex gap-2">
                @csrf
                <div class="flex-grow-1">
                    <textarea name="message"
                              id="message-input"
                              class="form-control"
                              rows="2"
                              placeholder="Type your message..."
                              style="resize: none;"></textarea>
                </div>
                <div class="d-flex flex-column gap-2">
                    <div class="dropdown">
                        <button class="btn btn-outline-secondary" type="button" data-bs-toggle="dropdown">
                            <i class="bi bi-paperclip"></i>
                        </button>
                        <div class="dropdown-menu p-3" style="min-width: 300px;">
                            <input type="file"
                                   id="attachment-input"
                                   name="attachment"
                                   class="form-control"
                                   accept="image/*,.pdf,.doc,.docx,.txt">
                            <div class="form-text mt-2">
                                Max size: 10MB
                            </div>
                        </div>
                    </div>
                    <button type="submit" class="btn btn-primary" id="send-btn">
                        <i class="bi bi-send-fill"></i>
                    </button>
                </div>
            </form>
            <div id="attachment-preview" class="mt-2" style="display: none;">
                <div class="alert alert-info d-flex align-items-center justify-content-between py-2">
                    <span id="attachment-name"></span>
                    <button type="button" class="btn-close" onclick="clearAttachment()"></button>
                </div>
            </div>
        </div>
    </div>
</div>

<!-- Conversation Info -->
<div class="col-lg-4">
    <div class="card border-0 shadow-sm">
        <div class="card-header bg-white py-3">
            <h5 class="mb-0">Conversation Info</h5>
        </div>
        <div class="card-body">
            <p class="small text-muted mb-2">
                <i class="bi bi-calendar3 me-2"></i>
                Started: {{ $conversation->created_at->format('M d, Y g:i A') }}
            </p>

            @if($conversation->last_message_at)
                <p class="small text-muted mb-3">
                    <i class="bi bi-clock-history me-2"></i>
                    Last activity: {{ $conversation->last_message_at->diffForHumans() }}
                </p>
            @endif

            <hr>

            <h6 class="fw-bold mb-2">Customer Details</h6>
            <p class="small mb-1">
                <strong>Name:</strong> {{ $conversation->customer->name ?? 'N/A' }}
            </p>
            <p class="small mb-1">
                <strong>Email:</strong> {{ $conversation->customer->email ?? 'N/A' }}
            </p>
            <p class="small mb-1">
                <strong>Joined:</strong> {{ $conversation->customer->created_at?->format('M d, Y') ?? 'N/A' }}
            </p>

            @if($conversation->book)
                <hr>
                <h6 class="fw-bold mb-2">Book Reference</h6>
                <p class="small mb-1">
                    <strong>Title:</strong> {{ $conversation->book->title }}
                </p>
                <p class="small mb-1">
                    <strong>Author:</strong> {{ $conversation->book->author }}
                </p>
                <a href="#" class="btn btn-sm btn-outline-primary mt-2">
                    <i class="bi bi-book me-1"></i>View Book
                </a>
            @endif
            <hr>
```

```
                    <form action="{{ route('store.chat.destroy', $conversation) }}"
                          method="POST"
                          onsubmit="return confirm('Are you sure you want to delete this conversation?')">
                        @csrf
                        @method('DELETE')
                        <button type="submit" class="btn btn-outline-danger w-100">
                            <i class="bi bi-trash me-2"></i>Delete Conversation
                        </button>
                    </form>
                </div>
            </div>
        </div>
    </div>
</div>

<style>
.avatar-circle {
    width: 40px;
    height: 40px;
    border-radius: 50%;
    display: flex;
    align-items: center;
    justify-content: center;
    font-weight: 600;
    font-size: 1rem;
}
.message-bubble {
    word-wrap: break-word;
    box-shadow: 0 2px 5px rgba(0,0,0,0.1);
}
.bg-primary .text-white-50 {
    color: rgba(255,255,255,0.7) !important;
}
.attachment-preview {
    border: 1px solid rgba(0,0,0,0.1);
}
#messages-container {
    scroll-behavior: smooth;
}
</style>

<script>
document.addEventListener('DOMContentLoaded', function() {
    const conversationId = {{ $conversation->id }};
    const messagesContainer = document.getElementById('messages-container');
    const messageForm = document.getElementById('message-form');
    const messageInput = document.getElementById('message-input');
    const sendBtn = document.getElementById('send-btn');
    const attachmentInput = document.getElementById('attachment-input');
    const attachmentPreview = document.getElementById('attachment-preview');
    const attachmentName = document.getElementById('attachment-name');

    let lastMessageId = {{ $messages->last()->id ?? 0 }};
    let pollingInterval;

    // Scroll to bottom on load
    scrollToBottom();

    // Auto-resize textarea
    messageInput.addEventListener('input', function() {
        this.style.height = 'auto';
        this.style.height = (this.scrollHeight) + 'px';
    });

    // Handle file selection
    attachmentInput.addEventListener('change', function() {
        if (this.files.length > 0) {
            const file = this.files[0];
            attachmentName.textContent = file.name + ' (' + (file.size / 1024).toFixed(1) + ' KB)';
            attachmentPreview.style.display = 'block';
        } else {
            clearAttachment();
        }
    });

    // Handle form submission
    messageForm.addEventListener('submit', async function(e) {
        e.preventDefault();

        const formData = new FormData();
        const message = messageInput.value.trim();
        const attachment = attachmentInput.files[0];

        if (!message && !attachment) {
            return;
        }

        if (message) {
            formData.append('message', message);
        }

        if (attachment) {
            formData.append('attachment', attachment);
        }

        // Disable form
        setFormDisabled(true);

        try {
            const response = await fetch(`/store/chat/${conversationId}/send`, {
                method: 'POST',
                headers: {
                    'X-CSRF-TOKEN': document.querySelector('input[name="_token"]').value,
                    'X-Requested-With': 'XMLHttpRequest'
                },
                body: formData
            });

            const data = await response.json();

            if (data.success) {
                // Clear form
                messageInput.value = '';
                messageInput.style.height = 'auto';
                clearAttachment();

                // Append new message
                appendMessage(data.message);
                scrollToBottom();
            } else {
                alert('Failed to send message: ' + data.error);
            }
        } catch (error) {
            console.error('Error:', error);
            alert('Failed to send message');
        } finally {
            setFormDisabled(false);
        }
```

```
    });

    // Poll for new messages
    function startPolling() {
        pollingInterval = setInterval(pollMessages, 3000);
    }

    async function pollMessages() {
        try {
            const response = await fetch(`/store/chat/${conversationId}/poll?last_id=${lastMessageId}`);
            const data = await response.json();

            if (data.success && data.messages.length > 0) {
                data.messages.forEach(msg => {
                    appendMessage(msg);
                    lastMessageId = Math.max(lastMessageId, msg.id);
                });
                scrollToBottom();
            }
        } catch (error) {
            console.error('Polling error:', error);
        }
    }

    function appendMessage(message) {
        const messageDiv = docume
```

(Content truncated due to size - showing first 15KB)

## File: resources\views\store\dashboard.blade.php

```
<!DOCTYPE html>
<html lang="en" data-bs-theme="light">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>BookTracker | Store Dashboard</title>
    <!-- Bootstrap 5 CSS -->
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0-alpha1/dist/css/bootstrap.min.css" rel="stylesheet">
    <!-- Bootstrap Icons -->
    <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.10.3/font/bootstrap-icons.css">
    <!-- Google Fonts -->
    <link href="https://fonts.googleapis.com/css2?family=Poppins:wght@300;400;500;600;700&display=swap" rel="stylesheet">
    <style>
        :root {
            --primary-color: #4e73df;
            --primary-dark: #3a56c4;
            --secondary-color: #858796;
            --success-color: #1cc88a;
            --info-color: #36b9cc;
            --warning-color: #f6c23e;
            --danger-color: #e74a3b;
            --light-color: #f8f9fc;
            --dark-color: #5a5c69;
            --sidebar-width: 250px;
            --sidebar-collapsed-width: 80px;
            --transition-speed: 0.3s;
            --book-color: #4361ee;
            --read-color: #1cc88a;
            --reading-color: #f6c23e;
            --toread-color: #e74a3b;
        }

        * {
            margin: 0;
            padding: 0;
            box-sizing: border-box;
        }

        body {
            font-family: 'Poppins', sans-serif;
            background-color: #f8f9fc;
            color: #333;
            overflow-x: hidden;
            min-height: 100vh;
            padding-top: 70px;
        }

        /* Navbar Styling */
        .navbar {
            background-color: white;
            box-shadow: 0 0.15rem 1.75rem 0 rgba(58, 59, 69, 0.15);
            padding: 0.75rem 0;
            position: fixed;
            top: 0;
            right: 0;
            left: 0;
            z-index: 1030;
            transition: all var(--transition-speed) ease;
            height: 70px;
        }

        .navbar-brand {
            font-weight: 700;
            font-size: 1.5rem;
            color: var(--book-color);
            display: flex;
            align-items: center;
        }

        .nav-user-img {
            width: 40px;
            height: 40px;
            border-radius: 50%;
            object-fit: cover;
            border: 2px solid #e3e6f0;
        }

        /* Sidebar Styling */
        #sidebar {
            width: var(--sidebar-width);
            background-color: white;
            color: #858796;
            position: fixed;
            top: 70px;
            left: 0;
            height: calc(100vh - 70px);
            z-index: 1000;
            box-shadow: 0 0.15rem 1.75rem 0 rgba(58, 59, 69, 0.15);
            transition: all var(--transition-speed) ease;
            overflow-y: auto;
            display: flex;
            flex-direction: column;
        }
        .sidebar-heading {
```

```
    padding: 1.5rem 1rem 0.5rem;
    font-size: 0.8rem;
    text-transform: uppercase;
    color: #b7b9cc;
    font-weight: 700;
    letter-spacing: 0.5px;
}

.sidebar-item {
    padding: 0.75rem 1rem;
    display: flex;
    align-items: center;
    color: #3a3b45;
    text-decoration: none;
    border-left: 3px solid transparent;
    transition: all 0.2s;
    white-space: nowrap;
}

.sidebar-item:hover,
.sidebar-item.active {
    color: var(--book-color);
    background-color: #f8f9fc;
    border-left-color: var(--book-color);
}

.sidebar-item i {
    margin-right: 10px;
    width: 20px;
    text-align: center;
    font-size: 1.1rem;
}

.sidebar-item span {
    transition: opacity var(--transition-speed);
}

/* Logout button in sidebar */
.sidebar-item.logout-btn {
    margin-top: auto;
    border-top: 1px solid #e3e6f0;
    padding: 0.75rem 1rem;
    display: flex;
    align-items: center;
    color: #3a3b45;
    text-decoration: none;
    border-left: 3px solid transparent;
    transition: all 0.2s;
    white-space: nowrap;
    width: 100%;
    background: none;
    border: none;
    cursor: pointer;
    text-align: left;
}

.sidebar-item.logout-btn:hover {
    color: var(--book-color);
    background-color: #f8f9fc;
    border-left-color: var(--book-color);
}

/* Main Content Area */
#content {
    margin-left: var(--sidebar-width);
    padding: 20px;
    min-height: calc(100vh - 70px);
    transition: all var(--transition-speed) ease;
}

/* Cards */
.dashboard-card {
    border-radius: 10px;
    border: none;
    box-shadow: 0 0.15rem 1.75rem 0 rgba(58, 59, 69, 0.1);
    transition: all 0.3s;
    overflow: hidden;
    height: 100%;
}

.dashboard-card:hover {
    transform: translateY(-5px);
    box-shadow: 0 0.5rem 2rem 0 rgba(58, 59, 69, 0.2);
}

.card-icon {
    font-size: 2.5rem;
    opacity: 0.8;
}

.border-left-book {
    border-left: 4px solid var(--book-color) !important;
}

.border-left-revenue {
    border-left: 4px solid var(--success-color) !important;
}

.border-left-rental {
    border-left: 4px solid var(--warning-color) !important;
}

.border-left-delivery {
    border-left: 4px solid var(--danger-color) !important;
}

/* Store Stats Cards */
.store-stat-card {
    border-radius: 8px;
    padding: 15px;
    margin-bottom: 15px;
    background: linear-gradient(135deg, #667eea 0%, #764ba2 100%);
    color: white;
    position: relative;
    overflow: hidden;
}

.store-stat-card::before {
    content: '';
    position: absolute;
    top: 0;
    left: 0;
    right: 0;
    bottom: 0;
    background: rgba(255, 255, 255, 0.1);
}

.store-stat-card.revenue {
```

```
    background: linear-gradient(135deg, #f093fb 0%, #f5576c 100%);
}

.store-stat-card.books {
    background: linear-gradient(135deg, #4facfe 0%, #00f2fe 100%);
}

.store-stat-card.rentals {
    background: linear-gradient(135deg, #43e97b 0%, #38f9d7 100%);
}

.store-stat-card.deliveries {
    background: linear-gradient(135deg, #fa709a 0%, #fee140 100%);
}

.store-stat-card.customers {
    background: linear-gradient(135deg, #a8edea 0%, #fed6e3 100%);
    color: #333;
}

.store-stat-card.owner {
    background: linear-gradient(135deg, #3a506b 0%, #1c2541 100%);
}

.store-stat-card.pending {
    background: linear-gradient(135deg, #f6d365 0%, #fda085 100%);
}

.store-stat-card.active {
    background: linear-gradient(135deg, #667eea 0%, #764ba2 100%);
}

.store-stat-card.completed {
    background: linear-gradient(135deg, #2af598 0%, #009efd 100%);
}

.store-stat-card.declined {
    background: linear-gradient(135deg, #ff758c 0%, #ff7eb3 100%);
}

.store-stat-card.today {
    background: linear-gradient(135deg, #4facfe 0%, #00f2fe 100%);
}

.store-stat-card.month {
    background: linear-gradient(135deg, #43e97b 0%, #38f9d7 100%);
}

/* Recent Orders Styling */
.order-card {
    border: 1px solid #e3e6f0;
    border-radius: 8px;
    margin-bottom: 15px;
    padding: 15px;
    transition: all 0.3s;
    background: white;
}

.order-card:hover {
    box-shadow: 0 4px 12px rgba(0, 0, 0, 0.1);
    transform: translateY(-2px);
}

.order-header {
    display: flex;
    justify-content: space-between;
    align-items: center;
    margin-bottom: 10px;
    padding-bottom: 10px;
    border-bottom: 1px dashed #e3e6f0;
}

.order-actions {
    display: flex;
    gap: 10px;
    margin-top: 15px;
}

/* Inventory Alerts */
.alert-card {
    border-left: 4px solid #f6c23e;
    background-color: #fff9e6;
    border-radius: 8px;
    padding: 15px;
    margin-bottom: 15px;
}

.alert-card.danger {
    border-left-color: #e74a3b;
    background-color: #ffeaea;
}

/* Quick Actions Grid */
.quick-actions-grid {
    display: grid;
    grid-template-columns: repeat(auto-fit, minmax(200px, 1fr));
    gap: 15px;
    margin-top: 20px;
}

.quick-action-btn {
    padding: 20px;
    border-radius: 10px;
    display: flex;
    flex-direction: column;
    align-items: center;
    justify-content: center;
    text-align: center;
    background: white;
    border: 2px solid #e3e6f0;
    transition: all 0.3s;
    cursor: pointer;
}

.quick-action-btn:hover {
    transform: translateY(-5px);
    box-shadow: 0 10px 20px rgba(0, 0, 0, 0.1);
    border-color: var(--book-color);
}

/* Dark Mode Styles */
body[data-bs-theme="dark"] {
    background-color: #12151e;
    color: #adb5bd;
}

body[data-bs-theme="dark"] .navbar {
    background-color: #1a1d28;
```

```
    box-shadow: 0 0.15rem 1.75rem 0 rgba(0, 0, 0, 0.3);
}

body[data-bs-theme="dark"] #sidebar {
    background-color: #1a1d28;
    box-shadow: 0 0.15rem 1.75rem 0 rgba(0, 0, 0, 0.3);
}

body[data-bs-theme="dark"] .dashboard-card {
    background-color: #1a1d28;
    box-shadow: 0 0.15rem 1.75rem 0 rgba(0, 0, 0, 0.3);
}

body[data-bs-theme="dark"] .sidebar-item {
    color: #adb5bd;
}

body[data-bs-theme="dark"] .sidebar-item:hover,
body[data-bs-theme="dark"] .sidebar-item.active {
    background-color: #12151e;
    color: var(--book-color);
}

body[data-bs-theme="dark"] .sidebar-item.logout-btn {
    border-top-color: #2a2d38;
    color: #adb5bd;
}

body[data-bs-theme="dark"] .sidebar-item.logout-btn:hover {
    background-color: #12151e;
    color: var(--book-color);
}

body[data-bs-theme="dark"] .table {
    color: #adb5bd;
}

body[data-bs-theme="dark"] .table-hover tbody tr:hover {
    background-color: rgba(255, 255, 255, 0.05);
}

/* Quick Action Buttons */
.quick-action-btn {
    padding: 15px;
    border-radius: 8px;
    display: flex;
    flex-direction: column;
    align-items: center;
    justify-content: center;
    text-align: center;
    height: 100%;
    transition: all 0.3s;
}

.quick-action-btn:hover {
    transform: translateY(-5px);
}

/* Status Badges */
.badge-read {
    background-color: var(--read-color);
}

.badge-reading {
    background-color: var(--reading-color);
}

.badge-toread {
    background-color: var(--toread-color);
}

/* Activity Timeline */
.timeline {
    position: relative;
    padding-left: 30px;
}

.timeline-item {
    position: relative;
    margin-bottom: 20px;
}

.timeline-marker {
    position: absolute;
    left: -30px;
    top: 0;
    width: 20px;
    height: 20px;
    border-radius: 50%;
    display: flex;
    align-items: center;
    justify-content: center;
    color: white;
    font-size: 0.8rem;
}

.timeline-content {
    padding: 10px 15px;
    background-color: rgba(78, 115, 223, 0.05);
    border-radius: 8px;
    border-left: 3px solid var(--book-color);
}

/* Responsive Adjustments */
@media (max-width: 768px) {
    #sidebar {
        transform: translateX(-100%);
        width: 280px;
    }

    #content {
        margin-left: 0;
    }

    .sidebar-open #sidebar {
        transform: translateX(0);
    }

    .sidebar-open::after {
        content: '';
        position: fixed;
        top: 0;
        left: 0;
        right: 0;
        bottom: 0;
        background-color: rgba(0, 0, 0, 0.5);
        z-index: 999;
    }
```

```
    .quick-actions-grid {
        grid-template-columns: 1fr;
    }
}

/* Animations */
.fade-in {
    animation: fadeIn 0.5s ease-in-out;
}

@keyframes fadeIn {
    from {
        opacity: 0;
        transform: translateY(20px);
    }

    to {
        opacity: 1;
        transform: translateY(0);
    }
}

/* Scrollbar Styling */
#sidebar::-webkit-scrollbar {
    width: 5px;
}

#sidebar::-webkit-scrollbar-track {
    background: #f1f1f1;
}

#sidebar::-webkit-scrollbar-thumb {
    background: #c1c1c1;
    border-radius: 10px;
}

#sidebar::-webkit-scrollbar-thumb:hover {
    background: #a8a8a8;
}

body[data-bs-theme="dark"] #sidebar::-webkit-scrollbar-track {
    background: #2a2d38;
}

body[data-bs-theme="dark"] #sidebar::-webkit-scrollbar-thumb {
    background: #4a4d58;
}

body[data-bs-theme="dark"] #sidebar::-webkit-scrollbar-thumb:hover {
    background: #5a5d68;
}

/* Badge Notification */
.notification-badge {
    position: absolute;
    top: -5px;
    right: -5px;
    padding: 0.25em 0.6em;
    font-size: 0.75rem;
}

/* Dropdown Menu */
.dropdown-menu {
    border: none;
    box-shadow: 0 0.15rem 1.75rem 0 rgb
```

(Content truncated due to size - showing first 15KB)

### File: resources\views\store\orders.blade.php

```
@extends('store.registration-layout')

@section('title', 'Order Management')

@section('content')
    <div class="container-fluid">
        <div class="d-flex align-items-center justify-content-between mb-3">
            <h1 class="h3 mb-0">Order Management</h1>
            <span class="text-muted">Review and manage store orders.</span>
        </div>

        <div class="card border-0 shadow-sm">
            <div class="card-body">
                <div class="text-muted">No orders to display yet.</div>
            </div>
        </div>
    </div>
@endsection
```

### File: resources\views\store\registration-layout.blade.php

```
<!DOCTYPE html>
<html lang="en" data-bs-theme="light">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>@yield('title', 'Book Collection Tracker')</title>

    <!-- Bootstrap 5 CSS -->
    <link href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0/dist/css/bootstrap.min.css" rel="stylesheet">
    <!-- Bootstrap Icons -->
    <link rel="stylesheet" href="https://cdn.jsdelivr.net/npm/bootstrap-icons@1.10.3/font/bootstrap-icons.css">
    <!-- Font Awesome -->
    <link rel="stylesheet" href="https://cdnjs.cloudflare.com/ajax/libs/font-awesome/6.4.0/css/all.min.css">
    <!-- Google Fonts -->
    <link href="https://fonts.googleapis.com/css2?family=Poppins:wght@300;400;500;600;700&display=swap" rel="stylesheet">

    <style>
        :root {
            --primary-color: #4e73df;
            --primary-dark: #3a56c4;
            --secondary-color: #858796;
            --success-color: #1cc88a;
            --info-color: #36b9cc;
            --warning-color: #f6c23e;
            --danger-color: #e74a3b;
            --light-color: #f8f9fc;
            --dark-color: #5a5c69;
            --sidebar-width: 250px;
            --transition-speed: 0.3s;
            --brand-color: #4361ee;
        }

        * {
            margin: 0;
            padding: 0;
            box-sizing: border-box;
        }

        body {
            font-family: 'Poppins', sans-serif;
            background-color: #f8f9fc;
            color: #333;
            overflow-x: hidden;
            min-height: 100vh;
            padding-top: 70px;
        }

        .navbar {
            background-color: white;
            box-shadow: 0 0.15rem 1.75rem 0 rgba(58, 59, 69, 0.15);
            padding: 0.75rem 0;
            position: fixed;
            top: 0;
            right: 0;
            left: 0;
            z-index: 1030;
            transition: all var(--transition-speed) ease;
            height: 70px;
        }

        .navbar-brand {
            font-weight: 700;
            font-size: 1.3rem;
            color: var(--brand-color);
            display: flex;
            align-items: center;
        }

        .nav-user-img {
            width: 40px;
            height: 40px;
            border-radius: 50%;
            object-fit: cover;
            border: 2px solid #e3e6f0;
        }

        #sidebar {
            width: var(--sidebar-width);
            background-color: white;
            color: #858796;
            position: fixed;
            top: 70px;
            left: 0;
            height: calc(100vh - 70px);
            z-index: 1000;
            box-shadow: 0 0.15rem 1.75rem 0 rgba(58, 59, 69, 0.15);
            transition: all var(--transition-speed) ease;
            overflow-y: auto;
            display: flex;
            flex-direction: column;
        }

        .sidebar-heading {
            padding: 1.5rem 1rem 0.5rem;
            font-size: 0.8rem;
            text-transform: uppercase;
            color: #b7b9cc;
            font-weight: 700;
            letter-spacing: 0.5px;
        }

        .sidebar-item {
```

```
    padding: 0.75rem 1rem;
    display: flex;
    align-items: center;
    color: #3a3b45;
    text-decoration: none;
    border-left: 3px solid transparent;
    transition: all 0.2s;
    white-space: nowrap;
}

.sidebar-item:hover,
.sidebar-item.active {
    color: var(--brand-color);
    background-color: #f8f9fc;
    border-left-color: var(--brand-color);
}

.sidebar-item i {
    margin-right: 10px;
    width: 20px;
    text-align: center;
    font-size: 1.1rem;
}

.sidebar-item.logout-bottom {
    margin-top: auto;
    border-top: 1px solid #e3e6f0;
}

.main-content {
    margin-left: var(--sidebar-width);
    padding: 20px;
    min-height: calc(100vh - 70px);
    transition: all var(--transition-speed) ease;
}

.header-nav-item {
    display: flex;
    align-items: center;
    gap: 8px;
    padding: 8px 16px;
    border-radius: 20px;
    background: #f8f9fc;
    color: #5a5c69;
    text-decoration: none;
    transition: all 0.3s;
    font-weight: 500;
    margin-right: 10px;
}

.header-nav-item:hover,
.header-nav-item.active {
    background: var(--brand-color);
    color: white;
}

.notification-badge {
    position: absolute;
    top: -5px;
    right: -5px;
    padding: 0.25em 0.6em;
    font-size: 0.75rem;
}

.dropdown-menu {
    border: none;
    box-shadow: 0 0.15rem 1.75rem 0 rgba(58, 59, 69, 0.2);
    border-radius: 10px;
}

@media (max-width: 768px) {
    #sidebar {
        transform: translateX(-100%);
        width: 280px;
    }

    .main-content {
        margin-left: 0;
    }

    .sidebar-open #sidebar {
        transform: translateX(0);
    }

    .sidebar-open::after {
        content: '';
        position: fixed;
        top: 0;
        left: 0;
        right: 0;
        bottom: 0;
        background-color: rgba(0, 0, 0, 0.5);
        z-index: 999;
    }
}

body[data-bs-theme="dark"] {
    background-color: #12151e;
    color: #adb5bd;
}

body[data-bs-theme="dark"] .navbar {
    background-color: #1a1d28;
    box-shadow: 0 0.15rem 1.75rem 0 rgba(0, 0, 0, 0.3);
}

body[data-bs-theme="dark"] #sidebar {
    background-color: #1a1d28;
    box-shadow: 0 0.15rem 1.75rem 0 rgba(0, 0, 0, 0.3);
}

body[data-bs-theme="dark"] .sidebar-item {
    color: #adb5bd;
}

body[data-bs-theme="dark"] .sidebar-item:hover,
body[data-bs-theme="dark"] .sidebar-item.active {
    background-color: #12151e;
    color: var(--brand-color);
}

body[data-bs-theme="dark"] .sidebar-item.logout-bottom {
    border-top-color: #2a2d38;
}

body[data-bs-theme="dark"] .dropdown-menu {
    background-color: #1a1d28;
}
```

```
        body[data-bs-theme="dark"] .dropdown-item {
            color: #adb5bd;
        }

        body[data-bs-theme="dark"] .dropdown-item:hover {
            background-color: #12151e;
            color: var(--brand-color);
        }

        #sidebar::-webkit-scrollbar {
            width: 5px;
        }

        #sidebar::-webkit-scrollbar-track {
            background: #f1f1f1;
        }

        #sidebar::-webkit-scrollbar-thumb {
            background: #c1c1c1;
            border-radius: 10px;
        }

        #sidebar::-webkit-scrollbar-thumb:hover {
            background: #a8a8a8;
        }
    </style>

    @yield('extra_css')
</head>
<body>
    <nav class="navbar navbar-expand-lg">
        <div class="container-fluid px-4">
            <button class="btn btn-link text-dark me-3 d-lg-none" id="sidebarToggle">
                <i class="bi bi-list" style="font-size: 1.5rem;"></i>
            </button>

            <a class="navbar-brand" href="{{ route('store.dashboard') }}">
                <i class="bi bi-shop me-2"></i>
                <span>My Book Store</span>
            </a>

            <div class="d-flex align-items-center ms-auto">
                <div class="me-4 d-none d-md-block">
                    <span class="text-muted">Welcome,</span>
                    <span class="fw-bold ms-1">{{ $accountOwner ?? (Auth::user()->name ?? Auth::user()->username) }}</span>
                </div>

                <div class="form-check form-switch me-4">
                    <input class="form-check-input" type="checkbox" id="darkModeToggle">
                    <label class="form-check-label" for="darkModeToggle">
                        <i class="bi bi-moon-fill"></i>
                    </label>
                </div>

                <div class="dropdown me-4">
                    <a href="#" class="text-dark position-relative" id="notificationDropdown" data-bs-toggle="dropdown">
                        <i class="bi bi-bell" style="font-size: 1.3rem;"></i>
                        <span class="position-absolute top-0 start-100 translate-middle badge rounded-pill bg-danger notification-badge">
                            {{ $pendingOrdersCount ?? 0 }}
                        </span>
                    </a>
                    <ul class="dropdown-menu dropdown-menu-end p-3" style="width: 300px;">
                        <li><h6 class="dropdown-header">Quick Alerts</h6></li>
                        <li>
                            <a class="dropdown-item" href="#">
                                <i class="bi bi-hourglass-split text-warning me-2"></i>
                                Pending Orders: {{ $pendingOrdersCount ?? 0 }}
                            </a>
                        </li>
                        <li>
                            <a class="dropdown-item" href="#">
                                <i class="bi bi-heart text-danger me-2"></i>
                                Wishlist Items: {{ $wishlistCount ?? 0 }}
                            </a>
                        </li>
                    </ul>
                </div>

                <div class="dropdown">
                    <a href="#" class="d-flex align-items-center text-dark text-decoration-none dropdown-toggle" id="userDropdown" data-bs-toggle="dropdown">
                        <img src="https://ui-avatars.com/api/?name=John+Doe&background=4361ee&color=fff&size=128" alt="User" class="nav-user-img me-2">
                        <span class="d-none d-md-inline">{{ $currentDisplayName ?? ($accountOwner ?? Auth::user()->username) }}</span>
                    </a>
                     <ul class="dropdown-menu dropdown-menu-end">
        <!-- ■ FIXED: profile.edit instead of profile -->
        <li>
            <a class="dropdown-item" href="{{ route('profile.edit') }}">
                <i class="bi bi-person me-2"></i>Profile
            </a>
        </li>
        <li><hr class="dropdown-divider"></li>
        <!-- ■ Logout is correct - route name 'logout' exists in auth.php -->
        <li>
            <form method="POST" action="{{ route('logout') }}" class="d-inline w-100">
                @csrf
                <button type="submit" class="dropdown-item logout-btn">
                    <i class="bi bi-box-arrow-right me-2"></i>Logout
                </button>
            </form>
        </li>
    </ul>
                </div>
            </div>
        </div>
    </nav>

    <div id="sidebar">
        <div class="sidebar-heading">Order Management</div>
        <a href="{{ route('store.dashboard') }}" class="sidebar-item @if(request()->routeIs('store.dashboard')) active @endif">
            <i class="bi bi-speedometer2"></i>
            <span>Dashboard</span>
        </a>
        <a href="#" class="sidebar-item @if(request()->routeIs('store.orders')) active @endif">
            <i class="bi bi-receipt"></i>
            <span>Order Management</span>
            @if(!empty($pendingOrdersCount))
            <span class="badge bg-danger ms-auto">{{ $pendingOrdersCount }}</span>
            @endif
        </a>
        <a href="#" class="sidebar-item @if(request()->routeIs('store.wishlist')) active @endif">
            <i class="bi bi-heart"></i>
            <span>Wishlisted Books</span>
            <span class="badge bg-warning ms-auto">{{ $wishlistCount ?? 0 }}</span>
        </a>

        <div class="sidebar-heading">Messages Management</div>
        <a class="sidebar-item @if(request()->routeIs('store.chat.*')) active @endif"
           href="{{ route('store.chat.index') }}">
```

```
                <i class="bi bi-chat-dots me-2"></i>
                Customer Chats
                @if(!empty($totalUnread))
                <span class="badge bg-danger ms-auto">{{ $totalUnread }}</span>
                @endif
            </a>
            <a class="sidebar-item @if(request()->routeIs('store.issue-reports.*')) active @endif" href="{{ route('store.issue-reports.index') }}">
                <i class="bi bi-headset me-2"></i>
                Support Chats
            </a>
           <a class="sidebar-item @if(request()->routeIs('store.issue-reports.create')) active @endif" href="{{ route('store.issue-reports.create') }}">
                <i class="bi bi-flag me-2"></i>
                Report Customer
            </a>

            <div class="sidebar-heading">Store Management</div>
            <a href="{{ route('store.registration.create') }}" class="sidebar-item @if(request()->routeIs('store.registration.create')) active @endif">
                <i class="bi bi-cart"></i>
                <span>Register Store</span>
            </a>
            <a href="{{ route('store.registration.view') }}" class="sidebar-item @if(request()->routeIs('store.registration.view')) active @endif">
                <i class="bi bi-list"></i>
                <span>View Stores</span>
            </a>

            <div class="sidebar-heading">Book Management</div>
            <a href="{{ route('add.book.registration') }}" class="sidebar-item @if(request()->routeIs('add.book.registration')) active @endif">
                <i class="bi bi-plus-circle"></i>
                <span>Add Book</span>
            </a>
            <a href="{{ route('view.inventory') }}" class="sidebar-item @if(request()->routeIs('view.inventory')) active @endif">
                <i class="bi bi-archive"></i>
                <span>View Inventory</span>
                <span class="badge bg-success ms-auto">{{ $storeMetrics['total_books'] ?? 0 }}</span>
            </a>
            <a href="{{ route('manage.books') }}" class="sidebar-item @if(request()->routeIs('manage.books')) active @endif">
                <i class="bi bi-pencil-square"></i>
                <span>Manage Books</span>
            </a>

            <form method="POST" action="{{ route('logout') }}" class="sidebar-item logout-bottom">
                @csrf
                <button type="submit" class="btn btn-link p-0 text-decoration-none d-flex align-items-center w-100" style="color: inherit; border: none; background: none;">
                    <i class="bi bi-box-arrow-right"></i>
                    <span>Logout</span>
                </button>
            </form>
        </div>

        <div class="main-content">
            @yield('content')
        </div>

        <script src="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0/dist/js/bootstrap.bundle.min.js"></script>
        <script>
            const sidebarToggle = document.getElementById('sidebarToggle');
            const darkModeToggle = document.getElementById('darkModeToggle');
            const sidebar = document.getElementById('sidebar');
            const body
```

(Content truncated due to size - showing first 15KB)

## File: resources\views\store\registration-view.blade.php

```
@extends('store.registration-layout')
@section('title', 'Store Management')
@section('content')

<div class="container-fluid py-4">

    <!-- Header + Add Button -->
    <div class="d-flex justify-content-between align-items-center mb-4">
        <h4 class="mb-0 fw-semibold text-dark">Store Management</h4>
        <a href="{{ route('store.registration.create') }}" class="btn btn-primary btn-lg shadow-sm">
            <i class="fas fa-plus me-2"></i>Add New Store
        </a>
    </div>
    @if (session('status'))
        <div class="alert alert-success">{{ session('status') }}</div>
    @endif
    @if (session('error'))
        <div class="alert alert-danger">{{ session('error') }}</div>
    @endif

    <div class="card shadow border-0">
        <div class="card-body p-0">
            <div class="table-responsive">
                <table class="table table-hover table-bordered align-middle mb-0 small">
                    <thead class="bg-dark text-white text-center">
                        <tr>
                            <th class="py-3">ID</th>
                            <th class="py-3">Store Name</th>
                            <th class="py-3">Owner</th>
                            <th class="py-3">Email</th>
                            <th class="py-3">Phone</th>
                            <th class="py-3">Type</th>
                            <th class="py-3">City</th>
                            <th class="py-3">Sub City</th>
                            <th class="py-3">Address</th>
                            <th class="py-3">Description</th>

                            <!-- Services -->
                            <th class="py-3">Rental</th>
                            <th class="py-3">Sale</th>
                            <th class="py-3">Delivery</th>
                            <th class="py-3">Del. Fee</th>
                            <th class="py-3">Bike</th>
                            <th class="py-3">Car</th>
                            <th class="py-3">Pickup</th>

                            <!-- Working Days - grouped visually -->
                            <th colspan="4" class="bg-secondary text-white">Monday</th>
                            <th colspan="4" class="bg-secondary text-white">Tuesday</th>
                            <th colspan="4" class="bg-secondary text-white">Wednesday</th>
                            <th colspan="4" class="bg-secondary text-white">Thursday</th>
                            <th colspan="4" class="bg-secondary text-white">Friday</th>
                            <th colspan="4" class="bg-secondary text-white">Saturday</th>
                            <th colspan="4" class="bg-secondary text-white">Sunday</th>

                            <!-- Rental Terms -->
                            <th class="py-3">Period</th>
                            <th class="py-3">Price</th>
                            <th class="py-3">Late Fee</th>
                            <th class="py-3">Deposit</th>
                            <th class="py-3">Max Books</th>
```

```
            <th class="py-3">Discount</th>
            <th class="py-3">Payments</th>
            <th class="py-3">Terms</th>

            <th class="py-3">Actions</th>
        </tr>
        <!-- Second header row for day details -->
        <tr class="bg-dark text-white text-center small fw-normal">
            <th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th>
            <!-- Services -->
            <th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th>
            <!-- Monday -->
            <th>Open</th>
            <th>Open Time</th>
            <th>Close Time</th>
            <th>Closed</th>
            <!-- Tuesday -->
            <th>Open</th>
            <th>Open Time</th>
            <th>Close Time</th>
            <th>Closed</th>
            <!-- Wednesday -->
            <th>Open</th>
            <th>Open Time</th>
            <th>Close Time</th>
            <th>Closed</th>
            <!-- Thursday -->
            <th>Open</th>
            <th>Open Time</th>
            <th>Close Time</th>
            <th>Closed</th>
            <!-- Friday -->
            <th>Open</th>
            <th>Open Time</th>
            <th>Close Time</th>
            <th>Closed</th>
            <!-- Saturday -->
            <th>Open</th>
            <th>Open Time</th>
            <th>Close Time</th>
            <th>Closed</th>
            <!-- Sunday -->
            <th>Open</th>
            <th>Open Time</th>
            <th>Close Time</th>
            <th>Closed</th>
            <!-- Rental -->
            <th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th>
            <th></th>
        </tr>
    </thead>

    <tbody class="text-center">
        @php
            $get = function ($store, array $keys, $default = null) {
                foreach ($keys as $key) {
                    $value = data_get($store, $key);
                    if ($value !== null && $value !== '') {
                        return $value;
                    }
                }
                return $default;
            };
            $yesNo = function ($value, $dash = '-') {
                return is_null($value) ? $dash : ($value ? 'Yes' : 'No');
            };
            $yesNoClosed = function ($value, $dash = '-') {
                return is_null($value) ? $dash : ($value ? 'Closed' : 'Open');
            };
            $money = function ($value) {
                return is_null($value) || $value == '' ? '0.00' : number_format((float) $value, 2, '.', '');
            };
            $text = function ($value, $dash = '-') {
                return is_null($value) || $value === '' ? $dash : $value;
            };
        @endphp
        @forelse ($stores as $store)
            @php
                $paymentMethods = $store->payment_methods ?? null;
                if (is_array($paymentMethods)) {
                    $paymentMethods = implode(', ', $paymentMethods);
                }
                $description = $get($store, ['store_description', 'description'], null);
            @endphp
            <tr>
                <td class="fw-bold text-muted">{{ $store->id }}</td>
                <td class="fw-semibold">{{ $text($get($store, ['store_name', 'name'])) }}</td>
                <td>{{ $text($get($store, ['owner_full_name', 'owner_name'])) }}</td>
                <td class="text-nowrap">{{ $text($get($store, ['email'])) }}</td>
                <td>{{ $text($get($store, ['phone'])) }}</td>
                <td>{{ $text($get($store, ['store_type', 'type'])) }}</td>
                <td>{{ $text($get($store, ['city'])) }}</td>
                <td>{{ $text($get($store, ['sub_city', 'subcity'])) }}</td>
                <td class="text-start">{{ $text($get($store, ['address'])) }}</td>
                <td class="text-start text-truncate" style="max-width: 180px;" title="{{ $description ?? '' }}">
                    {{ $description ? \Illuminate\Support\Str::words($description, 8, '...') : '-' }}
                </td>

                <td><span class="badge bg-success-subtle text-success">{{ $yesNo($get($store, ['offers_rental'])) }}</span></td>
                <td><span class="badge bg-success-subtle text-success">{{ $yesNo($get($store, ['offers_sale'])) }}</span></td>
                <td><span class="badge bg-info-subtle text-info">{{ $yesNo($get($store, ['offers_delivery'])) }}</span></td>
                <td class="fw-medium">${{ $money($get($store, ['delivery_fee'])) }}</td>
                <td>{{ $yesNo($get($store, ['delivery_bike'])) }}</td>
                <td>{{ $yesNo($get($store, ['delivery_car'])) }}</td>
                <td>{{ $yesNo($get($store, ['delivery_pickup'])) }}</td>

                <!-- Monday -->
                <td>{{ $yesNo($get($store, ['open_monday'])) }}</td>
                <td>{{ $text($get($store, ['open_time_monday'])) }}</td>
                <td>{{ $text($get($store, ['close_time_monday'])) }}</td>
                <td>{{ $yesNoClosed($get($store, ['closed_monday', 'close_monday'])) }}</td>

                <!-- Tuesday -->
                <td>{{ $yesNo($get($store, ['open_tuesday'])) }}</td>
                <td>{{ $text($get($store, ['open_time_tuesday'])) }}</td>
                <td>{{ $text($get($store, ['close_time_tuesday'])) }}</td>
                <td>{{ $yesNoClosed($get($store, ['closed_tuesday', 'close_tuesday'])) }}</td>

                <!-- Wednesday -->
                <td>{{ $yesNo($get($store, ['open_wednesday'])) }}</td>
                <td>{{ $text($get($store, ['open_time_wednesday'])) }}</td>
                <td>{{ $text($get($store, ['close_time_wednesday'])) }}</td>
                <td>{{ $yesNoClosed($get($store, ['closed_wednesday', 'close_wednesday'])) }}</td>

                <!-- Thursday -->
                <td>{{ $yesNo($get($store, ['open_thursday'])) }}</td>
                <td>{{ $text($get($store, ['open_time_thursday'])) }}</td>
                <td>{{ $text($get($store, ['close_time_thursday'])) }}</td>
```

```
                    <td>{{ $yesNoClosed($get($store, ['closed_thursday', 'close_thursday'])) }}</td>

                    <!-- Friday -->
                    <td>{{ $yesNo($get($store, ['open_friday'])) }}</td>
                    <td>{{ $text($get($store, ['open_time_friday'])) }}</td>
                    <td>{{ $text($get($store, ['close_time_friday'])) }}</td>
                    <td>{{ $yesNoClosed($get($store, ['closed_friday', 'close_friday'])) }}</td>

                    <!-- Saturday -->
                    <td>{{ $yesNo($get($store, ['open_saturday'])) }}</td>
                    <td>{{ $text($get($store, ['open_time_saturday'])) }}</td>
                    <td>{{ $text($get($store, ['close_time_saturday'])) }}</td>
                    <td>{{ $yesNoClosed($get($store, ['closed_saturday', 'close_saturday'])) }}</td>

                    <!-- Sunday -->
                    <td>{{ $yesNo($get($store, ['open_sunday'])) }}</td>
                    <td>{{ $text($get($store, ['open_time_sunday'])) }}</td>
                    <td>{{ $text($get($store, ['close_time_sunday'])) }}</td>
                    <td>{{ $yesNoClosed($get($store, ['closed_sunday', 'close_sunday'])) }}</td>

                    <!-- Rental Terms -->
                    <td>{{ $text($get($store, ['rental_period', 'rental_period_days'])) }}</td>
                    <td class="fw-medium">${{ $money($get($store, ['rental_price', 'rental_price_per_day'])) }}</td>
                    <td>${{ $money($get($store, ['late_fee', 'late_fee_per_day'])) }}</td>
                    <td>${{ $money($get($store, ['security_deposit'])) }}</td>
                    <td>{{ $text($get($store, ['max_books', 'max_books_per_customer'])) }}</td>
                    <td>{{ $text($get($store, ['discount_percent', 'student_discount_percent']), '0') }}%</td>
                    <td class="text-start">{{ $text($paymentMethods ?? $get($store, ['payment_methods', 'payment_method'])) }}</td>
                    <td>{{ $yesNo($get($store, ['agree_terms', 'agreed_terms'])) }}</td>

                    <td class="text-nowrap">
                        @if(($storeSource ?? 'registrations') === 'registrations')
                            <a href="{{ route('store.registration.edit', ['store_id' => $store->id]) }}" class="btn btn-outline-primary btn-sm me-2">
                                <i class="far fa-edit"></i>edit
                            </a>
                            <form action="{{ route('store.registration.destroy', $store->id) }}" method="post" class="d-inline">
                                @csrf
                                @method('DELETE')
                                <button type="submit" class="btn btn-outline-danger btn-sm"
                                        onclick="return confirm('Delete this store permanently?');">
                                    <i class="far fa-trash-alt"></i>delete
                                </button>
                            </form>
                        @else
                            <span class="text-muted">Not editable</span>
                        @endif
                    </td>
                </tr>
            @empty
                <tr>
                    <td colspan="70" class="text-center py-5 text-muted fs-5">
                        <i class="fas fa-store-slash me-2"></i>No stores found.
                    </td>
```

(Content truncated due to size - showing first 15KB)

## File: resources\views\store\wishlist.blade.php

```
@extends('store.registration-layout')

@section('title', 'Wishlisted Books')

@section('content')
    <div class="container-fluid">
        <div class="d-flex align-items-center justify-content-between mb-3">
            <h1 class="h3 mb-0">Wishlisted Books</h1>
            <span class="text-muted">Track books customers have wishlisted.</span>
        </div>

        <div class="card border-0 shadow-sm">
            <div class="card-body">
                <div class="text-muted">No wishlist items to display yet.</div>
            </div>
        </div>
    </div>
@endsection
```

## File: resources\views\store\books\add.blade.php

```
@extends('store.registration-layout')

@section('title', 'Add Book')

@section('content')
    <div class="container-fluid">


        <div class="card border-0 shadow-sm">
            <div class="card-body">
                <div class="min-h-screen bg-gray-100 py-10">
                    <div class="max-w-6xl mx-auto px-6">
                        <!-- HEADER -->
                        <div class="mb-10">
                            <h1 class="text-4xl font-bold text-gray-800 tracking-tight">
                                Add Book to Inventory
                            </h1>
                            <p class="text-gray-500 mt-2">Manage your bookstore catalog professionally</p>
                        </div>

                        @if($errors->any())
                            <div class="alert alert-danger">
                                <ul class="mb-0">
                                    @foreach($errors->all() as $error)
                                        <li>{{ $error }}</li>
                                    @endforeach
                                </ul>
                            </div>
                        @endif

                        <form method="POST" enctype="multipart/form-data" class="space-y-10" action="{{ route('books.store') }}">
                            @csrf

                            <!-- SECTION CARD STYLE -->
                            <div class="bg-white/80 backdrop-blur-sm rounded-2xl shadow-lg border border-gray-200 p-8 space-y-6">
                                <h2 class="text-lg font-semibold text-gray-700 flex items-center gap-2">
                                    ■ Book Information
                                </h2>

                                <div class="grid grid-cols-1 md:grid-cols-2 gap-6">
                                    <div class="space-y-1">
                                        <label class="text-sm font-medium text-gray-600">Title *</label>
                                        <input type="text" name="title" required
                                            class="w-full px-4 py-3 rounded-xl border border-gray-300
```

```
                        focus:ring-2 focus:ring-blue-500 focus:border-blue-500 transition form-control" placeholder="enter name of title">
                </div>

                <div class="space-y-1">
                    <label class="text-sm font-medium text-gray-600">Author *</label>
                    <input type="text" name="author" required
                        class="w-full px-4 py-3 rounded-xl border border-gray-300
                        focus:ring-2 focus:ring-blue-500 focus:border-blue-500 transition form-control" placeholder="enter author name">
                </div>

                <div class="space-y-1">
                    <label class="text-sm font-medium text-gray-600">Genre *</label>
                    <select name="genre" required
                        class="w-full px-4 py-3 rounded-xl border border-gray-300
                        focus:ring-2 focus:ring-blue-500 focus:border-blue-500 transition">
                        <option value="">Select Genre</option>
                        <option value="fiction">Fiction</option>
                        <option value="non-fiction">Non-Fiction</option>
                        <option value="sci-fi">Science Fiction</option>
                        <option value="fantasy">Fantasy</option>
                    </select>
                </div>

                <div class="space-y-1">
                    <label class="text-sm font-medium text-gray-600">Publication Year</label>
                    <input type="number" name="publication_year"
                        class="w-full px-4 py-3 rounded-xl border border-gray-300
                        focus:ring-2 focus:ring-blue-500 focus:border-blue-500 transition">
                </div>
            </div>
        </div>

        <!-- INVENTORY -->
        <div class="bg-white/80 backdrop-blur-sm rounded-2xl shadow-lg border border-gray-200 p-8 space-y-6">
            <h2 class="text-lg font-semibold text-gray-700 flex items-center gap-2">
                ■ Inventory Details
            </h2>

            <div class="grid grid-cols-1 md:grid-cols-3 gap-6">
                <input type="number" name="total_copies" required placeholder="Total Copies"
                    class="px-4 py-3 rounded-xl border border-gray-300 focus:ring-2 focus:ring-blue-500 transition">

                <input type="number" name="available_rent" required placeholder="Available for Rent"
                    class="px-4 py-3 rounded-xl border border-gray-300 focus:ring-2 focus:ring-blue-500 transition">

                <input type="number" name="available_sale" required placeholder="Available for Sale"
                    class="px-4 py-3 rounded-xl border border-gray-300 focus:ring-2 focus:ring-blue-500 transition">
            </div>
        </div>

        <!-- PRICING -->
        <div class="bg-white/80 backdrop-blur-sm rounded-2xl shadow-lg border border-gray-200 p-8 space-y-6">
            <h2 class="text-lg font-semibold text-gray-700 flex items-center gap-2">
                ■ Pricing
            </h2>

            <div class="grid grid-cols-1 md:grid-cols-2 gap-6">
                <div class="relative">
                    <span class="absolute left-4 top-3 text-gray-400">$</span>
                    <input type="number" name="rental_price" required step="0.01"
                        class="w-full pl-8 pr-4 py-3 rounded-xl border border-gray-300 form-control
                        focus:ring-2 focus:ring-blue-500 transition"
                        placeholder="Rental Price">
                </div>

                <div class="relative">
                    <span class="absolute left-4 top-3 text-gray-400">$</span>
                    <input type="number" name="sale_price" required step="0.01"
                        class="w-full pl-8 pr-4 py-3 rounded-xl border border-gray-300
                        focus:ring-2 focus:ring-blue-500 transition"
                        placeholder="Sale Price">
                </div>
            </div>
        </div>

        <!-- IMAGE UPLOAD SECTION -->
        <div class="bg-white/80 backdrop-blur-sm rounded-2xl shadow-lg border border-gray-200 p-8 space-y-6">
            <h2 class="text-lg font-semibold text-gray-700 flex items-center gap-2">
                ■■ Book Cover Image
            </h2>

            <div class="space-y-4">
                <div class="border-2 border-dashed border-gray-300 rounded-xl p-6 text-center hover:border-blue-500 transition cursor-pointer"
                     onclick="document.getElementById('cover_image').click()">
                    <input type="file" name="cover_image" id="cover_image" accept="image/*" class="hidden" onchange="previewImage(this)">

                    <!-- Image preview container -->
                    <div id="image_preview_container" class="hidden mb-4">
                        <img id="image_preview" src="#" alt="Cover preview" class="max-h-48 mx-auto rounded-lg shadow-md">
                    </div>

                    <!-- Upload icon and text -->
                    <div id="upload_prompt">
                        <svg class="mx-auto h-12 w-12 text-gray-400" stroke="currentColor" fill="none" viewBox="0 0 48 48">
                            <path d="M28 8H12a4 4 0 00-4 4v20m32-12v8m0 0v8a4 4 0 01-4 4H8a4 4 0 01-4-4v-20m32 12h-8m-12 0h-8" stroke-width="2" stroke-line
                        </svg>
                        <p class="mt-2 text-sm text-gray-600">Click to upload book cover image</p>
                        <p class="text-xs text-gray-500">PNG, JPG, GIF up to 5MB</p>
                    </div>
                </div>

                <!-- Remove image button -->
                <button type="button" onclick="removeImage()" class="text-sm text-red-600 hover:text-red-800 hidden" id="remove_image_btn">
                    <i class="fas fa-trash-alt mr-1"></i> Remove Image
                </button>
            </div>
        </div>

        <!-- STICKY ACTION BAR -->
        <div class="sticky bottom-0 border-t border-gray-200 p-6 flex justify-end gap-4 rounded-b-2xl shadow-lg bg-white">
            <button type="button"
                onclick="window.history.back()"
                class="px-6 py-3 rounded-xl border border-gray-300 hover:bg-gray-100 transition btn btn-danger">
                Cancel
            </button>

            <button type="submit" name="save_and_add"
                class="px-6 py-3 rounded-xl bg-green-600 text-white hover:bg-green-700 shadow-md transition btn btn-warning">
                Save & Add Another
            </button>

            <button type="submit" name="save_and_close"
                class="px-6 py-3 rounded-xl bg-blue-600 text-white hover:bg-blue-700 shadow-md transition btn btn-primary">
                Save & Close
            </button>
        </div>
    </form>
</div>
```

```
                </div>
            </div>
        </div>
    </div>

    <!-- Image Preview Script -->
    <script>
    function previewImage(input) {
        const previewContainer = document.getElementById('image_preview_container');
        const preview = document.getElementById('image_preview');
        const uploadPrompt = document.getElementById('upload_prompt');
        const removeBtn = document.getElementById('remove_image_btn');

        if (input.files && input.files[0]) {
            const reader = new FileReader();

            reader.onload = function(e) {
                preview.src = e.target.result;
                previewContainer.classList.remove('hidden');
                uploadPrompt.classList.add('hidden');
                removeBtn.classList.remove('hidden');
            }

            reader.readAsDataURL(input.files[0]);
        }
    }

    function removeImage() {
        const fileInput = document.getElementById('cover_image');
        const previewContainer = document.getElementById('image_preview_container');
        const uploadPrompt = document.getElementById('upload_prompt');
        const removeBtn = document.getElementById('remove_image_btn');

        fileInput.value = '';
        previewContainer.classList.add('hidden');
        uploadPrompt.classList.remove('hidden');
        removeBtn.classList.add('hidden');
    }
    </script>

    <!-- Alert Messages -->
    @if(session('messages'))
        <script>
            @foreach(session('messages') as $message)
                alert("{{ $message }}");
            @endforeach
        </script>
    @endif

    <style>
        .border-2 { border-width: 2px; }
        .border-dashed { border-style: dashed; }
        .hidden { display: none; }
    </style>
@endsection
```

### File: resources\views\store\books\edit.blade.php

```
@extends('store.registration-layout')

@section('title', 'Edit Book')

@section('content')
    <div class="container-fluid">
        <div class="card border-0 shadow-sm">
            <div class="card-body">
                <div class="min-h-screen bg-gray-100 py-10">
                    <div class="max-w-6xl mx-auto px-6">
                        <!-- HEADER -->
                        <div class="mb-10">
                            <h1 class="text-4xl font-bold text-gray-800 tracking-tight">
                                Edit Book
                            </h1>
                            <p class="text-gray-500 mt-2">Update your bookstore catalog</p>
                        </div>

                        @if($errors->any())
                            <div class="alert alert-danger">
                                <ul class="mb-0">
                                    @foreach($errors->all() as $error)
                                        <li>{{ $error }}</li>
                                    @endforeach
                                </ul>
                            </div>
                        @endif

                        <form method="POST" enctype="multipart/form-data" class="space-y-10" action="{{ route('books.update', $book->id) }}">
                            @csrf
                            @method('PUT')

                            <!-- SECTION CARD STYLE -->
                            <div class="bg-white/80 backdrop-blur-sm rounded-2xl shadow-lg border border-gray-200 p-8 space-y-6">
                                <h2 class="text-lg font-semibold text-gray-700 flex items-center gap-2">
                                    ■ Book Information
                                </h2>

                                <div class="grid grid-cols-1 md:grid-cols-2 gap-6">
                                    <div class="space-y-1">
                                        <label class="text-sm font-medium text-gray-600">Title *</label>
                                        <input type="text" name="title" required
                                            value="{{ old('title', $book->title) }}"
                                            class="w-full px-4 py-3 rounded-xl border border-gray-300
                                            focus:ring-2 focus:ring-blue-500 focus:border-blue-500 transition form-control" placeholder="enter name of title">
                                    </div>

                                    <div class="space-y-1">
                                        <label class="text-sm font-medium text-gray-600">Author *</label>
                                        <input type="text" name="author" required
                                            value="{{ old('author', $book->author) }}"
                                            class="w-full px-4 py-3 rounded-xl border border-gray-300
                                            focus:ring-2 focus:ring-blue-500 focus:border-blue-500 transition form-control" placeholder="enter author name">
                                    </div>

                                    <div class="space-y-1">
                                        <label class="text-sm font-medium text-gray-600">Genre *</label>
                                        <select name="genre" required
                                            class="w-full px-4 py-3 rounded-xl border border-gray-300
                                            focus:ring-2 focus:ring-blue-500 focus:border-blue-500 transition">
                                            @php
                                                $genre = old('genre', $book->genre);
                                            @endphp
                                            <option value="">Select Genre</option>
                                            <option value="fiction" @selected($genre === 'fiction')>Fiction</option>
                                            <option value="non-fiction" @selected($genre === 'non-fiction')>Non-Fiction</option>
                                            <option value="sci-fi" @selected($genre === 'sci-fi')>Science Fiction</option>
```

```
                        <option value="fantasy" @selected($genre === 'fantasy')>Fantasy</option>
                    </select>
                </div>

                <div class="space-y-1">
                    <label class="text-sm font-medium text-gray-600">Publication Year</label>
                    <input type="number" name="publication_year"
                        value="{{ old('publication_year', $book->publication_year) }}"
                        class="w-full px-4 py-3 rounded-xl border border-gray-300
                        focus:ring-2 focus:ring-blue-500 focus:border-blue-500 transition">
                </div>
            </div>
        </div>

        <!-- INVENTORY -->
        <div class="bg-white/80 backdrop-blur-sm rounded-2xl shadow-lg border border-gray-200 p-8 space-y-6">
            <h2 class="text-lg font-semibold text-gray-700 flex items-center gap-2">
                ■ Inventory Details
            </h2>

            <div class="grid grid-cols-1 md:grid-cols-3 gap-6">
                <input type="number" name="total_copies" required placeholder="Total Copies"
                    value="{{ old('total_copies', $book->total_copies) }}"
                    class="px-4 py-3 rounded-xl border border-gray-300 focus:ring-2 focus:ring-blue-500 transition">

                <input type="number" name="available_rent" required placeholder="Available for Rent"
                    value="{{ old('available_rent', $book->available_rent) }}"
                    class="px-4 py-3 rounded-xl border border-gray-300 focus:ring-2 focus:ring-blue-500 transition">

                <input type="number" name="available_sale" required placeholder="Available for Sale"
                    value="{{ old('available_sale', $book->available_sale) }}"
                    class="px-4 py-3 rounded-xl border border-gray-300 focus:ring-2 focus:ring-blue-500 transition">
            </div>
        </div>

        <!-- PRICING -->
        <div class="bg-white/80 backdrop-blur-sm rounded-2xl shadow-lg border border-gray-200 p-8 space-y-6">
            <h2 class="text-lg font-semibold text-gray-700 flex items-center gap-2">
                ■ Pricing
            </h2>

            <div class="grid grid-cols-1 md:grid-cols-2 gap-6">
                <div class="relative">
                    <span class="absolute left-4 top-3 text-gray-400">$</span>
                    <input type="number" name="rental_price" required step="0.01"
                        value="{{ old('rental_price', $book->rental_price) }}"
                        class="w-full pl-8 pr-4 py-3 rounded-xl border border-gray-300 form-control
                        focus:ring-2 focus:ring-blue-500 transition"
                        placeholder="Rental Price">
                </div>

                <div class="relative">
                    <span class="absolute left-4 top-3 text-gray-400">$</span>
                    <input type="number" name="sale_price" required step="0.01"
                        value="{{ old('sale_price', $book->sale_price) }}"
                        class="w-full pl-8 pr-4 py-3 rounded-xl border border-gray-300
                        focus:ring-2 focus:ring-blue-500 transition"
                        placeholder="Sale Price">
                </div>
            </div>
        </div>

        <!-- IMAGE UPLOAD SECTION -->
        <div class="bg-white/80 backdrop-blur-sm rounded-2xl shadow-lg border border-gray-200 p-8 space-y-6">
            <h2 class="text-lg font-semibold text-gray-700 flex items-center gap-2">
                ■■ Book Cover Image
            </h2>

            <div class="space-y-4">
                <div class="border-2 border-dashed border-gray-300 rounded-xl p-6 text-center hover:border-blue-500 transition cursor-pointer"
                     onclick="document.getElementById('cover_image').click()">
                    <input type="file" name="cover_image" id="cover_image" accept="image/*" class="hidden" onchange="previewImage(this)">

                    <!-- Image preview container -->
                    <div id="image_preview_container" class="@if(!$book->cover_image_path) hidden @endif mb-4">
                        <img id="image_preview" src="{{ $book->cover_image_path ? asset($book->cover_image_path) : '#' }}" alt="Cover preview" class="max-h

                    <!-- Upload icon and text -->
                    <div id="upload_prompt" class="@if($book->cover_image_path) hidden @endif">
                        <svg class="mx-auto h-12 w-12 text-gray-400" stroke="currentColor" fill="none" viewBox="0 0 48 48">
                            <path d="M28 8H12a4 4 0 00-4 4v20m32-12v8m0 0v8a4 4 0 01-4 4H8a4 4 0 01-4-4v-20m32 12h-8m-12 0h-8" stroke-width="2" stroke-line
                        </svg>
                        <p class="mt-2 text-sm text-gray-600">Click to upload book cover image</p>
                        <p class="text-xs text-gray-500">PNG, JPG, GIF up to 5MB</p>
                    </div>
                </div>

                <!-- Remove image button -->
                <button type="button" onclick="removeImage()" class="text-sm text-red-600 hover:text-red-800 @if(!$book->cover_image_path) hidden @endif" i
                    <i class="fas fa-trash-alt mr-1"></i> Remove Image
                </button>
            </div>
        </div>

        <!-- STICKY ACTION BAR -->
        <div class="sticky bottom-0 border-t border-gray-200 p-6 flex justify-end gap-4 rounded-b-2xl shadow-lg bg-white">
            <button type="button"
                onclick="window.history.back()"
                class="px-6 py-3 rounded-xl border border-gray-300 hover:bg-gray-100 transition btn btn-danger">
                Cancel
            </button>

            <button type="submit"
                class="px-6 py-3 rounded-xl bg-blue-600 text-white hover:bg-blue-700 shadow-md transition btn btn-primary">
                Save Changes
            </button>
        </div>
    </form>
</div>
</div>
</div>
</div>
</div>
</div>

<!-- Image Preview Script -->
<script>
function previewImage(input) {
    const previewContainer = document.getElementById('image_preview_container');
    const preview = document.getElementById('image_preview');
    const uploadPrompt = document.getElementById('upload_prompt');
    const removeBtn = document.getElementById('remove_image_btn');

    if (input.files && input.files[0]) {
        const reader = new FileReader();

        reader.onload = function(e) {
            preview.src = e.target.result;
```

```
                    previewContainer.classList.remove('hidden');
                    uploadPrompt.classList.add('hidden');
                    removeBtn.classList.remove('hidden');
                }

                reader.readAsDataURL(input.files[0]);
            }
        }

        function removeImage() {
            const fileInput = document.getElementById('cover_image');
            const previewContainer = document.getElementById('image_preview_container');
            const uploadPrompt = document.getElementById('upload_prompt');
            const removeBtn = document.getElementById('remove_image_btn');

            fileInput.value = '';
            previewContainer.classList.add('hidden');
            uploadPrompt.classList.remove('hidden');
            removeBtn.classList.add('hidden');
        }
        </script>

        <style>
            .border-2 { border-width: 2px; }
            .border-dashed { border-style: dashed; }
            .hidden { display: none; }
        </style>
    @endsection
```

### *File: resources\views\store\books\inventory.blade.php*

```
    @extends('store.registration-layout')

    @section('title', 'Inventory')

    @section('content')
        <div class="container-fluid">
            <div class="d-flex align-items-center justify-content-between mb-3">
                <h1 class="h3 mb-0">Inventory</h1>
                <span class="text-muted">Track books currently in stock.</span>
            </div>

            @if(session('messages'))
                <div class="alert alert-success">
                    @foreach((array) session('messages') as $message)
                        <div>{{ $message }}</div>
                    @endforeach
                </div>
            @endif

            <div class="card border-0 shadow-sm">
                <div class="card-body">

    <div class="table-responsive">
        <table class="table table-hover table-striped align-middle shadow-sm">
            <thead class="table-dark text-center">
                <tr>
                    <th>ID</th>
                    <th>Image</th>
                    <th>Title</th>
                    <th>Author</th>
                    <th>Genre</th>
                    <th>Publication Year</th>
                    <th>Total Copies</th>
                    <th>Available Rent</th>
                    <th>Available Sale</th>
                    <th>Rental Price</th>
                    <th>Sale Price</th>
                    <th>
                        <a href="{{ route('add.book.registration') }}"
                           class="btn btn-success btn-sm px-3">
                            <i class="fas fa-plus-circle me-1"></i> Add New
                        </a>
                    </th>
                </tr>
            </thead>

            <tbody class="text-center">
                @forelse($books as $book)
                    <tr>
                        <td class="fw-semibold">{{ $book->id }}</td>
                        <td>
                            <div style="width:48px; height:64px; margin:0 auto;">
                                @if($book->cover_image_path)
                                    <img src="{{ asset($book->cover_image_path) }}"
                                         alt="{{ $book->title }}"
                                         loading="lazy"
                                         style="width:100%; height:100%; object-fit:cover; border-radius:6px; border:1px solid #e5e7eb;">
                                @else
                                    <div class="d-flex align-items-center justify-content-center bg-light text-muted"
                                         style="width:100%; height:100%; border-radius:6px; border:1px solid #e5e7eb; font-size:0.7rem;">
                                        No Image
                                    </div>
                                @endif
                            </div>
                        </td>
                        <td>{{ $book->title }}</td>
                        <td>{{ $book->author }}</td>
                        <td>{{ $book->genre }}</td>
                        <td>{{ $book->publication_year ?? '-' }}</td>
                        <td>{{ $book->total_copies }}</td>
                        <td>{{ $book->available_rent }}</td>
                        <td>{{ $book->available_sale }}</td>
                        <td>${{ number_format($book->rental_price, 2) }}</td>
                        <td>${{ number_format($book->sale_price, 2) }}</td>
                        <td class="text-nowrap">
                            <a href="{{ route('books.edit', $book->id) }}" class="btn btn-outline-primary btn-sm me-2">
                                <i class="far fa-edit"></i> edit
                            </a>

                            <form action="{{ route('books.destroy', $book->id) }}" method="post" class="d-inline">
                                @csrf
                                @method('DELETE')
                                <button type="submit"
                                        class="btn btn-outline-danger btn-sm"
                                        onclick="return confirm('Delete this book permanently?');">
                                    <i class="far fa-trash-alt"></i>delete
                                </button>
                            </form>
                        </td>
                    </tr>
                @empty
                    <tr>
                        <td colspan="12" class="text-muted py-4">No books in inventory yet.</td>
                    </tr>
```

```
            @endforelse
        </tbody>
    </table>
</div>



            </div>
        </div>
    </div>
@endsection
```

### File: resources\views\store\books\manage.blade.php

```
@extends('store.registration-layout')

@section('title', 'Manage Books')

@section('content')
    <div class="container-fluid">
        <div class="d-flex align-items-center justify-content-between mb-3">
            <h1 class="h3 mb-0">Manage Books</h1>
            <span class="text-muted">Edit or remove books from your catalog.</span>
        </div>

        <div class="card border-0 shadow-sm">
            <div class="card-body">
                <div class="text-muted">No books to manage yet.</div>
            </div>
        </div>
    </div>
@endsection
```

### File: resources\views\store\issue_reports\create.blade.php

```
@extends('store.registration-layout')

@section('content')
<div class="container mx-auto px-4 py-8">
    <div class="max-w-3xl mx-auto">
        <div class="flex items-center gap-4 mb-6">
            <a href="{{ route('store.issue-reports.index') }}" class="text-gray-500 hover:text-indigo-600 transition-colors">
                <i class="bi bi-arrow-left text-xl"></i>
            </a>
            <div>
                <h1 class="text-2xl font-bold text-gray-900">Report a Customer</h1>
                <p class="text-gray-600 mt-1">If a customer violates our rules, report them here.</p>
            </div>
        </div>

        <div class="bg-white rounded-xl shadow-sm border border-gray-100 overflow-hidden">
            <div class="p-6 sm:p-8">
                <form action="{{ route('store.issue-reports.store') }}" method="POST" enctype="multipart/form-data" class="space-y-6">
                    @csrf

                    <div>
                        <label for="reported_user_id" class="block text-sm font-medium text-gray-700 mb-1">Customer to Report</label>
                        <select name="reported_user_id" id="reported_user_id" required class="block w-full pl-3 pr-10 py-2 text-base border-gray-300 focus:outline-none focus:r
                            <option value="">Select a customer...</option>
                            @foreach($customers as $customer)
                                <option value="{{ $customer->id }}" @selected(old('reported_user_id') == $customer->id)>
                                    {{ $customer->name }} ({{ $customer->email }})
                                </option>
                            @endforeach
                        </select>
                        @error('reported_user_id')
                            <p class="mt-1 flex items-center text-xs text-red-500 bg-red-50 px-2 py-1 rounded"><i class="bi bi-exclamation-circle mr-1"></i> {{ $message }}</p>
                        @enderror
                    </div>

                    <div>
                        <label for="subject" class="block text-sm font-medium text-gray-700 mb-1">Issue Subject</label>
                        <input type="text" name="subject" id="subject" value="{{ old('subject') }}" required placeholder="Brief description of the issue" class="block w-full s
                        @error('subject')
                            <p class="mt-1 flex items-center text-xs text-red-500 bg-red-50 px-2 py-1 rounded">{{ $message }}</p>
                        @enderror
                    </div>

                    <div>
                        <label for="description" class="block text-sm font-medium text-gray-700 mb-1">Full Details</label>
                        <textarea name="description" id="description" rows="5" required placeholder="Provide all necessary context so our admins can take action..." class="blo
                        @error('description')
                            <p class="mt-1 flex items-center text-xs text-red-500 bg-red-50 px-2 py-1 rounded">{{ $message }}</p>
                        @enderror
                    </div>

                    <div class="grid grid-cols-1 gap-6 sm:grid-cols-2">
                        <div>
                            <label for="priority" class="block text-sm font-medium text-gray-700 mb-1">Severity / Priority</label>
                            <select name="priority" id="priority" class="block w-full pl-3 pr-10 py-2 text-base border-gray-300 focus:outline-none focus:ring-indigo-500 focus:
                                <option value="low" @selected(old('priority') == 'low')>Low</option>
                                <option value="medium" @selected(old('priority', 'medium') == 'medium')>Medium</option>
                                <option value="high" @selected(old('priority') == 'high')>High (Urgent action needed)</option>
                            </select>
                        </div>

                        <div>
                            <label class="block text-sm font-medium text-gray-700 mb-1">Evidence (Optional)</label>
                            <div class="mt-1 flex justify-center px-6 pt-5 pb-6 border-2 border-gray-300 border-dashed rounded-md hover:bg-gray-50 transition-colors">
                                <div class="space-y-1 text-center">
                                    <i class="bi bi-cloud-arrow-up text-3xl text-gray-400"></i>
                                    <div class="flex text-sm text-gray-600 justify-center">
                                        <label for="evidence" class="relative cursor-pointer bg-white rounded-md font-medium text-indigo-600 hover:text-indigo-500 focus-within
                                            <span>Upload a file</span>
                                            <input id="evidence" name="evidence" type="file" class="sr-only" accept=".jpg,.jpeg,.png,.gif,.pdf,.doc,.docx,.txt">
                                        </label>
                                    </div>
                                    <p class="text-xs text-gray-500 border border-gray-200 mt-2 bg-white px-2 py-1 rounded inline-block" id="file-name">
                                        PNG, JPG, PDF up to 10MB
                                    </p>
                                </div>
                            </div>
                            @error('evidence')
                                <p class="mt-1 flex items-center text-xs text-red-500 bg-red-50 px-2 py-1 rounded">{{ $message }}</p>
                            @enderror
                        </div>
                    </div>

                    <div class="pt-4 border-t border-gray-100 flex justify-end">
                        <button type="submit" class="inline-flex justify-center py-2.5 px-6 border border-transparent shadow-sm text-sm font-medium rounded-md text-white bg-in
                            <i class="bi bi-send-fill mr-2"></i> Submit Report
                        </button>
                    </div>
```

```
                </form>
            </div>
        </div>
    </div>
</div>

<script>
    document.getElementById('evidence').addEventListener('change', function(e) {
        if(e.target.files.length > 0) {
            document.getElementById('file-name').innerHTML = '<span class="text-indigo-600 font-bold"><i class="bi bi-check-circle-fill"></i> ' + e.target.files[0].name + '</s
        }
    });
</script>
@endsection
```

### File: resources\views\store\issue_reports\index.blade.php

```
@extends('store.registration-layout')

@section('content')
<div class="container mx-auto px-4 py-8">
    <div class="flex justify-between items-center mb-6">
        <div>
            <h1 class="text-2xl font-bold text-gray-800">My Reports</h1>
            <p class="text-gray-600 mt-1">Reports you've filed against customers.</p>
        </div>
        <a href="{{ route('store.issue-reports.create') }}" class="bg-indigo-600 hover:bg-indigo-700 text-white font-bold py-2 px-4 rounded shadow">
            <i class="bi bi-flag-fill mr-2"></i> Report a Customer
        </a>
    </div>

    @if(session('status'))
        <div class="bg-green-50 border-l-4 border-green-500 p-4 mb-6 rounded shadow-sm">
            <div class="flex">
                <div class="flex-shrink-0">
                    <i class="bi bi-check-circle-fill text-green-500"></i>
                </div>
                <div class="ml-3">
                    <p class="text-sm text-green-700 font-medium">{{ session('status') }}</p>
                </div>
            </div>
        </div>
    @endif

    <div class="bg-white rounded-xl shadow-sm overflow-hidden border border-gray-100">
        <div class="overflow-x-auto">
            <table class="min-w-full divide-y divide-gray-200">
                <thead class="bg-gray-50">
                    <tr>
                        <th scope="col" class="px-6 py-3 text-left text-xs font-medium text-gray-500 uppercase tracking-wider">Report Info</th>
                        <th scope="col" class="px-6 py-3 text-left text-xs font-medium text-gray-500 uppercase tracking-wider">Reported Customer</th>
                        <th scope="col" class="px-6 py-3 text-left text-xs font-medium text-gray-500 uppercase tracking-wider">Status</th>
                        <th scope="col" class="px-6 py-3 text-left text-xs font-medium text-gray-500 uppercase tracking-wider">Date</th>
                        <th scope="col" class="relative px-6 py-3"><span class="sr-only">Actions</span></th>
                    </tr>
                </thead>
                <tbody class="bg-white divide-y divide-gray-200">
                    @forelse($reports as $report)
                    <tr class="hover:bg-gray-50 transition-colors">
                        <td class="px-6 py-4">
                            <div class="text-sm font-medium text-gray-900">{{ $report->subject }}</div>
                            <div class="text-sm text-gray-500">
                                Priority:
                                <span class="@if($report->priority == 'high') text-red-600 @elseif($report->priority == 'medium') text-yellow-600 @else text-blue-600 @endif fo
                                    {{ ucfirst($report->priority) }}
                                </span>
                            </div>
                        </td>
                        <td class="px-6 py-4 whitespace-nowrap">
                            <div class="flex items-center">
                                @if($report->reportedUser?->avatar)
                                    <img class="h-8 w-8 rounded-full mr-3 object-cover border border-gray-200" src="{{ asset('storage/' . $report->reportedUser->avatar) }}" al
                                @else
                                    <div class="h-8 w-8 rounded-full bg-indigo-100 text-indigo-700 flex items-center justify-center font-bold mr-3 border border-indigo-200">
                                        {{ substr($report->reportedUser?->name ?? '?', 0, 1) }}
                                    </div>
                                @endif
                                <div class="text-sm font-medium text-gray-900">{{ $report->reportedUser?->name ?? 'Unknown' }}</div>
                            </div>
                        </td>
                        <td class="px-6 py-4 whitespace-nowrap">
                            @php
                                $statusColors = [
                                    'open' => 'bg-blue-100 text-blue-800 border-blue-200',
                                    'in_review' => 'bg-yellow-100 text-yellow-800 border-yellow-200',
                                    'resolved' => 'bg-green-100 text-green-800 border-green-200',
                                    'closed' => 'bg-gray-100 text-gray-800 border-gray-200',
                                ];
                                $color = $statusColors[$report->status] ?? $statusColors['open'];
                            @endphp
                            <span class="px-3 py-1 inline-flex text-xs leading-5 font-semibold rounded-full border {{ $color }}">
                                {{ ucfirst(str_replace('_', ' ', $report->status)) }}
                            </span>
                        </td>
                        <td class="px-6 py-4 whitespace-nowrap text-sm text-gray-500">
                            {{ $report->created_at->format('M d, Y') }}<br>
                            <span class="text-xs text-gray-400">{{ $report->created_at->format('H:i') }}</span>
                        </td>
                        <td class="px-6 py-4 whitespace-nowrap text-right text-sm font-medium">
                            <a href="{{ route('store.issue-reports.show', $report) }}" class="text-indigo-600 hover:text-indigo-900 flex items-center justify-end gap-1">
                                View Details <i class="bi bi-chevron-right"></i>
                            </a>
                        </td>
                    </tr>
                    @empty
                    <tr>
                        <td colspan="5" class="px-6 py-12 text-center">
                            <div class="inline-flex items-center justify-center w-16 h-16 rounded-full bg-gray-100 text-gray-400 mb-4">
                                <i class="bi bi-flag fs-3"></i>
                            </div>
                            <h3 class="text-lg font-medium text-gray-900 mb-1">No reports filed</h3>
                            <p class="text-gray-500">You haven't reported any customers yet.</p>
                        </td>
                    </tr>
                    @endforelse
                </tbody>
            </table>
        </div>
    </div>
</div>
@endsection
```

### File: resources\views\store\issue_reports\show.blade.php

```
@extends('store.sales_dashboard')

@section('content')
<div class="container mx-auto px-4 py-8">
    <div class="max-w-4xl mx-auto">
        <div class="flex items-center gap-4 mb-6">
            <a href="{{ route('store.issue-reports.index') }}" class="text-gray-500 hover:text-indigo-600 transition-colors">
                <i class="bi bi-arrow-left text-xl"></i>
            </a>
            <div>
                <h1 class="text-2xl font-bold text-gray-900">Report Details</h1>
                <p class="text-gray-600 mt-1">Report #{{ $issueReport->id }}</p>
            </div>
        </div>

        <div class="bg-white rounded-xl shadow-sm border border-gray-100 overflow-hidden mb-6">
            <div class="p-6 sm:p-8 border-b border-gray-100 flex flex-wrap justify-between items-start gap-4">
                <div>
                    <h2 class="text-xl font-bold text-gray-900">{{ $issueReport->subject }}</h2>
                    <p class="text-gray-500 text-sm mt-1">Submitted on {{ $issueReport->created_at->format('F j, Y \a\t g:i A') }}</p>
                </div>
                <div class="flex gap-2">
                    @php
                        $statusColors = [
                            'open' => 'bg-blue-100 text-blue-800 border-blue-200',
                            'in_review' => 'bg-yellow-100 text-yellow-800 border-yellow-200',
                            'resolved' => 'bg-green-100 text-green-800 border-green-200',
                            'closed' => 'bg-gray-100 text-gray-800 border-gray-200',
                        ];
                        $color = $statusColors[$issueReport->status] ?? $statusColors['open'];
                    @endphp
                    <span class="px-3 py-1 inline-flex text-sm leading-5 font-semibold rounded-full border {{ $color }}">
                        {{ ucfirst(str_replace('_', ' ', $issueReport->status)) }}
                    </span>

                    <span class="px-3 py-1 inline-flex text-sm leading-5 font-semibold rounded-full border
                        @if($issueReport->priority == 'high') bg-red-100 text-red-800 border-red-200
                        @elseif($issueReport->priority == 'medium') bg-orange-100 text-orange-800 border-orange-200
                        @else bg-blue-100 text-blue-800 border-blue-200 @endif">
                        Priority: {{ ucfirst($issueReport->priority) }}
                    </span>
                </div>
            </div>

            <div class="p-6 sm:p-8 bg-gray-50 border-b border-gray-100 flex items-center gap-4">
                <div class="h-12 w-12 rounded-full bg-indigo-100 text-indigo-700 flex items-center justify-center font-bold text-xl border border-indigo-200 shadow-sm">
                    {{ substr($issueReport->reportedUser?->name ?? '?', 0, 1) }}
                </div>
                <div>
                    <h3 class="text-sm font-bold text-gray-500 uppercase tracking-wider mb-1">Reported Customer</h3>
                    <div class="text-gray-900 font-medium text-lg">{{ $issueReport->reportedUser?->name ?? 'Unknown Customer' }}</div>
                    @if($issueReport->reportedUser)
                        <div class="text-gray-500 text-sm">{{ $issueReport->reportedUser->email }}</div>
                    @endif
                </div>
            </div>

            <div class="p-6 sm:p-8">
                <h3 class="text-sm font-bold text-gray-500 uppercase tracking-wider mb-3">Description</h3>
                <div class="prose max-w-none text-gray-800 whitespace-pre-wrap bg-white border border-gray-200 rounded-lg p-5 shadow-inner">{{ $issueReport->description }}</di

                @if($issueReport->hasEvidence())
                    <h3 class="text-sm font-bold text-gray-500 uppercase tracking-wider mt-8 mb-3">Provided Evidence</h3>
                    <div class="border border-gray-200 rounded-lg p-4 bg-gray-50 flex flex-col gap-4">
                        <div class="flex items-center gap-3">
                            <i class="bi {{ $issueReport->isEvidenceImage() ? 'bi-file-image text-blue-500' : 'bi-file-earmark-text text-gray-500' }} text-3xl"></i>
                            <div class="flex-1 min-w-0">
                                <p class="text-sm font-medium text-gray-900 truncate">{{ $issueReport->evidence_name }}</p>
                                <a href="{{ $issueReport->evidence_url }}" target="_blank" class="text-indigo-600 hover:text-indigo-900 text-sm font-medium flex items-center g
                                    <i class="bi bi-box-arrow-up-right"></i> View File
                                </a>
                            </div>
                        </div>

                        @if($issueReport->isEvidenceImage())
                            <div class="mt-2 border border-gray-200 rounded overflow-hidden shadow-sm bg-white">
                                <img src="{{ $issueReport->evidence_url }}" alt="Evidence" class="max-w-full h-auto" style="max-height: 400px; object-fit: contain; width: 100%
                            </div>
                        @endif
                    </div>
                @endif
            </div>

            @if($issueReport->assignedAdmin)
            <div class="bg-indigo-50 p-6 sm:p-8 border-t border-indigo-100 flex items-center gap-3">
                <i class="bi bi-shield-check text-indigo-600 text-2xl"></i>
                <div>
                    <p class="text-indigo-900 font-medium">Assigned to Admin: {{ $issueReport->assignedAdmin->name }}</p>
                    <p class="text-indigo-700 text-sm">Our team is reviewing your report.</p>
                </div>
            </div>
            @endif
        </div>
    </div>
</div>
@endsection
```

### File: routes\auth.php

```
<?php

use App\Http\Controllers\Auth\AuthenticatedSessionController;
use App\Http\Controllers\Auth\ConfirmablePasswordController;
use App\Http\Controllers\Auth\EmailVerificationNotificationController;
use App\Http\Controllers\Auth\EmailVerificationPromptController;
use App\Http\Controllers\Auth\NewPasswordController;
use App\Http\Controllers\Auth\PasswordController;
use App\Http\Controllers\Auth\PasswordResetLinkController;
use App\Http\Controllers\Auth\RegisteredUserController;
use App\Http\Controllers\Auth\VerifyEmailController;
use Illuminate\Support\Facades\Route;

Route::middleware('guest')->group(function () {
    Route::get('register', [RegisteredUserController::class, 'create'])
        ->name('register');

    Route::post('register', [RegisteredUserController::class, 'store']);

    Route::get('login', [AuthenticatedSessionController::class, 'create'])
        ->name('login');

    Route::post('login', [AuthenticatedSessionController::class, 'store']);
    Route::get('forgot-password', [PasswordResetLinkController::class, 'create'])
```

```
        ->name('password.request');

    Route::post('forgot-password', [PasswordResetLinkController::class, 'store'])
        ->name('password.email');

    Route::get('reset-password/{token}', [NewPasswordController::class, 'create'])
        ->name('password.reset');

    Route::post('reset-password', [NewPasswordController::class, 'store'])
        ->name('password.store');
});

Route::middleware('auth')->group(function () {
    Route::get('verify-email', EmailVerificationPromptController::class)
        ->name('verification.notice');

    Route::get('verify-email/{id}/{hash}', VerifyEmailController::class)
        ->middleware(['signed', 'throttle:6,1'])
        ->name('verification.verify');

    Route::post('email/verification-notification', [EmailVerificationNotificationController::class, 'store'])
        ->middleware('throttle:6,1')
        ->name('verification.send');

    Route::get('confirm-password', [ConfirmablePasswordController::class, 'show'])
        ->name('password.confirm');

    Route::post('confirm-password', [ConfirmablePasswordController::class, 'store']);

    Route::put('password', [PasswordController::class, 'update'])
        ->name('password.update');

    Route::post('logout', [AuthenticatedSessionController::class, 'destroy'])
        ->name('logout');
});
```

## File: routes\console.php

```
<?php

use Illuminate\Foundation\Inspiring;
use Illuminate\Support\Facades\Artisan;

Artisan::command('inspire', function () {
    $this->comment(Inspiring::quote());
})->purpose('Display an inspiring quote');
```

## File: routes\web.php

```
<?php

use App\Http\Controllers\BookController;
use App\Http\Controllers\AdminChatController;
use App\Http\Controllers\AdminDashboardController;
use App\Http\Controllers\AdminIssueReportController;
use App\Http\Controllers\AdminUserController;
use App\Http\Controllers\AdminUserManagementController;
use App\Http\Controllers\CustomerBookController;
use App\Http\Controllers\CustomerCartController;
use App\Http\Controllers\CustomerChatController;
use App\Http\Controllers\CustomerOrderController;
use App\Http\Controllers\CustomerIssueReportController;
use App\Http\Controllers\CustomerWishlistController;
use App\Http\Controllers\CustomerDashboardController;
use App\Http\Controllers\ProfileController;
use App\Http\Controllers\StoreRegistrationController;
use App\Http\Controllers\StoreIssueReportController;
use App\Http\Controllers\StoreChatController;
use Illuminate\Foundation\Application;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Route;
use Inertia\Inertia;

/*
|--------------------------------------------------------------------------
| Web Routes
|--------------------------------------------------------------------------
*/

// Public Routes
Route::get('/', function () {
    return Inertia::render('Welcome', [
        'canLogin' => Route::has('login'),
        'canRegister' => Route::has('register'),
        'laravelVersion' => Application::VERSION,
        'phpVersion' => PHP_VERSION,
    ]);
});

// Dashboard Redirect based on user type
Route::get('/dashboard', function (Request $request) {
    $user = $request->user();

    if (!$user) {
        return redirect()->route('login');
    }

    if ($user->account_type === 'store_owner') {
        return redirect()->route('store.dashboard');
    }

    if ($user->account_type === 'customer') {
        return redirect()->route('customer.dashboard');
    }

    if (in_array($user->account_type, ['sub_admin', 'super_admin'], true)) {
        return redirect()->route('admin.dashboard');
    }

    return Inertia::render('Dashboard');
})->middleware(['auth', 'verified'])->name('dashboard');

// Customer Dashboard
Route::get('/customer/dashboard', [CustomerDashboardController::class, 'index'])
    ->middleware(['auth', 'verified'])
    ->name('customer.dashboard');

// Customer Book Routes
Route::get('/customer/books/{book}', [CustomerBookController::class, 'show'])
    ->name('books.show');

/*
|--------------------------------------------------------------------------
```

```
| Authenticated Customer Routes
|--------------------------------------------------------------------------
*/
Route::middleware('auth')->group(function () {
    // Profile Management
    Route::get('/profile', [ProfileController::class, 'edit'])->name('profile.edit');
    Route::patch('/profile', [ProfileController::class, 'update'])->name('profile.update');
    Route::delete('/profile', [ProfileController::class, 'destroy'])->name('profile.destroy');

    // Customer Issue Reports
    Route::get('/customer/issue-reports', [CustomerIssueReportController::class, 'index'])->name('issue-reports.index');
    Route::get('/customer/issue-reports/create', [CustomerIssueReportController::class, 'create'])->name('issue-reports.create');
    Route::post('/customer/issue-reports', [CustomerIssueReportController::class, 'store'])->name('issue-reports.store');
    Route::get('/customer/issue-reports/{issueReport}', [CustomerIssueReportController::class, 'show'])->name('issue-reports.show');

    /*
    |--------------------------------------------------------------------------
    | Customer Chat Routes (FIXED)
    |--------------------------------------------------------------------------
    */
    // Main chat listing
    Route::get('/customer/chat', [CustomerChatController::class, 'index'])->name('chat.index');

    // Start new conversation
    Route::post('/customer/chat', [CustomerChatController::class, 'startConversation'])->name('chat.start');

    // View conversation
    Route::get('/customer/chat/{conversation}', [CustomerChatController::class, 'show'])->name('chat.show');

    // Send message (with attachment support)
    Route::post('/customer/chat/{conversation}/send', [CustomerChatController::class, 'sendMessage'])->name('chat.send');

    // Mark messages as read
    Route::post('/customer/chat/{conversation}/mark-read', [CustomerChatController::class, 'markAsRead'])->name('chat.mark-read');

    // Poll for new messages
    Route::get('/customer/chat/{conversation}/poll', [CustomerChatController::class, 'pollMessages'])->name('chat.poll');

    // Get stores list for new chat
    Route::get('/customer/chat/stores/list', [CustomerChatController::class, 'getStores'])->name('chat.stores');

    // Get unread count
    Route::get('/chat/unread-count', [CustomerChatController::class, 'getUnreadCount'])->name('chat.unread');
});

// Include Auth Routes
require __DIR__ . '/auth.php';

/*
|--------------------------------------------------------------------------
| Store Owner Routes
|--------------------------------------------------------------------------
*/
Route::middleware(['auth'])->group(function () {
    // Store Dashboard
    Route::get('/store/dashboard', function (Request $request) {
        if ($request->header('X-Inertia')) {
            return Inertia::location(url('/store/dashboard'));
        }
        return view('store.dashboard');
    })->name('store.dashboard');

    // Store Views
    Route::view('/store/orders', 'store.orders')->name('store.orders');
    Route::view('/store/wishlist', 'store.wishlist')->name('store.wishlist');

    // Book Management
    Route::get('/store/books/add', [BookController::class, 'create'])->name('add.book.registration');
    Route::post('/store/books', [BookController::class, 'store'])->name('books.store');
    Route::get('/store/books/{book}/edit', [BookController::class, 'edit'])->name('books.edit');
    Route::put('/store/books/{book}', [BookController::class, 'update'])->name('books.update');
    Route::delete('/store/books/{book}', [BookController::class, 'destroy'])->name('books.destroy');
    Route::get('/store/inventory', [BookController::class, 'index'])->name('view.inventory');
    Route::view('/store/books/manage', 'store.books.manage')->name('manage.books');

    // Store Registration
    Route::get('/store/registration', [StoreRegistrationController::class, 'create'])
        ->name('store.registration.create');
    Route::post('/store/registration', [StoreRegistrationController::class, 'store'])
        ->name('store.registration.store');
    Route::get('/store/registration/update', [StoreRegistrationController::class, 'edit'])
        ->name('store.registration.edit');
    Route::post('/store/registration/update', [StoreRegistrationController::class, 'update'])
        ->name('store.registration.update');
    Route::delete('/store/registration/{store}', [StoreRegistrationController::class, 'destroy'])
        ->name('store.registration.destroy');
    Route::get('/store/registration/view', [StoreRegistrationController::class, 'show'])
        ->name('store.registration.view');

    /*
    |--------------------------------------------------------------------------
    | Store Chat Routes
    |--------------------------------------------------------------------------
    */
    // Main chat listing
    Route::get('/store/chats', [StoreChatController::class, 'index'])->name('store.chat.index');

    // View conversation
    Route::get('/store/chat/{conversation}', [StoreChatController::class, 'show'])->name('store.chat.show');

    // Send message (with attachment support)
    Route::post('/store/chat/{conversation}/send', [StoreChatController::class, 'sendMessage'])->name('store.chat.send');

    // Mark messages as read
    Route::post('/store/chat/{conversation}/mark-read', [StoreChatController::class, 'markAsRead'])->name('store.chat.mark-read');

    // Poll for new messages
    Route::get('/store/chat/{conversation}/poll', [StoreChatController::class, 'pollMessages'])->name('store.chat.poll');

    // Start new conversation
    Route::post('/store/chat/start', [StoreChatController::class, 'startConversation'])->name('store.chat.start');

    // Delete conversation
    Route::delete('/store/chat/{conversation}', [StoreChatController::class, 'destroy'])->name('store.chat.destroy');

    // Get unread count
    Route::get('/store/chat/unread-count', [StoreChatController::class, 'getUnreadCount'])->name('store.chat.unread');

    // Store Issue Reports
    Route::get('/store/issue-reports', [StoreIssueReportController::class, 'index'])->name('store.issue-reports.index');
    Route::get('/store/issue-reports/create', [StoreIssueReportController::class, 'create'])->name('store.issue-reports.create');
    Route::post('/store/issue-reports', [StoreIssueReportController::class, 'store'])->name('store.issue-reports.store');
    Route::get('/store/issue-reports/{issueReport}', [StoreIssueReportController::class, 'show'])->name('store.issue-reports.show');

});

/*
|--------------------------------------------------------------------------
```

```
| Admin Routes (Sub Admin & Super Admin)
|--------------------------------------------------------------------------
*/
Route::middleware(['auth', 'account_type:sub_admin,super_admin'])
    ->prefix('admin')
    ->name('admin.')
    ->group(function () {
        // Admin Dashboard
        Route::get('/dashboard', [AdminDashboardController::class, 'index'])->name('dashboard');

        // Issue Reports Management
        Route::get('/issue-reports', [AdminIssueReportController::class, 'index'])->name('issue-reports.index');
        Route::get('/issue-reports/{issueReport}', [AdminIssueReportController::class, 'show'])->name('issue-reports.show');
        Route::put('/issue-reports/{issueReport}', [AdminIssueReportController::class, 'update'])->name('issue-reports.update');
        Route::post('/issue-reports/{issueReport}/ban', [AdminIssueReportController::class, 'banUser'])->name('issue-reports.ban');
        Route::post('/issue-reports/{issueReport}/warn', [AdminIssueReportController::class, 'warnUser'])->name('issue-reports.warn');
        Route::post('/issue-reports/{issueReport}/restrict', [AdminIssueReportController::class, 'restrictUser'])->name('issue-reports.restrict');
        Route::post('/issue-reports/{issueReport}/resolve', [AdminIssueReportController::class, 'resolve'])->name('issue-reports.resolve');

        // Support Chats Management
        Route::get('/chats', [AdminChatController::class, 'index'])->name('chats.index');
        Route::get('/chats/{conversation}', [AdminChatController::class, 'show'])->name('chats.show');
        Route::post('/chats/{conversation}/message', [AdminChatController::class, 'sendMessage'])->name('chats.message');

        // Site Users Management (all customers & store owners)
        Route::get('/users', [AdminUserManagementController::class, 'index'])->name('users.index');
        Route::get('/users/{user}', [AdminUserManagementController::class, 'show'])->name('users.show');
        Route::post('/users/{user}/ban', [AdminUserManagementController::class, 'banUser'])->name('users.ban');
        Route::post('/users/{user}/unban', [AdminUserManagementController::class, 'unbanUser'])->name('users.unban');
        Route::post('/users/{user}/warn', [AdminUserManagementController::class, 'warnUser'])->name('users.warn');
        Route::post('/users/{user}/restrict', [AdminUserManagementController::class, 'restrictUser'])->name('users.restrict');
        Route::post('/users/{user}/unrestrict', [AdminUserManagementController::class, 'unrestrictUser'])->name('users.unrestrict');

        // Admin Users Management
        Route::get('/admins', [AdminUserController::class, 'index'])->name('admins.index');
        Route::get('/admins/create', [AdminUserController::class, 'create'])
            ->middleware('account_type:super_admin')
            ->name('admins.create');
        Route::post('/admins', [AdminUserController::class, 'store'])
            ->middleware('account_type:super_admin')
            ->name('admins.store');
        Route::get('/admins/{admin}/edit', [AdminUserController::class, 'edit'])
            ->middleware('account_type:super_admin')
            ->name('admins.edit');
        Route::put('/admins/{admin}', [AdminUserController::class, 'update'])
            ->middleware('account_type:super_admin')
            ->name('admins.update');
        Route::delete('/admins/{admin}', [AdminUserController::class, 'destroy'])
            ->middleware('account_type:super_admin')
            ->name('admins.destroy');
        Route::post('/admins/{admin}/toggle-active', [AdminUserController::class, 'toggleActive'])
            ->middleware('account_type:super_admin')
            ->name('admins.toggle-active');
    });

/*
|--------------------------------------------------------------------------
| Customer Routes (Cart, Wishlist, Orders)
|--------------------------------------------------------------------------
*/

// Wishlist Routes
Route::get('/customer/wishlist', [CustomerWishlistController::class, 'index'])
    ->middleware('auth')
    ->name('wishlist.index');
Route::get('/customer/wishlist/add/{book}', [CustomerWishlistController::class, 'add'])
    ->middleware('auth')
    ->name('wishlist.add');
Route::get('/customer/wishlist/remove/{book}', [CustomerWishlistController::class, 'remove'])
    ->middleware('auth')
    ->name('wishlist.remove');
Route::get('/customer/wishlist/clear', [CustomerWishlistController::class, 'clear'])
    ->middleware('auth')
    ->name('wishlist.clear');

// Cart Routes
Route::get('/customer/cart', [CustomerCartController::class, 'index'])
    ->middleware('auth')
    ->name('cart.index');
Route::get('/customer/cart/add/rent/{book}', [CustomerCartController::class, 'addRent'])
    ->middleware('auth')
    ->name('cart.add.rent');
Route::get('/customer/cart/add/buy/{book}', [CustomerCartController::class, 'addBuy'])
    ->middleware('auth')
    ->name('cart.add.buy');
Route::get('/customer/cart/remove/{book}/{type}', [CustomerCartController::class, 'remove'])
    ->middleware('auth')
    ->name('cart.remove');
Route::get('/get-cart-count', [CustomerCartController::class, 'count'])
    ->middleware('auth')
    ->name('cart.count');

// Checkout & Orders
Route::get('/customer/checkout', [CustomerCartController::class, 'checkout'])
    ->middleware('auth')
    ->name('orders.checkout');
Route::get('/customer/orders', [CustomerOrderController::class, 'index'])
    ->middleware('auth')
    ->name('orders.index');
Route::get('/customer/orders/{order}', [CustomerOrderController::class, 'show'])
    ->middleware('auth')
    ->name('orders.show');
Route::post('/customer/orders/{order}/finish', [CustomerOrderController::class, 'markFinished'])
    ->middleware('auth')
    ->name('orders.finish');
```

## Summary

Total files processed: 184
Skipped large files: 6
Total characters added: 779,900
Estimated PDF size: 7.80 MB