



OUI-CROISSANT

Security Assessment Report

Private and Confidential

PREPARED BY
FINALS-XX

DATE
Jan 19th, 2025

VERSION
VERSION 1.0

CONFIDENTIAL
INTERNAL USE ONLY

Notice of Confidentiality: This document is confidential and solely intended for OuiCroissant. Unauthorized access, viewing, or distribution of this document is prohibited and may violate federal and state laws, including Defend Trade Secrets Act (DTSA) and the Computer Fraud and Abuse Act (CFAA). Unauthorized individuals found in possession of or distributing this document may be subject to legal action.

Disclaimer of Warranty and Limitation of Liability: This report is intended solely for the purpose of assessing the security posture and data compliance status of OuiCroissant. The findings, recommendations, and information in this document are provided to help identify potential vulnerabilities and risks within the current operational framework. This document is not a comprehensive guarantee of immunity from future security incidents, data breaches, or other threats. FINALS-XX provides no assurance, warranty, or representation that the implementation of the recommendations provided will prevent or fully mitigate all forms of potential losses, damages, and/or liabilities.

TABLE OF CONTENTS

TABLE OF CONTENTS	3
INTRODUCTION	4
CONTACT INFORMATION	4
EXECUTIVE OVERVIEW	5
EXECUTIVE SUMMARY	5
KEY SECURITY STRENGTHS	5
KEY SECURITY IMPROVEMENTS	6
KEY AREAS OF IMPROVEMENT	6
REMEDIATION ROADMAP	7
ENGAGEMENT OUTLINE	8
METHODOLOGY	8
NETWORK DIAGRAM	8
SCOPE	8
TECHNICAL RISK ASSESSMENT METRICS	9
TECHNICAL FINDINGS	10
CRITICAL FINDINGS	10
HIGH FINDINGS	29
MEDIUM FINDINGS	48
LOW FINDINGS	63
APPENDICES	68
APPENDIX A: TOOLS	68
APPENDIX B: FINDING BLOCK LEGEND	71
APPENDIX C: NETWORK INVENTORY	72
APPENDIX D: SOCIAL ENGINEERING FINDINGS	73
APPENDIX E: ARTIFICIAL INTELLIGENCE MODEL EVALUATION	74
APPENDIX F: ARTIFACTS	77

Introduction

This penetration testing report provides a comprehensive assessment of the current security posture of OuiCroissant's IT infrastructure as of January 19, 2025. Penetration tests are a "snapshot in time" and as such, this report offers insights into potential security and operational risk based on existing configurations, network structures, and deployed defenses during the period of this engagement. Because network environments and threat landscapes continually evolve, this assessment reflects findings only observed at the time of testing. Regular, periodic testing is advised to maintain an up-to-date understanding of security risks.

This report is organized to support both executive decision-making and technical teams in understanding OuiCroissant's risk profile and in prioritizing strategic remediation efforts. The key sections of this report include:

- **Executive Summary:** Provides all stakeholders with a high-level overview of the penetration test findings, highlighting critical vulnerabilities and their implications. This section summarizes the organization's current security posture and presents distilled recommendations to improve defenses and align with organizational goals.
- **Strategic Plan:** Highlights key security strengths and areas of improvements, as well as providing prioritized recommendations for addressing identified vulnerabilities and improving the organization's security resilience. This includes both immediate, high-impact mitigations as well as long-term strategies for enhancing overall security posture and maturity.
- **Engagement Outline:** Describes the overall engagement, including the methodology employed, scope of the assessment, objectives, and timelines established for the engagement.
- **Severity and Risk Level Classifications:** Explanation of FINALS-XX scoring metrics used to categorize vulnerabilities based on severity and associated risk levels is provided.
- **Technical Findings:** Detailed account of the identified vulnerabilities, including their potential impact and risk ratings as best understood by FINALS-XX. Each finding includes technical details and actionable remediation steps, with vulnerabilities ranked by severity to streamline prioritization efforts.

Contact Information

Organization	Point of Contact	Contact Information
OuiCroissant	Jamie Thompson	jthompson@ouicroissant.com secops@ouicroissant.com
FINALS-XX	FINALS-XX	Cptc10-FINALS-XX@cptc.team

Executive Overview

Executive Summary

During the limited assessment period, FINALS-XX identified 33 unique vulnerabilities across critical, high, medium, and low severity categories. Notably, several critical findings with low attack complexity posed a risk of exposing both employee and customer data from the production network. These vulnerabilities present significant risks to Y and OuiCroissant, including potential data loss.

In addition to identifying vulnerabilities, this report highlights key security strengths within the organization, as well as areas for improvement. FINALS-XX provided additional supplementary testing services including large language model logic subversion as well as a user phishing exercise evading windows defender found in the appendices. Understanding these strengths will enable OuiCroissant and Y as a platform to build upon existing security measures while addressing identified weaknesses. The "Remediation Roadmap" section outlines both short-term and long-term remediation actions aimed at enhancing the overall security posture. These actions are designed to provide a structured approach to mitigating risks and ensuring compliance with security best practices.

Please note that due to the assessment's limited timeframe and the evolving nature of information security, additional vulnerabilities may exist. Ongoing assessments are essential to maintaining a robust and proactive security posture.

Δ LOW Δ	ΔΔ MEDIUM ΔΔ	ΔΔΔ HIGH ΔΔΔ	ΔΔΔΔ CRITICAL ΔΔΔΔ
3	9	11	11

Key Security Strengths

Throughout the engagement, FINALS-XX noticed two key strengths implemented in OuiCroissant's organization.

Automated PII Tooling

OuiCroissant has implemented automated tooling to minimize the storage and exposure of personally identifiable information (PII) and credentials. This demonstrates a strong commitment to safeguarding sensitive data and reducing the risk of data breaches.

AI Resiliency & Safety

OuiCroissant demonstrates a commitment to AI resiliency and safety by continuous red team testing via Scale and being proactive to ensure user safety and bias resiliency by being up-to-date with current legislation and recommendations.

Key Security Improvements

From FINALS-XX's last engagement with OuiCroissant, two notable improvements and mitigations were implemented to address previously identified findings. These changes reflect the organization's commitment to enhancing its overall security posture.

Improved Database Security

OuiCroissant has enhanced database security by addressing weak credentials and implementing network-based authentication on its MSSQL and PostgreSQL servers. These measures reflect an understanding of the critical role databases play in securing sensitive information and ensuring data integrity.

Enhanced Endpoint Security

OuiCroissant has deployed antivirus (AV) solutions across user workstation devices. This improves visibility into potential threats on endpoints and allows for faster detection and remediation of security incidents.

Enforced Principle of Least Privilege

FINALS-XX observed restricted membership in administrative groups on systems such as OC-Desktop01.oui.local and OC-Desktop04.oui.local. This highlights OuiCroissant's recognition of the importance of limiting privileged access to mitigate the risk of unauthorized actions or privilege escalation.

Key Areas of Improvement

During the engagement, FINALS-XX identified 33 unique vulnerabilities, highlighting common themes that require attention. Addressing these areas will be critical in strengthening OuiCroissant's security posture and preventing future vulnerabilities.

CWE-653: Improper Isolation or Compartmentalization

OuiCroissant's internal environment lacks sufficient isolation, allowing for unnecessary communication between services. Implementing a zero-trust architecture will enforce strict service-to-service communication policies, ensuring that interactions occur only where necessary.

CWE-284: Improper Access Control


Numerous vulnerabilities were identified due to improper authentication mechanisms, including client-side authentication for the Y admin panel, unauthenticated API, and use of weak credentials. Comprehensive access controls should be implemented across all systems and services, including robust authentication, secure API gateways, and enforcing secure programming practices.

CWE-200: Exposure of Sensitive Information to an Unauthorized Actor

Sensitive information, including verbose error messages, service banners, and local filesystem files, had the ability to be exposed in public-facing services. OuiCroissant should sanitize application inputs and responses and ensure secure storage of secrets to prevent potential data leaks.

Remediation Roadmap

The following road map has been created by FINALS-XX to provide OuiCroissant with a timeline by which to plan and execute recommended remediations related to found and exploitable vulnerabilities present in Y. Please note: FINALS-XX has a limited view into the backend of OuiCroissant and can only offer suggestions based on its prior experiences and findings during the assessment. All remediation recommendations are to be interpreted by qualified professionals with experience working with Y backend systems. Further technical details to remediation can be found in the Remediation section of each technical finding table.




Engagement Outline

Methodology

To ensure consistent and standardized results, the Penetration Testing Execution Standard (PTES), is used by FINALS-XX. This approach not only facilitates transparent communication during the pre-engagement phase but also ensures a thorough and all-encompassing assessment. Many regulatory frameworks and industry standards require or recommend penetration tests and using a standardized framework like PTES can help organizations demonstrate compliance with these requirements. Additionally, following standardized approaches allows future and past tests to be benchmarked, to see improvements or regressions, if any.

- **Pre-Engagement Interactions:** Scoping, Rules of Engagement, etc.
- **Intelligence Gathering:** Aims to gain information about OuiCroissant.
- **Threat Modeling:** Models potential threats and vulnerabilities specific to OuiCroissant.
- **Vulnerability Analysis:** Analyze potential threats for vulnerabilities.
- **Exploitation:** Exploit found vulnerabilities to gain initial access to systems.
- **Post Exploitation:** Attempt to move laterally within the network to gain further access.
- **Reporting:** Summarize findings and provide actionable recommendations.

Network Diagram



Scope

The scope of this test consisted of the production subnet (10.0.1.0/24) and the development subnet (10.0.2.0/24) within the OuiCroissant network. Spanning the two subnets was the yyy.chat web app. The entirety of this engagement was performed with the intention of the limited-scope subnet remaining available and functional. If modifications in reference to sensitive data and physical machines were changed through the process, all instructions to reset or revert such actions will be given within indicators of compromise (IOC) section within *Appendix D*, subsection: *Indicators of Compromise*.

Technical Risk Assessment Metrics

FINALS-XX categorizes findings using a combination of *severity* and *risk*. For severity, FINALS-XX utilizes the Common Vulnerability Scoring System (CVSSv3) to determine the severity of identified vulnerabilities. CVSS allows vulnerabilities in different applications and from different vendors to be evaluated in a standardized and repeatable way. While CVSS effectively measures severity, it is important to note, as the National Institute of Standards and Technology (NIST) explicitly states that "CVSS is not a measure of risk."

To address this gap, FINALS-XX combines CVSS with a modified version of the NIST SP-800-30 risk matrix to calculate a risk score. Risk-based testing considers the unique context of the organization and prioritizes vulnerabilities based on their potential impact on the business. This approach considers assets and likelihood of a successful attack.

By evaluating both the potential impact and the likelihood of a successful exploit, this approach ensures that security efforts are directed towards mitigating the most significant threats -- those that are not only highly impactful but also likely to materialize.

SEVERITY SCORE	
0.00	NONE
0.1 – 3.9	Δ LOW Δ
4.0 – 6.9	ΔΔ MEDIUM ΔΔ
7.0 – 8.9	ΔΔΔ HIGH ΔΔΔ
9.0 – 10.0	ΔΔΔΔ CRITICAL ΔΔΔΔ

CVSSv3 scoring table used to determine vulnerability severity

RISK LEVEL		LIKELIHOOD LEVEL			
		NONE/LOW	MEDIUM	HIGH	CRITICAL
IMPACT LEVEL	NONE/LOW	Δ	Δ	ΔΔ	ΔΔ
	MEDIUM	Δ	ΔΔ	ΔΔΔ	ΔΔΔ
	HIGH	ΔΔ	ΔΔΔ	ΔΔΔ	ΔΔΔΔ
	CRITICAL	ΔΔΔ	ΔΔΔ	ΔΔΔΔ	ΔΔΔΔ

FINALS-XX's modified NIST SP-800-30 risk matrix to calculate Risk Level based on likelihood and impact

OVERALL SCORE		SEVERITY LEVEL			
		NONE/LOW	MEDIUM	HIGH	CRITICAL
RISK LEVEL	NONE/LOW	Δ	Δ	ΔΔ	ΔΔ
	MEDIUM	Δ	ΔΔ	ΔΔΔ	ΔΔΔ
	HIGH	ΔΔ	ΔΔΔ	ΔΔΔ	ΔΔΔΔ
	CRITICAL	ΔΔΔ	ΔΔΔ	ΔΔΔΔ	ΔΔΔΔ

FINALS-XX's overall scoring matrix to calculate vulnerability score based on risk and severity

Technical Findings

Critical Findings

Blank Administrator Password on Workstations

Overview: The build-in Administrator account exists on every Windows machine to provide an administrative account at all times.

ΔΔΔΔ Blank Administrator Password on Workstations ΔΔΔΔ		CVSS	Risk
Impact	Critical	10.0	Critical
Likelihood	Critical		
CVSS String	AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:H		
Affected Scope	10.0.2.100 (OC-Desktop01.oui.local) 10.0.2.104 (OC-Desktop04.oui.local)		
Summary	FINALs-XX identified that the password for the administrator accounts on OC-Desktop01.oui.local and OC-Desktop04.oui.local is blank. This misconfiguration allows attackers to gain complete access critical systems and potentially extract sensitive data or escalate privileges within the domain.		
Technical Impact	The absence of administrator passwords on these systems allows unauthorized access with no credentials to the systems. This gives an attacker with network access to the machine complete control.		
Business Impact	The use of blank administrator passwords severely compromises OuiCroissant's IT security. Attackers could disrupt operations, compromise sensitive data, and undermine stakeholder trust.		
Likelihood Description	Exploiting blank administrator passwords is highly likely, as it requires no special tools or effort. Attackers can easily identify and misuse these accounts.		
MITRE ATT&CK	T1078: Valid Accounts M1027: Password Policies		
Evidence			
Remediation			
FINALs-XX recommend that strong administrator password be set. FINALs-XX also recommend that OuiCroissant audit for blank passwords on existing accounts.			

END OF FINDING BLOCK

Anonymous SMTP Login

Overview: Simple Mail Transfer Protocol (SMTP) is used for sending emails between servers and clients. SMTP servers can be configured to allow anonymous logins, enabling users to connect without authentication.

ΔΔΔΔ Anonymous SMTP Login ΔΔΔΔ		CVSS	Risk
Impact	Critical	8.6	Critical
Likelihood	Critical		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:H/A:L		
Affected Scope	10.0.1.7 (flakemail.oui.local)		
Summary	FINALIS-XX identified that the SMTP server on flakemail.oui.local allows anonymous login. This misconfiguration enables attackers to authenticate without credentials, potentially allowing them to send spoofed emails, relay spam, or exploit internal email systems to deliver phishing or malicious payloads.		
Technical Impact	The ability to log in to the SMTP server anonymously enable attackers to misuse the email service. This can lead to the unauthorized relay of emails, reputational damage through spam distribution, and the delivery of phishing attacks or malware. It also allows attackers to impersonate legitimate users, potentially bypassing email-based authentication or gaining further access to internal systems.		
Business Impact	The exploitation of an anonymous SMTP login could result in significant reputational damage to OuiCroissant due to spam distribution or email impersonation attacks. Phishing campaigns or malware delivery could disrupt operations and lead to financial losses. Regulatory penalties may also arise due to non-compliance with email security standards.		
Likelihood Description	Exploitation is highly likely due to the ease of identifying and abusing anonymous SMTP logins. Tools such as telnet or automated scanners can quickly determine if anonymous access is permitted. Attackers can leverage this access with minimal effort or skill to carry out a wide range of attacks.		
MITRE ATT&CK	T1566: Phishing T1586: Compromise Accounts M1041: Restrict Access to Network Services		
Evidence			

```

$ swaks --from discott@oui.local --to jthompson@oui.local --server flakemail.oui.local --attach @Release_Statement_0
1182025_new_new.docx --attach-body @body.txt --header "Subject: Release Statement Legal Update"
== Trying flakemail.oui.local:25...
== Connected to flakemail.oui.local.
c- 220 flakemail.oui.local Microsoft ESMTS MAIL Service ready at Sun, 19 Jan 2025 16:53:30 -0500
-> EHLO
c- 250-flakemail.oui.local Hello [10.0.254.206]
c- 250-SIZE 37748736
c- 250-PIPELINING
c- 250-DSN
c- 250-ENHANCEDSTATUSCODES
c- 250-STARTTLS

```

Figure 1 Swaks Anonymous SMTP Example

Remediation

FINALS-XX recommends that OuiCroissant require authentication to send emails through the flakemail SMTP server.

END OF FINDING BLOCK

Insecure Session Management on Administrative Panel

Overview: Insecure Session Management

ΔΔΔΔ Insecure Session Management on Administrative Panel ΔΔΔΔ		CVSS	Risk
Impact	Critical	10.0	Critical
Likelihood	High		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:N		
Affected Scope	10.0.2.5 3000/tcp		
Summary	The web application relies on a client-side JSON local storage object to determine user authentication status. By modifying the "username" field to "admin", an attacker can gain unauthorized administrative access, bypassing server-side authentication controls.		
Technical Impact	The use of client-side storage for authentication allows attackers to easily manipulate the username field and gain elevated privileges without interacting with the server-side authentication logic. This exposes critical functions to unauthorized users.		
Business Impact	This vulnerability allows for unauthorized users to gain full administrative control. This grants access to user information (first name, last name, and email) which is personally identifiable information and exposure can result in reputational damage and regulatory fines. Additionally, the ability to ban users can result in disruption of availability of Y to users.		
Likelihood Description	The vulnerability can be exploited with basic knowledge of browser developer tools, requiring no special skills or interaction from the server. The ease of exploitation results in a high likelihood of occurrence.		
MITRE ATT&CK	- T1556 - Modify Authentication Process - T1078 - Valid Accounts		
Evidence			
1. Visit http://admin.yyy.chat:3000 and use DevTools to inspect the application storage. 2. Modify the "username" local storage object to be 'admin' and refresh the page.			

http://10.0.2.5:3000	
Origin http://10.0.2.5:3000	
Key	Value
chakra-ui-color-mode	light
user	{"username":"admin"}

Figure2 – Shown is the Local Storage Session Identifier Viewed from a Chrome Devtools

Remediation
• Implement server-side session management and authentication controls to validate user credentials on the server. • Avoid relying on client-side mechanisms for authentication and ensure all sensitive operations are protected by server-side enforcement.

END OF FINDING BLOCK

Kerberoastable Service Account

Overview: Kerberos is an authentication protocol widely used in Active Directory environments. It facilitates secure user and service authentication through ticket-granting mechanisms. Service accounts are special users accounts used by applications or services to interact with other resources, such as databases or domain controllers, often requiring elevated privileges to perform their tasks. Service Principal Names (SPNs) are unique identifiers that allow Kerberos to associate a service instance with a service account, enabling clients to request tickets for that service.

Service:

ΔΔΔΔ Kerberoastable Service Account ΔΔΔΔ		CVSS	Risk
Impact	Critical	9.9	Critical
Likelihood	Critical		
CVSS String	AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H		
Affected Scope	Entire oui.local domain 10.0.1.6 (flakead.oui.local) 10.0.1.7 (flakemail.oui.local) 10.0.2.100 (OC-Desktop01.oui.local) 10.0.2.104 (OC-Desktop04.oui.local)		
Summary	A service account (FlakeBook_SSPR) was identified as vulnerable to a Kerberoasting attack. The attacker was able to request a Kerberos service ticket for this account, extract the hash, and crack it offline using Hashcat. This revealed the plaintext password for the service account.		
Technical Impact	The compromised service account credentials could allow an attacker to escalate privileges within the domain or pivot to other sensitive systems. An attacker with these credentials could access services or systems relying on this account. The attacker can now use this access to pivot further on the domain and potentially compromise the entire domain.		
Business Impact	The compromised of a service account linked to critical functions or data could lead to unauthorized access to sensitive systems disrupting operations and exposing data, cause a breach that undermines customer trust and harms OuiCroissant's reputation, and result in legal and regulatory penalties for failing to secure authentication mechanisms.		
Likelihood Description	Exploitation of this vulnerability is highly likely. Kerberoasting attacks are straightforward to execute with minimal requirements, and tools such as Impacket and Hashcat are readily available. Once an attacker has domain user credentials, they can request Kerberos tickets and extract hashes without being detected.		
MITRE ATT&CK	T1558: Steal and Forge Kerberos Tickets T1110:Brute Force M1026:Privileged Accounts Management: Limit service account privileges to the minimum required for their tasks M1027: Password Policies: Enforce strong, unique passwords for all service accounts and rotate them regularly.		
Evidence			

```

[*] Running for 10.0.1.0...
+ ServicePrincipalName Name MemberOf PasswordLastSet Lastlogon Delegation
+ -----
+ SSPR/Flakead FlakeBook_SSPR CN=all,CN=Users,DC=oui,DC=local 2025-01-17 10:55:20.265774 cnevers constrained
+ $krb5tgt$23$*flakeBook_SSPR$OUI.LOCAL$oui.local

[*] Scanned 1 of 1 hosts (100% complete)
[*] Auxiliary module execution completed

```

Figure3 – Kerberoast MSF

```

hashcat -m 13100 -r /usr/share/hashcat/rockyou.txt --stdout -O /usr/share/hashcat/notes/test04.txt
kerberos(1707)flakeBook_SSPR$23$*flakeBook_SSPR$OUI.LOCAL$oui.local

```

Figure4 – Cracking of the Hash.

Remediation

FINALS-XX recommends that OuiCroissant secure the FlakeBook_SSPR service account by configuring a strong, complex password and ensuring all service accounts have unique, regularly rotated passwords. FINALS-XX also recommends that OuiCroissant audit all accounts with the servicePrincipalName attribute and remove it from any accounts not actively required for Kerberos Authentication.

END OF FINDING BLOCK

Unauthenticated Admin API

Overview: The Y admin API lacks proper authentication

ΔΔΔΔ Unauthenticated Admin API ΔΔΔΔ		CVSS	Risk
Impact	Critical	10.0	Critical
Likelihood	Critical		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:L		
Affected Scope	10.0.2.5 7000/tcp		
Summary	The Y "users" API endpoint (/api/users/, /api/users/edit, /api/users/ban) is unauthenticated, allowing non-administrators to view and make changes to Y users.		
Technical Impact	The Y "users" endpoint does not enforce API authentication, allowing a malicious attacker to view all users, view specific users, ban users, and edit user information.		
Business Impact	An unauthenticated attacker can view all Y user metadata, including first name, last name, email address, and whether the user is banned. First name, last name, and email are considered personally identifiable information (PII) which if exposed, can lead to significant regulatory fines and reputational damage.		
Likelihood Description	The likelihood of this vulnerability being exploited is relatively high due to the low attack complexity involved.		
MITRE ATT&CK	T0871 - Execution through API		
Evidence			
1. Browse to http://10.0.2.5:7000/api/users/ on a private browser tab			




Figure5 – Example of the /api/users Endpoint That Lacks Proper Authentication Controls.

Remediation

- All critical operation API endpoints should enforce authentication and authorization via HTTP headers or cookies (JSON Web Tokens, access tokens, etc.) to ensure only allowed users can make requests.

END OF FINDING BLOCK

Stored XSS on Posts

Overview: Stored Cross-Site Scripting on /store/post on yyy.chat

ΔΔΔΔ Stored XSS on Posts ΔΔΔΔ		CVSS	Risk
Impact	Critical	10.0	High
Likelihood	High		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:H/I:H/A:N		
Affected Scope	10.0.1.5 9999/tcp		
Summary	The vulnerability within the /store/post API allows an attacker to inject arbitrary JavaScript code into the post_content field. When other users view the post, the injected code executes in their browsers, potentially leading to session hijacking, data theft, or further attacks on the application.		
Technical Impact	This vulnerability enables attackers to inject and execute arbitrary scripts in the context of other users' browsers. Consequently, malicious code can be used to manipulate the Document Object Model (DOM), steal cookies or session tokens, redirect users to phishing sites, or perform actions on behalf of the user without consent.		
Business Impact	The ability to execute arbitrary JavaScript poses severe risks to user data security and the overall integrity of yyy.chat. This could lead to unauthorized access, data breaches, and loss of user trust, severely affecting the reputation and operational stability of the business.		
Likelihood Description	The likelihood of exploitation is assessed as high due to the ease of detection and exploitation of this vulnerability. An attacker with basic knowledge can identify this issue through normal user interactions on the website, as there are no mitigating controls or protective measures in place on either the client or server side of the application. This lack of safeguards significantly lowers the barrier to entry, making the vulnerability readily exploitable by attackers with sufficient resources.		
MITRE ATT&CK			
Evidence			
1. Create a new post with the following content: <image src=1 href=1 onerror="javascript:alert(document.domain)"></image> 2. Browse to your user profile.			




Figure6 – Shown is an Alert Message Displaying the Associated Domain for the Target Machine in Accordance with the Payload

Remediation


- Deploy a [Content-Security Policy \(CSP\)](#) to limit the sources from which scripts can be loaded and executed.
- Sanitize user input via stripping HTML characters and/or URL encoding posts or use a tested third-party library such as [DOMPurify](#).

END OF FINDING BLOCK

OC-Desktop Unconstrained Delegation

Overview: In Active Directory environments, delegation allows a service or computer to impersonate users to access other services on their behalf. Unconstrained delegation occurs when a computer or service is configured to delegate user credentials without restrictions.

ΔΔΔΔ OC-Desktop Unconstrained Delegation ΔΔΔΔ		CVSS	Risk
Impact	Critical	10.0	Critical
Likelihood	High		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:C/C:H/I:H/A:H		
Affected Scope	Entire oui.local domain 10.0.1.6 (flakead.oui.local) 10.0.1.7 (flakemail.oui.local) 10.0.2.100 (OC-Desktop01.oui.local) 10.0.2.104 (OC-Desktop04.oui.local)		
Summary	FINALS-XX discovered that the system account oc-desktop01\$ is configured with unconstrained delegation rights on the oui.local domain. This configuration allows the system account to impersonate any user on any service, enabling attackers to potentially use the system to escalate privileges and impersonate privileged accounts, such as domain administrators.		
Technical Impact	The misconfiguration of unconstrained delegation exposes Kerberos TGTs of any users who log into or access OC-Desktop01. Attackers who gain control of this host can extract these TGTs and use them to impersonate domain users or administrators. This can lead to complete domain compromise, lateral movement, and privilege escalation.		
Business Impact	The exploitation of unconstrained delegation can result in significant operational disruptions, unauthorized access to sensitive accounts, and exposure of critical data. The compromise of privileged accounts, such as Domain Administrators, can lead to a complete takeover of the domain, jeopardizing the integrity of the organization's IT infrastructure and undermining customer trust. Regulatory penalties may also result from failure to secure sensitive authentication mechanisms.		
Likelihood Description	The likelihood of exploitation is high due to the simplicity of identifying and abusing unconstrained delegation. Tools such as PowerView and Rubeus make this attack accessible to even moderately skilled attackers. If attackers gain control of OC-Desktop, they can trivially extract and reuse TGTs.		
MITRE ATT&CK	T1550: Use Alternate Authentication Material M1026: Privileged Account Management		
Evidence			



END OF FINDING BLOCK

Hardcoded Plaintext Credentials for Y Admin Panel

Overview: Hardcoded credentials within application code expose sensitive information that led to administrative access to Y user management.

ΔΔΔΔ Hardcoded Plaintext Credentials for Y Admin Panel ΔΔΔΔ		CVSS	Risk
Impact	Critical	9.9	Critical
Likelihood	High		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:C/C:L/I:H/A:L		
Affected Scope	10.0.2.5 3000/tcp		
Summary	The presence of hardcoded plaintext credentials in a publicly accessible JavaScript file provides attackers with the means to gain privileged access to the application's administrative interface. This vulnerability can lead to unauthorized control over backend functionalities, exposure of sensitive user data, and potential manipulation of user information.		
Technical Impact	Attackers exploiting this flaw can use the disclosed credentials to impersonate administrative users, making unauthorized changes, accessing sensitive data, and potentially affecting the application's confidentiality, integrity, and availability.		
Business Impact	Exploiting this vulnerability could result in data breaches, loss of service integrity, and significant damage to the company's reputation. Moreover, unauthorized access to sensitive backend systems may expose the organization to legal repercussions and compliance violations.		
Likelihood Description	The likelihood of exploitation is extremely high due to the clear exposure of administrative credentials in a readily accessible JavaScript file. Attackers require no specialized skills to exploit this vulnerability.		
MITRE ATT&CK	- T1078 - Valid Accounts - T1552 - Unsecured Credentials - T0891 - Hardcoded Credentials		
Evidence			
1. Visit http://10.0.2.5:3000 and use DevTools to view static sources 2. View the contents of the 'login.jsx' file			

A screenshot of a code editor interface. The top bar shows three tabs: 'useAuth.jsx', 'ProtectedRoute.jsx', and 'login.jsx' (which is active). The code in 'login.jsx' is as follows:

```
8   const { login } = useAuth();
9   const handleLogin = async (e) => {
10      e.preventDefault();
11      if (username === [REDACTED] && password === [REDACTED]) {
12         await login({ username });
13      } else {
14         alert("Invalid username or password");
15      }
16   };
17   return (
```

The two instances of hardcoded credentials in the if-statement on line 11 are redacted with black boxes.

Figure8 – Shown is the Location Within Login.jsx Where the Hardcoded Credentials Are Present

Remediation

- Remove hardcoded credentials from the login.jsx file and implement a secure credential management system.
- Store sensitive credentials securely using environment variables or secure vaults.

END OF FINDING BLOCK

Unauthorized QR Code Generation for TOTP Setup

Overview: This vulnerability facilitates the generation of secret Time-Based One-Time Password authentication QR codes for any arbitrary user

ΔΔΔΔ Unauthorized QR Code Generation for TOTP Setup ΔΔΔΔ		CVSS	Risk
Impact	Critical	8.8	Critical
Likelihood	Critical		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:H		
Affected Scope	10.0.1.5 9999/tcp		
Summary	This vulnerability enables a malicious actor to generate Time-based One-Time Password (TOTP) QR codes used for TOTP authentication setup on behalf of any user without requiring authentication. By simply sending a request to the /TOTPWithQR endpoint, attackers can exploit this flaw to configure TOTP for legitimate accounts, thereby gaining the ability to intercept TOTP codes and compromise multi-factor authentication protections.		
Technical Impact	The exploitation of this vulnerability allows attackers to create TOTP setups for any account without needing to authenticate. As a result, attackers can receive TOTP codes through the authenticator app associated with the account, effectively circumventing the multi-factor authentication (MFA) protections and gaining unauthorized access to user accounts.		
Business Impact	Unauthorized access resulting from the circumvention of multi-factor authentication (MFA) could lead to the compromise of user accounts on the Y platform. This not only jeopardizes the security of OuiCroissant's customer base but also poses a serious threat to the company's overall reputation.		
Likelihood Description	The likelihood of exploitation is assessed as high due to the lack of authentication controls surrounding the QR code generation process. Attackers require only fundamental knowledge of the API endpoint and face no barriers to repeatedly generate TOTP QR codes. This unrestricted access makes it exceedingly simple for attackers to exploit the vulnerability and compromise user accounts without any hindrances.		
MITRE ATT&CK	- T1078 - Valid Accounts - M1036: Account Use Policies		
Evidence			
1. Make an HTTP request to the QR code generation endpoint with an arbitrary user ID:curl -XPOST "http://10.0.1.5:9999/TOTPWithQR" --data '{"UserID":1}' 2. Convert the base64 to a PNG:echo "iVB..." base64 -d > qr.png			

3. Use 'zbarimg' to decode the QR code and retrieve the otpauth URI: `zbarimg qr.png`
4. Use the otpauth npm package to convert the otpauth URI to a TOTP
5. Login to the target account using the generated TOTP




Figure9 – Arbitrary QR Code Generation for User ID 1

Remediation

It is recommended to implement strict authentication, and authorization checks before allowing QR code generation for TOTP setup to ensure users can request QR codes for only themselves.

END OF FINDING BLOCK

Lack of Host-Based Firewall

Overview: A host-based firewall is a critical security control designed to monitor and restrict incoming and outgoing network traffic based on predefined security rules. It provides an additional layer of defense against unauthorized access and reduces the attack surface of a system.

ΔΔΔΔ Lack of Host-Based Firewall ΔΔΔΔ		CVSS	Risk
Impact	Critical	N/A	Critical
Likelihood	Critical		
CVSS String	N/A		
Affected Scope	Entire oui.local domain • 10.0.1.6 (flakead.oui.local) • 10.0.1.7 (flakemail.oui.local) • 10.0.2.100 (oc-desktop01.oui.local) • 10.0.2.104 (oc-desktop04.oui.local)		
Summary	FINALS-XX identified multiple systems in the environment that do not have host-based firewalls enabled. This misconfiguration can permit unrestricted access to exposed services, significantly increasing the risk of exploitation. Without a firewall, attackers can directly connect to open ports, probe for vulnerabilities, and potentially gain unauthorized access to the systems.		
Technical Impact	The lack of a host-based firewall exposes systems to external and internal attacks. Attackers can scan for and exploit open services or ports without restrictions, bypassing one of the primary layers of network defense.		
Business Impact	The absence of host-based firewalls significantly increases the likelihood of system compromise, data breaches, and operational disruption. Attackers can exploit exposed services, leading to unauthorized access to sensitive data and potentially compromising other systems in the network.		
Likelihood Description	The likelihood of exploitation is extremely high due to the absence of restrictions on inbound and outbound traffic. Tools such as nmap and automated scanners can easily identify and exploit open ports and services on these systems.		
MITRE ATT&CK	T1595: Active Scanning M1037: Filter Network Traffic M1056: Pre-compromise		
Evidence			
Remediation			
FINALS-XX recommends that OuiCroissant enable and configure host-based firewalls on all systems to restrict incoming and outgoing network traffic. FINALS-XX also recommends implementing rules that limit access to critical services and allow traffic only from trusted IP ranges.			

END OF FINDING BLOCK

Lack of Host-Based Defenses

Overview:

ΔΔΔΔ Lack of Host-Based Defenses ΔΔΔΔ		CVSS	Risk
Impact	Critical	N/A	Critical
Likelihood	Critical		
CVSS String	N/A		
Affected Scope	10.0.1.6 (flakead.oui.local) 10.0.1.7 (flakemail.oui.local) 10.0.2.104 (oc-desktop04.oui.local)		
Summary	FINALS-XX identified that multiple systems in the environment that lack host-based defenses. This misconfiguration leaves these systems highly vulnerable to malware infections, unauthorized access, and privilege escalation attacks. Without proper host-based protections, attackers can execute malicious code and maintain persistence with minimal risk of detection.		
Technical Impact	The lack of host-based defenses significantly increases the risk of system compromise. Attackers can exploit these systems without encountering detection or mitigation mechanisms, allowing them to deliver and execute malware, establish persistence, and move laterally within the network. This vulnerability removes a critical layer of defense, leaving the organization reliant solely on network-based security measures.		
Business Impact	The absence of host-based defenses exposes OuiCroissant to significant operational and reputational risk. Malware infection or unauthorized access could disrupt business operations, compromise sensitive data, and damage customer trust. Furthermore, this gap in security could result in non-compliance with industry regulations, leading to financial penalties and legal liabilities.		
Likelihood Description	The likelihood of exploitation is extremely high due to the absence of detection or mitigation mechanisms on these systems. Tools and techniques for delivering malware or executing malicious payloads on unprotected endpoints are readily available and highly effective.		
MITRE ATT&CK	M1049: Antivirus/Antimalware M1050: Exploit Protection		
Evidence			
Remediation			
FINALS-XX recommends that OuiCroissant deploys and configures host-based defenses on all systems, including antivirus software and EDR solutions, to protect against malware and unauthorized access. The latest version of Windows machines come with a built-in, free antivirus called Microsoft Windows Defender.			


END OF FINDING BLOCK

High Findings

Authenticated Users Write Access to DNS Record

Overview: In Active Directory-integrated DNS, permissions on DNS records determine which users or systems can modify them. Improperly configured permissions can allow unauthorized changes to critical DNS entries, disrupting services or enabling attackers to redirect traffic maliciously.

AAA Authenticated Users Write Access to DNS Record AAA		CVSS	Risk
Impact	High	8.1	Medium
Likelihood	Low		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:U/C:N/I:H/A:H		
Affected Scope	10.0.1.6 (flakead.oui.local)		
Summary	FINALs-XX identified that authenticated users have write permissions to a critical DNS record. This misconfiguration allows any domain user to modify or delete the record, potentially redirecting traffic to a malicious destination or disrupting services relying on the affected DNS entry. This creates direct path to privilege escalation and further exploitation.		
Technical Impact	FINALs-XX identified that authenticated users with write access to DNS records can modify critical entries, such as those pointing to domain controllers or key services. This misconfiguration enables attackers to redirect traffic, preform man-in-the-middle (MitM) attacks, or disrupt the availability of essential services. Additionally, modified DNS records can be used to harvest credentials or propagate malware.		
Business Impact	Unauthorized modifications to DNS records pose a significant risk to OuiCroissant's business operations. Traffic redirection could expose a sensitive data, disrupt communications, or enable widespread credential theft. These actions would harm OuiCroissant 's reputation, disrupt business continuity, and result in regulatory non-compliance.		
Likelihood Description	While authenticated users have the necessary permissions to exploit the misconfiguration, identifying the specific record and leveraging the permissions require effort and domain knowledge. This, combined with the relatively uncommon nature of such attacks, results in a medium likelihood.		
MITRE ATT&CK	T1071.004: DNS		
Evidence			



END OF FINDING BLOCK

Insecure Domain Password Policy

Overview: The domain password policy defines the security requirements for user account passwords across the domain. Weak configurations, such as low minimum password length, lack of complexity requirements, or long maximum password ages, significantly increase the risk of unauthorized access through brute force or password-guessing attacks.

△△△ Insecure Domain Password Policy △△△		CVSS	Risk
Impact	Critical	N/A	High
Likelihood	Medium		
CVSS String	N/A		
Affected Scope	Entire oui.local domain 10.0.1.6 (flakead.oui.local) 10.0.1.7 (flakemail.oui.local) 10.0.2.100 (OC-Desktop01.oui.local) 10.0.2.104 (OC-Desktop04.oui.local)		
Summary	FINALS-XX identified that the domain-wide password policy is insecure. The current policy allows passwords as short as 5 characters, enforces no password history, and sets the maximum password age to 60 days. These weaknesses enable attackers to easily guess or brute force credentials and maintain access for extended periods. This creates a significant risk of unauthorized access and privilege escalation.		
Technical Impact	Weak password policies increase the likelihood of unauthorized access through brute force or password-spraying attacks. Attackers can exploit short or simple passwords to gain initial access and escalate privileges within the domain. The absence of password history enforcement allows users to reuse previously compromised passwords, further increasing risk.		
Business Impact	A weak domain password policy undermines OuiCroissant's ability to protect user accounts and sensitive systems. Unauthorized access could result in data breaches, operational disruptions, and loss of trust from stakeholders. Unauthorized access could result in data breaches, operational disruptions, and loss of trust from stakeholders. Regulatory penalties may also result from non-compliance with industry standards for password security.		
Likelihood Description	While password policies that enforce weak settings are easy to exploit with brute force or password-spraying tools, successful exploitation depends on the attacker identifying users with weak or default credentials. This results in medium likelihood rating.		
MITRE ATT&CK	T1110: Brute Force T1078: Valid Accounts M1027: Password Policies M1015: Active Directory Configuration		
Evidence			

Account Policies/Password Policy

Policy	Setting
Enforce password history	0 passwords remembered
Maximum password age	60 days
Minimum password age	0 days
Minimum password length	5 characters
Password must meet complexity requirements	Enabled
Store passwords using reversible encryption	Enabled

*Figure 11 Domain Password Policies***Remediation**

FINAL-XX recommends that OuiCroissant implement a secure domain password policy that enforces industry standard password policies. If possible, rotate all password after disabling reversible encryption.

END OF FINDING BLOCK

Authenticated Users can Add Computers to the Domain

Overview: In Active Directory environments, the ability to add computers to the domain is a sensitive privilege that should be restricted to administrators. When all authenticated users are allowed to join computers to the domain, attackers with low privileges can exploit this configuration to introduce rogue systems, enabling further attacks or persistence.

△△△ Authenticated Users can Add Computers to the Domain △△△		CVSS	Risk
Impact	High	N/A	High
Likelihood	High		
CVSS String	N/A		
Affected Scope	Entire oui.local domain 10.0.1.6 (flakead.oui.local) 10.0.1.7 (flakemail.oui.local) 10.0.2.100 (OC-Desktop01.oui.local) 10.0.2.104 (OS-Desktop04.oui.local)		
Summary	FINALS-XX identified that all authenticated users in the oui.local domain are permitted to add computers to the domain. This misconfiguration allows attackers to register rogue systems, bypassing typical security controls. By introducing rouge devices, attackers can spoof legitimate systems, intercepting traffic, or executing attacks against other domain systems.		
Technical Impact	Allowing authenticated users to add computers to the domain significantly increases the attack surface. Attackers can use this privilege to establish rogue systems with names that impersonate legitimate domain assets, capture credentials, or facilitate lateral movement and privilege escalation.		
Business Impact	Unauthorized domain additions jeopardize OuiCroissant's domain security by introducing uncontrolled devices. Rogue systems can lead to data breaches, disruptions of services, and regulatory penalties for failing to enforce proper access controls. This misconfiguration undermines the integrity and security of the organization's IT environment.		
Likelihood Description	Exploitation of this vulnerability requires domain credentials, which can often be obtained through phishing or other attacks. The ability to add computers is straightforward once an account is compromised, making this a high-likelihood vulnerability.		
MITRE ATT&CK	T1078: Valid Accounts M1026: Privileged Account Management M1015: Active Directory Configuration		
Evidence			
Add workstations to domain		NT AUTHORITY\Authenticated Users	
Figure12 – GPO of Auth Users Add Computer to Domain			
Remediation			
FINALS-XX recommends that OuiCroissant restrict the ability to add computer tot the domain to administrative accounts only. FINALS-XX also recommends auditing existing domain-joined systems to identify and remove any unauthorized devices. Group Policy Objects (GPOs) should be updated to enforce this restriction.			

END OF FINDING BLOCK

Unauthenticated Ollama API

Overview: Unauthenticated Ollama API

△△△ Unauthenticated Ollama API △△△		CVSS	Risk
Impact	Medium	7.5	High
Likelihood	High		
CVSS String	AV:N/AC:L/PR:N/UI:N/S :U/C:H/I:N/A:N		
Affected Scope	10.0.2.5 11434/tcp		
Summary	FINALS-XX discovered that dockercompute-dev.dev.oui.local exposes an Ollama API over port 11434 that lacks authentication		
Technical Impact	Exploitation of this vulnerability would enable attackers the ability to arbitrarily remove, list, and enumerate models present within the ollama instance.		
Business Impact	Successful exploitation of this vulnerability could result in loss of company work related to the use of any local ollama models. Additionally, attackers can enumerate currently running models.		
Likelihood Description	An attacker is very likely to discover this vulnerability and exploit it within the network with simple network scans		
MITRE ATT&CK			
Evidence			
OLLAMA_HOST=10.0.2.5 ollama ls			
Remediation			
The FINALS-XX team recommends implementing API keys to enforce authorization within the network. Additionally, the team recommends limiting API access to only the hosts that need access within the network.			

END OF FINDING BLOCK

Users have Debug Programs Rights on Domain Controller

Overview: The "Debug Programs" user rights allow a user to attach a debugger to any process, including those running under privileged accounts such as SYSTEM. On a Domain Controller, this privilege could be exploited to gain unauthorized access to sensitive processes or escalate privileges, leading to domain compromise.

AAA Users have Debug Programs Rights on Domain Controller AAA		CVSS	Risk
Impact	High	8.6	High
Likelihood	Medium		
CVSS String	CVSS:3.1/AV:N/AC:H/PR:L/UI:N/S:C/C:H/I:H/A:H		
Affected Scope	10.0.1.6 (flakead.oui.local)		
Summary	FINALs-XX identified that standard users on the Domain Controller have the "Debug Programs" user right. This misconfiguration allows attackers to attach a debugger to privileged processes, such as LSASS, to extract sensitive information like NTLM hashes or Kerberos tickets. This leads to direct path to privilege escalation and full domain compromise.		
Technical Impact	The "Debug Programs" privilege enables attackers to interact with or manipulate critical processes on the Domain Controller. Attackers can extract sensitive credentials from LSASS or inject malicious code into running processes, allowing lateral movement, privilege escalation, or persistence. This poses a severe risk to the integrity of the domain.		
Business Impact	Unauthorized access to Domain Controller process undermines the security of the entire domain. The exposure of sensitive credentials, such as those of privileged accounts, could lead to a domain compromise, disrupting business operations, exposing sensitive data, and damaging OuiCroissant's reputation. This configuration could also result in non-compliant with regulatory standards.		
Likelihood Description	While exploitation requires a low-privilege account and the ability to log into the Domain Controller, leveraging the "Debug Programs" privilege demands domain knowledge and specialized tools. This makes exploitation moderately difficult and results in a medium likelihood of occurrence.		
MITRE ATT&CK	T1078: Valid Accounts T1003: OS Credential Dumping M1028: Operating Systems Configuration M1043: Credential Access Protection		
Evidence			
Debug programs	BUILTIN\Administrators, BUILTIN\Users		
Figure 14Debug Programs Evidence			
Remediation			
FINALs-XX recommends that OuiCroissant deploy and configure host-based defenses on all systems, including antivirus software and EDR solutions, to protect against malware and unauthorized access. The latest version of Windows machines come with a built-in, free antivirus called Microsoft Windows Defender.			

END OF FINDING BLOCK

Anonymous LDAP Enabled

Overview: Lightweight Directory Access Protocol (LDAP) is used to query and modify directory services such as Active Directory. When LDAP is configured to allow anonymous access, attackers can query sensitive information about directory structure, users, groups without authentication, increasing the risk of reconnaissance and exploitation.

AAA Anonymous LDAP Enabled AAA		CVSS	Risk
Impact	Low	5.3	High
Likelihood	Critical		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N		
Affected Scope	10.0.1.6 (flakead.oui.local)		
Summary	FINALs-XX identified that the LDAP server on flakead.oui.local is configured to allow anonymous access. This misconfiguration enables unauthenticated users to query directory information, such as usernames, group membership, and organizational structure.		
Technical Impact	Anonymous LDAP access provides attackers with valuable reconnaissance. This can increase the risk of targeted attacks, such as password spraying or phishing, and can aid in privilege escalation by identifying high-value targets or misconfigurations.		
Business Impact	Unauthorized access to directory information poses a significant threat to OuiCroissant's security posture. Attackers could use this data to launch targeted attacks against the organization.		
Likelihood Description	While anonymous LDAP access is straightforward to exploit, its utility depends on the specified data exposed. It is exploitation is moderately likely, as attacker can easily leverage this configuration to gather directory information.		
MITRE ATT&CK	T1087: Account Discovery M1026: Privileged Account Management M1015: Active Directory Configuration		
Evidence			




Figure 15dsHeuristics Values

Remediation


Although Anonymous LDAP may be needed, FINALS-XX recommends OuiCroissant reconfigure infrastructure to allow for the dsHeuristic attribute's seventh digit to be set to 0 instead of 2.

END OF FINDING BLOCK

Insecure Configuration of Domain Computer fsserv

Overview: Constrained delegation gives a user, group, or system the ability to impersonate any user on a specific system and service. The specified service can be manipulated to any potential service name.

△△△ Insecure Configuration of Domain Computer fsserv △△△		CVSS	Risk
Impact	Critical	8.5	High
Likelihood	Low		
CVSS String	CVSS:3.1/AV:N/AC:H/PR:L/UI:N/S:C/C:H/I:H/A:H		
Affected Scope	Entire oui.local domain 10.0.1.6 (flakead.oui.local) 10.0.1.7 (flakemail.oui.local) 10.0.2.100 (OC-Desktop01.oui.local) 10.0.2.104 (OS-Desktop04.oui.local)		
Summary	FINALS-XX identified insecure configuration on the domain controller fsserv.oui.local. These misconfigurations allow attackers to exploit the delegation to the time service synchronization to the domain controller and the overly permissive password change permissions for all users. This directly enables attackers to escalate privileges and achieve full domain compromise by impersonating privileged accounts and controlling critical domain resources.		
Technical Impact	The insecure delegation of time synchronization and universal password change permissions create a direct path to full domain compromise. Attackers can exploit these configurations to impersonate privileged accounts, take control of domain resources, and disrupt organizational operations. Additionally, the ability for all users to change passwords introduces an elevated risk of unauthorized modification to user accounts, further undermining domain security.		
Business Impact	The ability to compromise the entire domain poses an existential risk to OuiCroissant’s infrastructure. Unauthorized access could lead to operational disruptions and data breaches. Full domain compromise would expose sensitive customer data, disrupt business continuity, and result in severe penalties.		
Likelihood Description	The attack vector for this vulnerability involves a complex chain of exploitation steps, including identifying and abusing the delegation of time synchronization and overly permissive password change permissions. While these steps require some level of attacker skill and access, they are achievable with moderate effort and widely available tools, leading to medium likelihood of exploitation.		
MITRE ATT&CK	T1078: Valid Accounts T1556: Modify Authentication Process M1015: Active Directory Configuration		
Evidence			






Figure17 – Everyone Can Change Password

Remediation


FINALIS-XX recommends that OuiCroissant audit the delegation configuration of the fsserv system to ensure it is limited to trusted systems and services. FINALIS-XX also recommends removing the "Change Password" permission from Everyone on the fsserv system to restrict the ability to authorized administrators.

END OF FINDING BLOCK

Authenticated Users Can Enable Per User Reversible Encryption

Overview: Reversible password encryption allows stored users passwords to be decrypted, exposing them in plaintext. This setting can be configured per system or per user.

AAA Authenticated Users Can Enable Per User Reversible Encryption AAA		CVSS	Risk
Impact	Critical	7.7	High
Likelihood	Low		
CVSS String	CVSS:3.1/AV:N/AC:H/PR:H/UI:N/S:C/C:H/I:H/A:N		
Affected Scope	Entire oui.local domain • 10.0.1.6 (flakead.oui.local) • 10.0.1.7 (flakemail.oui.local) • 10.0.2.100 (oc-desktop01.oui.local) • 10.0.2.104 (oc-desktop04.oui.local)		
Summary	FINALS-XX identified that authenticated users in the oui.local domain can enable per-user reversible password encryption. This misconfiguration allows attackers with standard domain user privileges to enable reversible encryption for other users' accounts, potentially exposing their plaintext passwords. This creates a risk of unauthorized access and further privilege escalate.		
Technical Impact	The ability to enable reversible encryption exposes plaintext credentials, significantly increasing the risk of unauthorized access. Attackers can exploit this to harvest credentials, escalate privileges, and compromise sensitive systems or services.		
Business Impact	Attackers can use the exposure of plaintext passwords to access sensitive systems, disrupt operations, and escalate privileges within the domain. This misconfiguration could result in financial penalties and reputational harm.		
Likelihood Description	Exploiting this misconfiguration requires domain user access and knowledge of how to enable and query reversible encryption. It would also require high privileges to access the password hashes.		
MITRE ATT&CK	T1003: Credential Dumping T1552: Unsecured Credentials M1015: Active Directory Configuration M1036: Account Use Policies		
Evidence			



Remediation

FINALs-XX recommends that OuiCroissant remove the "Enable-Per-User-Reversibly-Encrypted-Password" extended right from authenticated users. FINALs-XX also recommends that OuiCroissant audit and disable reversible password encryption for all accounts across the domain.

END OF FINDING BLOCK

Use of Hardcoded Credentials

Overview: Hardcoded credentials are embedded directly into an application. Typically, it is recommended to store it outside of source code, in an environment variable or configuration file.

AAA Use of Hardcoded Credentials AAA		CVSS	Risk
Impact	High	N/A	High
Likelihood	Medium		
CVSS String	CVSS:3.1/AV:L/AC:L/PR:L/UI:N/S:U/C:H/I:H/A:N		
Affected Scope	10.0.2.100 (oc-desktop01.oui.local)		
Summary	FINALS-XX identified the use of hardcoded credentials within the C:\PhishingPoleV3.0.02\PhishingPole.exe application. These credentials include a hardcoded domain name and password, which are accessible to anyone with access to the executable. Attackers who obtain the executable can easily extract these credentials and use them to gain unauthorized access to services or systems.		
Technical Impact	The presence of hardcoded credentials in the PhishingPole.exe executable exposes sensitive information to attackers. With these credentials, attackers can authenticate to services, extract data, and potentially escalate privileges. This creates a high risk of lateral movement, unauthorized access, and further exploitation of sensitive systems.		
Business Impact	The exposure of credentials within the executable compromises OuiCroissant's ability to safeguard its internal systems and sensitive data. Attackers can leverage the hardcoded credentials to bypass authentication and disrupt operations. Regulatory penalties and reputational damage may result from unauthorized access facilitated by this vulnerability.		
Likelihood Description	The likelihood of exploitation is medium, as the credentials are hardcoded in plaintext within the executable. Tools for reverse engineering applications, such as ILSpy, can easily extract sensitive information, making it trivial for attackers to exploit. However, attackers must first gain access to the system to retrieve the binary.		
MITRE ATT&CK	T1552: Unsecured Credentials T1078: Valid Accounts M1041: Encrypt Sensitive Information		
Evidence			
<pre>try { Pop3Client val = new Pop3Client(); try { string domainName = IPGlobalProperties.GetIPGlobalProperties().DomainName; EventLog.WriteEntry(source, "Domain Identified: " + domainName, EventLogEntryType.Information, 101, 1); string text = domainName + "\\DevAutomation"; string text2 = "[REDACTED]"; string text3 = "";</pre>			
Figure 19 – Phishing Pole Password			
Remediation			
FINALS-XX recommends that OuiCroissant refactor the PhisingPole.exe application to remove hardcoded credentials and replace them with a secure credential management			

approach, such as using environment variables or a secrets manager. Additionally, all hardcoded credentials should be rotated immediately, and secure coding practices should be enforced to prevent similar issues in future software development.

END OF FINDING BLOCK

Insecure Lockout Policies

Overview: Account lockout policies are designed to protect against brute force attacks by locking accounts after a specified number of failed login attempts.

AAA Insecure Lockout Policies AAA		CVSS	Risk
Impact	High	N/A	High
Likelihood	High		
CVSS String	N/A		
Affected Scope	Entire oui.local domain 10.0.1.6 (flakead.oui.local) 10.0.1.7 (flakemail.oui.local) 10.0.2.100 (OC-Desktop01.oui.local) 10.0.2.104 (OS-Desktop04.oui.local)		
Summary	FINALS-XX identified that the lockout policy for the oui.local domain is insecure. While the lockout policy threshold is set to 10 invalid attempts, the lockout period is set to 0 minutes. This configuration allows attackers to execute password-spraying or brute force attacks without facing significant restrictions, increasing the risk of unauthorized access.		
Technical Impact	The lack of an effective lockout period enables attackers to continue brute force attempts without significant delays. Weak lockout policies compromise the integrity of the authentication process, increasing the risk of unauthorized access to domain accounts and sensitive systems.		
Business Impact	An insecure lockout policy poses a critical risk to OuiCroissant ability to safeguard user accounts and sensitive data. Unauthorized access could disrupt operations, expose confidential information, and result in reputational damage. Regulatory penalties may also arise due to non-compliance with authentication security standards.		
Likelihood Description	The absence of an effective lockout period and the high threshold for invalid attempts make exploitation highly likely. Attackers can execute brute force or password-spraying with ease, making this a critical security concern.		
MITRE ATT&CK	T1110: Brute Force M1027: Password Policies		
Evidence			
Policy	Setting		
Account lockout duration	0 minutes		
Account lockout threshold	10 invalid logon attempt		
Reset account lockout counter after	0 minutes		
Figure20 – GPO of Insecure Lockout			
Remediation			
FINALS-XX recommends that OuiCroissant implement a secure account lockout policy based on industry standards.			

END OF FINDING BLOCK

Medium Findings

PowerShell Web Access on Domain Controller

Overview: PowerShell Web Access (PSWA) is a feature that provides browser-based access to a PowerShell session on a Windows server. When enabled on a Domain Controller, PSWA introduces significant risks, as it provides an entry point for attackers to execute commands and scripts with elevated privileges.

ΔΔ PowerShell Web Access on Domain Controller ΔΔ		CVSS	Risk
Impact	Medium	4.7	Medium
Likelihood	Medium		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:H/UI:N/S:U/C:L/I:L/A:L		
Affected Scope	10.0.1.6 (flakead.oui.local)		
Summary	FINALS-XX identified that PowerShell Web Access is enabled on the Domain Controller flakead.oui.local. While PSWA requires valid credentials for access, its presence allows attackers with compromised credentials to execute commands, manage Active Directory objects, and escalate privileges. The presence of PSQA on a critical domain asset exposes the domain to unauthorized access and misuse.		
Technical Impact	PowerShell Web Access on a Domain Controller increases the risk of command execution and privilege escalation. Attackers can use this feature, once authenticated, to enumerate domain objects, modify Active Directory configurations and establish persistence with the domain.		
Business Impact	The presence of PSWA on a Domain controller compromises OuiCroissant's domain security by providing attackers with an accessible and versatile entry point. Unauthorized actions could lead to data breaches, operational disruption, and significant regulatory penalties for failing to secure critical domain assets.		
Likelihood Description	While PSWA requires authenticated access, the feature significantly increases the attack surface for compromised user accounts. Attackers can exploit this configuration with moderate effort, making exploitation a medium likelihood.		
MITRE ATT&CK	T1078: Valid Accounts M1042: Disable or Remove Feature or Program		
Evidence			




Figure 21 Powershell Web Access

Remediation

FINALs-XX recommends that OuiCroissant disable PowerShell Web Access on the Domain Controller flakead.oui.local. FINALs-XX also recommends auditing existing PSQA authorization rules and restricting access to trusted administrators if this feature is required for legitimate purposes.

END OF FINDING BLOCK**Remote Image URL allows for Arbitrary File Read**

Overview: The remote image URL functionality is vulnerable to exploitation, allowing attackers to read arbitrary files from the server.

to read arbitrary files from the server.			
ΔΔ Remote Image URL allows for Arbitrary File Read ΔΔ		CVSS	Risk
Impact	Medium	5.9	Medium
Likelihood	Low		
CVSS String	CVSS:3.1/AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:N/A:N		
Affected Scope	10.0.1.5 9999/tcp		
Summary	The remote image URL storage feature can be used with the file:// protocol to save arbitrary files. This, coupled with predictable file ID generation allows for arbitrary file read of files on the filesystem.		
Technical Impact	This vulnerability allows attackers to access and potentially exfiltrate sensitive system files and configuration data, which can include passwords, secret keys, and other protected information, thereby compromising system integrity and confidentiality.		
Business Impact	Access to sensitive configurations and system files could lead to significant data breaches, operational disruptions, and exposure of confidential business information, triggering legal and regulatory ramifications and reputational harm.		
Likelihood Description	Exploiting this vulnerability requires precise timing to align with file ID generation and involves considerable effort in brute-forcing file identifiers, thus reducing the overall likelihood to low.		

MITRE ATT&CK	• T1083 - File and Directory Discovery • T1005 - Data from Local System • M1056 - Data Loss Prevention
Evidence	
1. Upload a normal image through the "Upload File" feature to upload a new image and observe the returned 'id' value. 2. At the same time, use the "Remote URL" upload feature to store an arbitrary file with the 'file://' protocol, such as 'file:///etc/passwd': <curl> 3. Based on the returned 'id' from Step 1, increment the 8th byte by 2 and the 24th byte by 7. Or bruteforce the byte indexes to guarantee a successful prediction: mp64 -l ?dc deadbee?ldeadbeefdeadbe?l?l xargs -I {} curl -f http://yyy.chat/api/upload/?id={} -o {} 4. Based on the predicted file ID, view the arbitrary file by going to http://yyy.chat/api/upload/?id=<predicted value>.	




Figure22 – Viewing the /etc/shadow From the Upload Server.

Remediation

- Disable the ability to use the `file://` protocol within the remote image URL functionality.
- Transition to secure, non-sequential file ID generation methods such as UUIDs to prevent predictable access patterns.
- Implement principle of least privilege by ensuring the process doesn't run as root unless necessary.

END OF FINDING BLOCK

Server-side Request Forgery on Remote Image Profile Picture

Overview: The upload remote image functionality does not implement a whitelist or blacklist, thus allowing for the ability to make HTTP requests to internal services.

△△ Server-side Request Forgery on Remote Image Profile Picture △△		CVSS	Risk
Impact	Medium	5.3	Low
Likelihood	High		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N		
Affected Scope	10.0.1.5 9999/tcp		
Summary	Due to inadequate validation of URLs in the upload remote image feature, an attacker can make arbitrary HTTP requests to internal services by inputting crafted URLs. This could exploit SSRF vulnerabilities, potentially leading to unauthorized access, data exfiltration, or network reconnaissance of internal systems.		
Technical Impact	The unrestricted functionality could allow attackers to leverage SSRF to interact with internal services, bypassing firewalls and gaining access to sensitive internal resources, potentially leading to data leakage or further system compromise.		
Business Impact	Exploiting this vulnerability could result in unauthorized access to internal systems, leading to data breaches, business disruption, and potential reputational damage. Such incidents may also result in non-compliance with data protection regulations.		
Likelihood Description	The likelihood of exploitation is high as the vulnerability can be directly exploited through crafted HTTP requests, enabling attackers to communicate with internal services without additional complex prerequisites.		
MITRE ATT&CK	- T1190 - Exploit Public-Facing Application - M1050: Network Segmentation		
Evidence			
1. Use curl or BurpSuite to craft a POST request to http://10.0.1.5:9999/store/remote_image with a "remote_url" of an internal IP address, such as "127.0.0.1:9999".			

Request

```

1 POST /api/auth/store/remote_image HTTP/1.1
2 Host: yyy.chat
3 Content-Length: 57
4 Accept-Language: en-US,en;q=0.9
5 Accept: application/json, text/plain, */*
6 Content-Type: application/json
7 User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64)
  AppleWebKit/537.36 (KHTML, like Gecko) Chrome/131.0.6770.140
  Safari/537.36
8 Origin: http://yyy.chat
9 Referer: http://yyy.chat/uploadImage
10 Accept-Encoding: gzip, deflate, br
11 Cookie: Authorization=
  [REDACTED]
12
13 CONNECTION: keep-alive
14
15 {
16   "remote_url": "http://127.0.0.1:9999",
17   "poster_id": 889151
18 }

```

Response

```

1 HTTP/1.1 200 OK
2 Access-Control-Allow-Credentials: true
3 Access-Control-Allow-Headers: Content-Type, Content-Length,
  Accept-Encoding, X-CSRF-Token, Authorization, accept, origin,
  Cache-Control, X-Requested-With
4 Access-Control-Allow-Methods: POST, OPTIONS, GET, PUT
5 Access-Control-Allow-Origin: *
6 Content-Length: 2
7 Content-Type: application/json; charset=utf-8
8 Date: Sun, 19 Jan 2025 19:26:47 GMT
9 Server: Caddy
10
11 {
12 }

```

Figure23 – BurpSuite 'repeater' Response of a Successful Response to a Request to the Loopback IP Address.

Remediation


- Implement strict URL validation, including a whitelist of permitted domains or a blacklist of unauthorized targets, to control where HTTP requests may be directed.
- Consider deploying network policies and firewalls to limit internal service access from exposed functionalities.

END OF FINDING BLOCK

Unrestricted Permissions on Shares

Overview: File permissions are in place to allow and restrict users and groups actions on files to what is configured. Best practice recommend that only needed permissions be allowed to needed users.

ΔΔ Unrestricted Permissions on Shares ΔΔ		CVSS	Risk
Impact	Medium	4.3	medium
Likelihood	medium		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:L/UI:N/S:U/C:L/I:N/A:N		
Affected Scope	10.0.1.6 (flakead.oui.local)		
Summary	FINAL-XX has identified that excessive permissions are configured on OuiCroissant's file shares. This misconfiguration allows for Everyone to access any share within the yyyFiles directory.		
Technical Impact	The absence of restriction on permissions allows unauthorized users to read files within the shares.		
Business Impact	Excessive permissions eliminate the authorization process as anyone can access the shares. Depending on the content, this could lead to data leakage.		
Likelihood Description	An attacker would need valid credentials to access the shares.		
MITRE ATT&CK	M1022: Restrict File and Directory Permissions		
Evidence			

*Figure24 – Share Permissions Screenshot***Remediation**


FINALIS-XX recommends that OuiCroissant restrict permissions on shares to only the department OUs that need access.

END OF FINDING BLOCK

Guest Account Enabled

Overview: The Windows Guest account is built-in account designed for temporary access with minimal privileges. However, when enabled, the Guest account can be exploited by attackers to gain unauthorized access to the system without requiring a valid user account.

△△ Guest Account Enabled △△		CVSS	Risk
Impact	Low	N/A	Medium
Likelihood	High		
CVSS String	N/A		
Affected Scope	Entire oui.local domain 10.0.1.6 (flakead.oui.local) 10.0.1.7 (flakemail.oui.local) 10.0.2.100 (OC-Desktop01.oui.local) 10.0.2.104 (OS-Desktop04.oui.local)		
Summary	FINAL-XX identified that the Guest account is enabled on multiple systems in the domain. This configuration provides an entry point for attackers. as the guest account bypasses standard authentication mechanisms and often lacks adequate logging or monitoring. The use of the Guest account increases the risk of unauthorized access and misuse of system resources.		
Technical Impact	An enabled Guest account allows attackers to bypass standard authentication and gain access to the system with minimal privileges. While the account itself is limited, it can be used for reconnaissance, lateral movement, or escalating privileges through misconfigurations.		
Business Impact	The presence of an enabled Guest account weakens the overall security posture of OuiCroissant's system. Unauthorized access could lead to disruptions of services, exposur of non-critical data, and regulatory non-compliance due to inadequate access controls.		
Likelihood Description	Exploiting this vulnerability requires identifying systems with the Guest account enabled, which is achievable with network scanning tools. While the account has limited privileges, its presence increases the attack surface, resulting in a medium likelihood rating.		
MITRE ATT&CK	T1078: Valid Accounts T1087: Account Discovery M1026: Privileged Account Management		
Evidence			



Remediation

FINALIS-XX recommends that OuiCroissant disable the Guest account on all systems where it is not explicitly required. FINALIS-XX also recommends auditing all built-in accounts regularly to ensure they are disabled or configured securely.

END OF FINDING BLOCK

Lack of Active Directory Logon Restrictions

Overview: Active Directory (AD) logon restriction allows administrators to control which control which account can log on to specific systems. Best practices recommended that Domain Administrators should only log on to Domain Controllers, and Domain Users should be restricted from logging on to Domain Controllers. This prevents the compromise of sensitive NTLM hashes and reduces the attack surface for privilege escalation.

ΔΔ Lack of Active Directory Logon Restrictions ΔΔ		CVSS	Risk
Impact	Medium	N/A	Medium
Likelihood	Medium		
CVSS String	N/A		
Affected Scope	Entire Domain		
Summary	FINALS-XX identified that Active Directory lacks adequate logon restrictions, allowing users without administrative roles to log in to sensitive systems, including Domain Controllers. This misconfiguration enables attackers with compromised credentials to gain access to critical systems and potentially escalate privileges or extract sensitive data.		
Technical Impact	The absence of logon restrictions exposes critical systems to unauthorized access by standard domain users. Attackers with compromised credentials can exploit this to log in to sensitive systems, conduct reconnaissance, or execute privilege escalation attacks.		
Business Impact	The lack of Active Directory restrictions compromises OuiCroissant ability to secure its environment. Unauthorized logins could lead to service disruptions, data breaches, and regulatory penalties for failing to enforce adequate access controls.		
Likelihood Description	This configuration requires valid credentials to access the system and opens to further pivoting. With the small amount of surface, this makes it a medium likelihood.		
MITRE ATT&CK	T1078: Valid Accounts M1026: Privileged Account Management M1015: Active Directory Configuration		
Evidence			
Policy	Setting		
Access this computer from the network	Everyone, BUILTIN\Administrators, NT AUTHORITY\Authenticated Users, NT AUTHORITY\ENTERPRISE DOMAIN CONTROLLERS BUILTIN\Pre-Windows 2000 Compatible Access		
Figure26 – GPO Screenshot			
Remediation			
FINALS-XX recommends that OuiCroissant restrict logons on Domain Controllers to only Domain Admins and to restrict Domain Admins logons to only Domain Controllers.			

END OF FINDING BLOCK

Unauthenticated Access to TUI Debug Application

Overview: Unauthenticated Access to TUI Debug Application

ΔΔ Unauthenticated Access to TUI Debug Application ΔΔ		CVSS	Risk
Impact	High	5.3	Low
Likelihood	Critical		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N		
Affected Scope	10.0.2.250 22/tcp		
Summary	The vulnerability allows unauthorized users to access a TUI debug application without authentication. This access provides the ability to execute network diagnostic commands, potentially revealing sensitive information about the network infrastructure and the systems connected to it.		
Technical Impact	By utilizing the debug application, attackers can execute PING, Traceroute, MTR, Open URL, and Netstat commands. This could enable them to gather information about network topology, latency to various hosts, open ports, and services running on systems. Such information could facilitate further attacks or exploitation of network vulnerabilities.		
Business Impact	Allowing unauthorized access to network diagnostic tools increases the risk of information leakage regarding the company's infrastructure. Attackers could gain insights that aid in planning more advanced attacks, jeopardizing sensitive data, and creating liability issues.		
Likelihood Description	It is highly likely that attackers utilize this vulnerability as it simply requires an attempt to connect to this machine over ssh as the root user. No other actions are required to gain access to this debug panel.		
MITRE ATT&CK			
Evidence			
ssh root@10.0.2.250			
Remediation			
FINALIS-XX recommends implementing robust authentication mechanisms for the TUI debug application to restrict access only to authorized users. Additionally, it is crucial to limit the functionality available in the debug application to only those commands necessary for authorized personnel, thereby reducing the risk of information leakage. Regular audits and monitoring for unauthorized access attempts should also be established.			

END OF FINDING BLOCK

Information Disclosure via packages Route

Overview: Information Disclosure via /packages Route

ΔΔ Information Disclosure via packages Route ΔΔ		CVSS	Risk
Impact	Medium	5.3	Low
Likelihood	Critical		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:N/A:N		
Affected Scope	10.0.2.5 • 3000/tcp 10.0.1.5 • 80/tcp		
Summary	The vulnerability allows any user to access the /packages route, exposing information about multiple versions of the company's applications. This can lead to the inadvertent disclosure of version details, dependencies, or even potential vulnerabilities in outdated software.		
Technical Impact	The information disclosed via the /packages route can provide attackers with insights into the application environment, including specific version numbers and configurations. This knowledge may enable them to identify, and exploit known vulnerabilities related to those versions, leading to potential breaches or service disruptions.		
Business Impact	The exposure of application version information poses significant risks to the company's security posture. Attackers could leverage this data to target vulnerabilities effectively, leading to unauthorized access, data breaches, and potential operational disruptions. Furthermore, the breach of sensitive operational information can erode customer trust and subject the company to potential remedial actions or regulatory scrutiny.		
Likelihood Description	This vulnerability exposes the /packages endpoint to all hosts able to visit the web servers and is trivial to discover and exploit		
MITRE ATT&CK			
Evidence			




The screenshot shows a web browser window with the address bar displaying "10.0.2.5:3000/package". The page content is a JSON object representing a package configuration. The browser's address bar shows navigation icons, a "Not secure" warning, and the URL "10.0.2.5:3000/package". The JSON content is as follows:

```

export const name = "admin-web";
export const version = "0.0.0";
export const type = "module";
export const scripts = {
  dev: "vite",
  build: "vite build --emptyOutDir --outDir ../Server/wwwroot/",
  "build-docker": "vite build --emptyOutDir --outDir /app/wwwroot/",
  lint: "eslint .",
  preview: "vite preview"
};
export const dependencies = {
  "@chakra-ui/react": "^2.8.2",
  "@emotion/react": "^11.13.3",
  "@emotion/styled": "^11.13.0",
  axios: "^1.7.7",
  "framer-motion": "^11.5.2",
  react: "^18.3.1",
  "react-dom": "^18.3.1",
  "react-hook-form": "^7.53.0",
  "react-router-dom": "^6.26.1"
};
export const devDependencies = {
  "@eslint/js": "^9.9.0",
  "@types/react": "^18.3.3",
  "@types/react-dom": "^18.3.0",
  "@vitejs/plugin-react": "^4.3.1",
  eslint: "^9.9.0",
  "eslint-plugin-react": "^7.35.0",
  "eslint-plugin-react-hooks": "^5.1.0-rc.0",
  "eslint-plugin-react-refresh": "^0.4.9",
  globals: "^15.9.0",
  vite: "^5.4.1"
};
export default {
  name: name,
  "private": true,
  version: version,
  type: type,
  scripts: scripts,
  dependencies: dependencies,
  devDependencies: devDependencies
};

```

Figure27 – Shown is the Rendered Html Shown When Visiting the Endpoint



```

export const name = "YYY: A social media platform";
export const version = "0.1.1";
export const description = "YYY: A social media platform";
export const productName = "YYY: A social media platform";
export const author = "French Toast";
export const scripts = {
  lint: "eslint --ext .js,.vue ./",
  format: "prettier --write \"**/*.\"{js,vue,scss,html,md,json}\" --ignore-path .gitignore",
  test: "echo \"No test specified\" && exit 0",
  dev: "quasar dev",
  build: "quasar build"
};
export const dependencies = {
  "@fireworks-js/vue": "^2.10.8",
  "@quasar/extras": "^1.16.4",
  "@vuelidate/core": "^2.0.3",
  "@vuelidate/validators": "^2.0.4",
  axios: "^1.7.0",
  "fireworks-js": "^2.10.8",
  quasar: "^2.17.5",
  vue: "^3.4.18",
  "vue-router": "^4.0.12"
};
export const devDependencies = {
  "@quasar/app-vite": "^1.9.0",
  autoprefixer: "^10.4.2",
  eslint: "^8.57.0",
  "eslint-config-prettier": "^8.1.0",
  "eslint-plugin-vue": "^9.0.0",
  postcss: "^8.4.14",
  prettier: "^2.5.1",
  "vite-plugin-checker": "^0.6.4"
};
export const engines = {
  node: "^20 || ^18 || ^16",
  npm: ">= 6.13.4",
  yarn: ">= 1.21.1"
};
export default {
  name: name,
  version: version,
  description: description,
  productName: productName,
  author: author,
  "private": true,
  scripts: scripts,
  dependencies: dependencies,
  devDependencies: devDependencies,
  engines: engines
};

```

Figure28 – Shown is the Rendered Html Shown When Visiting the Endpoint

Remediation

It is recommended any sensitive information contained in this endpoint should either be obfuscated or removed altogether, ensuring that only authorized personnel can access details pertinent to application versions. Regular security assessments should also be conducted to identify and mitigate similar vulnerabilities.

END OF FINDING BLOCK

Low Findings

Lack of Server-side Validation for File Upload Type

Overview: The "Upload File" profile picture functionality on Y only validates image files client-side, allowing for arbitrary files of any type to be uploaded.

Δ Lack of Server-side Validation for File Upload Type Δ		CVSS	Risk
Impact	Low	0.0	Low
Likelihood	Medium		
CVSS String	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:N		
Affected Scope	10.0.1.9		
Summary	The feature for uploading profile pictures does not perform server-side validation, permitting files of any type to be uploaded provided they bypass client-side checks. This insecure configuration could lead to unnecessary file storage or potential misuse.		
Technical Impact	Without server-side validation, non-image files can be uploaded, potentially leading to storage abuse. This could allow for unintended data storage, serve files unintentionally, affect storage resources, or potentially lead to code execution.		
Business Impact	Unnecessary files posing as images could consume storage resources or complicate file handling, leading to inefficiencies and increased operational overhead.		
Likelihood Description	The reliance on client-side validation increases the potential for misuse, though it presents a moderate risk as no immediate exploitability was identified during testing. Any bypass relies only on tampering with client-side checks.		
MITRE ATT&CK	T1036/008 - Masquerade File Type M1040 - Behavior Prevention on Endpoint		
Evidence			
1. Forge an HTTP request using BurpSuite, curl, or another HTTP request crafting tool 2. Modify the "Content-Type", filename, and contents to be that of any other file type (ie: text/plain)			




Figure29 – Uploading a .html File Through the /api/upload Endpoint.

Remediation

Implement methods of file type validation on the backend, such as enforcing "Content-Type", checking magic bytes, or utilizing a library such as pngcheck, jpeginf, etc to validate the file is a valid image.

END OF FINDING BLOCK

Reused JWT ID Claim

Overview: The JWT for Y authentication and authorization reuses the "jti" (JWT ID) claim.

Δ Reused JWT ID Claim Δ		CVSS	Risk
Impact	Low	3.7	Low
Likelihood	Low		
CVSS String	CVSS:3.1/AV:N/AC:H/PR:N/UI:N/S:U/C:N/I:L/A:N		
Affected Scope	yyy.chat		
Summary	The JWT authentication tokens contain a "jti" field, which "provides a unique identifier for the JWT" and must have a "negligible probability that the same value will be accidentally assigned to a different data object" (rfc7519 4.1.7). However, all JWT created within Y reuse the same jti, violating this principal and allowing for possible replay attacks.		
Technical Impact	The non-unique "jti" field compromises the ability to detect and prevent token replay attacks, leading to potential unauthorized access, session hijacking, and exposure of sensitive user or application data.		
Business Impact	If exploited, replay attacks can result in unauthorized data access, potentially leading to data loss, reputational damage, and non-compliance with security standards and regulations regarding token management.		
Likelihood Description	Exploitation is less likely due to the requirement for an attacker to capture a JWT using techniques such as cross-site scripting (XSS) or man-in-the-middle (MITM) attacks, which increases the complexity and reduces the likelihood of successful exploitation.		
MITRE ATT&CK	T1606 - Forge Web Credentials		
Evidence			
1. Decode a user JWT using jwt-decode: <code>echo "eyJ..." jwt decode -</code>			




Figure30 – Local Cyberchef Decoding of a JWT Showing Re-used JTI Across All User Tokens.

Remediation

- Generate a unique "jti" value for each JWT to ensure token uniqueness and to mitigate replay attack risks.
- Implement robust session management practices, including response mechanisms for detected replay attacks.

END OF FINDING BLOCK

Insecure Storage of Cookies

Overview: The 'Authorization' cookie is stored insecurely, lacking 'HttpOnly', 'SameSite', and 'Secure' attributes.

Δ Insecure Storage of Cookies Δ		CVSS	Risk																								
Impact	Low	0.0	Low																								
Likelihood	Low																										
CVSS String	CVSS:3.1/AV:N/AC:L/PR:N/UI:N/S:U/C:N/I:N/A:N																										
Affected Scope	yyy.chat																										
Summary	The absence of critical cookie attributes ('HttpOnly', 'SameSite', 'Secure') for the 'Authorization' cookie compromises its confidentiality and integrity. Without these safeguards, the cookie is vulnerable to theft through XSS, CSRF attacks, and network interception, potentially leading to unauthorized account access.																										
Technical Impact	The 'Authorization' cookie lacks 'HttpOnly', 'SameSite', and 'Secure' attributes. This can lead to potential security risks such as cross-site scripting (XSS) credential stealing, man-in-the-middle (MITM) eavesdropping, and cross-site request forgery (CSRF).																										
Business Impact	If the 'Authorization' cookie is exposed and misused, it could result in unauthorized access to sensitive data, leading to data breaches and reputational harm.																										
Likelihood Description	The likelihood of exploitation is reduced because successful attacks require additional vectors, such as XSS, MITM, or CSRF, increasing the complexity of an attack and thereby reducing the immediate risk.																										
MITRE ATT&CK	• T1539 - Steal Web Session Cookie																										
Evidence																											
1. Access http://yyy.chat and use DevTools to view application storage, and specifically, the "Authorization" cookie.																											
<table><tr><th>Name</th><th>Value</th><th>Do...</th><th>Path</th><th>Expi...</th><th>Size</th><th>Http...</th><th>Sec...</th><th>Se...</th><th>Part...</th><th>Cro...</th><th>Pri...</th></tr><tr><td>Authorization</td><td>eyJ...</td><td>yyy...</td><td>/</td><td>202...</td><td>252</td><td></td><td></td><td></td><td></td><td></td><td>Me...</td></tr></table>				Name	Value	Do...	Path	Expi...	Size	Http...	Sec...	Se...	Part...	Cro...	Pri...	Authorization	eyJ...	yyy...	/	202...	252						Me...
Name	Value	Do...	Path	Expi...	Size	Http...	Sec...	Se...	Part...	Cro...	Pri...																
Authorization	eyJ...	yyy...	/	202...	252						Me...																
Figure31 – Devtools View of Authorization Cookie Lacking Httponly, Samesite, and Secure Attributes.																											
Remediation																											
1. Ensure the 'Authorization' cookie is configured with the 'HttpOnly', 'SameSite=Strict' or 'SameSite=Lax', and 'Secure' attributes, as per Mozilla's Secure Cookie Configuration .																											

END OF FINDING BLOCK

Appendices

Appendix A: Tools

Reconnaissance

R3CON	
Description	URL
R3CON is a collaborative platform developed by FINALS-XX to centralize Nmap scans. FINALS-XX uses R3CON to reduce redundant scans after the reconnaissance phase and organize scan results on a centralized platform.	
Gobuster	
Gobuster is a tool used to brute-force: directories and files in websites, DNS subdomains, Virtual Host names on target web servers, Open Amazon S3 buckets, Open Google Cloud buckets and TFTP servers.	https://github.com/OJ/gobuster
Feroxbuster	
Feroxbuster is used for brute-forcing directories and files using wordlists.	https://github.com/epi052/feroxbuster
Autorecon	
Autorecon is a multi-threaded network reconnaissance tool which performs automated enumeration of services. AutoRecon can perform port scans and directory brute forcing.	https://github.com/Tib3rius/AutoRecon
Nmap	
Nmap uses raw IP packets to determine what hosts are available on the network, what services (application name and version) those hosts are offering, what operating systems (and OS versions) they are running, and what type of packet filters/firewalls are in use.	https://nmap.org/

Exploitation

Metasploit	
Description	URL
Metasploit provides various payloads, exploits, and auxiliary modules to exploit vulnerable versions of services.	https://github.com/rapid7/metasploit-framework
Msfrpc	
Msfrpc assists Metasploit in generating and encoding payloads	https://docs.metasploit.com/docs/using-metasploit/basics/how-to-use-msfrpc.html
Impacket	

Impacket is a collection of Python classes for working with network protocols.	https://github.com/forta/impacket
Swaks	
Swaks is a multi-tool for SMTP testing	https://github.com/jetmore/swaks
SQLMap	
SQLMap is an open-source penetration testing tool that automates the process of detecting and exploiting SQL injection flaws and taking over database servers.	https://github.com/sqlmapproject/sqlmap
NetExec	
NetExec is a network service exploitation tool that helps automate assessing common protocols and services.	https://github.com/Pennyw0rth/NetExec
Hydra	
Hydra is a parallelized login cracker which supports numerous protocols to attack and be used for password spraying.	https://github.com/vanhauser-thc/thc-hydra
Hashcat	
Hashcat is the world's fastest and most advanced password recovery utility, supporting five unique modes of attack for over 300 highly optimized hashing algorithms.	https://hashcat.net/hashcat/
Rubeus	
Rubeus is a C# toolset for raw Kerberos interaction and abuses. It is often used for ASP-REP Roasting attacks.	https://github.com/GhostPack/Ruebus
Python Upload Server	
FINALIS-XX uses a python upload server to upload evidence and tools needed to conduct thorough testing.	https://pypi.org/project/uploadserver/

Post-Exploitation

Evil-WinRM	
Description	URL
Evil-WinRM uses Powershell Remoting protocol to remotely login with to systems with credentials, plaintext or hashes.	https://github.com/Hackplayers/evil-winrm
ILSpy	

An open-source .NET assembly browser and decompiler.	https://github.com/icsharpcode/ILSpy
Bloodhound	
BloodHound uses graph theory to reveal the hidden and often unintended relationships within an Active Directory environment. It can identify attack paths within Active Directory.	https://github.com/BloodHoundAD/BloodHound
Mimikatz	
Mimikatz is used to extract plaintexts, passwords, hash, PIN code and kerberos tickets from memory.	https://github.com/ParrotSec/mimikatz
PEASS-ng	
PEASS-ng is a suite of tools used to search for possible local privilege escalation paths that you could exploit and print them to you with nice colors so you can recognize the misconfigurations easily.	https://github.com/peass-ng/PEASS-ng
adPEAS	
adPEAS is a PowerShell tool to automate Active Directory enumeration. Similar to PEASS-ng tools.	https://github.com/61106960/adPEAS
Certipy	
Certipy is an offensive tool for enumerating and abusing Active Directory Certificate Services.	https://github.com/ly4k/Certipy
PowerUp	
PowerUp targets common Windows privileges escalation vectors that rely on misconfigurations.	https://github.com/PowerShellMafia/PowerSploit/tree/master/Privesc
Seatbelt	

Seatbelt is another privilege escalation tool for Windows that checks for misconfigurations.	https://github.com/GhostPack/Seatbelt
Ligolo-ng	
Ligolo-ng is a simple, lightweight and fast tool that allows penetration testers to establish tunnels from a reverse TCP/TLS connection using a tun interface.	https://github.com/nicocha30/ligolo-ng

Appendix B: Finding Block Legend

The following tables explain the criteria for distinct categories of vulnerability severity, impact, and likelihood, ranging from "Low/None" to "Critical".

Severity Level Explanation

Critical	Vulnerability poses an immediate and significant threat, capable of causing extensive system compromise. It has the potential to lead to significant data breaches, severe operational disruption, or total system control by attackers. Immediate action is required to mitigate.
High	Vulnerability could lead to unauthorized access, data manipulation, or a significant reduction in system availability. Exploiting this vulnerability may not lead to full system compromise but can still result in considerable damage, including partial breaches and operational downtime.
Medium	Vulnerability may allow for limited access or manipulation of data but typically requires chaining with other vulnerabilities to cause significant harm. The issue may affect certain systems or users but does not pose an immediate, widespread threat. Mitigation is necessary, but less urgent compared to critical or high issues.
Low/None	Vulnerability has minimal impact on the system or data security. Exploitation is unlikely to lead to considerable damage or loss, often due to requiring multiple factors to be exploited effectively. These issues are usually more of a nuisance than a real threat but should still be addressed over time.

Impact Level Explanation

Critical	A breach or exploitation would cause catastrophic operational failure, significant economic loss, or severe reputational
-----------------	--

OUI CROISSANT PENTEST REPORT

	damage. This impact could potentially result in long-term damage to the organization.
High	The impact of this vulnerability is considerable, leading to substantial monetary loss or significant reputational damage. While the organization may recover over a reasonable period, it would face a significant hit in terms of customer trust or operational downtime.
Medium	The impact of exploitation may lead to moderate financial losses or operational issues. Reputational damage is limited in scope. The organization can recover, but will need effort to restore confidence or normal operations
Low/None	Exploitation would have minimal effect on operations or reputation. Fiscal impact is either negligible or easily mitigated. The organization can continue functioning with little interruption, and damage control is limited.

Likelihood Level Explanation

Critical	The vulnerability is extremely likely to be exploited in the near term. It is either actively being exploited in the wild or can easily be targeted due to known attack vectors. Exploitation typically requires minimal effort or skill and can have devastating consequences.
High	The vulnerability has a high chance of being exploited, with a known attack method available. It may not be actively targeted yet, but it is highly attractive to attackers. Exploitation would require only moderate effort or resources, making this a significant risk.
Medium	The vulnerability could be exploited, but the likelihood is lower due to the complexity of the attack, the need for insider knowledge, or the need for specific conditions. Exploitations may occur but would typically require some advanced skills or extensive access to the system.
Low/None	The vulnerability is unlikely to be exploited, either because it is difficult to exploit, requires significant expertise, or the attack surface is limited. Exploiting this vulnerability would require extensive resources or knowledge, making it less attractive to most attackers.

Appendix C: Network Inventory

IP Addr.	Hostname	Ports	OS
10.0.1.5	dockercompute.prod.oui.local	22, 80, 3000, 5000, 5432, 8080, 9999	Linux
10.0.1.6	flakead.oui.local	53, 80, 88, 135, 139, 389, 443, 445, 464, 593, 636, 3268, 3289, 3389	Windows

**CONFIDENTIAL
INTERNAL USE ONLY**

10.0.1.7	Flakemail.oui.local	25, 80, 81, 110, 135, 139, 143, 443, 444, 445, 465, 587, 593, 808, 993, 995, 2525, 3389, 3800, 3801, 3828, 5060, 6001, 6580, 6969	Windows
10.0.2.5	Dockercomputer-dev.dev.oui.local	22, 1433, 3000, 7000, 11434	Linux
10.0.2.100	OC-Desktop01.oui.local	135, 139, 445, 3389, 5985, 5986, 47001, 49664, 49665, 49666, 49668, 49669, 49670, 49703, 49704, 49875	Windows
10.0.2.104	OC-Desktop04.oui.local	135, 139, 445, 2121, 3389, 3389, 5985, 5986, 47001, 49664, 49665, 49666, 49668, 49669, 49670, 49703, 49704, 49875	Windows
10.0.2.250	networkdebug.dev.oui.local	22	Linux

Appendix D: Social Engineering Findings

Finals was tasked with reperforming a social engineering attack on OuiCroissant employees to test improvements in defenses and training since the last engagement. Social engineering attacks are manipulative tactics used by malicious actors to try and gain sensitive information or perform malicious actions.

To perform this test, FINALS-XX chose a target based on previous information gained through interactions with OuiCroissant employees. For the subject lines and body content of the emails, we crafted messages that mimicked internal communications. Our team crafted a document that encourages the receiving user to enable macros to "ensure the document opens properly." Once opened, the document would download and execute an undetected reverse shell payload in the background. After the payload was executed, the document would then populate the remaining text to maintain stealth.

Lastly, we utilized swaks to send the emails from the Flakemail.oui.local server (10.0.1.7), ensuring that the headers and content mimicked genuine internal emails to enhance credibility. By analyzing the responses and actions taken by the targets, FINALS-XX aimed to evaluate the effectiveness of OuiCroissant's employee security training and antivirus defense capabilities.

Social Engineering Email

TO	FROM
Jamie Thompson jthompson@oui.local	Devin Scott dscott@oui.local
SUBJECT	
Release Statement Legal Update	

BODY

Hi Jamie,

The legal team reviewed your public statement and have attached requested changes to prevent future lawsuits.

Thanks,
Devin Scott
General Counsel
OuiCroissant

Proof of Exploit

Once our team sent the phishing email, we received a valid shell that was validated by the OuiCroissant security team. Below is a screenshot of the swaks email payload and a screenshot of command execution on the victim system.

```
--# swaks --from dscott@oui.local --to jthompson@oui.local --server flakemail.oui.local --attach @Release_Statement_01182025_new_new.docx --attach-body @body.txt --header "Subject: Release Statement Legal Update"
--- Trying flakemail.oui.local:25...

C:\Users\Administrator\Downloads\phishing>cryptcat.exe -lvnp 443
listening on [any] 443 ...
connect to [10.0.254.106] from (UNKNOWN) [10.0.2.100] 50766
Microsoft Windows [Version 10.0.20348.2582]
(c) Microsoft Corporation. All rights reserved.

C:\PhishingPoleV3.0.02>whoami /all
whoami /all


USER INFORMATION
-----

User Name          SID
-----
oui\devautomation S-1-5-21-2208789051-685350900-1158447217-1217
```


Appendix E: Artificial Intelligence Model Evaluation

During the assessment time, FINALS-XX conducted a comprehensive security assessment of large language models through the ScaleAI testing platform. Each model was designed by OuiCroissant personnel, for specific use cases and were constrained to respect their given parameters. Testing the models emulating threat actors, FINALS-XX was able to in every case break the model's restrictions and produce unwanted/unexpected action. These results are produced by common means of Large Language Model exploitation, often involving "convincing" the model to violate its rules rather than any advanced technical exploitation. This process is often referred to as "Logic Subversion." After bypassing the model's restrictions, the violating statements were documented and submitted to OuiCroissant staff through the ScaleAI web portal.

Turing-Test




Lost in Time




Our Glorious Leader




Voight-Kampff-Test




Password Manager v2



Password Manager v3



Reverse-Turing-Test



Appendix F: Artifacts

Indicators Compromise (IOC)

Filename	SHA256 Hash
adPEAS.ps1	6f919785361c350dd35b21573e02f681806645c50da3e98ddc703d2efa838dd6
reverse.exe	3153a81c1dde42eb793f5c487bf5913f629a9a99cd6c03baa2e2b6115d1ed9e9
mimikatz.exe (mk.exe)	92804faaab2175dc501d73e814663058c78c0a042675a8937266357bcfb96c50
winPEASx64.exe	76fcec2c645144288aa559f25ea7719895b34131bc282f11c539b35a89cacc13
winPEAS.exe	7069adc04720431223902515c7eb66b8a1e431e20ffd66ef3715f41778a1c199
WebBrowserPassView.exe	72c3a786661ee9742cf1d0e3b99b89e976911ed87971695f08487cf42d7fc29d

Additionally, our team created a temporary domain administrator account named "kali". Our teams removed all mentioned IOC artifacts at the end of the engagement.

Compromised Accounts

- All OuiCroissant (oui.local) domain users

CPTC Scoring Team Feedback (AI Generated):

The report was praised for its professional design, clear layout, strong executive summary, effective remediation roadmap, compliance coverage, MITRE ATT&CK mapping, solid business/technical impact separation, and thoughtful features like artifact lists and a well-written introduction. Reviewers, however, noted sparse or missing reproduction steps, unclear or incomplete business impact details in some findings, a disorganized or overly long front section (with fluff that could move to the appendix), non-functional navigation (TOC/hyperlinks), inconsistent severity sorting, and occasional distracting formatting choices. Recommendations included adding a dedicated technical findings summary with prioritized critical issues, strengthening reproduction and remediation details with references, improving narrative coherence in the executive sections (scope, overall risk context), refining formatting (TOC placement, readability, link functionality), and ensuring all client-specific details (logos, language, timelines) are accurate and purposeful.