



## TECHNICAL SPECIFICATIONS

Material	100% recycled polypropylene or virgin polypropylene
Colour	White (virgin) or Grey (recycled)
Grid Dimension (in)	45.3" x 30.7" x 1.4" (1150mm x 780mm x 35mm)
Grid Weight (lbs)	6.4 lbs/m <sup>2</sup> (2.9kg/m <sup>2</sup> )
Cell Shape	Honeycomb
Cell Dimension(in)	2.0" x 1.4" x 0.09" (50mm x 35mm x 2.3mm)
Cell Wall Thickness	0.09" (2.3mm)
Crush Resistance (unfilled)	> 30 700 lbs/sq.ft. (150 tons/m <sup>2</sup> )
Load Bearing Capacity (filled)	> 51 200 lbs/sq.ft. (Over 250 tons/m <sup>2</sup> )
Temperature Range	-52°C to +90°C
Chemical Resistance	Excellent
UV Resistance	Excellent
Suggested Aggregate Size (in)	0.2"-0.6" (5-15mm)

## SUITABLE FOR

Residential parking, driveways, RV parking/access lanes, public pedestrian applications, bicycle trails, slope stabilization, etc.

## CERTIFICATES/COMPLIANT

AFNOR: NF EN ISO 844:2009 (determination of compressive properties).

SGS: ASTM D1621-04A (compressive test standard).

LEED: Used in SUDS and LEED compliant porous paving BMPs for ideal draining and minimal environmental impact.

ADA Compliant: Used in ADA disability compliant surfaces for pedestrians, bicycles, & wheelchair traffic.

Environmentally Approved: Maryland Department of the Environment, Montgomery County, and City of Victoria, British Columbia.

NOW AVAILABLE AT:

**LYNGSØ**

GARDEN MATERIALS, INC.