

Fizzer

New Gray-Box Fuzzer

Martin Jonáš, Jan Strejček, Marek Trtík, <u>Lukáš Urban</u>

Masaryk University


April 11, 2024

```
void main() {
    int x = nondet_int();
    if (x < 42) {
        // branch 1
    } else {
        // branch 2
    }
}</pre>
```

```
bool compare(int v) {
    return v < 42;
void main() {
    int x = nondet_int();
    bool res1 = compare(x);
    \chi++;
    bool res2 = compare(x);
    if (res1 || res2) {
     // branch 1
    } else {
     // branch 2
```

```
bool compare(int v) {
   __instr_abe(1, v < 42, v - 42);
   return v < 42;
void main() {
    int x = nondet int();
    instr call(1);
    bool res1 = compare(x);
    instr return();
   x++;
    instr call(2);
    bool res2 = compare(x);
    instr return();
    if (res1 || res2) {
    // branch 1
   } else {
     // branch 2
```

```
bool compare(int v) {
   __instr_abe(1, v < 42, v - 42);
   return v < 42;
void main() {
    int x = nondet int();
   instr call(1);
    bool res1 = compare(x);
   instr return();
   x++;
   instr call(2);
    bool res2 = compare(x);
   instr return();
    if (res1 || res2) {
    // branch 1
   } else {
     // branch 2
```



1. Sensitivity analysis

- Determine which bytes influence the distance value

- 1. Sensitivity analysis
 - Determine which bytes influence the distance value
- 2. Byteshare analysis
 - Use the input from a different calling context

- 1. Sensitivity analysis
 - Determine which bytes influence the distance value
- 2. Byteshare analysis
 - Use the input from a different calling context
- 3. Gradient descent.
 - Minimize the absolute value of the distance

■ Bronze medal in *Cover-Branches*

- Bronze medal in Cover-Branches
- Highest score in 3 sub-categories
 - ReachSafety-Floats
 - SoftwareSystems-AWS-C-Common-ReachSafety
 - SoftwareSystems-BusyBox- MemSafety