



PT Activity

Packet Tracer - Use a TFTP Server to Upgrade a Cisco IOS Image

Addressing Table

Device	Interface	IP Address	Subnet Mask	Default Gate
R1	G0/0/0	192.168.2.1	255.255.255.0	N/A
R2	G0/0/0	192.168.2.2	255.255.255.0	N/A
S1	VLAN 1	192.168.2.3	255.255.255.0	192.168.2.1
TFTP Server	NIC	192.168.2.254	255.255.255.0	192.168.2.1

Objectives

Part 1: Upgrade an IOS Image on a Cisco Device

Part 2: Backup an IOS Image on a TFTP Server

Scenario

A TFTP server can help manage the storage of IOS images and revisions to IOS images. For any network, it is good practice to keep a backup copy of the Cisco IOS Software image in case the system image in the router becomes corrupted or accidentally erased. A TFTP server can also be used to upgrade the IOS on a router.

Time Elapsed: 00:00:00

Completion: 100%

☐ Top
 ☐ Dock

1/1

Part 1 — Step 1

b. Which IOS images stored on the server are compatible with a 1941 router?

ตอบ:

c1900-universalk9-mz.SPA.151-4.M4.bin
c1900-universalk9-mz.SPA.155-3.M4a.bin

c. Available flash memory ของ R2

ตอบ:

221896413

e. How many IOS images are located in flash?

ตอบ:

2

a. Copy IOS ไป S1

ไม่มีคำถามให้ตอบ แต่ไฟล์ที่ต้องใช้คือ:

c2960-lanbasek9-mz.150-2.SE4.bin

Part 2

a. On R1, display the contents of flash and record the IOS image.

ตอบ:

isr4300-universalk9.03.16.05.S.155-3.S5-ext.SPA.bin