

205 SI

Specifications

Vehicle Identification (VIN prefix)

Manual - VF3 20CBD2

Auto - VF3 20CBD4

Engine

- Transverse 4 cylinder In line Alloy block and head SOHC belt drive

Family	XU5M3Z
Legistative type code	BDY
Capacity (cc)	1580
Bore (mm)	83
Stroke (mm)	73
Compression Ratio	8.95 : 1
Min Octane rating	92 RON unleaded
Max Power	65.5 kW @ 6400 rpm
Max Torque	132 Nm @ 3000 rpm
Liner protusion (mm)	Min: 0,03 Max: 0,10
Max. difference between adjacent liners	0,05 mm
Crankshaft end float	Min: 0,07 Max: 0,27
Cylinder head	
- nominal height	158,93 mm
Max: grinding permissible	0,2 mm
Flatness tolerance	0,05 mm
Valve Clearances (cold)	IN 0,20 mm EX 0,40 mm

Clutch

Pressure plate ref.	200CP4250
Centre plate diameter	200 mm
Control	Cable
Pedal stroke	140 mm

Transmission**Manual**

No of teeth (ratio)	BE3 / 5N
1st.....11x38 (3.45)	Front - 23 mm
2nd.....20x37 (1.85)	7 mm
3rd.....25x32 (1.28)	SAE API GL5 75W 80W – Part No P973358
4th.....32x31 (0.97)	2 litres
5th.....37x28 (0.76)	1.7 +/- 0.75 mm
Rev.....12x40 (3.33)	Front -050° +/- 30°

Final drive	16x63..(3.94)
Speedometer gear	22x20..(0.91)
Gearbox oil	SAE API GL5 75W 80W – Part No P973358
Capacity	2 litres

Automatic

ZF 4HP 14

Ratio's	1st.....0,398
	2nd.....0,701
	3rd.....0,960
	4th.....1,300
	Rev.....0,339

Final drive	17x65..(3.82)
Speedometer gear	22x20..(0.91)

Gearbox oil	Dextron II
Capacity	2.4 litres
– drain & refill	every 20,000k
– after overhaul	6.2 litres

Features

Driving and Safety equipment

- * 2 speed intermittent windscreen wiper
- * 1 speed tailgate wash / wipe
- * Side repeater flashers
- * High mount stop light
- * Rear fog light
- * Long range headlamps
- * Headlamp height adjustment
- * Internally adjustable rear view mirrors
- * Convex passenger door mirror
- * Heated rear screen
- * Tinted glass
- * Tinted front windscreen
- * Child seat anchor points

Instrument cluster – 4 gauges

- speedo
- tachometer
- fuel
- coolant temperature

Warning lights

- charge
- handbrake
- coolant temp.
- low fuel
- lights on
- central warning
- coolant level
- brake pad wear
- oil pressure
- brake fluid level

+ STOP LIGHT

Comfort equipment

- * Central locking doors and tailgate
 - * Lockable fuel filler cap
 - * Front electric windows
 - * Air conditioning
 - * Map reading lamp — IGN ON.
 - * Eurovox coded anti-theft digital AM/FM stereo radio/cassette with 4 speakers
 - * Split fold rear seat
 - * Sports steering wheel
 - * Full centre console
 - * Lockable glovebox
 - * Glovebox illumination
 - * Drivers and passengers side courtesy mirror
 - * Bumper bar insert chrome
 - * Narrow side mouldings
- From DRIVERS DOOR ONLY

Interior Trim

- * Pizano velour
- * Front and rear carpet — loop pile
- * Plastic mat on boot floor
Felt on side panels

Options

- * Metallic paint
- * Glass sunroof
- * Alloy wheels

Anti-corrosion treatment

- * Zinc-plated and galvanised panels in key areas
- * Anti-chipping compound on sills, underbody and wheel arches
- * Epoxy primer applied in Cataphoretic bath
- * Wax injected box panels
- * Clear varnish applied over metallic finishes
- * Final wax / Bitumen underside seal