



```
def store_target(state):
```

```
    ...
    state = execute(flip(state, angle=pi / 2))
    displacement = storage_displacement(state)
    state = execute(press_move(state, displacement=displacement))
    return state
```

 Π

```
def flip(state, angle):
```

```
    def cost(traj):
```

```
        return (
            angle_error(traj[-1], angle)
            + pivot_drift(traj)
            + contact_error(traj[-1], state.fixture)
            + support_violation(traj, state.support)
            + motion_roughness(traj)
        )
```

```
    return local_traj_opt(state, cost)
```

 $P_{i_{k-1}}$

```
def press_move(state, displacement):
```

```
    goal = state.target.position + displacement
```

```
    def cost(traj):
```

```
        return (
            position_error(traj[-1], goal)
            + orientation_error(traj, state.target)
            + tool_contact_loss(traj.moving)
            + support_violation(traj, state.support)
            + motion_roughness(traj)
        )
```

```
    return local_traj_opt(state, cost)
```

 P_{i_k}
 s_{k-1}

```
def storage_displacement(state):
```

```
    axis = along(state.fixture)
    goal_position = corridor(state.obstacle, state.fixture)
    offset = goal_position - state.target.position
    return dot(offset, axis) * axis
```

 c_k
 g_k