

Full Stack AI Software Development


Full-Stack Application Integration

Job Connector Program

Outline

- Set up a full-stack project
- Configure Tailwind
- Configure Postgres + Prisma with migrations
- Implement REST API endpoints in Express.js
- Integrate frontend with Axios and manage state with Zustand

The Tech Stack



Frontend

Vite + React
Tailwind CSS
Zustand
Axios



Backend

Node.js
Express.js
REST API



Database

PostgreSQL
Prisma ORM

High-Level Architecture

This integration follows a classic **Client-Server** model. The frontend handles UI and state, while the backend manages business logic and data persistence.

- **Client:** React app sends HTTP requests via Axios.
- **Server:** Express receives requests and uses Prisma Client.
- **Database:** Postgres stores data, managed by Prisma schema.

Project Initialization (Backend)

Initialize Node

Start by creating a dedicated server directory and initializing a standard Node.js project.

```
mkdir backend && cd backend  
npm init -y
```

Setup TypeScript

Install TypeScript and generate the configuration file to define compilation rules.

```
npm i -D typescript ts-node @type/node nodemon  
npx tsx init
```

Project Structure (Backend)

- **routes, controllers, services, and validators.**
- **config/db.ts** initializes Prisma.
- **server.ts** starts the Express server.
- **app.ts** configures middleware and routing.

```
backend/
├── src/
│   ├── routes/
│   │   ├── user.routes.ts
│   │   └── index.ts
│   ├── controllers/
│   │   └── user.controller.ts
│   ├── services/
│   │   └── user.service.ts
│   ├── validators/
│   │   └── user.validator.ts
│   ├── config/
│   │   ├── env.ts
│   │   └── db.ts          # Prisma client
│   ├── middlewares/
│   ├── utils/
│   ├── types/
│   ├── app.ts
│   └── server.ts
├── prisma/
│   ├── schema.prisma
│   └── migrations/
├── package.json
├── tsconfig.json
├── tsconfig.build.json
├── .env
└── .gitignore
```

Using ExpressJS

Installation

```
npm install express  
npm install -D @types/express
```

Basic Express App



```
// src/app.ts  
import express from "express";  
const app = express();  
  
app.use(express.json());  
export default app;
```



```
// src/server.ts  
import app from "./app";  
app.listen(3000, () => console.log("Server running"));  
.
```

Router Example & NPM Scripts

User Router

```
// src/routes/user.route.ts
import { Router } from "express";
const router = Router();

router.get("/", (_, res) => res.json({ message: "All
  users" }));
router.post("/", (req, res) => res.json({ created: req
  .body }));

export default router;
```

NPM Scripts

```
"scripts": {
  "dev": "nodemon src/server.ts",
  "build": "tsc",
  "start": "node dist/server.js"
}
```



Connecting to Database

Install Prisma & PostgreSQL Client

```
npm install prisma --D  
npm install @prisma/client  
npx prisma init
```

<https://www.prisma.io/docs/getting-started>

Setup Prisma Config



```
import "dotenv/config";  
import { defineConfig, env } from "prisma/config";  
  
export default defineConfig({  
  schema: "prisma/schema.prisma",  
  migrations: {  
    path: "prisma/migrations",  
  },  
  datasource: {  
    url: env("DATABASE_URL"),  
  },  
});
```

Define Prisma Model

Define Prisma Model

```
generator client {  
  provider = "prisma-client"  
  output   = "./generated"  
}  
  
datasource db {  
  provider = "postgresql"  
}  
  
model User {  
  id      Int      @id @default(autoincrement())  
  name    String  
  email   String   @unique  
}
```

Run Migration

```
npx prisma migrate dev --name init
```

Using Prisma in Controller

Setup Prisma Client

```

// src/config/db.ts
import { PrismaClient } from "@prisma/client";

const prisma = new PrismaClient();
export default prisma;
```

Using Prisma in Controller / Service

```

// src/controllers/user.controller.ts
import { Request, Response } from "express";
import prisma from "../config/db";

export const getUsers = async (_, res: Response) => {
  const users = await prisma.user.findMany();
  res.json(users);
};

export const createUser = async (req: Request, res: Response) => {
  const { name, email } = req.body;

  const user = await prisma.user.create({
    data: { name, email }
  });

  res.json(user);
};
```

Setup Router for API

Routes for User API

```
● ● ●
// src/routes/user.route.ts
import { Router } from "express";
import { getUsers, createUser } from "../controllers/user.controller";

const router = Router();

router.get("/", getUsers);
router.post("/", createUser);

export default router;
```

Add Routes to Express App

```
● ● ●
// src/app.ts
import express from "express";
import userRouter from "../routes/user.route";

const app = express();
app.use(express.json());
app.use("/users", userRouter);

export default app;
```

Project Initialization (Frontend)

Scaffold with Vite

Use Vite's creation tool to bootstrap a new React application. We explicitly select the React-TS template.

```
npm create vite@latest frontend -- --template react-ts  
cd frontend
```

Install & Run

Install the default dependencies and start the development server to verify the setup.

```
npm install  
npm run dev
```

<https://vite.dev/guide/>

Project Structure (Frontend)

- **src/pages:** Route-level views.
- **src/components:** Reusable UI elements.
- **src/store:** Global Zustand state.
- **src/hooks:** Custom React hooks.

```
frontend/  
├── src/  
│   ├── assets/  
│   ├── components/  
│   ├── hooks/  
│   ├── pages/  
│   ├── store/           # zustand  
│   ├── services/       # axios API calls  
│   ├── utils/  
│   ├── types/  
│   ├── App.tsx  
│   ├── main.tsx  
│   └── vite-env.d.ts  
├── public/  
├── index.html  
├── tsconfig.json  
├── vite.config.ts  
├── package.json  
└── .env
```

Styling with Tailwind

Installation

Install Tailwind CSS and its peer dependencies via npm, then generate the configuration files.

```
npm install tailwindcss @tailwindcss/vite
```

<https://tailwindcss.com/docs/installation/using-vite>

Configuration

Point Tailwind to your template files in **vite.config.ts** and add the directives to your main CSS file.

```
// vite.config.ts
import { defineConfig } from "vite";
import react from "@vitejs/plugin-react";
import tailwindcss from "@tailwindcss/vite";

// https://vite.dev/config/
export default defineConfig({
  plugins: [react(), tailwindcss()],
});
```

```
/* index.css */
@import "tailwindcss";
```

State with Zustand

Zustand provides a minimal API to manage global state. Create a store hook that can be accessed from any component.

This eliminates "**prop drilling**" and makes managing user sessions or fetched data significantly cleaner.

Installation

```
npm install zustand
```


State with Zustand

Create Store

```

// src/stores/useCounterStore.ts
import { create } from "zustand";

interface CounterState {
  count: number;
  increase: () => void;
  decrease: () => void;
}

export const useCounterStore = create<CounterState>((set) => ({
  count: 0,
  increase: () => set((s) => ({ count: s.count + 1 })),
  decrease: () => set((s) => ({ count: s.count - 1 })),
}));
```

Use in Component

```

// App.tsx
import { useCounterStore } from "../stores/useCounterStore";

function App() {
  const { count, increase, decrease } = useCounterStore();

  return (
    <>
      <h1>{count}</h1>
      <button onClick={increase}>+</button>
      <button onClick={decrease}>-</button>
    </>
  );
}
```

Connecting Frontend to Backend

Install Axios in Frontend Project

```
npm install axios
```

Create API Wrapper



```
// src/utils/api.ts  
import axios from "axios";  
  
export const api = axios.create({  
  baseURL: "http://localhost:3000",  
});
```

Connecting Frontend to Backend

API Call Service

```
// src/services/user.service.ts
import { api } from "../utils/api";

export const getUsers = async () => {
  const res = await api.get("/users");
  return res.data;
};

export const createUser = async (data: { name: string; email: string }) => {
  const res = await api.post("/users", data);
  return res.data;
};
```

Use in React Component

```
// src/App.tsx
import { useEffect, useState } from "react";
import { getUsers } from "../services/user.service";

function App() {
  const [users, setUsers] = useState([]);

  useEffect(() => {
    getUsers().then(setUsers);
  }, []);

  return (
    <div>
      <h1>Users</h1>
      {users.map((u) => (
        <p key={u.id}>{u.name}</p>
      ))}
    </div>
  );
}

export default App;
```

CORS Setup on Backend

Install cors

```
npm install cors  
npm install @types/cors -D
```

Add in Express



```
// src/app.ts  
import express from "express";  
import cors from "cors";  
const app = express();  
  
app.use(express.json());  
app.use(cors({ origin: "http://localhost:5173" })); // frontend  
  
export default app;
```

Exercise

Build a simple User Management App (CRUD) with a connected frontend and backend

- Backend: Express + TypeScript, Prisma ORM, PostgreSQL database, REST API (GET /users, POST /users).
- Frontend: Vite + React + TypeScript, Axios for API calls, UI to list and add users.
- Database: User model with id, name, email (unique).
- Connection: CORS enabled or Vite proxy; Axios baseURL set to backend.
- Output: Working CRUD flow, form submission creates user → saved in Postgres → auto-refresh list on UI.

Thank you

