Spectral Inconsistency Entropy: Distinguishing Local from Systemic Contradictions in Pairwise Comparison Graphs

Thomas Nauheimer
Independent Researcher (nauheimer.t@gmail.com)
November 2026

Abstract. *Pairwise comparison data—arising in sports rankings, autonomous sensor fusion, peer review, and RLHF preference modeling—frequently exhibits cyclic inconsistencies. While classical combinatorial Hodge theory (HodgeRank) quantifies the total magnitude of inconsistency via the cyclic residual ratio $\rho(G, w) = ||r||^2 / ||w||^2$, it is invariant to how contradictions are topologically distributed across the comparison network. We introduce* ***Spectral Inconsistency Entropy (H)****, a scale- and potential-invariant diagnostic defined as the Shannon entropy of the cyclic residual's energy projection across the distinct eigenspaces of the cycle-restricted 1-up-Laplacian $L_Z = Z^T B_1 B_1^T Z$. We prove four results: (1)* ***Universal Clique Degeneracy (Theorem 1):*** *By the simplicial Eckmann identity $B_0^T B_0 + B_1 B_1^T = n I_{|E|}$ on the clique 2-complex of K_n, $L_Z = n I_{\beta_1(K_n)}$ has a single eigenvalue $\lambda = n$ of multiplicity $(n-1)(n-2)/2$ for all $n \geq 3$, so $H(K_n, w) \equiv 0$ identically. (2)* ***Harmonic–Curl Separation & Scale Invariance (Theorem 2):*** *The $\lambda = 0$ eigenspace of L_Z is canonically isomorphic to $H^1(K_2(G)) = \ker(B_0) \cap \ker(B_1^T)$, while $\lambda > 0$ eigenspaces span $\mathrm{im}(B_1)$, and $H(G, B_0^T s + \alpha \delta) = H(G, \delta)$ for all s and $\alpha \neq 0$. (3)* ***Exact Isotropic Dirichlet–Digamma Asymptote (Theorem 3):*** *Under isotropic Gaussian cycle noise $c \sim N(0, \sigma^2 I_{\beta_1})$, the eigenspace energies follow Dirichlet$(d_1/2, ..., d_{|\Lambda|}/2)$ with closed-form expected entropy $H_{iso}(G)$. (4)* ***Empirical & Structural Boundaries:*** *Across 1,000 Monte Carlo trials per edit distance k on $G(15, 0.4)$, $H(G, w)$ grows monotonically from $k=1$ (3.7641 ± 0.0394 bits) to the exact Dirichlet–Digamma asymptote $H_{iso} = 4.1175$ bits (4.1274 ± 0.0124 bits at $k=40$), while cycle-leverage cosine alignment localizes single corrupted edges with 91.3%–100.0% Top-1 accuracy across five canonical graph families.*

1. Introduction and Mathematical Framework

Given a comparison graph $G = (V, E)$ with $|V| = n$ and $|E| = m$, an antisymmetric edge flow $w \in R^m$ is consistent if and only if $w = B_0^T s$ for a scalar node potential $s \in R^n$. Combinatorial Hodge theory (Jiang et al., 2011) decomposes R^m orthogonally into gradient flows $\mathrm{im}(B_0^T)$, triangular curl flows $\mathrm{im}(B_1)$, and harmonic 1-forms $H^1(K_2(G)) = \ker(B_0) \cap \ker(B_1^T)$. While the classical inconsistency index $\rho(G, w) = ||r||^2 / ||w||^2$ measures total cyclic energy, it confounds the ground-truth potential scale $||B_0^T s^*||^2$ with the fault topology and cannot distinguish a single faulty sensor (L_0 edit distance $k = 1$) from systemic network-wide noise.

Let $Z \in R^{|E| \times \beta_1(G)}$ be an orthonormal basis of the cycle space $Z = \ker(B_0)$, where $\beta_1(G) = |E| - |V| + c(G)$. Restricting the 1-up-Laplacian $L_1^{up} = B_1 B_1^T$ to Z yields the positive semi-definite operator $L_Z = Z^T B_1 B_1^T Z$. Let $\Lambda(G)$ be its distinct eigenvalues with multiplicities d_λ and orthogonal eigenspace projectors P_λ. For $c = Z^T w \neq 0$, the spectral energy fractions and Spectral Inconsistency Entropy are:

$$p_\lambda(G, w) = ||P_\lambda c||^2 / ||c||^2, \qquad H(G, w) = -\Sigma_{\lambda \in \Lambda(G)} p_\lambda(G, w) \log_2 p_\lambda(G, w) \in [0, \log_2 |\Lambda(G)|].$$

2. Main Theoretical Results

Theorem 1 (Universal Clique Degeneracy via Eckmann Identity). *For every complete graph K_n ($n \geq 3$), the 1-Hodge Laplacian on the clique 2-complex satisfies $B_0^T B_0 + B_1 B_1^T = n I_{|E|}$. Consequently, $L_Z = n I_{\beta_1(K_n)}$ with $\beta_1(K_n) = (n-1)(n-2)/2$ and a single eigenvalue $\lambda = n$. Therefore, $H(K_n, w) \equiv 0$ identically for all $n \geq 3$ and all flows w.*

Proof. Every edge $e = (u, v)$ in K_n has 2 endpoints and belongs to $n - 2$ triangles, giving diagonal entries $2 + (n - 2) = n$ in $B_0^T B_0 + B_1 B_1^T$. Disjoint edges share neither vertices nor triangles (off-diagonal 0). Two edges sharing one vertex have +1 in $B_0^T B_0$ and -1 in $B_1 B_1^T$ from their unique common triangle, canceling to 0. Since $B_0 Z = 0$, restricting to Z gives $L_Z = n I_{\beta_1(K_n)}$, so $|\Lambda(K_n)| = 1$ and $H(K_n, w) = 0$. Q.E.D.

Theorem 2 (Harmonic–Curl Separation & Scale/Potential Invariance). *(1) The $\lambda = 0$ eigenspace of L_Z maps via Z isomorphically onto $H^1(K_2(G)) = \ker(B_0) \cap \ker(B_1^T)$ (global non-triangular cycles of length ≥ 4), while $\oplus_{\lambda>0} V_\lambda$ maps onto $\mathrm{im}(B_1)$. (2) For any node potential $s \in R^{|V|}$, perturbation $\delta \notin \mathrm{im}(B_0^T)$, and $\alpha \neq 0$, $H(G, B_0^T s$*

$+ \alpha \delta) = H(G, \delta)$.

Theorem 3 (Exact Isotropic Dirichlet–Digamma Asymptote). *Under isotropic Gaussian cycle noise $c \sim N(0, \sigma^2 I_{\beta_1(G)})$, the squared projections $||P_\lambda c||^2 \sim \sigma^2 \chi^2_{d_\lambda}$ induce $(p_\lambda) \sim Dirichlet(d_1/2, ..., d_{|\Lambda|}/2)$ with exact expected entropy:*

$$H_{iso}(G) = (1 / \ln 2) \Sigma_{\lambda \in \Lambda(G)} (d_\lambda / \beta_1(G)) [\psi(\beta_1(G)/2 + 1) - \psi(d_\lambda/2 + 1)] \leq H_{sys}(G) = - \Sigma (d_\lambda / \beta_1) \log_2(d_\lambda / \beta_1).$$

3. Empirical Validation and Cross-Topology Regimes

On Erdős–Rényi G(15, 0.4) (seed=42, |V|=15, |E|=49, |T|=50, β_1=35, |Λ|=35), Theorem 3 predicts $H_{iso}(G) = (\psi(18.5) - \psi(1.5))/\ln 2 = 4.1175$ bits (Jensen bound $H_{sys} = \log_2(35) = 5.1293$ bits). Across 1,000 Monte Carlo trials per L_0 edit distance k, H(G, w) increases strictly monotonically toward $H_{iso}(G)$:

L0 Edit Distance (k)	Mean H(G, w) +/- 95% CI (bits)	Std H (bits)	Mean rho(G, w)	Top-1 Fault Loc.
1	3.7641 +/- 0.0394	0.6363	0.1217	100.0%
2	3.8806 +/- 0.0275	0.4432	0.2174	—
3	3.9308 +/- 0.0233	0.3765	0.2839	—
4	3.9459 +/- 0.0200	0.3235	0.3387	—
5	3.9826 +/- 0.0179	0.2889	0.3845	—
6	3.9928 +/- 0.0186	0.3001	0.4186	—
9	4.0308 +/- 0.0152	0.2445	0.4939	—
14	4.0795 +/- 0.0142	0.2288	0.5581	—
20	4.0925 +/- 0.0137	0.2203	0.5986	—
30	4.0965 +/- 0.0130	0.2098	0.6360	—
40	4.1274 +/- 0.0124	0.2007	0.6540	—

Comparing five graph families illustrates the structural regimes of H(G, w) alongside our cycle-leverage cosine localizer $\text{argmax}_j |\langle Z^T w, Z^T e_j \rangle| / (||Z^T w|| \, ||Z^T e_j||)$:

Network Topology	|V|	|E|	beta_1	|Lambda|	H(k=1)	H_iso	H_sys	Top-1 Loc.
Complete Graph K_8	8	28	21	1	0.0000	0.0000	0.0000	100.0%
Modular League (4x5 Caveman)	20	40	20	5	0.4809	1.4392	1.6710	97.4%
Small-World Tournament (NWS 16)	16	45	30	26	2.9614	3.6453	4.5199	100.0%
Erdos-Renyi G(15, 0.4)	15	49	35	35	3.7512	4.1175	5.1293	100.0%
Triangular Sensor Grid (4x4)	12	23	12	10	2.7750	2.4634	3.2516	91.3%

Structural Takeaway. In modular and heterogeneous comparison graphs (Modular League, Small-World Tournament, Erdős–Rényi), localized cycle modes ensure $H(k=1) < H_{iso}(G) < H_{sys}(G)$, providing a sharp diagnostic separation between single bad actors and systemic noise. On regular lattices (Triangular Sensor Grid), delocalized Bloch waves spread a single-edge delta spike across frequencies ($H(k=1) = 2.7750 > H_{iso} = 2.4634$ bits due to Porter–Thomas χ^2_1 fluctuations in single Gaussian realizations, while still respecting the Jensen bound $H_{sys} = 3.2516$ bits). Pairing H(G, w) with cycle-leverage cosine alignment yields both regime diagnosis and 91.3%–100.0% single-fault localization across all topologies.