

Assignment 3

Information Retrieval

CS 834

Fall 2017

Mohammed Nauman Sididque

November 9, 2017

# Contents

<b>1</b>	<b>Problem 6.2</b>	<b>4</b>
1.1	Problem Statement . . . . .	4
1.2	Solution . . . . .	4
1.2.1	Noisy Channel Model . . . . .	4
1.2.2	Steps for generating the predicted correct word using Noisy Channel Model . . . . .	13
1.2.3	Assumptions . . . . .	14
1.2.4	Outputs . . . . .	14
<b>2</b>	<b>Problem 6.4</b>	<b>16</b>
2.1	Problem Statement . . . . .	16
2.2	Solution . . . . .	16
2.2.1	Assumption about the Location Gazetteer . . . . .	16
2.2.2	Description of the Algorithm . . . . .	17
<b>3</b>	<b>Problem 6.5</b>	<b>23</b>

3.1	Problem Statement . . . . .	23
3.2	Solution . . . . .	23
3.2.1	Description of Galago Snippet Algorithm . . . . .	24
3.2.2	Little Text Content Problem . . . . .	26
3.2.3	Improvements to the Algorithm . . . . .	27
<b>4</b>	<b>Problem 6.9</b>	<b>28</b>
4.1	Problem Statement . . . . .	28
4.2	Solution . . . . .	28
4.2.1	Aaj Tak Website . . . . .	29
4.2.2	Aaj Tak News . . . . .	29
4.2.3	Dainik Bhaskar . . . . .	30
4.2.4	Urdu Newspaper . . . . .	30
4.2.5	Urdu Newspaper from Pakistan . . . . .	30
4.2.6	Possible reason for Wrong Translation . . . . .	31
<b>5</b>	<b>Problem 7.2</b>	<b>35</b>
5.1	Problem Statement . . . . .	35
5.2	Solution . . . . .	35
<b>6</b>	<b>Problem 7.7</b>	<b>40</b>
6.1	Problem Statement . . . . .	40
6.2	Solution . . . . .	40

<b>7</b>	<b>Problem MLN1</b>	<b>43</b>
7.1	Problem Statement . . . . .	43
7.2	Solution . . . . .	43
7.2.1	Description of Code . . . . .	43
7.2.2	Results . . . . .	51
<b>8</b>	<b>Problem MLN2</b>	<b>52</b>
8.1	Problem Statement . . . . .	52
8.2	Solution . . . . .	52
8.2.1	Description of Code . . . . .	52
8.2.2	Results . . . . .	61

# Chapter 1

## Problem 6.2

### 1.1 Problem Statement

Create a simple spelling corrector based on the noisy channel model. Use a single-word language model, and an error model where all errors with the same edit distance have the same probability. Only consider edit distances of 1 or 2. Implement your own edit distance calculator (example code can easily be found on the Web).

### 1.2 Solution

#### 1.2.1 Noisy Channel Model

This problem has been solved using Wiki small dataset provided by the text book. Initially we need to find the words in the corpus. The corpus contains 3902115 words of which 225744 are unique. The output of the total words is in file “word\_list.txt” which has been added to

the Assignment3 folder of Github.

Code parsing out words from the wiki small dataset

```
1  '''
2  Created on Nov 7, 2017
3
4  @author: nauman
5  '''
6  import os
7  from bs4 import BeautifulSoup
8  import codecs
9  from string import punctuation
10 import re
11
12 def RepresentsInt(s):
13     try:
14         int(s)
15         return True
16     except ValueError:
17         return False
18
19 ## Calculate Words in wiki small dataset
20 def createDictionary():
21     file_write=codecs.open("word_list.txt","w","utf-8")
22     exclude = set(punctuation)
23     doc_count = 0
```

```

24     for root, dirs, files in os.walk("F:\Fall2017\InformationRetreival\
Assignment2\en"):
25         for file in files:
26             if file.endswith(".html"):
27                 with codecs.open(root+"\\" + file, "r", "utf-8") as file_open:
28                     doc_count = doc_count + 1
29                     count = 0
30                     soup = BeautifulSoup(file_open, 'html.parser')
31                     for words in soup.findAll(text=True):
32                         if words.parent.name in ['style', 'script', 'head', '
title', 'meta', '[document]']:
33                             continue
34
35                     s = ''.join(ch for ch in str(words) if ch not in
exclude)
36                     words = s.split(" ")
37                     for word in words:
38                         count = count+1
39                         if not RepresentsInt(word.rstrip()):
40                             if re.search('[a-zA-Z]', word.rstrip()):
41                                 file_write.write(word.rstrip().lower())
42                                 file_write.write("\n")
43
44     file_write.close()
45     print("WordsOver")

```

The next step was to find the unique words of from the list of total words. I used unix commands as mentioned below:

```
1 $ sort word_list.txt | uniq -c > word_list_unique.txt
```

This command sorts my word\_list file and counts all the unique words to save it to the file word\_list\_unique.txt

```
1 $ awk '{print $1}' word\_list\_unique.txt > word_list_unique_frequency.txt
```

This command cuts the frequency of unique words from word\_list\_unique.txt and saves to word\_list\_unique\_frequency.txt

```
1 $ awk '{print $2}' word_list_unique.txt > word_list_unique_.txt
```

This command cuts the unique words listed from word\_list\_unique.txt and saves to word\_list\_unique\_.txt

The above two files were then used by the code to save them to lists.

```
1 '''
2 Created on Nov 7, 2017
3
4 @author: nauman
5 '''
6 import pickle
7 import codecs
8
9 def countWordFrequency():
10     file = codecs.open("word_list.txt", "r", "utf-8")
11     file_unique = open("word_unique.pkl", "w")
12     file_frequency = open("word_frequency.pkl", "w")
```



```

13     word = []
14     frequency_word = []
15     for line in file:
16         if line in word:
17             index = word.index(line)
18             temp = frequency_word[index]
19             frequency_word[index] = (temp+1)
20         else:
21             word.append(line.rstrip())
22             frequency_word.append(1)
23     print(line)
24     file.close()
25     file_unique.write(pickle.dumps(word))
26     file_frequency.write(pickle.dumps(frequency_word))
27     file_unique.close()
28     file_frequency.close()
29
30 #countWordFrequency()
31
32 def writeToList():
33     file_unique = open("word_unique.pkl", "w")
34     file_frequency = open("word_frequency.pkl", "w")
35     file_word = open("word_list_unique.txt", "r")
36     file_frequency1 = open("word_list_unique_frequency.txt", "r")
37     word = []
38     frequency = []

```

```

39     for line in file_word:
40         word.append(line.rstrip())
41     for line in file_frequency1:
42         frequency.append(line)
43     file_unique.write(pickle.dumps(word))
44     file_frequency.write(pickle.dumps(frequency))
45     file_unique.close()
46     file_frequency.close()
47
48 writeToList()

```

In calculating edit distance between strings insertion, deletion and replace have been considered. Transformation has not been implemented.

Code for calculating edit distance between two strings.

```

1  '''
2  Created on Nov 7, 2017
3
4  @author: nauman
5  '''
6
7  def editDistDP(str1, str2, m, n):
8
9      # Create a table to store results of subproblems
10     dp = [[0 for x in range(n+1)] for x in range(m+1)]
11
12     # Fill d[][] in bottom up manner

```

```

13     for i in range(m+1):
14         for j in range(n+1):
15
16             # If first string is empty, only option is to
17             # insert all characters of second string
18             if i == 0:
19                 dp[i][j] = j    # Minimum operations = j
20
21             # If second string is empty, only option is to
22             # remove all characters of second string
23             elif j == 0:
24                 dp[i][j] = i    # Minimum operations = i
25
26             # If last characters are same, ignore last char
27             # and recur for remaining string
28             elif str1[i-1] == str2[j-1]:
29                 dp[i][j] = dp[i-1][j-1]
30
31             # If last character are different, consider all
32             # possibilities and find minimum
33             else:
34                 dp[i][j] = 1 + min(dp[i][j-1],          # Insert
35                                    dp[i-1][j],          # Remove
36                                    dp[i-1][j-1])         # Replace
37
38     return dp[m][n]

```

## Code for NoisyChannel Model

```
1  '''
2  Created on Nov 7, 2017
3
4  @author: nauman
5  '''
6
7  from EditDistance import editDistDP
8  from WordList import createDictionary
9  from WordFrequency import countWordFrequency
10 import pickle
11 from decimal import *
12
13 ## Check for words that start with same capital letter
14 def getCorrectWord(word):
15     getcontext().prec = 28
16     suggestionList = []
17     probability_list = []
18     with open('word-unique.pkl', 'rb') as f:
19         wordlist = pickle.load(f)
20     with open('word-frequency.pkl', 'rb') as f:
21         frequency = pickle.load(f)
22     for i in range(0, len(wordlist)):
23         if checkLength(wordlist[i], word) and wordlist[i][:1] == word[:1]:
24             editDistance = editDistanceCalculator(wordlist[i], word)
25             if editDistance == 1:
```

```

26         probability = Decimal(int(frequency[i]))/Decimal(3902115* 0.6)
27     suggestionList.append(wordlist[i])
28     probability_list.append(probability)
29     elif editDistance == 2:
30         probability = Decimal(int(frequency[i]))/Decimal(3902115* 0.2)
31         suggestionList.append(wordlist[i])
32         probability_list.append(probability)
33     elif editDistance == 0:
34         print(wordlist[i])
35         exit(1)
36
37     maximum_probability = max(probability_list)
38     index = probability_list.index(maximum_probability)
39     print(suggestionList[index])
40
41 ## Check for words than that are in length of +1 and -1
42
43 def editDistanceCalculator(str1 , str2):
44     editDistance = editDistDP(str1 , str2 , len(str1) , len(str2))
45     return editDistance
46
47 def checkLength(word1 , word2):
48     len1 = len(word1)
49     len2 = len(word2)
50     if len1 == len2 or (len1 - len2) == 1 or (len2 - len1) == 1:
51         return True

```

```

52     else :
53         return False
54
55 def main() :
56     createDictionary()
57     countWordFrequency()
58     getCorrectWord("collectionz")
59
60
61 main()

```

Noisy Channel Code

$$W = \operatorname{argmax}_{w \in V} P(x|w)P(w)$$

where W is predicted word

$P(x|w)$  is the error model

$P(w)$  is the document mode

The above equation states that the word which has the highest product of document model and error model is the predicted word in noisy model channel.

## 1.2.2 Steps for generating the predicted correct word using Noisy Channel Model

- Parse out all possible words from the corpus.

- Identify all the unique words with their frequency from the word list.
- Calculate the edit distance of the input word with each unique word present in the word list of the corpus.
- For each unique word in the corpus compute the probability product using equation 1 .
- Find the word with highest probability and that is your predicted correct word from corpus for the word entered by the user.

### 1.2.3 Assumptions

- \* Consider only those unique words which have an edit distance of 0, 1 or 2.
- \* Calculate the edit distance if the first character of the unique word from corpus and word entered by user match.
- \* Calculate edit distance if the difference of the length of word entered by user and unique word from corpus is 1.
- \* The probability of error model have been provided with constant values. For edit distance 1 , the error model probability is set to 0.6 and for edit distance 2, the error model probability is set to 0.2.

### 1.2.4 Outputs

```
msiddique@wsdl-3102-03:~/Information Retrieval/Assignment3/Assignment3/Problem6_  
2$ python NoisyModel.py  
canadian
```

Figure 1.1: Output for input:canadai

```
msiddique@wsdl-3102-03:~/Information Retrieval/Assignment3/Assignment3/Problem6_  
2$ python NoisyModel.py  
0 Distance  
collection
```

Figure 1.2: Output for input:collection

```
msiddique@wsdl-3102-03:~/Information Retrieval/Assignment3/Assignment3/Problem6_  
2$ python NoisyModel.py  
collection
```

Figure 1.3: Output for input:collectionz

```
msiddique@wsdl-3102-03:~/Information Retrieval/Assignment3/Assignment3/Problem6_  
2$ python NoisyModel.py  
cup
```

Figure 1.4: Output for input:copr

```
msiddique@wsdl-3102-03:~/Information Retrieval/Assignment3/Assignment3/Problem6_  
2$ python NoisyModel.py  
victoria
```

Figure 1.5: Output for input:victora



# Chapter 2

## Problem 6.4

### 2.1 Problem Statement

Assuming you had a gazetteer of place names available, sketch out an algorithm for detecting place names or locations in queries. Show examples of the types of queries where your algorithm would succeed and where it would fail.

### 2.2 Solution

#### 2.2.1 Assumption about the Location Gazetteer

It does not accept any argument other than strings. It can not translate latitude and longitude, zipcodes and other aspects of address which rely on numerical value for translating address or location.

### 2.2.2 Description of the Algorithm

It parses the query term and splits them to query terms on the basis of space, colon and other punctuation marks used frequently in the address. Initially the algorithm sends all the query terms to the location gazatteer and if it is a hit it processes the query. In case of miss, it extracts each query term and sends them individually to the location gazatteer. In case of a hit, the index of the query term is saved and then the query term is split in two blocks with index term as mid point. For example, a sample query is Sushi in Norfolk Found. Each query term is passed individually to th location gazatteer. In case of Norfolk it is a hit. Now the query is split as Sushi in as first block , Found as second block and Norfolk is kept as index variable. The first half of the query terms are evaluated in reverse order starting from index location to zero position query term. Each time a query is formed by concatenating with the previous query term and send it to location gazatteer. In case of hit, the query tasks are perfomed but in case of a miss, the process is repeated again the previous query term is added to the query and checked with location gazatteer. This continues till all the elements prior to the index term have not been part of the query and been checked in the location gazatteer. If it is a overall miss, this step is then performed for query terms index to the end of the query terms. Each time a query term is appended to the query which has index query term to check for hit or miss with location gazatteer. If both the conditions fail then the index term is sent to location gazatteer and further actions are performed based on it.

```
//Function location dictionary return Trues in case of hit or False if it is a miss.
```

```

locationDictionary(word)

//Splitting query terms for a query

splitQuery(query){
  if(query.length == 1){
    if("=" in query){
      queryTerms <- split query by =
    }
    else if("&" in query){
      queryTerms <- split query by &
    }
    else if("-" in query){
      queryTerms <- split query by -
    }
    else if(": " in query){
      queryTerms <- split query by :
    }
    else if(", " in query){
      queryTerms <- split query by ,
    }
  }
}

```

```

}

else{

queryTerms <- split query by whitespace

if "=" or "&" or "-" or ":" or "," in queryTerms{

Deleted from the list of queryTerms

}

}

return queryTerms

}

//Find locations in queryTerms

findLocation(queryTerms){

if (locationDictionary(queryTerms)){

//Location identified in query

//Use the location in indexing results for the query

exit 0

}

else{

for(i in 0 to queryTerms.length){

if(locationDictionary(queryTerms[i])){

```

```

index = i

break

}

}

for(i in index-1 to 0){

if(queryModified == "" ){

queryModified = queryTerms[i] + queryTerms[index]

if (locationDictionary(queryModified)){

//Location identified in query

//Use the location in indexing results for the query

exit 0

}

}

else{

queryModified = queryTerms[i] + queryModified

if (locationDictionary(queryModified)){

//Location identified in query

//Use the location in indexing results for the query

exit 0

}

}

}

```

```

}

for(i in index+1 to queryTerms.length){

if(queryModified == "" ){

queryModified = queryTerms[index] + queryTerms[i]

if (locationDictionary(queryModified)){

//Location identified in query

//Use the location in indexing results for the query

exit 0

}

}

else{

queryModified = queryModified + queryTerms[i]

if (locationDictionary(queryModified)){

//Location identified in query

//Use the location in indexing results for the query

exit 0

}

}

}

if(locationDictionary(queryTerms(index))){

//Location identified in query

```

```
//Use the location in indexing results for the query
```

```
}
```

```
}
```

```
}
```

Queries where it works:

- New York City
- Royal Bazaar
- Norfolk
- Walmart Norfolk

Queries where it fails:

- IA 264
- ZIP 23508
- lat 88.0 long 12.34
- ODU Address

# Chapter 3

## Problem 6.5

### 3.1 Problem Statement

Describe the snippet generation algorithm in Galago. Would this algorithm work well for pages with little text content? Describe in detail how you would modify the algorithm to improve it.

### 3.2 Solution

#### Dataset Used

I am using wiki-small corpus downloaded from the book website to analyze the snippet generation algorithm in Galago.



### 3.2.1 Description of Galago Snippet Algorithm

As shown in figure 3.1, Galago Search Engine presents search results with snippets for each indexed search result containing a title, URL and a short web summary to help the users find their desired result in quickly.



Figure 3.1: Web Snippet In Galago

The title displayed in the snippets are extracted from header (h1, h2, h3....) tags of the body of the webpage. The URLs displayed on search results have been modified to show standard URLs rather than the localhost extended URLs. The text for web summaries are extracted from the paragraph (p) tags of the body of the webpage.

The text generated for web summaries are fragmented sentences rather than complete English language sentences. The texts extracted to form sentences for web summary contain the query terms in it. They do not stem the query terms for searching the word in the document. For query term gem stone, they search for the exact query terms and do not




Figure 3.2: Description of Web Snippet Generation

consider the words like gems or stones for forming web summaries. They roughly form fragmented sentences of ten words where the query term is the sixth term. In case, another query term falls within the range of fragmented sentence they extend the fragmented sentence by one. So, the general rule for the length of fragmented sentences is for each query term falling in the range of fragmented sentence the length increases by the number of query terms. For example, if three query terms lie in the fragmented sentence then the length will be twelve as two extra words have been added for two extra query terms showing up in the fragmented sentence. When framing fragmented sentences they follow the order in the webpage. For example, if the webpage has three query terms and the web summary is of two fragmented sentence then, the fragmented sentences are constructed of the first two occurrences of the query term. The length of the web summary in terms of fragmented sentences can be determined as roughly equal to half the query terms present in the webpage

must occur in the web summary. For example, if a page contains fifteen query terms, then the web summary must contain seven to eight query terms in their web summary. But this approach could mean that the number of fragmented sentences could be in range of one to eight.

### 3.2.2 Little Text Content Problem

One of the major problems with the Galago Snippet Generation algorithm with little text content is it might not produce any web summary if the query terms do not exactly match the words in the documents. As shown in figure 3.3, a web page with just a paragraph of text to validate our problem for little text content problem. For a search query gem stone the search result does not contain any web summary for this page as shown in figure 3.4. Although, the webpage does have one occurrence of word gems which is a plural form of gem which can be seen in figure 3.3. So, with little text content it is very tricky for the Galago snippet generation algorithm to find the exact query terms each time in the document but without stemming of query terms it is bound to produce no web summary almost every time on my search request.




Figure 3.3: Document containing query term

[Stewart School, Cuttack, Orissa - Wikipedia, the free encyclopedia](http://en.wikipedia.org/wiki/Stewart_School,_Cuttack,_Orissa)  
Stewart\_School,\_Cuttack,\_Orissa\_1d1c - http://wiki-  
corpus/S/t/e/Stewart\_School,\_Cuttack,\_Orissa\_1d1c.html

Figure 3.4: No Web summary generated for Query Term: Gem Stone

### 3.2.3 Improvements to the Algorithm

Firstly, the query terms need to be stemmed for incorporating their plural and other verb forms, which will help in generating web summaries for even little text content webpages. Secondly, the web summaries are supposed to be an abstract to the document, so the algorithm could extract some fragmented sentences from the metadata or the links which refer to the page rather than every time relying on the query term search in the document. Thirdly, the length of web summaries needs to have some minimum and maximum threshold as it becomes a story when the search result contains five or greater sentences in web summary. The algorithm could even implement a feedback mechanism or analyze the clickthrough logs to understand the reasons for clickthrough inversions related to web summaries. The length of fragmented sentences do not need to be hard bound by any length but rather should convey meaningful information relating the the page.

# Chapter 4

## Problem 6.9

### 4.1 Problem Statement

Give five examples of web page translation that you think is poor. Why do you think the translation failed?

### 4.2 Solution

I chose to translate webpages from Hindi to English and from Urdu to English. This was done due to my familiarity with these languages which help me understand in detail the problems happening in translated version of the webpage.

### 4.2.1 Aaj Tak Website

It is a hindi news website. I loaded the webpage in the hindi and translated it to english by selection the option of translate to english on right click of the webpage. The reason for choosing this website as a bad translation is due to one news in particular. In figure 4.2, there is a news on the left side of the figure saying “Hardline never reached Sibal’s meeting”. The original news in hindi as shown in figure 4.1, says ”The deadline on reservation ended by Patels, Hardik did not attend meeting with Sibal”.

Hardline never reached Sibal’s meeting - English Version

The deadline on reservation ended by Patels, Hardik did not attend meeting with Sibal -  
Hindi Version translated to English by me

If I look at both the news they seem very different to me because in english they converted Hardik to Hardline where Hardik is name of a person and hardline is something no where related to a name but it changes the whole narrative to the news now reading the headlines.

### 4.2.2 Aaj Tak News

Figure 4.3 is an English translation of a news from Aaj Tak, a Hindi news daily. The paragraph shown in the figure is gramatically incorrect and looks like the news in Hindi has been literally converted to English leaving out the rules of English language grammer.



Figure 4.1: News website: Aaj Tak in Hindi

### 4.2.3 Dainik Bhaskar

It is a Hindi news website. The paragraph of news translated in English as shown in figure 4.5 is not grammatically acceptable. There are numerous instances of wrong usage of capital and small letters and punctuations.

### 4.2.4 Urdu Newspaper

Figure 4.6 is an English translation of a news from Urdu newspaper. The texts in English are right to left aligned which is just a copy of the way urdu is written. Few proper nouns containing names of people mentioned in the news are wrong.

### 4.2.5 Urdu Newspaper from Pakistan

Figure 4.7 is an English translation of a news from Pakistani Urdu newspaper. The texts in English are right to left aligned which is just a copy of the way urdu is written. The most




Figure 4.2: News website: Aaj Tak in English

standout things to notice in the figure are the commas(,). They have been inverted in the document making the translated version look very rudimentary.

#### 4.2.6 Possible reason for Wrong Translation

Firstly, a major flaw in the translation of a webpage to English was with proper nouns containing names of people which are unique to the geographical area. Google might not have those names in its dictionary and translated it incorrectly. Second, most standout flaw was translating from a language that has a right to left writing style to English. It did not have any understanding of the layout of the text. Thirdly, a number of punctuations appeared weird in Urdu to English translation and it could be due to just reversing their direction and not keeping in consideration that the writing style had been changed from






Figure 4.3: News website: Aaj Tak News translated to English

right - left to left- right. Thirdly, one of the pages had a literal translation from Hindi to English. The reason could be due to word to word text translation from Hindi to English. Machines lack the understanding to look at sentences and paragraphs in context and often translate them as they encounter on word by word or sentence by sentence. The reason for grammatically incorrect translation in English from Hindi could be due to general flow of English language which does not follow a strict rule and above all the machines translating it must be trained to form sentences out of ideas rather than words. The reason even we are having this conversation of improvement in translation is due to Google which does a fairly good job at translating webpages but it is difficult to train machines to understand the behaviour of natural languages which are influenced by people who use it rather than any harlined grammar.



Figure 4.4: News website: Dainik Bhaskar in Hindi



Figure 4.5: News website: Dainik Bhaskar in English




Figure 4.6: News website: Urdu Newspaper translated to English




Figure 4.7: News website: Pakistani Urdu Newspaper translated to English

# Chapter 5

## Problem 7.2

### 5.1 Problem Statement

Can you think of another measure of similarity that could be used in the vector space model? Compare your measure with the cosine correlation using some example documents and queries with made-up weights. Browse the IR literature on the Web and see whether your measure has been studied (start with van Rijsbergens book).

### 5.2 Solution

We can use Manhattan Distance to find similarity in vector space model. Manhattan distance is the distance between two points is the sum of the absolute differences of their Cartesian coordinates. The lesser the distance the closer they are or similar the two points are. We can use Manhattan Distance as the closer a value is to zero the more the document and query

models.

Example:

In a plane with p1 at (x1, y1) and p2 at (x2, y2).

$$\text{ManhattanDistance} = |x1 - x2| + |y1 - y2|$$

Suppose we have three documents D1,D2,D3 and three queries with q1,q2,q3.

The document vectors are assumed to be:

$$D1 = [0.8, 0.7, 0.6]$$

$$D2 = [1, 0.5, 0.3]$$

$$D3 = [0.7, 0.4, 0.9]$$

The query vectors are assumed to be:

$$q1 = [0.4, 0.2, 0.8]$$

$$q2 = [0.8, 0.3, 0.9]$$

$$q3 = [0.7, 0.9, 0.8]$$

Cosine Similarity

For Query q1

$$D1 = (0.8 * 0.4) + (0.7 * 0.2) + (0.6 * 0.8) / \sqrt{(0.8^2 + 0.7^2 + 0.6^2) + (0.4^2 + 0.2^2 + 0.8^2)}$$

$$D1 = (0.32 + 0.14 + 0.48) / 1.59 = 0.59$$

$$D2 = (1 * 0.4) + (0.5 * 0.2) + (0.3 * 0.8) / \sqrt{(1^2 + 0.5^2 + 0.3^2) + (0.4^2 + 0.2^2 + 0.8^2)}$$

$$D2 = (0.4 + 0.1 + 0.24) / 1.086 = 0.681$$

$$D3 = (0.7 * 0.4) + (0.4 * 0.2) + (0.9 * 0.8) / \sqrt{(0.7^2 + 0.4^2 + 0.9^2) + (0.4^2 + 0.2^2 + 0.8^2)}$$

$$D3 = (0.28 + 0.08 + 0.72) / 1.517 = 0.712$$

Manhattan Distance

For Query q1

$$D1 = |0.8 - 0.4| + |0.7 - 0.2| + |0.6 - 0.8|$$

$$D1 = 0.4 + 0.5 + 0.2 = 1.1$$

$$D2 = |1 - 0.4| + |0.5 - 0.2| + |0.3 - 0.8|$$

$$D2 = 0.6 + 0.3 + 0.5 = 1.4$$

$$D3 = |0.7 - 0.4| + |0.4 - 0.2| + |0.9 - 0.8|$$

$$D3 = 0.3 + 0.2 + 0.1 = 0.6$$

For query q1 the cosine similarity index for documents D1, D2 and D3 are 0.59, 0.681 and 0.712. The ranking of documents in respect to the query q1 is  $D3 > D2 > D1$ . For query q2 the Manhattan Distance for documents D1, D2 and D3 are 1.1, 1.4 and 0.6. The ranking of documents in respect to the query q1 is  $D3 > D1 > D2$ .

Problems with Manhattan Distance The major flaw in the Manhattan Distance is the non-normalized value. In the above example the distance could vary from 0 to 3 because there are three co-ordinates to each vector. So to normalize the values of Manhattan Distance we can divide it by the number of co-ordinates in each vector which results in Manhattan Distance in range of 0 to 1.

$$\text{ModifiedManhattanDistance} = (|x1 - x2| + |y1 - y2|) / N$$

where N is the number of co-ordinates in each vector

Cosine Similarity

For Query q2

$$D1 = (0.8 * 0.8) + (0.7 * 0.3) + (0.6 * 0.9) / \sqrt{(0.8^2 + 0.7^2 + 0.6^2) + (0.8^2 + 0.3^2 + 0.9^2)}$$

$$D1 = (0.64 + 0.21 + 0.54) / 1.74 = 0.903$$

$$D2 = (1 * 0.8) + (0.5 * 0.3) + (0.3 * 0.9) / \sqrt{(1^2 + 0.5^2 + 0.3^2) + (0.8^2 + 0.3^2 + 0.9^2)}$$

$$D2 = (0.8 + 0.15 + 0.27) / 1.697 = 0.719$$

$$D3 = (0.7 * 0.8) + (0.4 * 0.3) + (0.9 * 0.9) / \sqrt{(0.7^2 + 0.4^2 + 0.9^2) + (0.8^2 + 0.3^2 + 0.9^2)}$$

$$D3 = (0.56 + 0.12 + 0.81) / 1.732 = 0.86$$

Modified Manhattan Distance

For Query q2

$$D1 = (|0.8 - 0.8| + |0.7 - 0.3| + |0.6 - 0.9|) / 3$$

$$D1 = (0 + 0.4 + 0.3) / 3 = 0.234$$

$$D2 = (|1 - 0.8| + |0.5 - 0.3| + |0.3 - 0.9|) / 3$$

$$D2 = (0.2 + 0.2 + 0.6) / 3 = 0.334$$

$$D3 = (|0.7 - 0.8| + |0.4 - 0.3| + |0.9 - 0.9|) / 3$$

$$D3 = (0.1 + 0.1 + 0) / 3 = 0.067$$

For query q1 the cosine similarity index for documents D1, D2 and D3 are 0.903, 0.719 and 0.86. The ranking of documents in respect to the query q1 is  $D1 > D3 > D2$ . For query q2 the Manhattan Distance for documents D1, D2 and D3 are 0.234, 0.334 and 0.067. The ranking of documents in respect to the query q1 is  $D3 > D1 > D2$ .

Research Papers on calculating similarity using Manhattan Distance for Vector Space

Model (used Google Scholar)

1. Evaluation of texture features for content-based image retrieval, by P Howarth, SM Rger  
- CIVR, 2004 - Springer

There are a few other research papers related to Manhattan Distance for Vector Space Model but they are either a modified version of Manhattan Distance or they are talking about improvements over Manhattan Distance.



# Chapter 6

## Problem 7.7

### 6.1 Problem Statement

What is the bucket analogy for a bigram language model? Give examples.

### 6.2 Solution

In context of Information Retrieval, Language Model is the ability to predict next word on the prior knowledge of the previous word. A language model for documents is the total vocabulary of the document which can be used to form query terms. A unigram language model is predicting the next word on the basis of their frequency in the document. For example, if all the words present in the document are in a bucket and it is needed to construct a new text with the bucket of words. A word is randomly chosen from the bucket without seeing in the bucket written down and the word is placed back again in the bucket and then

the search for next word happens in the similar fashion. It is the unigram language model where each word is independent of each other but are only just dependent on their occurrence in the document. But, a bigram language model uses the prior knowledge of the previous word to predict the next word. The main advantage of bigram language model over unigram language model is that it considers the previous word in context to predict the next word unlike the unigram model which treats each word individually on their frequency. It can be shown by the below equation.

$$P_{bi}(t_1t_2t_3t_4) = P(t_1)P(t_2|t_1)P(t_3|t_2)P(t_4|t_3)$$

In respect to the bucket analogy, if all the words in the document are in a bucket and a new text is to be constructed using bigram language model, initially a word is picked from the bucket of words at random and written down. Further on the bucket of words is replaced by the bucket of the words occurring with the prior word to select the next word and this process is continued where each time the bucket of words coming after the previous word is used to predict the next word.

For example, suppose there is a document that has following text.

i live in osaka .

i am a graduate student .

my school is in nara .

We want to find the probability of framing in osaka from the language model using bigram

model. It is defined by conditional probability of osaka occurring if in has already occurred. The below equation says that the conditional probability of osaka with in is equal to the frequencies of occurrence of term in osaka divided by frequency of in.

$$P(osaka|in) = c(inosaka)/c(in)$$

$$P(osaka|in) = 1/2 = 0.5$$

Similarly we want to predict the probability of nara occurring after in.

$$P(nara|in) = c(innara)/c(in)$$

$$P(nara|in) = 1/2 = 0.5$$

We want to predict school occurring after in.

$$P(school|in) = c(inschool)/c(in)$$

$$P(school|in) = 0/2 = 0$$

# Chapter 7

## Problem MLN1

### 7.1 Problem Statement

using the small wikipedia example, choose 10 words and create stem classes as per the algorithm on pp. 191-192..

### 7.2 Solution

#### 7.2.1 Description of Code

The code uses a random list of words extracted from the word list generated by parsing out the wiki-small dataset. The code for parsing words from wiki-small dataset has been reused from problem 6.2 and is not part of the code for this problem. Porter The code used Stemmer library of nltk package. The extracted words from the word list were stemmed to result in forming of 10 stems which will be used to build stem classes. The 10 stems,

extracted word list and the overall word list of the wiki-small dataset was passed as an argument `createPorterStemmerClass()` function which returns the stem classes by parsing out all of the word list and placing them in a stem class if it matches them. The stem classes are passed as an argument to the function `countCooccurence()` to return a 2-D matrix of co-occurrence of stem words of each class in a window size of 50.

```
1 '''
2 Created on Nov 9, 2017
3
4 @author: nauman
5 '''
6 from nltk.stem.porter import *
7 import codecs
8 import pickle
9 import os
10 from bs4 import BeautifulSoup
11 import codecs
12 from string import punctuation
13 import re
14
15 def RepresentsInt(s):
16     try:
17         int(s)
18         return True
19     except ValueError:
20         return False
```

```

21
22 def checkDigits(word):
23     return word.isalpha()
24
25
26 def createPorterStemmerClass(wordlist, stem_words):
27     word_frequency_matrix = []
28     for i in range(0,10):
29         new = [stem_words[i]]
30         word_frequency_matrix.append(new)
31     stemmer = PorterStemmer()
32     for plural in wordlist:
33         containsDigits = checkDigits(plural)
34         if containsDigits:
35             stem = stemmer.stem(str(plural))
36             if stem in stem_words:
37                 index = stem_words.index(stem)
38                 word_frequency_matrix[index].append(plural)
39     return word_frequency_matrix
40
41 def countCooccurence(word_frequency_matrix):
42     stem_cooccurence_matrix = []
43     for i in range(0,10):
44         new = []
45         for j in range(0, len(word_frequency_matrix[i])):
46             new.append(0)

```

```

47         stem_cooccurrence_matrix.append(new)
48
49     exclude = set(punctuation)
50     for root, dirs, files in os.walk("F:\Fall2017\InformationRetreival\
Assignment2\en"):
51         for file in files:
52             if file.endswith(".html"):
53                 with codecs.open(root+"\\" + file, "r", "utf-8") as file_open:
54                     count_range = [0,0,0,0,0,0,0,0,0,0]
55                     flag_wordFound = [False, False, False, False, False, False,
False, False, False, False]
56                     temp_word = ["", "", "", "", "", "", "", "", "", "", ""]
57                     soup = BeautifulSoup(file_open, 'html.parser')
58                     for words in soup.findAll(text=True):
59                         if words.parent.name in ['style', 'script', 'head', '
title', 'meta', '[document]']:
60                             continue
61
62                     s = ''.join(ch for ch in str(words) if ch not in
exclude)
63
64                     words = s.split(" ")
65                     for word in words:
66                         if not RepresentsInt(word.rstrip()):
67                             if re.search('[a-zA-Z]', word.rstrip()):
68                                 for i in range(0,10):

```

```

69         if word.rstrip().lower() in
word_frequency_matrix[i]:
70             if count_range[i] == 0:
71                 temp_word[i] = word.rstrip().
lower()
72                 flag_wordFound[i] = True
73             elif count_range[i] < 200 and
flag_wordFound[i]:
74                 index_prev =
word_frequency_matrix[i].index(temp_word[i])
75                 index_next =
word_frequency_matrix[i].index(word.rstrip().lower())
76                 temp = stem_cooccurrence_matrix
[i][index_next]
77                 stem_cooccurrence_matrix[
index_prev][index_next] = temp +1
78                 temp = stem_cooccurrence_matrix
[i][index_prev]
79                 stem_cooccurrence_matrix[
index_prev][index_prev] = temp +1
80                 temp_word[i] = word.rstrip().
lower()
81                 count_range[i] = 0
82             elif count_range < 200:
83                 count_range[i] = count_range[i] +
1

```



```

84         else:
85             count_range[i] = 0
86
87             flag_wordFound[i] = False
88
89     print("WordsOver")
90
91     return stem_cooccurrence_matrix
92
93 def main():
94     word_list = ["canada", "candidates", "collections", "competitive", "composition",
95                 ", "very", " couples", " victoria", " weapon", " defence"]
96
97     stemmer = PorterStemmer()
98
99     stem_words = [stemmer.stem(plural) for plural in word_list]
100
101     with open("word-unique.pkl", 'rb') as f:
102         wordlist = pickle.load(f)
103
104     word_frequency_matrix = createPorterStemmerClass(wordlist, stem_words)
105
106     file = open("StemClass.txt", "w")
107
108     file.write("Intital Stem Class without Co-occurrence" + "\n")
109
110     for i in range(0,10):
111
112     file.write("Stem Class: ")
113
114         for j in range(0, len(word_frequency_matrix[i])):
115
116             file.write(word_frequency_matrix[i][j] + " ")
117
118     file.write("\n")
119
120     file.write("\nFinal Stem classes after considering co-occurrence\n\n")
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999

```

```

109         file.write("Stem Class \n" )
110         for j in range(0,len(stem_cooccurrence_matrix[i])):
111             if stem_cooccurrence_matrix[i][j]> 0:
112                 file.write(word_frequency_matrix[i][j] + " ")
113             file.write("\n")
114         file.close()
115
116
117
118 main()

```

Intital Stem Class without Co-occurrence

Stem Class: canada canada canadas

Stem Class: candid candid candidate candidates candidating

Stem Class: collect collect collectable collected collectible collectibles collect

Stem Class: competit competing competition competitions competitive competitively

Stem Class: composit composite composites compositing composition compositional co

Stem Class: veri veri very

Stem Class: coupl couple coupled couples coupling couplings

Stem Class: victoria victoria victoriae victorias

Stem Class: weapon weapon weapons

Stem Class: defenc defence defences

Final Stem classes after considering co-occurrence

Stem Class

Stem Class

Stem Class

Stem Class

Stem Class

Stem Class

Stem Class

Stem Class

Stem Class

Stem Class

### 7.2.2 Results

The first stem result is for stems class generated by parsing the word list of the wiki-small dataset. It does not account for co-occurrence of the words in a stem class. The second output is empty, as none of the words in each stem class lied in a window size of 50,100 or 200.

# Chapter 8

## Problem MLN2

### 8.1 Problem Statement

Using the small wikipedia example, choose 10 words and compute MIM, EMIM, chi square, dice association measures for full document & 5 word windows (cf. pp. 203-205).

### 8.2 Solution

#### 8.2.1 Description of Code

The code uses a random list of words extracted from the word list generated by parsing out the wiki-small dataset. The code for parsing words from wiki-small dataset has been reused from problem 6.2 and is not part of the code for this problem. I extracted the random words keeping an assumption that their frequencies must be greater than 100, so that I can get frequency values for the extracted words in a window size of five. I have

provided constant values for the extracted word list, their frequencies and the total word list size of the wiki-small dataset. The extracted word list is passed as an argument to my function `findWordOccurence()` which creates a 10\*10 matrix for storing frequency of two words occurring in a window size of five. The 2-D matrix of frequency, frequency of each extracted word list and total word count for wiki-small dataset have been used to calculate Dice Co-efficient, MIM, EMIM, Chi-square for each pair of words in the extracted word list. The formulas for calculating each measure have been extracted from our text book.

```
1  '''
2  Created on Nov 9, 2017
3
4  @author: nauman
5  '''
6  import os
7  from bs4 import BeautifulSoup
8  import codecs
9  from string import punctuation
10 import re
11 import math
12
13 def RepresentsInt(s):
14     try:
15         int(s)
16         return True
17     except ValueError:
```

```

18         return False
19
20 def findWordOccurence(word_list):
21     #####Create a 2D matrix for word frequency
22     word_frequency_matrix = []
23     for i in range(0,10):
24         new = []
25         for j in range(0,10):
26             new.append(0)
27         word_frequency_matrix.append(new)
28
29     exclude = set(punctuation)
30     for root, dirs, files in os.walk("F:\Fall2017\InformationRetreival\
Assignment2\en"):
31         for file in files:
32             if file.endswith(".html"):
33                 with codecs.open(root+"\\" + file, "r", "utf-8") as file_open:
34                     count_range = 0
35                     flag_wordFound = False
36                     soup = BeautifulSoup(file_open, 'html.parser')
37                     for words in soup.findAll(text=True):
38                         if words.parent.name in ['style', 'script', 'head', '
title', 'meta', '[document]']:
39                             continue
40

```

```

41         s = ''.join(ch for ch in str(words) if ch not in
exclude)

42         words = s.split(" ")

43         for word in words:

44             if not RepresentsInt(word.rstrip()):

45                 if re.search('[a-zA-Z]', word.rstrip()):

46

47                     if word.rstrip().lower() in word_list and

count_range == 0:

48                         flag_wordFound = True

49                         temp_word = word.rstrip().lower()

50                         elif word.rstrip().lower() in word_list

and count_range <= 5:

51                             index_temp = word_list.index(temp_word

)

52                             index_next = word_list.index(word.

rstrip().lower())

53                             temp_frequency = word_frequency_matrix

[index_temp][index_next]

54                             word_frequency_matrix[index_temp][

index_next] = temp_frequency+1

55                             count_range = 0

56                             temp_word = word.rstrip().lower()

57                         elif count_range < 5 and flag_wordFound:

58                             count_range = count_range+1

59                     else:

```



```

60         flag_wordFound = False
61         count_range = 0
62
63     print("WordsOver")
64     return word_frequency_matrix
65
66 def findDiceCoefficient(word_frequency_matrix, word_frequency_list):
67     dice_coefficient = []
68     for i in range(0, len(word_frequency_list)-1):
69         for j in range(i+1, len(word_frequency_list)):
70             dice_temp = (word_frequency_matrix[i][j] + word_frequency_matrix[j]
71                          ][i]) / (word_frequency_list[i] + word_frequency_list[j])
72             dice_coefficient.append(dice_temp)
73     return dice_coefficient
74
75 def findMutualInforamtion(word_frequency_matrix, word_frequency_list):
76     mim = []
77     for i in range(0, len(word_frequency_list)-1):
78         for j in range(i+1, len(word_frequency_list)):
79             mim_temp = (word_frequency_matrix[i][j] + word_frequency_matrix[j][
80                          i]) / (word_frequency_list[i] * word_frequency_list[j])
81             mim.append(mim_temp)
82     return mim
83
84 def findExpectedMutualInforamtion(word_frequency_matrix, word_frequency_list,
85                                    N):

```

```

83     emim = []
84     for i in range(0, len(word_frequency_list)-1):
85         for j in range (i+1, len(word_frequency_list)):
86             nab = word_frequency_matrix[i][j] + word_frequency_matrix[j][i]
87             if nab > 0:
88                 emim_temp = nab * math.log((N * (nab / (word_frequency_list[i] *
word_frequency_list[j]))))
89             else:
90                 emim_temp = 0
91             emim.append(emim_temp)
92     return emim
93
94 def findChiSquare(word_frequency_matrix, word_frequency_list, N):
95     chi_square = []
96     for i in range(0, len(word_frequency_list)-1):
97         for j in range (i+1, len(word_frequency_list)):
98             nab = word_frequency_matrix[i][j] + word_frequency_matrix[j][i]
99             x = nab - ((word_frequency_list[i] * word_frequency_list[j]) / N)
100             chi_square_temp = math.pow(x, 2) / (word_frequency_list[i] *
word_frequency_list[j])
101             chi_square.append(chi_square_temp)
102     return chi_square
103
104 def main():
105     N = 3902115
106     word_frequency_list = [1090, 106, 105, 104, 104, 1062, 108, 510, 100, 210]

```

```

107     word_list=["canada","candidates","collections","competitive","composition
    ","very"," couples","victoria"," weapon"," defence"]
108     word_frequency_matrix = findWordOccurence(word_list)
109
110     for i in range(0,10):
111         for j in range(0,10):
112             print(word_frequency_matrix[i][j])
113
114     diceCoefficient = findDiceCoefficient(word_frequency_matrix,
word_frequency_list)
115
116     mim = findMutualInforamtion(word_frequency_matrix, word_frequency_list)
117
118     emim = findExpectedMutualInforamtion(word_frequency_matrix,
word_frequency_list, N)
119
120     chiSquare = findChiSquare(word_frequency_matrix, word_frequency_list, N)
121
122     file = open("Result.txt", "w")
123
124     file.write("Query Term1"+ " " + "Query Term2" + " " + "Dice Coefficient" +
    " " + "MIM" + " " + "EMIM" + " " + "Chi-Square" + "\n")
125
126     count =0;
127
128     for i in range(0,len(word_list)-1):
129         for j in range (i+1,len(word_list)):
130
131             file.write(word_list[i] + " " + word_list[j] + " " + str(
    diceCoefficient[count]) + " " + str(mim[count]) + " " + str(emim[count]) +
    " " + str(chiSquare[count]) + "\n")
132
133             count = count+1
134
135     file.close()
136
137     print("End")
138
139

```

127 main()

```
94 0 0 0 0 2 0 3 0 0
0 3 0 0 0 0 0 0 0 0
0 0 4 0 0 0 0 0 0 0
0 0 0 2 0 2 0 0 0 0
0 0 0 0 3 0 0 0 0 0
0 0 0 0 0 13 0 0 0 0
0 0 0 0 0 0 0 2 0 0
3 0 0 0 0 1 1 48 0 0
0 0 0 0 0 0 0 0 3 0
0 0 0 0 0 0 0 0 0 1
```

QueryTerm1	QueryTerm2	DiceCoefficient	MIM	EMIM	ChiSquare
------------	------------	-----------------	-----	------	-----------

canada	candidates	0.0 0.0 0	7.588085825438693e-09		
--------	------------	-----------	-----------------------	--	--

canada	collections	0.0 0.0 0	7.516500110104367e-09		
--------	-------------	-----------	-----------------------	--	--

canada	competitive	0.0 0.0 0	7.444914394770038e-09		
--------	-------------	-----------	-----------------------	--	--

canada	composition	0.0 0.0 0	7.444914394770038e-09		
--------	-------------	-----------	-----------------------	--	--

canada	very	0.0009293680297397769	1.727742359059417e-06	3.81666855066276	2.5064236337055
--------	------	-----------------------	-----------------------	------------------	-----------------

canada	couples	0.0 0.0 0	7.731257256107347e-09		
--------	---------	-----------	-----------------------	--	--

canada	victoria	0.00375	1.0793308148947653e-05	22.442670240498014	6.172110226621129e-05
--------	----------	---------	------------------------	--------------------	-----------------------

canada	weapon	0.0 0.0 0	7.158571533432729e-09		
--------	--------	-----------	-----------------------	--	--

canada defence 0.0 0.0 0 1.5033000220208733e-08  
 candidates collections 0.0 0.0 0 7.309623960284979e-10  
 candidates competitive 0.0 0.0 0 7.240008493996552e-10  
 candidates composition 0.0 0.0 0 7.240008493996552e-10  
 candidates very 0.0 0.0 0 7.393162519831094e-09  
 candidates couples 0.0 0.0 0 7.518470359150264e-10  
 candidates victoria 0.0 0.0 0 3.550388780709847e-09  
 candidates weapon 0.0 0.0 0 6.961546628842838e-10  
 candidates defence 0.0 0.0 0 1.4619247920569958e-09  
 collections competitive 0.0 0.0 0 7.171706527072056e-10  
 collections composition 0.0 0.0 0 7.171706527072056e-10  
 collections very 0.0 0.0 0 7.323415703606272e-09  
 collections couples 0.0 0.0 0 7.447541393497904e-10  
 collections victoria 0.0 0.0 0 3.516894546929565e-09  
 collections weapon 0.0 0.0 0 6.895871660646208e-10  
 collections defence 0.0 0.0 0 1.4481330487357034e-09  
 competitive composition 0.0 0.0 0 7.103404560147559e-10  
 competitive very 0.0017152658662092624 1.810806895552658e-05 8.515752702826394 3.5198306  
 competitive couples 0.0 0.0 0 7.376612427845543e-10  
 competitive victoria 0.0 0.0 0 3.483400313149284e-09  
 competitive weapon 0.0 0.0 0 6.830196692449576e-10

competitive defence 0.0 0.0 0 1.4343413054144112e-09  
 composition very 0.0 0.0 0 7.25366888738145e-09  
 composition couples 0.0 0.0 0 7.376612427845543e-10  
 composition victoria 0.0 0.0 0 3.483400313149284e-09  
 composition weapon 0.0 0.0 0 6.830196692449576e-10  
 composition defence 0.0 0.0 0 1.4343413054144112e-09  
 very couples 0.0 0.0 0 7.532656152280738e-09  
 very victoria 0.0006361323155216285 1.8463129131125143e-06 1.9747093442762524 1.36934123  
 very weapon 0.0 0.0 0 6.974681622482164e-09  
 very defence 0.0 0.0 0 1.4646831407212545e-08  
 couples victoria 0.0048543689320388345 5.446623093681917e-05 16.07729882286608 0.0001618  
 couples weapon 0.0 0.0 0 7.0928965652361e-10  
 couples defence 0.0 0.0 0 1.4895082786995808e-09  
 victoria weapon 0.0 0.0 0 3.349423378028158e-09  
 victoria defence 0.0 0.0 0 7.03378909385913e-09  
 weapon defence 0.0 0.0 0 1.3791743321292416e-09

## 8.2.2 Results

$N = 3902115$

word\_list = ["canada", "candidates", "collections", "competitive", "composition", "very", "cou-  
 ples", "victoria", "weapon", "defence"]

```
word_frequency_list = [1090,106,105,104,104,1062,108,510,100,210]
```

The above three lines show the values that have been provided to the code based on my previous problem. First line contains N which represents the total number of words in the wiki-small dataset. Second line contains the extracted word list and the last line has all the frequency values for each extracted word list. The file for results shows values a 10\*10 matrix which is the frequency of co-occurrence of two query terms in a window size of 5. Further the file shows for every two query terms their values in different measure. The results queries have been shown only for queries which have non-zero values for each measure of query expansion. The list of frequent occurring query terms in a window size of 5 which can be used for query expansion are:

canada very

canada victoria

competitive very

very victoria

couples victoria