


```
In [ ]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import utils
from sklearn.svm import SVC
```

Building an SVM to separate a linear dataset


```
In [ ]: # Loading the linear dataset

linear_data = pd.read_csv('linear.csv')
features = np.array(linear_data[['x_1', 'x_2']])
labels = np.array(linear_data['y'])
utils.plot_points(features, labels)
```



```
In [ ]: svm_linear = SVC(kernel='linear')
svm_linear.fit(features, labels)
print("Accuracy:", svm_linear.score(features, labels))
utils.plot_model(features, labels, svm_linear)
```


Accuracy: 0.9333333333333333




```
In [ ]: # C = 0.01
svm_c_001 = SVC(kernel='linear', C=0.01)
svm_c_001.fit(features, labels)
print("C = 0.01")
print("Accuracy:", svm_c_001.score(features, labels))
utils.plot_model(features, labels, svm_c_001)

# C = 100
svm_c_100 = SVC(kernel='linear', C=100)
svm_c_100.fit(features, labels)
print("C = 100")
print("Accuracy:", svm_c_100.score(features, labels))
utils.plot_model(features, labels, svm_c_100)
```

C = 0.01
Accuracy: 0.8666666666666667




C = 100
Accuracy: 0.9166666666666666



Building polynomial kernels for a circular dataset

```
In [ ]: # Loading the one_circle dataset
```


```
circular_data = pd.read_csv('one_circle.csv')
features = np.array(circular_data[['x_1', 'x_2']])
labels = np.array(circular_data['y'])
utils.plot_points(features, labels)
```




```
In [ ]: # Degree = 2
svm_degree_2 = SVC(kernel='poly', degree=2)
svm_degree_2.fit(features, labels)
print("Polynomial kernel of degree = 2")
print("Accuracy:", svm_degree_2.score(features, labels))
utils.plot_model(features, labels, svm_degree_2)

# Degree = 4
svm_degree_4 = SVC(kernel='poly', degree=4)
svm_degree_4.fit(features, labels)
print("Polynomial kernel of degree = 4")
print("Accuracy:", svm_degree_4.score(features, labels))
utils.plot_model(features, labels, svm_degree_4)
```

Polynomial kernel of degree = 2
Accuracy: 0.8909090909090909




Polynomial kernel of degree = 4
Accuracy: 0.9



Experimenting with gammas in the rbf kernel

```
In [ ]: # Loading the two_circles dataset
```

```
two_circles_data = pd.read_csv('two_circles.csv')
features = np.array(two_circles_data[['x_1', 'x_2']])
labels = np.array(two_circles_data['y'])
utils.plot_points(features, labels)
```



```
In [ ]: # gamma = 0.1
svm_gamma_01 = SVC(kernel='rbf', gamma=0.1)
svm_gamma_01.fit(features, labels)
print("Gamma = 0.1")
print("Accuracy:", svm_gamma_01.score(features, labels))
utils.plot_model(features, labels, svm_gamma_01)

# gamma = 1
svm_gamma_1 = SVC(kernel='rbf', gamma=1)
svm_gamma_1.fit(features, labels)
print("Gamma = 1")
print("Accuracy:", svm_gamma_1.score(features, labels))
utils.plot_model(features, labels, svm_gamma_1)


# gamma = 10
svm_gamma_10 = SVC(kernel='rbf', gamma=10)
svm_gamma_10.fit(features, labels)
print("Gamma = 10")
print("Accuracy:", svm_gamma_10.score(features, labels))
```

```
utils.plot_model(features, labels, svm_gamma_10)

# gamma = 100
svm_gamma_100 = SVC(kernel='rbf', gamma=100)
svm_gamma_100.fit(features, labels)
print("Gamma = 100")
print("Accuracy:", svm_gamma_100.score(features, labels))
utils.plot_model(features, labels, svm_gamma_100)
```


Gamma = 0.1

Accuracy: 0.8772727272727273




Gamma = 1


Accuracy: 0.9045454545454545



Gamma = 10
Accuracy: 0.9636363636363636



Gamma = 100
Accuracy: 0.990909090909091



```
In [ ]: # All accuracies are training accuracies
        # Compute the cross-validation accuracy for each model
```