

# Assignment 2

## CMPUT 474

Pranav Wadhwa  
1629510

February 13, 2022

1. Are the following languages context-free? Prove your answer in each case.

(a)  $\Sigma = \{0, 1\}^*$ ,  $L = \{xy \mid |x| = |y|, x \neq y\}$

(b)  $\Sigma = \{0, 1\}^*$ ,  $L = \{w \mid n_0(w) = n_1(w) \text{ and } w \text{ includes the string '001'}\}$  where  $n_0(w)$  and  $n_1(w)$  denote the number of 0s and 1s in  $w$  respectively.

**Solution:** Yes, the language is context free. We observe in language  $L$  that it is made up of 2 strings  $x$  and  $y$  which are of same length but the strings are not equal. So the strings differ on some character  $i$  and we can make a corresponding context-free grammar around this rule.

$$S \rightarrow AB|BA$$

$$A \rightarrow XAX|0$$

$$B \rightarrow XBX|1$$

$$X \rightarrow 0|1$$

2. Let  $G$  be a CFG in Chomsky normal form, and  $w \in L(G)$ . How long is  $w$  if there is a derivation of  $w$  using  $p$  steps? Explain why.

**Solution:**

Every context-free grammar that is in Chomsky normal form has rules of the form

$$A \rightarrow BC$$

$$A \rightarrow a$$

We have  $G$  a CFG in Chomsky normal form and  $w \in L(G)$ .  $w$  is derived in  $p$  steps. Every derivation in this form goes from  $A$  (non-terminal)  $\rightarrow BC$  (non-terminal)(non-terminal) or  $A$  (non-terminal)  $\rightarrow a$  terminal.

To derive a string of length  $w$  we will have  $w$  derivation of the first form from  $A \rightarrow BC$  to a terminal  $A \rightarrow a$  while expanding  $B$  as each step adds a total of +1 to each step. Then we will have a total of  $w - 1$  derivation from  $A \rightarrow C$  while expanding  $C$  to a terminal as the start symbol is already counted.

So the total number of derivations are  $w + (w - 1) = 2w - 1$ . We are given that the total derivations are  $p$ .

So,  $p = 2w - 1$  then  $w = \frac{p+1}{2}$


3. Let  $G$  be a CFG. Explain an algorithm to determine whether  $L(G)$  is finite. (Hint: use the pumping lemma).
4. Convert the CFG

$$\begin{aligned} S &\rightarrow E \\ E &\rightarrow E + T | T \\ T &\rightarrow T \times F | F \\ F &\rightarrow (E) | a \end{aligned}$$

to an equivalent PDA.

**Solution:**

A GPDA of the CFC



5. Recall that the class of context-free language is closed under the regular operations, union, concatenation, and star. Prove that every regular language is context free by showing how to convert a regular expression directly to an equivalent context-free grammar.
6. Consider the CFG  $G$  given by

$$S \rightarrow aSbS \mid bSaS \mid \epsilon$$

Prove that  $L(G)$  is the set of strings with an equal number of  $as$  and  $bs$ .

**Solution:**

We want to show that every string  $s$  in  $L(G)$  contains an equal number of  $a$ s and  $b$ s with strong induction.

Base Case:

$|s| = 1$ . If  $s$  is generated by  $G$  then the only possible string is  $\epsilon$  which has  $n_a = n_b = 0$

$|s| = 2$ . If  $s$  is generated by  $G$  then the possible strings are  $ab$  or  $ba$  where both have  $n_a = n_b = 1$ .

Inductive Hypothesis (IH):

$G$  produces strings that have  $n_a = n_b$  (number of  $a$ s is equal to number of  $b$ s).

Inductive Step:

Assume that  $IH$  holds for all strings in  $G$  that have length  $n$  or less than  $n$ . Consider the string  $s$  of length  $n + 1$  and it is first produced by rule  $S$ . We will go over each rule and see how it is generated.

If we use rule  $S \rightarrow aSbS$  then  $s$  consists of  $aw_1bw_2$  where  $w_1$  and  $w_2$  are strings derived from  $G$  and are of length less than  $n$ . From our  $IH$  we know that  $w_1$  and  $w_2$  have equal number of  $a$ s and  $b$ s. So then length of string  $|s| = |a| + |w_1| + |b| + |w_2|$  and string  $s$  adds one pair of  $a, b$  to  $w_1$  and  $w_2$  which makes the total number of  $a$ s and  $b$ s in  $s$  to be equal.

Similarly, if we use the rule  $S \rightarrow bSaS$  we find that it is made up of strings  $bw_1aw_2$  where  $w_1$  and  $w_2$  are both derived from  $G$  and are of length less than  $n$ . Due to similar reasons given above the string  $s$  generated by this rule also has equal number of  $a$ s and  $b$ s.

And lastly, if we use the rule  $S \rightarrow \epsilon$  then the string  $s$  would be of length  $n$  which given by  $IH$  has equal number of  $a$ s and  $b$ s.

Therefore we have proved that  $IH$  holds for string  $n + 1$  then  $L(G)$  is the set of strings with equal number of  $a$ s and  $b$ s.



7. Show the following grammar is ambiguous by drawing parse trees. Find an unambiguous grammar for this language.

$$S \rightarrow aSb \mid Sb \mid \epsilon$$

**Solution:**

Take this string generated from the grammar and its corresponding parse tree.

$abb$



Since the string has 2 parse trees therefore, the grammar is ambiguous.

8. Let  $P$  be the language of all palindromes over  $\{0, 1\}$  containing equal numbers of 0s and 1s. Show that  $P$  is not context free.

**Solution:** We assume that  $P$  is a CFL and obtain a contradiction. Let  $p$  be the pumping length for  $P$  and select a string that is a palindrome and also contains equal numbers of 0s and 1s. So let  $s = 1^p 0^p 1^p 0^p$  be the string that is also in  $P$ . We can shorten  $s$  into  $s = 1^p 0^{2p} 1^p$ .

By the pumping lemma we may choose  $u, v, x, y, z$  such that  $|vy| > 0$  and  $|vxy| < p$ . We can look over different cases of  $v$  and  $y$ .

case 1:  $v$  and  $y$  are in the middle and only consists of 0s. Then  $uxz$  would contain less 0s than 1s as  $uxz = 1^p 0^{2p-|vx|} 1^p$  which is not in  $P$ .

case 2:  $v$  or  $y$  contains  $m > 0$  amount of 0s and  $n > 0$  amount of 1s from one side of the string but no 1s from the other side. Then the corresponding string  $uxz$  generated would have the following cases for both sides:

$$1^{p-m} 0^{2p-n-|y|} 1^p \quad \text{or} \quad 1^p 0^{2p-n-|v|} 1^{p-m}$$

Both of them don't form a palindrome as number of 1s are not equal so  $uxz \notin P$ . Therefore we obtain a contradiction and  $P$  is not context free.

9. The language  $L = \{ww : w \in \{a, b\}^*\}$  is not context free. However, show that the complement language,  $\bar{L}$ , is context free.
10. Is there a *universal* pushdown automaton? That is, there is a single pushdown automaton, say  $M$  such that given a string  $s_G w$ , where  $s_g$  is a string that describes a context free grammar and  $w$  is an input string,  $M$  accepts  $s_G w$  if and only if  $G$  generates  $w$ ? Explain your answer.