

Status Finished

Started Monday, 23 December 2024, 5:33 PM

Completed Wednesday, 30 October 2024, 4:46 PM

Duration 54 days

Question 1

Correct

Marked out of
3.00

[Flag question](#)

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int a,b;
4     scanf("%d%d",&a,&b);
5     if(a%10==b%10)
6         printf("true");
7     else
8         printf("false");
9     return 0;
10 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Objective

In this challenge, we're getting started with conditional statements.

Task

Given an integer, n , perform the following conditional actions:

- If n is odd, print *Weird*
- If n is even and in the inclusive range of 2 to 5, print *Not Weird*
- If n is even and in the inclusive range of 6 to 20, print *Weird*

Given an integer, n , perform the following conditional actions:

- If n is odd, print **Weird**
- If n is even and in the inclusive range of **2** to **5**, print **Not Weird**
- If n is even and in the inclusive range of **6** to **20**, print **Weird**
- If n is even and greater than **20**, print **Not Weird**

Complete the stub code provided in your editor to print whether or not n is weird.

Input Format

A single line containing a positive integer, n .

Constraints

- $1 \leq n \leq 100$

Output Format

Print **Weird** if the number is weird; otherwise, print **Not Weird**.

Sample Input 0

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int n;
4     scanf("%d",&n);
5     if(n%2==1)
6     {
7         printf("Weird");
8     }
9     else if(n==2 || n==4)
10    {
11        printf("Not Weird");
12    }
13    else if(n%2==0 &&(n>=6 && n<=20))
14    {
15        printf("Weird");
16    }
17    else if(n%2==0 && n>20)
18    {
19        printf("Not Weird");
20    }
21    return 0;
22 }
23
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$. You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d\n%d\n%d",&a,&b,&c);
6     a=a*a;
7     b=b*b;
8     c=c*c;
9     if( a==b+c)
10 {
11     printf("yes");
12 }
13 else if(b==a+c)
14 {
15     printf("yes");
16 }
17 else if(c==a+b)
18 {
19     printf("yes");
20 }
21 else
22 {
23     printf("no");
24 }
25 return 0;
26 }
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓

Finish review