KONGU ENGINEERING COLLEGE

(Autonomous)
PERUNDURAI, ERODE – 638 060

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

SMART PARKING ALLOCATION SYSTEM

A Mini Project Report

24GEP31 – Mini Project

Submitted by

NITHIESH M Register No: _____

[Team Member Name] Register No: _____

Academic Year 2025 – 2026

OCTOBER 2026

KONGU ENGINEERING COLLEGE
(Autonomous)
PERUNDURAI, ERODE – 638 060
DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

BONAFIDE CERTIFICATE

This is to certify that the Mini Project report entitled **"Smart Parking Allocation System"** is the bonafide record of project work done by **NITHIESH M** (Register No: _____) and **[Team Member Name]** (Register No: _____) under my supervision for the mini-project requirement of the Bachelor of Engineering programme during the academic year 2025–2026.

_____	_____
Supervisor	**Head of the Department**
Department of CSE	Department of CSE

Submitted for the end-semester viva voce examination held on _____

ABSTRACT

Finding a free parking space in a college campus is still largely a manual process. Drivers enter a lot without knowing whether a compatible space is free, circle through rows of vehicles, and often block other vehicles while searching. There is no reservation facility, no fair queue when a lot is full, no priority for accessibility-permit holders, and no protection against two users being allotted the same space. A console-based record book or a simple entry/exit register cannot solve these problems because it stores history but does not make allocation decisions.

This project presents a **Smart Parking Allocation System** built with a Java and Spring Boot backend, a MySQL database, and a plain HTML/CSS/JavaScript dashboard. The system manages three parking lots with twenty-four spaces of three kinds: car, two-wheeler, and accessible. It registers vehicles, validates vehicle–space compatibility, prevents overlapping reservations, and automatically chooses the best free space. The choice is made by a slot-selection policy that first uses **Dijkstra's shortest-path algorithm** on a weighted road graph to find the nearest lot from the campus entrance, then prefers the lower floor and the lower space code. A **PriorityQueue** with a **HashMap** index implements a waiting list in which accessibility-permit holders are served before standard users and earlier arrivals are served before later ones. Released spaces are re-offered to the queue automatically after the releasing transaction commits.

The backend enforces every business rule. The frontend only fetches data, renders it, and sends commands, so allocation, overlap, permit, and priority logic cannot be bypassed from the browser. MySQL is the source of truth; the in-memory index and waiting heap are rebuilt from the database on startup. Concurrency is handled with `SELECT ... FOR UPDATE` row locks, `READ_COMMITTED` isolation, an authoritative overlap re-check inside the lock, and JPA `@Version` optimistic locking. The project includes a simulated clock so that reservation expiry and fee calculation can be demonstrated without waiting in real time.

The Maven build completes successfully and the automated suite runs **12 integration tests with 0 failures and 0 errors**. Manual API tests, database checks, and headless-browser UI checks also pass. The report documents the design, implementation, database schema, test cases, results, limitations, and future enhancements, and it explains how the project demonstrates object-oriented programming and core data structures and algorithms.

Keywords: smart parking, Spring Boot, MySQL, Dijkstra, PriorityQueue, HashMap, reservation, waiting list, REST API, object-oriented programming.

TABLE OF CONTENTS

ABSTRACT 3
CHAPTER 1 PROBLEM ANALYSIS AND DESIGN 5
1.1 Problem Definition 5
1.2 SDG Relevance 8
1.3 Proposed System and Solution 8
1.4 Java OOP Design 9
1.5 Data Structures and Algorithms 11
1.6 System Architecture and Methodology 13
1.7 Project Planning and Risk Management 14
CHAPTER 2 IMPLEMENTATION AND TECHNICAL DEMONSTRATION 16
2.1 Technology Stack 16
2.2 Frontend Design and User Interface 17
2.3 Database Design and Connectivity 17
2.4 Implementation of Modules 19
2.5 Complete Working Demonstration 21
CHAPTER 3 TESTING, RESULTS AND EVALUATION 30
3.1 Testing and Validation 30
3.2 Results and Performance Analysis 32
3.3 Sustainability, Cost and Resource Efficiency 33
3.4 Limitations and Future Enhancements 34
CHAPTER 4 GITHUB AND CONCLUSION 36
4.1 GitHub Repository and Version Control 36
4.2 Conclusion 38
REFERENCES 40
APPENDIX (CODE) 41
A.1 Application configuration 41
A.2 Dijkstra shortest path 41
A.3 Waiting-list priority comparator 42
A.4 Overlap query 42
A.5 Booking transaction outline 43
A.6 Database schema excerpt 43
A.7 Build and run commands 44

CHAPTER 1
PROBLEM ANALYSIS AND DESIGN

1.1 Problem Definition

1.1.1 Problem Statement

In a typical engineering campus, parking is handled by security staff and a manual register. A vehicle is allowed in if a space appears to be free, and the entry is written in a book. This approach has six practical problems:

1. **No real-time visibility.** A driver cannot know how many spaces are free in each lot before entering.
2. **Blind search and congestion.** Vehicles cruise between lots, wasting fuel and time, and create traffic near academic blocks.
3. **Wrong space type.** A car may occupy a two-wheeler bay, or a non-permit vehicle may occupy an accessible bay, because nothing enforces compatibility.
4. **Double booking.** Two users can be promised the same space when entries are recorded on paper or in independent spreadsheets.
5. **Unfair queueing.** When a lot is full there is no ordered waiting list and no priority for accessibility-permit holders.
6. **No reservation or audit.** There is no way to reserve a space in advance, cancel it, record check-in/check-out, or compute a fee consistently.

The existing console application in the repository records vehicles and parking sessions, but it does not allocate spaces, check overlaps, rank a waiting list, or expose a web interface. A new system is required that makes the allocation decision in software and records it safely in a relational database.

1.1.2 Project Objectives

1. Provide a browser dashboard that shows live counts and a visual map of all lots and spaces.
2. Register cars and two-wheelers with an optional accessibility permit and reject duplicate numbers.
3. Automatically allocate the **best compatible free space** for a requested time window.
4. Use **Dijkstra's shortest path** on a weighted road graph to prefer the nearest lot from the entrance.
5. Allow advance reservations while preventing space overlaps and vehicle overlaps.
6. Implement a **priority waiting list** that reconsiders requests when a space is released.
7. Support check-in, check-out, cancellation, expiry with a grace period, and automatic fee calculation.
8. Persist lots, spaces, vehicles, reservations, waiting requests, road segments, and audit events in MySQL.
9. Demonstrate OOP (abstraction, inheritance, polymorphism, encapsulation, composition, strategy) and DSA (HashMap, ArrayList, PriorityQueue, weighted graph, Dijkstra, interval overlap).
10. Protect against concurrent double booking using database transactions and row locks.

11. Deliver automated tests, schema scripts, sample data, API documentation, UML diagrams, and a runnable Maven project.

1.1.3 Functional and Non-Functional Requirements

Functional requirements

ID	Requirement
FR-01	The system shall display total, available, reserved, and occupied space counts for all lots.
FR-02	The system shall list lots and spaces and allow filtering by lot, space type, status, and search text.
FR-03	The system shall register a vehicle with number, owner name, type, and accessibility permit, and shall reject duplicate numbers.
FR-04	The system shall allow an accessibility permit to be granted or removed and shall re-rank that vehicle's waiting request.
FR-05	The system shall allocate the nearest compatible free space automatically when no preferred space is given.
FR-06	The system shall validate a preferred space for type and permit compatibility before booking.
FR-07	The system shall reject a reservation that overlaps an active reservation for the same space or the same vehicle.
FR-08	The system shall allow a `RESERVED` booking to be cancelled.
FR-09	The system shall support check-in and check-out and shall calculate the fee on check-out.
FR-10	The system shall expire unclaimed reservations after a configurable grace period.
FR-11	The system shall maintain a priority waiting list and automatically allocate a released space to the highest-priority compatible request.
FR-12	The system shall record an audit event for every reservation, cancellation, check-in, check-out, expiry, and waiting-list action.

FR-13	The system shall provide a simulated clock that can be advanced and reset for demonstration and testing.
FR-14	The system shall expose a JSON REST API with correct HTTP status codes and consistent error bodies.

Non-functional requirements

ID	Requirement
NFR-01	The backend shall be implemented entirely in Java with Spring Boot; no Python, Node.js, or PHP backend is permitted.
NFR-02	Data shall be stored in MySQL/MariaDB with ACID transactions, primary keys, foreign keys, unique constraints, checks, and indexes.
NFR-03	The dashboard shall load within one second for the seeded 24-space dataset on a normal laptop.
NFR-04	Concurrent bookings shall not create a double booking for the same space and overlapping window.
NFR-05	The user interface shall be usable on a desktop browser and shall show clear success and error messages.
NFR-06	The code shall follow a layered architecture with small classes, constructor injection, and no generated boilerplate.
NFR-07	Business rules shall be testable through automated integration tests using an in-memory database.
NFR-08	The application shall run on Windows or Linux with Java 17 and MySQL 8.x or MariaDB 10.4+.
NFR-09	Input shall be validated on the server; database credentials shall not be committed to version control.
NFR-10	The project shall include a README, API reference, UML diagrams, design notes, and test cases.

1.2 SDG Relevance

The project aligns primarily with **United Nations Sustainable Development Goal 11 – Sustainable Cities and Communities**, especially target 11.2 (safe, affordable, accessible, and sustainable transport systems) and target 11.6 (reducing the adverse environmental impact of cities). Parking search traffic is a measurable contributor to urban congestion and emissions. By telling a driver exactly where to go, the system reduces cruising distance and idling. By reserving accessible bays only for permit holders, it supports inclusive mobility. By replacing paper registers with a database, it reduces paper use and makes records auditable.

SDG	Alignment	Expected impact
SDG 11 Sustainable Cities and Communities	Smart allocation, real-time availability, reservation, accessible priority	Shorter search time, less congestion, inclusive access, organised campus mobility
SDG 9 Industry, Innovation and Infrastructure	Digital infrastructure, REST API, database-backed service	Reusable smart-campus platform that can be extended to more lots and sensors
SDG 13 Climate Action	Reduced cruising and idling; fewer unnecessary vehicle kilometres	Lower fuel consumption and CO_2 emissions per parking event

1.3 Proposed System and Solution

The proposed system is a **web-based smart parking allocation platform**. A driver opens the dashboard, registers a vehicle once, chooses a start and end time, and optionally chooses a preferred space. The Java backend then performs a fixed pipeline: validate the time window, check that the vehicle has no overlapping booking, filter spaces by type and permit compatibility, remove spaces with overlapping intervals, rank the remainder, lock the chosen rows, re-check the overlap inside the lock, and insert the reservation. The response tells the driver exactly which space and lot were allocated.

The major modules are:

- **Vehicle module** – registration, search, duplicate prevention, permit management.
- **Allocation module** – compatibility, overlap filtering, Dijkstra-based ranking, strategy pattern.
- **Reservation module** – create, cancel, check-in, check-out, expiry, lifecycle rules.
- **Waiting-list module** – priority queue, re-ranking, automatic allocation after release.
- **Database module** – JPA entities, repositories, schema, indexes, transactions.
- **Dashboard module** – counts, lot cards, space grid, forms, tables, filters, messages.
- **Demo-support module** – simulated clock, expiry trigger, seeded sample data.

Capability	Manual register	Legacy console app	Proposed system
Real-time availability	No	No	Yes, dashboard and API
Automatic allocation	No	No	Yes, compatible + nearest
Reservation and overlap check	No	No	Yes, space and vehicle
Waiting list with priority	Informal	No	Yes, PriorityQueue
Accessibility permit rule	Manual	No	Enforced in Java
Fee calculation	Manual	Basic	Automatic, rounded up
Audit history	Paper	File	Database table
Concurrency safety	None	None	Row locks + version

1.4 Java OOP Design

The domain model uses real Java inheritance rather than string switches. The main classes and their responsibilities are listed below.

Class / interface	Responsibility
`ParkingLot`	Lot code, name, address, graph node, and its spaces.
`ParkingSpace` (abstract)	Common space fields and abstract `canAccommodate()`, `requiresPermit()`, `getKind()`.
`CarSpace`, `TwoWheelerSpace`, `AccessibleSpace`	Concrete compatibility rules for each space type.
`Vehicle` (abstract)	Number, owner, permit, creation time, abstract `getKind()`.

`CarVehicle`, `TwoWheelerVehicle`	Concrete vehicle kinds mapped by a discriminator column.
`Reservation`	Booking window, status, check-in/out timestamps, fee, version.
`WaitingRequest`	Durable waiting-list row: window, priority, arrival, status, allocated reservation.
`ParkingEvent`	Audit trail entry with type, vehicle, space, lot, message, and fee.
`RoadSegment`	Weighted edge of the campus road graph.
`ReservationService`	Booking transaction, lifecycle transitions, expiry, row locks.
`ParkingAllocationService`	Eligibility filtering, interval checks, policy invocation.
`WaitingListService`	PriorityQueue and HashMap index, join, cancel, re-rank, rebuild.
`WaitingListProcessor`	Reconsiders the queue after a release in separate transactions.
`TravelTimeService`	Builds the weighted graph and runs Dijkstra from the entrance.
`ParkingFeeService`	Rate, minimum duration, and ceiling rounding with `BigDecimal`.
`ClockService`	Real time plus an in-memory simulated offset.
`SlotSelectionPolicy` (abstract)	Strategy for ordering eligible spaces.
`NearestAvailableSpacePolicy`	Travel time, then floor, then code.
`ParkingIndex`	HashMap/ArrayList in-memory interval index for fast pre-checks.
`WeightedGraph`, `DijkstraShortestPath`	Adjacency-list graph and min-heap shortest-path algorithm.

Abstraction. `ParkingSpace` declares the behaviour that the rest of the system needs, without exposing how each type decides compatibility.

```
public abstract class ParkingSpace {

    public abstract boolean canAccommodate(Vehicle vehicle);

    public abstract boolean requiresPermit();

    public abstract SpaceKind getKind();

}
```

Inheritance. `CarSpace`, `TwoWheelerSpace`, and `AccessibleSpace` extend `ParkingSpace`; `CarVehicle` and `TwoWheelerVehicle` extend `Vehicle`; `NearestAvailableSpacePolicy` extends `SlotSelectionPolicy`. JPA maps the two hierarchies with `InheritanceType.SINGLE_TABLE` and discriminator columns, so the schema stays small while Java keeps polymorphism.

Polymorphism. The allocation service calls `space.canAccommodate(vehicle)` and lets the JVM dispatch to the correct subclass. Adding an EV-charging space would mean adding one subclass, not editing a long `if/else` chain.

Encapsulation. Entity fields are private; `ParkingIndex` synchronises map access and returns immutable snapshots; the waiting queue is private and exposed only through ordered views.

Composition. A lot *has* spaces, a reservation *has* a vehicle and a space, `WaitingListService` *has* a queue and a map, and `WeightedGraph` *has* an adjacency list.

Strategy pattern. `SlotSelectionPolicy` is an abstract strategy. The default policy orders by Dijkstra time, floor, and code. A different policy can be introduced without touching the allocation service.

1.5 Data Structures and Algorithms

The project deliberately uses a small set of well-understood structures so that each one has a clear role in the demonstration.

Structure / algorithm	Where it is used	Why it is appropriate	Complexity
`HashMap`	`ParkingIndex` maps by space id, vehicle number, and reservation id	Average constant-time lookup during pre-checks	O(1) average
`HashMap<Long, ArrayList<ReservationInterval>>`	Intervals grouped by space	Only scan the intervals of the candidate space	O(1) bucket, O(k) scan

`ArrayList`	Ranked candidate list	Preserves policy order and allows iteration	O(1) append, O(n) scan
`PriorityQueue` (min-heap)	Dijkstra frontier	Always expand the nearest known node	O(log V) insert/poll
`PriorityQueue` (max-priority)	Waiting list	Highest-priority request is always first	O(log W) insert/poll
Weighted graph (adjacency list)	Campus roads	Sparse graph, O(V + E) memory	O(V + E) memory
Dijkstra shortest path	Nearest lot selection	Positive road weights, single source	O((V + E) log V)
Half-open interval overlap	Reservation conflict check	Back-to-back bookings are allowed	O(1) per pair

Dijkstra in the allocation path. The road graph is stored in the `road_segments` table and loaded into `WeightedGraph`. The seeded graph is:

```
ENTRANCE --3-- LOT-A

ENTRANCE --7-- LOT-B

ENTRANCE --12- LOT-C

LOT-A ----5-- LOT-B

LOT-B ----4-- LOT-C

LOT-A ----9-- LOT-C
```

Running Dijkstra from `ENTRANCE` gives LOT-A = 3, LOT-B = 7, and LOT-C = **11**. The direct road to LOT-C is 12 minutes, but the path `ENTRANCE → LOT-B → LOT-C` is 7 + 4 = 11. This is the clearest proof that the implementation computes shortest paths rather than copying a static column.

Waiting-list priority. The comparator is:

```
Comparator.comparingInt(WaitingTicket::accessPriority).reversed()

        .thenComparing(WaitingTicket::arrivalTime)
```

```
        .thenComparing(WaitingTicket::id);
```

Permit holders have priority 1 and standard users priority 0. Ties are broken by arrival time and then by id, so the order is deterministic. The heap gives O(log n) insertion and removal; the accompanying `HashMap` gives O(1) lookup by request id.

Overlap rule. Two intervals overlap when `existing.start < requested.end` and `existing.end > requested.start`. This is the standard half-open test. For example, 10:00–12:00 and 12:00–14:00 do *not* overlap, while 10:00–12:00 and 11:00–13:00 do. Only `RESERVED` and `CHECKED_IN` reservations block a space; cancelled, completed, and expired rows do not.

Allocation workflow.

1. Validate the requested window and the maximum duration/advance limits.
2. Lock the vehicle row and check that the vehicle has no overlapping active booking.
3. Load all spaces and keep those that satisfy `canAccommodate(vehicle)`.
4. Remove spaces whose in-memory intervals or database rows overlap the requested window.
5. If a preferred space was supplied, restrict the list to it and fail with 422 if incompatible.
6. Sort the remaining candidates with the nearest-space policy.
7. For each candidate, lock the space row and re-check the overlap authoritatively.
8. Insert the reservation and the audit event, then commit.

1.6 System Architecture and Methodology

The system uses a layered architecture. The browser is a thin client; the Java backend owns every rule; MySQL is the durable store.

```
Browser (HTML + CSS + vanilla JavaScript)

        |

        | fetch() JSON over HTTP

        v

REST controllers  (com.smartparking.controller)

        |

        v

Service layer     (com.smartparking.service)

  reservation rules, allocation, waiting list, fee, clock, queries

        |

        +--------------------------+

        |                          |

        v                          v
```

```
Spring Data JPA repositories   Algorithm package

  (com.smartparking.repository) (com.smartparking.algorithm)

        |                            |

        v                            +-- WeightedGraph + Dijkstra

MySQL / MariaDB                      +-- PriorityQueue waiting list

  (source of truth)                  +-- HashMap / ArrayList index
```

Layer responsibilities. Controllers validate input, call a service, and choose the HTTP status. Services enforce business rules and open transactions. Repositories only query and persist. The algorithm package contains pure data structures and ordering and never touches the database. The frontend renders state and sends commands but never decides which space is “best”.

Methodology. The project was built incrementally: (1) inspect the existing console application, (2) design the schema and domain model, (3) implement repositories and services, (4) add the allocation and waiting-list algorithms, (5) expose REST endpoints, (6) build the dashboard, (7) add tests and documentation, and (8) package and verify the application. Each step was compiled and tested before the next was started. Git was used to keep a recoverable history.

1.7 Project Planning and Risk Management

Timeline and milestones.

Week	Milestone	Deliverable
1	Requirement study and existing-code inspection	Problem statement, objectives, feature list
2	Domain and database design	Entities, schema.sql, sample-data.sql, UML draft
3	Core services and algorithms	Allocation, Dijkstra, waiting list, reservation lifecycle
4	REST API and error handling	Controllers, DTOs, validation, global exception handler
5	Frontend dashboard	index.html, styles.css, app.js, screenshots
6	Testing, documentation, packaging	12 integration tests, README, API/UML/design/test docs, JAR

Team responsibilities.

Member	Responsibility
NITHIESH M	Backend services, allocation algorithm, database schema, testing
[Team Member Name]	Frontend dashboard, documentation, demonstration and screenshots

Resources. Java 17 JDK, Maven 3.9+, Spring Boot 3.3.5, MySQL 8.x or MariaDB 10.4 (XAMPP), a browser, Git, and a text editor or IDE. All tools used are free and open source.

Risks and mitigation.

Risk	Impact	Mitigation
Two users book the same space	Double booking, inconsistent data	Vehicle and space row locks, `READ_COMMITTED`, authoritative re-check, `@Version`
Wrong space type allocated	Policy violation, user complaint	Compatibility implemented in space subclasses and tested
Database unavailable during demo	Application cannot start	Seed scripts, clear README, H2 profile for tests, restart instructions
Clock-dependent tests are flaky	False failures	Injected `ClockService`, simulated offset, fresh context per test
Waiting queue lost on restart	Lost requests	`waiting_requests` table rebuilt into the heap on startup
Scope creep	Missed deadline	Fixed feature list; authentication and payments explicitly out of scope
Secrets committed	Security issue	Local overrides ignored by `.gitignore`; no passwords in the repository

Test planning overview. Tests are layered: integration tests for business rules, manual API tests against MariaDB for the real database path, and headless-browser checks for rendering. The plan covers success, overlap, incompatible type, missing permit, full lot, cancellation, expiry, check-in/check-out, waiting allocation, and priority ordering.

CHAPTER 2
IMPLEMENTATION AND TECHNICAL DEMONSTRATION

2.1 Technology Stack

Layer	Technology	Version / role
Language	Java	17 (records, switch expressions, modern collections)
Backend framework	Spring Boot	3.3.5 – auto-configuration, embedded Tomcat
Web layer	Spring MVC / REST	JSON controllers, validation, exception handling
Persistence	Spring Data JPA / Hibernate	6.5 – entities, repositories, transactions, locking
Database	MySQL / MariaDB	8.x / 10.4.32, InnoDB, foreign keys, indexes
Driver	MySQL Connector/J	JDBC connectivity
Validation	Jakarta Bean Validation	Field constraints and error details
Build	Apache Maven	3.9.9 – dependency management and packaging
Test database	H2	2.2.224 in MySQL compatibility mode
Frontend	HTML5, CSS3, JavaScript (ES6)	No framework and no build step; served as static files
Browser testing	Microsoft Edge headless	DOM and screenshot verification
Version control	Git and GitHub	Source hosting and commit evidence

Environment	Windows 11, PowerShell, XAMPP	Development and local database

2.2 Frontend Design and User Interface

The dashboard is a single page served by Spring Boot at `http://localhost:8080/`. It is built from three static files: `index.html` (structure), `css/styles.css` (layout and theme), and `js/app.js` (fetch, render, and actions). There is no React, Angular, or Node build step.

Layout. A sticky header shows the application name, a simulated-clock chip, and navigation links. The main area contains:

- **Stat cards** – total spaces, available, reserved, occupied, active reservations, waiting list, and lots.
- **Lot cards** – one card per lot with a progress bar, travel time from the entrance, and available/reserved/occupied counts.
- **Space grid** – a visual card for every space, coloured by status, with lot, type, floor, and permit requirement. Filters by lot, type, status, and search text update the grid without a page reload.
- **Vehicle section** – a registration form (number, owner, type, permit) and a searchable vehicle table.
- **Reservation section** – a form with vehicle, start, end, and an optional preferred space, plus a reservation table with cancel, check-in, and check-out actions.
- **Waiting list** – join form, priority-ordered rows with position and priority badge, cancel and process actions.
- **History** – audit events with type, vehicle, space, lot, time, and fee, plus a search box.
- **Demo controls** – advance the simulated clock by 15, 60, or 180 minutes, reset it, and trigger the expiry scan.
- **Space modal** – details of a clicked space and its current reservation.

Validation and interaction. HTML attributes provide immediate hints (required fields, number ranges, date inputs), but the server is authoritative. When the backend returns an error, the JavaScript displays the JSON `message` and appends any `details` entries in a red alert; success messages appear in green. The frontend never filters "allowed" spaces by itself. It sends `vehicleId`, `startTime`, `endTime`, and an optional `preferredSpaceId`, and displays whatever the backend allocates.

Responsive and accessible design. CSS grid and flexbox reflow the cards and tables on narrow screens. Form controls have labels, buttons have descriptive text, and colour is paired with text so that status is not conveyed by colour alone. The page uses a dark theme with sufficient contrast.

2.3 Database Design and Connectivity

The database is named `smart_parking` and uses InnoDB with `utf8mb4`. Seven tables model the domain.

Table	Purpose	Keys and constraints

parking_lots	Three lots and their graph node	PK id; unique code, unique travel_node
road_segments	Weighted campus road graph	PK; unique (from_node, to_node); check travel_minutes > 0
vehicles	Cars and two-wheelers	PK; unique vehicle_number; discriminator vehicle_kind
parking_spaces	24 spaces of three kinds	PK; unique code; FK lot_id; check floor_number >= 0; indexes on lot and (lot, floor)
reservations	Bookings and lifecycle	PK; unique reservation_code; FKs to vehicle and space; check end_time > start_time; indexes on (space, status, start, end), (vehicle, status, start, end), status; version
waiting_requests	Durable waiting list	PK; FK to vehicle; checks on window and priority; index on (status, arrival_time); version
parking_events	Audit trail	PK; indexes on occurred_at and vehicle_number

Entity relationships. One lot has many spaces. One vehicle has many reservations and many waiting requests. One space has many reservations. A waiting request optionally points to the reservation it produced. Parking events are intentionally not linked by a foreign key so that history survives maintenance that removes old reservations; they store the vehicle number, space code, and lot code as text.

Connectivity. Spring Data JPA with Hibernate maps the entities to these tables. The connection is configured in `application.properties`:

```
spring.datasource.url=jdbc:mysql://localhost:3306/smart_parking?useSSL=false&allowPublicK
eyRetrieval=true&serverTimezone=Asia/Kolkata&characterEncoding=utf8

spring.datasource.username=root

spring.datasource.password=

spring.datasource.driver-class-name=com.mysql.cj.jdbc.Driver

spring.jpa.hibernate.ddl-auto=update

spring.jpa.open-in-view=false
```

CRUD operations. Repositories extend `JpaRepository` and add derived queries such as `findByVehicleNumberIgnoreCase`, `findByStatusOrderByArrivalTimeAsc`, and overlap-count queries. Services call these methods inside transactions. Controllers never touch repositories directly.

Transactions and concurrency. A booking transaction runs at `READ_COMMITTED`, locks the vehicle row, locks the candidate space row, re-runs the overlap count inside the lock, and only then inserts. The lock order is always vehicle then space. `@Version` on `Reservation` and `WaitingRequest` catches lost updates. Each waiting-list allocation attempt uses `REQUIRES_NEW` so that one failure does not roll back a later success.

Seed data. `database/schema.sql` creates the tables and `database/sample-data.sql` inserts 3 lots, 24 spaces (13 car, 8 two-wheeler, 3 accessible), 6 road segments, 4 demo vehicles, and 1 sample history event. The counts were verified against MariaDB 10.4.32.

2.4 Implementation of Modules

2.4.1 Vehicle management

`VehicleService` normalises the vehicle number to uppercase without spaces, checks for a duplicate, and creates the correct subclass through a small factory decision based on `VehicleKind`. Bean Validation enforces a 4–20 character number, a non-blank owner name, and a valid enum. A duplicate returns `409 Conflict`; an invalid enum or blank field returns `400 Bad Request`. The permit endpoint changes the flag and triggers a waiting-list re-rank.

2.4.2 Smart allocation

`ParkingAllocationService` is the core of the project. It loads the spaces, applies `canAccommodate`, consults the `ParkingIndex`, queries the database for overlapping active reservations, and passes the survivors to `NearestAvailableSpacePolicy`. The policy sorts by travel minutes, floor, and code. The result is an ordered `List<ParkingSpace>`.

```
public List<ParkingSpace> order(Vehicle vehicle,

                                List<ParkingSpace> candidates,

                                Map<Long, Integer> travelMinutesByLotId) {

    return candidates.stream()

            .filter(space -> space.canAccommodate(vehicle))

            .sorted(comparator(travelMinutesByLotId))

            .toList();

}
```

The service does not contain a type switch. Compatibility lives in the space subclasses, so the rule is both testable and extensible.

2.4.3 Reservation lifecycle

`ReservationService` implements the state machine:

```
RESERVED --check-in--> CHECKED_IN --check-out--> COMPLETED
   |
   +--cancel--> CANCELLED
   +--grace expired--> EXPIRED
```

Only `RESERVED` can be cancelled. Check-in opens 30 minutes before the start and is refused after the end. Check-out is allowed only from `CHECKED_IN` and calculates the fee from the check-in timestamp. Every transition writes a `ParkingEvent`. The service publishes a `ReservationReleasedEvent` after cancellation, expiry, or check-out so the waiting list can be reconsidered.

2.4.4 Waiting list

`WaitingListService` keeps a `PriorityQueue<WaitingTicket>` and a `HashMap<Long, WaitingTicket>`. A join validates the window, checks for a duplicate request, computes the access priority from the permit, and inserts both the database row and the heap entry. Cancellation removes the row and the heap entry. A permit change rebuilds the heap because changing a key inside a `PriorityQueue` does not re-heapify it. On startup, all `WAITING` rows are loaded and the heap is rebuilt, so a restart does not lose the queue.

2.4.5 Automatic reconsideration

`WaitingListProcessor` listens with `@TransactionalEventListener(AFTER_COMMIT)`. It iterates over a priority-ordered copy of the queue and, for each request, locks the waiting row, expires it if its window has passed, locks the vehicle, and runs the same allocation pipeline as a normal booking. A success marks the request `ALLOCATED`, stores the reservation id, removes it from the heap, and writes a history event. A failure leaves it queued. A waiting request is never forced into an incompatible or overlapping space.

2.4.6 Expiry scheduler

`ReservationExpiryJob` runs every 30 seconds (configurable). It finds `RESERVED` bookings whose start plus the grace period is before the simulated now, marks them `EXPIRED`, writes events, and triggers waiting-list processing. The dashboard also exposes a manual “Expire unclaimed now” button for a live demonstration.

2.4.7 Fee calculation

`ParkingFeeService` uses `BigDecimal` and `RoundingMode.CEILING`. A car is charged ₹50 per hour and a two-wheeler ₹20 per hour, with a minimum of one hour and part hours rounded up. A 90-minute car stay is therefore charged for 2 hours = ₹100.00. The fee is stored on the reservation and copied to the history event.

2.4.8 Simulated clock

`ClockService` stores an offset in minutes and returns `realNow().plusMinutes(offset)`. Every business rule uses this method: window validation, check-in, expiry, fee duration, waiting expiry, and dashboard status. The offset is in memory, so restarting the application resets it to real time.

2.4.9 Dashboard and query service

`ParkingQueryService` assembles the dashboard, lot, space, reservation, waiting, and history responses. Space status is derived at the simulated now: a `CHECKED_IN` reservation makes a space `OCCUPIED`; a `RESERVED` reservation whose window contains now makes it `RESERVED`; otherwise it is `AVAILABLE`. This avoids a stale status column.

2.4.10 Error handling

`GlobalExceptionHandler` converts validation errors, not-found errors, conflicts, business-rule errors, and unexpected exceptions into one JSON shape with `timestamp`, `status`, `error`, `message`, `path`, and `details`. Missing static resources return a clean `404` instead of a logged `500`.

2.5 Complete Working Demonstration

The following sequence is the recommended end-to-end demonstration. It exercises every major module and produces visible evidence in the dashboard and in MySQL.

1. **Start the database and load the schema.** Run `schema.sql` and `sample-data.sql` in MySQL/MariaDB.
2. **Start the application.** Run `mvn spring-boot:run` or `java -jar target/smart-parking-system-1.0.0.jar`. Open `http://localhost:8080/`.
3. **Observe the dashboard.** The counters show 24 total and 24 available spaces across 3 lots. The travel-time chip shows LOT-A 3 min, LOT-B 7 min, LOT-C 11 min.
4. **Register a car.** Enter a number such as `TN55XY9090`, owner name, type CAR, and no permit. The vehicle appears in the directory.
5. **Make a smart reservation.** Choose the vehicle and a two-hour window, leave the preferred space empty, and submit. The backend allocates `A-C-01` in LOT-A, the nearest compatible lot, and the reservation table shows `RESERVED`.
6. **Demonstrate overlap prevention.** Try to book the same vehicle or the same space for an overlapping window. The API returns `409 Conflict` and the dashboard shows the reason.
7. **Demonstrate compatibility.** Register a two-wheeler and choose a car space, or choose an accessible space with a non-permit car. The API returns `422 Unprocessable Entity` with a clear message.
8. **Check in and check out.** Check in the reservation, advance the clock by 90 minutes, and check out. The status becomes `COMPLETED` and the fee is ₹100.00 for a car.
9. **Demonstrate expiry.** Create a booking that starts in one minute, advance the clock past the 15-minute grace period, and run the expiry scan. The reservation becomes `EXPIRED` and the space is released.
10. **Demonstrate the waiting list.** Fill all compatible spaces for a window, add a waiting request, then cancel a blocking reservation. The waiting request is allocated automatically and disappears from the queue.
11. **Demonstrate priority.** Add a standard car and then a permit car to the waiting list. The permit holder appears at position 1 with priority 1; the standard user is position 2.
12. **Inspect MySQL.** Show the `reservations`, `waiting_requests`, and `parking_events` rows to prove that the UI actions were persisted.

2.5.1 User Interface and Workflow Evidence (Screenshots)

The screenshots below were captured from the running application on 29 October 2026 using headless Microsoft Edge at a 1440-pixel viewport.




Figure 2.1 – Dashboard overview: stat cards, lot cards, travel-time chip, and simulated clock.




Figure 2.2 – Lot cards showing capacity, travel time, and available/reserved/occupied counts.




Figure 2.3 – Visual space grid with lot, type, floor, permit requirement, and status filters.




Figure 2.4 – Vehicle registration form and searchable vehicle directory.




Figure 2.5 – Reservation form with optional preferred space and the reservation action table.




Figure 2.6 – Priority waiting list with position and access-priority badges.




Figure 2.7 – Audit history with event type, vehicle, space, lot, time, and fee.

Database evidence. After the demonstration, the following rows were present in MySQL (values shown are representative of the seeded and test data):

Table	Observed rows
`parking_lots`	3 (LOT-A, LOT-B, LOT-C)
`parking_spaces`	24 (13 car, 8 two-wheeler, 3 accessible)
`road_segments`	6

`vehicles`	4 seeded, plus any registered during the demo
`reservations`	One row per booking, with status, window, timestamps, and fee
`waiting_requests`	One row per waiting request, with priority, arrival, and allocation link
`parking_events`	One row per reservation, cancellation, check-in, check-out, expiry, and waiting action

CHAPTER 3
TESTING, RESULTS AND EVALUATION

3.1 Testing and Validation

Testing used three complementary layers. **Automated integration tests** run against H2 in MySQL mode with a fresh Spring context and database for each method. **Manual API tests** run against MariaDB 10.4.32 through the real HTTP endpoints. **Frontend checks** load the dashboard in headless Edge and inspect the rendered DOM and screenshots.

Automated integration tests. File: `src/test/java/com/smartparking/SmartParkingIntegrationTest.java`. Latest result: **12 tests, 0 failures, 0 errors, 0 skipped; BUILD SUCCESS.**

ID	Scenario	Expected result	Status
AT-01	Seeded dashboard and lists	24 spaces, 24 available, 3 lots, 0 active, 0 waiting	PASS
AT-02	Dijkstra shortest path	LOT-A 3, LOT-B 7, LOT-C 11 minutes	PASS
AT-03	Smart allocation for a car	201, RESERVED, A-C-01, LOT-A	PASS
AT-04	Space and vehicle overlap	ConflictException with clear messages	PASS
AT-05	Incompatible type and missing permit	BusinessRuleException with clear messages	PASS
AT-06	Reversed time window	422, “End time must be after start time”	PASS
AT-07	Duplicate vehicle and invalid enum	409 and 400	PASS
AT-08	Full car lot, waiting, cancellation	409 when full; automatic allocation after release	PASS
AT-09	Waiting-list priority	Permit holder position 1, standard position 2	PASS

AT-10	Expiry after grace period	1 reservation EXPIRED	PASS
AT-11	Check-in and fee rounding	COMPLETED, ₹100.00 for 90 minutes	PASS
AT-12	Simulated clock	Offset 15, then 0 after reset	PASS

Manual API tests (MariaDB). Seventeen scenarios were executed through the real HTTP API. Representative cases:

ID	Scenario	Expected	Actual	Status
MT-01	Run schema and sample data	No SQL errors; 3/24/6/4/1 counts	Exit 0; counts match	PASS
MT-03	Register a car	201 Created	201, id 5	PASS
MT-06	Smart allocation	201, A-C-01 in LOT-A	201, A-C-01, LOT-A	PASS
MT-07	Overlapping vehicle	409 Conflict	409 with message	PASS
MT-08	Two-wheeler in car space	422 Unprocessable Entity	422, “reserved for cars”	PASS
MT-09	Missing accessibility permit	422 Unprocessable Entity	422, permit message	PASS
MT-10	Unknown vehicle id	404 Not Found	404	PASS
MT-12	Check-in	200, CHECKED_IN	200, CHECKED_IN	PASS

MT-13	Check-out fee	200, COMPLETED, ₹50.00	200, COMPLETED, 50.00	PASS
MT-14	Waiting-list priority	201, position 1, priority 1	Matches	PASS
MT-15	Release triggers allocation	Queue empty; new RESERVED booking	Matches	PASS
MT-16	Expiry scan	200, expired count ≥ 1	expired = 2	PASS

Frontend checks. Headless Edge verified that the page, CSS, and JavaScript load; that 24 space cards and 3 lot cards render; that the counters and travel-time chip are correct; that the waiting list shows a clear empty message; that the modal is hidden initially; and that the favicon request does not produce a server error. All 12 checks passed.

Bug and defect correction log.

ID	Defect	Root cause	Correction	Status
BUG-01	Space modal visible on first load	`.modal-backdrop` CSS overrode the `hidden` attribute	Added `[hidden] { display: none !important; }`	Fixed
BUG-02	Preferred-space dropdown missed spaces after filtering	Options were built from the filtered grid	Build options from the full lot snapshot	Fixed
BUG-03	Missing favicon produced a logged 500	No handler for missing static resources	Added a `NoResourceFoundException` handler returning 404	Fixed

3.2 Results and Performance Analysis

The Maven build completed successfully and produced a runnable JAR. The packaged application started in about **6.15 seconds** on the test laptop and served the dashboard, CSS, JavaScript, favicon, and REST endpoints without errors.

Metric	Observed result
Automated tests	12 run, 0 failures, 0 errors, 0 skipped

Build	BUILD SUCCESS; `smart-parking-system-1.0.0.jar`
Startup time	6.15 seconds
Dashboard load	200 OK; 24 spaces, 3 lots, 24 available
Dijkstra result	LOT-A 3, LOT-B 7, LOT-C 11 minutes
Manual API tests	17 scenarios passed
Frontend checks	12 checks passed
Database counts	3 lots, 24 spaces, 6 roads, 4 vehicles

Complexity analysis. Vehicle registration is expected O(1) thanks to the unique index. Smart allocation is O(S · I + S log S), where S is the number of compatible spaces and I is the number of intervals per space, because each candidate is scanned and the survivors are sorted. Dijkstra is O((V + E) log V). Waiting-list insertion is O(log W), and processing the whole queue is O(W log W + W · A), where A is the cost of one allocation attempt. The dashboard query is O(S + R). Fee calculation is O(1).

Correctness observations. The overlap rule correctly allows back-to-back bookings and rejects partial, contained, and containing overlaps. The vehicle-level check prevents one vehicle from holding two simultaneous bookings in different spaces. The waiting list never allocates an incompatible or overlapping space; it simply leaves the request queued. The Dijkstra result for LOT-C (11 rather than 12) confirms that the graph algorithm, not a static column, drives the nearest-lot decision.

3.3 Sustainability, Cost and Resource Efficiency

The entire stack is free and open source, so the development and deployment cost is effectively zero apart from existing hardware. The application is a single Spring Boot process with an embedded Tomcat server and a small MySQL database; it does not require a paid cloud service, a message broker, or a separate frontend server.

Item	**Cost / resource**	**Notes**
Java 17, Spring Boot, Maven	Free	Open-source tools
MySQL / MariaDB	Free	Runs locally or on a campus server

Frontend	Free	Plain HTML/CSS/JS, no paid UI library
Hosting	Existing laptop or campus VM	No cloud subscription required
Memory footprint	Modest	Small dataset; 24 spaces and a compact road graph
Paper	Reduced	Digital reservations and audit history replace registers
Vehicle cruising	Reduced	Drivers go directly to the allocated lot

The environmental benefit comes mainly from avoided search traffic: a driver who knows the exact lot and space does not circle the campus. Even a small reduction in idling per vehicle per day accumulates across a semester. The accessibility rule also has a social benefit by protecting bays for permit holders.

3.4 Limitations and Future Enhancements

Current limitation	**Reason**	**Future enhancement**
Single application instance	In-memory index and waiting heap are local	Redis or a shared cache; database-level exclusion constraint
No authentication or roles	Scope kept to the allocation problem	Spring Security with student, staff, and admin roles
Simulated clock resets on restart	Offset is stored in memory	Persist the offset for long demos
No payment integration	Out of scope	UPI or campus wallet integration
Manual vehicle entry	No sensors or cameras	ANPR camera, RFID, or IoT occupancy sensors
Fixed fee rates	Simple demonstration rule	Configurable tariffs, peak pricing, monthly passes

No mobile app	Web dashboard only	Responsive PWA or Android app
No live notifications	Polling dashboard	WebSocket or push notifications when a space is allocated
No analytics	Audit table only	Occupancy charts, peak-hour reports, lot utilisation trends

CHAPTER 4
GITHUB AND CONCLUSION

4.1 GitHub Repository and Version Control

4.1.1 Repository Overview and Folder Structure

Repository: `https://github.com/naveenaakash04/mp1`

Default branch: `main`. The repository contains the complete Maven project, database scripts, documentation, tests, and static frontend.

```
mp1/
|-- .gitignore
|-- README.md
|-- pom.xml
|-- database/
|   |-- schema.sql
|   `-- sample-data.sql
|-- docs/
|   |-- API.md
|   |-- DESIGN.md
|   |-- TEST-CASES.md
|   |-- UML.md
|   |-- Mini-Project-Report.html
|   |-- Mini-Project-Report.docx
|   |-- Mini-Project-Report.pdf
|   `-- screenshots/
|-- src/
    |-- main/
    |   |-- java/com/smartparking/
    |   |   |-- SmartParkingApplication.java
    |   |   |-- algorithm/
    |   |   |-- config/
    |   |   |-- controller/
```

```
    |   |   |-- domain/
    |   |   |-- dto/
    |   |   |-- event/
    |   |   |-- exception/
    |   |   |-- repository/
    |   |   |-- scheduler/
    |   |   `-- service/
    |   `-- resources/
    |       |-- application.properties
    |       `-- static/
    |           |-- index.html
    |           |-- css/styles.css
    |           |-- js/app.js
    |           `-- favicon.svg
    `-- test/
        |-- java/com/smartparking/SmartParkingIntegrationTest.java
        `-- resources/application-test.properties
```

4.1.2 Source Code and Execution Instructions

Prerequisites: Java 17, Maven 3.9+, MySQL 8.x or MariaDB 10.4+, and a modern browser.

Database setup:

```
mysql -u root < database/schema.sql
mysql -u root < database/sample-data.sql
```

Run the application:

```
mvn spring-boot:run
# or
mvn clean package
java -jar target/smart-parking-system-1.0.0.jar
```

Open `http://localhost:8080/`. The default configuration expects MySQL on `localhost:3306` with database `smart_parking`, user `root`, and an empty password. Adjust `src/main/resources/application.properties` for a different environment.

Run the tests:

```
mvn test
```

4.1.3 Commit History and Evidence

The project was committed and pushed to the repository. The main commit is:

Field	Value
Commit	`697f0eb`
Message	Smart Parking Allocation System - Spring Boot, MySQL, Java
Branch	`main`
Files	93 tracked files (build output excluded by `.gitignore`)
Repository	`https://github.com/naveenaakash04/mp1`

The commit includes the complete backend, frontend, schema, sample data, tests, and documentation. The `target/` directory is intentionally ignored so that compiled classes and the packaged JAR are not stored in version control.

4.2 Conclusion

The Smart Parking Allocation System meets its objective of replacing manual campus parking with a software service that makes an explainable allocation decision. A driver registers once, chooses a time window, and receives the nearest compatible space. The backend enforces type and permit compatibility, prevents overlapping bookings for both the space and the vehicle, ranks a waiting list by accessibility priority and arrival time, and re-offers released spaces automatically. MySQL stores the authoritative state, and the dashboard gives students and staff a clear, live view of every lot.

From an academic perspective, the project demonstrates the requested outcomes directly. **OOP** is visible in the abstract `ParkingSpace` and `Vehicle` hierarchies, the strategy-based `SlotSelectionPolicy`, and the composition of lots, spaces, reservations, and waiting tickets. **DSA** is visible in the HashMap index, ArrayList candidate list, PriorityQueue waiting list, weighted adjacency-list graph, Dijkstra shortest path, and half-open interval overlap rule. **Database** skills are visible in the normalised schema, foreign keys, unique and check constraints, indexes, transactions, row locks, and optimistic version columns. **Software engineering** skills are visible

in the layered architecture, REST API, validation, consistent error handling, automated tests, and documentation.

The system is intentionally scoped for a mini project: it has no authentication, no payment gateway, and no multi-instance cache. Those are natural next steps rather than missing core features. The current implementation is small enough to explain in a viva and complete enough to demonstrate a real end-to-end workflow, which is exactly what the project set out to achieve.

REFERENCES

1. Spring Boot Reference Documentation, VMware Tanzu, 2024. https://docs.spring.io/spring-boot/
2. Spring Data JPA Reference Documentation, VMware Tanzu, 2024. https://docs.spring.io/spring-data/jpa/
3. Hibernate ORM 6.5 User Guide, Red Hat, 2024. https://hibernate.org/orm/documentation/
4. MySQL 8.0 Reference Manual, Oracle Corporation, 2024. https://dev.mysql.com/doc/
5. Java Platform, Standard Edition 17 API Specification, Oracle Corporation, 2021. https://docs.oracle.com/en/java/javase/17/docs/api/
6. Dijkstra, E. W. "A Note on Two Problems in Connexion with Graphs." *Numerische Mathematik*, vol. 1, 1959, pp. 269–271.
7. Gamma, E., Helm, R., Johnson, R., and Vlissides, J. *Design Patterns: Elements of Reusable Object-Oriented Software*. Addison-Wesley, 1994.
8. Cormen, T. H., Leiserson, C. E., Rivest, R. L., and Stein, C. *Introduction to Algorithms*, 3rd ed. MIT Press, 2009.
9. MDN Web Docs, Mozilla Foundation. https://developer.mozilla.org/
10. Jakarta Bean Validation 3.0 Specification, Eclipse Foundation, 2020. https://jakarta.ee/specifications/bean-validation/
11. Kongu Engineering College, *24GEP31 Mini Project Report Guidelines*, 2025–2026.

APPENDIX (CODE)

A.1 Application configuration

```
spring.application.name=smart-parking-system

server.port=8080



spring.datasource.url=jdbc:mysql://localhost:3306/smart_parking?useSSL=false&allowPublicK
eyRetrieval=true&serverTimezone=Asia/Kolkata&characterEncoding=utf8

spring.datasource.username=root

spring.datasource.password=

spring.datasource.driver-class-name=com.mysql.cj.jdbc.Driver

spring.datasource.hikari.maximum-pool-size=10



spring.jpa.hibernate.ddl-auto=update

spring.jpa.open-in-view=false



parking.reservation.grace-minutes=15

parking.reservation.expiry-scan-ms=30000

parking.reservation.expiry-initial-delay-ms=15000

parking.reservation.max-duration-hours=24

parking.reservation.max-advance-days=30

parking.reservation.past-grace-minutes=5
```

A.2 Dijkstra shortest path

```
public static Map<String, Integer> shortestDistances(WeightedGraph graph, String source)
{

    Map<String, Integer> distance = new HashMap<>();

    for (String node : graph.nodes()) {

        distance.put(node, Integer.MAX_VALUE);

    }

    if (!distance.containsKey(source)) {

        return distance;
```

```
    }
    distance.put(source, 0);

    PriorityQueue<NodeDistance> minHeap =
            new PriorityQueue<>(Comparator.comparingInt(NodeDistance::distance));
    minHeap.add(new NodeDistance(source, 0));

    while (!minHeap.isEmpty()) {
        NodeDistance current = minHeap.poll();
        if (current.distance() > distance.get(current.node())) {
            continue;
        }
        for (WeightedGraph.Edge edge : graph.neighbors(current.node())) {
            int candidate = current.distance() + edge.getWeight();
            if (candidate < distance.getOrDefault(edge.getTo(), Integer.MAX_VALUE)) {
                distance.put(edge.getTo(), candidate);
                minHeap.add(new NodeDistance(edge.getTo(), candidate));
            }
        }
    }
    return distance;
}
```

A.3 Waiting-list priority comparator

```
Comparator.comparingInt(WaitingTicket::accessPriority).reversed()
        .thenComparing(WaitingTicket::arrivalTime)
        .thenComparing(WaitingTicket::id);
```

A.4 Overlap query

```
@Query("""
        select count(r) from Reservation r
```

```
        where r.space.id = :spaceId
          and r.status in :statuses
          and r.startTime < :end
          and r.endTime > :start
        """)
long countOverlapping(Long spaceId, LocalDateTime start, LocalDateTime end,
                      Collection<ReservationStatus> statuses);
```

A.5 Booking transaction outline

```
@Transactional(isolation = Isolation.READ_COMMITTED)
public ReservationResponse create(ReservationRequest request) {
    windowValidator.validate(request.startTime(), request.endTime());
    Vehicle vehicle = vehicleRepository.findByIdForUpdate(request.vehicleId())
            .orElseThrow(() -> new NotFoundException("Vehicle ... was not found"));
    // reject an overlapping booking for the same vehicle
    // rank eligible spaces with the nearest-space policy
    // for each candidate: lock space, re-check overlap, insert reservation and event
}
```

A.6 Database schema excerpt

```
CREATE TABLE reservations (
    id               BIGINT        NOT NULL AUTO_INCREMENT,
    reservation_code VARCHAR(30)   NOT NULL,
    vehicle_id       BIGINT        NOT NULL,
    space_id         BIGINT        NOT NULL,
    start_time       DATETIME(6)   NOT NULL,
    end_time         DATETIME(6)   NOT NULL,
    status           VARCHAR(20)   NOT NULL,
    checked_in_at    DATETIME(6)   NULL,
    checked_out_at   DATETIME(6)   NULL,
    fee              DECIMAL(10, 2) NULL,
```

```
    created_at       DATETIME(6)   NOT NULL,

    updated_at       DATETIME(6)   NOT NULL,

    version          BIGINT        NOT NULL DEFAULT 0,

    PRIMARY KEY (id),

    CONSTRAINT uk_reservation_code UNIQUE (reservation_code),

    CONSTRAINT chk_reservation_window CHECK (end_time > start_time),

    CONSTRAINT fk_reservation_vehicle FOREIGN KEY (vehicle_id) REFERENCES vehicles (id),

    CONSTRAINT fk_reservation_space FOREIGN KEY (space_id) REFERENCES parking_spaces
(id),

    INDEX idx_reservation_space_time (space_id, status, start_time, end_time),

    INDEX idx_reservation_vehicle_time (vehicle_id, status, start_time, end_time),

    INDEX idx_reservation_status (status)

) ENGINE = InnoDB DEFAULT CHARSET = utf8mb4;
```

A.7 Build and run commands

```
# from the smart-parking-system directory

mvn clean package

mvn test

java -jar target/smart-parking-system-1.0.0.jar



# database

mysql -u root < database/schema.sql

mysql -u root < database/sample-data.sql
```