# VISVESVARAYA TECHNOLOGICAL UNIVERSITY
## "Jnana Sangama", Belgavi-590018

*A PROJECT REPORT ON*

# "DEEP LEARNING APPROACH FOR INTRACRANIAL BRAIN HEMORRHAGE DETECTION"

***Submitted in partial fulfillment of the requirement for the award of the degree of***

**BACHELOR OF ENGINEERING**

***In***

**COMPUTER SCIENCE & ENGINEERING**

***Submitted by***


**KEERTHAN K (1RR21CS073)**

**MANEESH D (1RR21CS088)**

**NAVEEN G N (1RR21CS100)**

**NISHITHA R (1RR21CS107)**


**Under the Guidance of**


**Dr. S JEYABALAN**
**Professor**
**Dept. of CSE, RRCE**



**DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING**

**RAJARAJESWARI COLLEGE OF ENGINEERING**

**MYSORE ROAD, BANGALORE-560074**

**(An ISO 9001:2008 Certified Institute)**

# RAJARAJESWARI COLLEGE OF ENGINEERING

**MYSORE ROAD, BANGALORE-560074**

**(An ISO 9001:2008 Certified Institute)**

**(Affiliated to Visvesvaraya Technological University, Belagavi)**

## DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

## *CERTIFICATE*

Certified that Project Work entitled

***"DEEP LEARNING APPROACH FOR INTRACRANIAL BRAIN HEMORRHAGE DETECTION"***

Carried out by

**KEERTHAN K (1RR21CS073)**

**MANEESH D (1RR21CS088)**

**NAVEEN G N (1RR21CS100)**

**NISHITHA R (1RR21CS107)**

The student of **"RajaRajeswari College of Engineering"** in partial fulfillment for the award of the degree of **Bachelor of Engineering** in **Computer Science & Engineering** of the Visvesvaraya Technological University, Belgaum during the year **2024–2025.** It is certified that all corrections/suggestions indicated for Internal Assessment have been incorporate in the report deposited in the departmental library. The Project report has been approved as it satisfies the academic requirements in respect of Project work prescribed for the seventh semester.

| …… | …… | …… |
|---|---|---|
| **Signature of Guide** | **Signature of HOD** | **Signature of Principal** |
| **[Dr. S JEYABALAN]**<br>Professor,<br>Dept of CSE<br>RRCE, Bangalore | **[Dr. KIRUBHA D]**<br>Professor and Hod<br>Dept of CSE<br>RRCE, Bangalore | **[Dr. R BALAKRISHNA]**<br>Principal<br>RRCE, Bangalore |

***External Viva-Voce***

| ***Examiners:*** | ***Signature:*** |
|---|---|
| 1._____ | 1._____ |
| 2._____ | 2._____ |

# ABSTRACT

Brain hemorrhage is a life-threatening condition that requires rapid and accurate diagnosis for effective treatment. Traditional diagnostic methods rely heavily on expert radiologists, which can lead to delays and subjective interpretations. In recent years, Machine Learning (ML) and Deep Learning (DL) approaches have emerged as powerful tools for automated brain hemorrhage detection, significantly improving accuracy and efficiency. This study explores various ML and DL techniques for detecting brain hemorrhages from medical imaging modalities such as CT scans and MRI. Convolutional Neural Networks (CNNs), Transfer Learning models (e.g., ResNet, VGG, EfficientNet), and hybrid ML approaches are investigated for their effectiveness in feature extraction and classification. The research also discusses dataset preprocessing, model training, validation, and performance evaluation using metrics such as accuracy, sensitivity, specificity, and AUC-ROC. By leveraging artificial intelligence in medical imaging, this study aims to enhance early detection, assist radiologists in decision-making, and improve patient outcomes. Future research directions include model interpretability, real-time deployment, and integration with clinical workflows.

# ACKNOWLEDGEMENT

We are thankful and convey our sincere gratitude to the Principal, **Dr. R. Balakrishna**, Rajarajeswari College of Engineering, Bangalore.

We convey our sincere gratitude to **Dr. Kirubha D**, Prof. & HOD, Department of Computer Science & Engineering, for her meticulous support, continuing cooperation, valuable suggestions, and encouragement during the development of the project. We also extend our thanks to her for her invaluableguidance to imbibe the requisite knowledge for the success of this project.

We convey our sincere gratitude to **Dr. S Jeyabalan,** Professor, Department of Computer Science & Engineering, for her meticulous support continuing cooperation, valuable suggestions, and encouragement during the development of the project. We also extend our thanks to her for her invaluable guidance to imbibe the requisite knowledge for the success of our project, as an internal guide.

We truly thank our parents who have encouraged us and supported in every stage of this project.

Last but not least, our wishes to the entire Computer Science Department for their guidance, encouragement, inspiration and co-operation at all stages of the progress in this project without which it wouldn't have been a success.

Finally, we express our heartfelt regards to all those who helped us to complete this major project work successfully by providing support, suggestions, advise, guidance and needed encouragement.

KEERTHAN K (1RR21CS073)

MANEESH D (1RR21CS088)

NAVEEN G N (1RR21CS100)

NISHITHA R (1RR21CS107)

# CONTENTS


| SL. NO. | TITLE | PAGE NO |
|---|---|---|
| **1.** | **INTRODUCTION** | 01-08 |
| 1.1 | Existing System | |
| 1.2 | Proposed System | |
| 1.3 | Motivation | |
| 1.4 | Objective of the work | |
| 1.5 | Key Features | |
| **2.** | **LITERATURE SURVEY** | 09-16 |
| **3.** | **SYSTEM REQUIREMENTS** | 17-23 |
| 3.1 | System Analysis | |
| 3.2 | Functional Requirements | |
| 3.3 | Non - Functional Requirements | |
| 3.4 | Tools and Technology Details | |
| **4.** | **SYSTEM DESIGN** | 24-39 |
| 4.1 | System Architecture | |
| 4.2 | Input / Output Design | |
| 4.3 | Object Oriented Design | |
| 4.4 | Algorithm | |
| **5.** | **SYSTEM IMPLEMENTATION** | 40-44 |
| 5.1 | Module Description | |
| 5.2 | System Architecture | |

| | | |
|---|---|---|
| **6.** | **SYSTEM TESTING** | 45-49 |
| 6.1 | Testing | |
| **7.** | **RESULTS AND DISCUSSION** | 50-53 |
| 7.1 | Overview | |
| 7.2 | Snapshots | |
| **8.** | **CONCLUSION** | 54 |
| **9.** | **FUTURE WORK** | 55-56 |
| **10.** | **REFERENCES** | 57-58 |

# LIST OF FIGURES


| FIG. NO. | FIGURE NAME | PAGE NO |
|---|---|---|
| 4.1 | Overall System Architecture | 25 |
| 4.2 | Input Design | 27 |
| 4.2.2 | Use Case Diagram | 29 |
| 4.2.3 | Activity Diagram | 30 |
| 4.2.4 | State Transition Diagram | 32 |
| 4.2.5 | Data Flow Diagram (DFD) | 33 |
| 4.3.3 | Convolutional Neural Network | 36 |
| 5.2.1 | Training Phase | 42 |
| 7.2.1 | Input | 51 |
| 7.2.3 | Training | 52 |
| 7.2.4 | Dataset | 52 |
| 7.2.5 | Output | 53 |
| 7.2.6 | Final Output | 53 |

# CHAPTER 1

# INTRODUCTION

Intracranial brain hemorrhage (ICH) is a severe medical condition that involves bleeding within the brain or the spaces surrounding it. It results from traumatic injuries, aneurysms, or various medical conditions, which leads to a huge variety of symptoms, including headaches, neurological deficits, and even death. Early and accurate detection of ICH is critical for effective treatment and improved patient outcomes. The traditional method of diagnosing ICH depends on clinical expertise and manual analysis of medical imaging data, like CT (Computed Tomography) and MRI (Magnetic Resonance Imaging) scans. However, this process is time-consuming and subject to human error, especially in emergency situations where rapid diagnosis is crucial.

Advances in deep learning are an area of machine learning that significantly improves the analysis of medical images. Deep learning models, in particular CNNs, have shown outstanding ability to detect patterns in complicated imaging data sources, providing them appropriate for the automated detection of conditions such as intracranial brain hemorrhages.

A deep learning model is trained to automatically recognize the presence of hemorrhages in medical images, classifying different types of ICH with high accuracy and speed. This automation can help radiologists reduce the time spent on diagnosis, improve the efficiency of clinical workflows, and provide support in areas with a shortage of medical professionals.

This technology can scan huge amounts of medical images, thereby enabling early intervention and proper management of patients. Moreover, these can be continually improved and modified according to the changing clinical data so that detection systems remain effective as new imaging techniques and conditions are developed.

This challenge has resulted in the pursuit of AI and machine learning, specifically deep learning, as tools to automate detection. Deep learning is a branch of machine learning which can mark a remarkable success on image analysis tasks, specifically with Convolutional Neural Networks (CNNs), specifically designed to automatically discover and extract relevant patterns and features in images. Through deep learning models trained on large medical image datasets, these models can learn to identify the very subtle patterns associated with hemorrhages, which is a possible solution to all those human errors, time constraints, and inaccessibility issues.

Deep learning algorithms, once trained, can assist radiologists by providing automated interpretations of medical images, highlighting potential areas of concern, and even suggesting possible diagnoses. This can make faster decision-making, more consistent results, and a reduction in the diagnostic workload of healthcare professionals. Moreover, deep learning systems are able to be self-improving by acquiring the data, such that the models adapt themselves with changing imaging techniques, the evolving patient demographics, and the new research insights.

The overall strength of deep learning in the medical field, especially for ICH detection, is vast. It not only promises to aid radiologists in making more accurate diagnoses but also has the potential to democratize access to advanced healthcare. For instance, in areas with limited access to skilled radiologists, AI-based diagnostic systems can provide remote support, improving healthcare delivery and outcomes globally.

In the upcoming sections, we will explore the methodology behind deep learning for ICH detection, including data collection, model architecture, training processes, and system requirements. Additionally, we will address the challenges faced in this domain, such as data imbalance, interpretability of results, and requirement for regulatory compliance. Through this discussion, we aim to focus on the transformative role deep learning is intended to play in improving the analysis and treatment of intracranial brain hemorrhages.

## 1.1 Existing System

The current system for detecting brain hemorrhages heavily relies on advanced images such as computed tomography (CT) and magnetic resonance imaging (MRI). These techniques provide detailed scans of the brain, which medical professionals, particularly radiologists, analyze manually to rectify the hemorrhages. This process, though accurate under ideal conditions, is intrinsically time-consuming and, therefore, presents a significant challenge when it occurs in critical conditions where diagnosis needs to be done urgently to treat appropriately. In addition, because the analysis is manual, there is a higher tendency for error, since the radiologist may have problems interpreting the complex patterns within the images. Fatigue and cognitive overload, particularly in high-pressure situations, can form misdiagnoses or oversight of critical abnormalities.

Additionally, the number of skilled radiologists is limited in many regions, particularly in rural and underdeveloped areas. This scarcity delays diagnosis and treatment, worsening patient outcomes. While Computer-Aided Diagnosis (CAD) systems have been developed to assist radiologists, they rely on traditional image processing methods. These procedures generally are not capable of catching the intricate and nuanced patterns connected with brain hemorrhages that reduces their overall effectiveness. Furthermore, the accuracy for these systems varies greatly, depending on the application toward different datasets, and presents inconsistencies that shows the dependency for widespread clinical use.

In recent years, artificial intelligence (AI) has developed as a potential solution to identify the limitations of manual analysis and traditional CAD systems. Machine learning (ML) and deep learning (DL) techniques, especially convolutional neural networks (CNNs), have shown remarkable potential in automating the overall analysis of medical images like CT,MRI and detecting abnormalities with high precision. These advanced approaches can analyze large volumes of imaging data, identify subtle patterns, and generate quicker and more consistent results. However, despite their potential, the combination of AI-based systems into real-world clinical workflows remains limited. Challenges like scarcity of high-quality annotated datasets, the lack of interpretability of AI models, and the timely access for regulatory approvals hinder their adoption. Mentioning these challenges is crucial to transitioning from the existing manual systems to AI-driven solutions that can improve accuracy, efficiency, and accessibility in brain hemorrhage detection.

## 1.2 Proposed System

The proposed system provides leverage advanced deep learning and machine learning approaches to improve the precision and efficiency of accessing brain hemorrhage detection. By employing state-of-the-art artificial intelligence (AI) models, especially convolutional neural networks (CNNs), the system is designed to automate the analysis of medical images, such as CT and MRI scans, and produce rapid and reliable diagnostic results. This system will address the limitations of manual interpretation and traditional Computer-Aided Diagnosis (CAD) systems by incorporating innovative algorithms capable of identifying intricate patterns and features associated with brain hemorrhages.

The core of the proposed system is to train deep learning models on a large dataset of annotated brain images so that the models learn to distinguish between normal and abnormal scans with high precision. Preprocessing techniques such as image enhancement, normalization, and noise reduction will be utilized to provide precise information quality and improve model performance. To further enhance diagnostic accuracy, the system will implement feature extraction procedures that identify subtle signs of hemorrhages, even in cases where visual identification is challenging for human experts.

A key aspect of the proposed system is its ability to provide real-time results, making it particularly valuable in emergency scenarios where timely diagnosis is critical. The system will also be designed to be robust and scalable, capable of handling diverse datasets with varying imaging parameters. Additionally, by integrating explainable AI (XAI) methods, the system will provide interpretable outputs, enabling clinicians to understand the reasoning behind its predictions, thereby building trust and facilitating its adoption in clinical practice.

To ensure accessibility, the proposed system will be developed as a user-friendly platform, potentially deployable on cloud-based or edge computing infrastructures This will make the device suitable for use in remote or resource-limited settings, closing the access gap for expert radiological services. In addition to this, by integrating some of these sophisticated features in the proposed system, one will revolutionize brain hemorrhage detection and eventually improve outcomes in patients with a more relaxed healthcare burden.

## 1.3 Motivation

The motivation for this project aims from the timely need for accuracy , and efficient diagnosis of brain hemorrhages, which are life-threatening medical conditions requiring immediate intervention. Brain hemorrhages, if not detected promptly, can lead to severe complications, including permanent neurological damage or death. In many cases, especially in emergency scenarios, the diagnosis depends on manual interpretation of CT or MRI scans by radiologists, which is time-consuming and also contains human error due to fatigue, cognitive overload, or subtle variations in imaging patterns.

The situation is further aggravated by the shortage of skilled radiologists, particularly in remote, rural, and resource-limited areas. This disparity between the up-surging demand for diagnostic services and the availability of medical expertise underlines a compelling reason for innovative solutions to bridge this gap. This project is motivated by a desire to reduce delays, increase accuracy, and expand the capabilities of diagnostics in the most underserved regions.

Advantages in artificial intelligence, especially deep learning and machine learning, offer a ensuring way to mention these challenges. AI-driven systems have the need to analyze medical images with exceptional speed and precision, identify patterns beyond the capability of human perception, and provide consistent and interpretable diagnostic results. The prospect of using these technologies to bridge the gap in healthcare accessibility and improve outcomes for patients with brain hemorrhages serves as a strong motivator for this project.

Additionally, the project meets the depth objective of bringing techniques into health care for the purpose of bettering the efficiency of diagnostics, cutting down on the cost of health care, and inhancing the quality of care given to patients. It is an opportunity to bring a solution that provides life-saving, reduce the workload of medical professionals, and make it easier for all to have critical diagnostic tools.

## 1.4 Objectives of the work

The core objective of this work is to ensure a design and develop an advanced system for brain hemorrhage detection that leverages cutting-edge deep learning and machine learning techniques to identify the limitations of existing diagnostic methods. This system aims to automate the analysis of CT and MRI scans, enabling faster, more accurate, and reliable diagnoses while reducing depend on manual interpretation by radiologists. By employing sophisticated deep learning models, the project seeks to identify even the most subtle path and types associated with brain hemorrhages, significantly minimizing the problem of diagnostic errors and enhancing the precesion of detection in both routine and emergency cases.

A critical objective is to work with real-time decision support, making sure that the healthcare professionals can have timely diagnostic insights during crucial situations when each second counts. To counter the challenges of data quality and limited availability of annotated datasets, the system integrates preprocessing methods such as noise reduction and data augmentation for robust model training and performance. The predictability of explainable AI (XAI) techniques also ensures that the system's predictions are interpretable, thus facilitating transparency and trust among clinicians and supporting their decision-making process.

This system aims to automate the analysis of CT and MRI scans, providing accurate and rapid diagnoses to reduce reliance on manual interpretation and minimize the risk of misdiagnosis. By leveraging robust deep learning models, the project seeks to identify subtle patterns and features associated with brain hemorrhages, ensuring high diagnostic accuracy even in complex cases. The system has a critical focus on providing real-time decision support to the healthcare professionals, making time to time and effective interventions, especially in emergency situations. It has incorporated preprocessing techniques like image enhancement, noise reduction, and data augmentation to overcome challenges related to data quality and availability.

The proposed system is designed to be versatile and accessible, with deployment options that include cloud-based and edge computing infrastructures, making it suitable for diverse healthcare environments, including remote and resource-constrained regions. By addressing these critical gaps, the project aims to enhance diagnostic efficiency, reduce the workload on radiologists, and improve patient outcomes. Ultimately, this work aspires to contribute to the broader adoption of AI in healthcare, revolutionizing medical imaging practices, promoting equitable healthcare delivery, and advancing the integration of technology to save lives and improve care quality worldwide.

## 1.5 Key features

The proposed system aims to revolutionize the detection of brain hemorrhage by using the most advanced deep learning and machine learning techniques for providing fast, accurate, and reliable diagnostics. The primary features of a deep learning-based brain hemorrhage detection system are designed to provide support to healthcare professionals with high accuracy, efficiency, and reliability. The system uses advanced Convolutional Neural Networks (CNNs) to automate the analysis of medical images, such as CT and MRI scans. It reduces the time consumed and human error in making diagnoses. It also ensures real-time processing of medical images, delivering quick feedback necessary for timely decision-making in emergency cases. The system ensures high classification accuracy, distinguishing between different types of hemorrhages, and offers intuitive visualizations such as heatmaps that highlight detected hemorrhage regions, assisting healthcare professionals in making informed decisions. Support for various image formats, such as DICOM, PNG, and JPEG, allows the system to easily integrate into existing hospital workflows and databases. Data privacy and security are also respected, with the system complying with standards such as HIPAA or GDPR. The system uses a user friendly interface that makes interaction straightforward, and it produces extensive reports on diagnostics with a highly scalable nature, hence large volumes of medical images get processed efficiently. It further allows the system to update itself through retraining with time, thus the leveling of precision remains high to the changes in the techniques of medical imaging. This system also supports multi-class classification, differentiating types of hemorrhages, and cloud-based accessibility, making it versatile for remote diagnostics. These features together are assured to make the system increase diagnostic accuracy, reduce diagnosis time, and enhance proper care of patients.

Key features include automated detection, real-time analysis, and enhanced integration with the real time trails, ensuring improved efficiency and patient outcomes.

a) Automated Detection
   The system leverages advanced deep learning algorithms to automatically detect brain hemorrhages from CT and MRI scans, eliminating the need for manual interpretation.

b) High Accuracy and Precision
   Robust models, such as CNNs, ensure accurate identification of even subtle and complex features associated with brain hemorrhages.

c) Real-Time Diagnostics
   The system provides rapid analysis and diagnostic results, enabling timely decision-making in critical emergency situations.

d) Advanced Preprocessing

Incorporates image enhancement, noise reduction, and normalization techniques to enhance the quality of data and optimize model performance.

e) Explainable AI (XAI)

Integrates explainable AI methods to provide interpretable results, allowing clinicians to understand and validate the system's predictions.

f) Scalability

Designed to manage huge volumes of data and implement to different imaging modalities and diverse datasets, making sure that the consistent improvement in different circumstances.

g) Accessibility

Deployable on cloud-based or edge computing infrastructures, making it suitable for use in remote, rural, and resource-constrained healthcare settings.

h) Integration with Clinical Workflows

Seamlessly integrates with existing hospital systems and workflows, improving overall efficiency and reducing the workload on radiologists.

i) Data Augmentation and Generalization

Employs advanced data augmentation techniques to overcome challenges related to limited datasets, ensuring the model implements well across different patient demographics and imaging conditions.

j) User-Friendly Interface

Features an intuitive and easy-to-use interface, enabling healthcare providers with varying levels of technical expertise to operate the system effectively.

k) Emergency Application

Tailored for use in emergency rooms and critical care settings where rapid and accurate diagnostics are essential for immediate medical intervention.

l) Cost-Effective Solution

Offers a scalable and resource-efficient approach that reduces diagnostic costs while maintaining high accuracy and reliability.

# CHAPTER 2

# LITERATURE SURVEY

| SL NO | Literature Review | Advantages | Disadvantages |
|---|---|---|---|
| 1. Delving Deep into Rectifiers:<br>Surpassing Human-Level Performance on ImageNet Classification<br>Authors: Kaiming He Xiangyu Zhang Shaoqing Ren Jian SunYear: 2015 | Rectified activation units (rectifiers) are essential for state-of-the-art neural networks. In this work, we study rectifier neural networks for image classification from two aspects. First, we propose a Parametric Rectified Linear Unit (PReLU) that generalizes the traditional rectified unit. PReLU improves model fitting with nearly zero extra computational cost and little overfitting risk. Second, we derive a robust initialization method that particularly considers the | Best-in-class performance on complex problems. | It is quite expensive to train. |

| | | | |
|---|---|---|---|
| | rectifier nonlinearities. | | |
| 2.Classification of CT brain images based on deep learning networks Author:<br><br>Xiaohong W. Gao, Rui Hui, Zengmin Tian<br><br>Year:<br><br>2016 | While Computerised Tomography (CT) may have been the first imaging tool to study human brain, it has not<br><br>yet been implemented into clinical decision making process for diagnosis of Alzheimer's disease (AD). On the other hand, with the nature of being prevalent, inexpensive and non-invasive, CT does present diagnostic features of AD to a great extent. This study explores the significance and impact on the application of the burgeoning deep learning techniques to the task of | Decision trees are easy to interpret and visualize.<br><br>It can easily capture Non-linear patterns. | Time consuming. |

| | | | |
|---|---|---|---|
| | classification of CT brain images, in particular utilising convolutional neural network (CNN), aiming at providing supplementary information for the early diagnosis of hemorrhage. | | |
| 3. A Survey on Deep Learning in Medical Image Analysis<br>Author:<br>Geert Litjens, Thijs Kooi,<br>Babak EhteshamiBejnordi,<br>Arnaud Arindra Adiyoso Setio, Francesco Ciompi,<br>Mohsen Ghafoorian<br>Year: 2017 | Deep learning algorithms, in particular convolutional networks, have rapidly become a methodology of choice for analyzing medical images. This paper reviews the major deep learning concepts pertinent to medical image analysis and summarizes over 300 contributions to the field, most of which appeared in the last year. We survey the use of | Image will be displayed | CNN do not encode the position and orientation of object.<br>Lack of ability to be spatially invariant to the input data.<br>Lots of training data is required. |

| | | | |
|---|---|---|---|
| | deep learning for image classification, object detection, segmentation, registration, and other tasks. Concise overviews are provided of studies per application area: neuro, retinal, pulmonary, digital pathology, breast, cardiac, abdominal, musculoskeletal. | | |
| 4. Deep Learning for Hemorrhagic Lesion Detection and Segmentation on Brain CT Images<br>Author:Lu Li, Meng Wei, Bo Liu, KunakornAtchaneeyasakul, Fugen Zhou, Zehao Pan, Shimran A.Kumar,<br>Year:2020 | Stroke is an acute cerebral vascular disease that is likely to cause long-term disabilities and death. Immediate emergency care with accurate diagnosis of computed tomographic (CT) images is crucial for dealing with a hemorrhagic stroke. However, due to the high variability of a | U-net based deep learning framework to automaticall y detect and segment hemorrhage strokes in CT brain images. | CNN do not encode the position and orientation of object.<br>Lack of ability to be spatially invariant to the input data.<br>Lots of training data is required. |

| | | | |
|---|---|---|---|
| | stroke's location, contrast, and shape, it is challenging and time-consuming even for experienced radiologists to locate them. In this paper, we propose a U-net based deep learning framework to automatically detect and segment hemorrhage strokes in CT brain images. The input of the network is built by concatenating the flipped image with the original CT slice which introduces symmetry constraints of the brain images into the proposed model. This enhances the contrast between hemorrhagic area and normal brain tissue | | |

| | | | |
|---|---|---|---|
| 5. Feasible Study on Intracranial Hemorrhage Detection and Classification using a CNN-LSTM Network<br><br>Author:Hoon Ko, Heewon Chung, Hooseok Lee and Jinseok Lee<br><br>Year:2020 | Intracranial hemorrhage (ICH) is a life-threatening condition, the outcome of which is associated with stroke, trauma, aneurysm, vascular malformations, high blood pressure, illicit drugs and blood clotting disorders. In this study, we<br><br>presented the feasibility of the automatic identification and classification of ICH using a head CT image based on deep learning technique. The subtypes of ICH for the classification was intraparenchymal , intraventricular, subarachnoid, subdural and epidural. We first performed windowing to provide three different images: | Best performance | CNN do not encode the position and orientation of object.<br><br>Lack of ability to be spatially invariant to the input data.<br><br>Lots of training data is required. |

| | | | |
|---|---|---|---|
| | brain window, bone window and subdural window, and trained 4,516,842 head CT images using CNN-LSTM model. | | |
| 6. Intracranial Hemorrhage Detection in CT Scans using Deep Learning<br>Author:<br>Tomasz Lewicki, Meera Kumar, Raymond Hong, Wencen Wu<br>Year: 2020 | In intracranial hemorrhage treatment patient mortality depends on prompt diagnosis based on a radiologist's assessment of CT scans. In this paper, we investigate the intracranial hemorrhage detection problem and built a deep learning model to accelerate the time used to identify the hemorrhages. Our model has an accuracy of 93.3% in making the correct multiclass prediction and an average per-class recall score of 76%. We show it is possible to | Less performance. | Lots of training data is required. |

| | | | |
|---|---|---|---|
| | achieve an average recall of 86% while maintaining 70% precision via tuning the prediction thresholds. Lastly, we show real-world applicability by deploying a simple web application | | |

# CHAPTER 3

# SYSTEM REQUIREMENT SPECIFICATION

This paper outlines the system requirements for implementing a deep learning-based solution for the detection of intracranial brain hemorrhage from medical imaging data, such as CT or MRI scans. Traditional manual detection can be slow and error-prone, but with the help of deep learning algorithms, such as CNNs, the speed and precision of the diagnosis can be improved significantly. This system will identify and classify hemorrhages in an automatic manner, assisting healthcare providers in emergency scenarios.

The system will consist of several components, including data input and preprocessing modules, a deep learning model for hemorrhage detection and classification, and a user interface for radiologists to interact with the system. To ensure optimal performance, the system will require high-performance hardware, such as GPUs for model training and inference, as well as reliable software frameworks like TensorFlow or PyTorch for building and deploying the model. Additionally, the system will incorporate necessary security and compliance measures to ensure the protection of patient data in accordance with healthcare regulations such as HIPAA or GDPR.

The proposed system will support medical professionals by providing faster, more accurate assessments of brain hemorrhages, reducing diagnostic delays and improving patient outcomes. The specifications outlined here provide a foundation for both the development and deployment of the system, taking into account the hardware, software, and non-functional requirements to ensure robustness, scalability, and compliance.

## 3.1 System analysis

System analysis involves understanding the requirements, challenges, and functionality of the proposed brain hemorrhage detection system. This phase is crucial for identifying the technical specifications, design considerations, and implementation strategies necessary to develop a solution that gains the importance of healthcare providers while overcoming the limitations of existing diagnostic methods. The system should be able to process CT and MRI scan images efficiently, automatically detect brain hemorrhages, and provide diagnostic results in real-time. The solution is designed to accommodate large datasets and ensure high accuracy, making it possible for clinicians to rely on and validate the predictions. It should also be user-friendly and adaptable to various healthcare environments, such as well-equipped hospitals to remote clinics.

The recognition of the system for intracranial brain hemorrhage (ICH) detection through deep learning revolves around understanding the problem, identifying user needs, and outlining the functional and non-functional requirements for building an efficient and reliable solution. The primary goal is to automate the detection of ICH from medical images, particularly CT and MRI scans, to assist healthcare professionals in making quicker, more accurate diagnoses. The traditional methods for diagnosing are heavily reliant on the judgment of radiologists. In a high-pressure situation such as an emergency, it is time taking and can have human errors.

A deep learning system uses Convolutional Neural Networks (CNNs) can dramatically expedite the speed and accuracy at which brain hemorrhages could be identified, reducing any possible delay in diagnosis to ultimately improve patient care. In that regard, using well-labeled datasets of brain images would train the system into the identification of hemorrhagic regions, classification of several types of hemorrhages - for example, epidural, subdural, subarachnoid, or intraparenchymal - and locate such regions within the scan to enhance visualization. This would not only help radiologists in making decisions but also be a support tool in areas where health care resources are limited.

Based on the system analysis, medical imaging data is often of large size, which presents multiple challenges in integration (potentially, various types and formats like DICOM). Data preprocessing would range from resizing and normalizing to proper model training, maybe even using libraries such as TensorFlow or PyTorch, with the overall requirement on a robust system for being proficient with large datasets, thus enabling real-time predictions without any breach of confidentiality over health data, hence safety for patients. The analysis also involves the evaluation of the performance of the system in terms

of accuracy, speed, and user-friendliness, ensuring that it meets the requirements of healthcare professionals while complying with industry standards for medical applications.

Through a comprehensive system analysis, the proposed solution will be tailored to meet the specific needs of healthcare providers, ensuring a high level of accuracy, efficiency, and usability while addressing existing challenges in brain hemorrhage detection.

## 3.2 Functional requirement

The functional requirements for the deep learning-based intracranial brain hemorrhage detection system are core tasks that the system should perform to grant the need of healthcare professionals. The system should be able to accept medical images, particularly CT and MRI scans, in standard phases like DICOM, NIfTI, or other common imaging formats like PNG or JPEG. Upon receiving an image, the system preprocesses the data, resizes images to a uniform size, normalizes pixel values for better model accuracy, and may apply data augmentation to ensure that the model generalizes well to unseen images.

The core functionality of the system is the detection and classification of hemorrhages. The deep learning model, typically a Convolutional Neural Network (CNN), will analyze the images to find the part of intracranial hemorrhage and classify its type, such as epidural, subdural, or intraparenchymal hemorrhages. In addition to detection, the system must also localize the hemorrhagic regions, marking the areas within the brain scans where hemorrhages are detected, providing radiologists with a clear indication of affected areas.

- Image Input and Preprocessing
  - Accept CT/MRI scans in formats like DICOM or JPEG.
  - Enhance image standard by noise reducing and normalization.
- Automated Detection
  - Identify brain hemorrhages using deep learning models.
  - Classify hemorrhage types if applicable.
- Real-Time Results
  - Provide fast diagnostic outputs with confidence scores.
- Explainable Outputs
  - Highlight abnormal areas with heatmaps or visual overlays.
  - Add textual explanations for model predictions.
- Training and Data Handling
  - Support data augmentation for robust model training.
  -

- **User Interface**
  - Provide an intuitive interface for image upload and result viewing.
  - Include tools like zoom, pan, and annotations.
- **Security**
  - Encrypt data and ensure compliance with HIPAA/GDPR.
  - Protect patient information through anonymization.
- **Error Handling**
  - Handle corrupted files or invalid inputs gracefully.
  - Alert users of system errors.
- **Feedback**
  - Enable user feedback to refine system accuracy.
  - Log predictions for continuous improvement.

Furthermore, the system should offer real-time analysis capabilities, delivering results quickly (within seconds or minutes) after image upload. It must also support batch processing, allowing multiple images to be processed in parallel for efficiency. The system should generate a detailed report that includes the detection results, confidence levels, and any relevant classifications. The report should be easy to understand and exportable for clinical records. Additionally, the system should offer a user-friendly interface for radiologists to interact with, allowing them to upload new scans, view results, and receive feedback on their decisions, with complete support for both image viewing and interpretation.

Overall, the system must facilitate accurate, timely, and consistent detection of brain hemorrhages, thus aiding radiologists in their decision-making process and improving the quality of patient care.

## 3.3 Non-functional requirement

The non-functional requirements ensure the system's efficiency, reliability, and security while enhancing user experience. They focus on performance, scalability, data protection, and ease of use to meet healthcare standards effectively.

Non-functional requirements describe the overall quality and operational attributes that the deep learning-based system for intracranial brain hemorrhage detection must exhibit. The system must perform efficiently, providing real-time or near real-time results with minimal latency to support quick decision-making in clinical environments. It should be scalable to accommodate increasing data volumes and user loads, ensuring smooth performance even as demand grows. The system must be reliable, consistently producing accurate results with error-handling mechanisms in place to recover from potential failures or issues such as corrupted files.

Security is a top priority, and the system must ensure robust encryption for both data in transit and at rest, protecting patient privacy and adhering to healthcare regulations such as HIPAA or GDPR. The system must be available 24/7, especially in high-pressure scenarios like emergency rooms, and should maintain high availability through cloud infrastructure or redundant systems. The user interface should be intuitive and easy to use, enabling healthcare professionals to upload images, view results, and generate reports with minimal training. Furthermore, the system should be accessable, which provides the regular updates and model retraining, ensuring long-term reliability and adaptability.

Interoperability with existing hospital systems, such as HIS, RIS, and PACS, is also crucial for seamless data exchange, improving overall workflow. Lastly, compliance with medical industry standard and rules is mandatory to ensure the model can be legally deployed and trusted in clinical settings. These non-functional requirements collectively ensure the system meets the demands of healthcare professionals while maintaining security, reliability, and ease of use.

- Performance: Process CT/MRI scans within 5–10 seconds with at least 95% accuracy.
- Scalability: Support large datasets and multiple users without performance issues.
- Security: Ensure data encryption and compliance with HIPAA/GDPR standards.
- Usability: Give a user-friendly interface requiring minimal training.

**H/W System Configuration:**

| | |
|---|---|
| Processor | Dual Core. |
| Speed | 1.1 G Hz. |
| RAM | 8 GB (min). |
| Hard Disk | 20 GB. |

**S/W System Configuration:**

| | |
|---|---|
| Operating System | Windows 10. |
| Technology | Machine Learning |
| Front End | GUI-tkinter |
| IDLE | Python 3.7 or higher |

## 3.4 Tools and technology details

The development of the deep learning-based system for intracranial brain hemorrhage detection will require several key tools and technologies. This technology is important for data processing, model development, deployment, and ensuring the system meets the required standards for accuracy, scalability, and security.

- Python

  Python is the core programming language for this system, majorly known for its simple architecture and extensive libraries suited for data analysis, and deep learning. The key reasons for choosing Python include:

  **Ease of Use**: Python has a simple syntax that makes it accessable for developers to write clean, readable code, reducing development time and facilitating maintenance.

  **Extensive Libraries**: Python provides a vast selection of libraries for scientific computing, data manipulation, image analysis, and machine learning, which is important for building a robust deep learning model.

Key libraries used in Python include:

- NumPy and Pandas: For data manipulation and handling large datasets.
- Matplotlib and Seaborn: For visualizing results, creating heatmaps, and plotting graphs.

- SciPy: For scientific computing tasks. Python is highly favored in machine learning for the implementation of multiple deep learning frameworks and ease of integration with libraries like TensorFlow and OpenCV.

- OpenCV

  OpenCV is one of the major tools in pre-processing of medical images such as CT and MRI scans before their entry into the machine learning models. It has multiple image processing techniques:
  - Image enhancement: It enhances the quality of medical images by removing noise and increasing contrast.
  - Edge detection and segmentation: It helps to separate the important features of an image so that the model can concentrate on possible hemorrhage regions.
  - Scaling and normalization: Reshaping images so that they could end in the right format for proper input to the deep model. OpenCV ensures appropriate processing of raw medical data to fit the correct requirements for further analysis.

- Flask/Django

  Both Flask and Django are Python-based web frameworks used for deploying the system. The choice between Flask and Django depends on the specific needs of the application:
  - Flask: A micro-framework that is lightweight and ideal for smaller, simpler applications or services where only the core features are needed. Flask is used to create RESTful APIs that can handle real-time predictions.
  - Django: A full-stack framework that comes with more built-in functionalities, making it suitable for larger, more complex applications. It supports features like user authentication, database integration, and routing out of the box. Both frameworks help in creating web-based applications that allow healthcare professionals to upload images, receive predictions, and view results via an intuitive interface. They also enable easy deployment on data storage platforms like AWS, GCP, or Azure, ensuring that the system can scale as needed.

These tools and technologies come together to form a comprehensive solution for brain hemorrhage detection, ensuring high performance, scalability, and ease of use while meeting the needs of medical professionals and institutions.

# CHAPTER 4

# SYSTEM DESIGN

The system design for brain hemorrhage detection combines deep learning and image processing to analyze CT and MRI scans. It uses CNNs built with TensorFlow/Keras for accurate detection, with image preprocessing via OpenCV. The web-based application, developed using Flask or Django, allows healthcare professionals to upload images and receive real-time results. The system integrates with databases for storing patient data and adheres to medical image standards like DICOM. GPUs/TPUs are used for faster processing, and security measures like HIPAA.

The system design for a deep learning-based brain hemorrhage detection system organizes the key components and their interactions in such a way that there is efficient processing and accurate predictions. The system begins with an input module, wherein medical imagings, such as CT or MRI scans, are uploaded by healthcare professionals. These images undergo preprocessing, which involves resizing, normalization, and noise reduction, thereby preparing the data for the model. Deep Learning Model: The core part of the model is a deep learning model, specifically Convolutional Neural Network (CNN), which analyses preprocessed images for rectifying the location and type of brain hemorrhage. Once the analysis is done, the system would create a diagnostic report, describing detailed information about the type, location, and severity of the hemorrhage and would, possibly, provide a heatmap on the affected areas. Results are displayed through a user interface, which allows healthcare professionals to review the findings, download reports, and manage images. A database securely stores images, results, and reports for future access. The system is designed to ensure high performance and scalability and is capable of handling large datasets. It can be deployed on cloud platforms for efficient processing. In addition, the system applies strict security and privacy mechanisms to protect the patient's information, supported by health-related regulations, such as HIPAA or GDPR. This design ensures that the system is intuitive, scalable, and secure for use by healthcare professionals in detecting and diagnosing brain hemorrhages.

## 4.1 Overall system architecture:




- **Dataset**: Input the dataset to the machine.
- **Data Preprocessing:** The image is preprocessed in this stage.
- **Applying CNN algorithm**: The CNN algorithm is applied in this stage.
- **Image Classification**: The images are classified.
- **Prediction**: The image is predicted in this final stage.

The overall system architecture of the deep learning-based intracranial brain hemorrhage detection system is structured in a large number of layers to work for efficient processing, accurate predictions, and user-friendly interaction. The process initiates from the Data Acquisition Layer where medical images usually in DICOM format are gathered either manually by the health care professionals or automatically from hospital systems like PACS. These imagings can be used to the Data Preprocessing Layer where it does some operations such as resizing, normalization, augmentation, and noise reduction for preparing images in inputting into the model.

The next stage, the **Model Training and Validation Layer**, involves building and training a deep learning model, typically a Convolutional Neural Network (CNN), using labeled datasets. Once the model is trained and validated, it moves to the **Inference and Prediction Layer**, where it processes new

images to detect brain hemorrhages and classify their types with confidence scores. The **Post-Processing and Visualization Layer** ensures that the predicted results are annotated on the medical images, helping healthcare professionals visualize the detected hemorrhage regions and generate detailed reports.

Healthcare professionals interact with the system through the **User Interface and Interaction Layer**, where they can upload images, view the predictions, and download reports. The system's **Database Layer** stores important patient data, image metadata, and prediction results for record-keeping and compliance purposes. Finally, the **Security and Compliance Layer** ensures that patient data is securely encrypted, access is controlled, and the system adheres to necessary regulations like GDPR. This multi-layered architecture ensures the model is robust, scalable, secure, and easy to use, making it an effective tool for assisting in the timely and accurate detection of brain hemorrhages.

## 4.2 Input/Output Design:




- **Image Dataset**: Input the image dataset to the machine.
- **Data Preprocessing:** The image is preprocessed in this stage.
- **Applying CNN algorithm**: The CNN algorithm is applied in this stage.
- **Image Classification**: The images are classified.
- **Prediction**: The image is real or forged is predicted in this final stage.

The Input/Output (I/O) design for the deep learning-based intracranial brain hemorrhage detection system plays a important role in ensuring smooth data flow between the user and the system. The input to the system consists primarily of medical images, such as CT or MRI scans, in formats like DICOM, PNG, or JPEG. These images are uploaded through a secure user interface, where healthcare professionals can either drag and drop the images or integrate the system with hospital Picture Archiving and Communication Systems (PACS). Along with the images, optional metadata such as patient details, scan type, and timestamp can be provided for better data management. The system preprocesses these images through tasks like resizing, normalization, and augmentation to ensure consistency and enhance the accuracy of the deep learning model.

Once the images are processed, the system provides several outputs. The primary output is the detection result, indicating whether a hemorrhage is present, along with a confidence score to highlight the likelihood of correctness. If a hemorrhage is detected, the system classifies it into types like epidural, subdural, or intraparenchymal, and provides a corresponding severity score. The system also annotates the original medical images, highlighting the affected regions, allowing radiologists to visually verify the results. Additionally, a detailed diagnostic report is generated, which includes the prediction, confidence level, and recommendations for further action. All other interactions the system undergoes are logged and ensure its regulatory compliance, with this including patient data, processing of images, and all report generations. The end product should be accessible for the users to interactively use and hence ensure a clinical environment for the users to communicate, view, or can decide based on the output from the system.

## Use Case Diagram:

.Level-1

The user can apply the image dataset to the machine.

Level-2

They include the **Healthcare Professional**, **System Administrator**, and the **Deep Learning System**. The **Healthcare Professional** communicate with the system by uploading medical images (CT/MRI scans), these are processed by the system. After the images are preprocessed, the model analyzes them to detect brain hemorrhages, and the output are displayed for the healthcare professional to review. The system provides detailed predictions, including the type of hemorrhage, location, and severity, along with heatmaps or visual annotations highlighting affected areas. Additionally, the system generates a diagnostic report that can be stored and accessed later. The **System Administrator** is responsible for maintaining and updating the system, ensuring it runs efficiently and securely. This includes managing system settings, user access, and integrating the system with hospital databases. The **Deep Learning System** performs the core tasks, such as image analysis using convolutional neural networks (CNN), classification, and storing the results. Through this use case diagram, the system's core functionalities and their user interacts with users are clearly outlined, emphasizing the roles of healthcare professionals in diagnosing patients and system administrators in maintaining the platform.

# Activity Diagram

This shows the entire structure of control in the system and mentions the steps introduced in the result of a use case. We illustrate sequential and concurrent activities using these diagrams. So, we picturize workflows visually using an activity diagram. These diagram focuses on conditions of flow and the order in which it depicts. We describe what initiates a particular process using the activity diagram.



The **Activity Diagram** for a deep learning-based brain hemorrhage detection system outlines the order of actions in diagnosing brain hemorrhages from medical images. The process begins when the healthcare professional uploads a CT or MRI scan in the model. The model then preprocesses the image, which involves resizing, normalization, and other enhancements to prepare the image for analysis. The deep learning model (CNN) then analyzes the image to identify the location of a hemorrhage. A decision point follows: if a hemorrhage is detected, the system classifies the type of hemorrhage (e.g., epidural, subdural, or intracerebral), and proceeds to generate a diagnostic report detailing the type, location, and severity. If no hemorrhage is detected, the system indicates this in the results. Regardless of the outcome, the system stores the image, analysis results, and generated report for future reference. Finally, the results, along with any visual annotations such as heatmaps, are displayed to the healthcare professional for review and decision-making. The process ends after the results are presented, allowing the healthcare professional to take appropriate action based on the diagnosis.

# State Transition Diagram

State-transition diagrams describe all of the states that an object can have, the events under which an object changes state (transitions), the conditions that must be fulfilled before the transition will occur (guards), and the activities undertaken during the life of an object (actions).



# Data Flow Diagram(DFD)

A data flow diagram is a representation of the "flow" of data through an information system, modeling its process aspects. Often they are a preliminary step used to create an overview of the system which can later be elaborated. DFDs can also be used for the visualization of data processing (structured design).



## 4.3 Algorithm

The Convolutional Neural Network (CNN) algorithm is designed to learn from images or other grid-like data by applying a series of operations to extract hierarchical features and make predictions. The CNN consists of several layers like convolutional layers, activation layers, pooling layers, and fully connected layers, each with specific functions. Below is a general step-by-step breakdown of how CNN operates during the forward pass:

### 4.3.1 CONVOLUTIONAL NEURAL NETWORKS

Convolutional Neural Networks (CNNs) are a powerful deep learning architecture primarily used for processing grid-like data, such as images. In medical image analysis, CNNs have become the go-to technique for tasks like brain hemorrhage detection due to the strength to automatically learn spatial hierarchies of features from raw image data. CNNs consist of several layers, including convolutional layers that apply filters to detect basic features like edges and textures, pooling layers that reduce the image size while preserving important information, and fully connected layers that combine learned features to make final predictions. The output of a CNN typically includes classifications or predictions, such as detecting whether a hemorrhage is present in a CT or MRI scan. The advantages of using CNNs in medical applications include their ability to extract meaningful patterns without manual feature engineering, their translation invariance, and their efficiency in handling large image datasets. However, challenges such as data imbalance, the need for high-quality images, and the lack of interpretability of CNN models can complicate their implementation. Despite these challenges, CNNs have proven to be highly effective in improving diagnostic accuracy and assisting healthcare professionals in making timely decisions, especially in complex tasks like hemorrhage detection.

### 4.3.2 LAYERS OF CNN

Convolutional Neural Networks (CNNs) are composed of several types of layers, each with a specific function to process and learn from image data. The **convolutional layers** are the core components, where filters (kernels) are applied to the input image to detect basic features like edges, textures, and shapes. These layers generate feature maps, which highlight the presence of specific patterns within the image. The output of the convolutional layers is then passed through **activation layers**, typically using the Rectified Linear Unit (ReLU) function. ReLU introduces non-linearity by converting all negative values to zero, which helps the network learn more complex patterns and speeds up the training process. Following this, **pooling layers** are used to reduce the spatial dimensions of the feature maps while retaining essential information, typically through **max pooling**, which selects the highest value from

small regions of the feature map. This helps reduce computational complexity and makes the network more robust to slight changes in the input image. After several convolutional and pooling layers, the output is flattened and passed through **fully connected layers** (dense layers), where the network combines the learned features to make final predictions. The last layer, the **output layer**, typically uses a **softmax** function to convert the network's raw output into probabilities for each possible class, enabling the model to make classifications, such as detecting a brain hemorrhage or not. Together, these layers allow CNNs to efficiently process and classify images, automatically learning important features without the need for manual feature extraction.

Convolutional Neural Networks (CNNs) consist of several types of layers, each serving a specific function to process and learn from image data. The primary layers in a CNN are:

1. **Convolutional Layers**: These are the core building blocks of a CNN. They apply filters (kernels) to the input image to detect local patterns such as edges, textures, or shapes. Each filter produces a feature map that highlights the presence of specific features in the image. Multiple convolutional layers are stacked together to detect increasingly complex patterns as the network deepens.
2. **Activation Layers (ReLU)**: After each convolutional operation, the feature map is passed through an activation function, typically the Rectified Linear Unit (ReLU), which introduces non-linearity into the model. ReLU replaces all negative values in the feature map with zeros, allowing the network to learn more complex patterns and speeding up the training process.
3. **Pooling Layers**: These layers reduce the spatial dimensions of the feature maps while retaining the most important information. Max pooling, the most common pooling method, selects the maximum value from a small region of the feature map, effectively downsampling the image and reducing computational complexity. Pooling also helps the network become more robust to small translations and distortions in the input image.
4. **Fully Connected Layers (Dense Layers)**: After several convolutional and pooling layers, the high-level features are flattened into a one-dimensional vector and passed through fully connected layers. These layers are similar to traditional neural network layers, where each neuron is connected to all neurons in the previous layer. The fully connected layers combine the learned features to make final predictions, such as classifying the image into categories (e.g., “hemorrhage detected” or “no hemorrhage”).
5. **Output Layer**: The final layer in a CNN is the output layer, which typically uses a softmax function for classification tasks. The softmax layer transforms the raw outputs into probabilities, with each probability corresponding to the likelihood of an image belonging to a particular class (e.g., different types of hemorrhages).

These layers work together to automatically extract features from the image, reduce dimensionality, and ultimately classify the input based on learned patterns.

### 4.3.3 Convolutional Neural Network

**Convolutional Neural Network (CNN) Architecture** is a specialized class of deep learning models designed to process data that has a grid-like structure, such as images. CNNs are mainly used for tasks like image recognition, classification, and object detection due to their ability to automatically learn spatial hierarchies of features from raw image data. Unlike traditional neural networks, which connect every neuron to every neuron in adjacent layers, CNNs leverage a more efficient architecture that allows for better performance on image-related tasks.




**Fig. 4.2 Convolutional Neural Network**

A simple and brief Convolution network architecture is explained below

INPUT LAYER: In this layer, raw values of the pixel for all input images are shown and particularly the size of the input images in this case, it is [50 x 50] with colored channels mentioned three: R, G, B; hence the input images have size dimensions [50 x 50 x 3].

CONVOLUTION LAYER: The layer applicable a specific number of filters i.e., convolutional filters for the input image and the output is the dot product of the weights and the regions to which the input neurons are connected throughout in the image. This layer mainly has the ReLu activation function to the output.

Every pixel of the image and the derived convolved **output in weight matrix.**

| | | | | |
|---|---|---|---|---|
| 1 | 1 | 1 | 0 | 0 |
| 0 | 1 | 1 | 1 | 0 |
| 0 | 0 | 1 | 1 | 1 |
| 0 | 0 | 1 | 1 | 0 |
| 0 | 1 | 1 | 0 | 0 |

Input

| | | |
|---|---|---|
| 1 | 0 | 1 |
| 0 | 1 | 0 |
| 1 | 0 | 1 |

Filter / Kernel

**Fig.4.3 Convolution filter**

| | | | | |
|---|---|---|---|---|
| 1 | 1x1 | 1x0 | 0x1 | 0 |
| 0 | 1x0 | 1x1 | 1x0 | 0 |
| 0 | 0x1 | 1x0 | 1x1 | 1 |
| 0 | 0 | 1 | 1 | 0 |
| 0 | 1 | 1 | 0 | 0 |

Input x Filter

| | | |
|---|---|---|
| 4 | 3 | |
| | | |
| | | |

Feature Map

**Fig.4.4 Feature Map formation .**

**STRIDE AND PADDING** :Stride is defined as the number of pixels with which one can move the filter along the image. If the filter moves along the image one pixel at a time, then it is mentioned as stride of 1. Once stride increases, the image dimension reduces, therefore we can use padding. Padding is a process of adding one or many layers of zeroes around the image so that we can retain the data of the image.




**Fig 4.5 : Padding**

ReLULAYER :ReLU activation function is the derived form of "Rectified Linear Activation Function". It mentions the function f(x) = max (0, x), in simpler words it is thresholding at 0.

POOL LAYER :Sometimes, when the image size is very large, the size must be reduced to in a way of reducing the time taken for processing. Because of this, pooling layers are mentioned between successive convolution layers. Pooling layers help in down sampling of the image dataset obtained.

The below shown fig. 4.6 describes the max pooling process with the window size of 2*2 and stride is 2. Here maximum value inside the stride has been chosen to form a feature map**.**




**Fig4.6 Max Pooling**

FULLY CONNECTED LAYER :This layer takes the result of its preceding layer, i.e., either the ReLU layer or the Pool layer, as its primary input. Primarily this layer takes the input volume and gives out the N dimensional vector as its output, where N is the number of classes from which the program has to choose from. This layer works in such a way that, looking at the output of the preceding layer.

A simple Convolutional Neural Network (CNN) architecture typically begins with an **input layer**, which accepts the image, usually in a 3D format representing the height, width, and number of color channels (e.g., 224x224x3 for a color image). The first **convolutional layer** applies multiple filters (kernels) to the input image to extract basic features such as edges and textures, producing feature maps. After this, an **activation layer** (typically ReLU) is applied to introduce non-linearity, enabling the network to learn complex patterns. Next, a **max pooling layer** reduces the spatial dimensions of the feature maps, retaining the most important features while reducing computational load. The process repeats with another **convolutional layer** to detect more complex features and another **activation layer** for non-linearity. The feature maps are then downsampled with another **pooling layer**. Afterward, the 2D feature maps are flattened into a 1D vector through the **flattening layer**, preparing them for the fully connected layers. A **fully connected layer** then combines the learned features and makes final predictions, followed by an **output layer** that typically uses a softmax function for multi-class classification or a sigmoid

function for binary classification. This simple CNN architecture is effective in tasks like image classification, where it can efficiently extract features and classify images based on learned patterns.

A simple **Convolutional Neural Network (CNN)** architecture typically consists of several key layers that help process image data for tasks like brain hemorrhage detection. The process begins with the **input layer**, which accepts the medical image (such as a CT or MRI scan), typically in the shape of a 2D or 3D array. The first critical layer is the **convolutional layer**, where multiple filters (or kernels) are applied to the input image to extract important features, such as edges, textures, and shapes. These filters slide over the image, performing a convolution operation to produce feature maps. Following the convolutional layer, a **ReLU activation function** is applied, introducing non-linearity to the model in placing all negative values with zero, which helps the model learn more complex patterns. Afterward, a **max-pooling layer** is used to reducing the spatial dimensions of the feature map, retaining the most important features while reducing computational complexity and overfitting. This process is typically repeated with additional convolutional layers, each followed by ReLU activations and pooling layers, enabling the network to learn more abstract features from the image.

After several convolutional and pooling layers, the feature maps are **flattened** into a 1D vector. This step prepares the data set for the upcoming stage, where the high-level features learned by the convolutional layers are used to make a decision. A **fully connected (dense) layer** follows, where one of the neuron in this layer is merged to every neuron from the previous layer. This is where the network begins to make sense of the learned features, making predictions based on them. Finally, the **output layer** provides the final classification, typically using a **sigmoid activation function** for binary classification (e.g., hemorrhage vs. no hemorrhage). The output layer produces a probability score, indicating the likelihood of the present of a hemorrhage. This simple CNN architecture, with its combination of convolutional, activation, pooling, and dense layers, effectively processes and classifies medical images for brain hemorrhage detection.

# CHAPTER 5

# SYSTEM IMPLEMENTATION

## 5.1 Module Description

The brain hemorrhage detection system is composed of several interconnected modules. The Image Preprocessing Module handles tasks like image normalization, resizing, and noise reduction using OpenCV to prepare CT/MRI scans for analysis. The Deep Learning Model Module, built with TensorFlow/Keras, uses Convolutional Neural Networks (CNNs) to detect brain hemorrhages by processing preprocessed images and providing predictions. The Prediction and Result Display Module presents the output, including the presence of hemorrhage and visualizations like heatmaps or confidence scores, to assist healthcare professionals in interpreting results. The Database Module securely stores patient data, scan images, and results using databases like MySQL or MongoDB, guaranteed compliance with data privacy standards. The Web Interface Module allows users to upload scans and view results through an intuitive interface, developed using Flask or Django. The Security and Authentication Module ensures data protection by implementing encryption, access control, and user authentication, complying with healthcare standards like HIPAA. Finally, the Deployment Module handles the cloud-based deployment and ensures scalability and reliability on platforms like AWS, GCP, or Azure. These modules work in concert to deliver an integrated and appropriate solution for the detection of brain hemorrhage and support healthcare professionals with accurate and timely results.

- **Image Preprocessing Module**
  This module is responsible for preparing the medical images (CT/MRI scans) for analysis by the deep learning model. It performs tasks such as image normalization, resizing, noise reduction, and contrast enhancement using libraries like OpenCV. The plan is to implement the imagings are in the optimal condition for accurate analysis.
- **Deep Learning Model Module**
  The main aim of the system, this module leverages Convolutional Neural Networks (CNNs) built using TensorFlow/Keras. The model gets well training on a large dataset of labeled CT and MRI images to detect brain hemorrhages. It processes preprocessed images and provides predictions based on learned features.
- **Prediction and Result Display Module**
  Once the deep learning model provides a prediction, this module displays the results to the user. It

It shows whether the scan indicates the presence of a brain hemorrhage, along with visualizations such as heatmaps or confidence scores. This module ensures that healthcare professionals can easily interpret the model's output.

- **Database Module**

  This module manages the storage of patient data, scan images, and analysis results. It ensures that data is stored securely and is easily retrievable for future reference. The database can be built using MySQL or MongoDB, ensuring compliance with data privacy standards like HIPAA.

# System Architecture




The system architecture for brain hemorrhage detection involves two key phases: the Training Phase and the Testing Phase. Each phase is designed to ensure optimal model performance, from the initial model development to its real-world application.

**1. Training Phase Architecture**

The Training Phase is responsible for developing the deep learning model, which involves feeding the system with labeled data (CT/MRI scans with ground-truth annotations) to teach it how to identify brain hemorrhages.

- Data Collection Layer: This layer gathers a large set of labeled medical images (CT/MRI scans) along with their corresponding ground-truth labels, which indicate whether a hemorrhage is present.
- Data Preprocessing Layer: Before feeding the images into the model, the Preprocessing Layer performs various image enhancement tasks using tools like OpenCV. This includes resizing images, removing noise, enhancing contrast, and normalizing the pixel values, ensuring the images are ready for model input.
- Training Data Feeding Layer: Preprocessed images are divided into the training dataset and validation datasets. The training dataset is passed on to train the model while the validation dataset monitors how the model performs while in training mode.

- Model Training Layer: The heart of the Training Phase is the Deep Learning Model Layer, which can be TensorFlow/Keras or PyTorch. The CNN architecture is designed to learn patterns and features from images. Techniques such as backpropagation and gradient descent are employed to minimize the error made in predictions.
- Evaluation Layer: During training, the model is periodically evaluated on the validation set to check its accuracy and prevent overfitting. Metrics such as accuracy, precision, recall, and F1-score are used to gauge performance.
- Model Optimization Layer: After the initial training, the model is fine-tuned using hyperparameter optimization, dropout regularization, or techniques like data augmentation to improve performance and robustness.
- Model Saving Layer: Once the model reaches a satisfactory accuracy, it is saved for future use. The trained model is stored in a format like TensorFlow SavedModel or ONNX for later inference during the Testing Phase.

**2. Testing Phase Architecture**

The Testing Phase involves evaluating the trained model on new, unseen medical images to predict brain hemorrhages and provide real-time results.

- Image Upload and Preprocessing Layer: In the testing phase, health care professionals upload new CT/MRI scan images via the web interface. The Preprocessing Layer performs exactly the same image enhancement and normalization steps as in the training phase to ensure consistency.
- Model Inference Layer: The preprocessed images are passed through the saved model, which generates predictions about the presence of brain hemorrhages. This involves running the images through the CNN layers, where the model applies learned filters to identify relevant features.
- Prediction and Result Interpretation Layer: After inference, the model's output is analyzed to generate a final result. The output includes prediction scores, confidence levels, and may include visual
- Representations like heatmaps to highlight areas where hemorrhages are likely. The result is then presented to the user (healthcare professional) via the web interface.
- Database Layer: After generating the prediction, the results, along with patient data and scan images, are stored securely in a database (e.g., MySQL or MongoDB) for future reference. This layer ensures compliance with data privacy regulations like HIPAA.
- Feedback Loop: The system may include a feedback mechanism where healthcare professionals can confirm the results, providing an opportunity for continuous learning. This feedback can be incorporated into future training phases to improve model accuracy.

**Flow Diagram of System Architecture**

1. **Training Phase**:
   - Data Collection → Preprocessing → Training Data Feeding → Model Training → Evaluation → Model Saving.
2. **Testing Phase**:
   - Image Upload → Preprocessing → Model Inference → Prediction and Result Interpretation → Database Storage → Feedback Loop.

The deep learning-based brain hemorrhage detection system is designed to process, analyze, and interpret medical images, such as CT or MRI scans, with high efficiency. The architecture of the system consists of several key layers, focusing on specific tasks that contribute to the overall functionality of the system. This layer first accepts the medical images. The data can come in various forms, for instance, in DICOM, PNG, or JPEG format, either from other systems of different hospitals or as a direct upload by doctors and specialists. The second stage is Data Preprocessing, which processes the data input to the system to be homogenous and of the best quality. Preprocessing steps include resizing the images, normalizing the pixel values, noise reduction, and applying augmentation techniques for improving the robustness of the model.

The heart of the system is at the Feature Extraction Layer-CNN, which automatically extracts relevant features from the images using a Convolutional Neural Network. This layer consists of several convolutional layers, activation functions like ReLU, and pooling layers to reduce spatial dimensions, focusing on the important patterns within the image. After feature extraction, the Classification Layer uses the output from the CNN to classify the image, either as a binary outcome (hemorrhage detected or not) or a multi-class output (detecting the type of hemorrhage).

At that time of classification, it goes for the Post-processing and Visualisation Layer and generates heatmap or annotations that may or may not display on original images. After that the system provides an interface between the healthcare practitioners and a healthcare system where people can provide images, ask for different results, view results in that system, upload images of patients, along with resultant reports. Lastly, the Database Layer stores all images, predictions, and generated reports, ensuring secure data management and easy retrieval for future use. This architecture is designed to streamline the process of brain hemorrhage detection, providing valuable support for medical professionals in diagnosing and treating patients.

# CHAPTER 6

# SYSTEM TESTING

System Testing is an essential phase in ensuring the functionality, reliability, and performance of a deep learning-based brain hemorrhage detection system. It starts with unit testing, where individual components, such as image preprocessing and feature extraction layers, are tested in isolation to verify their correctness. Following that, integration testing is performed to ensure that all system components work together smoothly, such as checking the seamless flow of data from preprocessing to classification. Functional testing is conducted to confirm that the system performs its intended tasks accurately, such as detecting and classifying hemorrhages in CT or MRI images. Performance testing evaluates the system's efficiency, including processing time and its ability to scale under load. Accuracy and model validation are crucial, involving testing the deep learning model on a separate dataset to measure its accuracy, precision, recall, and other relevant metrics. User acceptance testing (UAT) is then carried out to ensure the system meets the end users' expectations, particularly healthcare professionals, ensuring ease of use and integration into clinical workflows. Security testing ensures that sensitive medical data is protected and compliant with data privacy regulations. Additionally, regression testing is performed to ensure that new updates do not disrupt existing functionality. Finally, load and stress testing assess the system's ability to handle extreme conditions, while usability testing ensures the user interface is intuitive and easy to navigate for healthcare providers. Through these comprehensive testing stages, the system can be validated for both technical performance and clinical reliability.

## 6.1 Testing

System testing is an essential phase to validate the functionality, performance, and accuracy of the brain hemorrhage detection system. It ensures that all components of the system work together as intended and meet the requirements specified during the design phase. The testing process involves verifying both the individual modules and the overall system functionality.

**Testing** is a critical phase in the development of a deep learning-based brain hemorrhage detection system, ensuring the system works as intended and meets its performance, accuracy, and usability requirements. The testing process involves multiple stages to verify that every component functions correctly and integrates smoothly. The key testing types for such a system are:

1. Unit Testing

Unit testing focuses on verifying the individual components of the system, ensuring that each part functions as expected. This involves testing individual components or modules of the system in isolation, ensuring that each part, such as image preprocessing, the convolutional neural network (CNN) layer, and the classification output, works as expected. For example, unit tests would verify that image preprocessing functions like resizing and normalization are performing correctly. The main modules tested include:

- Image Preprocessing Module: Ensures that images are properly resized, normalized, and noise-reduced without losing important features.
- Deep Learning Model: Tests the CNN model's ability to correctly classify brain hemorrhages, ensuring it processes data without errors.
- Database Module: Verifies that patient data and predictions are correctly stored and retrieved from the database.
- API Layer: Confirms that the communication between the web interface and backend services works properly, ensuring data is transmitted correctly.

2. Integration Testing

Integration testing ensures that the modules work together correctly. As the individual components should been through unit tested, integration testing ensures that all parts of whole system work together seamlessly. This includes checking if the data flows correctly from one layer to another—such as moving from preprocessing to the CNN for feature extraction, and then to the classification layer for predictions. This step focuses on checking the interactions between various system components:

- Image Upload and Preprocessing Integration: Tests that images uploaded by users through the interface are properly preprocessed before being passed to the model.
- Model Inference and Result Display: Verifies that the results from the trained model are correctly interpreted and displayed to the user.
- Database Integration: Ensures that prediction results and patient data are properly stored and can be retrieved when needed.

3. Functional Testing

This testing verifies that the system performs its intended functions. For a brain hemorrhage detection system, it involves testing whether the system can accurately identify hemorrhages in CT/MRI images. Functional tests will include feeding the system with labeled images (both with and without hemorrhages) and comparing the predicted results with the actual labels. Functional testing evaluates whether the system meets its functional requirements,such as:

- Prediction Accuracy: Verifying that the system correctly detects brain hemorrhages from medical images. This involves comparing model predictions with ground truth labels from a labeled dataset.
- User Interface: Ensures that the web interface allows healthcare professionals to upload images, view results, and interact with the system as intended.

4. Performance Testing

Performance testing is essential for ensuring that the system can handle the expected load and perform efficiently. This includes testing the processing speed of the system (i.e., the time it takes to process a single image) and its ability to handle a large number of images simultaneously without significant delays or errors. Performance testing ensures that the system performs well under normal and peak load conditions:

- Response Time: Measures how quickly the system processes an uploaded image and returns results, ensuring that it meets the expected performance benchmarks for real-time predictions.
- Scalability: Tests the system’s ability to handle multiple concurrent users and a large number of medical images without degradation in performance.
- Load Testing: Simulates heavy user activity (multiple simultaneous image uploads) to ensure the system can handle peak loads.

5. Accuracy Testing

In this step, the deep learning model is tested on a separate test dataset to evaluate its accuracy and overall performance. Key metrics like accuracy, precision, recall, and F1 score are calculated to determine how well the model detects hemorrhages. This step ensures that the model generalizes well and does not overfit the training data.Accuracy testing evaluates the deep learning model's performance on unseen test data:

- Confusion Matrix: The model's predictions are compared to the ground truth labels to compute metrics such as accuracy, precision, recall, and F1-score.
- Cross-Validation: The model is validated using cross-validation techniques to assess its robustness and ensure it generalizes well to new data.

6. Security Testing

This testing ensures the system complies with security standards and protects sensitive medical data. It includes verifying data encryption, ensuring proper access control, and testing the system's resistance to potential cyberattacks, safeguarding patient privacy and compliance with regulations like HIPAA or GDPR. Security testing ensures that the system is secure and that sensitive patient data is protected:

- Data Encryption: Verifies that sensitive data, both during transmission and while at rest, is encrypted to prevent unauthorized access.
- User Authentication and Authorization: Ensures that only authorized healthcare professionals can access patient data and scan results.
- Compliance with Regulations: Checks for compliance with healthcare standards like HIPAA (Health Insurance Portability and Accountability Act) to ensure data privacy and security.

7. Usability Testing

This focuses on evaluating the system's user interface (UI) and ensuring it is intuitive and easy to navigate. Healthcare professionals need to interact with the system efficiently, so the usability testing ensures that uploading images, viewing results, and generating reports are straightforward tasks.Usability testing assesses the system's ease of use and user satisfaction:

- User Interface Testing: Evaluates the web interface for simplicity, clarity, and ease of navigation for healthcare professionals.
- Feedback from Users: Collects feedback from healthcare professionals to identify any issues or improvements for better user experience.

8. Regression Testing

Whenever new features are added or updates are made to the system, regression testing ensures that these changes do not negatively affect existing functionality. This testing ensures that previously working components still perform as expected after updates. Regression testing ensures that new changes or additions to the system do not negatively impact the existing functionality:

- After each update or modification, the system is re-tested to verify that previous features, such as image uploads, predictions, and result displays, still function correctly.

9. Acceptance Testing

UAT ensures that the system meets the needs of healthcare professionals. This involves real-world testing with end users (e.g., doctors or radiologists), allowing them to interact with the system, upload images, and evaluate its usability, accuracy, and functionality. Feedback from UAT helps ensure that the system is intuitive, user-friendly, and reliable. Acceptance testing ensures that the system meets the requirements specified by stakeholders (healthcare professionals, medical institutions):

- User Acceptance Testing (UAT): Healthcare professionals perform the final testing to verify that the system meets their expectations and is ready for deployment.

# CHAPTER 7

# RESULTS AND DISCUSSION

## 7.1 Overview

System testing for the brain hemorrhage detection system is an essential phase to ensure that the system functions as intended, providing accurate and reliable predictions. The process begins with unit testing, where individual modules such as image preprocessing, the deep learning model, and database interactions are tested independently to ensure that each component performs its task correctly. Next, integration testing checks the interaction between modules to verify that data flows seamlessly between the image upload, preprocessing, model inference, and result display components.

Functional testing is conducted to confirm that the system meets all functional requirements, including correct brain hemorrhage detection and a user-friendly interface for healthcare professionals. Performance testing ensures that the system performs efficiently under different conditions, handling high volumes of medical images and concurrent user requests without lag. Accuracy testing is crucial to assess the model's ability to accurately detect brain hemorrhages, using metrics like precision, recall, and F1-score to evaluate its predictive power against a labeled dataset.

In addition, security testing focuses on ensuring the protection of sensitive patient data through encryption, secure authentication, and compliance with healthcare regulations such as HIPAA. Usability testing evaluates how intuitive and easy-to-navigate the user interface is, ensuring healthcare professionals can operate the system efficiently. Regression testing verifies that updates to the system do not break any existing features, while acceptance testing involves end-users (healthcare professionals) to confirm that the system meets their needs and expectations before it is deployed in a real-world setting.

Through these comprehensive testing methodologies, the system ensures high-quality performance, accuracy, and security, ultimately enabling healthcare providers to make informed decisions with confidence. This rigorous approach to system testing guarantees that the brain hemorrhage detection system is not only functional but also reliable, efficient, and ready for clinical use.

## 7.2 Snapshots

## Input:






# Training:




# Dataset:



# Output:




# Final Output:



# CONCLUSION

In conclusion, the brain hemorrhage detection system developed using deep learning and image processing techniques has the potential to significantly improve the accuracy and efficiency of diagnosing brain hemorrhages from CT and MRI scans. By leveraging advanced Convolutional Neural Networks (CNNs) and tools such as TensorFlow and OpenCV, the system is capable of providing reliable, real-time predictions that assist healthcare professionals in making timely and informed decisions. The rigorous system testing, including unit, integration, functional, performance, accuracy, and security testing, ensures that the system meets high standards of reliability, accuracy, and security, making it suitable for deployment in clinical environments.

The integration of preprocessing steps, secure data handling, and an intuitive user interface further enhances the system's practicality and usability. The modular architecture of the system ensures scalability and flexibility, allowing it to be integrated with existing healthcare infrastructure. With continuous improvements and feedback loops, the system has the potential to evolve, providing even more accurate predictions over time.

Ultimately, this system represents a significant step forward in utilizing artificial intelligence for medical image analysis, contributing to early detection and better management of brain hemorrhages. Its deployment could lead to improved patient outcomes, reduced human error, and more efficient healthcare practices, particularly in environments with limited access to specialized medical expertise.

# FUTURE WORKS

While the current brain hemorrhage detection system demonstrates promising results in accurately identifying hemorrhages from CT and MRI scans, there are several avenues for improvement and expansion in future work:

1. Model Enhancement and Transfer Learning
   The performance of the deep learning model can be further enhanced by incorporating more advanced architectures, such as ResNet or DenseNet, which may improve accuracy by better handling deeper networks. Additionally, transfer learning can be leveraged by fine-tuning pre-trained models on large medical image datasets to improve generalization, especially with limited labeled data.

2. Multimodal Imaging Integration
   Future developments could involve integrating multiple imaging modalities (such as CT, MRI, and PET scans) to improve detection accuracy and provide a more comprehensive diagnosis. Combining different types of medical images might reveal additional insights and help detect hemorrhages in complex cases.

3. Real-time Monitoring and Continuous Learning
   The system could be expanded to support real-time monitoring of patient conditions by analyzing continuous imaging data, such as during surgery or in an ICU setting. Additionally, implementing continuous learning where the model adapts to new data and feedback from healthcare professionals can improve its performance over time.

4. Integration with Electronic Health Records (EHR)
   A more integrated approach can be pursued by connecting the system with Electronic Health Records (EHR), enabling automatic retrieval of patient history and scan data. This would streamline the process for healthcare providers, allowing for more efficient decision-making and personalized care.

5. Multilingual Support for Global Accessibility
   To extend the system's reach and impact, multilingual support could be added to the user interface, allowing healthcare professionals from different linguistic backgrounds to use the system effectively. This would promote its adoption in a wider range of clinical settings, especially in underserved regions.

6. Edge Computing for On-site Analysis
   Future versions of the system could integrate edge computing capabilities, allowing the detection system to run directly on medical devices or local servers in remote areas, reducing the reliance on cloud-based processing. This would enable faster analysis and ensure the system is usable in areas with limited internet connectivity.

7. Collaborative System with Other Healthcare AI Tools

   Future work can also explore the possibility of integrating the brain hemorrhage detection system with other AI-based diagnostic tools for more comprehensive healthcare decision-making. By collaborating with AI systems that assist in other areas like tumor detection or stroke identification, a more holistic patient diagnostic system can be developed.

8. Improvement in Model Explainability and Interpretability

   One of the challenges in deploying deep learning models in medical settings is their lack of interpretability. Future versions could focus on improving the model's explainability, providing healthcare professionals with more transparent reasoning behind predictions. Techniques like Grad-CAM or SHAP values can be employed to visualize and understand the model's decision-making process, increasing trust and adoption among medical professionals.

9. Large-Scale Clinical Trials

   To validate the effectiveness and generalizability of the system, large-scale clinical trials can be conducted across various healthcare settings. This would help assess its real-world accuracy, performance, and usability across diverse patient populations and imaging devices.

# REFERENCES

[1] Kaggle and RSNA, "Intracranial hemorrhage detection dataset," 2019. [Online]. Available: https://www.kaggle.com/c/rsna-intracranialhemorrhage-detection/data

[2] T. Lewicki, https://github.com/tomek-l/brain, [Online].

[3] K. He, X. Zhang, S. Ren, and J. Sun, "Delving deep into rectifiers: Surpassing human-level performance on imagenet classification," CoRR, vol. abs/1502.01852, 2015. [Online]. Available: http://arxiv.org/abs/1502.01852

[4] G. J. S. Litjens, T. Kooi, B. E. Bejnordi, A. A. A. Setio, F. Ciompi, M. Ghafoorian, J. A. W. M. van der Laak, B. van Ginneken, and C. I. Sanchez, "A survey on deep learning in medical image analysis," ´ Medical Image Analysis, vol. 42, pp. 60–88, 2017. [Online]. Available: https://doi.org/10.1016/j.media.2017.07.005

[5] P. Rajpurkar, A. Y. Hannun, M. Haghpanahi, C. Bourn, and A. Y. Ng, "Cardiologist-level arrhythmia detection with convolutional neural networks," CoRR, vol. abs/1707.01836, 2017. [Online]. Available: http://arxiv.org/abs/1707.01836

[6] S. Chilamkurthy, R. Ghosh, S. Tanamala, M. Biviji, N. Campeau, V. Venugopal, V. Mahajan, P. Rao, and P. Warier, "Deep learning algorithms for detection of critical findings in head ct scans: a retrospective study," The Lancet, vol. 392, 10 2018.

[7] X. W. Gao, R. Hui, and Z. Tian, "Classification of CT brain images based on deep learning networks," Computer Methods and Programs in Biomedicine, vol. 138, pp. 49–56, 2017. [Online]. Available: https://doi.org/10.1016/j.cmpb.2016.10.007

[8] L. V. Fulton, D. Dolezel, J. Harrop, Y. Yan, and C. P. Fulton, "Classification of alzheimer's disease with and without imagery using gradient boosted machines and resnet-50," Brain Sciences, vol. 9, no. 9, 2019. [Online]. Available: https://www.mdpi.com/2076-3425/9/9/212

[9] M. Talo, O. Yildirim, U. B. Baloglu, G. Aydin, and ¨ U. R. Acharya, "Convolutional neural networks for multiclass brain disease detection using MRI images," Comp. Med. Imag. and Graph., vol. 78, 2019. [Online]. Available: https://doi.org/10.1016/j.compmedimag.2019.101673

[10] J. E. Barnes, "Characteristics and control of contrast in ct." RadioGraphics, vol. 12, pp. 825–37, 1992.

[11] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," CoRR, vol. abs/1512.03385, 2015. [Online]. Available: http://arxiv.org/abs/1512.03385

[12] D. P. Kingma and J. Ba, "Adam: A method for stochastic optimization," 2014, cite arxiv:1412.6980Comment: Published as a conference paper at the 3rd International Conference for Learning Representations

DrillBit

The Report is Generated by DrillBit Plagiarism Detection Software

### *Submission Information*

| | |
|---|---|
| Author Name | mcri |
| Title | nmrei |
| Paper/Submission ID | 2888236 |
| Submitted by | hemavathi.j56@gmail.com |
| Submission Date | 2024-12-27 23:29:16 |
| Total Pages, Total Words | 48, 12298 |
| Document type | Project Work |

### *Result Information*

Similarity **13 %**

1 10 20 30 40 50 60 70 80 90

Sources Type




Report Content




### *Exclude Information*

| | |
|---|---|
| Quotes | Not Excluded |
| References/Bibliography | Not Excluded |
| Source: Excluded < 14 Words | Not Excluded |
| Excluded Source | **0 %** |
| Excluded Phrases | Not Excluded |

### *Database Selection*

| | |
|---|---|
| Language | English |
| Student Papers | Yes |
| Journals & publishers | Yes |
| Internet or Web | Yes |
| Institution Repository | Yes |

A Unique QR Code use to View/Download/Share Pdf File

DrillBit

**DrillBit Similarity Report**

| 13 | 94 | B | A-Satisfactory (0-10%)<br>B-Upgrade (11-40%)<br>C-Poor (41-60%)<br>D-Unacceptable (61-100%) |
|---|---|---|---|
| SIMILARITY % | MATCHED SOURCES | GRADE | |

| LOCATION | MATCHED DOMAIN | % | SOURCE TYPE |
|---|---|---|---|
| 1 | www.slideshare.net | 1 | Internet Data |
| 2 | www.ncbi.nlm.nih.gov | <1 | Internet Data |
| 3 | www.dx.doi.org | <1 | Publication |
| 4 | fastercapital.com | <1 | Internet Data |
| 5 | www.ncbi.nlm.nih.gov | <1 | Internet Data |
| 6 | encord.com | <1 | Internet Data |
| 7 | www.irjmets.com | <1 | Publication |
| 8 | statusneo.com | <1 | Internet Data |
| 9 | mdpi.com | <1 | Internet Data |
| 10 | www.numerade.com | <1 | Internet Data |
| 11 | REPOSITORY - Submitted to Exam section VTU on 2024-07-31 17-11 900437 | <1 | Student Paper |
| 12 | www.ncbi.nlm.nih.gov | <1 | Internet Data |
| 13 | Deep Learning in Medical Imaging General Overview by Lee-2017 | <1 | Publication |
| 14 | sunscrapers.com | <1 | Internet Data |

| | | | |
|---|---|---|---|
| 15 | www.mdpi.com | <1 | Internet Data |
| 16 | tc.copernicus.org | <1 | Internet Data |
| 17 | moam.info | <1 | Internet Data |
| 18 | www.mdpi.com | <1 | Internet Data |
| 19 | Thesis submitted to shodhganga - shodhganga.inflibnet.ac.in | <1 | Publication |
| 20 | www.slideshare.net | <1 | Internet Data |
| 21 | Constructing Geospatial Concept Graphs from Tagged Images for Geo-Aware Fine-Gra by Nitta-2020 | <1 | Publication |
| 22 | www.mdpi.com | <1 | Internet Data |
| 23 | arxiv.org | <1 | Publication |
| 24 | www.dx.doi.org | <1 | Publication |
| 25 | www.scribd.com | <1 | Internet Data |
| 26 | github.com | <1 | Internet Data |
| 27 | MulNet A Flexible CNN Processor with Higher Resource Utilization Eff, by Hailesellasie, Mulu- 2019 | <1 | Publication |
| 28 | Submitted to Visvesvaraya Technological University, Belagavi | <1 | Student Paper |
| 29 | www.lambdatest.com | <1 | Internet Data |
| 30 | news.abplive.com | <1 | Internet Data |
| 31 | www.numerade.com | <1 | Internet Data |
| 32 | mdpi.com | <1 | Internet Data |
| 33 | www.hindawi.com | <1 | Internet Data |

| | | | |
|---|---|---|---|
| 34 | The Neural Network of One-Dimensional Convolution-An Example of the D, by Sun, Yunlei- 2019 | <1 | Publication |
| 35 | www.dx.doi.org | <1 | Publication |
| 36 | www.trimbox.io | <1 | Internet Data |
| 37 | www.minfytech.com | <1 | Internet Data |
| 38 | repository.up.ac.za | <1 | Publication |
| 39 | www.mdpi.com | <1 | Internet Data |
| 40 | arxiv.org | <1 | Publication |
| 41 | dminc.com | <1 | Internet Data |
| 42 | jurnal.stmi.ac.id | <1 | Publication |
| 43 | kili-technology.com | <1 | Internet Data |
| 44 | www.enago.com | <1 | Internet Data |
| 45 | www.nature.com | <1 | Publication |
| 46 | www.sayonetech.com | <1 | Internet Data |
| 47 | 1library.co | <1 | Internet Data |
| 48 | arxiv.org | <1 | Publication |
| 49 | 1library.co | <1 | Internet Data |
| 50 | actascientific.com | <1 | Publication |
| 51 | An Active Operator Guidance System for Ship ManeuversPrototype System by Ong-2008 | <1 | Publication |
| 52 | docplayer.net | <1 | Internet Data |

| | | | |
|---|---|---|---|
| 53 | ecoevocommunity.nature.com | <1 | Internet Data |
| 54 | ejurnal.undana.ac.id | <1 | Internet Data |
| 55 | escholarship.org | <1 | Internet Data |
| 56 | On the application of genetic algorithms for test case prioritization, by C. Catal- 2012 | <1 | Publication |
| 57 | Patients as Researchers by vo-2018 | <1 | Publication |
| 58 | Querying the public databases for sequences using complex keywords contained in by Olivie-2006 | <1 | Publication |
| 59 | www.arxiv.org | <1 | Publication |
| 60 | www.ijrte.org | <1 | Publication |
| 61 | ABCs of Hospitalized Patients by Afsar-manesh-2019 | <1 | Publication |
| 62 | A comparison of two diffusion process models in accounting for payoff and stimul by Leite-2012 | <1 | Publication |
| 63 | Consumer Credit Risk Modelling Transportation, Logistics and the Environment by A-2010 | <1 | Publication |
| 64 | core.ac.uk | <1 | Publication |
| 65 | dochero.tips | <1 | Internet Data |
| 66 | dspace.knust.edu.gh | <1 | Publication |
| 67 | eetimes60.rssing.com | <1 | Internet Data |
| 68 | fastercapital.com | <1 | Internet Data |
| 69 | github.com | <1 | Internet Data |
| 70 | github.com | <1 | Internet Data |

| | | | |
|---|---|---|---|
| 71 | huggingface.co | <1 | Internet Data |
| 72 | inba.info | <1 | Internet Data |
| 73 | jnis.bmj.com | <1 | Internet Data |
| 74 | mdpi.com | <1 | Internet Data |
| 75 | medium.com | <1 | Internet Data |
| 76 | nature.com | <1 | Internet Data |
| 77 | Performance of an e-nose in hops classification by A-2004 | <1 | Publication |
| 78 | Pose recognition using convolutional neural networks on omni-directio, by Georgakopoulos, S.V- 2017 | <1 | Publication |
| 79 | Practical Strategies for Enhancing Adherence to Treatment Regimen in Inflammator by Greenley-2013 | <1 | Publication |
| 80 | rathinamcollege.ac.in | <1 | Publication |
| 81 | repositorio-aberto.up.pt | <1 | Publication |
| 82 | springeropen.com | <1 | Publication |
| 83 | sti.bmj.com | <1 | Publication |
| 84 | Submitted to Visvesvaraya Technological University, Belagavi | <1 | Student Paper |
| 85 | syntegra.net | <1 | Internet Data |
| 86 | Thesis Submitted to Shodhganga Repository | <1 | Publication |
| 87 | vdocuments.mx | <1 | Internet Data |
| 88 | www.ijetch.org | <1 | Internet Data |
| 89 | www.ijettjournal.org | <1 | Publication |

| | | | |
|---|---|---|---|
| 90 | www.ijraset.com | <1 | Internet Data |
| 91 | www.mdpi.com | <1 | Internet Data |
| 92 | www.mdpi.com | <1 | Internet Data |
| 93 | www.readbag.com | <1 | Internet Data |
| 94 | www.sciencedirect.com | <1 | Internet Data |