

MONGO DB

Structure of 'restaurants' collection:

EXERCISE 18

```
{
  "address": {
    "building": "1007",
    "coord": [ -73.856077, 40.848447 ],
    "street": "Morris Park Ave",
    "zipcode": "10462"
  },
  "borough": "Bronx",
  "cuisine": "Bakery",
  "grades": [
    { "date": { "$date": 1393804800000 }, "grade": "A", "score": 2 },
    { "date": { "$date": 1378857600000 }, "grade": "A", "score": 6 },
    { "date": { "$date": 1358985600000 }, "grade": "A", "score": 10 },
    { "date": { "$date": 1322006400000 }, "grade": "A", "score": 9 },
    { "date": { "$date": 1299715200000 }, "grade": "B", "score": 14 }
  ],
  "name": "Morris Park Bake Shop",
  "restaurant_id": "30075445"
}
```

1. Write a MongoDB query to find the restaurant Id, name, borough and cuisine for those restaurants which prepared dish except 'American' and 'Chinees' or

restaurant's name begins with letter 'Wil'.
`db.restaurants.find({$or: [{cuisine: {$nin: ['American', 'Chinese']}}, {name: 'Wil'}], {restaurant_id: 1, name: 1, borough: 1, cuisine: 1})`

2. Write a MongoDB query to find the restaurant Id, name, and grades for those

restaurants which achieved a grade of "A" and scored 11 on an ISODate "2014-08-

11T00:00:00Z" among many of survey dates..
`db.restaurants.find({grades: {$elemMatch: {grade: "A", score: 11, date: ISODate("2014-08-11T00:00:00Z")}}}, {restaurant_id: 1, name: 1, grades: 1})`

3. Write a MongoDB query to find the restaurant Id, name and grades for those

restaurants where the 2nd element of grades array contains a grade of "A" and

score 9 on an ISODate "2014-08-11T00:00:00Z".
`db.restaurants.find({grades: {1: {grade: "A", score: 9, date: ISODate("2014-08-11T00:00:00Z")}}}, {restaurant_id: 1, name: 1, grades: 1})`

4. Write a MongoDB query to find the restaurant Id, name, address and geographical

location for those restaurants where 2nd element of coord array contains a value
`db.restaurants.find({address.coord: {1: {$gt: 42, $lte: 52}}}, {restaurant_id: 1, name: 1, address: 1})`

which is more than 42 and upto 52..

5. Write a MongoDB query to arrange the name of the restaurants in ascending order along with all the columns.

`db.restaurants.find().sort({name: 1})`

6. Write a MongoDB query to arrange the name of the restaurants in descending order along with all the columns.

`db.restaurants.find().sort({name: -1})`

7. Write a MongoDB query to arranged the name of the cuisine in ascending order and for that same cuisine borough should be in descending order.

`db.restaurants.find().sort({cuisine: 1, borough: -1})`

8. Write a MongoDB query to know whether all the addresses contains the street or not.

`db.restaurants.find({'address.street': {'exists': true}})`

9. Write a MongoDB query which will select all documents in the restaurants collection where the coord field value is Double.

`db.restaurants.find({'address.coord': {'$type': 'double'}})`

10. Write a MongoDB query which will select the restaurant Id, name and grades for those restaurants which returns 0 as a remainder after dividing the score by 7.

`db.restaurants.find({'grades.score': {'$mod': [7, 0]}}, {'restaurant_id': 1, 'name': 1, 'grades': 1})`

11. Write a MongoDB query to find the restaurant name, borough, longitude and attitude and cuisine for those restaurants which contains 'mon' as three letters somewhere in its name.

`db.restaurants.find({'name': /mon/i}, {'name': 1, 'borough': 1, 'address.coord': 1, 'cuisine': 1})`

12. Write a MongoDB query to find the restaurant name, borough, longitude and latitude and cuisine for those restaurants which contain 'Mad' as first three letters of its name.

`db.restaurants.find({'name': /^Mad/i}, {'name': 1, 'borough': 1, 'address.coord': 1, 'cuisine': 1})`

13. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5.

`db.restaurants.find({'grades.score': {'$lt': 5}})`

14. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan.

`db.restaurants.find({'borough': 'Manhattan', 'grades.score': {'$lt': 5}})`

15. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn.

`db.restaurants.find({'borough': {'$in': ['Manhattan', 'Brooklyn']}, 'grades.score': {'$lt': 5}})`

16. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn,

and their cuisine is not American. `db.restaurants.find({'borough': {'$in': ['Manhattan', 'Brooklyn']}, 'cuisine': {'$ne': 'American'}, 'grades.score': {'$lt': 5}})`

17. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn,

and their cuisine is not American or Chinese. `db.restaurants.find({'borough': {'$in': ['Manhattan', 'Brooklyn']}, 'cuisine': {'$nin': ['American', 'Chinese']}, 'grades.score': {'$lt': 5}})`

18. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6.

`db.restaurants.find({'grades.score': {'$all': [2, 6]}})`

19. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan.

`db.restaurants.find({'borough': 'Manhattan', 'grades.score': {'$all': [2, 6]}})`

20. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn.

`db.restaurants.find({'borough': {'$in': ['Manhattan', 'Brooklyn']}, 'grades.score': {'$all': [2, 6]}})`

21. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn, and their cuisine is not American.

```
db.restaurants.find({borough:{$in:["Manhattan","Brooklyn"]}, cuisine:{$ne:"American"}, "grades.score":{$all:[2,6]}})
```

22. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn, and their cuisine is not American or Chinese.

```
db.restaurants.find({borough:{$in:["Manhattan","Brooklyn"]}, cuisine:{$nin:["American","Chinese"]}, "grades.score":{$all:[2,6]}})
```

23. Write a MongoDB query to find the restaurants that have a grade with a score of 2 or a grade with a score of 6.

```
db.restaurants.find({"grades.score":{$in:[2,6]}})
```

Sample document of 'movies' collection

```
{
  _id: ObjectId("573a1390f29313caabcd42e8"),
  plot: 'A group of bandits stage a brazen train hold-up, only to find a determined posse hot on their heels.',
  genres: [ 'Short', 'Western' ],
  runtime: 11,
  cast: [
    'A.C. Abadie',
    'Gilbert M. 'Broncho Billy' Anderson',
    'George Barnes',
    'Justus D. Barnes'
  ],
  poster: 'https://m.media-amazon.com/images/M/MV5BMTU3NjE5NzYtYTYyNS00MDVmLWlWYjgtMmYwYWlxdDYyNzU2XkEyXkFqcGdeQXVyNzQzNzQxNzI@._V1_SY1000_SX677_AL_.jpg',
  title: 'The Great Train Robbery',
  fullplot: "Among the earliest existing films in American cinema - notable as the first film that presented a narrative story to tell - it depicts a group of cowboy outlaws who hold up a train and rob the passengers. They are then pursued by a Sheriff's posse. Several scenes have color included - all hand tinted.",
```



```
languages: [ 'English' ],
released: ISODate("1903-12-01T00:00:00.000Z"),
directors: [ 'Edwin S. Porter' ],
rated: 'TV-G',
awards: { wins: 1, nominations: 0, text: '1 win.' },
lastupdated: '2015-08-13 00:27:59.177000000',
year: 1903,
imdb: { rating: 7.4, votes: 9847, id: 439 },
countries: [ 'USA' ],
type: 'movie',
tomatoes: {
viewer: { rating: 3.7, numReviews: 2559, meter: 75 },
fresh: 6,
critic: { rating: 7.6, numReviews: 6, meter: 100 },
rotten: 0,
lastUpdated: ISODate("2015-08-08T19:16:10.000Z")
}
```

1. Find all movies with full information from the 'movies' collection that released in the year 1893.

```
db.movies.find({year: 1893})
```

2. Find all movies with full information from the 'movies' collection that have a runtime greater than 120 minutes.

```
db.movies.find({runtime: {$gt: 120}})
```

3. Find all movies with full information from the 'movies' collection that have "Short" genre.

```
db.movies.find({genres: "Short"})
```

4. Retrieve all movies from the 'movies' collection that were directed by "William K.L. Dickson" and include complete information for each movie.

```
db.movies.find({directors: "William K.L. Dickson"})
```

5. Retrieve all movies from the 'movies' collection that were released in the USA and include complete information for each movie.

```
db.movies.find({countries: "USA"})
```

6. Retrieve all movies from the 'movies' collection that have complete information and are rated as "UNRATED".

```
db.movies.find({rated: "UNRATED"})
```

7. Retrieve all movies from the 'movies' collection that have complete information and have received more than 1000 votes on IMDb.

```
db.movies.find({"imdb.votes": {$gt: 1000}})
```

8. Retrieve all movies from the 'movies' collection that have complete information and have an IMDb rating higher than 7.

```
db.movies.find({"imdb.rating": {$gt: 7}})
```

9. Retrieve all movies from the 'movies' collection that have complete information and have a viewer rating higher than 4 on Tomatoes.

```
db.movies.find({"tomatoes.viewer.rating": {$gt: 4}})
```

10. Retrieve all movies from the 'movies' collection that have received an award.

```
db.movies.find({"awards.wins": {$gt: 0}})
```

11. Find all movies with title, languages, released, directors, writers, awards, year, genres, runtime, cast, countries from the 'movies' collection in MongoDB that have at least one nomination.

```
db.movies.find({"awards.nominations": {$gt: 0},  
{title: 1, languages: 1, released: 1, directors: 1, writers: 1, awards: 1, year: 1,  
genres: 1, runtime: 1, cast: 1, countries: 1})
```

12. Find all movies with title, languages, released, directors, writers, awards, year, genres, runtime, cast, countries from the 'movies' collection in MongoDB with cast

including "Charles Kayser". `db.movies.find({cast: "Charles Kayser"},
{title:1, languages:1, released:1, directors:1, writers:1, awards:1,
year:1, genres:1, runtime:1, cast:1, countries:1})`

13. Retrieve all movies with title, languages, released, directors, writers, countries from the 'movies' collection in MongoDB that released on May 9, 1893.

`db.movies.find({released: ISODate("1893-05-09T00:00:00Z")},
{title:1, languages:1, released:1, directors:1, writers:1, countries:1})`

14. Retrieve all movies with title, languages, released, directors, writers, countries from the 'movies' collection in MongoDB that have a word "scene" in the title.

`db.movies.find({title: /scene/}, {title:1, languages:1, released:1,
directors:1, writers:1, countries:1})`

C. Park
14/11/23

